```
classdef MdlResults
    %MDLRESULTS Shared functions for ML/DL models
       Input a trained model and test data for access to shared functions
       Functions:
    응
           classify
    응
           metrics
    응
    응
       Authors:
           Michael Caiola (Michael.Caiola@fda.hhs.gov)
    응
    응
           Meijun Ye (Meijun.Ye@fda.hhs.gov)
    응
    응
       Disclaimer: This software and documentation (the "Software") were
       developed at the Food and Drug Administration (FDA) by employees of
    응
       the Federal Government in the course of their official duties.
    응
       Pursuant to Title 17, Section 105 of the United States Code,
    응
       this work is not subject to copyright protection and is in the
       public domain. Permission is hereby granted, free of charge, to any
       person obtaining a copy of the Software, to deal in the Software
       without restriction, including without limitation the rights to
    응
       use, copy, modify, merge, publish, distribute, sublicense, or sell
    응
       copies of the Software or derivatives, and to permit persons to
    응
       whom the Software is furnished to do so. FDA assumes no
       responsibility whatsoever for use by other parties of the Software,
    응
       its source code, documentation or compiled executables, and makes
    응
    응
       no guarantees, expressed or implied, about its quality,
       reliability, or any other characteristic. Further, use of this code
    응
    응
       in no way implies endorsement by the FDA or confers any advantage
    응
       in regulatory decisions. Although this software can be
       redistributed and/or modified freely, we ask that any derivative
    응
       works bear some notice that they are derived from it, and any
       modified versions bear some notice that they have been modified.
       The Software is not intended to make clinical diagnoses or to be
       used in any way to diagnose or treat subjects for whom the EEG is
       taken.
   properties
       Mdl
       net
        testData
       testLabels
       YPred
       scores
       predictFcn
   end
   methods
        function obj = MdlResults(Mdl,testData,testLabels)
            %UNTITLED Construct an instance of this class
               Detailed explanation goes here
            if endsWith(string(class(Mdl)), "Network")
                obj.net = Mdl;
```

```
elseif isstruct(Mdl)
                names = string(fieldnames(Mdl));
                obj.Mdl = Mdl.(names(startsWith(names, "Classifi", "IgnoreCase", true)));
                obj.predictFcn = Mdl.predictFcn;
            else
                obj.Mdl = Mdl;
            end
            obj.testData = testData;
            obj.testLabels = testLabels;
            obj = makePrediction(obj);
        end
        function accuracy = classify(obj)
            figure;
            accuracy = round(mean(obj.YPred == obj.testLabels(1:length(obj.YPred)))*100);
            confusionchart(obj.testLabels(1:length(obj.YPred)), obj.YPred, "RowSummary", ✓
"row-normalized");
            title("Accuracy: " + accuracy' + "%")
        end
        function obj = makePrediction(obj)
            if ~isempty(obj.net)
                a = gpuDevice();
                %obj.testData.MiniBatchSize = 1;
                if contains(a.Name, "NVIDIA")
                         [obj.YPred,obj.scores] = classify(obj.net,obj.testData," <
ExecutionEnvironment", 'gpu');
                    catch
                        gpuDevice(1);
                        [obj.YPred,obj.scores] = classify(obj.net,obj.testData," 🗸
ExecutionEnvironment", 'gpu', MiniBatchSize=16);
                    end
                    if length(obj.YPred) ~= length(obj.scores)
                         [obj.YPred,obj.scores] = classify(obj.net,obj.testData," <
ExecutionEnvironment", 'gpu', MiniBatchSize=1);
                    end
                else
                    [obj.YPred,obj.scores] = classify(obj.net,obj.testData,"✓
ExecutionEnvironment", 'cpu', MiniBatchSize=1);
                    if length(obj.YPred) ~= length(obj.scores)
                         [obj.YPred,obj.scores] = classify(obj.net,obj.testData," <
ExecutionEnvironment", 'cpu', MiniBatchSize=1);
                    end
                end
            elseif ~isempty(obj.predictFcn)
                [obj.YPred, obj.scores] = obj.predictFcn(obj.testData);
                if isnumeric(obj.YPred(1)) %old format
                    in 0 = obj.YPred==0;
                    in 1 = obj.YPred==1;
                    in 2 = obj.YPred==2;
```

obj.YPred = string();

```
obj.YPred(in_0) = "HEA";
                    obj.YPred(in 1) = "TBI";
                    obj.YPred(in 2) = "STR";
                    in 0 = obj.testLabels==0;
                    in 1 = obj.testLabels==1;
                    in 2 = obj.testLabels==2;
                    obj.testLabels = string();
                    obj.testLabels(in 0) = "HEA";
                    obj.testLabels(in 1) = "TBI";
                    obj.testLabels(in 2) = "STR";
                    obj.scores = obj.scores(:,[1 3 2]);
                end
            else
                [obj.YPred,obj.scores] = predict(obj.Mdl,obj.testData);
            end
        end
        function rocObj = metrics(obj)
            if isempty(obj.scores)
                error("Run 'classify' before metrics.")
            end
            if isempty(obj.predictFcn)
                figure;
                histogram (max (obj.scores, [], 2), .34:.01:.99)
                title("Score Histogram")
                xlabel Scores
                acc=[];
                minacc=[];
                sens=[];
                prec=[];
                F1=[];
                numData = [];
                t=.33:.01:1;
                for i = t
                    score in = max(obj.scores,[],2)>i;
                    C=confusionmat(obj.testLabels(score_in), obj.YPred(score_in));
                    acc = [acc 100*((C(1,1)+C(2,2)+C(3,3))/(sum(C,'all')))];
                    minacc = [minacc min(100*[C(1,1) C(2,2) C(3,3)]./(sum(C,2)'),[],"\checkmark]
includenan")];
                    sens = [sens 100*(mean(diag(C)./sum(C,2)))];
                    prec = [prec 100*(mean(diag(C)./sum(C,1)'))];
                    F1 = [F1 (2*sens(end)*prec(end))/(sens(end)*prec(end))];
                    numData = [numData 100*sum(score in)/length(obj.scores)];
                end
                E = (2*F1 + acc + minacc + 10*log(numData))/5;
                [\sim,a] = \max(E);
                conf = t(a);
                c = colororder();
                figure;
                plot(t,acc,'LineWidth',2,'Color',c(1,:))
```

```
hold on
                plot(t,minacc,':','LineWidth',2,'Color',c(1,:))
                %plot(t,sens,'LineWidth',2,'Color',c(2,:))
                %plot(t,prec,'LineWidth',2,'Color',c(3,:))
                plot(t,F1,'LineWidth',2,'Color',c(2,:))
                plot(t, numData, 'LineWidth', 2, 'Color', c(3,:))
                plot([conf conf], [0 100], 'k--')
                legend(["Accuracy", "Min Acc", "F1", "Data Amount"], 'Location', 'southwest')
                title("Model Performance")
                xlabel Threshold
                score in = max(obj.scores,[],2)>conf;
                disp("Data Remaining: " + num2str(sum(score in)/length(obj.scores)))
                accuracy = round((sum(obj.YPred(score in) == obj.testLabels(score in)). ✓
/numel(obj.testLabels(score in)))*100);
                figure;
                confusionchart(obj.testLabels(score in), obj.YPred(score in), ✓
"RowSummary", "row-normalized");
                title("Optimized Accuracy: " + accuracy' + "%")
            end
            figure;
            rocObj = rocmetrics(obj.testLabels(1:length(obj.scores)),obj.scores,["HEA"," <
STR", "TBI"], AdditionalMetrics="accu");
            plot(rocObj, "AverageROCType", "micro")
        end
        function [ba,acc] = BinaryPlot(obj,class)
            if nargin < 2</pre>
                class = "TBI";
            end
            if ischar(class)
                class = string(class);
            end
            switch class
                case "HEA"
                    cid = 1;
                case "STR"
                    cid = 2;
                case "TBI"
                    cid = 3;
            end
            rocObj = rocmetrics(obj.testLabels,obj.scores,["HEA","STR","TBI"],...
                AdditionalMetrics=["accu", "prec"]);
            M = rocObj.Metrics;
            M.F1 = 2*(M.TruePositiveRate.*M.PositivePredictiveValue)./(M.TruePositiveRate ✓
+ M. Positive Predictive Value);
            M.BA = mean([M.TruePositiveRate, 1-M.FalsePositiveRate], 2);
            M.ClassName = string(M.ClassName);
            in = M.ClassName == class;
            M = M(in,:);
            [ba, n] = max(M.BA);
            thresh = M.Threshold(n);
```

```
ascores = obj.scores;
            ascores(:,1) = ascores(:,1) - max(ascores(:,2),ascores(:,3));
            ascores(:,2) = ascores(:,2) - max(ascores(:,1),ascores(:,3));
            ascores(:,3) = ascores(:,3) - max(ascores(:,1),ascores(:,2));
            in = ascores(:,cid) >= thresh;
            newLabels = repmat("Other", length(obj.scores), 1);
            newLabels(in) = class;
            newLabels = categorical(newLabels);
            labels = obj.testLabels;
            labels(labels ~= class) = "Other";
            labels = removecats(labels);
            acc = mean(labels==newLabels);
            figure;
            confusionchart(labels, newLabels, "RowSummary", "row-normalized","

✓
ColumnSummary", "column-normalized");
            title("Balanced Accuracy: " + (ba*100) + "%")
        end
        function mov = MoviePlot(obj,class)
            if nargin < 2
                class = "TBI";
            end
            if ischar(class)
                class = string(class);
            end
            switch class
                case "HEA"
                   cid = 1;
                case "STR"
                   cid = 2;
                case "TBI"
                   cid = 3;
            end
            rocObj = rocmetrics(obj.testLabels,obj.scores,["HEA","STR","TBI"],...
                AdditionalMetrics=["accu", "prec"]);
            M = rocObj.Metrics;
            M.ClassName = string(M.ClassName);
            in = M.ClassName == class;
            M = M(in,:);
            f = figure;
            f.Position(3) = f.Position(3)*2;
            mov(length(M.Threshold)) = struct('cdata',[],'colormap',[]);
            for i = 1:length(M.Threshold)
                subplot(1,2,1)
                ax = gca;
                ax.NextPlot = 'replaceChildren';
                plot(rocObj, "ClassNames", class, "ShowModelOperatingPoint", false)
                %plot(M.TruePositiveRate, M.FalsePositiveRate)
                hold on
                %plot([0 1],[0 1],'k--')
                scatter(M.FalsePositiveRate(i), M.TruePositiveRate(i))
```

```
legend([class, "Threshold"])
                subplot(1,2,2)
                %ax = qca;
                %ax.NextPlot = 'replaceChildren';
                ascores = obj.scores;
                ascores(:,1) = ascores(:,1) - max(ascores(:,2),ascores(:,3));
                ascores(:,2) = ascores(:,2) - max(ascores(:,1),ascores(:,3));
                ascores(:,3) = ascores(:,3) - max(ascores(:,1),ascores(:,2));
                in = ascores(:,cid) >= M.Threshold(i);
                newLabels = repmat("Other", length(obj.scores),1);
                newLabels(in) = class;
                newLabels = categorical(newLabels);
                labels = obj.testLabels;
                labels(labels ~= class) = "Other";
                labels = removecats(labels);
                acc = mean(labels==newLabels);
                confusionchart(labels, newLabels, "RowSummary", "row-normalized","✓
ColumnSummary", "column-normalized");
                cm = confusionmat(labels, newLabels);
                title("Accuracy = " + acc + "/Sensitivity = " + num2str(cm(1,1)/sum(cm
✓
(1,:))) + \dots
                    "/Precision = " + num2str(cm(1,1)/sum(cm(:,1))))
                mov(i).cdata = print('-RGBImage');
                %mov(i) = getframe(gcf);
            end
        end
        function scoremap = CAM(obj,plotAvg)
            if nargin <2</pre>
                plotAvg = false;
            end
            ind = obj.YPred==obj.testLabels;
            Cdata = subset(obj.testData,ind);
            Cscores = obj.scores(ind,:);
            tit = ["HEA", "STR", "TBI"];
            f = figure;
            f.Position(3) = f.Position(3) * 2;
            f.Position(4) = f.Position(4) * 3;
            for i = 1:3
                [m,in] = max(Cscores(:,i));
                scores = subset(Cdata,in);
                scores.MiniBatchSize = 1;
                reset (scores)
                y = read(scores);
                l = y.Response(1);
                y = y.Predictors{1};
                scoremap = gradCAM(obj.net,y,1);
                t = (0:1:length(y)-1)./scores.newHz;
                subplot(3,1,i)
                plot(t, y, Color=[0, 0, 0, 1/19]);
```

```
ylim([mean(min(y,[],2)) mean(max(y,[],2))])
        ylabel("EEG Activity")
        ax = gca;
        ax.ColorOrderIndex = 2;
        yyaxis("right")
        plot(t, scoremap, LineWidth=2);
        yl = ylim;
        ylim([0 yl(2)*2])
        ylabel("gradCAM Score")
        title(tit(i) +" (Score = " + m + ")")
        xlabel("Time (s)")
    end
    if plotAvg
        f = figure;
        f.Position(3) = f.Position(3) * 2;
        f.Position(4) = f.Position(4) * 3;
        for i = 1:3
            in = obj.testLabels(ind) == tit(i);
            [~, sin] = sort(obj.scores(in,i),'descend');
            sin = sin(1:floor(length(sin)/10));
            scores = subset(Cdata, sin);
            scores.MiniBatchSize = 1;
            reset (scores)
            avgmap=[];
            for j = 1:length(sin)
                y = read(scores);
                l = y.Response(1);
                y = y.Predictors{1};
                avgmap(j,:) = gradCAM(obj.net,y,l);
            end
            avgmap = mean(avgmap);
            t = (0:1:length(y)-1)./scores.newHz;
            subplot(3,1,i)
            plot(t,avgmap,LineWidth=2);
            yl = ylim;
            ylim([0 yl(2)*2])
            ylabel("gradCAM Score")
            title("Average " + tit(i) + " gradCAM")
            xlabel("Time (s)")
        end
    end
end
function scoremap = CAM2(obj,neg)
    if nargin <2 || neg == false</pre>
        neg = 1;
    else
        neg = -1;
    ind = obj.YPred==obj.testLabels;
    Cdata = subset(obj.testData,ind);
```

```
Cscores = obj.scores(ind,:);
            tit = ["HEA", "STR", "TBI"];
            f = figure;
            f.Position(3) = f.Position(3) * 5;
            f.Position(4) = f.Position(4) * 3;
            rw = [1:3;4:6;7:9];
            for i = 1:3
                [m,in] = \max \{(Cscores(:,i),3);
                scores = subset(Cdata,in);
                scores.MiniBatchSize = 1;
                reset (scores)
                for j = 1:3
                    y = read(scores);
                    1 = y.Response(1);
                    y = y.Predictors{1};
                    scoremap = gradCAM(obj.net,y,l);
                    t = (0:1:length(y)-1)./scores.newHz;
                    subplot(3,3,rw(j,i))
                    plot(t, y, Color=[0, 0, 0, 1/19]);
                    ylim([mean(min(y,[],2)) mean(max(y,[],2))])
                    ylabel("EEG Activity")
                    ax = qca;
                    ax.ColorOrderIndex = 2;
                    yyaxis("right")
                    %p = semilogy(t,neg.*scoremap,LineWidth=2);
                     p.Color(4) = .5;
                     %plot(t,scoremap,LineWidth=2);
                    bar(t, movmean(scoremap, 100))
                    yl = ylim;
                    ylim([0 yl(2)*2])
                     %ylim([10^-5 10^-2])
                    xlim([0 180])
                    ylabel("gradCAM Score")
                    %title(tit(i) +" (Score = " + m + ")")
                    xlabel("Time (s)")
                end
            end
              if plotAvg
응
응
                  f = figure;
                  f.Position(3) = f.Position(3) * 2;
응
                  f.Position(4) = f.Position(4) * 3;
응
응
                  for i = 1:3
응
                      in = obj.testLabels(ind) == tit(i);
응
                       [~, sin] = sort(obj.scores(in,i),'descend');
응
                      sin = sin(1:floor(length(sin)/10));
응
                       scores = subset(Cdata, sin);
응
                      scores.MiniBatchSize = 1;
응
                      reset (scores)
응
                       avgmap=[];
응
                       for j = 1:length(sin)
응
                           y = read(scores);
```

```
응
                           1 = y.Response(1);
응
                           y = y.Predictors{1};
응
                           avgmap(j,:) = gradCAM(obj.net,y,1);
응
                       end
응
                       avgmap = mean(avgmap);
응
                       t = (0:1:length(y)-1)./scores.newHz;
응
                       subplot(3,1,i)
응
                       plot(t,avgmap,LineWidth=2);
응
                       yl = ylim;
응
                       ylim([0 yl(2)*2])
응
                       ylabel("gradCAM Score")
                       title("Average " + tit(i) + " gradCAM")
응
                       xlabel("Time (s)")
응
응
                   end
응
              end
        end
        function scoremap = CAMpaper(obj,neg)
            if nargin <2 || neg == false</pre>
                neg = 1;
            else
                neg = -1;
            end
            ind = obj.YPred==obj.testLabels;
            Cdata = subset(obj.testData,ind);
            Cscores = obj.scores(ind,:);
            tit = ["HEA", "STR", "TBI"];
            f = figure("Units", "inches");
            f.Position(3) = 7.5;
            f.Position(4) = f.Position(4) * 3;
            rw = [1:3;4:6;7:9];
            k=1;
            for i = [1, 3, 2]
                [m,in] = \max(Cscores(:,i),3);
                scores = subset(Cdata,in);
                scores.MiniBatchSize = 1;
                reset (scores)
                y = read(scores);
                if i == 2
                     y = read(scores);
                 end
                l = y.Response(1);
                y = y.Predictors{1};
                 scoremap = gradCAM(obj.net,y,l);
                 t = (0:1:length(y)-1)./scores.newHz;
                 subplot(3,1,k)
                plot(t, y, Color=[0, 0, 0, 1/19]);
                ylim([mean(min(y,[],2)) mean(max(y,[],2))])
                ylabel("EEG Activity")
                 ax = gca;
```

```
ax.ColorOrderIndex = 2;
                yyaxis("right")
                %p = semilogy(t,neg.*scoremap,LineWidth=2);
                p.Color(4) = .5;
                %plot(t,scoremap,LineWidth=2);
                bar(t, movmean(scoremap, 100))
                yl = ylim;
                ylim([0 yl(2)*2])
                \gamma = 10^{-5} 10^{-2}
                xlim([0 180])
                ylabel("gradCAM Score")
                %title(tit(i) +" (Score = " + m + ")")
                xlabel("Time (s)")
                k= k + 1;
            end
        end
        function outputArg = method1(obj,inputArg)
            %METHOD1 Summary of this method goes here
            % Detailed explanation goes here
            outputArg = obj.Property1 + inputArg;
        end
   end
end
```