Spiral Systems Incorporated

SINGLE WALL ROUND
Stock Pipe and Fittings

Spiral Systems Stock Galvanized Gauges

Diameter	Spiral Pipe Gauge	Fitting Gauge
03”-09”	26	22
10”-18”	26	24
20”	24	22
22”	24	22
24”	24	22

- All pipe is stocked in 10’-0” lengths.
- Even and odd sizes available 3” through 9”, even sizes only available 10” through 24”.
- All stock fitting seams are spot welded and sealed with high-pressure duct sealant.
- All stock pipe and fittings are fabricated from G-90 or G-60 galvanized sheet steel meeting ASTM A-653 standards.
- All stock elbows have a centerline radius equal to 1-1/2 times the diameter.
- 3” thru 9” elbows are die-formed elbows, elbows 10” and larger are gored in accordance with SMACNA, 1995.
- Stocking items include: spiral pipe, 45 and 90 degree elbows, couplings, reducers, end caps/plugs, bell mouths, and start collars.
- Stock pipe and fittings are rated for (+) positive 10” W.G. and (-) negative 2” W.G. per SMACNA, 1995.

Spiral Systems Incorporated

SINGLE WALL ROUND
Positive Pressure Gauges

POSITIVE PRESSURE
SPIRAL DUCT & FITTING CONSTRUCTION STANDARDS

- Galvanized
- Paint Grade
- PVC Coated
- Stainless Steel

Diameter	+2" W.G.		+4" W.G.		+10" W.G.	
	Spiral Pipe	Fittings	Spiral Pipe	Fittings	Spiral Pipe	Fittings
3" - 6"	26	26	26	26	26	26
7" - 8"	26	26	26	26	26	26
9" - 10"	26	26	26	26	26	26
11" - 12"	26	26	26	26	26	24
13" - 14"	26	26	26	24	26	24
15" - 16"	26	24	26	24	24	22
17" - 18"	26	24	24	24	24	22
19" - 26"	26	24	24	22	24	22
27" - 36"	24	22	22	20	22	20
37" - 50"	22	20	20	20	20	20
51" - 60"	20	18	18	18	18	18
61" - 84"	18	16	18	16	18	16

Spiral Systems Incorporated

SINGLE WALL ROUND
Negative Pressure Gauges

NEGATIVE PRESSURE
SPIRAL DUCT & FITTING CONSTRUCTION STANDARDS

- Galvanized
- Paint Grade
- PVC Coated
- Stainless Steel

	- 2" W.G.		- 4" W.G.		- 10" W.G.	
Diameter	Spiral Pipe	Fittings	Spiral Pipe	Fittings	Spiral Pipe	Fittings
3" - 8"	26	26	26	26	26	26
9"	26	26	26	26	26	24
10"	26	26	26	26	26	22
11" - 12"	26	26	26	24	24	22
13"	26	26	26	24	24	20
14"	26	24	24	22	24	20
15"	26	24	24	22	22	20
16"	26	24	24	22	22	18
17"	26	24	24	20	22	18
18" - 19"	24	22	24	20	22	18
20"	24	22	22	20	22	16
22"	24	20	22	18	22	16
24"	22	20	22	18	20	16
26"	22	20	20	18	20	18R4
28" - 30"	22	18	20	16	18	16R4
32"	20	18	20	16	18	16R4
34"	20	18	20	20R6	18	16R4
36"	20	16	20	20R6	18	16R4
38" - 42"	20	16	18	18R6	18R12	
44" - 48"	Consult factory for gauge requirements					

R = Reinforcement Ring (Angle Ring) R12=12' centers, R6=6' centers, R4=4' centers.

Spiral Systems Incorporated

SINGLE WALL ROUND
Aluminum Gauges and Underground PVC Coated Gauges

SINGLE WALL ROUND SPIRAL DUCT CONSTRUCTION STANDARDS

Aluminum 3003-H14

	+2" W.G.		-2" W.G.	
Diameter	Spiral Pipe	Fittings	Spiral Pipe	Fittings
3" - 8"	.025"	.025"	.032"	.032"
9" - 14"	.025"	.025"	.032"	.032"
15" - 26"	.032"	.032"	.040"	.040"
27" - 36"	.040"	.040"	.050"	.050"
37" - 50"	.050"	.050"	.063"	.063"
51" - 60"	.063"	.063"	.071"	.071"
61" - 84"	.063"	.063"	.090"	.090"

Underground PVC Coated Spiral Duct Gauges

	+/- 4" W.G.		Load Specifications	
Diameter	Spiral Pipe	Fittings	Diameter	Lbs/ lin. ft.
3" - 8"	26	24	3" - 8"	400
9" - 14"	24	22	9" - 12"	600
15" - 26"	22	20	13" - 26"	1800
27" - 36"	20	18		
37" - 50"	18	16		

Spiral Systems Incorporated

SINGLE WALL ROUND

Spiral Pipe and Fittings
Material & Fabrication Options

Material Options	Gauges	Fitting Construction
Galvanized Steel G90 – G60, ASTM 527-1	▪ Pipe: 26 GA to 16 GA ▪ Fittings: 24 GA to 16 GA	▪ Spot welded and sealed ▪ Continuously welded
Paint Grade	▪ Pipe: 26 GA to 16 GA ▪ Fittings: 24 GA to 16 GA	▪ Spot welded and sealed ▪ Continuously welded
Aluminum 3003-H14	▪ Pipe: .025" to .063" ▪ Fittings: .032" to .090"	▪ Spot welded and sealed ▪ Continuously welded
PVC Coated (4 mil x 1 mil) (Polyvinyl-Chloride-Coated Galvanized Steel)	▪ Pipe: 26 GA to 16 GA ▪ Fittings: 24 GA to 16 GA	▪ Mechanically Fastened & Sealed
PVC Coated (4 mil x 4 mil) (Polyvinyl-Chloride-Coated Galvanized Steel)	▪ Pipe: 26 GA to 16 GA ▪ Fittings: 24 GA to 16 GA	▪ Mechanically Fastened & Sealed
Stainless Steel (Type 304-2B or 316-2B)	▪ Pipe: 26 GA to 18 GA ▪ Fittings: 24 GA to 16 GA	▪ Spot welded and sealed ▪ Continuously welded

- Standard fittings are spot welded and sealed with high-pressure water based duct sealant.
- Standard single wall pipe and fitting construction is slip joint. All pipe being female and all fittings being male.
- Fully welded fittings are available. (Except PVC coated)
- Pipe and fittings are available from 3" round to 96" round.
- Standard pipe length is 10'-0", other length are available as required.

All fittings and spiral pipe are fabricated per SMACNA HVAC Duct Construction Standards, Second Edition, 1995.