

Why the loop works: a learned path to the clean manifold, held on the physics at every step

the prior supplies the DIRECTION (it was trained on this very path); the measured data supplies the CONSTRAINT that keeps the direction honest

ONE STEP OF THE LOOP (x50)

-  PREDICT — the prior steps toward $\mathcal{M}_{clean}$
it knows the direction: it was TRAINED on this path
-  ESTIMATE — $\hat{\theta}$ is refit on that better image,
which RE-AIMS the constraint set itself
-  CORRECT — the data step pulls it back onto
 $\mathcal{C}(\hat{\theta})$; the TV corrector keeps it regular

prior alone:
a plausible image that does NOT
explain the measurement

$\mathcal{M}_{clean}$
motion-free images —
what the scan would have been

landing: $\bar{\theta}$ and the carried x_t

the ESTIMATE stage is what re-aims it: $\mathcal{C}(\hat{\theta}_0) \rightarrow \mathcal{C}(\hat{\theta}_k) \rightarrow \mathcal{C}(\theta_{true})$,
until the feasible set finally CONTAINS the clean image.

$\mathcal{C}(\hat{\theta}) = \{x : A_{\hat{\theta}} x \approx y\}$ — the constraint that PHYSICALLY EXISTS:
the measured projections. It is not a regularizer we chose, it is the scan.

GEOMETRY BRIDGE $\{\text{FDK}(y, P_{nom}T(s\theta))\}$

every point on it is a REAL reconstruction of the REAL data —
and it is exactly the path the prior was trained on ($v_{\psi} \approx dx_t/dt$)

START

$$x_0 = \text{FDK}(y, P_{nom})$$

streaked — and consistent
with the WRONG geometry

the two forces alternate $N = 50$ times — neither one reaches $\mathcal{M}_{clean}$ on its own

data step alone, at the geometry we started with ($\hat{\theta} = 0$): perfectly consistent — and still streaked