

SpringBootLibrarySphinx

Technical Documentation

Generated automatically by GitHub Actions · dipina

SpringBootLibrary Documentation

Welcome to the **SpringBootLibrary** technical documentation portal. This site aggregates all documentation artifacts generated for the project, including architectural guides, Javadoc API reference, test reports, and code quality reports.

Indices and tables

- [Index](#)
- [Search Page](#)

Project Overview

Purpose

SpringBootLibrarySphinx is an exemplary Spring Boot application developed for the **SPQ (Software Process and Quality)** subject. It demonstrates best practices in:

- RESTful API design with Spring Boot
- Layered MVC architecture
- Automated testing (unit, integration, performance)
- CI/CD pipelines with GitHub Actions
- Code quality tooling (JaCoCo, PMD, Checkstyle, JDepend)
- Technical documentation (Doxygen, Maven Site, **Sphinx**)

The application models a **library borrowing system** where users can borrow and return books through a shared platform.

Key Features

Feature	Technology
REST API backend	Spring Boot 3.4, Spring MVC
Database ORM	Spring Data JPA + Hibernate
Database	MySQL (prod), H2 (test)
API docs (interactive)	Springdoc OpenAPI / Swagger UI
Unit tests	JUnit 5 + Mockito
Integration tests	Spring Boot Test + MySQL
Performance tests	JUnitPerf
Code coverage	JaCoCo
Static analysis	PMD, Checkstyle, JDepend
Containerisation	Docker + Docker Compose
Technical docs	Doxygen, Maven Site, Sphinx

Live Documentation Links

Document	URL
Landing page	https://dipina.github.io/SpringBootLibrarySphinx/
This Sphinx hub	https://dipina.github.io/SpringBootLibrarySphinx/sphinx/index.html
Sphinx PDF	https://dipina.github.io/SpringBootLibrarySphinx/sphinx/SpringBootLibrarySphinx.pdf
Javadoc	https://dipina.github.io/SpringBootLibrarySphinx/site/apidocs/index.html
JaCoCo coverage	https://dipina.github.io/SpringBootLibrarySphinx/site/jacoco/index.html
Surefire unit tests	https://dipina.github.io/SpringBootLibrarySphinx/site/surefire-report.html
Performance tests	https://dipina.github.io/SpringBootLibrarySphinx/site/reports/perf-report.html
Checkstyle	https://dipina.github.io/SpringBootLibrarySphinx/site/checkstyle.html
PMD	https://dipina.github.io/SpringBootLibrarySphinx/site/pmd.html
Doxygen	https://dipina.github.io/SpringBootLibrarySphinx/doxygen/html/index.html
Swagger UI	http://localhost:8080/swagger-ui.html (local only)


Repository Structure

```
SpringBootLibrarySphinx/
├── .github/workflows/
│   ├── sphinx-docs.yml          ← Sphinx + PDF → GitHub Pages
│   └── maven-site-integration.yml ← Build, test, Maven site → GitHub Pages
├── docs-sphinx/                ← All Sphinx source files
│   ├── index.html              ← Landing page (committed, readable
HTML)
│   ├── Makefile                ← Linux/macOS build
│   ├── make.bat                ← Windows build
│   ├── requirements.txt        ← Python dependencies
│   └── source/
│       ├── conf.py
│       ├── index.rst
│       ├── overview.md
│       ├── architecture.md
│       ├── getting_started.md
│       ├── testing.md
│       ├── reports.md
│       ├── api_rest.md
│       ├── javadoc_link.md
│       ├── cicd.md
│       ├── docker.md
│       └── sphinx_101.md
├── src/                        ← Java source code
├── pom.xml                     ← Maven build
└── README.md
```

Architecture

MVC Pattern

SpringBootLibrary follows the classic **Model-View-Controller (MVC)** pattern, adapted for a REST API:



Package Structure

Package	Responsibility
<code>controller/</code>	REST endpoints — <code>BookController</code> , <code>BorrowingController</code> , <code>UserController</code>
<code>service/</code>	Business logic — <code>BookService</code> , <code>BorrowingService</code> , <code>UserService</code>
<code>repository/</code>	JPA repositories — CRUD + custom queries
<code>model/</code>	JPA entities — <code>Book</code> , <code>Borrowing</code> , <code>User</code>

Key Design Decisions

Spring Data JPA is used for the persistence layer. Repository interfaces extend `JpaRepository` , providing standard CRUD operations without boilerplate code.

H2 in-memory database is activated automatically in the `test` Spring profile, so unit and integration tests run without requiring a real MySQL instance (except when using `@SpringBootTest` with the `integration` Maven profile, which spins up a MySQL Docker container via GitHub Actions).

Springdoc OpenAPI auto-generates an interactive Swagger UI from the controller annotations at runtime, always reflecting the current API surface.

Static Resources

The frontend is a plain HTML + JavaScript + CSS single-page application located at:

```
src/main/resources/static/  
├─ index.html  
├─ app.js  
└─ style.css
```

It communicates with the backend over REST, keeping the view layer decoupled from the server.

Getting Started

Prerequisites

Tool	Minimum Version
Java (JDK)	17
Maven	3.9
MySQL	8.0
Docker & Docker Compose	24+ (optional)

Database Setup

```
mysql -u root -p < src/main/resources/dbsetup.sql
```

Then update `src/main/resources/application.properties` with your database credentials:

```
spring.datasource.url=jdbc:mysql://localhost:3306/libraryapidb
spring.datasource.username=<your_user>
spring.datasource.password=<your_password>
```

Running the Application

```
# Build and run (all checks)
mvn clean install
mvn spring-boot:run

# Skip tests for a fast start
mvn -DskipTests spring-boot:run
```

Access points once running:

Endpoint	URL
Frontend UI	http://localhost:8080
Swagger UI	http://localhost:8080/swagger-ui.html
OpenAPI JSON	http://localhost:8080/v3/api-docs

Running with Docker

```
# Start all services (app + MySQL)
docker-compose up

# Rebuild after Dockerfile changes
docker-compose up --build
```

Quick Reference: Maven Commands

Goal	Command
Unit tests	<code>mvn test</code>
Integration tests	<code>mvn -Pintegration integration-test</code>
Performance tests	<code>mvn -Pperformance integration-test</code>
JaCoCo coverage report	<code>mvn clean test jacoco:report</code>
Full Maven site	<code>mvn clean verify site</code>
Publish docs to <code>docs/</code>	<code>mvn post-site</code>
Build Sphinx docs	<code>cd docs-sphinx && make html</code>

Testing Strategy

The project applies a three-tier testing strategy, each with its own Maven profile and tooling.

Unit Tests

Framework: JUnit 5 + Mockito

Location: `src/test/java/com/example/library/` (excluding `integration/` and `performance/`)

Command:

```
mvn test
```

Unit tests mock all external dependencies (database, other services) and run in-process using the H2 in-memory database. They are fast and should run on every commit.

Key test classes:

- `BookServiceTest` — validates book availability, add/remove logic
- `UserServiceTest` — validates user registration and lookup
- `BorrowingServiceTest` — validates borrow/return business rules

Integration Tests

Framework: Spring Boot Test (`@SpringBootTest`) + real MySQL

Location: `src/test/java/com/example/library/integration/`

Maven profile: `integration`

Command:

```
mvn -Pintegration integration-test
```

Integration tests start the full Spring context against a live database. In CI they rely on the MySQL Docker service defined in the GitHub Actions workflow.

Performance Tests

Framework: JUnitPerf

Location: `src/test/java/com/example/library/performance/`

Maven profile: `performance`

Command:

```
mvn -Pperformance integration-test
```

Performance tests annotate methods with `@JUnitPerfTest` to define throughput and latency thresholds. The generated HTML report is saved to `target/reports/perf-report.html`.

Code Coverage

Tool: JaCoCo

Minimum line coverage enforced: 25 %

```
mvn clean test jacoco:report # generates target/site/jacoco/index.html
mvn clean verify             # enforces the coverage threshold
```

The JaCoCo report is included in the Maven Site and embedded in the Sphinx portal.

Static Analysis

Tool	Purpose	Report
Checkstyle	Code style conformance	<code>target/site/checkstyle.html</code>
PMD	Static bug-pattern detection	<code>target/site/pmd.html</code>
CPD (via PMD)	Copy-paste detection	<code>target/site/cpd.html</code>
JDepend	Package coupling metrics	<code>target/site/jdepend-report.html</code>

All static-analysis reports are produced during `mvn site`.

Test & Quality Reports

All reports are generated automatically by the CI/CD pipeline on every push to `main` and published to GitHub Pages alongside the Sphinx portal.

Javadoc API Reference

Generated by `maven-javadoc-plugin` during `mvn site`.

Note

→ [Open Javadoc](#)

JaCoCo — Code Coverage

Note

→ [JaCoCo Coverage Report](#)

Minimum enforced: **25 % line coverage** via `mvn verify`.

Surefire — Unit Test Report

Note

→ [Surefire Unit Test Report](#)

Performance Tests

Note

→ [Performance Report](#)

Generated by the `performance` Maven profile (`mvn -Pperformance integration-test`), then copied into `target/site/reports/` before `mvn site` runs.

Checkstyle

Note

→ [Checkstyle Report](#)

PMD — Static Analysis

Note

→ [PMD Report](#)

→ [CPD \(Copy-Paste Detector\)](#)

JDepend — Package Metrics

Note

→ [JDepend Report](#)

Doxygen

Note

→ [Doxygen HTML Reference](#)

Complete path map

Report	Published path on GitHub Pages	Generated by
Javadoc	<code>site/apidocs/index.html</code>	<code>maven-javadoc-plugin</code> in <code><reporting></code>
JaCoCo	<code>site/jacoco/index.html</code>	<code>mvn test jacoco:report</code>
Surefire	<code>site/surefire-report.html</code>	<code>surefire-report-plugin</code> <code>report</code> goal
Performance	<code>site/reports/perf-report.html</code>	<code>mvn -Pperformance integration-test</code>
Checkstyle	<code>site/checkstyle.html</code>	<code>mvn site</code>
PMD	<code>site/pmd.html</code>	<code>mvn site</code>
CPD	<code>site/cpd.html</code>	<code>mvn site</code>
JDepend	<code>site/jdepend-report.html</code>	<code>mvn site</code>
Doxygen	<code>doxygen/html/index.html</code>	<code>doxygen-maven-plugin</code> via <code>mvn site</code>

Generating All Reports Locally

```
# 1. Unit tests + JaCoCo
mvn test jacoco:report

# 2. Performance tests + copy report into site/reports/
mvn -Pperformance integration-test
mvn -Pperformance resources:copy-resources@copy-perf-report

# 3. Full Maven site (Javadoc, Checkstyle, PMD, JDepend, Surefire, JaCoCo,
Doxygen)
mvn site

# 4. Copy everything to docs/ (local preview only – not committed)
mvn post-site
```

REST API Reference

The API is documented interactively via **Springdoc OpenAPI** and is always in sync with the source code.

Swagger UI (Live)

When the application is running locally:

```
http://localhost:8080/swagger-ui.html
```

The OpenAPI JSON specification can be downloaded from:

```
http://localhost:8080/v3/api-docs
```

Endpoints Summary

Books

Method	Path	Description
GET	/api/books	List all books
GET	/api/books/{id}	Get book by ID
POST	/api/books	Add a new book
PUT	/api/books/{id}	Update a book
DELETE	/api/books/{id}	Delete a book

Users

Method	Path	Description
GET	/api/users	List all users
GET	/api/users/{id}	Get user by ID
POST	/api/users	Register a new user
DELETE	/api/users/{id}	Delete a user

Borrowings

Method	Path	Description
GET	/api/borrowings	List all borrowings
POST	/api/borrowings	Borrow a book
PUT	/api/borrowings/{id}/return	Return a borrowed book
GET	/api/borrowings/user/{userId}	Get borrowings for a user

Request / Response Examples

Borrow a book

Request:

```
POST /api/borrowings
Content-Type: application/json

{
  "userId": 1,
  "bookId": 42
}
```

Response 201 Created :

```
{
  "id": 7,
  "userId": 1,
  "bookId": 42,
  "borrowDate": "2025-04-20",
  "returnDate": null,
  "status": "BORROWED"
}
```

Return a book

```
PUT /api/borrowings/7/return
```

Response 200 OK :

```
{
  "id": 7,
  "returnDate": "2025-04-22",
  "status": "RETURNED"
}
```

Javadoc API Documentation

Full Javadoc is generated by `maven-javadoc-plugin` during `mvn site`.

Important

→ [Open Javadoc](#)

Why Javadoc was missing — and the fix

Javadoc is **only generated** when `maven-javadoc-plugin` is declared inside the `<reporting><plugins>` section of `pom.xml`. Without it, `mvn site` silently skips Javadoc and `site/apidocs/` is never created.

The plugin has been added to `pom.xml` in this project. The critical block is:

```
<reporting>
  <plugins>
    <!-- This block was missing – without it mvn site skips Javadoc -->
    <plugin>
      <groupId>org.apache.maven.plugins</groupId>
      <artifactId>maven-javadoc-plugin</artifactId>
      <version>3.6.3</version>
      <reportSets>
        <reportSet>
          <reports>
            <report>javadoc</report>
          </reports>
        </reportSet>
      </reportSets>
      <configuration>
        <doclint>none</doclint>
      </configuration>
    </plugin>
    <!-- ... other reporting plugins ... -->
  </plugins>
</reporting>
```

The `<doclint>none</doclint>` flag is important — without it, any comment that doesn't conform strictly to Javadoc syntax causes the build to fail.

Key Documented Classes

Class	Package	Description
<code>BorrowingController</code>	<code>controller</code>	REST endpoints for borrowing — includes <code>@Operation</code> (OpenAPI) annotations
<code>BookService</code>	<code>service</code>	Business logic for book inventory management
<code>Borrowing</code>	<code>model</code>	JPA entity modelling a borrowing transaction
<code>BookRepository</code>	<code>repository</code>	Spring Data JPA repository with custom query methods
<code>UserService</code>	<code>service</code>	User management operations

Generating Javadoc Locally

```
# As part of the full Maven site (recommended – also runs all other reports)
mvn site
# Open: target/site/apidocs/index.html

# Standalone
mvn javadoc:javadoc
# Open: target/site/apidocs/index.html
```

Javadoc vs Doxygen

Tool	Output	Strength
Javadoc	<code>site/apidocs/</code>	Standard Java API reference; IDE integration
Doxygen	<code>doxygen/html/</code>	Cross-referenced call graphs, class diagrams, richer navigation

CI/CD with GitHub Actions

The project ships with two GitHub Actions workflows:

Workflow file	Trigger	What it does
<code>maven-site-integration.yml</code>	Push to any branch + cron	Build, test, Maven site, deploy to Pages
<code>sphinx-docs.yml</code>	Push to <code>main</code>	Build Sphinx docs + merge into GitHub Pages

Workflow 1: `maven-site-integration.yml`

This is the main CI/CD workflow. It:

1. Starts a MySQL 8 Docker service
2. Waits for the database to be healthy
3. Runs the DB initialisation script
4. Executes integration tests (`-Pintegration`)
5. Generates the full Maven site (Javadoc, JaCoCo, PMD, Checkstyle, Surefire)
6. Copies all Maven site output + Doxygen into the `docs/site/` and `docs/doxygen/` sub-folders
7. Deploys the `docs/` directory to **GitHub Pages**

```

name: Maven Site & Integration Tests

on:
  push:
    branches: ['**']
  schedule:
    - cron: '0 18-23/2 * * *'
    - cron: '0 0-6/2 * * *'

jobs:
  build-and-test:
    runs-on: ubuntu-latest

    services:
      mysql:
        image: mysql:8.0
        env:
          MYSQL_ROOT_PASSWORD: root
          MYSQL_DATABASE: libraryapldb
        ports:
          - 3306:3306
        options: >-
          --health-cmd="mysqladmin ping -h 127.0.0.1 -uroot -proot"
          --health-interval=10s
          --health-timeout=5s
          --health-retries=5

    steps:
      - uses: actions/checkout@v4

      - name: Set up JDK 17
        uses: actions/setup-java@v4
        with:
          java-version: '17'
          distribution: 'temurin'

      - name: Cache Maven
        uses: actions/cache@v4
        with:
          path: ~/.m2/repository
          key: ${{ runner.os }}-maven-${{ hashFiles('**/pom.xml') }}

      - name: Wait for MySQL
        run: |

until mysqladmin ping -h 127.0.0.1 -uroot -proot --silent; do sleep 2; done

      - name: Init database

```



```
run: mysql -h 127.0.0.1 -uroot -proot < src/main/resources/
dbsetup.sql

- name: Integration tests
  run: mvn -Pintegration integration-test

- name: Maven site
  run: mvn site

- name: Publish docs to GitHub Pages
  uses: peaceiris/actions-gh-pages@v4
  with:
    github_token: ${ secrets.GITHUB_TOKEN }
    publish_dir: ./docs
    destination_dir: . # serve from root of gh-pages branch
    keep_files: true # keep Sphinx output from the other workflow
```

Workflow 2: `sphinx-docs.yml`

This workflow builds the Sphinx documentation and deploys it to the `gh-pages` branch **alongside** the Maven site output, without overwriting it.

```

name: Build and Deploy Sphinx Docs

on:
  push:
    branches: [main]
  workflow_dispatch:

jobs:
  sphinx:
    runs-on: ubuntu-latest

    steps:
      - uses: actions/checkout@v4

      - name: Set up Python
        uses: actions/setup-python@v5
        with:
          python-version: '3.12'

      - name: Install Sphinx dependencies
        run: |
          pip install -r docs-sphinx/requirements.txt

      - name: Build Sphinx HTML
        run: |
          cd docs-sphinx
          make html

      - name: Deploy Sphinx to GitHub Pages (sphinx/ subfolder)
        uses: peaceiris/actions-gh-pages@v4
        with:
          github_token: ${ secrets.GITHUB_TOKEN }
          publish_dir: ./docs-sphinx/_build/html
          destination_dir: sphinx # → gh-pages/sphinx/
          keep_files: true

```

GitHub Pages Setup

To enable GitHub Pages for this repository:

1. Go to **Settings** → **Pages**
2. Set **Source** to `gh-pages` branch, root `/`
3. Save — the site will be live at `https://<owner>.github.io/SpringBootLibrary/`

Permissions: Go to **Settings** → **Actions** → **General** → **Workflow permissions** and set **Read and write permissions** so that the `GITHUB_TOKEN` can push to the `gh-pages` branch.

Triggering Workflows via API

```
curl -X POST \
  https://api.github.com/repos/<owner>/SpringBootLibrary/actions/workflows/
sphinx-docs.yml/dispatches \
  -H "Accept: application/vnd.github+json" \
  -H "Authorization: Bearer $PAT_TOKEN" \
  -H "X-GitHub-API-Version: 2022-11-28" \
  -d '{"ref":"main"}'
```

Docker & Docker Compose

Quick Start

```
# Start application + MySQL (uses cached images)
docker-compose up

# Rebuild after code or Dockerfile changes
docker-compose up --build

# Run in background
docker-compose up -d

# Stop all services
docker-compose down
```

Dockerfile

The project's `Dockerfile` packages the Spring Boot fat JAR into a lightweight JRE image:

```
FROM eclipse-temurin:17-jre-alpine
WORKDIR /app
COPY target/*.jar app.jar
EXPOSE 8080
ENTRYPOINT ["java", "-jar", "app.jar"]
```

docker-compose.yml

The compose file wires the app container to a MySQL service, passing environment variables for the database connection:

```

version: '3.8'
services:
  app:
    build: .
    ports:
      - "8080:8080"
    environment:
      SPRING_DATASOURCE_URL: jdbc:mysql://db:3306/libraryapidb
      SPRING_DATASOURCE_USERNAME: root
      SPRING_DATASOURCE_PASSWORD: root
    depends_on:
      db:
        condition: service_healthy

  db:
    image: mysql:8.0
    environment:
      MYSQL_ROOT_PASSWORD: root
      MYSQL_DATABASE: libraryapidb
    healthcheck:
      test: ["CMD", "mysqladmin", "ping", "-h", "localhost"]
      interval: 10s
      timeout: 5s
      retries: 5

```

VisualVM Profiling

To enable remote profiling with VisualVM, the `spring-boot-maven-plugin` is configured with:

```
<jvmArguments>-Xverify:none</jvmArguments>
```

Then run `mvn spring-boot:run` and connect VisualVM to the local JVM from the **Local** tab.

Sphinx 101 — Complete Guide

What Is Sphinx?

Sphinx is an open-source documentation generator originally created for the Python language reference documentation (it still powers the official Python docs). Today it is widely used across languages — including Java, C++, and JavaScript projects — whenever developers need to produce structured, professional, multi-page technical documentation from plain text source files.

Sphinx takes plain text files written in **reStructuredText** (`.rst`) or **Markdown** (`.md` , via the **MyST parser extension**) and generates:

- Static HTML websites (the most common output)
- PDF documents (via LaTeX)
- ePub e-books
- Man pages

The result is a maintainable, version-controlled documentation site that lives alongside the source code and can be automatically published through CI/CD.

What Is Sphinx Useful For?

Use Case	Why Sphinx
Project portals	Aggregates API docs, guides, reports, and tutorials in one navigable site
API reference	Can auto-import Python docstrings; for Java projects, embeds Javadoc/Doxygen links
Tutorials & how-tos	Numbered sections, admonition boxes, code blocks with syntax highlighting
Multi-version docs	Tools like <code>sphinx-multiversion</code> serve docs for every tagged release
Search	Built-in full-text client-side search (no server needed)
Cross-references	<code>:ref:</code> , <code>:doc:</code> directives create typed links that break at build time if the target disappears
Theming	Dozens of themes (<code>sphinx_rtd_theme</code> , <code>furo</code> , <code>pydata_sphinx_theme</code>) give professional results instantly

Sphinx vs. Alternatives

Tool	Primary audience	Markup	Auto-API	Best for
Sphinx	Python / polyglot	RST / Markdown	Python (autodoc)	Comprehensive project portals
Javadoc	Java	Javadoc tags	Yes (Java)	API reference only
Doxygen	C/C++/Java	Doxygen tags	Yes	Cross-referenced code ref
MkDocs	Any	Markdown	No	Simple Markdown-first sites
Docusaurus	JS / React	Markdown/MDX	No	Product/SaaS documentation

Sphinx shines when you need a **single portal** that combines hand-written narrative documentation, auto-generated API references, test reports, and external links — exactly the goal of this project.

How Is Sphinx Used?

1. Install Sphinx

```
pip install sphinx sphinx-rtd-theme myst-parser
```

Or pin versions in a `requirements.txt` :

```
sphinx==7.4.7
sphinx-rtd-theme==2.0.0
myst-parser==3.0.1
```


2. Initialise a Project

```
sphinx-quickstart docs-sphinx
```

This interactive wizard creates `conf.py` (the configuration file), `index.rst` (the master table of contents), and a `Makefile`.

3. Source File Structure

```
docs-sphinx/
├── source/
│   ├── conf.py          ← Sphinx configuration
│   ├── index.rst        ← Master table of contents (toctree)
│   ├── overview.md      ← A page written in Markdown
│   ├── api.rst          ← A page written in reStructuredText
│   └── _static/         ← Custom CSS / images
├── Makefile             ← make html, make pdf, ...
└── requirements.txt     ← Pinned Python dependencies
```

4. The `toctree` Directive

The `.. toctree::` directive in `index.rst` defines the site's navigation hierarchy:

```
.. toctree::
   :maxdepth: 2
   :caption: Project Overview

   overview
   architecture
   getting_started
```

Each entry maps to a `.rst` or `.md` file. Sphinx resolves them recursively.

5. Build the Documentation

```
cd docs-sphinx
make html          # output → _build/html/index.html
make latexpdf      # output → _build/latex/*.pdf
make clean         # remove previous build artefacts
```

6. Key reStructuredText Syntax

Section Heading

=====

Sub-heading

A paragraph with **bold**, *italic*, and `inline code`.

.. code-block:: java

```
public class Hello {
    public static void main(String[] args) {
        System.out.println("Hello from Sphinx!");
    }
}
```

.. note::

This is an admonition – a highlighted information box.

.. warning::

This is a warning box.

7. Markdown with MyST

With the `myst-parser` extension enabled in `conf.py`, you can write pages in Markdown:

My Page

A paragraph with **bold** and *italic*.

```
```java
```

```
public class Hello { }
```

```
```
```

```
```{note}
```

This is a MyST admonition.

```
```
```

```
```{toctree}
```

```
:maxdepth: 2
```

```
overview
```

```
architecture
```

```
```
```

How to Integrate Sphinx with GitHub Actions

The workflow below builds the Sphinx HTML and publishes it to the `gh-pages` branch using the `peaceiris/actions-gh-pages` action. It preserves other content already on `gh-pages` (e.g., Maven Site) via `keep_files: true`.

```

# .github/workflows/sphinx-docs.yml
name: Build and Deploy Sphinx Docs

on:
  push:
    branches: [main]
  workflow_dispatch:      # allow manual trigger

jobs:
  sphinx:
    runs-on: ubuntu-latest

    steps:
      - name: Checkout repository
        uses: actions/checkout@v4

      - name: Set up Python 3.12
        uses: actions/setup-python@v5
        with:
          python-version: '3.12'

      - name: Cache pip packages
        uses: actions/cache@v4
        with:
          path: ~/.cache/pip
          key: ${ runner.os }-pip-${ hashFiles('docs-sphinx/requirements.txt') }
          restore-keys: ${ runner.os }-pip-

      - name: Install Sphinx & extensions
        run: pip install -r docs-sphinx/requirements.txt

      - name: Build Sphinx HTML
        run: |
          cd docs-sphinx
          make html

      - name: Deploy to GitHub Pages (sphinx/ subfolder)
        uses: peaceiris/actions-gh-pages@v4
        with:
          github_token: ${ secrets.GITHUB_TOKEN }
          publish_dir: ./docs-sphinx/_build/html
          destination_dir: sphinx      # published at /sphinx/ URL path
          keep_files: true             # preserve Maven Site & Doxygen content

```

Required Repository Settings

1. **Settings** → **Actions** → **General** → **Workflow permissions** → *Read and write permissions*
2. **Settings** → **Pages** → Source: `gh-pages` branch, folder: `/`

The Sphinx portal will then be live at:

```
https://<owner>.github.io/<repo>/sphinx/
```

How This Project Uses Sphinx

Documentation Architecture

The Sphinx portal for SpringBootLibrary is a **meta-documentation hub** — it does not duplicate content that already lives in other tools; instead it links out to the generated artefacts:

```
GitHub Pages (gh-pages branch)
├─ index.html          ← Landing page redirecting to Sphinx or Maven
site
├─ sphinx/             ← Sphinx portal (this site)
│   ├─ index.html
│   ├─ overview.html
│   ├─ testing.html
│   ├─ reports.html    ← Links to JaCoCo, Surefire, PMD reports
│   ├─ javadoc_link.html ← Links to Javadoc in site/apidocs/
│   └─ sphinx_101.html ← This page
├─ site/               ← Maven Site (Javadoc, JaCoCo, PMD, Checkstyle ...)
│   ├─ apidocs/
│   ├─ jacoco/
│   ├─ surefire-report.html
│   └─ ...
└─ doxygen/            ← Doxygen cross-referenced HTML
    └─ html/
```

Integration Points

| External Artefact | Where Sphinx links to it |
|--------------------|---|
| Javadoc | <code>javadoc_link.md</code> → <code>../site/apidocs/index.html</code> |
| JaCoCo | <code>reports.md</code> → <code>../site/jacoco/index.html</code> |
| Surefire | <code>reports.md</code> → <code>../site/surefire-report.html</code> |
| PMD / Checkstyle | <code>reports.md</code> → <code>../site/pmd.html</code> |
| Performance report | <code>reports.md</code> → <code>../site/reports/perf-report.html</code> |
| Doxygen | <code>javadoc_link.md</code> → <code>../doxygen/html/index.html</code> |

Adding a New Documentation Page

1. Create `docs-sphinx/source/my_page.md`
2. Add `my_page` to the appropriate `.. toctree::` in `index.rst`
3. Push to `main` — the GitHub Actions workflow rebuilds and redeploys automatically

Adding the `conf.py` Extensions for This Project

```
extensions = [  
    'sphinx.ext.autodoc',      # auto-import Python docstrings (optional here)  
    'sphinx.ext.viewcode',    # adds [source] links  
    'sphinx.ext.napoleon',    # Google/NumPy style docstrings  
    'myst_parser',            # Markdown .md files  
    'sphinx_rtd_theme',       # Read the Docs theme  
]
```

Useful Sphinx Resources

| Resource | URL |
|----------------------------|---|
| Official Sphinx docs | https://www.sphinx-doc.org |
| MyST Markdown parser | https://myst-parser.readthedocs.io |
| Read the Docs theme | https://sphinx-rtd-theme.readthedocs.io |
| Furo theme (modern) | https://pradyunsg.me/furo |
| sphinx-multiversion | https://holzhaus.github.io/sphinx-multiversion |
| peaceiris/actions-gh-pages | https://github.com/peaceiris/actions-gh-pages |