

# Formal Methods in Software Engineering

## Laboratory 1

1. Install Dafny and familiarize with its use.
2. Read first the blog *Clear Separation of Specification and Implementation in Dafny* [8].
3. Define a predicate  $IsOddNat(x)$  that holds when the integer  $x$  is an odd natural number.
4. Define a subsort  $Odd$ , defining the odd natural numbers.
5. Define a predicate  $IsEvenNat(x)$  that holds when the integer  $x$  is an even natural number.
6. Define a subsort  $Even$ , defining the even natural numbers.
7. Define a lemma showing that the addition of two odd numbers is an even number.
8. Define a predicate  $IsPrime(x)$ , which holds when the integer  $x$  is a prime number.
9. Define a lemma showing that any prime number  $x > 2$  is an odd number.
10. Define a type  $int32$  that represents signed integers with values that range from negative 2,147,483,648 (which is represented by the `Int32.MinValue` constant) through positive 2,147,483,647 (which is represented by the `Int32.MaxValue` constant). Define functions that implements the operations of this type in the same way your preferred programming language does it.

## References

- [1] Dafny Site. <https://dafny.org/dafny/>
- [2] Dafny: Visual Studio Code Extension.  
<https://marketplace.visualstudio.com/items?itemName=dafny-lang.ide-vscode>

- [3] Dafny: Github Repository.  
<https://github.com/dafny-lang/dafny>
- [4] Dafny: Emacs Mode.  
<https://github.com/boogie-org/boogie-friends>
- [5] Dafny: Command Line Options.  
<https://manpages.debian.org/testing/dafny/dafny.1.en.html>
- [6] DAFNY POWER USER.  
<http://leino.science/dafny-power-user/>
- [7] Verier Luke Herbert, K. Rustan M. Leino, and Jose Quaresma. Using Dafny, an Automatic Program. LNCS, volume 7682
- [8] Aaron Tomb. Clear Separation of Specification and Implementation in Dafny  
<https://dafny.org/blog/2023/08/14/clear-specification-and-implementation/>
- [9] K. Rustan M. Leino. Program Proofs. The MIT Press, 2023  
<https://mitpress.mit.edu/9780262546232/program-proofs/>

## A Many Sorted Logic in Dafny

### A.1 Builtin theories

Each builtin type defines in fact many sorted logic theory. For instance, the type `int` defines the following theory:

**Sorts:** `int`

**Function symbols:**  $\Sigma_{[],int} = \{\dots, -2, -1, 0, 1, 2, \dots\}$  (all integers),  $\Sigma_{int\ int,int} = \{+, -, +, *, /, \%\}$ ,  $\Sigma_{int,int} = \{-\}$ ,  $\dots$

**Predicate symbols:**  $\Pi_{int\ int} = \{<, <=, >, >=\}$

Formulas expressing, e.g., that the binary operators are left associative.

### A.2 User defined sorts

Example:

```
newtype int8 = x: int | -128 <= x < 128
```

### A.3 User defined functions

Example:

```
function addInt8(a: int8, b: int8): int8
{
  var res := a as int + b as int;
  if (-128 <= res < 128) then res as int8 else 0
}
```

## A.4 User defined predicates

Example:

```
predicate evenInt8(x: int8)
{
    (x as int) % 2 == 0
}
```