



Existing Bed Level in (mPWD)	
11.004	4.234
12.004	2.555
14.005	0.804
16.006	0.344
17.006	(-)1.456
18.007	(-)1.236
19.007	(-)1.756
21.008	(-)2.256
25.108	(-)9.580
29.350	(-)9.700
35.004	(-)10.350
38.558	(-)11.010
40.708	(-)11.100
45.167	(-)11.400
46.743	(-)11.530
48.943	(-)12.090
53.351	(-)12.460
58.145	(-)12.070
63.144	(-)13.080
68.144	(-)12.760
70.948	(-)12.520
74.546	(-)12.480
76.743	(-)12.370

TYPICAL CROSS SECTION AT KM 0.000
(APPLICABLE FROM KM 0.000 TO KM 0.070)

Bangladesh Water Development Board			
Office of The Superintending Engineer, Design Circle-8			
Protection of Morreiganj Upazila Sadar and adjacent areas from erosion Pangusi river in Bagerhat District and Re-excavation/Dredging of Bishkhali river			
River Bank Protective Work From Sannashi to Khawlia From km 0.000 to km 4.500 = 4.500 km			
TYPICAL CROSS SECTION OF FROM SANNASHI TO KHAWLIA			
DESIGNED BY:	PROTECTIVE WORK	RECOMMENDED BY:	
(ZAYED BIN SAIF),AE		(MOHAMMAD SAIF UDDIN),SE	
CHECKED BY:		APPROVED BY:	
(JAKARIA PERVEZ),EE		(MD. ENAYET ULLAH),CE,DESIGN	
DATE:08-11-2022		Drawing No:DC-8-XXXX-04/50	