

GENERAL NOTES

- 1.THE SPECIFICATION OF MATERIALS AND WORKMANSHIP SHALL CONFORM TO THE STANDARD TECHNICAL SPECIFICATION OF BWDB, IN GENERAL.
2. ALL DIMENSIONS ARE IN MILLIMETERS AND ALL ELEVATIONS ARE IN MPWD UNLESS OTHERWISE MENTIONED IN THE DRAWINGS.
3. COMPRESSIVE STRENGTH OF REINFORCED CEMENT CONCRETE SHALL HAVE MINIMUM 28 DAYS CYLINDER STRENGTH, $f_c \geq 25.00 \text{ N/mm}^2$ (ITEM CODE: 28-230-10) AND SHALL BE CHECKED BY COLLECTING SAMPLES AND TESTING DURING CONSTRUCTION.
4. REINFORCING BAR SHALL BE DEFORMED MILD STEEL HAVING YIELD STRENGTH, $f_y \geq 400.00 \text{ N/mm}^2$. (ITEM CODE-76-120-10), (MADE FROM BILLET) IN R.C.C. WORK.
5. CONCRETE FOR CC BLOCKS SHALL HAVE MINIMUM STRENGTH, $f_c \geq 10.50 \text{ N/mm}^2$ AT 28 DAYS.
6. CURING OF CONCRETE SHALL BE CONTINUED FOR MINIMUM 21 DAYS AFTER CASTING.
7. CONCRETE SHALL BE POURED IN DRY BED CONDITION.
8. THE SURFACE OF CONSTRUCTION JOINTS SHALL BE WASHED THOROUGHLY WITH WATER JET & SHALL BE CLEAN ENOUGH AFTER THAT, SURFACE SHALL BE DRY PRIOR TO PLACEMENT OF ADJOINING CONCRETE.
9. CONCRETE MIXTURE SHALL BE POURED AS QUICK AS POSSIBLE BUT NOT LATER THAN 45 MINUTES AFTER MIXING.
10. 75 mm LEAN CONCRETE AT BASE SHALL BE IN 1:3:6.
11. THE LEAN CONCRETE AT FOUNDATION OF THE PROPOSED REGULATOR SHALL BE PLACED AFTER PROPERLY PREPARING & COMPACTING EXCAVATED BASE.
12. CLEAR COVER FOR REINFORCEMENT SHALL BE AS FOLLOWS:
 - a) Operating deck & Railing : 25mm
 - b) Concrete adjacent to earth at foundation: 75mm
 - c) Concrete exposed to weather and water or others: 75mm
 - d) Concrete exposed to weather and water or others: 75mm
 - e) Beam: 40mm
13. MINIMUM LAP LENGTH SHALL BE 40 TIMES THE BAR DIAMETER.
14. LAP SHALL BE STAGGERED SO THAT NOT MORE THEN 50% OF BARS ARE LAPPED IN ANY ONE CROSS SECTION. WHERE BARS MUST LAPPED IN ONE CROSS SECTION, THEN LAP LENGTH SHALL NOT BE LESS THEN 1.30 TIMES MINIMUM LAP LENGTH.
15. REINFORCING BAR MUST BE SUPPORTED IN ITS PROPER POSITION BY USE OF MORTAR BLOCK, SUPPORTS OR BY OTHERS APPROVED MEANS.
16. SAND FILLING IN FOUNDATION SHOULD BE DONE WITH SAND OF $F_m \leq 1.50$ IN LAYERS OF 150 mm THICK LAYER BY LAYER AND COMPACTED TO ATTAIN MINIMUM 50% RELATIVE DENSITY.
17. UNLESS OTHERWISE SPECIFIED, BACK FILLING SHALL BE DONE WITH SAND ($F_m > 0.80$) FREE FROM VEGETABLE ROOTS AND ORGANIC MATTER, BACK FILLING FOR U-SHAPED WALL SHALL BE DONE SIMULTANEOUSLY ON BOTH WALLS.
18. DESIGN OF GATE AND HOISTING SYSTEM WILL BE PREPARED BY DESIGN CIRCLE-III, BWDB, DHAKA.
19. GATE TO BE OPERATED IN CONTROLLED WAY TO AVOID ANY SCOUR WHEN HEAD DIFFERENCE IS BEYOND 0.60m.
20. THE EMBEDDED PARTS OF GATE TO BE INSTALLED DURING CONSTRUCTION OF BARREL PART AND IT SHALL BE DONE IN ACCORDANCE WITH APPROVED MECHANICAL DRAWING.
21. THE GATE SHALL BE INSTALLED BEFORE THE OPERATION OF THE STRUCTURE.
22. ANY ERROR/OMISSION IF DETECTED SHALL BE REFERRED TO THE CONCERNED DESIGN OFFICE TAKING NECESSARY ACTION.
23. ALL BORE HOLES SHALL BE SEALED BEFORE CONSTRUCTION OF REGULATOR.

SPECIAL NOTES:

1. THIS DRAWING IS PREPARED AS PER PROPOSAL AND DESIGN DATA SUBMITTED BY SE, KHULNA O&M CIRCLE, BWDB, KHULNA VIDE HIS OFFICE MEMO NO: 761, DATE: 12-01-2022 AND ADDITIONAL DATA RECEIVED FROM EE, SATKHIRA O&M DIVISION-2 BWDB SATKHIRA TROUGH EMAIL ON 02-04-2022.
2. THE WORK SHALL BE EXECUTED WITH PRIOR ADMINISTRATIVE AND FINANCIAL APPROVAL FROM THE COMPETENT AUTHORITY & WITHIN THE DPP / BUDGET PROVISION .
3. EXISTING KHAL/LINK KHAL AT THE U/S & D/S OF THIS PROPOSED REGULATOR TO BE RE-EXCAVATED UPTO THE REQUIRED LENGTH AND LEVEL IF NECESSARY.

NOTES FOR SHEET PILES:

1. HOT ROLLED U-SHAPE STEEL SHEET PILE SHALL BE USED. COLD ROLLED SHEET PILE SHALL NEVER BE USED.
2. COATING SHALL BE PROVIDED OVER SHEET PILE IN THE FOLLOWING WAY :-
 - i) CLEAN THE SHEET PILE SURFACE PREFERABLY WITH SAND BLASTING.
 - ii) PROVIDE 1 (ONE) COAT OF ZINC PHOSPHATE AS PRIMARY COAT.
 - iii) PROVIDE 2 (TWO) COAT OF COAL TAR EPOXY COAT OVER PRIMARY COAT.
3. THICKNESS OF SHEET PILE SHALL BE 10.50mm (+0.50mm) (ITEM CODE: 44-240-10).
4. CONCERNED EXECUTIVE ENGINEER MUST ENSURE SHEET PILE INTERLOCKING, LENGTH, & DRIVING.
5. TOP LEVEL OF EVERY CONNECTED SHEET PILES MUST HAVE SAME LEVEL.

NOTES FOR EMBEDDED PARTS, GROOVE AND GATE:

1. ALL EMBEDDED PARTS OF GROOVE AND OTHERS WILL BE STAINLESS STEEL (SUS-304)
2. ALL PARTS OF MECHANICAL GATE WILL BE STAINLESS STEEL (SUS-304).

Bangladesh Water Development Board	
Office of the Superintending Engineer Design Circle-8	
DRAINAGE IMPROVEMENT OF POLDER 1,2-6-8 AND 6-8(EXTENSION)	
DESIGN OF DRAINAGE CUM FLUSHING REGULATOR 2-VENT(1.50mX1.80m) ON BAIBOSOT KHAL AT KM 13.00 IN POLDER NO-6-8(EXT) IN SATKHIRA DISTRICT, UNDER SATKHIRA O&M DIVISION-2, BWDB, SATKHIRA.	
NOTES	
DESIGNED BY :	APPROVED BY :
(ZAYED BIN SAIF, AE	
CHECKED & RECOMMENDED BY :	
(JAKARIA PERVEZ), EE	(MOHAMMAD SAIF UDDIN), SE
DATE:	DWG. NO.:DC-8-0000-04/21