

GEOTECHNICAL DESIGN OF DRIVEN PILES UNDER AXIAL LOADS

Sakib Bin Rafi Tonmoy, Jakaria Pervez

05/04/2023

1 Settlement of Piled-Raft System with floating piles

If concrete columns are not end bearing, the settlement may become an issue. The settlement of concrete column-reinforced soft foundations can be estimated using the method for piled rafts or pile groups. Horikoshi and Randolph (1999) and Poulos (2001) proposed simplified design methods to calculate the settlement of piled rafts, which are based on pile-raft interaction.




Figure 1: Equivalent Pier

Randolph (1999) used the equivalent pier concept for the piled raft method

as shown in 1.Independent parameters that are required known before calculation are as follows:

Material Properties :

E_c = modulus of Elasticity for pile materials in Mpa

E_s = modulus of Elasticity for soil in Mpa

ν = Poisson's ratio for soil

G_L = shear modulus of the soil at the base of columns MPa

G_b = shear modulus of the soil below the base of columns Mpa

G_{avg} = average shear modulus of the soil within the length of columns Mpa

column Properties :

N_{cl} = Number of columns

s = spacings of column in meter

L_c = *Length of column in meter*

r_c = radius of pile

A_{ci} = Area of ith column in meter

Raft Properties

A_r = Width or Diameter of the raft

B_r = Width or Diameter of the raft

I_s = Influence Factor 0.88 for square raft or 0.79 for circular raft

2 Calculation Steps

Step1:Calcualte Shear Modulus of Soil

G_L = shear modulus of the soil at the base of columns MPa

G_b = shear modulus of the soil below the base of columns Mpa

$$G = \frac{E}{2(1 + \nu)}$$

$$G_{avg} = \frac{G_L + G_b}{2}$$

$$\zeta = \frac{G_L}{G_b}$$

$$\rho = \frac{G_{avg}}{G_L}$$