



Existing Bed Level in (mPWD)	
7.000	3.893
8.000	3.203
9.000	2.573
11.000	1.843
12.000	0.881
13.500	0.341
15.000	(-)0.249
16.000	(-)0.679
17.000	(-)1.579
18.000	(-)2.579
20.000	(-)3.429
23.000	(-)4.529
26.000	(-)6.049
30.000	(-)7.829
32.000	(-)8.679
34.000	(-)9.429
40.000	(-)10.529
50.000	(-)11.629
55.000	(-)12.379
60.000	(-)13.529
65.000	(-)13.779
70.000	(-)14.429
75.000	(-)13.479
80.000	(-)13.729
85.000	(-)12.429

TYPICAL CROSS SECTION AT KM 0.080
(APPLICABLE FROM KM 0.070 TO KM 0.190)

Bangladesh Water Development Board			
Office of The Superintending Engineer, Design Circle-8			
Protection of Morrelganj Upazila Sadar and adjacent areas from erosion Pangusi river in Bagerhat District and Re-excavation/Dredging of Bishkhali river			
River Bank Protective Work From Sannashi to Khawlia From km 0.000 to km 4.500 = 4.500 km			
TYPICAL CROSS SECTION OF PROTECTIVE WORK FROM SANNAASHI TO KHAWLIA			
DESIGNED BY:	RECOMMENDED BY:		
(ZAYED BIN SAIF),AE	(MOHAMMAD SAIF UDDIN),SE		
CHECKED BY:	APPROVED BY:		
(JAKARIA PERVEZ),EE	(MD. ENAYET ULLAH),CE,DESIGN		
DATE:06-06-2021	Drawing No:DC-8-0073-06/09		