- KHULNA VIDE MEMO NO: 293, DATED-24/08/2022. 1. THIS DRAWING HAS BEEN PREPARED BASED ON DATA SENT BY THE SUPERINTENDING ENGINEER, KHULNA O & M CIRCLE, BWDB,
- 2. FOR ANY ERROR, OMISSION OR CONFUSION PLEASE REFER TO THIS OFFICE AS QUICK AS POSSIBLE FOR NECESSARY ACTION.
- 3. THE WORK SHALL BE EXECUTED WITH PRIOR FINANCIAL & ADMINISTRATIVE APPROVAL AND TECHNICAL SANCTION FROM THE
- 4. ALL DIMENSIONS ARE IN MILLIMETRE (mm) AND ALL ELEVATIONS ARE IN METRE (PWD) UNLESS OTHERWISE MENTIONED IN THE
- 5. THE MATERIAL & WORKMANSHIP SHALL CONFORM TO THE STANDARD SPECIFICATIONS OF BWDB MANUAL
- 6. NECESSARY LAND SHALL BE ARRANGED BEFORE EXECUTION OF WORK.
- 7. THE GEO-TEXTILE FILTER HAVE THICKNESS OF 3.00 mm.
- THE TOP OF THE SLOPE AS SHOWN IN THE DRAWING. 8. GEO-TEXTILE FILTER SHALL BE EXTENDED UPTO 1000 mm BELOW THE W.W.L/TOE & SHALL HAVE TO BE ANCHORED CAREFULLY AT
- 9. GEO-TEXTILE MATERIALS SHALL BE PRESERVED AGAINST UV RAY AND FROM ANY OTHER DAMAGES
- IMMEDIATELY AFTER PLACEMENT. 10. GEO-TEXTILE MATERIALS AFTER PLACING SHALL NEVER BE EXPOSED TO SUNLIGHT. GEO-TEXTILE FILTER SHALL BE COVERED
- 12. FULL LENGTH OF PROPOSED PROTECTIVE WORK SHALL BE DONE AT A TIME IN ONE DRY SEASON FOR EFFECTIVENESS
- G.L WITH LOCAL EARTH AND SHALL BE COMPACTED AS PER SCHEDULE BEFORE STARTING THE PROTECTIVE WORK. 13. IF THERE ARE ANY POND OR DITCH EXISTS WITHIN 100 m DISTANCE FROM THE RIVER BANK, IT MUST BE PROPERLY FILLED UPTO
- FILLING SHALL BE DONE IN THIS RESPECT AS PER FIELD REQUIREMENT. STEEPER THAN 2H:1V. ALL BANK IRREGULARITIES ABOVE WORKING WATER LEVEL SHALL BE REMOVED. NECESSARY CUTTING & 14. SLOPE OF PITCHING WORK SHALL BE MAINTAINED AS PER EXISTING SLOPE OR AS PER Rehabilitation SECTION, BUT NOT
- PROTECTIVE WORK. TOP LEVEL OF PITCHING WORK SHOULD BE MATCH WITH EXISTING BANK LEVEL 15. A SMOOTH TRANSITION TO BE PROVIDED BETWEEN HIGHER & LOWER LEVEL AND FLATTER & STEEPER SLOPE OF THE
- PREVIOUSLY COMPLETED WORK MUST BE GRADUAL AND TANGENTIAL. 16. AT THE STARTING AND AT THE END OF THE PROTECTIVE WORK TRANSITION TO THE EXISTING UNPROTECTED BANK OR THE

NOTES FOR C.C BLOCKS:.

- CONCRETE FOR C.C BLOCK SHALL HAVE MINIMUM CYLINDER STRENGTH OF 15.00N/mm2 AT 28 DAYS.
- 2. CURING OF C.C BLOCKS SHALL BE CONTINUED FOR 21 DAYS
- 3. THE PITCHING WORK SHALL BE PLACED ON PROPERLY COMPACTED SLOPE.
- 1. EACH BAG DELIVERED AT SITE SHALL BE MARKED WITH LABELS THAT IDENTIFY BRAND NAME, CONTRACT PACKAGE NO, SIZE OF BAG, ATE OF PRODUCTION OF GEOTEXTILE, NAME OF CONTRACTOR ETC.
- 2. SEWING SHALL BE DONE BY MACHINE WITH LOCK STITCH (TYPE 301 UNDER ISO 4915/DIN61400) OR DOUBLE CHAIN STITCH (TYPE 401 UNDER ISO 4915/DIN61400) AS PER BWDB TECHNICAL SPECIFICATION AND TENDER DOCUMENT. THREAD FOR STITCHING SHOULD BE 100% POLYPROPYLENE OR NYLON.
- 3. FILLING MATERIAL OF GEOBAG SHOULD BE SAND AND 80% SHOULD RETAIN ON #100 SEIVE. SAND SHOULD BE FREE FROM CLAY & ORGANIC MATTER.
- 4. MATERIAL OF GEOBAG SHALL BE 100% POLYPROPYLENE.
- DONE (AS PER ACTUAL NEED). SPECIFICATIONS OF GEOTEXTILE SHALL BE AS PER ITEM CODE 40-500-40. 5. SIEVE ANALYSIS FOR CHECKING 80% RETAINED ON #100 SIEVE AND TEST FOR CLAY & ORGANIC MATTER CONTENT SHOULD BE
- 1. WORK SHALL BE EXECUTED ONLY WHEN WL IS AT OR NEAR WORKING L.W.L AS SHOWN IN THE DRAWING
- AT SITE BEFORE START OF DUMPING. 2. 2. SURVEY BOAT EQUIPPED WITH NECESSARY DUMPING EQUIPMENT, SURVEY EQUIPMENT & SURVEY TEAM SHOULD BE ENSURED
- 3. 3. DUMPING MATERIALS SHALL BE DUMPED FROM BARGE EQUIPPED WITH GUIDED FENCE SO THAT DUMPING MATERIALS CAN BE DUMPED INTO PROPER POSITION

Bangladesh Water Development Board Office of The Superintending Enginner, Design Circle-8 rotection of Morrelganj Upazila Sadar and adjacent areas from erosior Pangusi river in Bagerhat District and Re-excavation/Dredging of Bishkhali river

River Bank Protective Work From Sannashi to Khawlia From km 0.000 to km 4.500 = 4.500 km

DATE:06-06-2021	(JAKARIA PERVEZ),EE	CHECKED BY:	(ZAYED BIN SAIF),AE	DESIGNED BY:	
Drawing No:DC-8-0073-02/09	(MD. ENAYET ULLAH),CE,DESIGN	APPROVED BY:	(MOHAMMAD SAIF UDDIN),SE	RECOMMENDED BY:	NOTES