

Aprimo DAM REST API documentation

Topics

- [Getting started](#)
 - [REST API configuration](#)
 - [Navigating the API](#)
 - [Current version](#)
 - [Media types](#)
- [Tutorials & examples](#)
 - [Examples](#)
 - [Working with records](#)
 - [Working with record locks](#)
 - [Working with files](#)
 - [Working with file versions](#)
 - [Working with file previews](#)
 - [Working with download links](#)
 - [Working with collections](#)
 - [Working with content subscriptions](#)
 - [Working with classifications](#)
 - [Working with content types](#)
 - [Working with field definitions](#)
 - [Working with field groups](#)
 - [Working with orders](#)
 - [Working with maintenance jobs](#)
 - [Working with permissions](#)
 - [Working with rules](#)
 - [Working with setting definitions](#)
 - [Working with settings](#)
 - [Working with setting categories](#)
 - [Working with file types](#)
 - [Working with translations](#)
 - [Working with public links](#)
 - [Working with audit trail](#)
 - [Searching](#)
 - [Synonyms](#)
- [Basic concepts](#)
 - [Selecting](#)
 - [Sub-resources](#)
 - [Attributes](#)
 - [Explicit fields selection](#)
 - [Default values in field selection](#)
 - [Advanced selecting and preventing recursion](#)
 - [Embedding/following relations that result in missing data](#)
 - [Filtering](#)
 - [Sorting](#)
 - [Paging](#)
 - [Relations](#)
 - [Localization](#)
 - [Exception handling](#)
 - [Downloading files](#)
- [Usage](#)
 - [Authentication](#)
 - [Bearer authentication](#)
 - [Endpoint header requirements](#)
 - [Editing resources](#)
 - [Uploading files](#)
 - [Filename restrictions](#)
 - [Uploading files below 20 MB](#)
 - [Uploading files above 20 MB - in segments](#)
 - [Uploading files directly to the blob storage](#)
 - [Cleaning the uploads](#)
 - [Advanced searching](#)
 - [Search expression parameters](#)
 - [Facets](#)
 - [Suggestions](#)
 - [Statistics](#)
 - [Toggling statistics gathering](#)
 - [Retrieving statistics](#)

- [Clearing statistics](#)
- [System Administration](#)
 - [Enterprise Search](#)
- [Log message Event IDs](#)
- [Resources](#)

Introduction

The Assets API allows you to interact with our system programmatically from your own application. Using the API you interact with Resources such as:

- Record
- Classification, RecordClassification
- Field, FieldDefinition
- File, FileVersion, FilePreview, AdditionalFile
- Image, Watermark
- Language
- MaintenanceJob
- etc.

The API follows some aspects of hypermedia-driven web APIs, like using linked/embedded resources in the returned resource representation. Each resource can be accessed directly through its URI but it can also be accessed as an embedded sub-resource in its parent resource, like collection resource for example.

To read a resource, a standard HTTP GET request is used. The request can include some optional parameters which allow you to control how much of the information should be included/excluded in the returned resource, depending on how much information is needed.

To update a resource, a standard HTTP PUT request is used. Here, you can also specify the amount of data to be changed in the resource by not specifying in your request those resource properties which you don't want to change. Only the values of resource properties, which are specified in your request, are changed/updated.

To create a new resource, a standard HTTP POST request is performed on the appropriate collection of such resources. For example, if you would like to create a new record, you would perform an HTTP POST request on a record collection. If you don't specify some of the optional resource properties in your request, the default values will be used.

To delete a resource, a standard HTTP DELETE request is used. Based on your access rights, you might be denied the request to delete a resource.

If you want to know more about how to find your way around the API, see [Navigating the API \(#gettingstarted_navigation\)](#)

Getting started

REST API configuration

After deployment of the Aprimo DAM REST API, you should also configure the Aprimo DAM structures that are used by the REST API.

This configuration will, among other things, create a `.rest_SettingsWhitelist` system setting. If you want to work with Aprimo DAM settings via the REST API, this setting should be provisioned by an Aprimo DAM administrator, as described in [the setting resource documentation \(resources/setting.html\)](#). However, the whitelist does not affect users from the Aprimo DAM Administrator and Operator user groups: they have access to all their Aprimo DAM settings, irrespective of the whitelist.

To do the configuration:

1. [Authenticate \(#usage_authentication\)](#), using the credentials of an Aprimo DAM administrator account on the Aprimo DAM registration that you want to initialize, and use the [token \(#usage_authentication_token\)](#) to connect to the setup endpoint.
2. Perform an HTTP POST request on the `/setup` endpoint. This POST request should have an empty body.

Note: If you have more than one Aprimo DAM registration, you have to repeat this request for each of the Aprimo DAM registrations.

```
POST /setup HTTP/1.1
Authorization: Token Y2ZkZDdjZTc2NDdmNDBlOWE5NDI2ZDhjNjY2MDRhMTU6QURBTU5FVA==
API-VERSION: 1
```

The command above will upgrade your REST API system structures to the up-to-date state. However, such upgrade depends on other components of the system and previous upgrades. You may face a situation when configuration call passes successfully, but there is still an issue e.g. when uploading files. If you see such issues, these are the possible actions to fix them:

1. First, try rebuilding an Enterprise Search index and/or ensure synchronization is started. Consult Aprimo DAM Administrator Guide or [Enterprise Search Administration \(#usage_sa_searchindex\)](#) on how to do this.
2. If step 1 doesn't solve the issue, you can try to repair your REST API structures by performing a forced configuration call. It differs from regular configuration call by an added request body containing a `forceRebuild` flag. Of course, you should also add the `content-type` header.

Note: this form of configuration request is an emergency action that is not normally needed. All the missing items needed by REST API will be recreated. This means that as the result of this command you may get useless objects in your system if you previously renamed them manually.

```
POST /setup HTTP/1.1
Authorization: Token Y2ZkZDdjZTc2NDdmNDBlOWE5NDI2ZDhjNjY2MDRhMTU6QURBTU5FVA==
API-VERSION: 1
Content-Type: application/json
{ "forceRebuild": true }
```

Navigating the API

The Aprimo DAM REST API supports two different ways of consuming and navigating the API:

HAL/JSON hypermedia

Once a resource is retrieved, your client can bookmark the URI in its cache. The existing relation names will not change over time, but new relations can be introduced.

Links in the returned resource representation help you to navigate the API, just by following those links. Using this approach helps create API clients/servers that do not depend too much on each other and can be developed in an independent way, as long as both the client and the server have a common understanding of media types used in the communication. For example, you can start using the API by going to the root URI of the API and discover all the resources you can access. From that point on, you can follow links and explore the resources existing throughout the API. You can use the "select" keys, present in most of the resources, which provide you with information about which sub-resources can be embedded in that resource. This way you can retrieve the exact information needed in a single request, which helps you optimize the chattiness of the API for your specific use case.

Plain JSON consumption

Next to using the HAL/JSON hypermedia API, clients can also consume the API using plain JSON. This is a simpler but less robust approach, since it lacks discoverability and requires upfront knowledge of the URI's for all the endpoints that the client will need. For pure JSON clients, we provide an exhaustive [list of the endpoints \(endpoints.html\)](#) available in the API.

Current version

A required request header parameter, which specifies which version of the API the request will refer to:

```
API-Version: 1
```

There are some exceptions to this requirement, like the root resource and the "supported versions" resource. These resources are version-agnostic, meaning they will always display the same result, no matter which "API-Version" parameter has been specified (if any). Also, they will never change what exists, but can add new information to ensure backwards-compatibility. The reason for this exception is a requirement to provide consumers with a way to discover the list of existing and supported API versions before they start using it. If these resources were also version-aware, consumers wouldn't have a way to discover the proper values that can be specified in the "API-Version" parameter.

For the complete list of exceptions, refer to the [Endpoint header requirements \(#usage_endpointheaders\)](#) section.

Media types

The Aprimo DAM REST API supports the following media types:

- Response media types:
 - `application/hal+json` (default)
 - `application/json`
- Request media types:
 - `application/json` (default)

Tutorials & examples

Examples

The following examples show you how you can use the Aprimo DAM REST API to perform common tasks in Aprimo DAM.

- Working with records
 - [Reading a record \(resources/record.html#example-read\)](#)
 - [Reading a record using a unique identifier field \(resources/record.html#example-Read-using-unique-identifier-field\)](#)
 - [Reading a record using a file id \(resources/record.html#example-Read-using-file-id\)](#)
 - [Immediate propagation for record updates \(resources/record.html#example-records-direct-push\)](#)
 - [Creating a new record \(resources/recordpagedcollection.html#example-create\)](#)
 - [Editing a record \(resources/record.html#example-edit\)](#)
 - [Deleting a record \(resources/record.html#example-delete\)](#)
 - [Reading locks using a unique record id \(resources/recordlock.html#example-read-locks-for-a-record\)](#)
 - [Uploading files \(index.html#usage_uploading\)](#)
- Working with record locks
 - [Reading locks using a unique record id \(resources/recordlock.html#example-read-locks-for-a-record\)](#)
 - [Creating a new lock for a record \(resources/recordlock.html#example-add-a-lock\)](#)
- Working with files
 - [Adding or updating a record's file \(resources/file.html#example-uploading-a-file\)](#)
 - [Checking a file out and back in \(resources/file.html#example-checking-out-a-file\)](#)

- [Undoing a file check-out](#) (resources/file.html#example-undoing-a-file-check-out)
- [Applying a watermark](#) (resources/file.html#example-applying-watermark)
- Working with file versions
 - [Adding or updating a file version](#) (resources/fileversion.html#example-add-edit)
 - [Setting publication items](#) (resources/fileversion.html#publication-item)
 - [Applying a watermark](#) (resources/fileversion.html#example-applying-watermark)
- Working with file previews
 - [Uploading a file preview](#) (resources/filepreview.html#example-uploading-a-file-preview)
 - [Adding or updating a file preview](#) (resources/filepreview.html#example-using-a-file-preview)
- Working with download links
 - [Searching for download links](#) (resources/downloadlinkpagedcollection.html#example-search)
 - [Reading a download link](#) (resources/downloadlink.html#example-read)
- Working with collections
 - [Searching for collections](#) (resources/collectionpagedcollection.html#example-search)
 - [Creating a new collection](#) (resources/collectionpagedcollection.html#example-create)
 - [Reading a collection](#) (resources/collection.html#example-read)
 - [Editing a collection](#) (resources/collection.html#example-edit)
 - [Deleting a collection](#) (resources/collection.html#example-delete)
 - [Reading collection permissions](#) (resources/collection.html#example-readpermissions)
 - [Editing collection permissions](#) (resources/collection.html#example-editpermissions)
 - [Reading collection's records](#) (resources/collection.html#example-readrecords)
 - [Editing collection's records](#) (resources/collection.html#example-editrecords)
- Working with content subscriptions
 - [Working with Content Subscriptions](#) (resources/contentsubscriptions.html)
- Working with classifications
 - [Reading a classification using a name path](#) (resources/classification.html#example-read-using-name-path)
 - [Reading a classification using unique identifier](#) (resources/classification.html#example-read-using-identifier)
 - [Immediate propagation for classification updates](#) (resources/classification.html#example-classifications-direct-push)
 - [Creating a new classification](#) (resources/classificationpagedcollection.html#example-create)
 - [Editing a classification](#) (resources/classification.html#example-edit)
 - [Deleting a classification](#) (resources/classification.html#example-delete)
 - [Editing of classification permissions](#) (resources/classification.html#example-classificationpermissions)
 - [Setting the follower classifications](#) (resources/classification.html#example-followerclassifications)
 - [Reading a user's classification tree permissions](#) (resources/classification.html#example-classificationtreepermissionread)
- Working with content types
 - [Reading a content type](#) (resources/contenttype.html#example-read)
 - [Creating a new content type](#) (resources/contenttypepagedcollection.html#example-create)
 - [Editing a content type](#) (resources/contenttype.html#example-edit)
 - [Deleting a content type](#) (resources/contenttype.html#example-delete)
- Working with field definitions
 - [Creating a new field definition](#) (resources/fielddefinitionpagedcollection.html#example-create)
 - [Editing a field definition](#) (resources/fielddefinition.html#example-edit)
 - [Deleting a field definition](#) (resources/fielddefinition.html#example-delete)
- Working with field groups
 - [Searching for field groups](#) (resources/fieldgrouppagedcollection.html#example-search)
 - [Creating a new field group](#) (resources/fieldgrouppagedcollection.html#example-create)
 - [Editing a field group](#) (resources/fieldgroup.html#example-edit)
 - [Deleting a field group](#) (resources/fieldgroup.html#example-delete)
- Working with orders
 - [Creating a new order](#) (resources/ordercollection.html#example-add)
 - [Creating a download order to get a link to the original file](#) (resources/ordercollection.html#example-original-file)
 - [Creating a download order without preliminary checks](#) (resources/ordercollection.html#mass-download-order)
 - [Creating a new email order](#) (resources/ordercollection.html#example-email-order)
 - [Creating a new FTP resort order](#) (resources/ordercollection.html#example-ftp-resort-order)
 - [Creating a new public CDN order](#) (resources/ordercollection.html#example-public-cdn-order)
 - [Following up on an order](#) (resources/ordercollection.html#example-follow-up)
- Working with maintenance jobs

- [Creating a new maintenance job](#) (resources/maintenancejobpagedcollection.html#example-create)
- [Reading a maintenance job](#) (resources/maintenancejob.html#example-read)
- Working with permissions
 - [Searching for permissions](#) (resources/permissionpagedcollection.html#example-search)
 - [Searching for the permissions of a user](#) (resources/permissioncollection.html#example-example-search)
 - [Searching for the permissions of a user group](#) (resources/permissioncollection.html#example-example-search)
 - [Editing a permission](#) (resources/permission.html#example-edit)
 - [Editing the permissions of a user](#) (resources/permissioncollection.html#example-edit)
 - [Editing the permissions of a user group](#) (resources/permissioncollection.html#example-edit)
 - [Reading a calculated permission](#) (resources/calculatedpermission.html#example-read)
- Working with rules
 - [Searching for rules](#) (resources/rulepagedcollection.html#example-example-search)
 - [Creating a new rule](#) (resources/rulepagedcollection.html#example-create)
 - [Reading a rule](#) (resources/rule.html#example-example-search)
 - [Editing a rule](#) (resources/rule.html#example-edit)
 - [Deleting a rule](#) (resources/rule.html#example-delete)
- Working with setting definitions
 - [Searching for setting definitions](#) (resources/settingdefinitionpagedcollection.html#example-search)
 - [Creating a setting definition](#) (resources/settingdefinitionpagedcollection.html#example-create)
 - [Editing a setting definition](#) (resources/settingdefinition.html#example-edit)
 - [Deleting a setting definition](#) (resources/settingdefinition.html#example-delete)
- Working with settings
 - [Reading a setting](#) (resources/setting.html#example-read)
 - [Setting a setting value](#) (resources/setting.html#example-edit)
 - [Getting multiple settings](#) (resources/settingcollection.html#example-list)
- Working with setting categories
 - [Searching for setting categories](#) (resources/settingcategorypagedcollection.html#example-search)
 - [Creating a setting category](#) (resources/settingcategorypagedcollection.html#example-create)
 - [Editing a setting category](#) (resources/settingcategory.html#example-edit)
 - [Deleting a setting category](#) (resources/settingcategory.html#example-delete)
- Working with file types
 - [Searching for file types](#) (resources/filetypepagedcollection.html#example-search)
 - [Creating a new file type](#) (resources/filetypepagedcollection.html#example-create)
 - [Reading a file type](#) (resources/filetype.html#example-read)
 - [Editing a file type](#) (resources/filetype.html#example-edit)
 - [Deleting a file type](#) (resources/filetype.html#example-delete)
- Working with translations
 - [Searching for translations](#) (resources/translationpagedcollection.html#example-search)
 - [Creating a new translation](#) (resources/translationpagedcollection.html#example-create)
 - [Reading a translation](#) (resources/translation.html#example-read)
 - [Reading a translation using a key](#) (resources/translation.html#example-read-using-key)
 - [Editing a translation](#) (resources/translation.html#example-edit)
 - [Deleting a translation](#) (resources/translation.html#example-delete)
- Working with public links
 - [Creating a bring-your-own-CDN public link](#) (resources/publiclink.html#example-create)
 - [Editing existing public link](#) (resources/publiclink.html#example-edit)
 - [Reading a public link](#) (resources/publiclink.html#example-read)
 - [Delete a public link](#) (resources/publiclink.html#example-delete)
 - [Filtering public links](#) (resources/publiclink.html#example-read-filter)
- Working with audit trail
 - [Reading the audit trail of a record](#) (resources/auditentry.html#example-read)
 - [Reading the list of changes of an audit trail event](#) (resources/auditentryid.html#example-read)
- Searching
 - [Searching for records](#) (resources/recordpagedcollection.html#example-search)
 - [Searching for classifications](#) (resources/classificationpagedcollection.html#example-search)
 - [Searching for languages](#) (resources/languagepagedcollection.html#example-search)
 - [Searching for field definitions](#) (resources/fielddefinitionpagedcollection.html#example-search)
 - [Advanced searching for records and classifications](#) (#usage_searching)

- **Synonyms**
 - [Exporting synonyms](#) (resources/language.html#example-export)
 - [Importing synonyms](#) (resources/language.html#example-import)

Basic concepts

Selecting

The selecting feature is used in the Aprimo DAM REST API to support the dynamic nature of the Aprimo DAM resources and to provide the API consumers with a way to select a custom granularity level for the resource representation they want to retrieve from Aprimo DAM. It helps consumers retrieve more information using a single request.

By default, when a resource is requested, it is usually returned using a minimal representation, which contains as little data as possible (for example, all of the sub-resources of the requested resource are not returned in this minimal representation). If needed, a consumer can extend this resource representation by selecting more data to be included, using the "select" header parameter.

The general format of the select parameter is: `"Select-{Resource}: SubResource1,SubResource2,SubResource3, ..."` where the value is a comma-separated list of subresources to be included in the resulting resource representation. It specifies that the returned resource's representation also contain its subresources, beside the basic/minimal data, which is always returned. For example, to request a list of records, with their classifications and files included with each returned record resource, a consumer typically performs a request like this:

```
GET /records HTTP/1.1
accept: application/hal+json
select-record: classifications, files
```

It is also possible to further select the sub-resource's additional attributes in the same request. For example, if a consumer likes to select the children for each classification returned with each record, it is done in this way:

```
GET /records HTTP/1.1
accept: application/hal+json
select-record: classifications, files
select-classification: children
```

The returned records collection resource contains records, each of which has the embedded files collection resource and the classifications collection resource with each classification's children collection embedded in the classification resource. All of this has been accomplished in a single request.

There is a possible recursion issue in this particular case, since the "children" sub-resource is also a collection of classifications, each of which can have "children" as a sub-resource, too, which could lead to an unexpected data overflow. To avoid this, a [limit \(#concepts_selecting_advanced\)](#) was introduced to return only the first level of recursive sub-resources.

Sub-resources

In case sub-resources are returned as linked resources of another parent resource, all of those sub-resources will have an additional attribute named "select-key". This parameter indicates that the sub-resource can be selected (embedded) in the parent resource representation. The value of the "select-key" parameter can be used as a value of the "select-<parent-resource>" parameter. For example, to get a record:

```
GET /record/250d22a231ed4f0ba9afa49900b0252e HTTP/1.1
accept: application/hal+json
```

We can see there are numerous linked resources available for that record, which can be selected (embedded) in the returned record representation, using the specified "select-key" parameter:

```
{
  "_links": {
    "self": {
      "href": "/record/250d22a231ed4f0ba9afa49900b0252e"
    },
    "fields": {
      "href": "/record/250d22a231ed4f0ba9afa49900b0252e/fields",
      "select-key": "fields"
    },
    "files": {
      "href": "/record/250d22a231ed4f0ba9afa49900b0252e/files",
      "select-key": "files"
    },
    ...
  },
  "id": "250d22a231ed4f0ba9afa49900b0252e",
  "createdOn": "2015-05-15T10:41:19.51Z",
  "modifiedOn": "2015-06-12T11:13:15.433Z",
```



```
"tag": null
}
```

To request a record resource, with, for example, all the fields selected, look at the "fields" linked resource for the " `select-key`" parameter with the value " `fields`". This value means that you can include this sub-resource within the record resource just by specifying: " `select-record: fields`", when requesting the record next time, like this:

```
GET /record/250d22a231ed4f0ba9afa49900b0252e HTTP/1.1
accept: application/hal+json
select-record: fields
```

This time you will get the fields embedded within the record resource instead of just returning a linked resource. This way you can dynamically change the amount of information returned for the same resource requested.

For a more detailed example, see: [Reading a record](#) (resources/record.html#example-read)

Attributes

Next to the sub-resources, some resource attributes can also be selected (included or excluded from the requested resource representation). If not selected, these attributes will NOT be returned by default. This will be clearly indicated in the description of the property on the resource page.

The listed attributes were either rarely used or the calculation of their value was too expensive to be included in the default representation of a resource, consequently, it was decided to hide these attributes unless a consumer specifically selects them.

Explicit fields selection

When selecting the fields of a record, classification, user or file, it can be useful to select only certain fields, instead of having them all included in the returned resource. For example, to select fields of a record:

```
GET /record/250d22a231ed4f0ba9afa49900b0252e HTTP/1.1
accept: application/hal+json
select-record: fields
```

This selects all the fields on that record. To filter out specific fields (or field groups), you can use additional header parameters that provide such filtering, like " `select-record-fields`" and " `select-record-fieldgroups`". The value for these parameters is a comma-separated list of fields/fieldgroups. Fields and field groups can be specified using their Ids (in the form of a GUID) or their names. Since the field/fieldgroup names can contain random text, it is advised to properly encode them using the "[Percent-Encoding](https://tools.ietf.org/html/rfc3986#section-2.1)" (<https://tools.ietf.org/html/rfc3986#section-2.1>) so that they can safely pass over the network to the API server. Also take into account that the "comma" character needs to be escaped because it has a special meaning in the HTTP header values. This is an example of the selected fields' filtering feature:

```
GET /record/250d22a231ed4f0ba9afa49900b0252e HTTP/1.1
accept: application/hal+json
select-record: fields
select-record-fields: 295B1779-A381-4018-BE1D-B29E3458B41C, MyField, DummyField
select-record-fieldgroups: TestFieldGroup, CDE8E0C4-CD7E-47BC-93D3-0F54C7109FB6, FooBarGroup
```

In the previous example there was no need to use the percent-encoding, but let's consider an example where escaping is required. The field " `My,Field,With,Commas`" contains a "comma" character in its name. To escape it properly, because in HTTP the header values represent the list of comma-separated values, and to avoid selecting fields with these names: `My`", " `Field`", " `With`" and " `Commas`", you need to percent-encode the field name so that the request reads as follows:

```
GET /record/250d22a231ed4f0ba9afa49900b0252e HTTP/1.1
accept: application/hal+json
select-record: fields
select-record-fields: My%2CField%2CWith%2CCommas
```

This request will result in one field only, named " `My,Field,With,Commas`".

Default values in field selection

You can choose receive default values in your result set by adding an additional header parameter named **select-resolve-default-values**. The value for this parameter must either contain `true` or `false`. Empty values and spaces will be ignored. True will return default values and false will omit default values. If this parameter is omitted, you will receive default values in your selected fields.

```
GET /record/250d22a231ed4f0ba9afa49900b0252e HTTP/1.1
accept: application/hal+json
select-record: fields
select-record-fields: 295B1779-A381-4018-BE1D-B29E3458B41C, MyField, DummyField
select-record-fieldgroups: TestFieldGroup, CDE8E0C4-CD7E-47BC-93D3-0F54C7109FB6, FooBarGroup
select-resolve-default-values: false
```

Advanced selecting and preventing recursion

The REST API will intelligently decide on whether or not to select a resource. Selecting is done based on the resource type. However, the number of times a resource is selected, is limited to prevent recursion. Without that limitation, querying for instance a user with "Select-User: CreatedBy" can lead to a recursive embedding loop where the selection is endlessly re-applied to the embedded resource.

To remedy this, the API will preform selections in such a way that any resource type cannot occur more than two times in the path leading from the topmost resource to the leaves. For instance:

```
GET /user/{id} HTTP/1.1
select-user: createdby
```

will return the `user`, and embed the `createdby`. The `select-user: createdby` will no longer be applied to the embedded `createdby` user, even though this too is a user resource. Similarly:

```
GET /classification/{id} HTTP/1.1
select-classification: parent, children
```

will return the specified classification, and embed its parents and children. However, the children of the parent and the parent of the children will not be embedded. This also applies to deeper levels of nesting:

```
GET /user/{id} HTTP/1.1
select-user: fields
select-field: definition
select-fielddefinition: createdby
```

will return the following 'tree' of embedded resources:

```
user
  .field
    .definition
      .createdby
  .field
    .definition
      .createdby
```

After the second occurrence of the `createdby` the embedding will stop, because the API will detect that `createdby` is of type user, which also appears higher up in the embedding tree.

Embedding/following relations that result in missing data

When a relation points to either of the following:

- an image with `HasImage=false`
- a `null` value, e.g. when a record's MasterFile has no files
- an `obsolete value`, e.g. CreatedBy/ModifiedBy that points to a user who was removed from the database

Then clicking that type of link will have the API by default return a `404 NotFound` error containing a meaningful error message. Selecting that type of link will by default have the `propertyname: null` embedded in the output.

Filtering

A filter expression can be passed in the request with the `filter` parameter. It can be specified as a query string or a header parameter. The parameter is only taken into account on collections of resources.

A filter expression is a single-line Aprimo DAM search expression without parameters or any additional options. See [simple search examples \(#examples_searching\)](#) for more details.

Warning: Searching for records/classifications using a search expression is done in 2 steps: first ElasticSearch is queried to get a list of matching IDs, then those IDs are used to query the Aprimo DAM database.

If any of the search results is deleted between step 1 and 2, the TotalCount value will be out of sync with the real count of search results.

Sorting

A sort expression can be passed in the request with the `sort` parameter. It can be specified in the query string or as a header. The parameter is only taken into account on collections of resources. See [simple search examples \(#examples_searching\)](#) for more details.

Paging

Although there are pre-built pagination links via relations such as: "`first`", "`prev`", "`next`" and "`last`", you can also control the page number and the number of items per page if you provide the "`page`" and/or "`pageSize`" parameters. These parameters can be passed as a query string or header parameters. For performance reasons, the "`pageSize`" parameter has a limit of 1000. When omitted, it defaults to 50. See [simple search examples \(#examples_searching\)](#) for more details.

Newer or more recently updated routes preferentially support Skip and Take pagination and may not support page and pagesize. `skip` - bypass a specified number of search results then return the remaining results of this paged collection (int32). `take` - specify the number of search results to return in this paged collection (int32)

Relations

The following registered relations are used: " `self`", " `first`", " `prev`", " `next`" and " `last`" (as specified in the [Web Linking RFC \(http://www.iana.org/assignments/link-relations/link-relations.xhtml\)](http://www.iana.org/assignments/link-relations/link-relations.xhtml)). Other custom relations are added per resource to allow intuitive navigation of the Rest API.

Note that not all entities, which are exposed as resources through the Rest API, are returned as relations if referenced by another entity. For small and static collections, such as languages, the client application should fetch and cache the list of resources at startup and then map the Ids to resources on the client-side. These resources are not returned as relations but as plain GUIDs.

Localization

Fields and labels can be requested in specific languages using the `languages` header parameter. This parameter can be a single language Id, a comma-separated list of language IDs or an asterisk ("*") that represents all languages. If omitted, this parameter will return the current user's default language.

Exception handling

When unexpected exceptions occur, the Aprimo DAM REST API will feed this back to the API consumer via an HTTP error response containing an exception object as body. The HTTP response code will correspond to the type of exception that occurred:

- HTTP 4xx response codes indicate specific error conditions (validation errors, malformed requests, access denied, resource not available...)
- HTTP 500 internal server error is returned for all other exceptions

The error object returned can contain the following properties:

Property	Description
<code>exceptionMessage</code>	A description of what went wrong. Depending on the exception this can be a technical or a more user-friendly message.
<code>exceptionType</code>	The full type name of the exception. This can be used in automatic error handling or to reinstantiate the exception on the client.
<code>stackTrace</code>	Can contain the full stack trace of the exception for debugging purposes.
<code>innerException</code>	Can contain the inner exception for debugging purposes.

The verbosity of this exception object is controlled by the `<customErrors />` ([https://msdn.microsoft.com/en-us/library/h0hfz6fc\(v=vs.100\).aspx](https://msdn.microsoft.com/en-us/library/h0hfz6fc(v=vs.100).aspx)) settings element. By default the full object is only returned for callers from the same host as where the server is located. At low verbosity, the `stackTrace` and `innerException` properties are omitted.

Downloading files

When downloading a file using a link returned by an [Order \(resources/downloadorder.html\)](#) or a `URI` property of an [Image \(resources/image.html\)](#) resource, the file name is not always known upfront. This can be the case, e.g. when a resize action is applied during the ordering of an object, because that action changes the file name.

Download URI will contain a security token set to expire

- after 30 hours, if default File store is configured to use disk as a storage.
- not sooner than the value of the setting `.minimumAvailableTimeForPreviews` (for `/additionalfile`, `/image/preview` and `/image/thumbnail` endpoints) or `.minimumAvailableTimeForOrders` (for download orders) (See the DAM Operations help for more information), if the default File store is configured to use Azure blob storage.

The download URI can return

- file content
- a redirect to the proper file location in case CDN is enabled. It then responds with the http status code "MovedPermanently" (301) or "Redirect" (302)".

It is possible to specify CDN location by setting the value of the optional `Location-Alias` header. Used values:

- `us1` - for South America, Antarctica, North America, Central America, Caribbean
- `eu2` - for Europe, Africa, Middle East
- `au1` - for Australia, Pacific, Asia (except China)
- `cn1` - for China

For reference, the `Content-Disposition` header is added to the response, and contains the file name, e.g. `Content-Disposition: attachment; filename="fname.ext"`

For more information, see: [section 19.5.1 or RFC 2616 \(http://www.w3.org/Protocols/rfc2616/rfc2616-sec19.html#sec19.5.1\)](http://www.w3.org/Protocols/rfc2616/rfc2616-sec19.html#sec19.5.1).

Usage

Authentication

The Aprimo DAM REST API supports 2 modes of authentication: Bearer and Token-based authentication.

There are several endpoints in the Aprimo DAM REST API that do not require authentication. You can find them in the [Endpoint Requirements \(#usage_endpointheaders\)](#) section.

Bearer authentication

Aprimo DAM REST API, among other features, supports editing of resources. In order to create a new resource, you need to perform a **POST** request on a collection to which you want to add a new resource. Performing a **PUT** request updates an existing resource and issuing a **DELETE** request deletes an existing resource. You need to have appropriate privileges in order to

perform these requests.

In most cases, you can reuse the response (in application/json format) of the read operation to provide that response as a request body for the edit requests.

Also, in most cases, setting a resource's property to null resets its value (like "tag" for example).

For changing the nested collections, you can use `addOrUpdate` and `remove` sections in the collections request, which contain id's of elements which have to be added/updated (removed) in (from) nested collections.

Each resource contains the "Examples" section on its documentation page, which provides more info on how to properly perform editing requests on that resource.

Uploading files

Files should be uploaded through the upload service. The upload service is a dedicated service made for uploading files only. Each file that you upload through the upload service can be added to a record. Do note that each uploaded file should be used only once. After the uploaded file has been used by this API a cleanup service will remove the upload from the storage location. The upload service implements 3 approaches to upload files. An http upload for small files (smaller than 20 MB), an http upload for big files (larger than 20 MB) and a direct upload to the blob storage using AzCopy.

Filename restrictions

The following characters are not supported in a filename:

<>: " / \ | ? *

Uploading files below 20 MB

Uploading a file through the Aprimo Upload Service is done in the following way:

```
POST [CustomerURL]/uploads HTTP/1.1
```

".RoleExecuteMaintenanceJobs" and ".RoleViewMaintenanceJobs" privileges are required for users that want to process uploaded files through this API, due to the internal implementation.

Right now only multipart form-data content-type is supported. This means that you cannot simply `POST` binary stream to `/uploads` endpoint. Instead, you produce proper multipart form-data request. However, multipart form-data is the default format for modern HTTP clients, so crafting such a request should not be a problem. The multipart form-data request looks similar to this:

```
POST [CustomerURL]/uploads HTTP/1.1
Content-Length: 244947
User-Agent: Mozilla/5.0 (Windows NT 6.1; WOW64) ...
api-version: 1
Authorization: Bearer eyJ0e...(base64-encoded JWT security token)...jrzpAg
Content-Type: multipart/form-data; boundary=----BoundaryzZaqkP0Sxn4p9XFF
Accept: */*
-----BoundaryzZaqkP0Sxn4p9XFF
Content-Disposition: form-data; name="file1"; filename="Logo_flame.png"
Content-Type: image/png
[binary content]
```

Currently only one file per request is supported, even though the format allows the multi-upload.

When successful, either a HTTP 200 OK response is returned, or a HTTP 202 Accepted response. If the response is 200 OK, it contains a file upload token which can then be used in e.g. the edit record file request. There is also direct access to the file through a `sasUrl`.

```
{
  "token": "eyJQGXRoIjoicWE1LXJlZg4NDZqZTZiZDY4MzQxYjY4YjI5NWE5ZWZkZGE0MmZmL21pa2UucG5nIiwV9sdW1lSWQzI0zI0OTA2MmFiZC1mYmYxLTgwMTYtYTMwYS1iYjdkYWQ2ODM4YzIifQ==",
  "sasUrl": "https://[blobstoragename].blob.core.windows.net/[customer specific container]/8846be6bd68341f68b295a9eadda42ff/Logo_flame.png?sv=2024-11-04&st=2026-01-22T"
}
```

Uploading files above 20 MB - in segments

1. Prepare file segments to upload.
2. Set up the upload
3. Upload each segment
4. Commit the upload
5. Cancel the upload

1. PREPARE THE FILE SEGMENTS TO UPLOAD

This is the responsibility of the consumer of the API. This depends on the technology in which the client program is written.

2. SET UP THE UPLOAD

This is meant to notify the server that an upload flow is initiated by the client.

successful, the response will have HTTP Response Code 200 OK and will contain a URI which can be used to upload the file segments in the next step.

In this step, each segment of the file will be uploaded to the URI provided returned in the response in the previous step.

The name of the file provided in the upload form is not important.

The client needs to specify the index of the uploaded segment as a query string parameter.

The index of the segment is ZERO based

There should be one segment with index=0 and there should be no gaps between indexes.

Step needs to be repeated for every segment of the file. It is possible to upload different file segments in parallel requests.

This step needs to be repeated for every segment of the file. It is possible to upload different file segments in parallel requests.

When successful, the response will have HTTP Response Code 202 Accepted.

After all the segments have been uploaded, the upload flow can be committed.

The client needs to provide the total number of segments which have been uploaded and the name of the original file.

As step validation will occur which will make sure that all the file segments have been uploaded to the server.

In this step validation will occur which will make sure that all the file segments have been uploaded to the server.

In case all the file segments are present, the file will be re-assembled from fragments and will persist on the server.

When successful, a HTTP 200 OK response is returned. If the response is 200 OK, it contains a file upload token which can then be used in e.g. the edit record file request. There is also direct access to the file through a sasUrl.

```
{
  "token": "eyJQGXRoIjoicWE1LXJlZG4NDZqZTZiZDY4MzQxZjY4YjI5NWE5ZWZkZGE0MmZmL21pa2UucG5nIiwiaWVm9sdW1lSWQzOiZl00TA2MmFiZC1mYmYxLTgwMTYtYTmWYS1iYjdkYWQ2ODM4YzIifQ==",
  "sasUrl": "https://[blobstorageName].blob.core.windows.net/[customer specific container]/8846be6bd68341f68b295a9eadda42ff/photo.png?sv=2024-11-04&st=2026-01-22T11%3A"
}
```

An upload flow can be cancelled at any moment after its setup was executed.

```
DELETE [CustomerURL]/uploads/segments/NzVmMDY5YTA4MGU1NDBhMDkyY2FmYzQ3YzQwMzNjMmQ%3d HTTP/1.1
User-Agent: Mozilla/5.0 (Windows NT 6.1; WOW64) ...
api-version: 1
Authorization: Bearer eyJ0e...(base64-encoded JWT security token)...jrzpAg
Accept: */*
```

When successful, the response will have HTTP Response Code 204 No Content.

Uploading files directly to the blob storage

It is possible to upload a file directly to the blob storage using AzCopy, bypassing the http upload service. AzCopy is a command-line utility developed by Microsoft that you can use to copy blobs or files to a storage account. An http call to the upload service is still required to create a writable location on the blob storage. The returned sasUrl can be used to upload the file with AzCopy:

```
POST [CustomerURL]/uploads HTTP/1.1
```

Currently only one file per request is supported.

```
POST /uploads HTTP/1.1
Authorization: Bearer eyJ0e...(base64-encoded JWT security token)...jrzpAg
api-version: 1
Content-Type: application/json

{
  "fileName" : "bigfile.psd"
}
```

When successful, a HTTP 200 OK response is returned. It contains a file upload token which can then be used in the REST API, e.g. the edit record file request.

```
{
  "token": "eyJQGXRoIjoicWE1LXJjLzZqNDZqZTZiZDY4MzQxZjY4YjI5NW5ZWfZGZGE0MmZmL21pa2UucG5nIiwV9sdW1lSWQiOzI0OTA2MmFiZC1mYmYxLTg1MTYtYTmWYS1iYjdkYWQ2ODM4YzIifQ==",
  "sasUrl": "https://[blobstoragename].blob.core.windows.net/[customer specific container]/8846be6bd68341f68b295a9eadda42ff/bigfile.psd?sv=2024-11-04&st=2026-01-22T11:00:00Z"
}
```

Keep in mind that the token can only be used after the file has finished uploading. The AzCopy command would look like this:

```
azcopy copy "C:\path\to\local\file\bigfile.psd" "https://blobstoragename.blob.core.windows.net/local-uploads/65c369ac-6b5c-4e19-b2c4-bf826f74ab6d/bigfile.psd?sv=2017-04-17&sr=c&sig=oINgt6eKwnOYNnDVJB4qHZxylqLzGERbHdo892KCUuc%3D&st=2020-05-05T13%3A49%3A39Z&se=2020-05-06T14%3A04%3A39Z&sp=rw1"
```

Cleaning the uploads

Every file that is uploaded to the upload service is automatically cleaned up after a few days. This means that the tokens you receive back in the upload response are not valid after the cleanup.

Advanced searching

Basic search functionality is provided by the [filter \(#concepts_filtering\)](#) parameter that can be passed in requests to the top-level collection endpoints. See the [Examples: Searching \(#examples_searching\)](#) section for details.

For more complex search queries on records and classifications, the REST API provides the top-level `/search` endpoint.

Advanced searching for records is done in the following way:

```
POST /search/records HTTP/1.1
```

The body of the request is in the following format:

```
{
  "searchExpression": {
    "disabledKeywords": null,
    "supportWildcards": false,
    "defaultLogicalOperator": "AND",
    "languages": ["c2bd4f9bbb954bcb80c31e924c9c26dc"],
    "expression": "CreatedOn < 2015-09-29T12:24:22.287Z",
    "parameters": [],
  }
}
```

```

    "namedParameters": {},
    "subExpressions": null
  },
  "facets": [
    {
      "name": "price",
      "type": "numericFieldRange",
      "fieldId": "b7a3a79f-f403-4af3-9f4c-a3cd0069b2c4",
      "rangeStart": 0,
      "rangeEnd": 1000,
      "spans": [1, 2]
    }
  ],
  "logRequest": true
}

```

The result for the above query has the following structure:

```

{
  "facets": [
    {
      "name": "price",
      "values": [
        {
          "key": {
            "from": 0,
            "to": 1
          },
          "count": 645
        },
        {
          "key": {
            "from": 1,
            "to": 3
          },
          "count": 2945
        },
        ...
      ]
    }
  ],
  "page": 1,
  "pageSize": 50,
  "totalCount": 38610,
  "items": [ ... ]
}

```

Advanced searching for classifications is done in the following way:

```
POST /search/classifications HTTP/1.1
```

The body of the request is in the following format:

```

{
  "searchExpression":
  {
    "disabledKeywords": null,
    "supportWildcards": false,
    "defaultLogicalOperator": "AND",
    "languages": ["c2bd4f9bbb954bcb80c31e924c9c26dc"],
    "expression": "NamePath = ?",
    "parameters": ["/Goods/Phones"],
    "namedParameters": {},
    "subExpressions": null
  },
  "logRequest": true
}

```

The result for the above query is similar to a regular [classification search](#) (resources/classificationpagedcollection.html#example-search).

Some remarks:

- Due to the way search works, the TotalCount returned is an approximation and might not be the same as the amount of returned search results. The retrieved facet count is also an approximation.
- Facet values with a count of 0 are omitted from the reply, even if they are directly specified, e.g. as explicit values. If the consuming application needs to display facet values with a count of 0, it should keep track of them internally.
- The `/search/classifications` endpoint supports only `searchExpression` and `logRequest` parameters.

The search request has the following parameters:

Parameter	Description
<code>searchExpression</code>	An advanced search expression. See below (#usage_searchexpressionparams) for the detailed list of search expression parameters.
<code>facets</code>	An array of facet definitions, when specified, the search response will contain the number of hits matching each facet. See the Facets section below (#usage_facets) for more details.
<code>logRequest</code>	<code>LogRequest</code> is an optional parameter used for logging advanced search expressions in the Aprimo DAM Enterprise Search Log. If the value is not set or if it's set to <code>false</code>, then the REST API will not perform search expression logging. When set to <code>true</code> the REST API will log the search query including its result information. NOTE: search logging stores the “origin” parameter and it is read by REST API from <code>REFERER</code> header. If it's not specified in the request from the custom applications/services, the REST API will use the <code>USER-AGENT</code> header to fill the "origin". The "origin" may be used to distinguish several search sources within the same application or several applications/services. NOTE: Search logging is also controlled by the <code>.enterpriseSearchActionsToLog</code> and <code>.enterpriseSearchLogDetail</code> settings in Aprimo DAM. See the Aprimo DAM Administrator Guide for more information.
<code>ignoreInvalidFacets</code>	<code>IgnoreInvalidFacets</code> is an optional parameter indicating whether invalid facets in the request should be ignored. An invalid facet is a facet pointing to a field that doesn't exist or the user has no read rights to, or to a field that is not enabled for searching. If the value is not set or if it's set to <code>false</code> and there are invalid facets passed in the request, then the REST API will not execute the search and return an error message. When set to <code>true</code> the REST API will execute the search and ignore any invalid facets passed in the request.

Search expression parameters

Parameter	Description
<code>expression</code>	The actual search expression, may optionally contain named or unnamed parameters. You can specify either an expression or subExpressions as parameter of a search expression, but not both.
<code>parameters</code>	An array of values that will fill in the question marks in the expression query.
<code>namedParameters</code>	A collection of key value pairs holding the values for the named parameters prefixed with an @ sign in the query.
<code>disabledKeywords</code>	Allows you to disable specific keywords in the query. You can choose one or more of the options listed below: • <code>And</code> • <code>At</code> • <code>Contains</code> • <code>Dot</code> • <code>Equals</code> • <code>GreaterThan</code> • <code>GreaterThanOrEqual</code> • <code>In</code> • <code>LessThan</code> • <code>LessThanOrEqual</code> • <code>MinusSign</code> • <code>None</code> • <code>Not</code> • <code>NotEquals</code> • <code>Or</code> • <code>PlusSign</code> • <code>QuestionMark</code>
<code>supportWildcards</code>	Indicates whether an asterisk (*) in a value is considered to be a wildcard (true) or whether it is considered to be part of the value. Also applies to question marks (?) in quoted strings: when the <code>supportWildcards</code> flag is set, the question marks will match any single character.
<code>defaultLogicalOperator</code>	Boolean operator that is automatically added to the search query when a Boolean operator is missing. The logical operator can be <code>AND</code> or <code>OR</code> , the default value is <code>AND</code> .
<code>languages</code>	Allows restriction of the search to a list of one or more language ids. If omitted, all language ids are taken into account.

Parameter	Description
<code>subExpressions</code>	An optional collection of sub-expression. If specified, only records will be returned that will match all of the sub-expressions (logical AND). You can specify either an expression or subExpressions as parameter of a search expression, but not both.

Facets

All facets have these parameters in common:

Parameter	Required	Description
<code>name</code>	yes	A textual identifier for this facet, used only by the client to correlate requests with responses.
<code>type</code>	yes	Type of the facet, depending on facet type different parameters, combinations of parameters and parameter types are possible. The possible facet types are: <code>classification</code> <code>classificationListField</code> <code>contentType</code> <code>createdBy</code> <code>createdOn</code> <code>dateFieldRange</code> <code>dateTimeFieldRange</code> <code>fileType</code> <code>modifiedBy</code> <code>modifiedOn</code> <code>numericField</code> <code>numericFieldRange</code> <code>optionListField</code> <code>textField</code> <code>textListField</code> <code>timeFieldRange</code> <code>dateFieldRangeFilter</code> <code>numericFieldRangeFilter</code>
<code>filters</code>	no	Filters allow you to limit the hits returned without affecting facets. If filters are specified, the aggregated counts in the facets remain the same. However, only records that match the filter criteria specified in the facet are returned. The parameter type of the filters depends on the facet type, but is always the same type as the <code>explicitValues</code> or <code>explicitRanges</code> parameter. NOTE: In the below examples, filters are sometimes specified as an example, but not always. All facets, however, accept filters.

The number of facets that can be returned per request is limited. The limit is 12 facets per request. If more than the allowed number of facets, is submitted in the request, the list of facets will be truncated. This means that the search engine will only include the first 12 facets from the list, and all others will be ignored. The list of ignored facet names are later on listed in the search response, in the property **TruncatedFacets**. See search response resource for more information on its properties.

The following facet types are supported:

- CLASSIFICATIONFACET

```
{
  "name": "brand",
  "type": "classification",
  "facetRootId": "BCAEDD3B-DA09-4DED-817D-D92D335158AF",
  "options": ["FacetRoot", "Children"],
  "directLinkedOnly": true,
  "maximumFacetValues": 20,
  "filters": []
}
```

or

```
{
  "name": "brand",
  "type": "classification",
  "explicitValues": ["BCAEDD3B-DA09-4DED-817D-D92D335158AF", "20099504-462F-408F-A5F8-51CB140A7A43"],
  "directLinkedOnly": true,
  "filters": ["BCAEDD3B-DA09-4DED-817D-D92D335158AF"]
}
```

Parameter	Required	Description
<code>facetRootId</code>	no	The classification Id used to determine which classifications will be faceted on, in combination with the options parameter. You must specify either explicitValues or facetRootId .
<code>options</code>	no	These options specify how the facetRootId is used to determine which classifications are faceted on. This must be a combination of FacetRoot, Children, Descendants or All: <code>FacetRoot</code>: include the facet root classification as facet value. <code>Children</code>: include the facet root classifications children as facet values. <code>Descendants</code>: include all the facet root classifications descendants as facet values. <code>All</code>: include the facet root classification and all its descendants as facet values. Defaults to FacetRoot.
<code>directLinkedOnly</code>	no	Determines if facet counts only take records into account that are directly linked to the facet classification, or also records that are linked to children or descendants of the facet classification.
<code>explicitValues</code>	no	A list of Ids, when specified, only shows facets corresponding to the specified classifications. You must specify either explicitValues or classificationId .
<code>maximumFacetValues</code>	no	Maximum number of facet values.

• CLASSIFICATIONLISTFIELD FACET

```
{
  "name": "region",
  "type": "classificationListField",
  "fieldId": "9336117A-047E-4C76-BCBC-0A4A7316F8A6",
  "explicitValues": [
    "42A9A761-D22B-4694-A196-618282B64957",
    "9F4205FD-4977-488C-A8E4-6FB4D6B09AC5"
  ]
}
```

Parameter	Required	Description
<code>fieldId</code>	yes	The Id of the field this facet should operate on.
<code>explicitValues</code>	no	A list of Ids. When specified, only shows facets corresponding to the specified classification items. If not specified, all classification items are included.
<code>maximumFacetValues</code>	no	Maximum number of facet values returned.
<code>alwaysIncludeFiltersInFacetValues</code>	no	Determines if the filters applied to this facet should always be part of the facet values. When maximumFacetValues is set and explicitValues is not and filters are applied, it is possible that the items being filtered on are not part of the facet values. If you want to prevent this from happening, set this property to True . Defaults to False .

• CONTENTTYPE FACET

```
{
  "name": "Content Types",
  "type": "contentType",
  "rootContentType": "Image",
  "maximumFacetValues": 20,
  "directLinkedOnly": true
}
```

or

```
{
  "name": "Content Types",
  "type": "contentType",
  "explicitValues": [
    "Image",
    "Video"
  ]
}
```

```
]
}
```

Parameter	Required	Description
<code>explicitValues</code>	no	A list of content type names. When specified, only shows facets corresponding to the specified content types. If not specified, all content types are included.
<code>maximumFacetValue</code> <code>s</code>	no	Maximum number of facet values returned.
<code>directLinkedOnly</code>	no	Determines if facet counts only take records into account that are directly linked to the facet content type, or also records that are linked to child content types.
<code>rootContentType</code>	no	Specify the content type to be used as the root. All child content types will be returned. The selected root content type will be included.

- CREATEDBYFACET

```
{
  "name": "creator",
  "type": "createdBy",
  "explicitValues": [ "BCAEDD3B-DA09-4DED-817D-D92D335158AF", "20099504-462F-408F-A5F8-51CB140A7A43" ],
  "maximumFacetValues": 12,
  "filters": [ "20099504-462F-408F-A5F8-51CB140A7A43" ]
}
```

Parameter	Required	Description
<code>explicitValues</code>	no	A list of Ids. When specified, only shows facets corresponding to the specified users. When not specified, all users are taken into account.
<code>maximumFacetValues</code>	no	Maximum number of facet values returned.

- CREATEDONFACET

```
{
  "name": "date of creation",
  "type": "createdOn",
  "rangeStart": "2014-05-15T10:41:19.51Z",
  "rangeEnd": "2015-05-15T10:41:19.51Z",
  "spans": [
    {
      "dateTimeUnit": "days",
      "value": 7
    },
    {
      "dateTimeUnit": "months",
      "value": 1
    }
  ],
  "boundaries": ["Lower", "Upper"],
  "filters": [
    {
      "rangeStart": "2014-05-01T10:41:19.51Z",
      "rangeEnd": "2014-05-15T10:41:19.51Z"
    },
    {
      "rangeStart": "2014-05-15T10:41:19.51Z",
      "rangeEnd": "2014-05-31T10:41:19.51Z"
    }
  ]
}
```

or

```
{
  "name": "date of creation",
  "type": "createdOn",
  "explicitRanges": [
```

```
{
  rangeStart: "2014-05-01T10:41:19.51Z",
  rangeEnd: "2014-05-15T10:41:19.51Z"
},
{
  rangeStart: "2014-05-15T10:41:19.51Z",
  rangeEnd: "2014-05-31T10:41:19.51Z"
}
],
"boundaries": ["Lower", "Upper"],
"filters": []
}
```

Parameter	Required	Description
rangeStart	no	Start date and time of the range to take into account. Cannot be specified if explicitRanges is specified.
rangeEnd	no	End date and time of the range to take into account. Cannot be specified if explicitRanges is specified.
spans	no	Allows for the explicit specification of spans to divide the facet in. If the range specified is larger than the sum of all spans, the last span will be repeated to cover the entire range. Spans are objects that have a number property value , and a dateUnit that can be one of years , months , days , hours , minutes or seconds . Cannot be specified if explicitRanges is specified. If spans are specified, rangeStart and rangeEnd are mandatory.
explicitRanges	no	Allows for the explicit specification of ranges to include in the facet. If explicitRanges are specified, you cannot specify rangeStart , rangeEnd or spans .
boundaries	no	Specifies how to include hits that coincide with range or span boundaries. Can be a combination of Lower , Upper , All , Edge or None . Defaults to None .

• DATEFIELDRANGEFACET

```
{
  "name": "productionDate",
  "type": "dateFieldRange",
  "fieldId": "E63E2645-BC54-4D64-AEE6-FC5458DB6AAE",
  "rangeStart": "2014-05-15T00:00:00.00Z",
  "rangeEnd": "2015-05-15T00:00:00.00Z",
  "spans": [
    {
      "dateUnit": "days",
      "value": 7
    },
    {
      "dateUnit": "months",
      "value": 1
    }
  ],
  "boundaries": ["Lower", "Upper"],
  "filters": []
}
```

or

```
{
  "name": "productionDate",
  "type": "dateFieldRange",
  "fieldId": "53092CEF-A15C-42EE-AA89-369D9A0E1E1B",
  "explicitRanges": [
    {
      "rangeStart": "2014-05-01T00:00:00.00Z",
      "rangeEnd": "2014-05-15T00:00:00.00Z"
    },
    {
      "rangeStart": "2014-05-15T00:00:00.00Z",
      "rangeEnd": "2014-05-31T00:00:00.00Z"
    }
  ],
  "boundaries": [
    "Lower",
```

```
    "Upper"
  ],
  "filters": [
    {
      "rangeStart": "2014-05-15T00:00:00.00Z",
      "rangeEnd": "2014-05-31T00:00:00.00Z"
    }
  ]
}
```

Parameter	Required	Description
<code>fieldId</code>	yes	The Id of the field this facet should operate on.
<code>rangeStart</code>	no	Start date of the range to take into account. Cannot be specified if explicitRanges is specified.
<code>rangeEnd</code>	no	End date of the range to take into account. Cannot be specified if explicitRanges is specified.
<code>spans</code>	no	Allows for the explicit specification of spans to divide the facet in. If the range specified is larger than the sum of all spans, the last span will be repeated to cover the entire range. Spans are objects that have a number property value , and a dateUnit that can be one of years , months or days . Cannot be specified if explicitRanges is specified. If spans are specified, rangeStart and rangeEnd are mandatory.
<code>explicitRanges</code>	no	Allows for the explicit specification of ranges to include in the facet. If explicitRanges are specified, you cannot specify rangeStart , rangeEnd or spans .
<code>boundaries</code>	no	Specifies how to include hits that fall on range or span boundaries. Can be a combination of Lower , Upper , All , Edge or None . Defaults to None .

• DATETIMEFIELDRANGEFACET

```
{
  "name": "productionDateTime",
  "type": "dateTimeFieldRange",
  "fieldId": "53092CEF-A15C-42EE-AA89-369D9A0E1E1B",
  "rangeStart": "2014-05-15T10:41:19.51Z",
  "rangeEnd": "2015-05-15T10:41:19.51Z",
  "spans": [
    {
      "dateTimeUnit": "hours",
      "value": 4
    },
    {
      "dateTimeUnit": "days",
      "value": 1
    }
  ],
  "boundaries": [
    "Lower",
    "Upper"
  ],
  "filters": []
}
```

or

```
{
  "name": "productionDateTime",
  "type": "dateTimeFieldRange",
  "explicitRanges": [
    {
      "rangeStart": "2014-05-01T10:41:19.51Z",
      "rangeEnd": "2014-05-15T10:41:19.51Z"
    },
    {
      "rangeStart": "2014-05-15T10:41:19.51Z",
      "rangeEnd": "2014-05-31T10:41:19.51Z"
    }
  ],
  "boundaries": [
    "Lower",
```

```
"Upper"
],
"filters": []
}
```

Parameter	Required	Description
fieldId	yes	The Id of the field this facet should operate on.
rangeStart	no	Start date and time of the range to take into account. Cannot be specified if explicitRanges is specified.
rangeEnd	no	End date and time of the range to take into account. Cannot be specified if explicitRanges is specified.
spans	no	Allows for the explicit specification of spans to divide the facet in. If the range specified is larger than the sum of all spans, the last span will be repeated to cover the entire range. Spans are objects that have a number property value , and a dateTimeUnit that can be one of years , months , days , hours , minutes or seconds . Cannot be specified if explicitRanges is specified. If spans are specified, rangeStart and rangeEnd are mandatory.
explicitRanges	no	Allows for the explicit specification of ranges to include in the facet. If explicitRanges are specified, you cannot specify rangeStart , rangeEnd or spans .
boundaries	no	Specifies how to include hits that fall on range or span boundaries. Can be a combination of Lower , Upper , All , Edge or None . Defaults to None .

• FILETYPEFACET

```
{
  "name": "type of file",
  "type": "fileType",
  "explicitValues": [
    "BCAEDD3B-DA09-4DED-817D-D92D335158AF",
    "20099504-462F-408F-A5F8-51CB140A7A43"
  ],
  "maximumFacetValues": 9,
  "filters": [
    "20099504-462F-408F-A5F8-51CB140A7A43"
  ]
}
```

Parameter	Required	Description
explicitValues	no	A list of Ids, when specified, only shows facets corresponding to the specified file types. When not specified, all file types are taken into account.
maximumFacetValues	no	Maximum number of facet values returned.

• MODIFIEDBYFACET

```
{
  "name": "modifier",
  "type": "modifiedBy",
  "explicitValues": [
    "BCAEDD3B-DA09-4DED-817D-D92D335158AF",
    "20099504-462F-408F-A5F8-51CB140A7A43"
  ],
  "maximumFacetValues": 9,
  "filters": [
    "BCAEDD3B-DA09-4DED-817D-D92D335158AF"
  ]
}
```

Parameter	Required	Description
explicitValues	no	A list of Ids. When specified, only shows facets corresponding to the specified users. When not specified, all users are taken into account.
maximumFacetValues	no	Maximum number of facet values returned.

• MODIFIEDONFACET


```
{
  "name": "date of modification",
  "type": "modifiedOn",
  "rangeStart": "2014-05-15T10:41:19.51Z",
  "rangeEnd": "2015-05-15T10:41:19.51Z",
  "spans": [
    {
      "dateTimeUnit": "days",
      "value": 7
    },
    {
      "dateTimeUnit": "months",
      "value": 1
    }
  ],
  "boundaries": [
    "Lower",
    "Upper"
  ]
}
```

or

```
{
  "name": "date of modification",
  "type": "modifiedOn",
  "explicitRanges": [
    {
      "rangeStart": "2014-05-01T10:41:19.51Z",
      "rangeEnd": "2014-05-15T10:41:19.51Z"
    },
    {
      "rangeStart": "2014-05-15T10:41:19.51Z",
      "rangeEnd": "2014-05-31T10:41:19.51Z"
    }
  ],
  "boundaries": [
    "Lower",
    "Upper"
  ]
}
```

Parameter	Required	Description
<code>rangeStart</code>	no	Start date and time of the range to take into account. Can not be specified if explicitRanges is specified.
<code>rangeEnd</code>	no	End date and time of the range to take into account. Can not be specified if explicitRanges is specified.
<code>spans</code>	no	Allows for the explicit specification of spans to divide the facet in. If the range specified is larger than the sum of all spans, the last span will be repeated to cover the entire range. Spans are objects that have a number property value , and a dateUnit that can be one of years , months , days , hours , minutes or seconds . Can not be specified if explicitRanges is specified. If spans are specified, rangeStart and rangeEnd are mandatory.
<code>explicitRanges</code>	no	Allows for the explicit specification of ranges to include in the facet. If explicitRanges are specified, you cannot specify rangeStart , rangeEnd or spans .
<code>boundaries</code>	no	Specifies how to include hits that fall on range or span boundaries. Can be a combination of Lower , Upper , All , Edge or None . Defaults to None .

- NUMERICFIELD FACET

```
{
  "name": "price",
  "type": "numericField",
  "fieldId": "EE85EBFD-E46E-44DF-AE44-90A6A4FEC9D7",
  "explicitValues": [
    10,
    99.9,
    12,
    27
  ],
}
```

```
"maximumFacetValues": 9,
"filters": [
  10,
  12
]
}
```

Parameter	Required	Description
fieldId	yes	The Id of the field this facet should operate on.
explicitValues	no	A list of Ids, when specified, only shows facets corresponding to the specified values. When not specified, all occurring values are returned.
maximumFacetValues	no	Maximum number of facet values returned.

- NUMERICFIELDRANGEFACET

```
{
  "name": "priceRange",
  "type": "numericFieldRange",
  "fieldId": "53092CEF-A15C-42EE-AA89-369D9A0E1E1B",
  "rangeStart": 100,
  "rangeEnd": 999,
  "spans": [
    5,
    5,
    10
  ],
  "boundaries": [
    "Lower",
    "Upper"
  ],
  "filters": []
}
```

or

```
{
  "name": "priceRange",
  "type": "numericFieldRange",
  "fieldId": "53092CEF-A15C-42EE-AA89-369D9A0E1E1B",
  "explicitRanges": [
    {
      "rangeStart": 5,
      "rangeEnd": 25
    },
    {
      "rangeStart": 26,
      "rangeEnd": 50
    }
  ],
  "boundaries": [
    "Lower",
    "Upper"
  ]
}
```

Parameter	Required	Description
fieldId	yes	The Id of the field this facet should operate on.
rangeStart	no	Start of the range to take into account. Cannot be specified if explicitRanges is specified.
rangeEnd	no	End of the range to take into account. Cannot be specified if explicitRanges is specified.
spans	no	Allows for the explicit specification of spans to divide the facet in. If the range specified is larger than the sum of all spans, the last span will be repeated to cover the entire range. Cannot be specified if explicitRanges is specified. If spans are specified, rangeStart and rangeEnd are mandatory.

Parameter	Required	Description
<code>explicitRanges</code>	no	Allows for the explicit specification of ranges to include in the facet. If explicitRanges are specified, you cannot specify rangeStart , rangeEnd or spans .
<code>boundaries</code>	no	Specifies how to include hits that fall on range or span boundaries. Can be a combination of Lower , Upper , All , Edge or None . Defaults to None .

- OPTIONLISTFIELDFACET

```
{
  "name": "choice",
  "type": "optionListField",
  "fieldId": "40A5C3E5-518A-4368-823D-CD289723F78F",
  "explicitValues": [
    "BCAEDD3B-DA09-4DED-817D-D92D335158AF",
    "20099504-462F-408F-A5F8-51CB140A7A43"
  ]
}
```

Parameter	Required	Description
<code>fieldId</code>	yes	The Id of the field this facet should operate on.
<code>explicitValues</code>	no	A list of Ids. When specified, only shows facets corresponding to the specified option collection items. If not specified, all option collection items are included.
<code>maximumFacetValues</code>	no	Maximum number of facet values returned.

- TEXTFIELDFACET

```
{
  "name": "color",
  "type": "textField",
  "fieldId": "40A5C3E5-518A-4368-823D-CD289723F78F",
  "explicitValues": [
    "green",
    "yellow",
    "blue"
  ],
  "caseSensitive": false,
  "filters": [
    "yellow"
  ]
}
```

Parameter	Required	Description
<code>fieldId</code>	yes	The Id of the field this facet should operate on.
<code>explicitValues</code>	no	A list of strings. When specified, only returns facet values for these strings. If not specified, all occurring strings are returned.
<code>maximumFacetValues</code>	no	Maximum number of facet values returned.
<code>caseSensitive</code>	no	Whether or not strings that only differ in case are aggregated into the same facet.

- TEXTLISTFIELDFACET

```
{
  "name": "status",
  "type": "textListField",
  "fieldId": "CDB72463-2056-4A2D-8903-54D7A1DBBBDD0",
  "explicitValues": [
    "available",
    "out of stock"
  ]
}
```

```
]
}
```

Parameter	Required	Description
fieldId	yes	The Id of the field this facet should operate on.
explicitValues	no	A list of string values. When specified, only shows facets corresponding to the specified option collection items. If not specified, all option collection items are included.
maximumFacetValues	no	Maximum number of facet values returned.
alwaysIncludeFiltersInFacetValues	no	Determines if the filters applied to this facet should always be part of the facet values. When maximumFacetValues is set and explicitValues is not and filters are applied, it is possible that the items being filtered on are not part of the facet values. If you want to prevent this from happening, set this property to True . Defaults to False .

- TIMEFIELDRANGEFACET

```
{
  "name": "productionTime",
  "type": "timeFieldRange",
  "fieldId": "53092CEF-A15C-42EE-AA89-369D9A0E1E1B",
  "rangeStart": "10:41:19",
  "rangeEnd": "18:41:19",
  "spans": [
    "00:15:00",
    "00:30:00",
    "01:00:00"
  ],
  "boundaries": [
    "Lower",
    "Upper"
  ]
}
```

or

```
{
  "name": "productionTime",
  "type": "timeFieldRange",
  "fieldId": "53092CEF-A15C-42EE-AA89-369D9A0E1E1B",
  "explicitRanges": [
    {
      "rangeStart": "10:41:00",
      "rangeEnd": "14:40:59"
    },
    {
      "rangeStart": "14:41:00",
      "rangeEnd": "18:41:00"
    }
  ],
  "boundaries": [
    "Lower",
    "Upper"
  ]
}
```

Parameter	Required	Description
fieldId	yes	The Id of the field this facet should operate on.
rangeStart	no	Start time of the range to take into account. Cannot be specified if explicitRanges is specified.
rangeEnd	no	End time of the range to take into account. Cannot be specified if explicitRanges is specified.
spans	no	Allows for the explicit specification of spans to divide the facet in. If the range specified is larger than the sum of all spans, the last span will be repeated to cover the entire range. Spans are also expressed as times. Cannot be specified if explicitRanges is specified. If spans are specified, rangeStart and rangeEnd are mandatory.

Parameter	Required	Description
<code>explicitRanges</code>	no	Allows for the explicit specification of ranges to include in the facet. If explicitRanges are specified, you cannot specify rangeStart , rangeEnd or spans .
<code>boundaries</code>	no	Specifies how to include hits that fall on range or span boundaries. Can be a combination of Lower , Upper , All , Edge or None . Defaults to None .

- DATEFIELDRANGEFILTER

```
{
  "name": "expirationDate",
  "type": "dateFieldRangeFilter",
  "fieldId": "835C1B53-AFD5-46E0-801F-02054A85DE22",
  "filters": []
}
```

or

```
{
  "name": "expirationDate",
  "type": "dateFieldRangeFilter",
  "fieldId": "98C9974E-260C-4399-866C-AF330057B0A4",
  "filters": [
    {
      "rangeStart": "2022-08-24T00:00:00.00Z",
      "rangeEnd": "2022-08-29T00:00:00.00Z"
    }
  ]
}
```

Parameter	Required	Description
<code>fieldId</code>	yes	The Id of the field this facet should operate on.
<code>rangeStart</code>	no	Start date of the range to take into account. If both rangeStart and rangeEnd are specified in the filters, it will contain all the items related to the search between the dates supplied. Otherwise, it will contain all the items related to the search.
<code>rangeEnd</code>	no	End date of the range to take into account. If both rangeStart and rangeEnd are specified in the filters, it will contain all the items related to the search between the dates supplied. Otherwise, it will contain all the items related to the search.

- NUMERICFIELDRANGEFILTER

```
{
  "name": "Test Numeric",
  "type": "numericFieldRangeFilter",
  "fieldId": "b0a96b8a-243b-475e-ac2d-afaf009d81df",
  "filters": []
}
```

or

```
{
  "name": "Test Numeric",
  "type": "numericFieldRangeFilter",
  "fieldId": "b0a96b8a-243b-475e-ac2d-afaf009d81df",
  "filters": [
    {
      "rangeStart": 1.5,
      "rangeEnd": 612.155
    }
  ]
}
```

Parameter	Required	Description
<code>fieldId</code>	yes	The Id of the field this facet should operate on.

Parameter	Required	Description
<code>rangeStart</code>	no	Start value of the range to take into account. If both rangeStart and rangeEnd are specified in the filters, it will contain all the items related to the search between the numeric values supplied. Otherwise, it will contain all the items related to the search.
<code>rangeEnd</code>	no	End value of the range to take into account. If both rangeStart and rangeEnd are specified in the filters, it will contain all the items related to the search between the numeric values supplied. Otherwise, it will contain all the items related to the search.

Suggestions

The REST API exposes Aprimo DAM's Enterprise Search support for record suggestions via the `/search/records/suggestions` endpoint. Issue a **POST** request with the following body:

```
POST /search/records/suggestions HTTP/1.1
User-Agent: Mozilla/5.0 (Windows NT 6.1; WOW64) ...
api-version: 1
Authorization: Token Y2ZkZDdjZTc2NDdmNDBlOWE5NDI2ZDhjNjY2MDRhMTU6QURBTU5FVA==
Accept: */*
Content-Type: application/json
{
  "input": "TRY",
  "languageids": [
    "c2bd4f9b-bb95-4bcb-80c3-1e924c9c26dc"
  ],
  "fieldids": [
    "72de5be85e4b453e867ea3cd0069b0f4"
  ],
  "fuzziness": 1,
  "numberOfSuggestions": 10
}
```

This suggestions request object contains the following properties:

Property	Required	Description
<code>input</code>	yes	A string that serves as input for the suggestions. This typically corresponds to e.g. partially entered user input.
<code>languageIds</code>	yes	A list of Ids of the languages that should be taken into account for the suggestions search.
<code>fieldIds</code>	yes	A list of IDs of the fields that should be taken into account for the suggestion search. Note that your Aprimo DAM installation must be configured so that these fields are included in the suggestion search engine indexing, by including them in the .enterpriseSearchSuggestionConfiguration system setting.
<code>fuzziness</code>	no	A number specifying the fuzziness of the suggestion search. Must be between 0.0 and 2.0. This fuzziness can be interpreted as a Levenshtein Edit Distance — the number of one character changes that need to be made to one string to make it the same as another string.
<code>numberOfSuggestions</code>	no	The maximum number of suggestions returned. The default value is 5.

The suggestions response contains a list of suggestions per input language:

```
[
  {
    "languageId": "c2bd4f9bbb954bcb80c31e924c9c26dc",
    "suggestions": [
      {
        "text": "TRYGG",
        "score": 17.31806755065918
      },
      {
        "text": "EKBY VALTER/ EKBY TRYGGVE",
        "score": 8.439911842346191
      }
    ]
  }
]
```

Each suggestion contains the matched text and a score estimating how well the input was matched.

Statistics

For diagnostic purposes, the REST API can perform and report some performance measurements, such as timing statistics of requests and some breakdown of these timings. This functionality is exposed via the `/statistics` endpoint.

NOTE that this a feature intended for support & debugging purposes only; it is subject to change and should not be used in normal operation of the API. Not all detailed output will be meaningful without internal knowledge of the REST API.

Toggling statistics gathering

Enabling or disabling the collection of statistics can be done via a PUT to the statistics endpoint. By default the gathering of statistics is disabled.

```
PUT /statistics HTTP/1.1
User-Agent: Mozilla/5.0 (Windows NT 6.1; WOW64) ...
api-version: 1
Authorization: Token Y2ZkZDdjZTc2NDdmNDBlOWE5NDI2ZDhjNjY2MDRhMTU6QURBTU5FVA==
Accept: */*
Content-Type: application/json
{
  "enabled": "true"
}
```

Retrieving statistics

To retrieve the gathered statistics, perform a HTTP GET request to the `/statistics` endpoint. Statistics are structured as a call tree, aggregated at the top level per request type:

```
{
  "get classification/{classificationId}": {
    "identifier": "get classification/{classificationId}",
    "children": {
      "classificationByIdQuery": {
        "identifier": "ClassificationByIdQuery",
        "children": null,
        "occurrences": 1,
        "minDuration": 955,
        "maxDuration": 955,
        "average": 955
      },
      "mappingRequest<Classification, ClassificationResource>": {
        "identifier": "MappingRequest<Classification, ClassificationResource>",
        "children": {
          "classificationChildrenByParentIdQuery": {
            "identifier": "ClassificationChildrenByParentIdQuery",
            "children": null,
            "occurrences": 1,
            ...
          },
          "occurrences": 1,
          "minDuration": 158,
          "maxDuration": 158,
          "average": 158
        }
      },
      "occurrences": 1,
      "minDuration": 1293,
      "maxDuration": 1293,
      "average": 1293
    }
  }
}
```

Clearing statistics

Clearing the running statistics is also possible, by performing a HTTP DELETE on the `/statistics` endpoint.

System Administration

Enterprise Search

- [Reading the search index state](#) (resources/searchindex.html#example-example-get)
- [Rebuilding the search index](#) (resources/searchindex.html#example-rebuild)

Log message Event IDs

Event ID	Description
1001	General exception. Log message should be checked for the complete exception stack trace.
1002	An API client provided a unsupported content type value in the request header. Only 'application/json' is supported.
1003	Method the API client used is not supported. Supported HTTP methods are endpoint specific and can be one of the following: GET, POST, PUT, PATCH, DELETE
1005	A problem with the authentication happened. Log message should be checked for a detailed message and exception stack trace.
1006	Aprimo DAM REST API service couldn't be started. Log message should be checked for more details and the detailed exception stack trace.
1007	Record file has been checked out for edit.
1008	Record file has been reverted to the non-checkout-out state.
1009	Record file has been uploaded.
1010	All the record file segments have been uploaded.
1011	Record file has been checked in and new version of a file is added.
1012	Raw request / response message with full body, headers and additional details.
1013	Application starting, stopping and similar events.

Note that other event IDs might be present in your eventlog, propagated from Aprimo DAM through REST.

Resources

- [AccessList](#) (resources/accesslist.html)
- [AccessListPagedCollection](#) (resources/accesslistpagedcollection.html)
- [AdditionalFile](#) (resources/additionalfile.html)
- [AdditionalFileCollection](#) (resources/additionalfilecollection.html)
- [AdditionalFilePreview](#) (resources/additionalfilepreview.html)
- [AdditionalFilePreviewCollection](#) (resources/additionalfilepreviewcollection.html)
- [ActionTypeCollection](#) (resources/actiontypecollection.html)
- [AkamaiCdnOrder](#) (resources/akamaicdnorder.html)
- [Annotation](#) (resources/annotation.html)
- [AuditEntry](#) (resources/auditentry.html)
- [AuditEntryId](#) (resources/auditentryid.html)
- [BooleanSettingDefinition](#) (resources/booleansettingdefinition.html)
- [BrandTemplateOrder](#) (resources/brandtemplateorder.html)
- [BrandTemplatePreprocessingOrder](#) (resources/brandtemplatepreprocessingorder.html)
- [CalculatedPermission](#) (resources/calculatedpermission.html)
- [CalculatedPermissionCollection](#) (resources/calculatedpermissioncollection.html)
- [Classification](#) (resources/classification.html)
- [ClassificationCollection](#) (resources/classificationcollection.html)
- [ClassificationDownloadPermissions](#) (resources/classificationdownloadpermissions.html)
- [ClassificationListField](#) (resources/classificationlistfield.html)
- [ClassificationListFieldDefinition](#) (resources/classificationlistfielddefinition.html)
- [ClassificationMaintenanceTarget](#) (resources/classificationmaintenancetarget.html)
- [ClassificationPagedCollection](#) (resources/classificationpagedcollection.html)
- [ClassificationPermissions](#) (resources/classificationpermissions.html)
- [ClassificationUserPermissions](#) (resources/classificationuserpermissions.html)
- [Collection](#) (resources/collection.html)
- [CollectionPagedCollection](#) (resources/collectionpagedcollection.html)
- [CollectionPermissions](#) (resources/collectionpermissions.html)
- [Comment](#) (resources/comment.html)
- [CommentPagedCollection](#) (resources/commentpagedcollection.html)
- [ContentType](#) (resources/contenttype.html)
- [ContentTypePagedCollection](#) (resources/contenttypepagedcollection.html)
- [CounterCollection](#) (resources/countercollection.html)
- [Crop](#) (resources/crop.html)
- [CropRendition](#) (resources/croprendition.html)
- [Csp](#) (resources/csp.html)

- [Check](#) (resources/check.html)
- [CheckCategoryCollection](#) (resources/checkcategorycollection.html)
- [CheckCollection](#) (resources/checkcollection.html)
- [CustomFile](#) (resources/customfile.html)
- [CustomRendition](#) (resources/customrendition.html)
- [DateField](#) (resources/datefield.html)
- [DateFieldDefinition](#) (resources/datefielddefinition.html)
- [DateTimeField](#) (resources/datetimetype.html)
- [DateTimeFieldDefinition](#) (resources/datetimetypedefinition.html)
- [DateTimeSettingDefinition](#) (resources/datetimesettingdefinition.html)
- [DefSchemaSettingDefinition](#) (resources/defschemasettingdefinition.html)
- [DownloadAgreement](#) (resources/downloadagreement.html)
- [DownloadAgreementClassification](#) (resources/downloadagreementclassification.html)
- [DownloadAgreementClassificationCollection](#) (resources/downloadagreementclassificationcollection.html)
- [DownloadAgreementContent](#) (resources/downloadagreementcontent.html)
- [DownloadAgreementContentCollection](#) (resources/downloadagreementcontentcollection.html)
- [DownloadAgreementPagedCollection](#) (resources/downloadagreementpagedcollection.html)
- [DownloadAgreementUserGroup](#) (resources/downloadagreementusergroup.html)
- [DownloadAgreementUserGroupCollection](#) (resources/downloadagreementusergroupcollection.html)
- [DownloadContactSheet](#) (resources/downloadcontactsheet.html)
- [DownloadLink](#) (resources/downloadlink.html)
- [DownloadLinkPagedCollection](#) (resources/downloadlinkpagedcollection.html)
- [DownloadLinkTargetCollection](#) (resources/downloadlinktargetcollection.html)
- [DownloadOrder](#) (resources/downloadorder.html)
- [DurationField](#) (resources/durationfield.html)
- [DurationFieldDefinition](#) (resources/durationfielddefinition.html)
- [EmailOrder](#) (resources/emailorder.html)
- [EncryptedTextSettingDefinition](#) (resources/encryptedtextsettingdefinition.html)
- [ExportAuditDownloadLinkTarget](#) (resources/exportauditdownloadlinktarget.html)
- [ExportAuditDownloadLinkTargetCollection](#) (resources/exportauditdownloadlinktargetcollection.html)
- [ExportAuditMaintenanceJob](#) (resources/exportauditmaintenancejob.html)
- [ExportMetadataDownloadLinkTarget](#) (resources/exportmetadatadownloadlinktarget.html)
- [ExportMetadataDownloadLinkTargetCollection](#) (resources/exportmetadatadownloadlinktargetcollection.html)
- [ExternalFile](#) (resources/externalfile.html)
- [FieldCollection](#) (resources/fieldcollection.html)
- [FieldDefinition](#) (resources/fielddefinition.html)
- [FieldDefinitionCollection](#) (resources/fielddefinitioncollection.html)
- [FieldDefinitionPagedCollection](#) (resources/fielddefinitionpagedcollection.html)
- [FieldGroup](#) (resources/fieldgroup.html)
- [FieldGroupPagedCollection](#) (resources/fieldgrouppagedcollection.html)
- [FieldPopulationLogSummary](#) (resources/fieldpopulationlogsummary.html)
- [FieldPopulationLogPrediction](#) (resources/fieldpopulationlogprediction.html)
- [File](#) (resources/file.html)
- [FileCollection](#) (resources/filecollection.html)
- [FilePreview](#) (resources/filepreview.html)
- [FilePreviewCollection](#) (resources/filepreviewcollection.html)
- [FilePreviewPagedCollection](#) (resources/filepreviewpagedcollection.html)
- [FileProcessAction](#) (resources/fileprocessaction.html)
- [FileProcessActionCollection](#) (resources/fileprocessactioncollection.html)
- [FileProcessActionLog](#) (resources/fileprocessactionlog.html)
- [FileProcessActionLogCollection](#) (resources/fileprocessactionlogcollection.html)
- [FileType](#) (resources/filetype.html)
- [FileTypePagedCollection](#) (resources/filetypepagedcollection.html)
- [FileVersion](#) (resources/fileversion.html)
- [FileVersionCheckResult](#) (resources/fileversioncheckresult.html)
- [FileVersionCheckResultCollection](#) (resources/fileversioncheckresultcollection.html)
- [FileVersionCheckResultFinding](#) (resources/fileversioncheckresultfinding.html)
- [FileVersionCheckResultFindingCollection](#) (resources/fileversioncheckresultfindingcollection.html)
- [FileVersionCollection](#) (resources/fileversioncollection.html)
- [FileVersionPagedCollection](#) (resources/fileversionpagedcollection.html)
- [FileVersionPermissions](#) (resources/fileversionpermissions.html)
- [FtpOrder](#) (resources/ftporder.html)
- [FtpResortOrder](#) (resources/ftpresortorder.html)
- [Home](#) (resources/home.html)
- [HtmlField](#) (resources/htmlfield.html)
- [HtmlFieldDefinition](#) (resources/htmlfielddefinition.html)
- [HyperlinkListField](#) (resources/hyperlinklistfield.html)
- [HyperlinkListFieldDefinition](#) (resources/hyperlinklistfielddefinition.html)
- [Image](#) (resources/image.html)
- [ImageOverlay](#) (resources/imageoverlay.html)

- [ImageOverlayClassification](#) (resources/imageoverlayclassification.html)
- [ImageOverlayClassificationCollection](#) (resources/imageoverlayclassificationcollection.html)
- [ImageOverlayCollection](#) (resources/imageoverlaycollection.html)
- [ImageOverlayUserGroup](#) (resources/imageoverlayusergroup.html)
- [ImageOverlayUserGroupCollection](#) (resources/imageoverlayusergroupcollection.html)
- [Info](#) (resources/info.html)
- [JsonField](#) (resources/jsonfield.html)
- [JsonFieldDefinition](#) (resources/jsonfielddefinition.html)
- [Language](#) (resources/language.html)
- [LanguageListField](#) (resources/languagelistfield.html)
- [LanguageListFieldDefinition](#) (resources/languagelistfielddefinition.html)
- [LanguagePagedCollection](#) (resources/languagepagedcollection.html)
- [LinkedClassification](#) (resources/linkedclassification.html)
- [LinkedClassificationCollection](#) (resources/linkedclassificationcollection.html)
- [LinkedRecord](#) (resources/linkedrecord.html)
- [LinkedRecordCollection](#) (resources/linkedrecordcollection.html)
- [LinkedVersionInfoCollection](#) (resources/linkedversioninfocollection.html)
- [MaintenanceJob](#) (resources/maintenancejob.html)
- [MaintenanceJobPagedCollection](#) (resources/maintenancejobpagedcollection.html)
- [MaintenanceTargetCollection](#) (resources/maintenancetargetcollection.html)
- [MultiLineTextField](#) (resources/multilinetextfield.html)
- [MultiLineTextFieldDefinition](#) (resources/multilinetextfielddefinition.html)
- [Null](#) (resources/null.html)
- [NumericField](#) (resources/numericfield.html)
- [NumericFieldDefinition](#) (resources/numericfielddefinition.html)
- [NumericSettingDefinition](#) (resources/numericsettingdefinition.html)
- [OptionListField](#) (resources/optionlistfield.html)
- [OptionListFieldDefinition](#) (resources/optionlistfielddefinition.html)
- [OrderCollection](#) (resources/ordercollection.html)
- [OrderDownloadLinkMassTarget](#) (resources/orderdownloadlinkmasstarget.html)
- [OrderDownloadLinkTarget](#) (resources/orderdownloadlinktarget.html)
- [OrderPagedCollection](#) (resources/orderpagedcollection.html)
- [OrderTarget](#) (resources/ordertarget.html)
- [OrderTargetCollection](#) (resources/ordertargetcollection.html)
- [OriginalRendition](#) (resources/originalrendition.html)
- [Permission](#) (resources/permission.html)
- [PermissionCollection](#) (resources/permissioncollection.html)
- [PermissionPagedCollection](#) (resources/permissionpagedcollection.html)
- [PermissionValue](#) (resources/permissionvalue.html)
- [PermissionValueCollection](#) (resources/permissionvaluecollection.html)
- [PresetRendition](#) (resources/presetrendition.html)
- [PublicCdnOrder](#) (resources/publiccdnorder.html)
- [PublicCdnAdaptiveStreamingOrder](#) (resources/publiccdnadaptivestreamingorder.html)
- [PublicLink](#) (resources/publiclink.html)
- [PublicLinkCollection](#) (resources/publiclinkcollection.html)
- [PublicUri](#) (resources/publicuri.html)
- [PublicUriCollection](#) (resources/publicuricollection.html)
- [Record](#) (resources/record.html)
- [RecordAccessList](#) (resources/recordaccesslist.html)
- [RecordAccessListCollection](#) (resources/recordaccesslistcollection.html)
- [RecordAnalytics](#) (resources/recordanalytics.html)
- [RecordClassification](#) (resources/recordclassification.html)
- [RecordClassificationCollection](#) (resources/recordclassificationcollection.html)
- [RecordCollection](#) (resources/recordcollection.html)
- [RecordLinkField](#) (resources/recordlinkfield.html)
- [RecordLinkFieldDefinition](#) (resources/recordlinkfielddefinition.html)
- [RecordListField](#) (resources/recordlistfield.html)
- [RecordListFieldDefinition](#) (resources/recordlistfielddefinition.html)
- [RecordLock](#) (resources/recordlock.html)
- [RecordLocks](#) (resources/recordlocks.html)
- [RecordMaintenanceTarget](#) (resources/recordmaintenancetarget.html)
- [RecordManagedContent](#) (resources/recordmanagedcontent.html)
- [RecordPagedCollection](#) (resources/recordpagedcollection.html)
- [RecordPermissions](#) (resources/recordpermissions.html)
- [ReferenceSettingDefinition](#) (resources/referencesettingdefinition.html)
- [Rendition](#) (resources/rendition.html)
- [RenditionCollection](#) (resources/renditioncollection.html)
- [ReportingMaintenanceTarget](#) (resources/reportingmaintenancetarget.html)
- [RoleSettingDefinition](#) (resources/rolesettingdefinition.html)
- [Rule](#) (resources/rule.html)

- [RuleActionCollection](#) (resources/ruleactioncollection.html)
- [RuleConditionCollection](#) (resources/ruleconditioncollection.html)
- [RuleMaintenanceTarget](#) (resources/rulemaintenancetarget.html)
- [RulePagedCollection](#) (resources/rulepagedcollection.html)
- [SearchIndex](#) (resources/searchindex.html)
- [SearchResponse](#) (resources/searchresponse.html)
- [Setting](#) (resources/setting.html)
- [SettingCategory](#) (resources/settingcategory.html)
- [SettingCategoryPagedCollection](#) (resources/settingcategorypagedcollection.html)
- [SettingCollection](#) (resources/settingcollection.html)
- [SettingDefinition](#) (resources/settingdefinition.html)
- [SettingDefinitionPagedCollection](#) (resources/settingdefinitionpagedcollection.html)
- [SharedDownloadLink](#) (resources/shareddownloadlink.html)
- [SharedDownloadLinkFile](#) (resources/shareddownloadlinkfile.html)
- [SharedDownloadLinkFileCollection](#) (resources/shareddownloadlinkfilecollection.html)
- [SharedDownloadLinkFileDownloadUri](#) (resources/shareddownloadlinkfiledownloaduri.html)
- [ShareDownloadLinkOrder](#) (resources/sharedownloadlinkorder.html)
- [SingleLineTextField](#) (resources/singlelinetextfield.html)
- [SingleLineTextFieldDefinition](#) (resources/singlelinetextfielddefinition.html)
- [Spinset](#) (resources/spinset.html)
- [Still](#) (resources/still.html)
- [Subscription](#) (resources/subscription.html)
- [Subtitle](#) (resources/subtitle.html)
- [TextListField](#) (resources/textlistfield.html)
- [TextListFieldDefinition](#) (resources/textlistfielddefinition.html)
- [TextSettingDefinition](#) (resources/textsettingdefinition.html)
- [ThreeDimensionalFile](#) (resources/threedimensionalfile.html)
- [TimeField](#) (resources/timefield.html)
- [TimeFieldDefinition](#) (resources/timefielddefinition.html)
- [Translation](#) (resources/translation.html)
- [TranslationPagedCollection](#) (resources/translationpagedcollection.html)
- [Trim](#) (resources/trim.html)
- [TrimRendition](#) (resources/trimrendition.html)
- [UniqueKeyIndex](#) (resources/uniquekeyindex.html)
- [User](#) (resources/user.html)
- [UserGroup](#) (resources/usergroup.html)
- [UserGroupCollection](#) (resources/usergroupcollection.html)
- [UserGroupListField](#) (resources/usergrouplistfield.html)
- [UserGroupListFieldDefinition](#) (resources/usergrouplistfielddefinition.html)
- [UserGroupListFieldItem](#) (resources/usergrouplistfielditem.html)
- [UserGroupPagedCollection](#) (resources/usergrouppagedcollection.html)
- [UserListField](#) (resources/userlistfield.html)
- [UserListFieldDefinition](#) (resources/userlistfielddefinition.html)
- [UserListFieldItem](#) (resources/userlistfielditem.html)
- [UserPagedCollection](#) (resources/userpagedcollection.html)
- [Version](#) (resources/version.html)
- [VersionCollection](#) (resources/versioncollection.html)
- [Watermark](#) (resources/watermark.html)
- [WatermarkPagedCollection](#) (resources/watermarkpagedcollection.html)
- [XmlSettingDefinition](#) (resources/xmlsettingdefinition.html)