

C8000V IPsec Testbed

Test evidence — every command run on every device

Run started	07 September 2026, 19:21 UTC
Duration	19.4 minutes
Result	208 of 208 tests passed
Suites	22
Device commands recorded	1406
Topology	hub-and-spoke: R1 hub, R2 and R3 spokes, one Linux host per router
Encryption	IKEv2 + static VTI, ESP-AES-256 / SHA256, one tunnel per spoke
Routing	eBGP inside the tunnels; AS 65001 hub, AS 65002 / 65003 spokes

Suite results

Suite	Tests	Passed	Failed	Commands	Time
01 Platform	5	5	0	10	1s
02 Configuration	5	5	0	14	2s
03 Wan	6	6	0	19	1s
04 Dmvpn	13	13	0	37	25s
05 Capture State	12	12	0	79	16s
06 Wire Encryption	3	3	0	27	34s
07 Ipsec Negative	3	3	0	63	124s
08 Management Api	6	6	0	7	3s
09 Bgp	26	26	0	623	302s
10 Host To Host	10	10	0	47	79s
11 Throughput	3	3	0	10	81s
12 Nat	10	10	0	51	79s
13 Nat Pool	13	13	0	50	89s
14 Ntp	12	12	0	39	3s
15 Syslog	10	10	0	21	47s
16 Snmpv3	13	13	0	87	15s

17 Snmp Polling	14	14	0	74	17s
18 Mtu	8	8	0	17	21s
19 Oob	9	9	0	68	31s
20 Tacacs	12	12	0	35	25s
21 Vty Acl	9	9	0	22	1s
22 Banner	6	6	0	6	21s

Each test below lists the commands it issued, in order, with the device that ran them and the output it returned. Router commands are marked in teal, Linux host commands in amber. Long output is trimmed to the first 14 lines; complete captures are in results/.

01 Platform

1.01 PASS Both Routers Report Catalyst 8000V Software (0.2s, 2 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output matches **Cisco IOS[-]XE Software, Version ld+l.ld+** (checked 2×)
- output contains **C8000V** (checked 2×)

How it was checked

R1 show version

```
Cisco IOS XE Software, Version 17.15.06
Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-UNIVERSALK9-M), Version 17.15.6, RELEASE
SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 by mcpre
```

```
Cisco IOS-XE software, Copyright (c) 2005-2026 by cisco Systems, Inc.
All rights reserved. Certain components of Cisco IOS-XE software are
licensed under the GNU General Public License ("GPL") Version 2.0. The
software code licensed under GPL Version 2.0 is free software that comes
with ABSOLUTELY NO WARRANTY. You can redistribute and/or modify such
GPL code under the terms of GPL Version 2.0. For more details, see the
documentation or "License Notice" file accompanying the IOS-XE software,
... 52 more lines
```

R2 show version

```
Cisco IOS XE Software, Version 17.15.06
Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-UNIVERSALK9-M), Version 17.15.6, RELEASE
SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 by mcpre
```

```
Cisco IOS-XE software, Copyright (c) 2005-2026 by cisco Systems, Inc.
All rights reserved. Certain components of Cisco IOS-XE software are
licensed under the GNU General Public License ("GPL") Version 2.0. The
software code licensed under GPL Version 2.0 is free software that comes
with ABSOLUTELY NO WARRANTY. You can redistribute and/or modify such
GPL code under the terms of GPL Version 2.0. For more details, see the
documentation or "License Notice" file accompanying the IOS-XE software,
... 52 more lines
```

Teardown (suite) Close All Routers

1.02 PASS Hostnames Match The Day0 Bootstrap Configs (0.2s, 2 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains **\${expected}** (checked 2×)

How it was checked

R1 show running-config | include ^hostname

```
hostname c8000v-r1
```

R2 show running-config | include ^hostname

```
hostname c8000v-r2
```

Teardown (suite) Close All Routers

1.03 PASS Management Interfaces Are Up With DHCP Addresses (0.1s, 2 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output matches **GigabitEthernet1s+10\0.0\2\ld+ls+YES\DHCP\up\up** (checked 2×)

How it was checked

R1 `show ip interface brief GigabitEthernet1`

Interface	IP-Address	OK?	Method	Status	Protocol
GigabitEthernet1	10.0.2.15	YES	DHCP	up	up

R2 `show ip interface brief GigabitEthernet1`

Interface	IP-Address	OK?	Method	Status	Protocol
GigabitEthernet1	10.0.2.15	YES	DHCP	up	up

Teardown (suite) Close All Routers

1.04 **PASS** Crypto Feature License Is Active (0.1s, 2 commands)

Without a feature license the crypto CLI does not exist at all, so every IPsec test downstream depends on this.

Setup (suite) Open All Routers

Acceptance criteria

- output matches **License Level:ls*S+** (checked 2×)

How it was checked

R1 `show version | include License Level`

```
License Level: network-premier
Addon License Level: dna-premier
```

R2 `show version | include License Level`

```
License Level: network-premier
Addon License Level: dna-premier
```

Teardown (suite) Close All Routers

1.05 **PASS** Management Plane Services Are Enabled (0.2s, 2 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains **netconf-yang** (checked 2×)
- output contains **restconf** (checked 2×)

How it was checked

R1 `show running-config | include ^netconf-yang|^restconf`

```
netconf-yang
restconf
```

R2 `show running-config | include ^netconf-yang|^restconf`

```
netconf-yang
restconf
```

Teardown (suite) Close All Routers

02 Configuration

2.01 **PASS** Create A Loopback Interface (0.1s, 6 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain % **Invalid input**
- output does not contain % **Incomplete command**
- output does not contain % **Ambiguous command**

How it was checked

R1 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R1 interface Loopback100

#{output} =

R1 description ROBOT-MANAGED

#{output} =

R1 ip address 192.0.2.1 255.255.255.0

#{output} =

R1 no shutdown

#{output} =

R1 end

#{output} =

Teardown (this test) Run Keyword If Test Failed (Log, #{TEST_NAME} failed -- see the console on port 5001)

2.02 **PASS** Loopback Appears In The Interface Table (0.0s, 1 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output matches **#{LOOPBACK}#{s}#{LOOPBACK_IP}#{s}+YES#{s}+manual#{s}+up#{s}+up**

How it was checked

R1 show ip interface brief Loopback100

Interface	IP-Address	OK?	Method	Status	Protocol
Loopback100	192.0.2.1	YES	manual	up	up

Teardown (this test) Run Keyword If Test Failed (Log, #{TEST_NAME} failed -- see the console on port 5001)

2.03 **PASS** Loopback Is Reachable From The Device Itself (2.1s, 2 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains **Success rate is 100 percent**

How it was checked

R1 ping 192.0.2.1 repeat 2

Type escape sequence to abort.

Sending 2, 100-byte ICMP Echos to 192.0.2.1, timeout is 2 seconds:

..!

Success rate is 50 percent (1/2), round-trip min/avg/max = 1/1/1 ms

R1 ping 192.0.2.1 repeat 5

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 192.0.2.1, timeout is 2 seconds:

!!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms

Teardown (this test) Run Keyword If Test Failed (Log, #{TEST_NAME} failed -- see the console on port 5001)

2.04 **PASS** Loopback Is Present In The Running Config (0.0s, 1 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains **description** ROBOT-MANAGED
- output contains **ip address** \${LOOPBACK_IP} \${LOOPBACK_MASK}

How it was checked

R1 show running-config interface Loopback100

Building configuration...

```
Current configuration : 92 bytes
!
interface Loopback100
  description ROBOT-MANAGED
  ip address 192.0.2.1 255.255.255.0
end
```

Teardown (this test) Run Keyword If Test Failed (Log, \${TEST_NAME} failed -- see the console on port 5001)

2.05 PASS Removing The Loopback Cleans It Up (0.1s, 4 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain \${LOOPBACK_IP}

How it was checked

R1 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R1 no interface Loopback100

\${output} =

R1 end

\${output} =

R1 show ip interface brief Loopback100

```
^
% Invalid input detected at '^' marker.
```

Teardown (this test) Run Keyword If Test Failed (Log, \${TEST_NAME} failed -- see the console on port 5001)

03 Wan

3.01 PASS Every Router Is On The Shared WAN Segment (0.1s, 3 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output matches **GigabitEthernet2** is **\${WAN_IP}** is **YES** is **IS** is **up** is **up** (checked 3×)

How it was checked

```
R1 show ip interface brief | include GigabitEthernet2
GigabitEthernet2    100.64.0.1      YES TFTP   up          up
R2 show ip interface brief | include GigabitEthernet2
GigabitEthernet2    100.64.0.2      YES TFTP   up          up
R3 show ip interface brief | include GigabitEthernet2
GigabitEthernet2    100.64.0.3      YES TFTP   up          up
```

Teardown (suite) Close All Connections

3.02 PASS Every Router Can Reach Every Other Router On It (0.2s, 6 commands)

Including spoke to spoke, which is the precondition for a direct tunnel and the property the VTI lab deliberately did not have. Tested at the underlay, before any tunnel exists.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **Success rate is 100 percent** (checked 6×)

How it was checked

```
R2 ping 100.64.0.2 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 100.64.0.2, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
R3 ping 100.64.0.3 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 100.64.0.3, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
R1 ping 100.64.0.1 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 100.64.0.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/1 ms
R3 ping 100.64.0.3 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 100.64.0.3, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
R1 ping 100.64.0.1 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 100.64.0.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/1 ms
R2 ping 100.64.0.2 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 100.64.0.2, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
```

Teardown (suite) Close All Connections

3.03 PASS The Spokes Reach Each Other Directly, Not Through The Hub (0.0s, 1 commands)

One hop at the underlay. If this became two the spokes would still have connectivity, and DMVPN would still form tunnels -- but every "direct" spoke-to-spoke path would quietly be transiting the hub anyway.

Setup (suite) Open All Routers

Acceptance criteria

- output contains `${R3_WAN_IP}`
- output does not contain `${R1_WAN_IP}`
the spokes reach each other via the hub at the underlay:\n\${trace}

How it was checked

R2 `traceroute 100.64.0.3 probe 1 timeout 1 numeric`

```
Type escape sequence to abort.
Tracing the route to 100.64.0.3
VRF info: (vrf in name/id, vrf out name/id)
 1 100.64.0.3 1 msec
```

Teardown (suite) Close All Connections

3.04 **PASS** Each Router Learns The Others On The Segment (0.1s, 3 commands)

A shared segment, so every router should have resolved every other -- unlike a point-to-point link with exactly one neighbour.

Setup (suite) Open All Routers

Acceptance criteria

- output contains `${WAN_IP}${peer}` (checked 9×)

How it was checked

R1 `show ip arp GigabitEthernet2`

Protocol	Address	Age (min)	Hardware Addr	Type	Interface
Internet	100.64.0.1	-	5254.00c8.0102	ARPA	GigabitEthernet2
Internet	100.64.0.2	67	5254.00c8.0202	ARPA	GigabitEthernet2
Internet	100.64.0.3	66	5254.00c8.0302	ARPA	GigabitEthernet2

R2 `show ip arp GigabitEthernet2`

Protocol	Address	Age (min)	Hardware Addr	Type	Interface
Internet	100.64.0.2	-	5254.00c8.0202	ARPA	GigabitEthernet2
Internet	100.64.0.1	67	5254.00c8.0102	ARPA	GigabitEthernet2
Internet	100.64.0.3	66	5254.00c8.0302	ARPA	GigabitEthernet2

R3 `show ip arp GigabitEthernet2`

Protocol	Address	Age (min)	Hardware Addr	Type	Interface
Internet	100.64.0.3	-	5254.00c8.0302	ARPA	GigabitEthernet2
Internet	100.64.0.1	67	5254.00c8.0102	ARPA	GigabitEthernet2
Internet	100.64.0.2	66	5254.00c8.0202	ARPA	GigabitEthernet2

Teardown (suite) Close All Connections

3.05 **PASS** The Underlay Carries No Site Prefixes (0.1s, 3 commands)

The WAN is a transport, not a routing domain. A site prefix appearing here would mean traffic could reach a LAN without ever entering the tunnel -- unencrypted, and invisible to every test that watches the overlay.

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain `${LAN_NET}${peer}` (checked 9×)
would put site traffic on the underlay instead of the tunnel
- output contains `${WAN_NET}` (checked 3×)

How it was checked

R1 `show ip route | include GigabitEthernet2`

```
C 100.64.0.0/24 is directly connected, GigabitEthernet2
L 100.64.0.1/32 is directly connected, GigabitEthernet2
```

R2 `show ip route | include GigabitEthernet2`

```
C 100.64.0.0/24 is directly connected, GigabitEthernet2
L 100.64.0.2/32 is directly connected, GigabitEthernet2
```

R3 `show ip route | include GigabitEthernet2`

```
C 100.64.0.0/24 is directly connected, GigabitEthernet2
L 100.64.0.3/32 is directly connected, GigabitEthernet2
```

Teardown (suite) Close All Connections

3.06 PASS No Routing Protocol Runs On The WAN Segment (0.1s, 3 commands)

BGP peers over the tunnel, so the underlay should carry no adjacency at all. One here would be a second, unprotected path for the control plane.

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain `${WAN_NET}rsplit('.', 2)[0]]`. (checked 3×)

How it was checked

R1 `show bgp ipv4 unicast summary | begin Neighbor`

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
172.20.0.2	4	65002	21	24	28	0	0	00:02:16	3
172.20.0.3	4	65003	100	110	28	0	0	00:14:48	3

R2 `show bgp ipv4 unicast summary | begin Neighbor`

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
172.20.0.1	4	65001	24	21	46	0	0	00:02:16	6

R3 `show bgp ipv4 unicast summary | begin Neighbor`

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
172.20.0.1	4	65001	110	100	146	0	0	00:14:49	6

Teardown (suite) Close All Connections

04 Dmvpn

4.01 **PASS** Every Router Runs One Multipoint Tunnel With No Destination (0.1s, 4 commands)

The structural difference from a static VTI. A configured destination would make this point-to-point again and there would be nothing for NHRP to resolve.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **tunnel mode gre multipoint** (checked 3×)
- output does not contain **tunnel destination** (checked 3×)
- output contains **tunnel source GigabitEthernet2** (checked 3×)
- output contains **ip address \${DMVPN_IP}\${r}** (checked 3×)
- output contains **Number of lines which match regexp = 1**
the hub has more than one tunnel interface, which is the VTI shape

How it was checked

R1 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 399 bytes
!
interface Tunnel0
  description DMVPN hub
  ip address 172.20.0.1 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp redirect
  ip tcp adjust-mss 1360
... 6 more lines
```

R2 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 433 bytes
!
interface Tunnel0
  description DMVPN spoke
  ip address 172.20.0.2 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
  ip tcp adjust-mss 1360
... 6 more lines
```

R3 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 433 bytes
!
interface Tunnel0
  description DMVPN spoke
  ip address 172.20.0.3 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
  ip tcp adjust-mss 1360
... 6 more lines
```

R1 show ip interface brief | count Tunnel

Number of lines which match regexp = 1

Teardown (suite) Restore Nhrp, Close All Connections

4.02 **PASS** The Tunnel Is Protected By IPsec On Every Router (0.1s, 3 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains **tunnel protection ipsec profile** (checked 3×)

How it was checked

R1 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 399 bytes
!
interface Tunnel0
 description DMVPN hub
 ip address 172.20.0.1 255.255.255.0
 no ip redirects
 ip nat outside
 ip nhrp authentication LabNhrp
 ip nhrp network-id 100
 ip nhrp holdtime 300
 ip nhrp redirect
 ip tcp adjust-mss 1360
... 6 more lines
```

R2 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 433 bytes
!
interface Tunnel0
 description DMVPN spoke
 ip address 172.20.0.2 255.255.255.0
 no ip redirects
 ip nat outside
 ip nhrp authentication LabNhrp
 ip nhrp network-id 100
 ip nhrp holdtime 300
 ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
 ip tcp adjust-mss 1360
... 6 more lines
```

R3 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 433 bytes
!
interface Tunnel0
 description DMVPN spoke
 ip address 172.20.0.3 255.255.255.0
 no ip redirects
 ip nat outside
 ip nhrp authentication LabNhrp
 ip nhrp network-id 100
 ip nhrp holdtime 300
 ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
 ip tcp adjust-mss 1360
... 6 more lines
```

Teardown (suite) Restore Nhrp, Close All Connections

4.03 **PASS** NHRP Shares A Network ID And Authentication Everywhere (0.1s, 3 commands)

Both must match across the cloud; a mismatch in either leaves registrations silently unanswered.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **ip nhrp network-id \${NHRP_NETWORK_ID}** (checked 3×)
- output contains **ip nhrp authentication \${NHRP_AUTH}** (checked 3×)

How it was checked

R1 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 399 bytes
!
```

```

interface Tunnel0
description DMVPN hub
ip address 172.20.0.1 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp redirect
ip tcp adjust-mss 1360
... 6 more lines

```

R2 show running-config interface Tunnel0

Building configuration...

```

Current configuration : 433 bytes
!
interface Tunnel0
description DMVPN spoke
ip address 172.20.0.2 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
ip tcp adjust-mss 1360
... 6 more lines

```

R3 show running-config interface Tunnel0

Building configuration...

```

Current configuration : 433 bytes
!
interface Tunnel0
description DMVPN spoke
ip address 172.20.0.3 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
ip tcp adjust-mss 1360
... 6 more lines

```

Teardown (suite) Restore Nhrp, Close All Connections

4.04 PASS The Hub Is The Next Hop Server And The Spokes Point At It (0.1s, 4 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains `ip nhrp nhs ${R1_DMVPN_IP} nbma ${R1_WAN_IP}` (checked 2×)
- output does not contain `ip nhrp nhs`
the hub points at a next hop server, so it is behaving as a spoke
- output matches `${WAN_IP}[${r}]\s+${DMVPN_IP}[${r}]\s+UP` (checked 2×)
- `${dynamic}` has exactly 2 entries
the hub does not show two dynamically registered peers

How it was checked

R2 show running-config interface Tunnel0

Building configuration...

```

Current configuration : 433 bytes
!
interface Tunnel0
description DMVPN spoke
ip address 172.20.0.2 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
ip tcp adjust-mss 1360
... 6 more lines

```

R3 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 433 bytes
!
interface Tunnel0
  description DMVPN spoke
  ip address 172.20.0.3 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
  ip tcp adjust-mss 1360
... 6 more lines
```

R1 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 399 bytes
!
interface Tunnel0
  description DMVPN hub
  ip address 172.20.0.1 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp redirect
  ip tcp adjust-mss 1360
... 6 more lines
```

R1 show dmvpn

Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
N - NATed, L - Local, X - No Socket
T1 - Route Installed, T2 - Nexthop-override, B - BGP
C - CTS Capable, I2 - Temporary
Ent --> Number of NHRP entries with same NBMA peer
NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
UpDn Time --> Up or Down Time for a Tunnel

Interface: Tunnel0, IPv4 NHRP Details
Type:Hub, NHRP Peers:2,

```
# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
... 2 more lines
```

Teardown (suite) Restore Nhrp, Close All Connections

4.05 PASS This Is Phase 3, Not Phase 1 Or 2 (0.1s, 3 commands)

Redirect on the hub and shortcut on the spokes are what make the overlay reorganise itself. Without them the tests below about direct paths cannot pass, and the design is a different one.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **ip nhrp redirect**
the hub sends no NHRP redirects
- output contains **ip nhrp nhs** (checked 2x)

How it was checked

R1 show running-config interface Tunnel0

Building configuration...

```
Current configuration : 399 bytes
!
interface Tunnel0
  description DMVPN hub
  ip address 172.20.0.1 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
```

```

ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp redirect
ip tcp adjust-mss 1360
... 6 more lines

```

R2 show running-config interface Tunnel0

Building configuration...

```

Current configuration : 433 bytes
!
interface Tunnel0
description DMVPN spoke
ip address 172.20.0.2 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
ip tcp adjust-mss 1360
... 6 more lines

```

R3 show running-config interface Tunnel0

Building configuration...

```

Current configuration : 433 bytes
!
interface Tunnel0
description DMVPN spoke
ip address 172.20.0.3 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
ip tcp adjust-mss 1360
... 6 more lines

```

Teardown (suite) Restore Nhrp, Close All Connections

4.06 PASS Both Spokes Register With The Hub (0.0s, 1 commands)

Registration is dynamic: the hub is configured with no spoke addresses at all and learns them as they arrive.

Setup (suite) Open All Routers

Acceptance criteria

- output matches `${WAN_IP}${r}}\s+${DMVPN_IP}${r}}\s+UP` (checked 2x)
 - `${dynamic}` has exactly 2 entries
- the hub does not show two dynamically registered peers

How it was checked

R1 show dmvpn

```

Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
         N - NATed, L - Local, X - No Socket
         T1 - Route Installed, T2 - Nexthop-override, B - BGP
         C - CTS Capable, I2 - Temporary
# Ent --> Number of NHRP entries with same NBMA peer
NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
UpDn Time --> Up or Down Time for a Tunnel
=====

```

```

Interface: Tunnel0, IPv4 NHRP Details
Type:Hub, NHRP Peers:2,

```

```

# Ent  Peer NBMA Addr Peer Tunnel Add State  UpDn Tm Attrb
-----
... 2 more lines

```

Teardown (suite) Restore Nhrp, Close All Connections

4.07 PASS The Hub Maps Each Spoke's Tunnel Address To Its NBMA Address (0.0s, 1 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output matches `(?s){DMVPN_IP}{r}/32.*?{WAN_IP}{r}` (checked 2×)
the hub has no NBMA mapping for `{r}`
- output contains **registered**

How it was checked

R1 show ip nhrp

```
172.20.0.2/32 via 172.20.0.2
  Tunnel0 created 00:00:49, expire 00:04:46
  Type: dynamic, Flags: registered nhop bfd
  NBMA address: 100.64.0.2
172.20.0.3/32 via 172.20.0.3
  Tunnel0 created 00:00:49, expire 00:04:10
  Type: dynamic, Flags: registered nhop bfd
  NBMA address: 100.64.0.3
```

Teardown (suite) Restore Nhrp, Close All Connections

4.08 PASS Every DMVPN Peering Is Encrypted (0.0s, 2 commands)

One IPsec profile protects the multipoint tunnel, so each peering formed over it -- including ones the configuration never named -- is protected by construction.

Setup (suite) Open All Routers

Acceptance criteria

- output contains `{R1_WAN_IP}` (checked 2×)
- output matches `{R1_WAN_IP}\s+Tu0\s+.*UA` (checked 2×)

How it was checked

R2 show crypto session brief

```
Status: A - Active, U - Up, D - Down, I - Idle, S - Standby, N - Negotiating
K - No IKE
```

```
ivrf = (none)
```

Peer	I/F	Username	Group/Phase1_id	Uptime	Status
100.64.0.3	Tu0		100.64.0.3	00:00:45	UA
100.64.0.1	Tu0		100.64.0.1	00:00:49	UA

R3 show crypto session brief

```
Status: A - Active, U - Up, D - Down, I - Idle, S - Standby, N - Negotiating
K - No IKE
```

```
ivrf = (none)
```

Peer	I/F	Username	Group/Phase1_id	Uptime	Status
100.64.0.2	Tu0		100.64.0.2	00:00:45	UA
100.64.0.1	Tu0		100.64.0.1	00:00:49	UA

Teardown (suite) Restore Nhrp, Close All Connections

4.09 PASS A Spoke Learns The Far Spoke As The BGP Next Hop (0.1s, 2 commands)

The routing half of Phase 3, and the reason "next-hop-unchanged" is configured on the hub. If the hub rewrote the next hop to itself, every spoke-to-spoke prefix would resolve to the hub, NHRP would never be asked to find the far spoke, and no shortcut could form.

Setup (suite) Open All Routers

Acceptance criteria

- output contains `{R3_DMVPN_IP}`
R2 does not see R3's tunnel address as the next hop for R3's prefix
- output contains `{R2_DMVPN_IP}`
R3 does not see R2's tunnel address as the next hop for R2's prefix

How it was checked

R2 show bgp ipv4 unicast 10.20.3.1

```
BGP routing table entry for 10.20.3.1/32, version 43
Paths: (1 available, best #1, table default)
  Not advertised to any peer
  Refresh Epoch 1
```

```

65001 65003
172.20.0.3 from 172.20.0.1 (172.16.1.1)
  Origin IGP, localpref 100, valid, external, best
  Community: 65003:1
  rx pathid: 0, tx pathid: 0x0
  Updated on Sep 7 2026 23:19:46 UTC

```

R3 show bgp ipv4 unicast 10.20.2.1

```

BGP routing table entry for 10.20.2.1/32, version 144
Paths: (1 available, best #1, table default)
  Not advertised to any peer
  Refresh Epoch 1
65001 65002
172.20.0.2 from 172.20.0.1 (172.16.1.1)
  Origin IGP, localpref 100, valid, external, best
  Community: 65002:1
  rx pathid: 0, tx pathid: 0x0
  Updated on Sep 7 2026 23:20:08 UTC

```

Teardown (suite) Restore Nhrp, Close All Connections

4.10 PASS Spoke To Spoke Traffic Works Before Any Shortcut Exists (12.1s, 4 commands)

The fallback path. With the NHRP cache cleared there is no direct entry, so the first packets go through the hub -- which is what makes the shortcut an optimisation rather than a prerequisite for connectivity.

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain `${WAN_IP}${peer}`
- output contains **Success rate is**
- `${loss}[0] > 0` holds

How it was checked

```

R2 clear ip nhrp
${output} =
R3 clear ip nhrp
${output} =
R2 show ip nhrp 172.20.0.3
${output} =
R2 ping 10.20.3.1 source Loopback1 repeat 30
Type escape sequence to abort.
Sending 30, 100-byte ICMP Echos to 10.20.3.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.2.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
Success rate is 96 percent (29/30), round-trip min/avg/max = 1/1/7 ms

```

Teardown (suite) Restore Nhrp, Close All Connections

4.11 PASS A Shortcut Forms On Demand (12.1s, 6 commands)

The defining behaviour. Cleared first so the entry cannot be left over from an earlier test: it has to be created by this traffic, here.

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain `${WAN_IP}${peer}`
- output contains `${WAN_IP}${peer}` (checked 2x)

How it was checked

```

R2 clear ip nhrp
${output} =
R3 clear ip nhrp
${output} =
R2 show ip nhrp 172.20.0.3
${output} =
R2 ping 10.20.3.1 source Loopback1 repeat 20
Type escape sequence to abort.
Sending 20, 100-byte ICMP Echos to 10.20.3.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.2.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!

```

Success rate is 95 percent (19/20), round-trip min/avg/max = 1/1/1 ms

R2 show ip nhrp 172.20.0.3

```
172.20.0.3/32 via 172.20.0.3
  Tunnel0 created 00:00:02, expire 00:04:58
  Type: dynamic, Flags: router nhop bfd
  NBMA address: 100.64.0.3
```

R3 show ip nhrp 172.20.0.2

```
172.20.0.2/32 via 172.20.0.2
  Tunnel0 created 00:00:02, expire 00:04:58
  Type: dynamic, Flags: router implicit nhop bfd
  NBMA address: 100.64.0.2
```

Teardown (suite) Restore Nhrp, Close All Connections

4.12 PASS Traffic Then Leaves The Hub Out Of The Path (0.1s, 2 commands)

The point of the shortcut, and the strongest statement this suite makes: with the direct path installed, a trace from one spoke to the other reaches it in a single hop instead of transiting the hub.

Setup (suite) Open All Routers

Acceptance criteria

- output contains `${WAN_IP}${peer}]`
- output contains `${R3_DMVPN_IP}`
- output does not contain `${R1_DMVPN_IP}`
the trace still passes through the hub, so no shortcut is in use:\n\${trace}
- `${hops}[-1]` equals 1
the far spoke is `${hops}[-1]` hops away, expected 1

How it was checked

R2 show ip nhrp 172.20.0.3

```
172.20.0.3/32 via 172.20.0.3
  Tunnel0 created 00:00:02, expire 00:04:57
  Type: dynamic, Flags: router nhop bfd
  NBMA address: 100.64.0.3
```

R2 traceroute 10.20.3.1 source Loopback1 probe 1 timeout 1 numeric

```
Type escape sequence to abort.
Tracing the route to 10.20.3.1
VRF info: (vrf in name/id, vrf out name/id)
 1 172.20.0.3 2 msec
```

Teardown (suite) Restore Nhrp, Close All Connections

4.13 PASS The Shortcut Gets Its Own IPsec Session (0.0s, 2 commands)

A direct path between two routers that were never configured with each other's addresses, protected all the same, because the profile is bound to the tunnel rather than to a peer.

Setup (suite) Open All Routers

Acceptance criteria

- output contains `${WAN_IP}${peer}]`
- output contains `${R3_WAN_IP}`
R2 has no IPsec session with R3's NBMA address:\n\${sess}
- `${count}` has exactly 2 entries
R2 holds `${count}` tunnel sessions, expected one to the hub and one to R3

How it was checked

R2 show ip nhrp 172.20.0.3

```
172.20.0.3/32 via 172.20.0.3
  Tunnel0 created 00:00:02, expire 00:04:57
  Type: dynamic, Flags: router nhop bfd
  NBMA address: 100.64.0.3
```

R2 show crypto session brief

```
Status: A- Active, U - Up, D - Down, I - Idle, S - Standby, N - Negotiating
      K - No IKE
ivrf = (none)
Peer      I/F      Username      Group/Phase1_id      Uptime      Status
```

100.64.0.3	Tu0	100.64.0.3	00:00:02 UA
100.64.0.1	Tu0	100.64.0.1	00:01:14 UA

Teardown (suite) Restore Nhrp, Close All Connections

05 Capture State

5.01 **PASS** Capture Running Config From Every Router (13.1s, 3 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria

- output contains **hostname** (checked 3×)
- output matches **(?m)^endls*\$** (checked 3×)

How it was checked

R1 show running-config

Building configuration...

```
Current configuration : 21292 bytes
!
! Last configuration change at 23:22:01 UTC Mon Sep 7 2026 by lab
!
version 17.15
service timestamps debug datetime msec
service timestamps log datetime msec show-timezone
service sequence-numbers
platform qfp utilization monitor load 80
platform sslvpn use-pd
platform console serial
!
... 624 more lines
```

R2 show running-config

Building configuration...

```
Current configuration : 19872 bytes
!
! Last configuration change at 23:21:14 UTC Mon Sep 7 2026 by lab
!
version 17.15
service timestamps debug datetime msec
service timestamps log datetime msec show-timezone
service sequence-numbers
platform qfp utilization monitor load 80
platform sslvpn use-pd
platform console serial
!
... 582 more lines
```

R3 show running-config

Building configuration...

```
Current configuration : 19832 bytes
!
! Last configuration change at 23:21:14 UTC Mon Sep 7 2026 by lab
!
version 17.15
service timestamps debug datetime msec
service timestamps log datetime msec show-timezone
service sequence-numbers
platform qfp utilization monitor load 80
platform sslvpn use-pd
platform console serial
!
... 579 more lines
```

Teardown (suite) Close Nms, Close All Connections

5.02 **PASS** Capture Routing Table From Every Router (0.2s, 3 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria

- output contains **Gateway of last resort** (checked 3×)
- output contains **Codes:** (checked 3×)

How it was checked

R1 show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
 D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
 N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
 E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
 n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
 i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
 ia - IS-IS inter area, * - candidate default, U - per-user static route
 H - NHRP, G - NHRP registered, g - NHRP registration summary
 o - ODR, P - periodic downloaded static route, l - LISP
 a - application route
 + - replicated route, % - next hop override, p - overrides from PfR
 & - replicated local route overrides by connected

Gateway of last resort is 10.0.2.2 to network 0.0.0.0
 ... 24 more lines

R2 show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
 D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
 N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
 E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
 n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
 i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
 ia - IS-IS inter area, * - candidate default, U - per-user static route
 H - NHRP, G - NHRP registered, g - NHRP registration summary
 o - ODR, P - periodic downloaded static route, l - LISP
 a - application route
 + - replicated route, % - next hop override, p - overrides from PfR
 & - replicated local route overrides by connected

Gateway of last resort is 10.0.2.2 to network 0.0.0.0
 ... 24 more lines

R3 show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
 D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
 N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
 E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
 n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
 i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
 ia - IS-IS inter area, * - candidate default, U - per-user static route
 H - NHRP, G - NHRP registered, g - NHRP registration summary
 o - ODR, P - periodic downloaded static route, l - LISP
 a - application route
 + - replicated route, % - next hop override, p - overrides from PfR
 & - replicated local route overrides by connected

Gateway of last resort is 10.0.2.2 to network 0.0.0.0
 ... 24 more lines

Teardown (suite) Close Nms, Close All Connections

5.03 PASS Capture BGP Table And Neighbours From Every Router (0.2s, 6 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

R1 show bgp ipv4 unicast

BGP table version is 28, local router ID is 172.16.1.1
 Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
 r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
 x best-external, a additional-path, c RIB-compressed,
 t secondary path, L long-lived-stale,
 Origin codes: i - IGP, e - EGP, ? - incomplete
 RPKI validation codes: V valid, I invalid, N Not found

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 10.20.1.1/32	0.0.0.0	0		32768	i
*> 10.20.2.1/32	172.20.0.2	0		0	65002 i
*> 10.20.3.1/32	172.20.0.3	0		0	65003 i
*> 10.30.1.0/24	0.0.0.0	0		32768	i
*> 10.30.2.0/24	172.20.0.2	0		0	65002 i

... 4 more lines

R1 show bgp ipv4 unicast summary

BGP router identifier 172.16.1.1, local AS number 65001
 BGP table version is 28, main routing table version 28
 9 network entries using 2232 bytes of memory

```

9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5720 total bytes of memory
BGP activity 136/127 prefixes, 139/130 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:48:55.594 ago)

```

```

Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

```

R2 show bgp ipv4 unicast

```

BGP table version is 46, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
               x best-external, a additional-path, c RIB-compressed,
               t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.1.1/32	172.20.0.1	0		0	65001 i
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.20.3.1/32	172.20.0.3			0	65001 65003 i
*>	10.30.1.0/24	172.20.0.1	0		0	65001 i
*>	10.30.2.0/24	0.0.0.0	0		32768	i

... 4 more lines

R2 show bgp ipv4 unicast summary

```

BGP router identifier 172.16.2.1, local AS number 65002
BGP table version is 46, main routing table version 46
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 64 bytes of memory
6 BGP community entries using 144 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5736 total bytes of memory
BGP activity 160/151 prefixes, 162/153 paths, scan interval 60 secs
31 networks peaked at 22:34:42 Sep 7 2026 UTC (00:48:12.674 ago)

```

```

Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 1 more lines

```

R3 show bgp ipv4 unicast

```

BGP table version is 146, local router ID is 172.16.3.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
               x best-external, a additional-path, c RIB-compressed,
               t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.1.1/32	172.20.0.1	0		0	65001 i
*>	10.20.2.1/32	172.20.0.2			0	65001 65002 i
*>	10.20.3.1/32	0.0.0.0	0		32768	i
*>	10.30.1.0/24	172.20.0.1	0		0	65001 i
*>	10.30.2.0/24	172.20.0.2			0	65001 65002 i

... 4 more lines

R3 show bgp ipv4 unicast summary

```

BGP router identifier 172.16.3.1, local AS number 65003
BGP table version is 146, main routing table version 146
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 64 bytes of memory
6 BGP community entries using 144 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5736 total bytes of memory
BGP activity 72/63 prefixes, 77/68 paths, scan interval 60 secs
9 networks peaked at 22:15:22 Sep 7 2026 UTC (01:07:32.746 ago)

```

```

Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 1 more lines

```

Teardown (suite) Close Nms, Close All Connections

5.04 PASS Capture Crypto State From Every Router (0.3s, 6 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 604, #pkts encrypt: 604, #pkts digest: 604
  #pkts decaps: 594, #pkts decrypt: 594, #pkts verify: 594
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ikev2 sa

IPv4 Crypto IKEv2 SA

Tunnel-id	Local	Remote	fvrf/ivrf	Status
1	100.64.0.1/500	100.64.0.2/500	none/none	READY
Encr: AES-CBC, keysize: 256, PRF: SHA256, Hash: SHA256, DH Grp:14, Auth sign: PSK, Auth verify: PSK				
Life/Active Time: 86400/100 sec				
CE id: 1029, Session-id: 26				
Local spi: 674CC240C9A38803 Remote spi: 6B960B9A3952A45C				

Tunnel-id	Local	Remote	fvrf/ivrf	Status
2	100.64.0.1/500	100.64.0.3/500	none/none	READY
Encr: AES-CBC, keysize: 256, PRF: SHA256, Hash: SHA256, DH Grp:14, Auth sign: PSK, Auth verify: PSK				
Life/Active Time: 86400/100 sec				
CE id: 1030, Session-id: 27				

... 3 more lines

R2 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
current_peer 100.64.0.1 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 1135, #pkts encrypt: 1135, #pkts digest: 1135
  #pkts decaps: 1133, #pkts decrypt: 1133, #pkts verify: 1133
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 33 more lines
```

R2 show crypto ikev2 sa

IPv4 Crypto IKEv2 SA

Tunnel-id	Local	Remote	fvrf/ivrf	Status
1	100.64.0.2/500	100.64.0.1/500	none/none	READY
Encr: AES-CBC, keysize: 256, PRF: SHA256, Hash: SHA256, DH Grp:14, Auth sign: PSK, Auth verify: PSK				
Life/Active Time: 86400/101 sec				
CE id: 1029, Session-id: 24				
Local spi: 6B960B9A3952A45C Remote spi: 674CC240C9A38803				

IPv6 Crypto IKEv2 SA

R3 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.3

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
current_peer 100.64.0.1 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 9361, #pkts encrypt: 9361, #pkts digest: 9361
  #pkts decaps: 9395, #pkts decrypt: 9395, #pkts verify: 9395
  #pkts compressed: 0, #pkts decompressed: 0
```

```
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 33 more lines
```

R3 show crypto ikev2 sa

IPv4 Crypto IKEv2 SA

```
Tunnel-id Local Remote fvr/ivrf Status
1 100.64.0.3/500 100.64.0.1/500 none/none READY
Encr: AES-CBC, keysize: 256, PRF: SHA256, Hash: SHA256, DH Grp:14, Auth sign: PSK, Auth verify: PSK
Life/Active Time: 86400/101 sec
CE id: 1026, Session-id: 26
Local spi: 54006597FF55CAD2 Remote spi: C7ABC0CAC6503940
```

IPv6 Crypto IKEv2 SA

Teardown (suite) Close Nms, Close All Connections

5.05 PASS Capture NAT State From Every Router (0.5s, 6 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

R1 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.1.128	192.168.10.88	---	---
---	10.30.1.129	192.168.10.85	---	---
---	10.30.1.113	192.168.10.93	---	---
---	10.30.1.114	192.168.10.69	---	---
---	10.30.1.116	192.168.10.73	---	---
---	10.30.1.119	192.168.10.71	---	---
---	10.30.1.123	192.168.10.78	---	---
---	10.30.1.120	192.168.10.82	---	---
---	10.30.1.126	192.168.10.76	---	---
---	10.30.1.125	192.168.10.84	---	---
---	10.30.1.101	192.168.10.90	---	---
---	10.30.1.102	192.168.10.89	---	---
---	10.30.1.111	192.168.10.70	---	---

... 28 more lines

R1 show ip nat statistics

```
Total active translations: 40 (10 static, 30 dynamic; 0 extended)
Outside interfaces:
Tunnel0
Inside interfaces:
GigabitEthernet3
Hits: 457 Misses: 123
Reserved port setting disabled provisioned no
Dynamic overload mapping configured: 0
Expired translations: 123
Dynamic mappings:
-- Inside Source
[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 30
pool SITE-POOL: id 1, netmask 255.255.255.0
start 10.30.1.100 end 10.30.1.129
... 9 more lines
```

R2 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.2.128	192.168.20.89	---	---
---	10.30.2.129	192.168.20.84	---	---
---	10.30.2.106	192.168.20.68	---	---
---	10.30.2.105	192.168.20.88	---	---
---	10.30.2.111	192.168.20.92	---	---
---	10.30.2.108	192.168.20.80	---	---
---	10.30.2.101	192.168.20.64	---	---
---	10.30.2.102	192.168.20.65	---	---
---	10.30.2.126	192.168.20.77	---	---
---	10.30.2.125	192.168.20.86	---	---
---	10.30.2.123	192.168.20.79	---	---
---	10.30.2.120	192.168.20.74	---	---
---	10.30.2.116	192.168.20.82	---	---

... 28 more lines

R2 show ip nat statistics

```
Total active translations: 40 (10 static, 30 dynamic; 0 extended)
Outside interfaces:
```

```

Tunnel0
Inside interfaces:
  GigabitEthernet3
Hits: 337 Misses: 83
Reserved port setting disabled provisioned no
Dynamic overload mapping configured: 0
Expired translations: 83
Dynamic mappings:
-- Inside Source
[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 30
  pool SITE-POOL: id 1, netmask 255.255.255.0
    start 10.30.2.100 end 10.30.2.129
... 9 more lines

```

R3 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.3.104	192.168.30.84	---	---
---	10.30.3.107	192.168.30.93	---	---
---	10.30.3.109	192.168.30.92	---	---
---	10.30.3.110	192.168.30.89	---	---
---	10.30.3.103	192.168.30.85	---	---
---	10.30.3.100	192.168.30.83	---	---
---	10.30.3.124	192.168.30.90	---	---
---	10.30.3.127	192.168.30.81	---	---
---	10.30.3.121	192.168.30.80	---	---
---	10.30.3.122	192.168.30.77	---	---
---	10.30.3.118	192.168.30.86	---	---
---	10.30.3.117	192.168.30.75	---	---
---	10.30.3.115	192.168.30.82	---	---

... 28 more lines

R3 show ip nat statistics

```

Total active translations: 40 (10 static, 30 dynamic; 0 extended)
Outside interfaces:
  Tunnel0
Inside interfaces:
  GigabitEthernet3
Hits: 120 Misses: 40
Reserved port setting disabled provisioned no
Dynamic overload mapping configured: 0
Expired translations: 40
Dynamic mappings:
-- Inside Source
[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 30
  pool SITE-POOL: id 1, netmask 255.255.255.0
    start 10.30.3.100 end 10.30.3.129
... 9 more lines

```

Teardown (suite) Close Nms, Close All Connections

5.06 PASS Capture NTP State From Every Router (0.1s, 6 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

R1 show ntp status

```

Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0022 Hz, precision is 2**10
ntp uptime is 410100 (1/100 of seconds), resolution is 4000
reference time is EE49C50C.33B64630 (23:19:40.202 UTC Mon Sep 7 2026)
clock offset is 1.1201 msec, root delay is 50.71 msec
root dispersion is 10.94 msec, peer dispersion is 5.58 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000008787 s/s
system poll interval is 128, last update was 195 sec ago.

```

R1 show ntp associations

```

address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10  68.183.147.240  3    61   128   377  0.928  1.120  5.584
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured

```

R2 show ntp status

```

Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0017 Hz, precision is 2**10
ntp uptime is 410100 (1/100 of seconds), resolution is 4000
reference time is EE49C517.28B439C8 (23:19:51.159 UTC Mon Sep 7 2026)
clock offset is -0.2035 msec, root delay is 49.85 msec
root dispersion is 69.46 msec, peer dispersion is 3.79 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000007002 s/s

```

system poll interval is 64, last update was 184 sec ago.

R2 show ntp associations

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10  68.183.147.240  3    24    64    17  0.062 -0.203 3.798
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

R3 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0021 Hz, precision is 2**10
ntp uptime is 410100 (1/100 of seconds), resolution is 4000
reference time is EE49C439.2A7EFA50 (23:16:09.166 UTC Mon Sep 7 2026)
clock offset is 0.5161 msec, root delay is 47.91 msec
root dispersion is 13.66 msec, peer dispersion is 4.91 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000008467 s/s
system poll interval is 128, last update was 406 sec ago.
```

R3 show ntp associations

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10  68.183.147.240  3    2    128  377  0.058  0.516 4.914
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

Teardown (suite) Close Nms, Close All Connections

5.07 PASS Capture Logging State From Every Router (0.2s, 3 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

R1 show logging | include Trap logging|Logging to|Syslog logging

Syslog logging: enabled (0 messages dropped, 3 messages rate-limited, 0 flushes, 0 overruns, xml disabled, filtering disabled)

Trap logging: level informational, 1046 message lines logged

Logging to 192.168.99.10 (MGMT) (udp port 514, audit disabled,

000142: *Sep 7 22:14:37.628 UTC: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 192.168.99.10 port 0 CLI Request Triggered

000144: *Sep 7 22:14:37.632 UTC: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 192.168.99.10 port 514 (MGMT) started - CLI initiated

R2 show logging | include Trap logging|Logging to|Syslog logging

Syslog logging: enabled (0 messages dropped, 3 messages rate-limited, 0 flushes, 0 overruns, xml disabled, filtering disabled)

Trap logging: level informational, 1336 message lines logged

Logging to 192.168.99.10 (MGMT) (udp port 514, audit disabled,

000718: .Sep 7 22:47:06.797 UTC: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 192.168.99.10 port 514 (MGMT) started - reconnection

000721: .Sep 7 22:47:20.338 UTC: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 192.168.99.10 port 514 (MGMT) started - reconnection

001203: .Sep 7 23:17:12.492 UTC: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 192.168.99.10 port 514 (MGMT) started - reconnection

001206: .Sep 7 23:17:30.372 UTC: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 192.168.99.10 port 514 (MGMT) started - reconnection

R3 show logging | include Trap logging|Logging to|Syslog logging

Syslog logging: enabled (0 messages dropped, 3 messages rate-limited, 0 flushes, 0 overruns, xml disabled, filtering disabled)

Trap logging: level informational, 873 message lines logged

Logging to 192.168.99.10 (MGMT) (udp port 514, audit disabled,

000142: *Sep 7 22:14:37.619 UTC: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 192.168.99.10 port 0 CLI Request Triggered

000143: *Sep 7 22:14:37.620 UTC: %SYS-6-LOGGINGHOST_STARTSTOP: Logging to host 192.168.99.10 port 514 (MGMT) started - CLI initiated

Teardown (suite) Close Nms, Close All Connections

5.08 PASS Capture SNMP State From Every Router (0.2s, 9 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

R1 show snmp user

User name: labmon

Engine ID: 800000090300525400C80101

storage-type: nonvolatile active

```
Authentication Protocol: SHA
Privacy Protocol: AES128
Group-name: LABGRP
```

R1 show snmp host

```
Notification host: 192.168.99.10      udp-port: 1162  VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

```
Notification host: 192.168.99.10      udp-port: 162   VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

R1 show snmp engineID

```
Local SNMP engineID: 800000090300525400C80101
Remote Engine ID      IP-addr  Port
```

R2 show snmp user

```
User name: labmon
Engine ID: 800000090300525400C80201
storage-type: nonvolatile      active
Authentication Protocol: SHA
Privacy Protocol: AES128
Group-name: LABGRP
```

R2 show snmp host

```
Notification host: 192.168.99.10      udp-port: 1162  VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

```
Notification host: 192.168.99.10      udp-port: 162   VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

R2 show snmp engineID

```
Local SNMP engineID: 800000090300525400C80201
Remote Engine ID      IP-addr  Port
```

R3 show snmp user

```
User name: labmon
Engine ID: 800000090300525400C80301
storage-type: nonvolatile      active
Authentication Protocol: SHA
Privacy Protocol: AES128
Group-name: LABGRP
```

R3 show snmp host

```
Notification host: 192.168.99.10      udp-port: 1162  VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

```
Notification host: 192.168.99.10      udp-port: 162   VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

R3 show snmp engineID

```
Local SNMP engineID: 800000090300525400C80301
Remote Engine ID      IP-addr  Port
```

Teardown (suite) Close Nms, Close All Connections

5.09 PASS Capture The NMS View Of Every Router (0.5s, 16 commands)

The same system group, but seen over SNMPv3 from the NMS rather than read off the console. Captured next to the CLI output so the two can be compared in the evidence PDF.

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

NMS ip -br addr; ip route

```
lo                UNKNOWN      127.0.0.1/8 ::1/128
ens3              UP              10.0.2.15/24 metric 100 fec0::5054:ff:febb:101/64 fe80::5054:ff:febb:101/64
ens4              UP              192.168.10.20/24 fe80::5054:ff:febb:102/64
ens5              UP              192.168.99.10/24 fe80::5054:ff:febb:103/64
default via 10.0.2.2 dev ens3 proto dhcp src 10.0.2.15 metric 100
10.0.2.0/24 dev ens3 proto kernel scope link src 10.0.2.15 metric 100
10.0.2.2 dev ens3 proto dhcp scope link src 10.0.2.15 metric 100
10.0.2.3 dev ens3 proto dhcp scope link src 10.0.2.15 metric 100
10.30.0.0/16 via 192.168.10.1 dev ens4
192.168.10.0/24 dev ens4 proto kernel scope link src 192.168.10.20
192.168.20.0/24 via 192.168.10.1 dev ens4
192.168.30.0/24 via 192.168.10.1 dev ens4
192.168.99.0/24 dev ens5 proto kernel scope link src 192.168.99.10
```

NMS ip -br addr; ip route

```
lo                UNKNOWN      127.0.0.1/8 ::1/128
ens3              UP              10.0.2.15/24 metric 100 fec0::5054:ff:febb:101/64 fe80::5054:ff:febb:101/64
```

```

ens4          UP          192.168.10.20/24 fe80::5054:ff:febb:102/64
ens5          UP          192.168.99.10/24 fe80::5054:ff:febb:103/64
default via 10.0.2.2 dev ens3 proto dhcp src 10.0.2.15 metric 100
10.0.2.0/24 dev ens3 proto kernel scope link src 10.0.2.15 metric 100
10.0.2.2 dev ens3 proto dhcp scope link src 10.0.2.15 metric 100
10.0.2.3 dev ens3 proto dhcp scope link src 10.0.2.15 metric 100
10.30.0.0/16 via 192.168.10.1 dev ens4
192.168.10.0/24 dev ens4 proto kernel scope link src 192.168.10.20
192.168.20.0/24 via 192.168.10.1 dev ens4
192.168.30.0/24 via 192.168.10.1 dev ens4
192.168.99.0/24 dev ens5 proto kernel scope link src 192.168.99.10

```

NMS snmpget --version 2>&1 | head -1

```
NET-SNMP version: 5.9.4.pre2
```

NMS snmpget --version 2>&1 | head -1

```
NET-SNMP version: 5.9.4.pre2
```

NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.10.1

1.3.6.1.2.1.1

```

.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (415000) 1:09:10.00
.1.3.6.1.2.1.1.4.0 = ""
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"
.1.3.6.1.2.1.1.6.0 = ""
.1.3.6.1.2.1.1.7.0 = INTEGER: 78
.1.3.6.1.2.1.1.8.0 = Timeticks: (0) 0:00:00.00

```

NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.10.1

1.3.6.1.2.1.1

```

.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (415000) 1:09:10.00
.1.3.6.1.2.1.1.4.0 = ""
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"
.1.3.6.1.2.1.1.6.0 = ""
.1.3.6.1.2.1.1.7.0 = INTEGER: 78
.1.3.6.1.2.1.1.8.0 = Timeticks: (0) 0:00:00.00

```

NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.10.1

1.3.6.1.2.1.2.2.1.2

```

.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"

```

NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.10.1

1.3.6.1.2.1.2.2.1.2

```

.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"

```

NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.20.1

1.3.6.1.2.1.1

```

.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (415086) 1:09:10.86
.1.3.6.1.2.1.1.4.0 = ""
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
.1.3.6.1.2.1.1.6.0 = ""

```

```

.1.3.6.1.2.1.1.7.0 = INTEGER: 78
.1.3.6.1.2.1.1.8.0 = Timeticks: (0) 0:00:00.00
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.20.1
1.3.6.1.2.1.1
.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (415086) 1:09:10.86
.1.3.6.1.2.1.1.4.0 = ""
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
.1.3.6.1.2.1.1.6.0 = ""
.1.3.6.1.2.1.1.7.0 = INTEGER: 78
.1.3.6.1.2.1.1.8.0 = Timeticks: (0) 0:00:00.00
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.20.1
1.3.6.1.2.1.2.2.1.2
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.20.1
1.3.6.1.2.1.2.2.1.2
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.30.1
1.3.6.1.2.1.1
.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (414990) 1:09:09.90
.1.3.6.1.2.1.1.4.0 = ""
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r3.lab.local"
.1.3.6.1.2.1.1.6.0 = ""
.1.3.6.1.2.1.1.7.0 = INTEGER: 78
.1.3.6.1.2.1.1.8.0 = Timeticks: (0) 0:00:00.00
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.30.1
1.3.6.1.2.1.1
.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (414990) 1:09:09.90
.1.3.6.1.2.1.1.4.0 = ""
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r3.lab.local"
.1.3.6.1.2.1.1.6.0 = ""
.1.3.6.1.2.1.1.7.0 = INTEGER: 78
.1.3.6.1.2.1.1.8.0 = Timeticks: (0) 0:00:00.00
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.30.1
1.3.6.1.2.1.2.2.1.2
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"

```

```

NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 192.168.30.1
1.3.6.1.2.1.2.2.1.2
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"

```

Teardown (suite) Close Nms, Close All Connections

5.10 PASS Capture Collector State From The NMS (0.3s, 12 commands)

What the collectors actually hold: the tail of each router's syslog file and of snmptrapd's decrypted log. This is the management-plane evidence that used to come off h1.

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

NMS systemctl is-active rsyslog snmptrapd lab-trapcap

```

active
active
active

```

NMS systemctl is-active rsyslog snmptrapd lab-trapcap

```

active
active
active

```

NMS sudo ls -l /var/log/lab

```

total 2660
-rw-r--r-- 1 syslog syslog 128123 Sep  7 23:22 192.168.99.1.log
-rw-r--r-- 1 syslog syslog 159924 Sep  7 23:22 192.168.99.2.log
-rw-r--r-- 1 syslog syslog 105045 Sep  7 23:22 192.168.99.3.log
-rw-r--r-- 1 root  root   881546 Sep  7 23:22 snmptrapd.log
-rw-r--r-- 1 root  root  1416130 Sep  7 23:22 traps-raw.log

```

NMS sudo ls -l /var/log/lab

```

total 2660
-rw-r--r-- 1 syslog syslog 128123 Sep  7 23:22 192.168.99.1.log
-rw-r--r-- 1 syslog syslog 159924 Sep  7 23:22 192.168.99.2.log
-rw-r--r-- 1 syslog syslog 105045 Sep  7 23:22 192.168.99.3.log
-rw-r--r-- 1 root  root   881546 Sep  7 23:22 snmptrapd.log
-rw-r--r-- 1 root  root  1416130 Sep  7 23:22 traps-raw.log

```

NMS sudo tail -40 /var/log/lab/192.168.10.1.log

```
tail: cannot open '/var/log/lab/192.168.10.1.log' for reading: No such file or directory
```

NMS sudo tail -40 /var/log/lab/192.168.10.1.log

```
tail: cannot open '/var/log/lab/192.168.10.1.log' for reading: No such file or directory
```

NMS sudo tail -40 /var/log/lab/192.168.20.1.log

```
tail: cannot open '/var/log/lab/192.168.20.1.log' for reading: No such file or directory
```

NMS sudo tail -40 /var/log/lab/192.168.20.1.log

```
tail: cannot open '/var/log/lab/192.168.20.1.log' for reading: No such file or directory
```

NMS sudo tail -40 /var/log/lab/192.168.30.1.log

```
tail: cannot open '/var/log/lab/192.168.30.1.log' for reading: No such file or directory
```

NMS sudo tail -40 /var/log/lab/192.168.30.1.log

```
tail: cannot open '/var/log/lab/192.168.30.1.log' for reading: No such file or directory
```

NMS sudo tail -40 /var/log/lab/snmptrapd.log

```

2026-09-07 23:22:26 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:39.57 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.7
iso.3.6.1.4.1.9.9.171.1.3.2.1.9.29 3600 iso.3.6.1.4.1.9.9.171.1.3.2.1.8.29 4608000
iso.3.6.1.4.1.9.9.171.1.3.3.1.3.29.1 1 iso.3.6.1.4.1.9.9.171.1.3.3.1.4.29.1 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.5.29.1 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.3.3.1.9.29.1 1
iso.3.6.1.4.1.9.9.171.1.3.3.1.10.29.1 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.3.3.1.11.29.1 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.6.29.1 47 iso.3.6.1.4.1.9.9.171.1.3.3.1.7.29.1 0
2026-09-07 23:22:26 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:40.66 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.7
iso.3.6.1.4.1.9.9.171.1.3.2.1.9.29 3600 iso.3.6.1.4.1.9.9.171.1.3.2.1.8.29 4608000
iso.3.6.1.4.1.9.9.171.1.3.3.1.3.29.1 1 iso.3.6.1.4.1.9.9.171.1.3.3.1.4.29.1 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.5.29.1 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.3.3.1.9.29.1 1
iso.3.6.1.4.1.9.9.171.1.3.3.1.10.29.1 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.3.3.1.11.29.1 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.6.29.1 47 iso.3.6.1.4.1.9.9.171.1.3.3.1.7.29.1 0

```

```
2026-09-07 23:22:27 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:40.41 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.137.0.1
iso.3.6.1.4.1.9.10.137.1.2.1.8.1708049 0 iso.3.6.1.4.1.9.10.137.1.2.1.8.1708049 0
iso.3.6.1.2.1.2.2.1.1.8 8
2026-09-07 23:22:27 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.50 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.137.0.1
iso.3.6.1.4.1.9.10.137.1.2.1.8.1708035 0 iso.3.6.1.4.1.9.10.137.1.2.1.8.1708035 0
iso.3.6.1.2.1.2.2.1.1.8 8
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.80 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.62.2.0.4
iso.3.6.1.4.1.9.10.62.1.2.3.1.1.2.14.84.117.110.110.101.108.48.45.104.101.97.100.45.48 3
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.71 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.2
iso.3.6.1.4.1.9.9.171.1.2.2.1.6.1.4.100.64.0.3.1.4.100.64.0.2.29 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.2.2.1.7.1.4.100.64.0.3.1.4.100.64.0.2.29 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.2.3.1.16.29 2 iso.3.6.1.4.1.9.9.171.1.4.2.1.1.2.29 4
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.80 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.8
iso.3.6.1.4.1.9.9.171.1.3.2.1.10.29 213 iso.3.6.1.4.1.9.9.171.1.4.3.1.1.12.28 213
iso.3.6.1.4.1.9.9.171.1.4.3.1.1.10.28 3600 iso.3.6.1.4.1.9.9.171.1.4.3.1.1.9.28 4608000
iso.3.6.1.4.1.9.9.171.1.4.3.1.1.2.28 1 iso.3.6.1.4.1.9.9.171.1.4.3.2.1.5.28 1
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.11.28 1 iso.3.6.1.4.1.9.9.171.1.4.3.2.1.6.28 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.7.28 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.4.3.2.1.12.28 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.13.28 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.4.3.2.1.8.28 47
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.9.28 0
... 26 more lines
```

NMS sudo tail -40 /var/log/lab/snmptrapd.log

```
2026-09-07 23:22:26 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:39.57 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.7
iso.3.6.1.4.1.9.9.171.1.3.2.1.9.29 3600 iso.3.6.1.4.1.9.9.171.1.3.2.1.8.29 4608000
iso.3.6.1.4.1.9.9.171.1.3.3.1.3.29.1 1 iso.3.6.1.4.1.9.9.171.1.3.3.1.4.29.1 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.5.29.1 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.3.3.1.9.29.1 1
iso.3.6.1.4.1.9.9.171.1.3.3.1.10.29.1 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.3.3.1.11.29.1 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.6.29.1 47 iso.3.6.1.4.1.9.9.171.1.3.3.1.7.29.1 0
2026-09-07 23:22:26 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:40.66 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.7
iso.3.6.1.4.1.9.9.171.1.3.2.1.9.29 3600 iso.3.6.1.4.1.9.9.171.1.3.2.1.8.29 4608000
iso.3.6.1.4.1.9.9.171.1.3.3.1.3.29.1 1 iso.3.6.1.4.1.9.9.171.1.3.3.1.4.29.1 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.5.29.1 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.3.3.1.9.29.1 1
iso.3.6.1.4.1.9.9.171.1.3.3.1.10.29.1 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.3.3.1.11.29.1 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.6.29.1 47 iso.3.6.1.4.1.9.9.171.1.3.3.1.7.29.1 0
2026-09-07 23:22:27 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:40.41 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.137.0.1
iso.3.6.1.4.1.9.10.137.1.2.1.8.1708049 0 iso.3.6.1.4.1.9.10.137.1.2.1.8.1708049 0
iso.3.6.1.2.1.2.2.1.1.8 8
2026-09-07 23:22:27 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.50 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.137.0.1
iso.3.6.1.4.1.9.10.137.1.2.1.8.1708035 0 iso.3.6.1.4.1.9.10.137.1.2.1.8.1708035 0
iso.3.6.1.2.1.2.2.1.1.8 8
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.80 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.62.2.0.4
iso.3.6.1.4.1.9.10.62.1.2.3.1.1.2.14.84.117.110.110.101.108.48.45.104.101.97.100.45.48 3
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.71 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.2
iso.3.6.1.4.1.9.9.171.1.2.2.1.6.1.4.100.64.0.3.1.4.100.64.0.2.29 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.2.2.1.7.1.4.100.64.0.3.1.4.100.64.0.2.29 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.2.3.1.16.29 2 iso.3.6.1.4.1.9.9.171.1.4.2.1.1.2.29 4
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.80 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.8
iso.3.6.1.4.1.9.9.171.1.3.2.1.10.29 213 iso.3.6.1.4.1.9.9.171.1.4.3.1.1.12.28 213
iso.3.6.1.4.1.9.9.171.1.4.3.1.1.10.28 3600 iso.3.6.1.4.1.9.9.171.1.4.3.1.1.9.28 4608000
iso.3.6.1.4.1.9.9.171.1.4.3.1.1.2.28 1 iso.3.6.1.4.1.9.9.171.1.4.3.2.1.5.28 1
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.11.28 1 iso.3.6.1.4.1.9.9.171.1.4.3.2.1.6.28 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.7.28 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.4.3.2.1.12.28 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.13.28 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.4.3.2.1.8.28 47
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.9.28 0
... 26 more lines
```

Teardown (suite) Close Nms, Close All Connections

5.11 PASS Capture Config And Routing Table From Every Host (0.1s, 6 commands)

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria

- output contains **eth1** (checked 3×)
- output contains **default via** (checked 3×)

How it was checked

H1 ip addr

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue qlen 1000
   link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
   inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
   inet6 ::1/128 scope host
       valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
   link/ether 52:54:00:aa:01:01 brd ff:ff:ff:ff:ff:ff
   inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0
       valid_lft 82334sec preferred_lft 71534sec
   inet6 fec0::5054:ff:feaa:101/64 scope site dynamic noprefixroute flags 100
       valid_lft 86212sec preferred_lft 14212sec
   inet6 fe80::5054:ff:feaa:101/64 scope link
       valid_lft forever preferred_lft forever
... 84 more lines
```

H1 ip route

```
default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.10.1 dev eth1
169.254.0.0/16 dev eth1 scope link src 169.254.229.55 metric 1003
192.168.10.0/24 dev eth1 scope link src 192.168.10.10
192.168.20.0/24 via 192.168.10.1 dev eth1
192.168.30.0/24 via 192.168.10.1 dev eth1
```

H2 ip addr

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue qlen 1000
   link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
   inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
   inet6 ::1/128 scope host
       valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
   link/ether 52:54:00:aa:02:01 brd ff:ff:ff:ff:ff:ff
   inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0
       valid_lft 82337sec preferred_lft 71537sec
   inet6 fec0::5054:ff:feaa:201/64 scope site dynamic noprefixroute flags 100
       valid_lft 86083sec preferred_lft 14083sec
   inet6 fe80::5054:ff:feaa:201/64 scope link
       valid_lft forever preferred_lft forever
... 84 more lines
```

H2 ip route

```
default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.20.1 dev eth1
192.168.30.10 via 192.168.20.1 dev eth1
169.254.0.0/16 dev eth1 scope link src 169.254.199.41 metric 1003
192.168.10.0/24 via 192.168.20.1 dev eth1
192.168.30.10 via 192.168.20.1 dev eth1
192.168.20.0/24 dev eth1 scope link src 192.168.20.10
192.168.30.0/24 via 192.168.20.1 dev eth1
192.168.30.10 via 192.168.20.1 dev eth1
```

H3 ip addr

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue qlen 1000
   link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
   inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
   inet6 ::1/128 scope host
       valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
   link/ether 52:54:00:aa:03:01 brd ff:ff:ff:ff:ff:ff
   inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0
       valid_lft 82336sec preferred_lft 71536sec
   inet6 fec0::5054:ff:feaa:301/64 scope site dynamic noprefixroute flags 100
       valid_lft 86292sec preferred_lft 14292sec
   inet6 fe80::5054:ff:feaa:301/64 scope link
       valid_lft forever preferred_lft forever
... 84 more lines
```

H3 ip route

```
default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.30.1 dev eth1
169.254.0.0/16 dev eth1 scope link src 169.254.207.242 metric 1003
192.168.10.0/24 via 192.168.30.1 dev eth1
192.168.20.0/24 via 192.168.30.1 dev eth1
192.168.30.0/24 dev eth1 scope link src 192.168.30.10
```

Teardown (suite) Close Nms, Close All Connections

5.12 PASS Every Router Routing Table Holds All Three LANs (0.2s, 3 commands)

A content check on what was just captured: in a working hub-and-spoke every router reaches every LAN, the spokes reaching each other's through the hub.

Setup (suite) Open All Routers, Open All Hosts, Open Nms

Acceptance criteria

- output contains **#{R1_LAN_NET}** (checked 3×)
- output contains **#{R2_LAN_NET}** (checked 3×)
- output contains **#{R3_LAN_NET}** (checked 3×)

How it was checked

R1 show ip route

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
& - replicated local route overrides by connected
```

Gateway of last resort is 10.0.2.2 to network 0.0.0.0
... 24 more lines

R2 show ip route

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
& - replicated local route overrides by connected
```

Gateway of last resort is 10.0.2.2 to network 0.0.0.0
... 24 more lines

R3 show ip route

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
& - replicated local route overrides by connected
```

Gateway of last resort is 10.0.2.2 to network 0.0.0.0
... 24 more lines

Teardown (suite) Close Nms, Close All Connections

06 Wire Encryption

6.01 PASS Protected Traffic Appears On The Link As ESP (15.7s, 9 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains **ESP**
- output matches `${R1_WAN_IP}\s+>\s+${R2_WAN_IP}`

How it was checked

R1 no monitor capture ROBOTCAP

Capture does not exist

R1 monitor capture ROBOTCAP interface GigabitEthernet2 both
\${output} =

R1 monitor capture ROBOTCAP match ipv4 any any
\${output} =

R1 monitor capture ROBOTCAP buffer size 5
\${output} =

R1 monitor capture ROBOTCAP start
Started capture point : ROBOTCAP

R1 ping 172.16.2.1 source Loopback0 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.2.1, timeout is 2 seconds:
Packet sent with a source address of 172.16.1.1
.....
Success rate is 0 percent (0/5)

R1 monitor capture ROBOTCAP stop
Stopped capture point : ROBOTCAP

R1 show monitor capture ROBOTCAP buffer brief

```
-----
#    size    timestamp      source          destination     dscp    protocol
-----
0  138      0.000000    100.64.0.1      -> 100.64.0.2     48 CS6   ESP
1  138      0.000992    100.64.0.2      -> 100.64.0.1     48 CS6   ESP
2  138      0.123986    100.64.0.1      -> 100.64.0.3     48 CS6   ESP
3  138      0.123986    100.64.0.3      -> 100.64.0.1     48 CS6   ESP
4  138      0.137993    100.64.0.1      -> 100.64.0.3     48 CS6   ESP
5  138      0.333982    100.64.0.2      -> 100.64.0.1     48 CS6   ESP
6  138      0.369036    100.64.0.3      -> 100.64.0.1     48 CS6   ESP
7  138      0.369036    100.64.0.1      -> 100.64.0.3     48 CS6   ESP
8  138      0.412033    100.64.0.2      -> 100.64.0.1     48 CS6   ESP
9  138      0.412033    100.64.0.1      -> 100.64.0.2     48 CS6   ESP
10 138      0.421035    100.64.0.1      -> 100.64.0.2     48 CS6   ESP
... 275 more lines
```

R1 no monitor capture ROBOTCAP
\${output} =

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, Close All Routers

6.02 PASS Protected Endpoint Addresses Never Appear In Cleartext On The Link (15.7s, 9 commands)

The strongest statement this lab can make about encryption: traffic between the loopbacks crosses the wire without either loopback address being visible, and with no cleartext ICMP.

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain `${R1_LOOPBACK}`
- output does not contain `${R2_LOOPBACK}`
- output does not contain **ICMP**

How it was checked

R1 no monitor capture ROBOTCAP
Capture does not exist

R1 monitor capture ROBOTCAP interface GigabitEthernet2 both

```

${output} =
R1 monitor capture ROBOTCAP match ipv4 any any
${output} =
R1 monitor capture ROBOTCAP buffer size 5
${output} =
R1 monitor capture ROBOTCAP start
Started capture point : ROBOTCAP
R1 ping 172.16.2.1 source Loopback0 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.2.1, timeout is 2 seconds:
Packet sent with a source address of 172.16.1.1
.....
Success rate is 0 percent (0/5)
R1 monitor capture ROBOTCAP stop
Stopped capture point : ROBOTCAP
R1 show monitor capture ROBOTCAP buffer brief
-----
#    size    timestamp      source          destination      dscp    protocol
-----
0  138      0.000000    100.64.0.3      -> 100.64.0.1      48 CS6   ESP
1  138      0.000000    100.64.0.1      -> 100.64.0.3      48 CS6   ESP
2  138      0.016998    100.64.0.1      -> 100.64.0.2      48 CS6   ESP
3  138      0.026000    100.64.0.1      -> 100.64.0.2      48 CS6   ESP
4  138      0.026992    100.64.0.2      -> 100.64.0.1      48 CS6   ESP
5  138      0.159996    100.64.0.1      -> 100.64.0.3      48 CS6   ESP
6  138      0.160988    100.64.0.3      -> 100.64.0.1      48 CS6   ESP
7  138      0.279985    100.64.0.2      -> 100.64.0.1      48 CS6   ESP
8  138      0.279985    100.64.0.1      -> 100.64.0.2      48 CS6   ESP
9  138      0.331984    100.64.0.3      -> 100.64.0.1      48 CS6   ESP
10 138      0.391978    100.64.0.3      -> 100.64.0.1      48 CS6   ESP
... 269 more lines
R1 no monitor capture ROBOTCAP
${output} =

```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, Close All Routers

6.03 PASS Unprotected Link Traffic Is Visible As Cleartext ICMP (2.5s, 9 commands)

Positive control for the capture itself. Without this, the absence asserted above could just mean the capture was broken.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **ICMP**
- output matches `${R1_WAN_IP}\s+->\s+${R2_WAN_IP}\s+\s+\s+\s+\s+ICMP`

How it was checked

```

R1 no monitor capture ROBOTCAP
Capture does not exist
R1 monitor capture ROBOTCAP interface GigabitEthernet2 both
${output} =
R1 monitor capture ROBOTCAP match ipv4 any any
${output} =
R1 monitor capture ROBOTCAP buffer size 5
${output} =
R1 monitor capture ROBOTCAP start
Started capture point : ROBOTCAP
R1 ping 100.64.0.2 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 100.64.0.2, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/1 ms
R1 monitor capture ROBOTCAP stop
Stopped capture point : ROBOTCAP
R1 show monitor capture ROBOTCAP buffer brief

```

```

-----
#    size    timestamp      source          destination      dscp    protocol
-----
0  138      0.000000    100.64.0.3      -> 100.64.0.1      48 CS6   ESP
1  138      0.000000    100.64.0.1      -> 100.64.0.3      48 CS6   ESP
2  114      0.020995    100.64.0.1      -> 100.64.0.2      0  BE    ICMP

```

```
3 114 0.020995 100.64.0.2 -> 100.64.0.1 0 BE ICMP
4 114 0.021987 100.64.0.1 -> 100.64.0.2 0 BE ICMP
5 114 0.022994 100.64.0.2 -> 100.64.0.1 0 BE ICMP
6 114 0.023986 100.64.0.1 -> 100.64.0.2 0 BE ICMP
7 114 0.023986 100.64.0.2 -> 100.64.0.1 0 BE ICMP
8 114 0.023986 100.64.0.1 -> 100.64.0.2 0 BE ICMP
9 114 0.024993 100.64.0.2 -> 100.64.0.1 0 BE ICMP
10 114 0.024993 100.64.0.1 -> 100.64.0.2 0 BE ICMP
... 54 more lines
```

R1 no monitor capture ROBOTCAP

`${output} =`

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, Close All Routers

07 Ipsec Negative

7.01 **PASS** IKEv2 Refuses To Establish With A Mismatched Pre-Shared Key (13.3s, 13 commands)

Proves authentication is actually enforced. Without this, a tunnel that accepted any peer would still pass suite 04.

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain **Success rate is 100 percent**
- output does not contain **READY**

How it was checked

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 crypto ikev2 keyring LAB-KR

#{output} =

R2 peer ANY

#{output} =

R2 pre-shared-key WrongKeyOnPurpose999

#{output} =

R2 end

#{output} =

R1 clear crypto sa

#{output} =

R1 clear crypto ikev2 sa

#{output} =

R2 clear crypto sa

#{output} =

R2 clear crypto ikev2 sa

#{output} =

R3 clear crypto sa

#{output} =

R3 clear crypto ikev2 sa

#{output} =

R1 ping 172.16.2.1 source Loopback0 repeat 5

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 172.16.2.1, timeout is 2 seconds:

Packet sent with a source address of 172.16.1.1

.....

Success rate is 0 percent (0/5)

R2 show crypto ikev2 sa

#{output} =

Teardown (suite) Restore Baseline Crypto, Close All Routers

7.02 **PASS** Tunnel Recovers Once The Correct Key Is Restored (14.3s, 13 commands)

Also guarantees the previous test cannot leave the lab broken.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **Success rate is 100 percent** (checked 2x)

How it was checked

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 crypto ikev2 keyring LAB-KR

#{output} =

R2 peer ANY

#{output} =

R2 pre-shared-key LabPreSharedKey123

#{output} =

R2 end

#{output} =

```

R1 clear crypto sa
${output} =
R1 clear crypto ikev2 sa
${output} =
R2 clear crypto sa
${output} =
R2 clear crypto ikev2 sa
${output} =
R3 clear crypto sa
${output} =
R3 clear crypto ikev2 sa
${output} =
R1 ping 10.20.2.1 source Loopback1 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.20.2.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.1.1
...!!
Success rate is 40 percent (2/5), round-trip min/avg/max = 1/1/1 ms
R1 ping 10.20.2.1 source Loopback1 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.20.2.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.1.1
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms

```

Teardown (suite) Restore Baseline Crypto, Close All Routers

7.03 PASS IPsec Rekeys And Traffic Still Flows Afterwards (96.1s, 37 commands)

Drops the SA lifetime to the 120s platform minimum, waits for the outbound SPI to rotate, then re-checks connectivity. Rekey is where real tunnels break.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **Success rate is 100 percent** (checked 3×)
 - **\${m}** is not empty (checked 10×)
 - **\${new}** differs from **\${old}** (checked 9×)
- SPI **\${new}** has not rotated yet

How it was checked

```

R1 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R1 crypto ipsec security-association lifetime seconds 120
Warning! Lifetime value of 120 sec is lower than the recommended optimum value of 900 sec
R1 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 crypto ipsec security-association lifetime seconds 120
Warning! Lifetime value of 120 sec is lower than the recommended optimum value of 900 sec
R2 end
${output} =
R3 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R3 crypto ipsec security-association lifetime seconds 120
Warning! Lifetime value of 120 sec is lower than the recommended optimum value of 900 sec
R3 end
${output} =
R1 clear crypto sa
${output} =
R1 clear crypto ikev2 sa
${output} =
R2 clear crypto sa
${output} =
R2 clear crypto ikev2 sa
${output} =

```

```

R3 clear crypto sa
${output} =

R3 clear crypto ikev2 sa
${output} =

R1 ping 10.20.2.1 source Loopback1 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.20.2.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.1.1
...!!
Success rate is 40 percent (2/5), round-trip min/avg/max = 1/1/1 ms

R1 ping 10.20.2.1 source Loopback1 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.20.2.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.1.1
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/1 ms

R1 show crypto ipsec sa
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

  protected vrf: (none)
  local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
  remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
  current_peer 100.64.0.2 port 500
    PERMIT, flags={origin_is_acl,}
    #pkts encaps: 68, #pkts encrypt: 68, #pkts digest: 68
    #pkts decaps: 69, #pkts decrypt: 69, #pkts verify: 69
    #pkts compressed: 0, #pkts decompressed: 0
    #pkts not compressed: 0, #pkts compr. failed: 0
    #pkts not decompressed: 0, #pkts decompress failed: 0
    #send errors 0, #recv errors 0
  ... 78 more lines

R1 show crypto ipsec sa
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

  protected vrf: (none)
  local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
  remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
  current_peer 100.64.0.2 port 500
    PERMIT, flags={origin_is_acl,}
    #pkts encaps: 68, #pkts encrypt: 68, #pkts digest: 68
    #pkts decaps: 69, #pkts decrypt: 69, #pkts verify: 69
    #pkts compressed: 0, #pkts decompressed: 0
    #pkts not compressed: 0, #pkts compr. failed: 0
    #pkts not decompressed: 0, #pkts decompress failed: 0
    #send errors 0, #recv errors 0
  ... 78 more lines

R1 show crypto ipsec sa
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

  protected vrf: (none)
  local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
  remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
  current_peer 100.64.0.2 port 500
    PERMIT, flags={origin_is_acl,}
    #pkts encaps: 133, #pkts encrypt: 133, #pkts digest: 133
    #pkts decaps: 131, #pkts decrypt: 131, #pkts verify: 131
    #pkts compressed: 0, #pkts decompressed: 0
    #pkts not compressed: 0, #pkts compr. failed: 0
    #pkts not decompressed: 0, #pkts decompress failed: 0
    #send errors 0, #recv errors 0
  ... 78 more lines

R1 show crypto ipsec sa
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

  protected vrf: (none)
  local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
  remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
  current_peer 100.64.0.2 port 500
    PERMIT, flags={origin_is_acl,}
    #pkts encaps: 192, #pkts encrypt: 192, #pkts digest: 192
    #pkts decaps: 191, #pkts decrypt: 191, #pkts verify: 191
    #pkts compressed: 0, #pkts decompressed: 0
    #pkts not compressed: 0, #pkts compr. failed: 0

```

```
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 251, #pkts encrypt: 251, #pkts digest: 251
#pkts decaps: 249, #pkts decrypt: 249, #pkts verify: 249
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 309, #pkts encrypt: 309, #pkts digest: 309
#pkts decaps: 309, #pkts decrypt: 309, #pkts verify: 309
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 369, #pkts encrypt: 369, #pkts digest: 369
#pkts decaps: 373, #pkts decrypt: 373, #pkts verify: 373
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 436, #pkts encrypt: 436, #pkts digest: 436
#pkts decaps: 434, #pkts decrypt: 434, #pkts verify: 434
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 495, #pkts encrypt: 495, #pkts digest: 495
#pkts decaps: 494, #pkts decrypt: 494, #pkts verify: 494
#pkts compressed: 0, #pkts decompressed: 0
```

```
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 550, #pkts encrypt: 550, #pkts digest: 550
#pkts decaps: 548, #pkts decrypt: 548, #pkts verify: 548
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R1 ping 10.20.2.1 source Loopback1 repeat 5

```
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.20.2.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.1.1
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/3 ms
```

R1 configure terminal

```
Enter configuration commands, one per line. End with CNTL/Z.
```

R1 no crypto ipsec security-association lifetime seconds 120

```
${output} =
```

R1 end

```
${output} =
```

R2 configure terminal

```
Enter configuration commands, one per line. End with CNTL/Z.
```

R2 no crypto ipsec security-association lifetime seconds 120

```
${output} =
```

R2 end

```
${output} =
```

R3 configure terminal

```
Enter configuration commands, one per line. End with CNTL/Z.
```

R3 no crypto ipsec security-association lifetime seconds 120

```
${output} =
```

R3 end

```
${output} =
```

Teardown (this test) Restore Default SA Lifetime

08 Management Api

8.01 PASS RESTCONF Reports The Same Hostname As The CLI (0.4s, 3 commands)

Setup (suite) Open All Routers, Create RESTCONF Sessions

Acceptance criteria

- output contains `${name}` (checked 3×)

How it was checked

```
R1 show running-config | include ^hostname
hostname c8000v-r1
```

```
R2 show running-config | include ^hostname
hostname c8000v-r2
```

```
R3 show running-config | include ^hostname
hostname c8000v-r3
```

Teardown (suite) Run Keyword And Ignore Error, Delete RESTCONF Loopback, Close All Routers

8.02 PASS RESTCONF Interface State Agrees With The CLI (0.1s, 1 commands)

Setup (suite) Open All Routers, Create RESTCONF Sessions

Acceptance criteria

- `${status}` equals up
- output matches `GigabitEthernet2` is `${R1_WAN_IP}` is YES is `IS` is `up` is `up`

How it was checked

```
R1 show ip interface brief GigabitEthernet2
```

Interface	IP-Address	OK?	Method	Status	Protocol
GigabitEthernet2	100.64.0.1	YES	TFTP	up	up

Teardown (suite) Run Keyword And Ignore Error, Delete RESTCONF Loopback, Close All Routers

8.03 PASS Config Pushed Over RESTCONF Appears In The CLI (0.3s, 1 commands)

Write path plus cross-check: RESTCONF and the CLI must be two views of one datastore, not two datastores.

Setup (suite) Open All Routers, Create RESTCONF Sessions

Acceptance criteria

- `${resp.status_code}` in (201, 204) holds
- output contains `${RC_LOOPBACK_IP}`

How it was checked

```
R1 show running-config interface Loopback200
Building configuration...

Current configuration : 68 bytes
!
interface Loopback200
 ip address 198.51.100.1 255.255.255.0
end
```

Teardown (suite) Run Keyword And Ignore Error, Delete RESTCONF Loopback, Close All Routers

8.04 PASS Config Deleted Over RESTCONF Disappears From The CLI (0.8s, 1 commands)

Runs after the PUT test, which creates the interface; a 404 here would mean the create silently failed.

Setup (suite) Open All Routers, Create RESTCONF Sessions

Acceptance criteria

- `${resp.status_code}` equals 204
- RESTCONF DELETE returned `${resp.status_code}`; expected 204 for the loopback created by the previous test
- output does not contain `${RC_LOOPBACK_IP}`

How it was checked

```
R1 show ip interface brief Loopback200
```

```
^  
% Invalid input detected at '^' marker.
```

Teardown (suite) Run Keyword And Ignore Error, Delete RESTCONF Loopback, Close All Routers

8.05 **PASS** NETCONF Reports The Same Hostname As The CLI (0.8s, 1 commands)

Setup (suite) Open All Routers, Create RESTCONF Sessions

Acceptance criteria

- `${name}` equals `${R1_NAME}`
- output contains `${name}`

How it was checked

```
R1 show running-config | include ^hostname  
hostname c8000v-r1
```

Teardown (suite) Run Keyword And Ignore Error, Delete RESTCONF Loopback, Close All Routers

8.06 **PASS** NETCONF Advertises The Expected Base Capabilities (0.5s, 0 commands)

IOS-XE does not list per-module URIs such as Cisco-IOS-XE-native in the hello; modules are exposed via yang-library. That the native model is usable is proven by the hostname test above, which queries the native namespace directly.

Setup (suite) Open All Routers, Create RESTCONF Sessions

Acceptance criteria

- `${hit}` is not empty (checked 3×)

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Run Keyword And Ignore Error, Delete RESTCONF Loopback, Close All Routers

09 Bgp

9.01 PASS BGP Sessions Are Established With The Expected Peer AS (0.1s, 4 commands)

The hub holds one session per spoke; each spoke holds exactly one.

Setup (suite) Establish BGP

Acceptance criteria

- output matches `${peer}\s+4\s+${peer_asn}(\s+ld+){5}\s+!S+\s+ld+` (checked 4x)

How it was checked

R1 show bgp ipv4 unicast summary

```
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 40, main routing table version 40
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
3 BGP route-map cache entries using 216 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5936 total bytes of memory
BGP activity 139/130 prefixes, 145/136 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:51:43.657 ago)
```

```
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines
```

R1 show bgp ipv4 unicast summary

```
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 40, main routing table version 40
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
3 BGP route-map cache entries using 216 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5936 total bytes of memory
BGP activity 139/130 prefixes, 145/136 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:51:43.692 ago)
```

```
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines
```

R2 show bgp ipv4 unicast summary

```
BGP router identifier 172.16.2.1, local AS number 65002
BGP table version is 70, main routing table version 70
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 64 bytes of memory
6 BGP community entries using 144 bytes of memory
6 BGP route-map cache entries using 432 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 6168 total bytes of memory
BGP activity 172/163 prefixes, 174/165 paths, scan interval 60 secs
31 networks peaked at 22:34:42 Sep 7 2026 UTC (00:51:00.728 ago)
```

```
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 1 more lines
```

R3 show bgp ipv4 unicast summary

```
BGP router identifier 172.16.3.1, local AS number 65003
BGP table version is 152, main routing table version 152
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 64 bytes of memory
6 BGP community entries using 144 bytes of memory
3 BGP route-map cache entries using 216 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5952 total bytes of memory
BGP activity 75/66 prefixes, 80/71 paths, scan interval 60 secs
9 networks peaked at 22:15:22 Sep 7 2026 UTC (01:10:20.761 ago)
```

```
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 1 more lines
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.02 **PASS** Each Spoke Learns The Other Spoke Prefix Through The Hub (0.1s, 2 commands)

The defining property of this topology: spokes never peer with each other, so R3's prefix can only reach R2 via the hub, and its AS path must show both hops.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **\${via}** (checked 2×)
- output matches **\${R1_ASN}|s+\${far_asn}** (checked 2×)

How it was checked

R2 show bgp ipv4 unicast 10.20.3.1

```
BGP routing table entry for 10.20.3.1/32, version 67
Paths: (1 available, best #1, table default)
  Not advertised to any peer
  Refresh Epoch 1
  65001 65003
    172.20.0.3 from 172.20.0.1 (172.16.1.1)
      Origin IGP, localpref 100, valid, external, best
      Community: 65003:1
      rx pathid: 0, tx pathid: 0x0
      Updated on Sep 7 2026 23:24:08 UTC
```

R3 show bgp ipv4 unicast 10.20.2.1

```
BGP routing table entry for 10.20.2.1/32, version 150
Paths: (1 available, best #1, table default)
  Not advertised to any peer
  Refresh Epoch 1
  65001 65002
    172.20.0.2 from 172.20.0.1 (172.16.1.1)
      Origin IGP, localpref 100, valid, external, best
      Community: 65002:1
      rx pathid: 0, tx pathid: 0x0
      Updated on Sep 7 2026 23:24:34 UTC
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.03 **PASS** Every Peer Is Configured With MD5 Authentication (0.4s, 3 commands)

The negative test below proves a wrong password is rejected; this proves no peer was left without one in the first place.

Setup (suite) Establish BGP

Acceptance criteria

- **\${remote}** is not empty (checked 3×)
 - **\${remote}** matches **\${secured}** exactly (checked 3×)
- msg=\${r}: neighbours **\${remote}** but only **\${secured}** carry a password

How it was checked

R1 show running-config | include ^ neighbor .* remote-as|^ neighbor .* password

```
neighbor 172.20.0.2 remote-as 65002
neighbor 172.20.0.2 password LabBgpSecret
neighbor 172.20.0.3 remote-as 65003
neighbor 172.20.0.3 password LabBgpSecret
```

R2 show running-config | include ^ neighbor .* remote-as|^ neighbor .* password

```
neighbor 172.20.0.1 remote-as 65001
neighbor 172.20.0.1 password LabBgpSecret
```

R3 show running-config | include ^ neighbor .* remote-as|^ neighbor .* password

```
neighbor 172.20.0.1 remote-as 65001
neighbor 172.20.0.1 password LabBgpSecret
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.04 **PASS** A BFD Session Is Up For Every BGP Peer (0.1s, 3 commands)

One BFD session per peer, on the tunnel the peer address lives on -- the hub therefore holds two.

Setup (suite) Establish BGP

Acceptance criteria

- output contains `${R2_TUNNEL_LOCAL}`
- output contains `${R3_TUNNEL_LOCAL}`
- output does not contain **Down** (checked 3×)
- output contains `${r}_TUNNEL_HUB` (checked 2×)

How it was checked

R1 show bfd neighbors

IPv4 Sessions				
NeighAddr	LD/RD	RH/RS	State	Int
172.20.0.2	4097/4102	Up	Up	Tu0
172.20.0.3	4098/4097	Up	Up	Tu0

R2 show bfd neighbors

IPv4 Sessions				
NeighAddr	LD/RD	RH/RS	State	Int
172.20.0.1	4102/4097	Up	Up	Tu0

R3 show bfd neighbors

IPv4 Sessions				
NeighAddr	LD/RD	RH/RS	State	Int
172.20.0.1	4097/4098	Up	Up	Tu0

Teardown (suite) Restore BGP Baseline, Close All Routers

9.05 PASS BGP Uses BFD For Fall-over On Every Peer (0.4s, 6 commands)

A BFD session that no protocol consumes would detect failures and change nothing, so this checks BGP is the registered client rather than just that BFD is running.

Setup (suite) Establish BGP

Acceptance criteria

- `${remote}` matches `${bfd}` exactly (checked 3×)
- msg=\${r}: neighbours \${remote} but only \${bfd} use BFD fall-over
- output does not contain **Down** (checked 3×)

How it was checked

R1 show running-config | include ^ neighbor .* remote-as|fall-over bfd

```
neighbor 172.20.0.2 remote-as 65002
neighbor 172.20.0.2 fall-over bfd
neighbor 172.20.0.3 remote-as 65003
neighbor 172.20.0.3 fall-over bfd
```

R1 show bfd neighbors client bgp

IPv4 Sessions				
NeighAddr	LD/RD	RH/RS	State	Int
172.20.0.2	4097/4102	Up	Up	Tu0
172.20.0.3	4098/4097	Up	Up	Tu0

R2 show running-config | include ^ neighbor .* remote-as|fall-over bfd

```
neighbor 172.20.0.1 remote-as 65001
neighbor 172.20.0.1 fall-over bfd
```

R2 show bfd neighbors client bgp

IPv4 Sessions				
NeighAddr	LD/RD	RH/RS	State	Int
172.20.0.1	4102/4097	Up	Up	Tu0

R3 show running-config | include ^ neighbor .* remote-as|fall-over bfd

```
neighbor 172.20.0.1 remote-as 65001
neighbor 172.20.0.1 fall-over bfd
```

R3 show bfd neighbors client bgp

IPv4 Sessions				
NeighAddr	LD/RD	RH/RS	State	Int
172.20.0.1	4097/4098	Up	Up	Tu0

Teardown (suite) Restore BGP Baseline, Close All Routers

9.06 PASS BFD Tears The Session Down Long Before The Hold Time (42.8s, 32 commands)

The test that makes BFD more than configuration. An ACL on the hub's tunnel drops only BFD control packets (UDP 3784 and 3785) and leaves BGP's TCP session untouched, so ordinary BGP liveness is unaffected. Without fall-over the session would survive until the 30s hold time expires; with it, BFD declares the peer down in about a second and BGP follows.

Setup (suite) Establish BGP

Acceptance criteria

- output matches `${peer}\s+4\s+${peer_asn}(\s+ld+){5}\s+ls+\s+ld+` (checked 4×)
- output does not match `^ld+$` (checked 3×)
- `${elapsed} < ${HOLD_TIME}` holds
- output contains **Known via "bgp** (checked 8×)

How it was checked

R1 show bgp ipv4 unicast summary

```
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 40, main routing table version 40
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
3 BGP route-map cache entries using 216 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5936 total bytes of memory
BGP activity 139/130 prefixes, 145/136 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:51:44.666 ago)
```

```
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines
```

R1 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R1 ip access-list extended BLOCK-BFD

```
${output} =
```

R1 deny udp any any eq 3784

```
${output} =
```

R1 deny udp any any eq 3785

```
${output} =
```

R1 permit ip any any

```
${output} =
```

R1 end

```
${output} =
```

R1 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R1 interface Tunnel0

```
${output} =
```

R1 ip access-group BLOCK-BFD in

```
${output} =
```

R1 end

```
${output} =
```

R1 show bgp ipv4 unicast summary | include 172.20.0.2

```
172.20.0.2      4      65002      17      19      40      0      0 00:01:35      3
```

R1 show bgp ipv4 unicast summary | include 172.20.0.2

```
172.20.0.2      4      65002      17      20      40      0      0 00:01:36      3
```

R1 show bgp ipv4 unicast summary | include 172.20.0.2

```
172.20.0.2      4      65002      0        0        1      0      0 00:00:00 Idle
```

R1 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R1 interface Tunnel0

```
${output} =
```

R1 no ip access-group BLOCK-BFD in

```
${output} =
```

R1 end

```
${output} =
```

R1 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R1 no ip access-list extended BLOCK-BFD

```

${output} =
R1 end
${output} =
R1 show bgp ipv4 unicast summary
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 46, main routing table version 46
3 network entries using 744 bytes of memory
3 path entries using 408 bytes of memory
1/1 BGP path/bestpath attribute entries using 296 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 1448 total bytes of memory
BGP activity 139/136 prefixes, 145/142 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:51:47.175 ago)

Neighbor      V          AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
172.20.0.2    4          65002      0       0        1    0   0 00:00:01 Idle
172.20.0.3    4          65003      0       0        1    0   0 00:00:00 Idle

R1 show bgp ipv4 unicast summary
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 49, main routing table version 49
6 network entries using 1488 bytes of memory
6 path entries using 816 bytes of memory
4/4 BGP path/bestpath attribute entries using 1184 bytes of memory
1 BGP AS-PATH entries using 24 bytes of memory
3 BGP community entries using 72 bytes of memory
3 BGP route-map cache entries using 216 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 3800 total bytes of memory
BGP activity 142/136 prefixes, 148/142 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:51:52.214 ago)

Neighbor      V          AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

R1 show bgp ipv4 unicast summary
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 52, main routing table version 52
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
6 BGP route-map cache entries using 432 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 6152 total bytes of memory
BGP activity 145/136 prefixes, 151/142 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:51:57.255 ago)

Neighbor      V          AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

R1 show ip route 10.20.2.1
Routing entry for 10.20.2.1/32
  Known via "bgp 65001", distance 20, metric 0
  Tag 65002, type external
  Last update from 172.20.0.2 00:00:05 ago
  Routing Descriptor Blocks:
    * 172.20.0.2, from 172.20.0.2, 00:00:05 ago
      opaque_ptr 0x747B4EAD51F8
      Route metric is 0, traffic share count is 1
      AS Hops 1
      Route tag 65002
      MPLS label: none

R3 show ip route 10.20.2.1
% Subnet not in table

R3 show ip route 10.20.2.1
% Subnet not in table

R3 show ip route 10.20.2.1
% Subnet not in table

R3 show ip route 10.20.2.1
% Subnet not in table

R3 show ip route 10.20.2.1
% Subnet not in table

R3 show ip route 10.20.2.1
% Subnet not in table

R3 show ip route 10.20.2.1
% Subnet not in table

```

```

Routing entry for 10.20.2.1/32
  Known via "bgp 65003", distance 20, metric 0
  Tag 65001, type external
  Last update from 172.20.0.2 00:00:05 ago
  Routing Descriptor Blocks:
    * 172.20.0.2, from 172.20.0.1, 00:00:05 ago
      opaque_ptr 0x75671E6AB998
      Route metric is 0, traffic share count is 1
      AS Hops 2
      Route tag 65001
      MPLS label: none

```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.07 PASS Every Peer Has An Outbound Route-map Over Per-class Prefix-lists (0.6s, 13 commands)

One prefix-list per prefix class, and a route-map clause per class so each can carry its own community. The clauses are the whitelist: the route-map's implicit deny is what stops anything unnamed being advertised.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **RM-OUT- $\{peer\}$** (checked 4×)
- output contains **PL-OWN- $\{cls\}$** (checked 9×)

How it was checked

```

R2 show running-config | include route-map RM-OUT-R2 out
neighbor 172.20.0.2 route-map RM-OUT-R2 out

```

```

R3 show running-config | include route-map RM-OUT-R3 out
neighbor 172.20.0.3 route-map RM-OUT-R3 out

```

```

R1 show ip prefix-list PL-OWN-L0
ip prefix-list PL-OWN-L0: 1 entries
seq 5 permit 10.20.1.1/32

```

```

R1 show ip prefix-list PL-OWN-NAT
ip prefix-list PL-OWN-NAT: 1 entries
seq 5 permit 10.30.1.0/24

```

```

R1 show ip prefix-list PL-OWN-LAN
ip prefix-list PL-OWN-LAN: 1 entries
seq 5 permit 192.168.10.0/24

```

```

R1 show running-config | include route-map RM-OUT-R1 out
neighbor 172.20.0.1 route-map RM-OUT-R1 out

```

```

R2 show ip prefix-list PL-OWN-L0
ip prefix-list PL-OWN-L0: 1 entries
seq 5 permit 10.20.2.1/32

```

```

R2 show ip prefix-list PL-OWN-NAT
ip prefix-list PL-OWN-NAT: 1 entries
seq 5 permit 10.30.2.0/24

```

```

R2 show ip prefix-list PL-OWN-LAN
ip prefix-list PL-OWN-LAN: 1 entries
seq 5 permit 192.168.20.0/24

```

```

R1 show running-config | include route-map RM-OUT-R1 out
neighbor 172.20.0.1 route-map RM-OUT-R1 out

```

```

R3 show ip prefix-list PL-OWN-L0
ip prefix-list PL-OWN-L0: 1 entries
seq 5 permit 10.20.3.1/32

```

```

R3 show ip prefix-list PL-OWN-NAT
ip prefix-list PL-OWN-NAT: 1 entries
seq 5 permit 10.30.3.0/24

```

```

R3 show ip prefix-list PL-OWN-LAN
ip prefix-list PL-OWN-LAN: 1 entries
seq 5 permit 192.168.30.0/24

```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.08 PASS Every Peer Has An Inbound Policy Matching Community And AS Path (0.6s, 11

commands)

Both matches sit in one permit clause, so they are ANDed and the clause's implicit deny is the drop: a prefix with an unknown community *or* an unexpected AS path falls through.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **RM-IN- $\{peer\}$** (checked 4×)
- output contains **community (community-list filter): CL-VALID** (checked 4×)
- output matches **as-path $\{as-path\}$ filter): $\{as-path\}$** (checked 4×)
- **$\{entries\}$** has exactly 9 entries (checked 3×)

How it was checked

R2 show running-config | include route-map RM-IN-R2 in
neighbor 172.20.0.2 route-map RM-IN-R2 in

R2 show route-map RM-IN-R2
route-map RM-IN-R2, permit, sequence 10
Match clauses:
as-path (as-path filter): 10
community (community-list filter): CL-VALID
Set clauses:
Policy routing matches: 0 packets, 0 bytes

R3 show running-config | include route-map RM-IN-R3 in
neighbor 172.20.0.3 route-map RM-IN-R3 in

R3 show route-map RM-IN-R3
route-map RM-IN-R3, permit, sequence 10
Match clauses:
as-path (as-path filter): 20
community (community-list filter): CL-VALID
Set clauses:
Policy routing matches: 0 packets, 0 bytes

R1 show ip community-list CL-VALID
Named Community standard list CL-VALID
permit 65001:1
permit 65001:2
permit 65001:3
permit 65002:1
permit 65002:2
permit 65002:3
permit 65003:1
permit 65003:2
permit 65003:3

R1 show running-config | include route-map RM-IN-R1 in
neighbor 172.20.0.1 route-map RM-IN-R1 in

R1 show route-map RM-IN-R1
route-map RM-IN-R1, permit, sequence 10
Match clauses:
as-path (as-path filter): 10
community (community-list filter): CL-VALID
Set clauses:
Policy routing matches: 0 packets, 0 bytes

R2 show ip community-list CL-VALID
Named Community standard list CL-VALID
permit 65001:1
permit 65001:2
permit 65001:3
permit 65002:1
permit 65002:2
permit 65002:3
permit 65003:1
permit 65003:2
permit 65003:3

R1 show running-config | include route-map RM-IN-R1 in
neighbor 172.20.0.1 route-map RM-IN-R1 in

R1 show route-map RM-IN-R1
route-map RM-IN-R1, permit, sequence 10
Match clauses:
as-path (as-path filter): 10
community (community-list filter): CL-VALID
Set clauses:

Policy routing matches: 0 packets, 0 bytes

R3 show ip community-list CL-VALID

```
Named Community standard list CL-VALID
permit 65001:1
permit 65001:2
permit 65001:3
permit 65002:1
permit 65002:2
permit 65002:3
permit 65003:1
permit 65003:2
permit 65003:3
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.09 PASS Every Received Prefix Carries The Community Of Its Origin (0.6s, 18 commands)

A prefix is tagged by the router that owns it, so the community identifies both the origin AS and the kind of prefix. Checked on the receiver, which is the only place it proves the tag survived the wire.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **\${expected}** (checked 18×)

How it was checked

R1 show bgp ipv4 unicast 10.20.2.1/32

```
BGP routing table entry for 10.20.2.1/32, version 52
Paths: (1 available, best #1, table default)
  Advertised to update-groups:
    33
  Refresh Epoch 1
  65002
    172.20.0.2 from 172.20.0.2 (172.16.2.1)
      Origin IGP, metric 0, localpref 100, valid, external, best
      Community: 65002:1
      rx pathid: 0, tx pathid: 0x0
      Updated on Sep 7 2026 23:25:51 UTC
```

R1 show bgp ipv4 unicast 10.20.3.1/32

```
BGP routing table entry for 10.20.3.1/32, version 49
Paths: (1 available, best #1, table default)
  Advertised to update-groups:
    34
  Refresh Epoch 1
  65003
    172.20.0.3 from 172.20.0.3 (172.16.3.1)
      Origin IGP, metric 0, localpref 100, valid, external, best
      Community: 65003:1
      rx pathid: 0, tx pathid: 0x0
      Updated on Sep 7 2026 23:25:50 UTC
```

R1 show bgp ipv4 unicast 10.30.2.0/24

```
BGP routing table entry for 10.30.2.0/24, version 51
Paths: (1 available, best #1, table default)
  Advertised to update-groups:
    33
  Refresh Epoch 1
  65002
    172.20.0.2 from 172.20.0.2 (172.16.2.1)
      Origin IGP, metric 0, localpref 100, valid, external, best
      Community: 65002:2
      rx pathid: 0, tx pathid: 0x0
      Updated on Sep 7 2026 23:25:51 UTC
```

R1 show bgp ipv4 unicast 10.30.3.0/24

```
BGP routing table entry for 10.30.3.0/24, version 48
Paths: (1 available, best #1, table default)
  Advertised to update-groups:
    34
  Refresh Epoch 1
  65003
    172.20.0.3 from 172.20.0.3 (172.16.3.1)
      Origin IGP, metric 0, localpref 100, valid, external, best
      Community: 65003:2
      rx pathid: 0, tx pathid: 0x0
      Updated on Sep 7 2026 23:25:50 UTC
```

R1 show bgp ipv4 unicast 192.168.20.0/24

BGP routing table entry for 192.168.20.0/24, version 50
Paths: (1 available, best #1, table default)
Advertised to update-groups:
33
Refresh Epoch 1
65002
172.20.0.2 from 172.20.0.2 (172.16.2.1)
Origin IGP, metric 0, localpref 100, valid, external, best
Community: 65002:3
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R1 show bgp ipv4 unicast 192.168.30.0/24

BGP routing table entry for 192.168.30.0/24, version 47
Paths: (1 available, best #1, table default)
Advertised to update-groups:
34
Refresh Epoch 1
65003
172.20.0.3 from 172.20.0.3 (172.16.3.1)
Origin IGP, metric 0, localpref 100, valid, external, best
Community: 65003:3
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:50 UTC

R2 show bgp ipv4 unicast 10.20.1.1/32

BGP routing table entry for 10.20.1.1/32, version 79
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001
172.20.0.1 from 172.20.0.1 (172.16.1.1)
Origin IGP, metric 0, localpref 100, valid, external, best
Community: 65001:1
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R2 show bgp ipv4 unicast 10.20.3.1/32

BGP routing table entry for 10.20.3.1/32, version 80
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001 65003
172.20.0.3 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65003:1
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R2 show bgp ipv4 unicast 10.30.1.0/24

BGP routing table entry for 10.30.1.0/24, version 78
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001
172.20.0.1 from 172.20.0.1 (172.16.1.1)
Origin IGP, metric 0, localpref 100, valid, external, best
Community: 65001:2
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R2 show bgp ipv4 unicast 10.30.3.0/24

BGP routing table entry for 10.30.3.0/24, version 81
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001 65003
172.20.0.3 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65003:2
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R2 show bgp ipv4 unicast 192.168.10.0/24

BGP routing table entry for 192.168.10.0/24, version 77
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001
172.20.0.1 from 172.20.0.1 (172.16.1.1)
Origin IGP, metric 0, localpref 100, valid, external, best
Community: 65001:3
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R2 show bgp ipv4 unicast 192.168.30.0/24

BGP routing table entry for 192.168.30.0/24, version 82
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001 65003
172.20.0.3 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65003:3
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R3 show bgp ipv4 unicast 10.20.1.1/32

BGP routing table entry for 10.20.1.1/32, version 161
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001
172.20.0.1 from 172.20.0.1 (172.16.1.1)
Origin IGP, metric 0, localpref 100, valid, external, best
Community: 65001:1
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:50 UTC

R3 show bgp ipv4 unicast 10.20.2.1/32

BGP routing table entry for 10.20.2.1/32, version 162
Paths: (1 available, best #1, table default)
Flag: 0x8100
Not advertised to any peer
Refresh Epoch 1
65001 65002
172.20.0.2 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65002:1
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:26:21 UTC

R3 show bgp ipv4 unicast 10.30.1.0/24

BGP routing table entry for 10.30.1.0/24, version 160
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001
172.20.0.1 from 172.20.0.1 (172.16.1.1)
Origin IGP, metric 0, localpref 100, valid, external, best
Community: 65001:2
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:50 UTC

R3 show bgp ipv4 unicast 10.30.2.0/24

BGP routing table entry for 10.30.2.0/24, version 163
Paths: (1 available, best #1, table default)
Flag: 0x8100
Not advertised to any peer
Refresh Epoch 1
65001 65002
172.20.0.2 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65002:2
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:26:21 UTC

R3 show bgp ipv4 unicast 192.168.10.0/24

BGP routing table entry for 192.168.10.0/24, version 159
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001
172.20.0.1 from 172.20.0.1 (172.16.1.1)
Origin IGP, metric 0, localpref 100, valid, external, best
Community: 65001:3
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:50 UTC

R3 show bgp ipv4 unicast 192.168.20.0/24

BGP routing table entry for 192.168.20.0/24, version 164
Paths: (1 available, best #1, table default)
Flag: 0x8100
Not advertised to any peer
Refresh Epoch 1
65001 65002
172.20.0.2 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65002:3

rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:26:21 UTC

Teardown (suite) Restore BGP Baseline, Close All Routers

9.10 PASS Re-advertised Prefixes Keep Their Origin Community Through The Hub (0.1s, 4 commands)

A spoke-to-spoke prefix crosses the hub, which re-advertises it. If the hub re-tagged it the community would say 65001 and the origin would be lost, so this asserts the far spoke's own community survives the hop.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **\${expected}** (checked 4x)

How it was checked

R2 show bgp ipv4 unicast 10.20.3.1/32

BGP routing table entry for 10.20.3.1/32, version 80
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001 65003
172.20.0.3 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65003:1
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R2 show bgp ipv4 unicast 192.168.30.0/24

BGP routing table entry for 192.168.30.0/24, version 82
Paths: (1 available, best #1, table default)
Not advertised to any peer
Refresh Epoch 1
65001 65003
172.20.0.3 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65003:3
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:25:51 UTC

R3 show bgp ipv4 unicast 10.20.2.1/32

BGP routing table entry for 10.20.2.1/32, version 162
Paths: (1 available, best #1, table default)
Flag: 0x8100
Not advertised to any peer
Refresh Epoch 1
65001 65002
172.20.0.2 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65002:1
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:26:21 UTC

R3 show bgp ipv4 unicast 192.168.20.0/24

BGP routing table entry for 192.168.20.0/24, version 164
Paths: (1 available, best #1, table default)
Flag: 0x8100
Not advertised to any peer
Refresh Epoch 1
65001 65002
172.20.0.2 from 172.20.0.1 (172.16.1.1)
Origin IGP, localpref 100, valid, external, best
Community: 65002:3
rx pathid: 0, tx pathid: 0x0
Updated on Sep 7 2026 23:26:21 UTC

Teardown (suite) Restore BGP Baseline, Close All Routers

9.11 PASS A Prefix With An Unknown Community Is Rejected Inbound (26.0s, 40 commands)

*The prefix is explicitly permitted *outbound* by a temporary clause, so the outbound whitelist cannot be what stops it -- only the inbound community match can. The test asserts R2 really did advertise it before asserting R1 refused it, otherwise it would pass whenever the advertisement failed.*

Setup (suite) Establish BGP

Acceptance criteria

- output contains **#{BAD_COMM_ADDR}** (checked 6×)
R2 is not yet advertising the test prefix
- output contains **#{BAD_COMM_ADDR}**
R2 never advertised the prefix, so this proves nothing about the inbound policy
- output contains **Network not in table**
the hub accepted a prefix carrying community **#{UNKNOWN_COMM}**

How it was checked

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 interface Loopback98

#{output} =

R2 ip address 10.88.88.88 255.255.255.255

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 ip prefix-list PL-TEST seq 5 permit 10.88.88.88/32

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 route-map RM-OUT-R1 permit 5

#{output} =

R2 match ip address prefix-list PL-TEST

#{output} =

R2 set community 65500:9

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 router bgp 65002

#{output} =

R2 address-family ipv4 unicast

#{output} =

R2 network 10.88.88.88 mask 255.255.255.255

#{output} =

R2 end

#{output} =

R2 clear ip bgp * soft out

#{output} =

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 82, local router ID is 172.16.2.1

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,

Origin codes: i - IGP, e - EGP, ? - incomplete

RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0		0	32768	i
*>	10.30.2.0/24	0.0.0.0		0	32768	i
*>	192.168.20.0	0.0.0.0		0	32768	i

Total number of prefixes 3

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 83, local router ID is 172.16.2.1

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,

Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

Total number of prefixes 3

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 83, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

Total number of prefixes 3

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 83, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

Total number of prefixes 3

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 83, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

Total number of prefixes 3

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 83, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	10.88.88.88/32	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

... 1 more lines

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 83, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
--	---------	----------	--------	--------	--------	------

```
*> 10.20.2.1/32      0.0.0.0      0      32768 i
*> 10.30.2.0/24      0.0.0.0      0      32768 i
*> 10.88.88.88/32    0.0.0.0      0      32768 i
*> 192.168.20.0      0.0.0.0      0      32768 i
```

... 1 more lines

R1 show bgp ipv4 unicast 10.88.88.88

% Network not in table

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 router bgp 65002

#{output} =

R2 address-family ipv4 unicast

#{output} =

R2 no network 10.88.88.88 mask 255.255.255.255

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 no route-map RM-OUT-R1 permit 5

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 no ip prefix-list PL-TEST

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 no interface Loopback98

#{output} =

R2 end

#{output} =

Teardown (this test) Remove Test Prefix From R2

9.12 PASS Every Peer Has A Maximum-prefix Limit With Headroom (0.5s, 6 commands)

Filtering controls what a peer may send; this controls how much. The limit must sit above normal load or it would trip in steady state -- a hub holds 3 prefixes per spoke, a spoke 6 -- and far below anything that could exhaust memory.

Setup (suite) Establish BGP

Acceptance criteria

- **#{remote}** matches **#{limited}** exactly (checked 3×)
msg=#{r}: neighbours #{remote} but only #{limited} have a maximum-prefix
- **#{n} < #{MAX_PREFIX}** holds (checked 3×)

How it was checked

R1 show running-config | include ^ neighbor .* remote-as|maximum-prefix

```
neighbor 172.20.0.2 remote-as 65002
neighbor 172.20.0.3 remote-as 65003
neighbor 172.20.0.2 maximum-prefix 15 80
neighbor 172.20.0.3 maximum-prefix 15 80
```

R1 show bgp ipv4 unicast summary | begin Neighbor

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
172.20.0.2	4	65002	18	16	52	0	0	00:01:02	3
172.20.0.3	4	65003	13	16	52	0	0	00:01:03	3

R2 show running-config | include ^ neighbor .* remote-as|maximum-prefix

```
neighbor 172.20.0.1 remote-as 65001
neighbor 172.20.0.1 maximum-prefix 15 80
```

R2 show bgp ipv4 unicast summary | begin Neighbor

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
172.20.0.1	4	65001	16	18	83	0	0	00:01:02	6

```
R3 show running-config | include ^ neighbor .* remote-as|maximum-prefix
neighbor 172.20.0.1 remote-as 65001
neighbor 172.20.0.1 maximum-prefix 15 80

R3 show bgp ipv4 unicast summary | begin Neighbor
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
172.20.0.1    4      65001    16     13    164    0   0 00:01:03      6
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.13 PASS A Peer That Floods Prefixes Is Torn Down Rather Than Absorbed (37.0s, 344 commands)

R2 originates 20 extra prefixes, tagged with a valid community and carrying a valid AS path, and explicitly permitted outbound -- so neither the whitelist, the community match nor the AS-path filter can be what stops them. Only the prefix count is left. The hub must drop the session instead of accepting an unbounded table.

Setup (suite) Establish BGP

Acceptance criteria

- output does not match `^ld+$` (checked 7×)
- output contains **PfxCt**
the session went down, but not because of the prefix count: `$(state)`
- output contains `$(R2_TUNNEL_LOCAL)`
the hub logged no maximum-prefix violation for `$(R2_TUNNEL_LOCAL)`

How it was checked

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

```
R2 ip prefix-list PL-FLOOD seq 5 permit 10.99.0.0/16 le 32
${output} =
```

```
R2 end
${output} =
```

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

```
R2 route-map RM-OUT-R1 permit 7
${output} =

R2 match ip address prefix-list PL-FLOOD
${output} =
```

```
R2 set community 65002:1
${output} =
```

```
R2 end
${output} =
```

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

```
R2 ip route 10.99.0.0 255.255.255.0 Null0
${output} =
```

```
R2 end
${output} =
```

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

```
R2 ip route 10.99.1.0 255.255.255.0 Null0
${output} =
```

```
R2 end
${output} =
```

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

```
R2 ip route 10.99.2.0 255.255.255.0 Null0
${output} =
```

```
R2 end
${output} =
```

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

```
R2 ip route 10.99.3.0 255.255.255.0 Null0
${output} =
```

```
R2 end
```

```

    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.4.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.5.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.6.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.7.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.8.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.9.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.10.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.11.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.12.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.13.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.14.0 255.255.255.0 Null0
    ${output} =

```

```

R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.15.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.16.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.17.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.18.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 ip route 10.99.19.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.0.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.1.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.2.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002

```

```

    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.3.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.4.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.5.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.6.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.7.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.8.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.9.0 mask 255.255.255.0
    ${output} =

```

```

R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.10.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.11.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.12.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.13.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.14.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 network 10.99.15.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002

```

```

    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.16.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.17.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.18.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 network 10.99.19.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R1 show bgp ipv4 unicast summary | include 172.20.0.2
172.20.0.2      4      65002      18      17      52      0      0 00:01:06      3
R1 show bgp ipv4 unicast summary | include 172.20.0.2
172.20.0.2      4      65002      19      17      52      0      0 00:01:11      3
R1 show bgp ipv4 unicast summary | include 172.20.0.2
172.20.0.2      4      65002      19      18      52      0      0 00:01:16      3
R1 show bgp ipv4 unicast summary | include 172.20.0.2
172.20.0.2      4      65002      20      18      52      0      0 00:01:21      3
R1 show bgp ipv4 unicast summary | include 172.20.0.2
172.20.0.2      4      65002      20      19      52      0      0 00:01:26      3
R1 show bgp ipv4 unicast summary | include 172.20.0.2
172.20.0.2      4      65002      21      19      52      0      0 00:01:31      3
R1 show bgp ipv4 unicast summary | include 172.20.0.2
172.20.0.2      4      65002      0       0       1      0      0 00:00:04 Idle (PfxCt)
R1 show bgp ipv4 unicast summary | include 172.20.0.2
172.20.0.2      4      65002      0       0       1      0      0 00:00:04 Idle (PfxCt)
R1 show logging | include MAXPFEXCEED
000408: Sep  7 22:33:59.581 UTC: %BGP-3-MAXPFEXCEED: Number of prefixes received from 172.20.0.2 1/1
(afi/safi): 16 exceeds limit 15
000748: Sep  7 23:03:35.410 UTC: %BGP-3-MAXPFEXCEED: Number of prefixes received from 172.20.0.2 1/1
(afi/safi): 16 exceeds limit 15
001152: Sep  7 23:27:24.049 UTC: %BGP-3-MAXPFEXCEED: Number of prefixes received from 172.20.0.2 1/1
(afi/safi): 16 exceeds limit 15
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =

```

```

R2 no network 10.99.0.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.0.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 no network 10.99.1.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.1.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 no network 10.99.2.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.2.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 no network 10.99.3.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.3.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 no network 10.99.4.0 mask 255.255.255.0

```

```

    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.4.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 no network 10.99.5.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.5.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 no network 10.99.6.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.6.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 no network 10.99.7.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.7.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 no network 10.99.8.0 mask 255.255.255.0
    ${output} =

```

```

R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line.  End with CNTL/Z.
R2 no ip route 10.99.8.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line.  End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 no network 10.99.9.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line.  End with CNTL/Z.
R2 no ip route 10.99.9.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line.  End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 no network 10.99.10.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line.  End with CNTL/Z.
R2 no ip route 10.99.10.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line.  End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 no network 10.99.11.0 mask 255.255.255.0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line.  End with CNTL/Z.
R2 no ip route 10.99.11.0 255.255.255.0 Null0
  ${output} =
R2 end
  ${output} =
R2 configure terminal
  Enter configuration commands, one per line.  End with CNTL/Z.
R2 router bgp 65002
  ${output} =
R2 address-family ipv4 unicast
  ${output} =
R2 no network 10.99.12.0 mask 255.255.255.0
  ${output} =
R2 end

```

```

    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.12.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 no network 10.99.13.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.13.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 no network 10.99.14.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.14.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 no network 10.99.15.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.15.0 255.255.255.0 Null0
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
    ${output} =
R2 address-family ipv4 unicast
    ${output} =
R2 no network 10.99.16.0 mask 255.255.255.0
    ${output} =
R2 end
    ${output} =

```

```

R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.16.0 255.255.255.0 Null0
${output} =
R2 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
${output} =
R2 address-family ipv4 unicast
${output} =
R2 no network 10.99.17.0 mask 255.255.255.0
${output} =
R2 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.17.0 255.255.255.0 Null0
${output} =
R2 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
${output} =
R2 address-family ipv4 unicast
${output} =
R2 no network 10.99.18.0 mask 255.255.255.0
${output} =
R2 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.18.0 255.255.255.0 Null0
${output} =
R2 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 router bgp 65002
${output} =
R2 address-family ipv4 unicast
${output} =
R2 no network 10.99.19.0 mask 255.255.255.0
${output} =
R2 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip route 10.99.19.0 255.255.255.0 Null0
${output} =
R2 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 no route-map RM-OUT-R1 permit 7
${output} =
R2 end
${output} =
R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
R2 no ip prefix-list PL-FLOOD
${output} =
R2 end

```

```

${output} =
R1 clear ip bgp 172.20.0.2
${output} =

```

Teardown (this test) Stop Flooding From R2

9.14 PASS The Session Recovers Once The Flood Stops (25.2s, 8 commands)

A maximum-prefix teardown is deliberately sticky -- no "restart" is configured -- so recovery takes an operator clearing it. This asserts the lab returns to a converged state rather than leaving the next suite a broken topology.

Setup (suite) Establish BGP

Acceptance criteria

- output matches `${peer}ls+4ls+${peer_asn}(ls+ld+){5}ls+S+ls+ld+` (checked 2×)
- output contains **Known via "bgp"** (checked 6×)

How it was checked

R1 show bgp ipv4 unicast summary

```

BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 79, main routing table version 79
6 network entries using 1488 bytes of memory
6 path entries using 816 bytes of memory
8/4 BGP path/bestpath attribute entries using 2368 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
7 BGP community entries using 168 bytes of memory
7 BGP route-map cache entries using 504 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5392 total bytes of memory
BGP activity 158/152 prefixes, 164/158 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:53:32.901 ago)

```

```

Neighbor          V      AS MsgRcvd MsgSent   TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

```

R1 show bgp ipv4 unicast summary

```

BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 82, main routing table version 82
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
8/7 BGP path/bestpath attribute entries using 2368 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
7 BGP community entries using 168 bytes of memory
7 BGP route-map cache entries using 504 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 6544 total bytes of memory
BGP activity 161/152 prefixes, 167/158 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:53:37.936 ago)

```

```

Neighbor          V      AS MsgRcvd MsgSent   TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

```

R1 show ip route 10.20.2.1

```

Routing entry for 10.20.2.1/32
  Known via "bgp 65001", distance 20, metric 0
  Tag 65002, type external
  Last update from 172.20.0.2 00:00:00 ago
  Routing Descriptor Blocks:
    * 172.20.0.2, from 172.20.0.2, 00:00:00 ago
      opaque_ptr 0x747B4EAD51F8
      Route metric is 0, traffic share count is 1
      AS Hops 1
      Route tag 65002
      MPLS label: none

```

R3 show ip route 10.20.2.1

```
% Subnet not in table
```

R3 show ip route 10.20.2.1

```
% Subnet not in table
```

R3 show ip route 10.20.2.1

```
% Subnet not in table
```

R3 show ip route 10.20.2.1

```
% Subnet not in table
```

R3 show ip route 10.20.2.1

```

Routing entry for 10.20.2.1/32
  Known via "bgp 65003", distance 20, metric 0

```

```

Tag 65001, type external
Last update from 172.20.0.2 00:00:03 ago
Routing Descriptor Blocks:
* 172.20.0.2, from 172.20.0.1, 00:00:03 ago
  opaque_ptr 0x75671E6AB998
  Route metric is 0, traffic share count is 1
  AS Hops 2
  Route tag 65001
  MPLS label: none

```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.15 PASS A Prefix With An Invalid AS Path Is Rejected Inbound (10.8s, 38 commands)

Same prefix, this time with a valid community but an AS path this topology cannot produce. Only the AS-path match differs, so a rejection here isolates that filter.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **#{BAD_COMM_ADDR}** (checked 3×)
R2 is not yet advertising the test prefix
- output contains **#{BAD_COMM_ADDR}**
R2 never advertised the prefix, so this proves nothing about the inbound policy
- output contains **Network not in table**
the hub accepted a prefix whose AS path contained **#{BOGUS_AS}**

How it was checked

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 interface Loopback98

#{output} =

R2 ip address 10.88.88.88 255.255.255.255

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 ip prefix-list PL-TEST seq 5 permit 10.88.88.88/32

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 route-map RM-OUT-R1 permit 5

#{output} =

R2 match ip address prefix-list PL-TEST

#{output} =

R2 set community 65002:1

#{output} =

R2 set as-path prepend 65099

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 router bgp 65002

#{output} =

R2 address-family ipv4 unicast

#{output} =

R2 network 10.88.88.88 mask 255.255.255.255

#{output} =

R2 end

#{output} =

R2 clear ip bgp * soft out

#{output} =

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 136, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

Total number of prefixes 3

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 137, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

Total number of prefixes 3

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 137, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	10.88.88.88/32	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

... 1 more lines

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 137, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	10.88.88.88/32	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

... 1 more lines

R1 show bgp ipv4 unicast 10.88.88.88

% Network not in table

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 router bgp 65002

#{output} =

R2 address-family ipv4 unicast

#{output} =

R2 no network 10.88.88.88 mask 255.255.255.255

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

```

R2 no route-map RM-OUT-R1 permit 5
   ${output} =
R2 end
   ${output} =
R2 configure terminal
   Enter configuration commands, one per line.  End with CNTL/Z.
R2 no ip prefix-list PL-TEST
   ${output} =
R2 end
   ${output} =
R2 configure terminal
   Enter configuration commands, one per line.  End with CNTL/Z.
R2 no interface Loopback98
   ${output} =
R2 end
   ${output} =

```

Teardown (this test) Remove Test Prefix From R2

9.16 PASS Each Peer Is Advertised Exactly Its Whitelisted Prefixes (0.3s, 4 commands)

Not "at least" -- exactly. A whitelist that permits more than intended still passes a containment check, so the advertised set is compared for equality against what the peer should get: a spoke sends only its own prefixes, the hub sends its own plus the far spoke's.

Setup (suite) Establish BGP

Acceptance criteria

- **\${actual}** matches **\${expected}** exactly (checked 4×)
- msg=\${from} advertises \${actual} to \${to}, expected \${expected}

How it was checked

R2 show bgp ipv4 unicast neighbors 172.20.0.2 advertised-routes

BGP table version is 82, local router ID is 172.16.1.1
 Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
 r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
 x best-external, a additional-path, c RIB-compressed,
 t secondary path, L long-lived-stale,
 Origin codes: i - IGP, e - EGP, ? - incomplete
 RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.1.1/32	0.0.0.0	0		32768	i
*>	10.20.3.1/32	172.20.0.3	0		0 65003	i
*>	10.30.1.0/24	0.0.0.0	0		32768	i
*>	10.30.3.0/24	172.20.0.3	0		0 65003	i
*>	192.168.10.0	0.0.0.0	0		32768	i

... 3 more lines

R3 show bgp ipv4 unicast neighbors 172.20.0.3 advertised-routes

BGP table version is 82, local router ID is 172.16.1.1
 Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
 r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
 x best-external, a additional-path, c RIB-compressed,
 t secondary path, L long-lived-stale,
 Origin codes: i - IGP, e - EGP, ? - incomplete
 RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.1.1/32	0.0.0.0	0		32768	i
*>	10.20.2.1/32	172.20.0.2	0		0 65002	i
*>	10.30.1.0/24	0.0.0.0	0		32768	i
*>	10.30.2.0/24	172.20.0.2	0		0 65002	i
*>	192.168.10.0	0.0.0.0	0		32768	i

... 3 more lines

R1 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 138, local router ID is 172.16.2.1
 Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
 r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
 x best-external, a additional-path, c RIB-compressed,
 t secondary path, L long-lived-stale,
 Origin codes: i - IGP, e - EGP, ? - incomplete
 RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.2.1/32	0.0.0.0	0		32768	i
*>	10.30.2.0/24	0.0.0.0	0		32768	i
*>	192.168.20.0	0.0.0.0	0		32768	i

Total number of prefixes 3

R1 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

BGP table version is 170, local router ID is 172.16.3.1

Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,

Origin codes: i - IGP, e - EGP, ? - incomplete

RPKI validation codes: V valid, I invalid, N Not found

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.3.1/32	0.0.0.0	0		32768	i
*>	10.30.3.0/24	0.0.0.0	0		32768	i
*>	192.168.30.0	0.0.0.0	0		32768	i

Total number of prefixes 3

Teardown (suite) Restore BGP Baseline, Close All Routers

9.17 PASS A Prefix Outside The Whitelist Is Not Advertised (10.5s, 20 commands)

The point of a whitelist. A spoke originates a prefix nobody authorised; it appears in that spoke's own BGP table, so the origination worked, and must still never reach the hub.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **\${OFF_LIST_ADDR}**
R2 never originated the prefix, so this test proves nothing
- output does not contain **\${OFF_LIST_ADDR}/32**
R2 advertised an unlisted prefix to the hub
- output contains **Network not in table**
an unlisted prefix reached the hub

How it was checked

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 interface Loopback99

\${output} =

R2 ip address 10.77.77.77 255.255.255.255

\${output} =

R2 end

\${output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 router bgp 65002

\${output} =

R2 address-family ipv4 unicast

\${output} =

R2 network 10.77.77.77 mask 255.255.255.255

\${output} =

R2 end

\${output} =

R2 show bgp ipv4 unicast 10.77.77.77

BGP routing table entry for 10.77.77.77/32, version 139

Paths: (1 available, best #1, table default)

Flag: 0x8100

Not advertised to any peer

Refresh Epoch 1

Local

0.0.0.0 from 0.0.0.0 (172.16.2.1)

Origin IGP, metric 0, localpref 100, weight 32768, valid, sourced, local, best

rx pathid: 0, tx pathid: 0x0

Updated on Sep 7 2026 23:28:10 UTC

R2 show bgp ipv4 unicast neighbors 172.20.0.1 advertised-routes

```

BGP table version is 139, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
               x best-external, a additional-path, c RIB-compressed,
               t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

```

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 10.20.2.1/32	0.0.0.0	0		32768	i
*> 10.30.2.0/24	0.0.0.0	0		32768	i
*> 192.168.20.0	0.0.0.0	0		32768	i

Total number of prefixes 3

R1 show bgp ipv4 unicast 10.77.77.77

% Network not in table

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 router bgp 65002

#{output} =

R2 address-family ipv4 unicast

#{output} =

R2 no network 10.77.77.77 mask 255.255.255.255

#{output} =

R2 end

#{output} =

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 no interface Loopback99

#{output} =

R2 end

#{output} =

Teardown (suite) Restore BGP Baseline, Close All Routers

9.18 PASS Each Router Receives The Peer Prefix (0.1s, 2 commands)

Setup (suite) Establish BGP

Acceptance criteria

- output matches `!*>ls+#{R2_BGP_PREFIX}/32ls+#{R2_TUNNEL_LOCAL}`
- output contains `#{R2_ASN}`
- output matches `!*>ls+#{R1_BGP_PREFIX}/32ls+#{R2_TUNNEL_HUB}`
- output contains `#{R1_ASN}`

How it was checked

R1 show bgp ipv4 unicast

```

BGP table version is 82, local router ID is 172.16.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
               x best-external, a additional-path, c RIB-compressed,
               t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

```

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 10.20.1.1/32	0.0.0.0	0		32768	i
*> 10.20.2.1/32	172.20.0.2	0		0	65002 i
*> 10.20.3.1/32	172.20.0.3	0		0	65003 i
*> 10.30.1.0/24	0.0.0.0	0		32768	i
*> 10.30.2.0/24	172.20.0.2	0		0	65002 i

... 4 more lines

R2 show bgp ipv4 unicast

```

BGP table version is 140, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
               x best-external, a additional-path, c RIB-compressed,
               t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

```

Network	Next Hop	Metric	LocPrf	Weight	Path
---------	----------	--------	--------	--------	------

```
*> 10.20.1.1/32      172.20.0.1      0      0 65001 i
*> 10.20.2.1/32      0.0.0.0          0      32768 i
*> 10.20.3.1/32      172.20.0.3      0      0 65001 65003 i
*> 10.30.1.0/24      172.20.0.1      0      0 65001 i
*> 10.30.2.0/24      0.0.0.0          0      32768 i
... 4 more lines
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.19 **PASS** Peer Prefix Is Learned Via BGP And Not A Static Route (0.0s, 1 commands)

Distinguishes a genuinely BGP-installed route from one that merely happens to exist. eBGP is distance 20; a static is 1.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **Known via "bgp \${R1_ASN}"**
- output contains **distance 20**
- output contains **type external**

How it was checked

R1 `show ip route 10.20.2.1`

```
Routing entry for 10.20.2.1/32
  Known via "bgp 65001", distance 20, metric 0
  Tag 65002, type external
  Last update from 172.20.0.2 00:00:42 ago
  Routing Descriptor Blocks:
  * 172.20.0.2, from 172.20.0.2, 00:00:42 ago
    opaque_ptr 0x747B4EAD51F8
    Route metric is 0, traffic share count is 1
    AS Hops 1
    Route tag 65002
    MPLS label: none
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.20 **PASS** BGP Route Resolves Out The Encrypted Tunnel (0.0s, 1 commands)

The next hop is a tunnel address, so the forwarding path must recurse to Tunnel0 rather than the cleartext link.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **\${R2_TUNNEL_LOCAL}**
- output contains **Tunnel0**

How it was checked

R1 `show ip cef 10.20.2.1`

```
10.20.2.1/32
  nexthop 172.20.0.2 Tunnel0
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.21 **PASS** Traffic Over The BGP-Learned Route Reaches The Peer (0.0s, 1 commands)

End to end: this only succeeds because BGP installed the route.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **Success rate is 100 percent**

How it was checked

R1 `ping 10.20.2.1 source Loopback1 repeat 5`

```
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.20.2.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.1.1
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
```

9.22 PASS BGP-Routed Traffic Is Encrypted (5.7s, 7 commands)

Setup (suite) Establish BGP

Acceptance criteria

- output contains **Success rate is 100 percent**
- **\${r1_enc} >= \${expected}** holds (checked 2×)
- **\${r1_dec} >= \${expected}** holds (checked 2×)
- **\${r2_enc} >= \${expected}** holds (checked 2×)
- **\${r2_dec} >= \${expected}** holds (checked 2×)

How it was checked

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 968, #pkts encrypt: 968, #pkts digest: 968
  #pkts decaps: 966, #pkts decrypt: 966, #pkts verify: 966
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

R2 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
current_peer 100.64.0.1 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 2105, #pkts encrypt: 2105, #pkts digest: 2105
  #pkts decaps: 2100, #pkts decrypt: 2100, #pkts verify: 2100
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 33 more lines
```

R1 ping 10.20.2.1 source Loopback1 repeat 20

```
Type escape sequence to abort.
Sending 20, 100-byte ICMP Echos to 10.20.2.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.1.1
!!!!!!!!!!!!!!!!!!!!!!
Success rate is 100 percent (20/20), round-trip min/avg/max = 1/1/2 ms
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 968, #pkts encrypt: 968, #pkts digest: 968
  #pkts decaps: 978, #pkts decrypt: 978, #pkts verify: 978
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

R2 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
```

```

local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
current_peer 100.64.0.1 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 2105, #pkts encrypt: 2105, #pkts digest: 2105
#pkts decaps: 2100, #pkts decrypt: 2100, #pkts verify: 2100
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 33 more lines

```

R1 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 1024, #pkts encrypt: 1024, #pkts digest: 1024
#pkts decaps: 1027, #pkts decrypt: 1027, #pkts verify: 1027
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

R2 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
current_peer 100.64.0.1 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 2160, #pkts encrypt: 2160, #pkts digest: 2160
#pkts decaps: 2159, #pkts decrypt: 2159, #pkts verify: 2159
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 33 more lines

```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.23 PASS BGP Control Plane Traffic Is Encrypted On The Wire (18.8s, 8 commands)

The reason for peering over the tunnel. Captures a keepalive window and asserts the session is invisible: no TCP, no peering addresses, no advertised prefixes -- only ESP.

Setup (suite) Establish BGP

Acceptance criteria

- output contains ESP
- output does not contain TCP
- output does not contain \${R2_TUNNEL_HUB}
- output does not contain \${R2_TUNNEL_LOCAL}
- output does not contain \${R1_BGP_PREFIX}
- output does not contain \${R2_BGP_PREFIX}

How it was checked

R1 no monitor capture BGPCAP

Capture does not exist

R1 monitor capture BGPCAP interface GigabitEthernet2 both

\${output} =

R1 monitor capture BGPCAP match ipv4 any any

\${output} =

R1 monitor capture BGPCAP buffer size 5

\${output} =

R1 monitor capture BGPCAP start

Started capture point : BGPCAP

R1 monitor capture BGPCAP stop

Stopped capture point : BGPCAP

R1 show monitor capture BGPCAP buffer brief

```
-----
#   size   timestamp      source            destination      dscp   protocol
-----
0   138     0.000000    100.64.0.2        -> 100.64.0.1      48 CS6   ESP
1   138     0.000000    100.64.0.1        -> 100.64.0.2      48 CS6   ESP
2   138     0.063992    100.64.0.1        -> 100.64.0.2      48 CS6   ESP
3   138     0.224994    100.64.0.1        -> 100.64.0.2      48 CS6   ESP
4   138     0.224994    100.64.0.2        -> 100.64.0.1      48 CS6   ESP
5   138     0.248980    100.64.0.1        -> 100.64.0.3      48 CS6   ESP
6   138     0.248980    100.64.0.3        -> 100.64.0.1      48 CS6   ESP
7   138     0.350040    100.64.0.2        -> 100.64.0.1      48 CS6   ESP
8   138     0.426025    100.64.0.3        -> 100.64.0.1      48 CS6   ESP
9   138     0.426025    100.64.0.1        -> 100.64.0.3      48 CS6   ESP
10  138     0.445036    100.64.0.2        -> 100.64.0.1      48 CS6   ESP
... 319 more lines
```

R1 no monitor capture BGPCAP

\${output} =

Teardown (suite) Restore BGP Baseline, Close All Routers

9.24 PASS Withdrawing A Prefix Removes It From The Peer (60.5s, 23 commands)

Shuts the advertised interface on R2 and requires R1 to lose both the BGP path and the route, then restores it.

Setup (suite) Establish BGP

Acceptance criteria

- output contains **% Subnet not in table** (checked 7×)
- output contains **Known via "bgp"** (checked 8×)

How it was checked**R2 configure terminal**

Enter configuration commands, one per line. End with CNTL/Z.

R2 interface Loopback1

\${output} =

R2 shutdown

\${output} =

R2 end

\${output} =

R1 show ip route 10.20.2.1

```
Routing entry for 10.20.2.1/32
  Known via "bgp 65001", distance 20, metric 0
  Tag 65002, type external
  Last update from 172.20.0.2 00:01:07 ago
  Routing Descriptor Blocks:
    * 172.20.0.2, from 172.20.0.2, 00:01:07 ago
      opaque_ptr 0x747B4EAD51F8
      Route metric is 0, traffic share count is 1
      AS Hops 1
      Route tag 65002
      MPLS label: none
```

R1 show ip route 10.20.2.1

```
Routing entry for 10.20.2.1/32
  Known via "bgp 65001", distance 20, metric 0
  Tag 65002, type external
  Last update from 172.20.0.2 00:01:12 ago
  Routing Descriptor Blocks:
    * 172.20.0.2, from 172.20.0.2, 00:01:12 ago
      opaque_ptr 0x747B4EAD51F8
      Route metric is 0, traffic share count is 1
      AS Hops 1
      Route tag 65002
      MPLS label: none
```

R1 show ip route 10.20.2.1

```
Routing entry for 10.20.2.1/32
  Known via "bgp 65001", distance 20, metric 0
  Tag 65002, type external
  Last update from 172.20.0.2 00:01:17 ago
  Routing Descriptor Blocks:
    * 172.20.0.2, from 172.20.0.2, 00:01:17 ago
```

```
opaque_ptr 0x747B4EAD51F8
Route metric is 0, traffic share count is 1
AS Hops 1
Route tag 65002
MPLS label: none
```

R1 show ip route 10.20.2.1

```
Routing entry for 10.20.2.1/32
Known via "bgp 65001", distance 20, metric 0
Tag 65002, type external
Last update from 172.20.0.2 00:01:22 ago
Routing Descriptor Blocks:
* 172.20.0.2, from 172.20.0.2, 00:01:22 ago
  opaque_ptr 0x747B4EAD51F8
  Route metric is 0, traffic share count is 1
  AS Hops 1
  Route tag 65002
  MPLS label: none
```

R1 show ip route 10.20.2.1

```
Routing entry for 10.20.2.1/32
Known via "bgp 65001", distance 20, metric 0
Tag 65002, type external
Last update from 172.20.0.2 00:01:27 ago
Routing Descriptor Blocks:
* 172.20.0.2, from 172.20.0.2, 00:01:27 ago
  opaque_ptr 0x747B4EAD51F8
  Route metric is 0, traffic share count is 1
  AS Hops 1
  Route tag 65002
  MPLS label: none
```

R1 show ip route 10.20.2.1

```
Routing entry for 10.20.2.1/32
Known via "bgp 65001", distance 20, metric 0
Tag 65002, type external
Last update from 172.20.0.2 00:01:32 ago
Routing Descriptor Blocks:
* 172.20.0.2, from 172.20.0.2, 00:01:32 ago
  opaque_ptr 0x747B4EAD51F8
  Route metric is 0, traffic share count is 1
  AS Hops 1
  Route tag 65002
  MPLS label: none
```

R1 show ip route 10.20.2.1

```
% Subnet not in table
```

R2 configure terminal

```
Enter configuration commands, one per line. End with CNTL/Z.
```

R2 interface Loopback1

```
${output} =
```

R2 no shutdown

```
${output} =
```

R2 end

```
${output} =
```

R1 show ip route 10.20.2.1

```
% Subnet not in table
```

R1 show ip route 10.20.2.1

```
% Subnet not in table
```

R1 show ip route 10.20.2.1

```
% Subnet not in table
```

R1 show ip route 10.20.2.1

```
% Subnet not in table
```

R1 show ip route 10.20.2.1

```
% Subnet not in table
```

R1 show ip route 10.20.2.1

```
% Subnet not in table
```

R1 show ip route 10.20.2.1

```
Routing entry for 10.20.2.1/32
Known via "bgp 65001", distance 20, metric 0
Tag 65002, type external
Last update from 172.20.0.2 00:00:04 ago
Routing Descriptor Blocks:
* 172.20.0.2, from 172.20.0.2, 00:00:04 ago
  opaque_ptr 0x747B4EAD51F8
  Route metric is 0, traffic share count is 1
  AS Hops 1
  Route tag 65002
```

MPLS label: none

R2 show ip route 10.20.1.1

```
Routing entry for 10.20.1.1/32
  Known via "bgp 65002", distance 20, metric 0
  Tag 65001, type external
  Last update from 172.20.0.1 00:02:07 ago
  Routing Descriptor Blocks:
    * 172.20.0.1, from 172.20.0.1, 00:02:07 ago
      opaque_ptr 0x7E32CED11C60
      Route metric is 0, traffic share count is 1
      AS Hops 1
      Route tag 65001
      MPLS label: none
```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.25 PASS Session Recovers After A Hard Clear (10.2s, 5 commands)

Setup (suite) Establish BGP

Acceptance criteria

- output matches `${peer}\s+4\s+${peer_asn}(\s+ld+){5}\s+1\s+1\s+ld+` (checked 3x)
- output contains **Known via "bgp"**

How it was checked

R1 clear ip bgp *

`${output}` =

R1 show bgp ipv4 unicast summary

```
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 1, main routing table version 1
3 network entries using 744 bytes of memory
3 path entries using 408 bytes of memory
2/0 BGP path/bestpath attribute entries using 592 bytes of memory
1 BGP AS-PATH entries using 24 bytes of memory
1 BGP community entries using 24 bytes of memory
1 BGP route-map cache entries using 72 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 1864 total bytes of memory
BGP activity 165/162 prefixes, 171/168 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:55:44.780 ago)
```

```
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines
```

R1 show bgp ipv4 unicast summary

```
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 1, main routing table version 1
3 network entries using 744 bytes of memory
3 path entries using 408 bytes of memory
2/0 BGP path/bestpath attribute entries using 592 bytes of memory
1 BGP AS-PATH entries using 24 bytes of memory
1 BGP community entries using 24 bytes of memory
1 BGP route-map cache entries using 72 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 1864 total bytes of memory
BGP activity 165/162 prefixes, 171/168 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:55:49.814 ago)
```

```
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines
```

R1 show bgp ipv4 unicast summary

```
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 10, main routing table version 10
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
6 BGP route-map cache entries using 432 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 6152 total bytes of memory
BGP activity 171/162 prefixes, 177/168 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:55:54.853 ago)
```

```
Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines
```

R1 show ip route 10.20.2.1

```

Routing entry for 10.20.2.1/32
  Known via "bgp 65001", distance 20, metric 0
  Tag 65002, type external
  Last update from 172.20.0.2 00:00:01 ago
  Routing Descriptor Blocks:
    * 172.20.0.2, from 172.20.0.2, 00:00:01 ago
      opaque_ptr 0x747B4EAD51F8
      Route metric is 0, traffic share count is 1
      AS Hops 1
      Route tag 65002
      MPLS label: none

```

Teardown (suite) Restore BGP Baseline, Close All Routers

9.26 PASS Mismatched MD5 Password Prevents The Session Coming Up (50.4s, 19 commands)

Negative control on BGP authentication, mirroring the IPsec wrong-PSK test: without it, a session that accepted any peer would still pass everything above.

Setup (suite) Establish BGP

Acceptance criteria

- output does not match `${peer}(\s+\d+){6}\s+\s+\s+\d+\s*${`
- output matches `${peer}\s+4\s+${peer_asn}(\s+\d+){5}\s+\s+\s+\d+` (checked 2x)

How it was checked

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 router bgp 65002

`$(output) =`

R2 neighbor 172.20.0.1 password WrongBgpSecret999

`$(output) =`

R2 end

`$(output) =`

R1 clear ip bgp *

`$(output) =`

R2 clear ip bgp *

`$(output) =`

R1 show bgp ipv4 unicast summary

```

BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 1, main routing table version 1
6 network entries using 1488 bytes of memory
6 path entries using 816 bytes of memory
7/0 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
6 BGP route-map cache entries using 432 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5000 total bytes of memory
BGP activity 177/171 prefixes, 183/177 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:56:40.023 ago)

Neighbor          V              AS MsgRcvd MsgSent   TblVer  InQ  OutQ  Up/Down  State/PfxRcd
... 2 more lines

```

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 router bgp 65002

`$(output) =`

R2 neighbor 172.20.0.1 password LabBgpSecret

`$(output) =`

R2 end

`$(output) =`

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 interface Loopback1

`$(output) =`

R2 no shutdown

`$(output) =`

R2 end

```

${output} =
R1 clear ip bgp *
${output} =
R2 clear ip bgp *
${output} =
R1 show bgp ipv4 unicast summary
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 1, main routing table version 1
3 network entries using 744 bytes of memory
3 path entries using 408 bytes of memory
7/0 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
6 BGP route-map cache entries using 432 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 3848 total bytes of memory
BGP activity 180/177 prefixes, 186/183 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:56:40.214 ago)

Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

R1 show bgp ipv4 unicast summary
BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 1, main routing table version 1
3 network entries using 744 bytes of memory
3 path entries using 408 bytes of memory
7/0 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
6 BGP route-map cache entries using 432 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 3848 total bytes of memory
BGP activity 180/177 prefixes, 186/183 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:56:45.249 ago)

Neighbor      V      AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

```

Teardown (this test) Restore BGP Baseline

10 Host To Host

10.01 **PASS** Every Host Holds Its LAN Address (0.1s, 3 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains `#{HOST_IP}#{h}` (checked 3×)

How it was checked

H1 ip addr show eth1

```
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:01:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.10.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.229.55/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.12/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.13/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.14/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
... 70 more lines
```

H2 ip addr show eth1

```
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:02:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.20.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.199.41/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.12/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.13/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.14/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
... 70 more lines
```

H3 ip addr show eth1

```
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:03:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.30.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.207.242/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.12/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.13/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.14/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
... 70 more lines
```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.02 **PASS** Every Host Routes The Other Two LANs Via Its Own Router (0.0s, 3 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output matches `#{net}/24 via #{HOST_GW}#{h}` (checked 9×)

How it was checked

H1 ip route

```
default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.10.1 dev eth1
```

```
169.254.0.0/16 dev eth1 scope link src 169.254.229.55 metric 1003
192.168.10.0/24 dev eth1 scope link src 192.168.10.10
192.168.20.0/24 via 192.168.10.1 dev eth1
192.168.30.0/24 via 192.168.10.1 dev eth1
```

H2 ip route

```
default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.20.1 dev eth1
169.254.0.0/16 dev eth1 scope link src 169.254.199.41 metric 1003
192.168.10.0/24 via 192.168.20.1 dev eth1
192.168.20.0/24 dev eth1 scope link src 192.168.20.10
192.168.30.0/24 via 192.168.20.1 dev eth1
```

H3 ip route

```
default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.30.1 dev eth1
169.254.0.0/16 dev eth1 scope link src 169.254.207.242 metric 1003
192.168.10.0/24 via 192.168.30.1 dev eth1
192.168.20.0/24 via 192.168.30.1 dev eth1
192.168.30.0/24 dev eth1 scope link src 192.168.30.10
```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.03 PASS Every Host Can Reach Its Default Gateway (12.3s, 3 commands)

Isolates the host-to-router leg so a failure further along is not misread as a broken LAN.

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains **0% packet loss** (checked 3×)
ping from \${alias} to \${target} lost packets: \${out}

How it was checked

H1 ping -c 5 192.168.10.1

```
PING 192.168.10.1 (192.168.10.1) 56(84) bytes of data.
64 bytes from 192.168.10.1: icmp_seq=1 ttl=255 time=0.442 ms
64 bytes from 192.168.10.1: icmp_seq=2 ttl=255 time=0.385 ms
64 bytes from 192.168.10.1: icmp_seq=3 ttl=255 time=0.359 ms
64 bytes from 192.168.10.1: icmp_seq=4 ttl=255 time=0.436 ms
64 bytes from 192.168.10.1: icmp_seq=5 ttl=255 time=0.377 ms

--- 192.168.10.1 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4103ms
rtt min/avg/max/mdev = 0.359/0.399/0.442/0.033 ms
```

H2 ping -c 5 192.168.20.1

```
PING 192.168.20.1 (192.168.20.1) 56(84) bytes of data.
64 bytes from 192.168.20.1: icmp_seq=1 ttl=255 time=0.543 ms
64 bytes from 192.168.20.1: icmp_seq=2 ttl=255 time=0.411 ms
64 bytes from 192.168.20.1: icmp_seq=3 ttl=255 time=0.396 ms
64 bytes from 192.168.20.1: icmp_seq=4 ttl=255 time=0.389 ms
64 bytes from 192.168.20.1: icmp_seq=5 ttl=255 time=0.375 ms

--- 192.168.20.1 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4103ms
rtt min/avg/max/mdev = 0.375/0.422/0.543/0.061 ms
```

H3 ping -c 5 192.168.30.1

```
PING 192.168.30.1 (192.168.30.1) 56(84) bytes of data.
64 bytes from 192.168.30.1: icmp_seq=1 ttl=255 time=0.393 ms
64 bytes from 192.168.30.1: icmp_seq=2 ttl=255 time=0.446 ms
64 bytes from 192.168.30.1: icmp_seq=3 ttl=255 time=0.381 ms
64 bytes from 192.168.30.1: icmp_seq=4 ttl=255 time=0.333 ms
64 bytes from 192.168.30.1: icmp_seq=5 ttl=255 time=0.325 ms

--- 192.168.30.1 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4100ms
rtt min/avg/max/mdev = 0.325/0.375/0.446/0.043 ms
```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.04 PASS Every Host Can Reach Every Other Host (24.1s, 6 commands)

The full mesh, including h2 <-> h3 which never touches a direct link and can only work if the hub re-advertises between spokes.

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains **0% packet loss** (checked 6×)
ping from \${alias} to \${target} lost packets: \${out}

How it was checked

H2 ping -c 5 192.168.20.10

```
PING 192.168.20.10 (192.168.20.10) 56(84) bytes of data.  
64 bytes from 192.168.20.10: icmp_seq=1 ttl=62 time=1.09 ms  
64 bytes from 192.168.20.10: icmp_seq=2 ttl=62 time=1.21 ms  
64 bytes from 192.168.20.10: icmp_seq=3 ttl=62 time=1.15 ms  
64 bytes from 192.168.20.10: icmp_seq=4 ttl=62 time=1.16 ms  
64 bytes from 192.168.20.10: icmp_seq=5 ttl=62 time=1.22 ms  
  
--- 192.168.20.10 ping statistics ---  
5 packets transmitted, 5 received, 0% packet loss, time 4006ms  
rtt min/avg/max/mdev = 1.094/1.165/1.221/0.045 ms
```

H3 ping -c 5 192.168.30.10

```
PING 192.168.30.10 (192.168.30.10) 56(84) bytes of data.  
64 bytes from 192.168.30.10: icmp_seq=1 ttl=62 time=1.18 ms  
64 bytes from 192.168.30.10: icmp_seq=2 ttl=62 time=1.24 ms  
64 bytes from 192.168.30.10: icmp_seq=3 ttl=62 time=1.19 ms  
64 bytes from 192.168.30.10: icmp_seq=4 ttl=62 time=1.26 ms  
64 bytes from 192.168.30.10: icmp_seq=5 ttl=62 time=1.35 ms  
  
--- 192.168.30.10 ping statistics ---  
5 packets transmitted, 5 received, 0% packet loss, time 4006ms  
rtt min/avg/max/mdev = 1.179/1.242/1.346/0.059 ms
```

H1 ping -c 5 192.168.10.10

```
PING 192.168.10.10 (192.168.10.10) 56(84) bytes of data.  
64 bytes from 192.168.10.10: icmp_seq=1 ttl=62 time=1.32 ms  
64 bytes from 192.168.10.10: icmp_seq=2 ttl=62 time=1.05 ms  
64 bytes from 192.168.10.10: icmp_seq=3 ttl=62 time=1.25 ms  
64 bytes from 192.168.10.10: icmp_seq=4 ttl=62 time=1.18 ms  
64 bytes from 192.168.10.10: icmp_seq=5 ttl=62 time=1.18 ms  
  
--- 192.168.10.10 ping statistics ---  
5 packets transmitted, 5 received, 0% packet loss, time 4005ms  
rtt min/avg/max/mdev = 1.053/1.195/1.318/0.088 ms
```

H3 ping -c 5 192.168.30.10

```
PING 192.168.30.10 (192.168.30.10) 56(84) bytes of data.  
64 bytes from 192.168.30.10: icmp_seq=1 ttl=62 time=1.15 ms  
64 bytes from 192.168.30.10: icmp_seq=2 ttl=62 time=1.15 ms  
64 bytes from 192.168.30.10: icmp_seq=3 ttl=62 time=1.13 ms  
64 bytes from 192.168.30.10: icmp_seq=4 ttl=62 time=1.20 ms  
64 bytes from 192.168.30.10: icmp_seq=5 ttl=62 time=1.09 ms  
  
--- 192.168.30.10 ping statistics ---  
5 packets transmitted, 5 received, 0% packet loss, time 4005ms  
rtt min/avg/max/mdev = 1.089/1.143/1.198/0.035 ms
```

H1 ping -c 5 192.168.10.10

```
PING 192.168.10.10 (192.168.10.10) 56(84) bytes of data.  
64 bytes from 192.168.10.10: icmp_seq=1 ttl=62 time=1.27 ms  
64 bytes from 192.168.10.10: icmp_seq=2 ttl=62 time=1.45 ms  
64 bytes from 192.168.10.10: icmp_seq=3 ttl=62 time=1.23 ms  
64 bytes from 192.168.10.10: icmp_seq=4 ttl=62 time=1.12 ms  
64 bytes from 192.168.10.10: icmp_seq=5 ttl=62 time=1.13 ms  
  
--- 192.168.10.10 ping statistics ---  
5 packets transmitted, 5 received, 0% packet loss, time 4006ms  
rtt min/avg/max/mdev = 1.121/1.239/1.445/0.117 ms
```

H2 ping -c 5 192.168.20.10

```
PING 192.168.20.10 (192.168.20.10) 56(84) bytes of data.  
64 bytes from 192.168.20.10: icmp_seq=1 ttl=62 time=1.24 ms  
64 bytes from 192.168.20.10: icmp_seq=2 ttl=62 time=1.30 ms  
64 bytes from 192.168.20.10: icmp_seq=3 ttl=62 time=1.15 ms  
64 bytes from 192.168.20.10: icmp_seq=4 ttl=62 time=1.11 ms  
64 bytes from 192.168.20.10: icmp_seq=5 ttl=62 time=1.20 ms  
  
--- 192.168.20.10 ping statistics ---  
5 packets transmitted, 5 received, 0% packet loss, time 4006ms  
rtt min/avg/max/mdev = 1.111/1.201/1.296/0.065 ms
```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.05 PASS Spoke To Spoke Traffic Is Routed Through The Hub (0.1s, 3 commands)

R2 must reach R3's LAN via the hub's tunnel address, not by any direct path -- there is no spoke-to-spoke link.

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains **Known via "bgp \${R2_ASN}"**
- output contains **\${R2_TUNNEL_HUB}**
- output contains **Tunnel0** (checked 2×)

How it was checked

R2 show ip route 192.168.30.0

```
Routing entry for 192.168.30.0/24
  Known via "bgp 65002", distance 20, metric 0
  Tag 65001, type external
  Last update from 172.20.0.3 00:01:29 ago
  Routing Descriptor Blocks:
  * 172.20.0.3, from 172.20.0.1, 00:01:29 ago
    opaque_ptr 0x7E32CED11C60
    Route metric is 0, traffic share count is 1
    AS Hops 2
    Route tag 65001
    MPLS label: none
```

R2 show ip cef 192.168.30.10

```
192.168.30.0/24
  nexthop 172.20.0.3 Tunnel0
```

R3 show ip cef 192.168.20.10

```
192.168.20.0/24
  nexthop 172.20.0.2 Tunnel0
```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.06 PASS Hub Reaches Both Spoke LANs On Separate Tunnels (0.0s, 2 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains **\${DMVPN_TUNNEL}** (checked 2×)

How it was checked

R1 show ip cef 192.168.20.10

```
192.168.20.0/24
  nexthop 172.20.0.2 Tunnel0
```

R1 show ip cef 192.168.30.10

```
192.168.30.0/24
  nexthop 172.20.0.3 Tunnel0
```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.07 PASS Host Traffic Is Encrypted In Transit (19.6s, 5 commands)

No host runs crypto: the routers encrypt for them, so the ESP counters must move by the traffic the hosts generated.

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains **0% packet loss**
ping from \${alias} to \${target} lost packets: \${out}
- **\${r1_enc} >= \${expected}** holds
- **\${r1_dec} >= \${expected}** holds
- **\${r2_enc} >= \${expected}** holds
- **\${r2_dec} >= \${expected}** holds

How it was checked

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1
```

```
protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 2544, #pkts encrypt: 2544, #pkts digest: 2544
#pkts decaps: 2546, #pkts decrypt: 2546, #pkts verify: 2546
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R2 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 260, #pkts encrypt: 260, #pkts digest: 260
#pkts decaps: 264, #pkts decrypt: 264, #pkts verify: 264
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

H1 ping -c 20 192.168.20.10

```
PING 192.168.20.10 (192.168.20.10) 56(84) bytes of data.
64 bytes from 192.168.20.10: icmp_seq=1 ttl=62 time=1.70 ms
64 bytes from 192.168.20.10: icmp_seq=2 ttl=62 time=1.24 ms
64 bytes from 192.168.20.10: icmp_seq=3 ttl=62 time=1.24 ms
64 bytes from 192.168.20.10: icmp_seq=4 ttl=62 time=1.24 ms
64 bytes from 192.168.20.10: icmp_seq=5 ttl=62 time=1.28 ms
64 bytes from 192.168.20.10: icmp_seq=6 ttl=62 time=1.14 ms
64 bytes from 192.168.20.10: icmp_seq=7 ttl=62 time=1.22 ms
64 bytes from 192.168.20.10: icmp_seq=8 ttl=62 time=1.25 ms
64 bytes from 192.168.20.10: icmp_seq=9 ttl=62 time=1.11 ms
64 bytes from 192.168.20.10: icmp_seq=10 ttl=62 time=1.05 ms
64 bytes from 192.168.20.10: icmp_seq=11 ttl=62 time=1.14 ms
64 bytes from 192.168.20.10: icmp_seq=12 ttl=62 time=1.28 ms
64 bytes from 192.168.20.10: icmp_seq=13 ttl=62 time=1.21 ms
... 11 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 2673, #pkts encrypt: 2673, #pkts digest: 2673
#pkts decaps: 2683, #pkts decrypt: 2683, #pkts verify: 2683
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

R2 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 369, #pkts encrypt: 369, #pkts digest: 369
#pkts decaps: 373, #pkts decrypt: 373, #pkts verify: 373
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines
```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.08 PASS Host Addresses Never Appear In Cleartext On The Spoke Link (11.7s, 9 commands)

Capture the R1<->R2 link while the hosts talk: only ESP between the link addresses should be visible.

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains **0% packet loss**
ping from \${alias} to \${target} lost packets: \${out}
- output contains **ESP**
- output does not contain **\${H1_IP}**
- output does not contain **\${H2_IP}**
- output does not contain **ICMP**

How it was checked

R1 no monitor capture HOSTCAP

Capture does not exist

R1 monitor capture HOSTCAP interface GigabitEthernet2 both

\${output} =

R1 monitor capture HOSTCAP match ipv4 any any

\${output} =

R1 monitor capture HOSTCAP buffer size 5

\${output} =

R1 monitor capture HOSTCAP start

Started capture point : HOSTCAP

H1 ping -c 10 192.168.20.10

```
PING 192.168.20.10 (192.168.20.10) 56(84) bytes of data.
64 bytes from 192.168.20.10: icmp_seq=1 ttl=62 time=2.04 ms
64 bytes from 192.168.20.10: icmp_seq=2 ttl=62 time=1.15 ms
64 bytes from 192.168.20.10: icmp_seq=3 ttl=62 time=1.28 ms
64 bytes from 192.168.20.10: icmp_seq=4 ttl=62 time=1.12 ms
64 bytes from 192.168.20.10: icmp_seq=5 ttl=62 time=1.24 ms
64 bytes from 192.168.20.10: icmp_seq=6 ttl=62 time=1.24 ms
64 bytes from 192.168.20.10: icmp_seq=7 ttl=62 time=1.18 ms
64 bytes from 192.168.20.10: icmp_seq=8 ttl=62 time=1.44 ms
64 bytes from 192.168.20.10: icmp_seq=9 ttl=62 time=1.14 ms
64 bytes from 192.168.20.10: icmp_seq=10 ttl=62 time=1.06 ms

--- 192.168.20.10 ping statistics ---
10 packets transmitted, 10 received, 0% packet loss, time 9012ms
... 1 more lines
```

R1 monitor capture HOSTCAP stop

Stopped capture point : HOSTCAP

R1 show monitor capture HOSTCAP buffer brief

#	size	timestamp	source	destination	dscp	protocol
0	138	0.000000	100.64.0.1	-> 100.64.0.3	48 CS6	ESP
1	138	0.000000	100.64.0.3	-> 100.64.0.1	48 CS6	ESP
2	170	0.002990	100.64.0.1	-> 100.64.0.2	0 BE	ESP
3	170	0.004989	100.64.0.2	-> 100.64.0.1	0 BE	ESP
4	138	0.037992	100.64.0.2	-> 100.64.0.1	48 CS6	ESP
5	138	0.077983	100.64.0.2	-> 100.64.0.1	48 CS6	ESP
6	138	0.077983	100.64.0.1	-> 100.64.0.2	48 CS6	ESP
7	138	0.086986	100.64.0.3	-> 100.64.0.1	48 CS6	ESP
8	138	0.086986	100.64.0.1	-> 100.64.0.3	48 CS6	ESP
9	138	0.199986	100.64.0.1	-> 100.64.0.2	48 CS6	ESP
10	138	0.199986	100.64.0.2	-> 100.64.0.1	48 CS6	ESP

... 230 more lines

R1 no monitor capture HOSTCAP

\${output} =

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.09 PASS Spoke To Spoke Traffic Is Encrypted On The Direct Path (11.5s, 11 commands)

The VTI lab this mirrors captured the hub's second link, because h2 to h3 crossed two tunnels and was decrypted and re-encrypted in between. Under DMVPN there is no second leg to capture: once the shortcut forms the hub is not on the path at all, so the capture moves to the spoke's own WAN interface -- the only place that traffic now appears. It should be ESP there, with neither host address visible.

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains **\${R3_WAN_IP}**
R2 has not resolved R3 directly, so no shortcut is in place
- output contains **0% packet loss**
ping from \${alias} to \${target} lost packets: \${out}
- output contains **ESP**
- output does not contain **\${H2_IP}**
- output does not contain **\${H3_IP}**
- output does not contain **ICMP**

How it was checked

R2 ping 10.20.3.1 source Loopback1 repeat 5

```
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.20.3.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.2.1
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
```

R2 show ip nhrp 172.20.0.3

```
172.20.0.3/32 via 172.20.0.3
  Tunnel0 created 00:01:15, expire 00:03:44
  Type: dynamic, Flags: router nhop bfd
  NBMA address: 100.64.0.3
```

R2 no monitor capture HOSTCAP

Capture does not exist

R2 monitor capture HOSTCAP interface GigabitEthernet2 both

\${output} =

R2 monitor capture HOSTCAP match ipv4 any any

\${output} =

R2 monitor capture HOSTCAP buffer size 5

\${output} =

R2 monitor capture HOSTCAP start

Started capture point : HOSTCAP

H2 ping -c 10 192.168.30.10

```
PING 192.168.30.10 (192.168.30.10) 56(84) bytes of data.
 64 bytes from 192.168.30.10: icmp_seq=1 ttl=62 time=1.24 ms
 64 bytes from 192.168.30.10: icmp_seq=2 ttl=62 time=1.19 ms
 64 bytes from 192.168.30.10: icmp_seq=3 ttl=62 time=1.19 ms
 64 bytes from 192.168.30.10: icmp_seq=4 ttl=62 time=1.27 ms
 64 bytes from 192.168.30.10: icmp_seq=5 ttl=62 time=1.25 ms
 64 bytes from 192.168.30.10: icmp_seq=6 ttl=62 time=1.23 ms
 64 bytes from 192.168.30.10: icmp_seq=7 ttl=62 time=1.25 ms
 64 bytes from 192.168.30.10: icmp_seq=8 ttl=62 time=1.27 ms
 64 bytes from 192.168.30.10: icmp_seq=9 ttl=62 time=1.18 ms
 64 bytes from 192.168.30.10: icmp_seq=10 ttl=62 time=1.32 ms
```

```
--- 192.168.30.10 ping statistics ---
10 packets transmitted, 10 received, 0% packet loss, time 9013ms
... 1 more lines
```

R2 monitor capture HOSTCAP stop

Stopped capture point : HOSTCAP

R2 show monitor capture HOSTCAP buffer brief

#	size	timestamp	source	destination	dscp	protocol
0	170	0.000000	100.64.0.2	-> 100.64.0.3	0 BE	ESP
1	170	0.001007	100.64.0.3	-> 100.64.0.2	0 BE	ESP
2	138	0.057996	100.64.0.3	-> 100.64.0.2	48 CS6	ESP
3	138	0.057996	100.64.0.2	-> 100.64.0.3	48 CS6	ESP
4	138	0.189993	100.64.0.2	-> 100.64.0.3	48 CS6	ESP
5	138	0.244982	100.64.0.1	-> 100.64.0.2	48 CS6	ESP
6	138	0.244982	100.64.0.2	-> 100.64.0.1	48 CS6	ESP
7	138	0.269990	100.64.0.2	-> 100.64.0.1	48 CS6	ESP
8	138	0.270982	100.64.0.1	-> 100.64.0.2	48 CS6	ESP
9	138	0.312987	100.64.0.2	-> 100.64.0.3	48 CS6	ESP
10	138	0.312987	100.64.0.3	-> 100.64.0.2	48 CS6	ESP

... 215 more lines

R2 no monitor capture HOSTCAP

\${output} =

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

10.10 **PASS** The Hub Is Not On The Spoke To Spoke Path (0.0s, 2 commands)

The routing consequence of the shortcut, from the hosts' point of view rather than the routers'.

Setup (suite) Open All Routers, Open All Hosts, Wait For LAN Routes, Warm Up Host Paths

Acceptance criteria

- output contains **\${R3_WAN_IP}**
R2 has not resolved R3 directly, so no shortcut is in place
- output does not contain **\${R1_DMVPN_IP}**
host traffic between the spokes still transits the hub:\n\${trace}

How it was checked

R2 `show ip nhrp 172.20.0.3`

```
172.20.0.3/32 via 172.20.0.3
  Tunnel0 created 00:01:26, expire 00:03:33
  Type: dynamic, Flags: router nhop bfd
  NBMA address: 100.64.0.3
```

H2 `traceroute -n -q 1 -w 1 192.168.30.10`

```
traceroute to 192.168.30.10 (192.168.30.10), 30 hops max, 60 byte packets
 1  192.168.20.1  1.112 ms
 2  172.20.0.3  1.089 ms
 3  192.168.30.10  2.095 ms
```

Teardown (suite) Run Keyword And Ignore Error, Delete Capture, R1, HOSTCAP, Close All Connections

11 Throughput

11.01 **PASS** Hub To Spoke Hosts Sustain The Target Throughput (32.0s, 2 commands)

h1 -> h2 crosses one tunnel.

Setup (suite) Open All Routers, Open All Hosts, Wait For Fabric

Acceptance criteria

- `${m}` is not empty
- `${mbps} >= ${TP_TARGET}` holds

How it was checked

```
H1 nc -l -p 5001 > /dev/null 2>&1 &
${output} =
```

```
H1 S=$(date +%s); dd if=/dev/zero bs=64k count=1024 2>/dev/null | nc -w 1 192.168.20.10 5001; echo SECS=$(( $(date +%s) - S ))
SECS=31
```

Teardown (suite) Close All Connections

11.02 **PASS** Spoke To Spoke Hosts Sustain The Target Throughput (31.9s, 2 commands)

h2 -> h3 crosses two tunnels, being decrypted and re-encrypted at the hub, so it is the more demanding path.

Setup (suite) Open All Routers, Open All Hosts, Wait For Fabric

Acceptance criteria

- `${m}` is not empty
- `${mbps} >= ${TP_TARGET}` holds

How it was checked

```
H2 nc -l -p 5001 > /dev/null 2>&1 &
${output} =
```

```
H2 S=$(date +%s); dd if=/dev/zero bs=64k count=1024 2>/dev/null | nc -w 1 192.168.30.10 5001; echo SECS=$(( $(date +%s) - S ))
SECS=31
```

Teardown (suite) Close All Connections

11.03 **PASS** Bulk Throughput Traffic Is Encrypted (17.5s, 6 commands)

Rate alone says nothing about protection. A transfer of this size must move thousands of packets through ESP, so assert the counters rose in proportion to the bytes actually sent.

Setup (suite) Open All Routers, Open All Hosts, Wait For Fabric

Acceptance criteria

- `${m}` is not empty
- `${data_out} >= ${expected}` holds
- `${data_in} >= ${expected}` holds
- `${ack_in} > 0` holds
- `${ack_out} > 0` holds

How it was checked

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 53004, #pkts encrypt: 53004, #pkts digest: 53004
#pkts decaps: 28767, #pkts decrypt: 28767, #pkts verify: 28767
#pkts compressed: 0, #pkts decompressed: 0
```

```

#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

R2 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 50699, #pkts encrypt: 50699, #pkts digest: 50699
#pkts decaps: 26301, #pkts decrypt: 26301, #pkts verify: 26301
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

H1 nc -l -p 5001 > /dev/null 2>&1 &

```
[1]+  Stopped (tty input) nc -l -p 5001 1>/dev/null 2>&1
```

H1 S=\$(date +%s); dd if=/dev/zero bs=64k count=512 2>/dev/null | nc -w 1 192.168.20.10 5001; echo SECS=\$((\$(date +%s) - S))

```
SECS=15
```

R1 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 78000, #pkts encrypt: 78000, #pkts digest: 78000
#pkts decaps: 41206, #pkts decrypt: 41206, #pkts verify: 41206
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

R1 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 50797, #pkts encrypt: 50797, #pkts digest: 50797
#pkts decaps: 26398, #pkts decrypt: 26398, #pkts verify: 26398
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

Teardown (suite) Close All Connections

12 Nat

12.01 PASS Every Router Has A Static Source NAT Mapping For Its Host (0.3s, 3 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains `${HOST_IP}${h}}` (checked 3×)
- output contains `${HOST_NAT}${h}}` (checked 3×)
- output contains `route-map NAT-TO-DOMAIN` (checked 3×)

How it was checked

H1 show running-config | include ip nat inside source

```
ip nat inside source static 192.168.10.10 10.30.1.10 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.11 10.30.1.11 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.12 10.30.1.12 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.13 10.30.1.13 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.14 10.30.1.14 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.15 10.30.1.15 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.16 10.30.1.16 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.17 10.30.1.17 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.18 10.30.1.18 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.19 10.30.1.19 route-map NAT-TO-DOMAIN
ip nat inside source list NAT-POOL-SRC pool SITE-POOL
```

H2 show running-config | include ip nat inside source

```
ip nat inside source static 192.168.20.10 10.30.2.10 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.11 10.30.2.11 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.12 10.30.2.12 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.13 10.30.2.13 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.14 10.30.2.14 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.15 10.30.2.15 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.16 10.30.2.16 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.17 10.30.2.17 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.18 10.30.2.18 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.19 10.30.2.19 route-map NAT-TO-DOMAIN
ip nat inside source list NAT-POOL-SRC pool SITE-POOL
```

H3 show running-config | include ip nat inside source

```
ip nat inside source static 192.168.30.10 10.30.3.10 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.11 10.30.3.11 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.12 10.30.3.12 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.13 10.30.3.13 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.14 10.30.3.14 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.15 10.30.3.15 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.16 10.30.3.16 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.17 10.30.3.17 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.18 10.30.3.18 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.19 10.30.3.19 route-map NAT-TO-DOMAIN
ip nat inside source list NAT-POOL-SRC pool SITE-POOL
```

Teardown (suite) Close All Connections

12.02 PASS NAT Inside And Outside Interfaces Are Marked Correctly (0.3s, 7 commands)

The LAN faces inside, the tunnels face outside. Getting this backwards silently disables translation rather than erroring.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains `ip nat inside` (checked 3×)
- output contains `ip nat outside` (checked 4×)

How it was checked

R1 show running-config interface GigabitEthernet3

Building configuration...

```
Current configuration : 145 bytes
!
interface GigabitEthernet3
 description LAN toward the local host
 ip address 192.168.10.1 255.255.255.0
 ip nat inside
 negotiation auto
```

```

end

R1 show running-config interface Tunnel0
Building configuration...

Current configuration : 399 bytes
!
interface Tunnel0
  description DMVPN hub
  ip address 172.20.0.1 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp redirect
  ip tcp adjust-mss 1360
  ... 6 more lines

R2 show running-config interface GigabitEthernet3
Building configuration...

Current configuration : 145 bytes
!
interface GigabitEthernet3
  description LAN toward the local host
  ip address 192.168.20.1 255.255.255.0
  ip nat inside
  negotiation auto
end

R2 show running-config interface Tunnel0
Building configuration...

Current configuration : 433 bytes
!
interface Tunnel0
  description DMVPN spoke
  ip address 172.20.0.2 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
  ip tcp adjust-mss 1360
  ... 6 more lines

R3 show running-config interface GigabitEthernet3
Building configuration...

Current configuration : 145 bytes
!
interface GigabitEthernet3
  description LAN toward the local host
  ip address 192.168.30.1 255.255.255.0
  ip nat inside
  negotiation auto
end

R3 show running-config interface Tunnel0
Building configuration...

Current configuration : 433 bytes
!
interface Tunnel0
  description DMVPN spoke
  ip address 172.20.0.3 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
  ip tcp adjust-mss 1360
  ... 6 more lines

R1 show running-config interface Tunnel0
Building configuration...

Current configuration : 399 bytes
!
interface Tunnel0
  description DMVPN hub

```

```

ip address 172.20.0.1 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp redirect
ip tcp adjust-mss 1360
... 6 more lines

```

Teardown (suite) Close All Connections

12.03 **PASS** Mapped Prefixes Are Advertised Across The Fabric (0.1s, 3 commands)

Return traffic can only find its way home if each site's NAT range is reachable, so the mapped prefixes ride BGP like the real ones.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains **Known via "bgp \${R2_ASN}"** (checked 2×)
- output contains **Known via "bgp \${R3_ASN}"**

How it was checked

R2 show ip route 10.30.1.0

```

Routing entry for 10.30.1.0/24
  Known via "bgp 65002", distance 20, metric 0
  Tag 65001, type external
  Last update from 172.20.0.1 00:03:47 ago
  Routing Descriptor Blocks:
    * 172.20.0.1, from 172.20.0.1, 00:03:47 ago
      opaque_ptr 0x7E32CED118A0
      Route metric is 0, traffic share count is 1
      AS Hops 1
      Route tag 65001
      MPLS label: none

```

R2 show ip route 10.30.3.0

```

Routing entry for 10.30.3.0/24
  Known via "bgp 65002", distance 20, metric 0
  Tag 65001, type external
  Last update from 172.20.0.3 00:03:47 ago
  Routing Descriptor Blocks:
    * 172.20.0.3, from 172.20.0.1, 00:03:47 ago
      opaque_ptr 0x7E32CED119E0
      Route metric is 0, traffic share count is 1
      AS Hops 2
      Route tag 65001
      MPLS label: none

```

R3 show ip route 10.30.1.0

```

Routing entry for 10.30.1.0/24
  Known via "bgp 65003", distance 20, metric 0
  Tag 65001, type external
  Last update from 172.20.0.1 00:03:48 ago
  Routing Descriptor Blocks:
    * 172.20.0.1, from 172.20.0.1, 00:03:48 ago
      opaque_ptr 0x75671E6ABAD8
      Route metric is 0, traffic share count is 1
      AS Hops 1
      Route tag 65001
      MPLS label: none

```

Teardown (suite) Close All Connections

12.04 **PASS** Every Host Reaches Every Other Host At Its Mapped Address (24.1s, 6 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains **0% packet loss** (checked 6×)
- ping from \${alias} to \${target} lost packets: \${out}

How it was checked

H2 ping -c 5 10.30.2.10

```

PING 10.30.2.10 (10.30.2.10) 56(84) bytes of data.

```

```
64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.35 ms
64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.17 ms
64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.20 ms
64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.11 ms
64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.39 ms

--- 10.30.2.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4005ms
rtt min/avg/max/mdev = 1.110/1.244/1.394/0.107 ms
```

H3 ping -c 5 10.30.3.10

```
PING 10.30.3.10 (10.30.3.10) 56(84) bytes of data.
64 bytes from 10.30.3.10: icmp_seq=1 ttl=62 time=1.08 ms
64 bytes from 10.30.3.10: icmp_seq=2 ttl=62 time=1.21 ms
64 bytes from 10.30.3.10: icmp_seq=3 ttl=62 time=1.10 ms
64 bytes from 10.30.3.10: icmp_seq=4 ttl=62 time=1.20 ms
64 bytes from 10.30.3.10: icmp_seq=5 ttl=62 time=1.21 ms

--- 10.30.3.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4005ms
rtt min/avg/max/mdev = 1.076/1.157/1.210/0.057 ms
```

H1 ping -c 5 10.30.1.10

```
PING 10.30.1.10 (10.30.1.10) 56(84) bytes of data.
64 bytes from 10.30.1.10: icmp_seq=1 ttl=62 time=1.29 ms
64 bytes from 10.30.1.10: icmp_seq=2 ttl=62 time=1.58 ms
64 bytes from 10.30.1.10: icmp_seq=3 ttl=62 time=1.09 ms
64 bytes from 10.30.1.10: icmp_seq=4 ttl=62 time=1.10 ms
64 bytes from 10.30.1.10: icmp_seq=5 ttl=62 time=1.11 ms

--- 10.30.1.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.091/1.233/1.579/0.187 ms
```

H3 ping -c 5 10.30.3.10

```
PING 10.30.3.10 (10.30.3.10) 56(84) bytes of data.
64 bytes from 10.30.3.10: icmp_seq=1 ttl=62 time=1.16 ms
64 bytes from 10.30.3.10: icmp_seq=2 ttl=62 time=1.27 ms
64 bytes from 10.30.3.10: icmp_seq=3 ttl=62 time=1.24 ms
64 bytes from 10.30.3.10: icmp_seq=4 ttl=62 time=1.17 ms
64 bytes from 10.30.3.10: icmp_seq=5 ttl=62 time=1.14 ms

--- 10.30.3.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4005ms
rtt min/avg/max/mdev = 1.135/1.194/1.265/0.049 ms
```

H1 ping -c 5 10.30.1.10

```
PING 10.30.1.10 (10.30.1.10) 56(84) bytes of data.
64 bytes from 10.30.1.10: icmp_seq=1 ttl=62 time=1.27 ms
64 bytes from 10.30.1.10: icmp_seq=2 ttl=62 time=1.23 ms
64 bytes from 10.30.1.10: icmp_seq=3 ttl=62 time=1.29 ms
64 bytes from 10.30.1.10: icmp_seq=4 ttl=62 time=1.16 ms
64 bytes from 10.30.1.10: icmp_seq=5 ttl=62 time=1.10 ms

--- 10.30.1.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.097/1.209/1.287/0.071 ms
```

H2 ping -c 5 10.30.2.10

```
PING 10.30.2.10 (10.30.2.10) 56(84) bytes of data.
64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.35 ms
64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.26 ms
64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.33 ms
64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.02 ms
64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.21 ms

--- 10.30.2.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.018/1.232/1.352/0.118 ms
```

Teardown (suite) Close All Connections

12.05 PASS Translations Show The Host Rewritten To Its Mapped Address (4.2s, 2 commands)

The inside-local / inside-global pair is the direct evidence that the source address was rewritten.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains **0% packet loss**
ping from \${alias} to \${target} lost packets: \${out}

- output matches `icmpseq=${H1_NAT_IP}:::id+ls=${H1_IP}:::id+ls=${H2_NAT_IP}`

How it was checked

H1 ping -c 5 10.30.2.10

```
PING 10.30.2.10 (10.30.2.10) 56(84) bytes of data.
64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.17 ms
64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.28 ms
64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.15 ms
64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.19 ms
64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.16 ms

--- 10.30.2.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.147/1.188/1.284/0.049 ms
```

R1 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.1.128	192.168.10.88	---	---
---	10.30.1.129	192.168.10.85	---	---
---	10.30.1.113	192.168.10.93	---	---
---	10.30.1.114	192.168.10.69	---	---
---	10.30.1.116	192.168.10.73	---	---
---	10.30.1.119	192.168.10.71	---	---
---	10.30.1.123	192.168.10.78	---	---
---	10.30.1.120	192.168.10.82	---	---
---	10.30.1.126	192.168.10.76	---	---
---	10.30.1.125	192.168.10.84	---	---
---	10.30.1.101	192.168.10.90	---	---
---	10.30.1.102	192.168.10.89	---	---
---	10.30.1.111	192.168.10.70	---	---

... 35 more lines

Teardown (suite) Close All Connections

12.06 PASS The Far Host Sees The Mapped Source Not The Real One (4.2s, 2 commands)

On the receiving router the peer appears as the sender's mapped address, which is the whole point of source NAT.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains **0% packet loss**
ping from \${alias} to \${target} lost packets: \${out}
- output contains `${H1_NAT_IP}`
- output does not contain `${H1_IP}`

How it was checked

H1 ping -c 5 10.30.2.10

```
PING 10.30.2.10 (10.30.2.10) 56(84) bytes of data.
64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.27 ms
64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.11 ms
64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.58 ms
64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.25 ms
64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.17 ms

--- 10.30.2.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.112/1.276/1.583/0.163 ms
```

R2 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.2.128	192.168.20.89	---	---
---	10.30.2.129	192.168.20.84	---	---
---	10.30.2.106	192.168.20.68	---	---
---	10.30.2.105	192.168.20.88	---	---
---	10.30.2.111	192.168.20.92	---	---
---	10.30.2.108	192.168.20.80	---	---
---	10.30.2.101	192.168.20.64	---	---
---	10.30.2.102	192.168.20.65	---	---
---	10.30.2.126	192.168.20.77	---	---
---	10.30.2.125	192.168.20.86	---	---
---	10.30.2.123	192.168.20.79	---	---
---	10.30.2.120	192.168.20.74	---	---
---	10.30.2.116	192.168.20.82	---	---

... 36 more lines

Teardown (suite) Close All Connections

12.07 PASS Spoke To Spoke NAT Works Through The Hub (4.4s, 3 commands)

h2 -> h3 by mapped address crosses two tunnels and two translations, with no direct spoke-to-spoke path.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains **0% packet loss**
ping from \${alias} to \${target} lost packets: \${out}
- output contains **\${H3_NAT_IP}**
- output contains **\${H2_NAT_IP}**

How it was checked

H2 ping -c 5 10.30.3.10

```
PING 10.30.3.10 (10.30.3.10) 56(84) bytes of data.  
64 bytes from 10.30.3.10: icmp_seq=1 ttl=62 time=1.19 ms  
64 bytes from 10.30.3.10: icmp_seq=2 ttl=62 time=1.23 ms  
64 bytes from 10.30.3.10: icmp_seq=3 ttl=62 time=1.24 ms  
64 bytes from 10.30.3.10: icmp_seq=4 ttl=62 time=1.21 ms  
64 bytes from 10.30.3.10: icmp_seq=5 ttl=62 time=1.18 ms  
  
--- 10.30.3.10 ping statistics ---  
5 packets transmitted, 5 received, 0% packet loss, time 4006ms  
rtt min/avg/max/mdev = 1.179/1.208/1.241/0.023 ms
```

R2 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.2.128	192.168.20.89	---	---
---	10.30.2.129	192.168.20.84	---	---
---	10.30.2.106	192.168.20.68	---	---
---	10.30.2.105	192.168.20.88	---	---
---	10.30.2.111	192.168.20.92	---	---
---	10.30.2.108	192.168.20.80	---	---
---	10.30.2.101	192.168.20.64	---	---
---	10.30.2.102	192.168.20.65	---	---
---	10.30.2.126	192.168.20.77	---	---
---	10.30.2.125	192.168.20.86	---	---
---	10.30.2.123	192.168.20.79	---	---
---	10.30.2.120	192.168.20.74	---	---
---	10.30.2.116	192.168.20.82	---	---

... 37 more lines

R3 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.3.104	192.168.30.84	---	---
---	10.30.3.107	192.168.30.93	---	---
---	10.30.3.109	192.168.30.92	---	---
---	10.30.3.110	192.168.30.89	---	---
---	10.30.3.103	192.168.30.85	---	---
---	10.30.3.100	192.168.30.83	---	---
---	10.30.3.124	192.168.30.90	---	---
---	10.30.3.127	192.168.30.81	---	---
---	10.30.3.121	192.168.30.80	---	---
---	10.30.3.122	192.168.30.77	---	---
---	10.30.3.118	192.168.30.86	---	---
---	10.30.3.117	192.168.30.75	---	---
---	10.30.3.115	192.168.30.82	---	---

... 38 more lines

Teardown (suite) Close All Connections

12.08 PASS NATted Traffic Is Still Encrypted (19.6s, 5 commands)

Translation happens before encryption, so NATted traffic must still raise the ESP counters.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains **0% packet loss**
ping from \${alias} to \${target} lost packets: \${out}
- **\${r1_enc} >= \${expected}** holds
- **\${r1_dec} >= \${expected}** holds

- `${r2_enc} >= ${expected}` holds
- `${r2_dec} >= ${expected}` holds

How it was checked

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 78330, #pkts encrypt: 78330, #pkts digest: 78330
  #pkts decaps: 41533, #pkts decrypt: 41533, #pkts verify: 41533
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

R2 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 51108, #pkts encrypt: 51108, #pkts digest: 51108
  #pkts decaps: 26710, #pkts decrypt: 26710, #pkts verify: 26710
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

H1 ping -c 20 10.30.2.10

```
PING 10.30.2.10 (10.30.2.10) 56(84) bytes of data.
64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.29 ms
64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.08 ms
64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.23 ms
64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.22 ms
64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.36 ms
64 bytes from 10.30.2.10: icmp_seq=6 ttl=62 time=1.26 ms
64 bytes from 10.30.2.10: icmp_seq=7 ttl=62 time=1.24 ms
64 bytes from 10.30.2.10: icmp_seq=8 ttl=62 time=1.15 ms
64 bytes from 10.30.2.10: icmp_seq=9 ttl=62 time=1.07 ms
64 bytes from 10.30.2.10: icmp_seq=10 ttl=62 time=1.22 ms
64 bytes from 10.30.2.10: icmp_seq=11 ttl=62 time=1.10 ms
64 bytes from 10.30.2.10: icmp_seq=12 ttl=62 time=1.28 ms
64 bytes from 10.30.2.10: icmp_seq=13 ttl=62 time=1.13 ms
... 11 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 78460, #pkts encrypt: 78460, #pkts digest: 78460
  #pkts decaps: 41665, #pkts decrypt: 41665, #pkts verify: 41665
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

R2 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 51217, #pkts encrypt: 51217, #pkts digest: 51217
```

```

#pkts decaps: 26818, #pkts decrypt: 26818, #pkts verify: 26818
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

Teardown (suite) Close All Connections

12.09 PASS Mapped Addresses Never Appear In Cleartext On The WAN (14.0s, 18 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains **0% packet loss**
ping from \${alias} to \${target} lost packets: \${out}
- output contains **ESP**
- output does not contain **\${H1_NAT_IP}**
- output does not contain **\${H2_NAT_IP}**
- output does not contain **\${H1_IP}**

How it was checked

R1 no monitor capture NATCAP

Capture does not exist

R1 monitor capture NATCAP interface GigabitEthernet2 both

\${output} =

R1 monitor capture NATCAP match ipv4 any any

\${output} =

R1 monitor capture NATCAP buffer size 5

\${output} =

R1 monitor capture NATCAP start

Started capture point : NATCAP

R1 ping 100.64.0.2 repeat 2

Type escape sequence to abort.

Sending 2, 100-byte ICMP Echos to 100.64.0.2, timeout is 2 seconds:

!!

Success rate is 100 percent (2/2), round-trip min/avg/max = 1/1/2 ms

R1 monitor capture NATCAP stop

Stopped capture point : NATCAP

R1 show monitor capture NATCAP buffer brief

```

-----
#   size  timestamp      source          destination    dscp  protocol
-----
0  114    0.000000    100.64.0.1      -> 100.64.0.2    0 BE  ICMP
1  114    0.000000    100.64.0.2      -> 100.64.0.1    0 BE  ICMP
2  114    0.001007    100.64.0.1      -> 100.64.0.2    0 BE  ICMP
3  114    0.001998    100.64.0.2      -> 100.64.0.1    0 BE  ICMP
4  138    0.049008    100.64.0.1      -> 100.64.0.2    48 CS6 ESP
5  138    0.050000    100.64.0.2      -> 100.64.0.1    48 CS6 ESP
6  138    0.133995    100.64.0.1      -> 100.64.0.3    48 CS6 ESP
7  138    0.135002    100.64.0.3      -> 100.64.0.1    48 CS6 ESP
8  138    0.161994    100.64.0.3      -> 100.64.0.1    48 CS6 ESP
9  138    0.161994    100.64.0.1      -> 100.64.0.3    48 CS6 ESP
10 138    0.387040    100.64.0.2      -> 100.64.0.1    48 CS6 ESP
... 39 more lines

```

R1 no monitor capture NATCAP

\${output} =

R1 no monitor capture NATCAP

Capture does not exist

R1 monitor capture NATCAP interface GigabitEthernet2 both

\${output} =

R1 monitor capture NATCAP match ipv4 any any

\${output} =

R1 monitor capture NATCAP buffer size 5

\${output} =

R1 monitor capture NATCAP start

Started capture point : NATCAP

H1 ping -c 10 10.30.2.10

PING 10.30.2.10 (10.30.2.10) 56(84) bytes of data.

```

64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.20 ms
64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.19 ms
64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.15 ms
64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.21 ms
64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.19 ms
64 bytes from 10.30.2.10: icmp_seq=6 ttl=62 time=1.65 ms
64 bytes from 10.30.2.10: icmp_seq=7 ttl=62 time=1.23 ms
64 bytes from 10.30.2.10: icmp_seq=8 ttl=62 time=1.12 ms
64 bytes from 10.30.2.10: icmp_seq=9 ttl=62 time=1.34 ms
64 bytes from 10.30.2.10: icmp_seq=10 ttl=62 time=1.25 ms

--- 10.30.2.10 ping statistics ---
10 packets transmitted, 10 received, 0% packet loss, time 9013ms
... 1 more lines

```

R1 monitor capture NATCAP stop

Stopped capture point : NATCAP

R1 show monitor capture NATCAP buffer brief

```

-----
#   size  timestamp      source          destination    dscp    protocol
-----
0   170    0.000000    100.64.0.1     -> 100.64.0.2    0 BE    ESP
1   170    0.000992    100.64.0.2     -> 100.64.0.1    0 BE    ESP
2   138    0.005997    100.64.0.2     -> 100.64.0.1    48 CS6   ESP
3   138    0.005997    100.64.0.1     -> 100.64.0.2    48 CS6   ESP
4   138    0.035994    100.64.0.3     -> 100.64.0.1    48 CS6   ESP
5   138    0.035994    100.64.0.1     -> 100.64.0.3    48 CS6   ESP
6   138    0.130990    100.64.0.1     -> 100.64.0.3    48 CS6   ESP
7   138    0.148995    100.64.0.3     -> 100.64.0.1    48 CS6   ESP
8   138    0.248980    100.64.0.2     -> 100.64.0.1    48 CS6   ESP
9   138    0.248980    100.64.0.1     -> 100.64.0.2    48 CS6   ESP
10  138    0.403971    100.64.0.1     -> 100.64.0.2    48 CS6   ESP
... 226 more lines

```

R1 no monitor capture NATCAP

\${output} =

Teardown (suite) Close All Connections

12.10 PASS The Untranslated LAN Path Still Works (8.0s, 2 commands)

Guards the route-map scoping. If translation ever widened to all traffic, replies on this path would arrive from a mapped address the sender never contacted, and this would fail.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Warm Up NAT Paths

Acceptance criteria

- output contains **0% packet loss** (checked 2×)
ping from \${alias} to \${target} lost packets: \${out}

How it was checked

H1 ping -c 5 192.168.20.10

```

PING 192.168.20.10 (192.168.20.10) 56(84) bytes of data.
64 bytes from 192.168.20.10: icmp_seq=1 ttl=62 time=1.19 ms
64 bytes from 192.168.20.10: icmp_seq=2 ttl=62 time=1.34 ms
64 bytes from 192.168.20.10: icmp_seq=3 ttl=62 time=1.34 ms
64 bytes from 192.168.20.10: icmp_seq=4 ttl=62 time=1.10 ms
64 bytes from 192.168.20.10: icmp_seq=5 ttl=62 time=1.09 ms

--- 192.168.20.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.093/1.210/1.337/0.107 ms

```

H2 ping -c 5 192.168.30.10

```

PING 192.168.30.10 (192.168.30.10) 56(84) bytes of data.
64 bytes from 192.168.30.10: icmp_seq=1 ttl=62 time=1.20 ms
64 bytes from 192.168.30.10: icmp_seq=2 ttl=62 time=1.19 ms
64 bytes from 192.168.30.10: icmp_seq=3 ttl=62 time=1.18 ms
64 bytes from 192.168.30.10: icmp_seq=4 ttl=62 time=1.28 ms
64 bytes from 192.168.30.10: icmp_seq=5 ttl=62 time=1.22 ms

--- 192.168.30.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4005ms
rtt min/avg/max/mdev = 1.180/1.213/1.275/0.033 ms

```

Teardown (suite) Close All Connections

13 Nat Pool

13.01 **PASS** Every Host Carries Its Full Block Of Addresses (0.1s, 6 commands)

10 statically mapped plus 30 pool-eligible, on one interface.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- output contains `${lan}.${o}/24` (checked 12×)
- `${n}` equals 40 (checked 3×)

How it was checked

H1 ip addr show eth1

```
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:01:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.10.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.229.55/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.12/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.13/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.14/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    ... 70 more lines
```

```
H1 ip addr show eth1 | grep -c 'inet 192.168.10.'
40
```

H2 ip addr show eth1

```
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:02:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.20.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.199.41/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.12/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.13/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.14/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    ... 70 more lines
```

```
H2 ip addr show eth1 | grep -c 'inet 192.168.20.'
40
```

H3 ip addr show eth1

```
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:03:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.30.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.207.242/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.12/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.13/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.14/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    ... 70 more lines
```

```
H3 ip addr show eth1 | grep -c 'inet 192.168.30.'
40
```

Teardown (suite) Close All Connections

13.02 **PASS** Every Router Configures Ten Static Mappings And A Thirty Address Pool (0.4s, 6 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- output contains = **10** (checked 3×)
- output contains **total addresses 30** (checked 3×)

How it was checked

H1 `show running-config | count ^ip nat inside source static`

Number of lines which match regexp = 10

H1 `show ip nat statistics`

Total active translations: 10 (10 static, 0 dynamic; 0 extended)

Outside interfaces:

Tunnel0

Inside interfaces:

GigabitEthernet3

Hits: 0 Misses: 0

Reserved port setting disabled provisioned no

Dynamic overload mapping configured: 0

Expired translations: 0

Dynamic mappings:

-- Inside Source

[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 0

pool SITE-POOL: id 1, netmask 255.255.255.0

start 10.30.1.100 end 10.30.1.129

... 9 more lines

H2 `show running-config | count ^ip nat inside source static`

Number of lines which match regexp = 10

H2 `show ip nat statistics`

Total active translations: 10 (10 static, 0 dynamic; 0 extended)

Outside interfaces:

Tunnel0

Inside interfaces:

GigabitEthernet3

Hits: 0 Misses: 0

Reserved port setting disabled provisioned no

Dynamic overload mapping configured: 0

Expired translations: 0

Dynamic mappings:

-- Inside Source

[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 0

pool SITE-POOL: id 1, netmask 255.255.255.0

start 10.30.2.100 end 10.30.2.129

... 9 more lines

H3 `show running-config | count ^ip nat inside source static`

Number of lines which match regexp = 10

H3 `show ip nat statistics`

Total active translations: 10 (10 static, 0 dynamic; 0 extended)

Outside interfaces:

Tunnel0

Inside interfaces:

GigabitEthernet3

Hits: 0 Misses: 0

Reserved port setting disabled provisioned no

Dynamic overload mapping configured: 0

Expired translations: 0

Dynamic mappings:

-- Inside Source

[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 0

pool SITE-POOL: id 1, netmask 255.255.255.0

start 10.30.3.100 end 10.30.3.129

... 9 more lines

Teardown (suite) Close All Connections

13.03 **PASS** The Pool Access List Is One Range And Excludes The Static Block (0.1s, 3 commands)

A single /27 range rather than thirty host entries, and it must not overlap the statically mapped addresses -- otherwise which rule wins depends on evaluation order.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- **#{permits}** has exactly **1** entries (checked 3×)
NAT-POOL-SRC should hold one range entry, found #{permits}
- output contains **#{lan}.#{DYN_OCTET_FIRST} 0.0.0.31** (checked 3×)
- output does not contain **host #{lan}.#{o}** (checked 6×)

How it was checked

H1 show ip access-lists NAT-POOL-SRC

```
Extended IP access list NAT-POOL-SRC
 10 permit ip 192.168.10.64 0.0.0.31 10.30.0.0 0.0.255.255
```

H2 show ip access-lists NAT-POOL-SRC

```
Extended IP access list NAT-POOL-SRC
 10 permit ip 192.168.20.64 0.0.0.31 10.30.0.0 0.0.255.255
```

H3 show ip access-lists NAT-POOL-SRC

```
Extended IP access list NAT-POOL-SRC
 10 permit ip 192.168.30.64 0.0.0.31 10.30.0.0 0.0.255.255
```

Teardown (suite) Close All Connections

13.04 PASS All Ten Static Addresses Translate To Their Own Fixed Mapping (9.5s, 2 commands)

Static NAT is one-to-one and deterministic: inside .10-.19 must appear outside as .10-.19, each to its own.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- **#{static}** has exactly **10** entries
only #{static} of the 10 static addresses were translated
- **#{d}** equals **10**
the 10 static addresses shared outside addresses; they must be one-to-one
- **#{aligned}** holds

How it was checked

H1 for i in \$(seq 10 19) \$(seq 64 93); do ping -c 2 -W 2 -I 192.168.10.\$i 10.30.2.10 >/dev/null 2>&1 & done; wait; echo SENT

```
SENT
[40]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[39]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[38]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[37]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[36]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[35]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[34]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[33]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[32]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[31]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[30]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[29]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
[28]+ Done ping -c 2 -W 2 -I 192.168.10.#{i} 10.30.2.10 1>/dev/null 2>&1
... 27 more lines
```

R1 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.1.128	192.168.10.89	---	---
---	10.30.1.129	192.168.10.82	---	---
---	10.30.1.113	192.168.10.77	---	---
---	10.30.1.114	192.168.10.66	---	---
---	10.30.1.116	192.168.10.69	---	---
---	10.30.1.119	192.168.10.86	---	---
---	10.30.1.123	192.168.10.93	---	---
---	10.30.1.120	192.168.10.76	---	---
---	10.30.1.126	192.168.10.71	---	---
---	10.30.1.125	192.168.10.72	---	---
---	10.30.1.101	192.168.10.84	---	---
---	10.30.1.102	192.168.10.83	---	---
---	10.30.1.111	192.168.10.67	---	---
---	...	68 more lines	---	---

Teardown (suite) Close All Connections

13.05 **PASS** All Thirty Pool Addresses Translate Into The Pool And Are Distinct (0.5s, 1

commands)

Without overload each client takes its own pool address, so 30 clients must yield 30 different outside addresses.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- **\${dyn}** has exactly **30** entries
only **\${dyn}** of the 30 pool clients were translated
- **\${d}** equals **30**
pool clients shared outside addresses; that is overload, not a 1:1 pool
- **\${within}** holds

How it was checked

R1 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.1.128	192.168.10.89	---	---
---	10.30.1.129	192.168.10.82	---	---
---	10.30.1.113	192.168.10.77	---	---
---	10.30.1.114	192.168.10.66	---	---
---	10.30.1.116	192.168.10.69	---	---
---	10.30.1.119	192.168.10.86	---	---
---	10.30.1.123	192.168.10.93	---	---
---	10.30.1.120	192.168.10.76	---	---
---	10.30.1.126	192.168.10.71	---	---
---	10.30.1.125	192.168.10.72	---	---
---	10.30.1.101	192.168.10.84	---	---
---	10.30.1.102	192.168.10.83	---	---
---	10.30.1.111	192.168.10.67	---	---
... 68 more lines				

Teardown (suite) Close All Connections

13.06 **PASS** The Pool Is Exactly Consumed With No Misses (0.0s, 1 commands)

30 clients against a 30 address pool: full allocation and no misses is the evidence that none of them shared or failed.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- output contains **allocated 30 (100%)**
- output matches **misses 0**

How it was checked

R1 show ip nat statistics

```
Total active translations: 80 (10 static, 70 dynamic; 40 extended)
Outside interfaces:
  Tunnel0
Inside interfaces:
  GigabitEthernet3
Hits: 120 Misses: 40
Reserved port setting disabled provisioned no
Dynamic overload mapping configured: 0
Expired translations: 0
Dynamic mappings:
-- Inside Source
[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 60
  pool SITE-POOL: id 1, netmask 255.255.255.0
    start 10.30.1.100 end 10.30.1.129
... 9 more lines
```

Teardown (suite) Close All Connections

13.07 PASS A Thirty-first Client Gets No Translation Once The Pool Is Exhausted (7.3s, 8

commands)

The boundary the pool sizing never otherwise reaches. The pool holds exactly as many addresses as there are clients, which means the exhaustion path is never exercised by a normal run -- and an off-by-one in pool bounds would look identical to a correct configuration. So bring up one more client inside the pool ACL and require the router to refuse it: no translation, no borrowing of another client's address, and the miss counted. Without "overload" there is nothing to share, so silently reusing an address would be a correctness bug, not graceful degradation. Run against R1/H1, because it is R1's pool that the tests above fill: the suite drives traffic from H1 first and only reaches the other routers later. Asserting exhaustion on a router whose pool is still empty would test nothing.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- output contains **allocated 30 (100%)**
- **`\${n}`** is not empty (checked 3×)
- output contains **100% packet loss**
the thirty-first client was translated even though the pool was exhausted
- **`\${xlate}`** is empty
- **`\${after}`** > **`\${before}`** holds (checked 2×)

How it was checked

R1 show ip nat statistics | include allocated

type generic, total addresses 30, allocated 30 (100%), misses 0

R1 show ip nat statistics

Total active translations: 80 (10 static, 70 dynamic; 40 extended)

Outside interfaces:

Tunnel0

Inside interfaces:

GigabitEthernet3

Hits: 120 Misses: 40

Reserved port setting disabled provisioned no

Dynamic overload mapping configured: 0

Expired translations: 0

Dynamic mappings:

-- Inside Source

[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 60

pool SITE-POOL: id 1, netmask 255.255.255.0

start 10.30.1.100 end 10.30.1.129

... 9 more lines

H1 sudo ip addr add 192.168.10.94/24 dev eth1

\${output} =

H1 ping -c 3 -W 2 -I 192.168.10.94 10.30.2.10

PING 10.30.2.10 (10.30.2.10) from 192.168.10.94 : 56(84) bytes of data.

From 192.168.10.1 icmp_seq=1 Destination Host Unreachable

From 192.168.10.1 icmp_seq=2 Destination Host Unreachable

From 192.168.10.1 icmp_seq=3 Destination Host Unreachable

--- 10.30.2.10 ping statistics ---

3 packets transmitted, 0 received, +3 errors, 100% packet loss, time 2049ms

R1 show ip nat translations | include 192.168.10.94

\${output} =

R1 show ip nat statistics

Total active translations: 80 (10 static, 70 dynamic; 40 extended)

Outside interfaces:

Tunnel0

Inside interfaces:

GigabitEthernet3

Hits: 120 Misses: 40

Reserved port setting disabled provisioned no

Dynamic overload mapping configured: 0

Expired translations: 0

Dynamic mappings:

-- Inside Source

[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 60

pool SITE-POOL: id 1, netmask 255.255.255.0

start 10.30.1.100 end 10.30.1.129

... 9 more lines

R1 show ip nat statistics

Total active translations: 80 (10 static, 70 dynamic; 40 extended)

Outside interfaces:

```

Tunnel0
Inside interfaces:
  GigabitEthernet3
Hits: 120 Misses: 40
Reserved port setting disabled provisioned no
Dynamic overload mapping configured: 0
Expired translations: 0
Dynamic mappings:
-- Inside Source
[Id: 1] access-list NAT-POOL-SRC pool SITE-POOL refcount 60
  pool SITE-POOL: id 1, netmask 255.255.255.0
    start 10.30.1.100 end 10.30.1.129
... 9 more lines

```

```

H1 sudo ip addr del 192.168.10.94/24 dev eth1
${output} =

```

Teardown (this test) Remove The Spare Client From H1

13.08 PASS The Pool Is Still Intact After The Exhaustion Attempt (0.5s, 2 commands)

The refusal must cost nothing: the thirty legitimate clients keep the addresses they held, and none was evicted to make room for the one that was turned away.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- output contains **allocated 30 (100%)**
- **\${dyn}** has exactly **30** entries
only **\${dyn}** of the original thirty pool clients still hold a translation
- **\${d}** equals **30**
the refused client caused two survivors to share an address

How it was checked

R1 show ip nat statistics | include allocated

```

type generic, total addresses 30, allocated 30 (100%), misses 3

```

R1 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.1.128	192.168.10.89	---	---
---	10.30.1.129	192.168.10.82	---	---
---	10.30.1.113	192.168.10.77	---	---
---	10.30.1.114	192.168.10.66	---	---
---	10.30.1.116	192.168.10.69	---	---
---	10.30.1.119	192.168.10.86	---	---
---	10.30.1.123	192.168.10.93	---	---
---	10.30.1.120	192.168.10.76	---	---
---	10.30.1.126	192.168.10.71	---	---
---	10.30.1.125	192.168.10.72	---	---
---	10.30.1.101	192.168.10.84	---	---
---	10.30.1.102	192.168.10.83	---	---
---	10.30.1.111	192.168.10.67	---	---
---	...	68 more lines	---	---

Teardown (suite) Close All Connections

13.09 PASS Static And Pool Translations Coexist Across The Whole Block (0.5s, 1 commands)

All 40 of a host's addresses in flight, translated by two different mechanisms, with no outside address reused.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- **\${all}** has exactly **40** entries
expected 40 translated addresses, found **\${all}**
- **\${d}** equals **40**
the 40 inside addresses did not receive 40 distinct outside addresses

How it was checked

R1 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.1.128	192.168.10.89	---	---
---	10.30.1.129	192.168.10.82	---	---

```

--- 10.30.1.113      192.168.10.77      ---      ---
--- 10.30.1.114      192.168.10.66      ---      ---
--- 10.30.1.116      192.168.10.69      ---      ---
--- 10.30.1.119      192.168.10.86      ---      ---
--- 10.30.1.123      192.168.10.93      ---      ---
--- 10.30.1.120      192.168.10.76      ---      ---
--- 10.30.1.126      192.168.10.71      ---      ---
--- 10.30.1.125      192.168.10.72      ---      ---
--- 10.30.1.101      192.168.10.84      ---      ---
--- 10.30.1.102      192.168.10.83      ---      ---
--- 10.30.1.111      192.168.10.67      ---      ---
... 68 more lines

```

Teardown (suite) Close All Connections

13.10 PASS Both Mechanisms Work On Every Router (19.5s, 4 commands)

The spokes carry the same scheme, not just the hub.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- `${static}` has exactly **10** entries (checked 2×)
- `${dyn}` has exactly **30** entries (checked 2×)
- `${aligned}` holds (checked 2×)

How it was checked

H2 for i in \$(seq 10 19) \$(seq 64 93); do ping -c 2 -W 2 -I 192.168.20.\$i 10.30.1.10 >/dev/null 2>&1 & done; wait;

echo SENT

```

SENT
[40]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[39]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[38]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[37]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[36]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[35]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[34]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[33]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[32]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[31]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[30]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[29]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
[28]+ Done      ping -c 2 -W 2 -I 192.168.20.${i} 10.30.1.10 1>/dev/null 2>&1
... 27 more lines

```

H2 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.2.128	192.168.20.87	---	---
---	10.30.2.129	192.168.20.82	---	---
---	10.30.2.106	192.168.20.66	---	---
---	10.30.2.105	192.168.20.84	---	---
---	10.30.2.111	192.168.20.77	---	---
---	10.30.2.108	192.168.20.75	---	---
---	10.30.2.101	192.168.20.91	---	---
---	10.30.2.102	192.168.20.64	---	---
---	10.30.2.126	192.168.20.72	---	---
---	10.30.2.125	192.168.20.74	---	---
---	10.30.2.123	192.168.20.93	---	---
---	10.30.2.120	192.168.20.83	---	---
---	10.30.2.116	192.168.20.79	---	---

... 108 more lines

H3 for i in \$(seq 10 19) \$(seq 64 93); do ping -c 2 -W 2 -I 192.168.30.\$i 10.30.1.10 >/dev/null 2>&1 & done; wait;

echo SENT

```

SENT
[40]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[39]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[38]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[37]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[36]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[35]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[34]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[33]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[32]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[31]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[30]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[29]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1
[28]+ Done      ping -c 2 -W 2 -I 192.168.30.${i} 10.30.1.10 1>/dev/null 2>&1

```

... 27 more lines

H3 show ip nat translations

Pro	Inside global	Inside local	Outside local	Outside global
---	10.30.3.104	192.168.30.75	---	---
---	10.30.3.107	192.168.30.92	---	---
---	10.30.3.109	192.168.30.93	---	---
---	10.30.3.110	192.168.30.91	---	---
---	10.30.3.103	192.168.30.88	---	---
---	10.30.3.100	192.168.30.87	---	---
---	10.30.3.124	192.168.30.90	---	---
---	10.30.3.127	192.168.30.83	---	---
---	10.30.3.121	192.168.30.86	---	---
---	10.30.3.122	192.168.30.82	---	---
---	10.30.3.118	192.168.30.89	---	---
---	10.30.3.117	192.168.30.84	---	---
---	10.30.3.115	192.168.30.77	---	---

... 68 more lines

Teardown (suite) Close All Connections

13.11 PASS Only The Static Mappings Live In The Configuration (0.1s, 1 commands)

Static mappings are configuration and survive a reload; pool allocations are runtime state and do not. Confusing the two is how NAT surprises people after a reboot.

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- output contains **static** `${H1_IP} ${H1_NAT_IP}`
- output does not contain `${NAT24}[R1].${POOL_OCTET_FIRST}`
- output contains **ip nat inside source list NAT-POOL-SRC pool SITE-POOL**

How it was checked

R1 show running-config | include ip nat inside source

```
ip nat inside source static 192.168.10.10 10.30.1.10 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.11 10.30.1.11 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.12 10.30.1.12 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.13 10.30.1.13 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.14 10.30.1.14 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.15 10.30.1.15 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.16 10.30.1.16 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.17 10.30.1.17 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.18 10.30.1.18 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.19 10.30.1.19 route-map NAT-TO-DOMAIN
ip nat inside source list NAT-POOL-SRC pool SITE-POOL
```

Teardown (suite) Close All Connections

13.12 PASS Traffic From Both Mechanisms Is Encrypted (38.6s, 6 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- output contains **0% packet loss** (checked 2×)
ping from `${source}` on `${alias}` to `${target}` lost packets
- `${r1_enc} >= ${expected}` holds
- `${r1_dec} >= ${expected}` holds
- `${r2_enc} >= ${expected}` holds
- `${r2_dec} >= ${expected}` holds

How it was checked

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

  protected vrf: (none)
  local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
  remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
  current_peer 100.64.0.2 port 500
    PERMIT, flags={origin_is_acl,}
```

```

#pkts encaps: 79005, #pkts encrypt: 79005, #pkts digest: 79005
#pkts decaps: 42201, #pkts decrypt: 42201, #pkts verify: 42201
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

R2 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 51572, #pkts encrypt: 51572, #pkts digest: 51572
#pkts decaps: 27172, #pkts decrypt: 27172, #pkts verify: 27172
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

H1 ping -c 20 -I 192.168.10.10 10.30.2.10

```

PING 10.30.2.10 (10.30.2.10) from 192.168.10.10 : 56(84) bytes of data.
64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.31 ms
64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.13 ms
64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.19 ms
64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.12 ms
64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.18 ms
64 bytes from 10.30.2.10: icmp_seq=6 ttl=62 time=1.13 ms
64 bytes from 10.30.2.10: icmp_seq=7 ttl=62 time=1.21 ms
64 bytes from 10.30.2.10: icmp_seq=8 ttl=62 time=1.22 ms
64 bytes from 10.30.2.10: icmp_seq=9 ttl=62 time=1.04 ms
64 bytes from 10.30.2.10: icmp_seq=10 ttl=62 time=1.22 ms
64 bytes from 10.30.2.10: icmp_seq=11 ttl=62 time=1.08 ms
64 bytes from 10.30.2.10: icmp_seq=12 ttl=62 time=1.07 ms
64 bytes from 10.30.2.10: icmp_seq=13 ttl=62 time=1.30 ms
... 11 more lines

```

H1 ping -c 20 -I 192.168.10.64 10.30.2.10

```

PING 10.30.2.10 (10.30.2.10) from 192.168.10.64 : 56(84) bytes of data.
64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.15 ms
64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.14 ms
64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.15 ms
64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.18 ms
64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.25 ms
64 bytes from 10.30.2.10: icmp_seq=6 ttl=62 time=1.30 ms
64 bytes from 10.30.2.10: icmp_seq=7 ttl=62 time=1.40 ms
64 bytes from 10.30.2.10: icmp_seq=8 ttl=62 time=1.12 ms
64 bytes from 10.30.2.10: icmp_seq=9 ttl=62 time=1.12 ms
64 bytes from 10.30.2.10: icmp_seq=10 ttl=62 time=1.10 ms
64 bytes from 10.30.2.10: icmp_seq=11 ttl=62 time=1.22 ms
64 bytes from 10.30.2.10: icmp_seq=12 ttl=62 time=1.16 ms
64 bytes from 10.30.2.10: icmp_seq=13 ttl=62 time=1.20 ms
... 11 more lines

```

R1 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 79269, #pkts encrypt: 79269, #pkts digest: 79269
#pkts decaps: 42468, #pkts decrypt: 42468, #pkts verify: 42468
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

R2 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500

```

```

    PERMIT, flags={origin_is_acl,}
#pkts encaps: 51793, #pkts encrypt: 51793, #pkts digest: 51793
#pkts decaps: 27393, #pkts decrypt: 27393, #pkts verify: 27393
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0
... 78 more lines

```

Teardown (suite) Close All Connections

13.13 PASS Neither Real Nor Translated Addresses Appear In Cleartext (11.5s, 9 commands)

Setup (suite) Open All Routers, Open All Hosts, Wait For NAT Routes, Reset Translations

Acceptance criteria

- output contains **0% packet loss**
ping from \${source} on \${alias} to \${target} lost packets
- output contains **ESP**
- output does not contain **\${LAN24}[H1].\${DYN_OCTET_FIRST}**
- output does not contain **\${NAT24}[R1].\${POOL_OCTET_FIRST}**

How it was checked

R1 no monitor capture POOLCAP

Capture does not exist

R1 monitor capture POOLCAP interface GigabitEthernet2 both

\${output} =

R1 monitor capture POOLCAP match ipv4 any any

\${output} =

R1 monitor capture POOLCAP buffer size 5

\${output} =

R1 monitor capture POOLCAP start

Started capture point : POOLCAP

H1 ping -c 10 -I 192.168.10.64 10.30.2.10

```

PING 10.30.2.10 (10.30.2.10) from 192.168.10.64 : 56(84) bytes of data.
 64 bytes from 10.30.2.10: icmp_seq=1 ttl=62 time=1.36 ms
 64 bytes from 10.30.2.10: icmp_seq=2 ttl=62 time=1.14 ms
 64 bytes from 10.30.2.10: icmp_seq=3 ttl=62 time=1.06 ms
 64 bytes from 10.30.2.10: icmp_seq=4 ttl=62 time=1.23 ms
 64 bytes from 10.30.2.10: icmp_seq=5 ttl=62 time=1.45 ms
 64 bytes from 10.30.2.10: icmp_seq=6 ttl=62 time=1.21 ms
 64 bytes from 10.30.2.10: icmp_seq=7 ttl=62 time=1.49 ms
 64 bytes from 10.30.2.10: icmp_seq=8 ttl=62 time=1.17 ms
 64 bytes from 10.30.2.10: icmp_seq=9 ttl=62 time=1.27 ms
 64 bytes from 10.30.2.10: icmp_seq=10 ttl=62 time=1.55 ms

```

--- 10.30.2.10 ping statistics ---

10 packets transmitted, 10 received, 0% packet loss, time 9013ms
... 1 more lines

R1 monitor capture POOLCAP stop

Stopped capture point : POOLCAP

R1 show monitor capture POOLCAP buffer brief

```

-----
#   size  timestamp      source          destination    dscp  protocol
-----
0  170    0.000000    100.64.0.1     -> 100.64.0.2    0 BE   ESP
1  170    0.000000    100.64.0.2     -> 100.64.0.1    0 BE   ESP
2  138    0.148003    100.64.0.3     -> 100.64.0.1    48 CS6  ESP
3  138    0.148003    100.64.0.1     -> 100.64.0.3    48 CS6  ESP
4  138    0.264986    100.64.0.2     -> 100.64.0.1    48 CS6  ESP
5  138    0.264986    100.64.0.1     -> 100.64.0.2    48 CS6  ESP
6  138    0.309997    100.64.0.1     -> 100.64.0.3    48 CS6  ESP
7  138    0.310989    100.64.0.3     -> 100.64.0.1    48 CS6  ESP
8  138    0.325987    100.64.0.1     -> 100.64.0.2    48 CS6  ESP
9  138    0.326995    100.64.0.2     -> 100.64.0.1    48 CS6  ESP
10 138    0.370983    100.64.0.1     -> 100.64.0.2    48 CS6  ESP
... 218 more lines

```

R1 no monitor capture POOLCAP

\${output} =

Teardown (suite) Close All Connections

14 Ntp

14.01 PASS Every Router Is An NTP Client Of The NMS Over The Management VRF (0.3s, 3 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains **ntp source \${OOB_INTF}[\${r}]** (checked 3×)
- output contains **ntp server vrf \${MGMT_VRF} \${NMS_OOB_IP}** (checked 3×)
- output does not contain **pool.ntp.org** (checked 3×)

How it was checked

R1 show running-config | include ^ntp

```
ntp source GigabitEthernet4
ntp server vrf MGMT 192.168.99.10
```

R2 show running-config | include ^ntp

```
ntp source GigabitEthernet4
ntp server vrf MGMT 192.168.99.10
```

R3 show running-config | include ^ntp

```
ntp source GigabitEthernet4
ntp server vrf MGMT 192.168.99.10
```

Teardown (suite) Close Nms Session, Close All Connections

14.02 PASS The NMS Itself Synchronises To The Public Pool (2.4s, 2 commands)

The precondition the rest of this suite rests on. chrony is configured "local stratum 10", so it serves time whether or not it has an upstream -- meaning the routers can agree perfectly on time that came from nowhere. This requires a real upstream: a reference that is not the local clock, and a stratum that proves it came from somewhere else.

Setup (suite) Open All Routers

Acceptance criteria

- output does not contain **7F7F0101**
the NMS is serving its own local clock, so lab time is fabricated
- **\${m}** is not empty
- **0 < \${m}[0] < \${MAX_STRATUM}** holds
- output matches **^*!s+!d+!l.d+!l.d+!l.d+**
the NMS has selected no upstream source: \${sources}

How it was checked

NMS chronyc tracking

```
Reference ID      : 44B793F0 (68.183.147.240)
Stratum          : 3
Ref time (UTC)   : Mon Sep 07 23:28:02 2026
System time      : 0.000295948 seconds fast of NTP time
Last offset      : -0.000096958 seconds
RMS offset       : 0.000707182 seconds
Frequency        : 8.692 ppm fast
Residual freq    : -0.005 ppm
Skew             : 0.229 ppm
Root delay       : 0.047848970 seconds
Root dispersion  : 0.003390881 seconds
Update interval  : 520.1 seconds
Leap status      : Normal
```

NMS chronyc -n sources

MS Name/IP address	Stratum	Poll	Reach	LastRx	Last sample
^+ 162.254.225.151	2	10	377	392	-3230us[-3230us] +/- 53ms
^* 68.183.147.240	2	10	377	582	+1658us[+1561us] +/- 28ms
^- 51.81.226.229	2	10	377	514	+862us[+862us] +/- 105ms
^+ 172.234.44.141	2	10	377	393	-401us[-401us] +/- 70ms
^+ 69.164.213.136	2	10	377	461	+239us[+239us] +/- 52ms
^+ 23.168.24.210	2	10	377	641	-2175us[-2271us] +/- 37ms

Teardown (suite) Close Nms Session, Close All Connections

14.03 PASS Every Router Appears As A Client Of The NMS (0.1s, 1 commands)

Seen from the server, which is where a missing client shows up as an absence rather than as a router quietly using something else.

Setup (suite) Open All Routers

Acceptance criteria

- output contains `${r}_OOB_IP` (checked 3×)

How it was checked

NMS `sudo chronyc clients`

Hostname	NTP	Drop	Int	IntL	Last	Cmd	Drop	Int	Last
192.168.99.3	74	0	7	-	88	0	0	-	-
192.168.99.2	82	0	7	-	37	0	0	-	-
192.168.99.1	75	0	7	-	22	0	0	-	-
localhost	0	0	-	-	-	24	0	7	0

Teardown (suite) Close Nms Session, Close All Connections

14.04 PASS Every Router Forms Associations With Pool Servers (0.1s, 3 commands)

Setup (suite) Open All Routers

Acceptance criteria

- `${rows}` is not empty (checked 3×)

How it was checked

R1 `show ntp associations`

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    22   128  377 0.075 0.224 4.458
* sys.peer, # selected, - outlyer, x falseticker, ~ configured
```

R2 `show ntp associations`

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    37   128  377 0.066 -1.229 5.509
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

R3 `show ntp associations`

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    88   128  377 0.072 0.066 4.738
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

Teardown (suite) Close Nms Session, Close All Connections

14.05 PASS Associations Become Reachable (0.1s, 3 commands)

A non-zero reach register means packets are actually coming back, which distinguishes a working client from one that has merely been configured.

Setup (suite) Open All Routers

Acceptance criteria

- `${up}` is not empty (checked 3×)

How it was checked

R1 `show ntp associations`

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    22   128  377 0.075 0.224 4.458
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

R2 `show ntp associations`

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    37   128  377 0.066 -1.229 5.509
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

R3 `show ntp associations`

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    88   128  377 0.072 0.066 4.738
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

Teardown (suite) Close Nms Session, Close All Connections

14.06 PASS Every Router Selects A System Peer (0.1s, 3 commands)

Setup (suite) Open All Routers

Acceptance criteria

- `${peer}` differs from `$(None)` (checked 3×)

How it was checked

R1 show ntp associations

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    22   128  377 0.075 0.224 4.458
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

R2 show ntp associations

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    38   128  377 0.066 -1.229 5.509
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

R3 show ntp associations

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    89   128  377 0.072 0.066 4.738
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

Teardown (suite) Close Nms Session, Close All Connections

14.07 PASS Every Router Clock Is Synchronised (0.1s, 3 commands)

The end state: IOS declares the clock synchronised. This lags real accuracy by a long way. IOS holds the flag back until its loopfilter leaves the 'FREQ' drift-measurement phase, measured on this platform at about 17 minutes from a cold NTP start -- while the offset is already within milliseconds well before that. The wait below is bounded to cover a freshly provisioned lab; on a lab that has been up it returns on the first poll and costs nothing.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **Clock is synchronized** (checked 3×)

How it was checked

R1 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0022 Hz, precision is 2**10
ntp uptime is 499000 (1/100 of seconds), resolution is 4000
reference time is EE49C932.33B64630 (23:37:22.202 UTC Mon Sep 7 2026)
clock offset is 0.2243 msec, root delay is 47.92 msec
root dispersion is 9.37 msec, peer dispersion is 4.45 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000008782 s/s
system poll interval is 128, last update was 23 sec ago.
```

R2 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0017 Hz, precision is 2**10
ntp uptime is 499000 (1/100 of seconds), resolution is 4000
reference time is EE49C7CF.28B439C8 (23:31:27.159 UTC Mon Sep 7 2026)
clock offset is -1.2297 msec, root delay is 47.91 msec
root dispersion is 13.09 msec, peer dispersion is 5.50 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000007039 s/s
system poll interval is 128, last update was 378 sec ago.
```

R3 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0021 Hz, precision is 2**10
ntp uptime is 499000 (1/100 of seconds), resolution is 4000
reference time is EE49C6D8.2AC08388 (23:27:20.167 UTC Mon Sep 7 2026)
clock offset is 0.0665 msec, root delay is 50.63 msec
root dispersion is 14.92 msec, peer dispersion is 4.73 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000008462 s/s
system poll interval is 128, last update was 625 sec ago.
```

Teardown (suite) Close Nms Session, Close All Connections

14.08 PASS Stratum Is Sane On Every Router (0.1s, 3 commands)

Stratum 16 means unsynchronised. A client of a stratum 1-2 pool server should land well below the limit.

Setup (suite) Open All Routers

Acceptance criteria

- `#{m}` is not empty (checked 3×)
- `#{m}[0] < #{MAX_STRATUM}` holds (checked 3×)

How it was checked

R1 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0022 Hz, precision is 2**10
ntp uptime is 499100 (1/100 of seconds), resolution is 4000
reference time is EE49C932.33B64630 (23:37:22.202 UTC Mon Sep 7 2026)
clock offset is 0.2243 msec, root delay is 47.92 msec
root dispersion is 9.37 msec, peer dispersion is 4.45 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000008782 s/s
system poll interval is 128, last update was 23 sec ago.
```

R2 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0017 Hz, precision is 2**10
ntp uptime is 499000 (1/100 of seconds), resolution is 4000
reference time is EE49C7CF.28B439C8 (23:31:27.159 UTC Mon Sep 7 2026)
clock offset is -1.2297 msec, root delay is 47.91 msec
root dispersion is 13.09 msec, peer dispersion is 5.50 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000007039 s/s
system poll interval is 128, last update was 378 sec ago.
```

R3 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0021 Hz, precision is 2**10
ntp uptime is 499000 (1/100 of seconds), resolution is 4000
reference time is EE49C6D8.2AC08388 (23:27:20.167 UTC Mon Sep 7 2026)
clock offset is 0.0665 msec, root delay is 50.63 msec
root dispersion is 14.92 msec, peer dispersion is 4.73 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000008462 s/s
system poll interval is 128, last update was 625 sec ago.
```

Teardown (suite) Close Nms Session, Close All Connections

14.09 PASS The Reference Is One Of The Peers The Router Actually Polls (0.1s, 6 commands)

Guards against a router calling itself synchronised to something that is not in its association list.

Setup (suite) Open All Routers

Acceptance criteria

- `#{ref}` is not empty (checked 3×)
- output contains `#{ref}[0]` (checked 3×)

How it was checked

R1 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0022 Hz, precision is 2**10
ntp uptime is 499100 (1/100 of seconds), resolution is 4000
reference time is EE49C932.33B64630 (23:37:22.202 UTC Mon Sep 7 2026)
clock offset is 0.2243 msec, root delay is 47.92 msec
root dispersion is 9.37 msec, peer dispersion is 4.45 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000008782 s/s
system poll interval is 128, last update was 23 sec ago.
```

R1 show ntp associations

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    23   128  377  0.075  0.224  4.458
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

R2 show ntp status

```
Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0017 Hz, precision is 2**10
ntp uptime is 499000 (1/100 of seconds), resolution is 4000
reference time is EE49C7CF.28B439C8 (23:31:27.159 UTC Mon Sep 7 2026)
clock offset is -1.2297 msec, root delay is 47.91 msec
root dispersion is 13.09 msec, peer dispersion is 5.50 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000007039 s/s
system poll interval is 128, last update was 378 sec ago.
```

R2 show ntp associations

```
address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10 68.183.147.240 3    38   128  377  0.066 -1.229  5.509
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured
```

R3 show ntp status

```

Clock is synchronized, stratum 4, reference is 192.168.99.10
nominal freq is 250.0000 Hz, actual freq is 250.0021 Hz, precision is 2**10
ntp uptime is 499000 (1/100 of seconds), resolution is 4000
reference time is EE49C6D8.2AC08388 (23:27:20.167 UTC Mon Sep 7 2026)
clock offset is 0.0665 msec, root delay is 50.63 msec
root dispersion is 14.92 msec, peer dispersion is 4.73 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -0.000008462 s/s
system poll interval is 128, last update was 625 sec ago.

```

R3 show ntp associations

```

address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10  68.183.147.240  3    89   128  377  0.072  0.066  4.738
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured

```

Teardown (suite) Close Nms Session, Close All Connections

14.10 PASS Clock Offset Is Small On Every Router (0.1s, 3 commands)

Setup (suite) Open All Routers

Acceptance criteria

- $\{\text{peer}\}$ differs from $\{\text{None}\}$ (checked 3×)
- $\{\text{offset}\} < \{\text{MAX_OFFSET_MS}\}$ holds (checked 3×)

How it was checked

R1 show ntp associations

```

address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10  68.183.147.240  3    23   128  377  0.075  0.224  4.458
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured

```

R2 show ntp associations

```

address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10  68.183.147.240  3    38   128  377  0.066 -1.229  5.509
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured

```

R3 show ntp associations

```

address      ref clock      st  when  poll reach delay offset disp
*~192.168.99.10  68.183.147.240  3    89   128  377  0.072  0.066  4.738
* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~ configured

```

Teardown (suite) Close Nms Session, Close All Connections

14.11 PASS All Routers Agree On The Time (0.0s, 3 commands)

The practical payoff: three independently synchronised clocks should read the same, which is what makes logs across the fabric correlatable.

Setup (suite) Open All Routers

Acceptance criteria

- $\{\text{s12}\} < \{\text{MAX_SKEW_SECONDS}\}$ holds
- $\{\text{s13}\} < \{\text{MAX_SKEW_SECONDS}\}$ holds

How it was checked

R1 show clock

```

23:37:45.512 UTC Mon Sep 7 2026

```

R2 show clock

```

23:37:45.525 UTC Mon Sep 7 2026

```

R3 show clock

```

23:37:45.535 UTC Mon Sep 7 2026

```

Teardown (suite) Close Nms Session, Close All Connections

14.12 PASS The Clock Is No Longer At The Boot Epoch (0.1s, 6 commands)

An unsynchronised IOS device reports a 1993 or 1900 clock; a synchronised one reports now. This is the crude check that catches a clock that never moved at all.

Setup (suite) Open All Routers

Acceptance criteria

- `${year} >= 2026` holds (checked 3×)
- output does not contain `*` (checked 3×)

How it was checked

R1 show clock

23:37:45.548 UTC Mon Sep 7 2026

R1 show clock

23:37:45.560 UTC Mon Sep 7 2026

R2 show clock

23:37:45.575 UTC Mon Sep 7 2026

R2 show clock

23:37:45.588 UTC Mon Sep 7 2026

R3 show clock

23:37:45.601 UTC Mon Sep 7 2026

R3 show clock

23:37:45.614 UTC Mon Sep 7 2026

Teardown (suite) Close Nms Session, Close All Connections

15 Syslog

15.01 **PASS** The Collector Is A Service On The NMS Serving Every Router On One Port (0.1s, 2 commands)

What the move bought: one rsyslog listener for all three routers instead of one busybox listener per router, and a system service rather than something a suite starts -- so no run can leave a stale listener swallowing another's messages.

Setup (suite) Start Collector And Routers

Acceptance criteria

- `${state}` equals **active**
- output contains `:${SYSLOG_PORT}`
- output contains **rsyslogd**

How it was checked

NMS `systemctl is-active rsyslog`
active

NMS `sudo ss -ltnp | grep ':514 ' || echo NONE`

UNCONN	0	0	0.0.0.0:514	0.0.0.0:*	users:("rsyslogd",pid=2925,fd=6))
UNCONN	0	0	:::514	:::*	users:("rsyslogd",pid=2925,fd=7))

Teardown (suite) Close Collector, Close All Connections

15.02 **PASS** Every Router Is Configured To Log To The Collector (0.3s, 3 commands)

Setup (suite) Start Collector And Routers

Acceptance criteria

- output contains **logging host** `:${SYSLOG_HOST}` (checked 3×)
- output contains **logging source-interface** `:${OOB_INTF}[${r}] vrf ${MGMT_VRF}` (checked 3×)
- output contains **service sequence-numbers** (checked 3×)

How it was checked

R1 `show running-config | include ^logging|^service (timestamps|sequence)`

```
service timestamps debug datetime msec
service timestamps log datetime msec show-timezone
service sequence-numbers
logging source-interface GigabitEthernet4 vrf MGMT
logging host 192.168.99.10 vrf MGMT
```

R2 `show running-config | include ^logging|^service (timestamps|sequence)`

```
service timestamps debug datetime msec
service timestamps log datetime msec show-timezone
service sequence-numbers
logging source-interface GigabitEthernet4 vrf MGMT
logging host 192.168.99.10 vrf MGMT
```

R3 `show running-config | include ^logging|^service (timestamps|sequence)`

```
service timestamps debug datetime msec
service timestamps log datetime msec show-timezone
service sequence-numbers
logging source-interface GigabitEthernet4 vrf MGMT
logging host 192.168.99.10 vrf MGMT
```

Teardown (suite) Close Collector, Close All Connections

15.03 **PASS** Every Router Reports The Collector As An Active Logging Host (0.2s, 3 commands)

The router's own view: it should name the collector and show a non-zero count of messages sent to it.

Setup (suite) Start Collector And Routers

Acceptance criteria

- output contains `:${SYSLOG_HOST}` (checked 3×)
- output contains **level** `:${TRAP_LEVEL}` (checked 3×)

How it was checked

```
R1 show logging | include Trap logging|Logging to 192.168.99.10
  Trap logging: level informational, 1238 message lines logged
    Logging to 192.168.99.10 (MGMT) (udp port 514, audit disabled,
R2 show logging | include Trap logging|Logging to 192.168.99.10
  Trap logging: level informational, 1616 message lines logged
    Logging to 192.168.99.10 (MGMT) (udp port 514, audit disabled,
R3 show logging | include Trap logging|Logging to 192.168.99.10
  Trap logging: level informational, 974 message lines logged
    Logging to 192.168.99.10 (MGMT) (udp port 514, audit disabled,
```

Teardown (suite) Close Collector, Close All Connections

15.04 PASS The Hub Message Reaches The Collector (4.0s, 1 commands)

End to end over the LAN: emit a uniquely marked message and find it at the collector.

Setup (suite) Start Collector And Routers

Acceptance criteria

- $\${n} > 0$ holds

How it was checked

```
NMS sudo grep -c -- 'LABSYSLOG-HUB-193745' /var/log/lab/192.168.99.1.log 2>/dev/null || echo 0
1
```

Teardown (suite) Close Collector, Close All Connections

15.05 PASS Each Spoke Message Reaches The Collector Across The Tunnel (8.1s, 2 commands)

The spokes have no direct path to h1's LAN; their messages are carried by the tunnels and the hub's routing.

Setup (suite) Start Collector And Routers

Acceptance criteria

- $\${n} > 0$ holds (checked 2×)

How it was checked

```
NMS sudo grep -c -- 'LABSYSLOG-R2-193745' /var/log/lab/192.168.99.2.log 2>/dev/null || echo 0
1
NMS sudo grep -c -- 'LABSYSLOG-R3-193745' /var/log/lab/192.168.99.3.log 2>/dev/null || echo 0
1
```

Teardown (suite) Close Collector, Close All Connections

15.06 PASS Received Messages Carry Facility Severity And Mnemonic (4.1s, 2 commands)

Setup (suite) Start Collector And Routers

Acceptance criteria

- $\${n} > 0$ holds
- $\${m}[facility]$ equals FACCHECK
- $\${m}[mnemonic]$ equals MNEMCHECK
- $\${m}[sev]$ equals 5

How it was checked

```
NMS sudo grep -c -- 'LABSYSLOG-FIELDS-193745' /var/log/lab/192.168.99.1.log 2>/dev/null || echo 0
1
NMS sudo cat /var/log/lab/192.168.99.1.log 2>/dev/null || true
<189>207: 000203: *Sep  7 22:17:21.168 UTC: %SSH-5-SSH2_SESSION: SSH2 Session request from 10.0.2.2 (tty =
0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>208: 000204: *Sep  7 22:17:21.214 UTC: %SEC_LOGIN-5-LOGIN_SUCCESS: Login Success [user: lab] [Source:
10.0.2.2] [localport: 22] at 22:17:21 UTC Mon Sep 7 2026
<189>209: 000205: *Sep  7 22:17:21.214 UTC: %SSH-5-SSH2_USERAUTH: User 'lab' authentication for SSH2 Session
from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<190>210: 000206: *Sep  7 22:17:56.590 UTC: %SYS-6-LOGOUT: User lab has exited tty session 434(10.0.2.2)
<189>211: 000207: *Sep  7 22:17:56.591 UTC: %SSH-5-SSH2_CLOSE: SSH2 Session from 10.0.2.2 (tty = 0) for user
'' using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' closed
<189>212: 000208: *Sep  7 22:18:27.361 UTC: %SSH-5-SSH2_SESSION: SSH2 Session request from 10.0.2.2 (tty =
```

```

0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>213: 000209: *Sep 7 22:18:27.410 UTC: %SEC_LOGIN-5-LOGIN_SUCCESS: Login Success [user: lab] [Source:
10.0.2.2] [localport: 22] at 22:18:27 UTC Mon Sep 7 2026
<189>214: 000210: *Sep 7 22:18:27.410 UTC: %SSH-5-SSH2_USERAUTH: User 'lab' authentication for SSH2 Session
from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>215: 000211: *Sep 7 22:18:27.605 UTC: %SYS-5-CONFIG-I: Configured from console by lab on vty0
(10.0.2.2)
<190>216: 000212: *Sep 7 22:18:27.747 UTC: %SYS-6-LOGOUT: User lab has exited tty session 434(10.0.2.2)
<189>217: 000213: *Sep 7 22:18:27.747 UTC: %SSH-5-SSH2_CLOSE: SSH2 Session from 10.0.2.2 (tty = 0) for user
'' using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' closed
<187>218: 000214: *Sep 7 22:19:26.134 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.3 NBMA: 100.64.0.1)
<187>219: 000215: *Sep 7 22:19:26.227 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.2 NBMA: 100.64.0.1)
<187>220: 000216: *Sep 7 22:19:26.906 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.3 NBMA: 100.64.0.1)
... 1020 more lines

```

Teardown (suite) Close Collector, Close All Connections

15.07 PASS Received Messages Carry Sequence Numbers (0.1s, 1 commands)

'service sequence-numbers' is configured, so every message should be numbered -- which is how a collector detects loss.

Setup (suite) Start Collector And Routers

Acceptance criteria

- $\{\text{msgs}\}$ is not empty
- $\{\text{uniq}\} > 1$ holds
- $\min(\{\text{seqs}\}) \geq 0$ holds

How it was checked

NMS `sudo cat /var/log/lab/192.168.99.1.log 2>/dev/null || true`

```

<189>207: 000203: *Sep 7 22:17:21.168 UTC: %SSH-5-SSH2_SESSION: SSH2 Session request from 10.0.2.2 (tty =
0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>208: 000204: *Sep 7 22:17:21.214 UTC: %SEC_LOGIN-5-LOGIN_SUCCESS: Login Success [user: lab] [Source:
10.0.2.2] [localport: 22] at 22:17:21 UTC Mon Sep 7 2026
<189>209: 000205: *Sep 7 22:17:21.214 UTC: %SSH-5-SSH2_USERAUTH: User 'lab' authentication for SSH2 Session
from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<190>210: 000206: *Sep 7 22:17:56.590 UTC: %SYS-6-LOGOUT: User lab has exited tty session 434(10.0.2.2)
<189>211: 000207: *Sep 7 22:17:56.591 UTC: %SSH-5-SSH2_CLOSE: SSH2 Session from 10.0.2.2 (tty = 0) for user
'' using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' closed
<189>212: 000208: *Sep 7 22:18:27.361 UTC: %SSH-5-SSH2_SESSION: SSH2 Session request from 10.0.2.2 (tty =
0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>213: 000209: *Sep 7 22:18:27.410 UTC: %SEC_LOGIN-5-LOGIN_SUCCESS: Login Success [user: lab] [Source:
10.0.2.2] [localport: 22] at 22:18:27 UTC Mon Sep 7 2026
<189>214: 000210: *Sep 7 22:18:27.410 UTC: %SSH-5-SSH2_USERAUTH: User 'lab' authentication for SSH2 Session
from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>215: 000211: *Sep 7 22:18:27.605 UTC: %SYS-5-CONFIG-I: Configured from console by lab on vty0
(10.0.2.2)
<190>216: 000212: *Sep 7 22:18:27.747 UTC: %SYS-6-LOGOUT: User lab has exited tty session 434(10.0.2.2)
<189>217: 000213: *Sep 7 22:18:27.747 UTC: %SSH-5-SSH2_CLOSE: SSH2 Session from 10.0.2.2 (tty = 0) for user
'' using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' closed
<187>218: 000214: *Sep 7 22:19:26.134 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.3 NBMA: 100.64.0.1)
<187>219: 000215: *Sep 7 22:19:26.227 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.2 NBMA: 100.64.0.1)
<187>220: 000216: *Sep 7 22:19:26.906 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.3 NBMA: 100.64.0.1)
... 1020 more lines

```

Teardown (suite) Close Collector, Close All Connections

15.08 PASS Message Timestamps Agree With The Router Clock (4.1s, 3 commands)

Ties syslog to NTP: a message's timestamp should match the sending router's clock. Skewed timestamps make a collector's correlation across devices worthless.

Setup (suite) Start Collector And Routers

Acceptance criteria

- $\${n} > 0$ holds
- $\${skew} < \${MAX_TS_SKEW}$ holds

How it was checked

```
NMS sudo grep -c -- 'LABSYSLOG-TIME-193745' /var/log/lab/192.168.99.1.log 2>/dev/null || echo 0
1
```

R1 show clock

23:38:08.968 UTC Mon Sep 7 2026

```
NMS sudo cat /var/log/lab/192.168.99.1.log 2>/dev/null || true
```

```
<189>207: 000203: *Sep 7 22:17:21.168 UTC: %SSH-5-SSH2_SESSION: SSH2 Session request from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>208: 000204: *Sep 7 22:17:21.214 UTC: %SEC_LOGIN-5-LOGIN_SUCCESS: Login Success [user: lab] [Source: 10.0.2.2] [localport: 22] at 22:17:21 UTC Mon Sep 7 2026
<189>209: 000205: *Sep 7 22:17:21.214 UTC: %SSH-5-SSH2_USERAUTH: User 'lab' authentication for SSH2 Session from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<190>210: 000206: *Sep 7 22:17:56.590 UTC: %SYS-6-LOGOUT: User lab has exited tty session 434(10.0.2.2)
<189>211: 000207: *Sep 7 22:17:56.591 UTC: %SSH-5-SSH2_CLOSE: SSH2 Session from 10.0.2.2 (tty = 0) for user '' using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' closed
<189>212: 000208: *Sep 7 22:18:27.361 UTC: %SSH-5-SSH2_SESSION: SSH2 Session request from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>213: 000209: *Sep 7 22:18:27.410 UTC: %SEC_LOGIN-5-LOGIN_SUCCESS: Login Success [user: lab] [Source: 10.0.2.2] [localport: 22] at 22:18:27 UTC Mon Sep 7 2026
<189>214: 000210: *Sep 7 22:18:27.410 UTC: %SSH-5-SSH2_USERAUTH: User 'lab' authentication for SSH2 Session from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>215: 000211: *Sep 7 22:18:27.605 UTC: %SYS-5-CONFIG_I: Configured from console by lab on vty0 (10.0.2.2)
<190>216: 000212: *Sep 7 22:18:27.747 UTC: %SYS-6-LOGOUT: User lab has exited tty session 434(10.0.2.2)
<189>217: 000213: *Sep 7 22:18:27.747 UTC: %SSH-5-SSH2_CLOSE: SSH2 Session from 10.0.2.2 (tty = 0) for user '' using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' closed
<187>218: 000214: *Sep 7 22:19:26.134 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel: 172.20.0.3 NBMA: 100.64.0.1)
<187>219: 000215: *Sep 7 22:19:26.227 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel: 172.20.0.2 NBMA: 100.64.0.1)
<187>220: 000216: *Sep 7 22:19:26.906 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel: 172.20.0.3 NBMA: 100.64.0.1)
... 1021 more lines
```

Teardown (suite) Close Collector, Close All Connections

15.09 PASS Messages Below The Trap Level Are Not Forwarded (14.0s, 1 commands)

Negative control. Trap level is informational (6), so a debug-severity (7) message must not reach the collector. If this ever passes traffic, the level filter is not working and the positive tests above prove much less than they appear to.

Setup (suite) Start Collector And Routers

Acceptance criteria

- $\${n}$ equals 0
- a debug-severity message reached the collector despite trap level $\${TRAP_LEVEL}$

How it was checked

```
NMS sudo grep -c -- 'LABSYSLOG-DEBUG-193745' /var/log/lab/192.168.99.1.log 2>/dev/null || echo 0
0
0
```

Teardown (suite) Close Collector, Close All Connections

15.10 PASS All Three Routers Are Represented At The Collector (12.1s, 3 commands)

Messages from every router, distinguishable at the collector, which is the point of a central log host.

Setup (suite) Start Collector And Routers

Acceptance criteria

- $\${n} > 0$ holds (checked 3×)

How it was checked

```
NMS sudo grep -c -- 'LABSYSLOG-ALL-R1-193745' /var/log/lab/192.168.99.1.log 2>/dev/null || echo 0
1
NMS sudo grep -c -- 'LABSYSLOG-ALL-R2-193745' /var/log/lab/192.168.99.2.log 2>/dev/null || echo 0
1
NMS sudo grep -c -- 'LABSYSLOG-ALL-R3-193745' /var/log/lab/192.168.99.3.log 2>/dev/null || echo 0
1
```

Teardown (suite) Close Collector, Close All Connections

16 Snmpv3

16.01 PASS Both Trap Receivers Are Services On The NMS (0.1s, 2 commands)

snmptrapd on the standard port and the raw capture on a second one, both system services rather than listeners a suite starts -- so no run can leave one behind, which is how a negative test once passed while nothing was arriving.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- `${state}` equals **active active**
- output contains `:${TRAP_PORT}`
- output contains `:${TRAP_RAW_PORT}`

How it was checked

```
NMS systemctl is-active snmptrapd lab-trapcap | tr '\n' ' '
active active

NMS sudo ss -ltnp | grep -E ':(162|1162) ' || echo NONE
UNCONN 0      0      0.0.0.0:1162    0.0.0.0:*      users:(("python3",pid=3082,fd=3))
UNCONN 0      0      0.0.0.0:162    0.0.0.0:*      users:(("snmptrapd",pid=3043,fd=3),("systemd",pid=1,fd=124))
UNCONN 0      0      [::]:162      [::]:*         users:(("snmptrapd",pid=3043,fd=4),("systemd",pid=1,fd=125))
```

Teardown (suite) Close Trap Collector, Close All Connections

16.02 PASS Every Router Has An SNMPv3 User With Authentication And Privacy (0.1s, 3 commands)

v3 without auth and priv is barely better than v2c, so the protocols in use are asserted, not just the user's existence.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- output contains **User name: `${SNMP_USER}`** (checked 3×)
- output contains **Authentication Protocol: SHA** (checked 3×)
- output contains **Privacy Protocol: AES128** (checked 3×)
- output contains **Group-name: `${SNMP_GROUP}`** (checked 3×)

How it was checked

```
R1 show snmp user
User name: labmon
Engine ID: 800000090300525400C80101
storage-type: nonvolatile      active
Authentication Protocol: SHA
Privacy Protocol: AES128
Group-name: LABGRP

R2 show snmp user
User name: labmon
Engine ID: 800000090300525400C80201
storage-type: nonvolatile      active
Authentication Protocol: SHA
Privacy Protocol: AES128
Group-name: LABGRP

R3 show snmp user
User name: labmon
Engine ID: 800000090300525400C80301
storage-type: nonvolatile      active
Authentication Protocol: SHA
Privacy Protocol: AES128
Group-name: LABGRP
```

Teardown (suite) Close Trap Collector, Close All Connections

16.03 PASS Every Router Has A v3 Group Requiring Privacy (0.1s, 3 commands)

Setup (suite) Start Snmp Collectors

Acceptance criteria

- output contains **groupname: \${SNMP_GROUP}** (checked 3×)
- output contains **security model:v3 priv** (checked 3×)

How it was checked

R1 show snmp group

```
groupname: ILMI                               security model:v1
contextname: <no context specified>           storage-type: permanent
readview : *ilmi                             writeview: *ilmi
notifyview: <no notifyview specified>
row status: active

groupname: ILMI                               security model:v2c
contextname: <no context specified>           storage-type: permanent
readview : *ilmi                             writeview: *ilmi
notifyview: <no notifyview specified>
row status: active

groupname: LABGRP                             security model:v3 priv
contextname: <no context specified>           storage-type: nonvolatile
... 3 more lines
```

R2 show snmp group

```
groupname: ILMI                               security model:v1
contextname: <no context specified>           storage-type: permanent
readview : *ilmi                             writeview: *ilmi
notifyview: <no notifyview specified>
row status: active

groupname: ILMI                               security model:v2c
contextname: <no context specified>           storage-type: permanent
readview : *ilmi                             writeview: *ilmi
notifyview: <no notifyview specified>
row status: active

groupname: LABGRP                             security model:v3 priv
contextname: <no context specified>           storage-type: nonvolatile
... 3 more lines
```

R3 show snmp group

```
groupname: ILMI                               security model:v1
contextname: <no context specified>           storage-type: permanent
readview : *ilmi                             writeview: *ilmi
notifyview: <no notifyview specified>
row status: active

groupname: ILMI                               security model:v2c
contextname: <no context specified>           storage-type: permanent
readview : *ilmi                             writeview: *ilmi
notifyview: <no notifyview specified>
row status: active

groupname: LABGRP                             security model:v3 priv
contextname: <no context specified>           storage-type: nonvolatile
... 3 more lines
```

Teardown (suite) Close Trap Collector, Close All Connections

16.04 PASS No Router Accepts SNMPv1 Or v2c Communities (0.3s, 3 commands)

Security posture: configuring v3 is pointless if a community string still gets you in.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- **\${out}** is empty (checked 3×)

How it was checked

R1 show running-config | include ^snmp-server community
\${output} =

R2 show running-config | include ^snmp-server community
\${output} =

R3 show running-config | include ^snmp-server community
\${output} =

Teardown (suite) Close Trap Collector, Close All Connections

16.05 PASS Every Router Targets The Collector With v3 Privacy (0.1s, 3 commands)

Setup (suite) Start Snmp Collectors

Acceptance criteria

- output contains **\${COLLECTOR}** (checked 3×)
- output contains **security model: v3 priv** (checked 3×)
- output contains **user: \${SNMP_USER}** (checked 3×)

How it was checked

R1 show snmp host

```
Notification host: 192.168.99.10      udp-port: 1162  VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

```
Notification host: 192.168.99.10      udp-port: 162   VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

R2 show snmp host

```
Notification host: 192.168.99.10      udp-port: 1162  VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

```
Notification host: 192.168.99.10      udp-port: 162   VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

R3 show snmp host

```
Notification host: 192.168.99.10      udp-port: 1162  VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

```
Notification host: 192.168.99.10      udp-port: 162   VRFName: MGMT  type: trap
user: labmon      security model: v3 priv
```

Teardown (suite) Close Trap Collector, Close All Connections

16.06 PASS Global Trap Sending Is Enabled (0.1s, 3 commands)

Enabling individual trap types leaves the global switch off: the router builds trap PDUs and never sends them, which looks exactly like a broken collector.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- output contains **SNMP global trap: enabled** (checked 3×)

How it was checked

R1 show snmp | include global trap

```
SNMP global trap: enabled
```

R2 show snmp | include global trap

```
SNMP global trap: enabled
```

R3 show snmp | include global trap

```
SNMP global trap: enabled
```

Teardown (suite) Close Trap Collector, Close All Connections

16.07 PASS Traps From Every Router Reach The Collector (13.0s, 51 commands)

Setup (suite) Start Snmp Collectors

Acceptance criteria

- **\${traps}** is not empty (checked 3×)

How it was checked

R1 configure terminal

```
Enter configuration commands, one per line.  End with CNTL/Z.
```

R1 interface Loopback270

```
${output} =
```

R1 ip address 10.99.97.1 255.255.255.255

```
${output} =
```

R1 snmp trap link-status

```

    ${output} =
R1 end
    ${output} =
R1 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R1 interface Loopback270
    ${output} =
R1 shutdown
    ${output} =
R1 end
    ${output} =
R1 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R1 interface Loopback270
    ${output} =
R1 no shutdown
    ${output} =
R1 end
    ${output} =
R1 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R1 no interface Loopback270
    ${output} =
R1 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 interface Loopback270
    ${output} =
R2 ip address 10.99.97.1 255.255.255.255
    ${output} =
R2 snmp trap link-status
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 interface Loopback270
    ${output} =
R2 shutdown
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 interface Loopback270
    ${output} =
R2 no shutdown
    ${output} =
R2 end
    ${output} =
R2 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R2 no interface Loopback270
    ${output} =
R2 end
    ${output} =
R3 configure terminal
    Enter configuration commands, one per line. End with CNTL/Z.
R3 interface Loopback270
    ${output} =
R3 ip address 10.99.97.1 255.255.255.255
    ${output} =
R3 snmp trap link-status
    ${output} =

```

```
R3 end
${output} =

R3 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.

R3 interface Loopback270
${output} =

R3 shutdown
${output} =

R3 end
${output} =

R3 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.

R3 interface Loopback270
${output} =

R3 no shutdown
${output} =

R3 end
${output} =

R3 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.

R3 no interface Loopback270
${output} =

R3 end
${output} =

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d66d8c3bf10781cd8fcab6521f98448783a6d9bf665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbcc0607f9fe235937749231d4e94bb8fdcc059dcffbbba830d801e015c85863d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcba
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6dda4f4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d3535538a2851e16b3bc0d2979168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aedd6db
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9faf06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e8fac890bae9434f944d06cc273d3d6bb9fd842b28c4aa4b6f7723acfc5a8d378b7f6d6019f1c750dbd
2b44a96e3e05c10c5df1deb3c7c8f3b1022054494304e4456fad68c0f554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acf8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cfff78355da4f4fcfa92bdd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb7781b788f02536a47b9893019f437a968d65cf16414aaecf588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cbc82aeec80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9ea11abc6a118939fad85eb0735991d6b9d8e891ccf0bd9c9b99abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aaef04a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5c3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48944635bbb890fd08e79baae5523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a07f793b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335fef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59bebf6f1
7b912bab7415c3068dc730665587dd829e838b378fbc81aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316cd7d6a27f4300e3b40e92dcf8449782b483b7eb1c0a3da45f5be4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ac5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fdf8a3d87f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c877165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81bab3f02f7acbecb25144995899c1430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aef74784d41426
fcac7b0d1a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f56ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa5493b61193e1193edcca3f3f0abd1c6f25b35985eb169cb05adfaa725d29e505e5
```

```
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5df6e6a36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbd6c6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625Feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
0201020200a204066c61626d6f6e040cd0e347d7a518a7f37c1b0408a7c7be9c6fe405d0482018cd8efa54000ad401bbc326d
2bbcd825ab5152edf654545b7ab79bde2ffadf60703003bf05fd372b55c6598a7edececfd536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25afe53f39a555ecb3dcfd727a08432dc9340b766d913d297b4bb
07970a2510babb3db4f4c0e0bb07f1f91fffd45e6fb29ef8feac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecd96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d6985b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbb0562387f969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca80228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036bea30c4256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836cd483314
b637ad7fc13ded93b704de011795cd6883a9036f15a8f96224a3c162abd83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd5500b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfc1cfcfcf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4abf6a7517db34fbe0d2965d0cedde29f5e9a919fa5f14ad44ce1b2ffcc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea219ad6b4f73721c87b7d23da00a98478bc9f8f206e82d8a3606be7431
... 3229 more lines
```

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

```
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c9330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d66d8c3bf10781cd8fcb6521f98448783a6db9fb665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbcbccc0607f9fe235937749231d4e94bb8fdcc059dcffbb8a30d801e015c85863d7
158e72f510620b1c9e484b7417bd43a185d046ea549f3642f787698207c3f818a4b10c5927a8e880fcb8
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeb771b4c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d3535358a2851e16b3bc0d29719168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c1a06b8620cf2bdfae08224d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aed6db
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9faF06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a338399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8ba6788d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e87fac89b0ae9434f944d06cc273d36bb9bf842b28c44aa4b6f7723acfc5a8d378b7f6d6019f1c750dd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68cf0554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e94031213bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea6b3a3c15acfa8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cfff78355da4f4fcfa92bdd9281133bec7f9ae933da59e755762b26e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9893019f437a968d653c16414aac7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cb8c2aaec80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e8b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9eab11abc6a118939fad85eb0735991d6b9d8e891ccf0bdf9cb99abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aeae0f4a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f2f59507f8016a328a4c7a9ad1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5cf3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48946635bbb890df08e79baaef5523fd4bd8e7aa0f86d71427b43736a5d9d7bf6f4403
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587dd829e838b378fbcd81aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7eb1b1c0a3da45fbae4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ec561d0408a7c7be9c6efe405b0481a3fa3381e2249898d5098d5e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fddfa83d87f9bb9b1854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c8717165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81bab3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aef47484d41426
fcac7bd01a45e729fb041e4e0053bfc6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dadd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc2b4299f7257f7f9aaa3362d185225a4037aefee8a61fb964fcd2e3cf759405bf4911bb9c8e3a30b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaef3f3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5df6e6a36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbd6c6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625Feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
```

```
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcd825ab5152edf654545b7ab79bde2ffadf60703003bf05fd372b55c6598a7edececf536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb873625a9acd114f2efc9c842fde25afe53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebb07f01f9ff4d5e6fb29ef8feac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdcd96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2d3d34b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de884455b5342f2d76797f484d9471253faea500058a89ac76482836cd83314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd550b0799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbeb0d2965d0cedde29f5e6919fa5f14ad44ce1b2fffc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bfd23d6a00a98a878bc9f8f206e82d8a3606be17431
... 329 more lines
```

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

```
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb629484408363079650d246d66d8c3bf10781cd8fcab6521f98448783a6d9bf665ade
b66e773f6cb948e6c84fbc1c22baffabcb9a7c820adbcc0c0607f9f2c35937749231d4e94bb8fddcc05cfbbba830d801e015c858637
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcbba
1788819441.768 192.168.99.2 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173af140f39665d400408bdf4dc46c97074930481a3485df5849e5eeb771b44c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a0fafa80f5d3535538a2851e16b3bc0d2979168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da012a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9daeed6db
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbb312cc01027c101b15d
95d74b6c51ef9f9af06b70481620af82d566719918aab054f980854153c2688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d328663995d404089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba984a4e8fac890bae9434f944d06cc273d3d6bb9f0842b28c44aa4b6f7723acfc5a8d378bf7f6d6019f1c750bd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68cf0f554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acfa8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd39f1feaf8f93f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9bf78cfff7835da44f4cfa92bddd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a74b9893019f437a968d65cf16414aaec7588c7ac3f1617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8bcb2aeec80408ba7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900ddda1de7d41080b83bf95c9c0743949bd5c4af9eaa11abc6a118939fad85eb0735991d6b9d8e891ccf0bdc9cb99abf172
805a89b5e5d778a279e1a0384713bb1028ba0b0be1d56a9527722e5f0d7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aaef04a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f749d38cda2be1bf1bf7d7f4f9d835a5cf3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48944635bbb890fd08e79baaef5523fd4db8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d02014020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d0397f5910408bdf4dc46c97074970481a33116ac4348d5c39ad28f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587dd829e838b378fbc81aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316cf7d66a27f4300e3b40e92dcf8449782b483b7ebb10c0a3da45f5be4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ec5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fdf8a3d87f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c87f7165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81bab3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab089df64d04089b184efb1b39c21e0481a3b1a6978d7875aefa7484d41426
fcac7bd01a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e81fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaef3f3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5df6ea36ba9
061eb6d5f8e4cea2b2f8283e04ff27fe21962da8a88d91b1c4cf5bdc6a5d339e9dd070feed2193e628e3bdc3aaeaa01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cfc589265feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aefc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcd825ab5152edf654545b7ab79bde2ffadf60703003bf05fd372b55c6598a7edececf536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb873625a9acd114f2efc9c842fde25afe53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebb07f01f9ff4d5e6fb29ef8feac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ff
```

```
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdcd96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 308f1f020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836c4d83314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd5500b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfcfb1cfeccf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbe0d2965d0cedde29f5e6919fa5f14ad44ce1b2ffc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bf23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3229 more lines
```

Teardown (suite) Close Trap Collector, Close All Connections

16.08 PASS Received Traps Are SNMP Version 3 (0.2s, 3 commands)

Reads the version field out of the datagram itself rather than trusting the configuration.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- `${traps}` is not empty (checked 3×)
- `${versions}` equals `${[[3]]}` (checked 3×)

How it was checked

NMS `sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true`

```
1788819441.732 192.168.99.1 308f1f020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d6d8c3bf10781cd8fcb6521f98448783a6db9bf665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbcbccc0607f9fe235937749231d4e94bb8fddcc059dcfffbba830d801e015c85863d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcbba
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d353538a2851e16b3bc0d29179168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aed6db
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9faf06c0670481620af82d566719918aab054f90805415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e8fac890bae9434f944d06cc273d36bb9f842b28c44aa4b6f7723acfc5a8d378b7f6d6019f1c750dbd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68cf0554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c5e940321235bbb7431f7f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acfa8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cff78355da4f4fcfa92bdd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb718b1788f02536a47b9893019f437a968d65cf16414aaec7acf31617d6f2d26c240f
1788819442.056 192.168.99.2 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cb8c2aaec80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9ea11abc6a118939fad85eb0735991d6b9d8e891ccf0b9d9cb99abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aaeaf04a
dcaabcf43bd1c13a51d4087e88c6a9a9c9bf270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5c3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe4844635bb890df08e79baaef5523fd4bd8e7aa0f86d71427b43736a5d9d7bfe4403
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587d0829e838b378fbc81aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7eb1c0a3da45fbae4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a190349c5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fddfa83d87f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c877165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81bab3f027acbecb251449958991c430e24f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aef47484d41426
fcac7bd01a45e729fb041e4e0053bcf6e1eb7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
```

f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aefe861fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaec3f3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6fc3fcb1f5df6ea36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbdc6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625feded62ba54a93598fd3604d189683a16364138220d45f3a5
2b61fddeb71554fcc5d3fa447dc868123ae12ab5d517c513e3981ae8abdd5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcd8e25ab5152edf654545b7ab79bde2ffadf60703003bf05fd372b55c6598a7edecfecfd536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25afe53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebb07f01f9fffd45e6fb29ef8feac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20cedcd6990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836c4d83314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd5500b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfb1cfe88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbe0d2965d0cedde29f5e6919fa5f14ad44ce1b2fffc828265b33e2d45f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eeaa2197adb6a4e73721c87bfd23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3230 more lines

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d66d8c3bf10781cd8fca6b521f98448783a6db9fb665ade
b66ef77f36bc948e6c84fbc1c22baffabc9a7c820adbcbcc0607f9f9e235937749231d4e94bb8fdcc059dcffbb838d081e3a15e58563d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcbab
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb140f39665400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a0fa8a0f5d3535538a2851e16b3bc0d2979168bf06354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da01022a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aeddd6b
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9faf06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3dbb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d328663995d404089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e8fac890bae9434f944d06cc273d36dbb9f7842b28c44aa4b6f7723acfc5a8d378b7f6d6019f1c759dbd
2b44a96e3e05c10c5df1d6b37c8cf120205449430e4456fad68c0f554db6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f408bdf4dc46c97074950481a3d122cd69208ae6a3a33c15acfa8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cff78355da4f4fcfa92bddd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9890319f437a968d65cf16414aaec7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040cc97f59d812586c8cbc82aeecc80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda7de7d41080b83bf95c9c0743949bd5b4ca9f2a11abc6a118939fad85eb0735991d6b9d8e891ccfb0bd9cb99abf172
805a8c9b5e5d778a27f4300e3b40e92dcf8449782b483b7eb1b1c9a3048a45fbc424622a7d600f36d7023
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cc9e7d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee5a2a2e7caf58003f3aeaf04a
dcaabcf43bd1c13a51d4087e88c6a9a9c9fb270aec98cf2cbdfc6f6d803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328aa47a9d1b80aa4219982fe2f74978cda2b6ef1bf7d7faf9d835a5cf3f9042d5c74a4e898d39833cc1db0e52
02b505f5d02dbbe48944635bb8b90fd08e79baae75523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d02014020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587dd829e838b378fbc8d1aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316cf7d66a27f4300e3b40e92dcf8449782b483b7eb1b1c9a3048a45fbc424622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ec5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fd8a3b7f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a5629139b44704b325f28a9b0c3c74d18b4c3bd08fc9130c877165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bd48165bf
d95c8ff1fe7981815276c5c81bab3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f6d5404089b184efb1b39c21e0481a3b1a6978d7875ae7f484d41426
fcac7bd01a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aefe861fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaec3f3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6fc3fcb1f5df6ea36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbdc6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e

69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
0201020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcde825ab5152edf65454b7ab79bde2ffad6f0703003bf05fd372b55c6598a7edececf536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25afe53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebbb07f01f9fdd45e6fb29ef87feac58621e67b692935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecd96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836c4d83314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27c5500b799d76f31678bbff135288e19a3de00a02ab2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfb1cfecf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbe0d2965d0cedde29b919fa5f14ad44ce1b2ffcc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bfd23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3230 more lines

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d24d66d6d8c3bf10781cd8fcab6521f98448783a6d9bf665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbcbccc0607f9fe235937749231d4e94bb8fdcc059dcffbb8a30d801e015c85863d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e800fcbab
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb1407396654d00408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8089ef
ae317dcaed8d6702a20fa8a0f5d3535583a2851e16b3bcd02979168bf60354d2878e5cd7ac03c1daa98f242eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aedd6db
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcb312cc01027c101b15d
95d74b6c51ef9faf06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266ba89add3db3176843bbfc92d3b4f09d4b901ba83ff7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7fa161bb4df34a5d637d8bac78d89f95b126d7f786e1521239899f10d3d27949f04880309da8e456a7f
4b512b0558a7215ca4ba984d8fac89b0bae9434f944d06cc2783d36bb9fd842b28c44aa4b6f7723acfc5a8d378b7f6d6019a1c756dbd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68cf0554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acf8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8c5f78355da4f4fcfa92bdd9281133bce7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9893019f437a968d65cf16414aac7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cb8c2aaec80408a7c7be9c6efe40590481a3944f05c35a695e08ab698a77fc0
679d4817a25d2867b284b355b9560d1abe0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1f
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9e611abc6a118939fad85eb0735991d6b9d8e891ccf0bd9cb99abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaaef04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aaef04a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9dd1b80a4219982fe27f4978cda2b2ef1bf7d7faf98d35a5cf3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48944635bbe48b890fd08e79baae5523df4b08de7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ad428f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef72ad9631cd12834db86976c08bc0949678ce7926afec969d51ff59b6ef8d1
7b912bab7415c3068dc730665587dd829e838b378fbc81aeea7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7eb1c0a3da45f5be4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ec5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fd8a3d87f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c87f7165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d7b6fad8165bf
d95c8ff1fe7981815276c5c811bab3f027acbecb251449958991c430e2aef57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c37a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aeaf7484d41426
fcac7bd01aa5e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d0a8bb1e683b91e18d5d070c8eeb40fd5392669c3139475a2e
f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39fb9b
caf86df01c6728b43aa549379361193e7dccaec3f3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6fc3fb1f5df6ea36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbdcd6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcde825ab5152edf65454b7ab79bde2ffad6f0703003bf05fd372b55c6598a7edececf536ad432095fb9260748bd46f1cc973fce

```
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25afe53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebb07f01f9fffd45e6fb29ef8feac58621e67b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdcd96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329be9c7e11633aa36dc290f9784b5cc2f25a844f00d69d85b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836c4d83314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd5500b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfb1cfecf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbed2965d0cedde29f5e6919fa5f14ad44ce1b2ffcc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bfd23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3230 more lines
```

Teardown (suite) Close Trap Collector, Close All Connections

16.09 PASS Received Traps Carry The Configured User And Privacy Flags (0.2s, 3 commands)

Setup (suite) Start Snmp Collectors

Acceptance criteria

- `${users}` equals `${['${SNMP_USER}']}` (checked 3×)
- `${all_priv}` holds (checked 3×)

How it was checked

NMS `sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true`

```
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d6d8c3bf10781cd8fcab6521f98448783a6d9bf665ade
b66e773f6cb948e6c84fbc1c22baffab9a7c820adbcbccc0607f9fe235937749231d4e94bb8fddcc059dcffbbba830d801e015c85863d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcbba
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6dda4f4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20f6a00f5d3535538a2851e16b3bc0d2979168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc82dabf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aedd6db
b3ee8cb9bfc314d080a0fa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9f9af06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d1a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e8fac890bae9434f944d06c7f3d3d6bb9fd842b28c44aa4b6f7723acfc5a8d378b7fd6d019f1c750dbd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68c0f554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acfa8
7a5102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79fe
ea5d0c4c1aab31cc9b7f8cfff78355da4f4fcfa92bdd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9893019f437a968d65cf16414aaec7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.2 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cbc82aeecc80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9e6a11abc6a118939fad85eb0735991d6b9d8e891ccf0bd9cb99abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaf04089b184efb1b39c21c0481a3ee52a2e7ca7f58003f3aaef04a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5cf3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48944635bbb890fd08e79baae5523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bffa42f9f6dadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6bf1d
7b912bab7415c3068dc730665587f8d8a28e838b378fbc273d11abc6a118939fad85eb0735991d6b9d8e891ccf0bd9cb99abf172
8921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7ebbb1c0a3da45fbc4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ec5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fd8a387f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c877165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81bab3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aefa7484d41426
```

```
fcac7bd01a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaef3f30abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5dfe6a36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbd6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc3a6e500c2a923e4766fa1263512636869017b82c6c5982625feded62ba54a93598fd3604d189683a1634613822d045f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040c0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcde825ab5152edf654545b7ab79bde2ffad6f0703003bf05fd372b55c6598a7edececfd536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25afe53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510badd3db4f4ce0ebb07fd1f9ffdd45e6fb29ef8feac58621e67b62935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdd696990e12ab506b0cb8e915f9e5b37d553f38e991971986ec070324af943
30b1625bd961d67078f27e4290be8c1b30bf9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2c9b3b21d583ae4f38bbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c1f375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836c4d83314
b637ad7f7c13ded93b704de011795cd6883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd5500b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfb1cfecf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbe0d2965d0cedde29f5e6919fa5cf1ad44ce1b2ffc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bdf23d6a00a93a8789cf8f2c06e82d8a3606be17431
... 3231 more lines
```

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

```
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd140020704089b184efb1b39c2180481a3010cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d66d8c3bf10781cd8fca6521f98448783ad69bf665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbcbccc0607f9fe235937749231d4e94bb8f8fcc059dcffbbba830d801e015c85863d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcbca
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6dda4f7b7ba8b009f4cb725b19f5e751850a70e9cd62e9471572848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d3353538a2851e16b3bc0d29719168bf603534d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aed6db
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbbc312cc01027c101b15d
95d74b6c51ef9f9af06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e8fac890bae9434f944d06ce273d36dbb9f0842b28c44aa4b6f7723acfc5a8d378bf76d6019fc1750dbd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68c0f554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e94032135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acfa8
7a45102a3213ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cfff78355da4f4cfca92bdd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9893019f437a968d65cf16414aaec7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cbc82aeec80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399df882e9fa2c2b2a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd54f9ea11abc6a118939fad85eb0735991db9d8e891ccf0bd9cb99abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aeae04a
dcaabcF43bd1c13a51d4087e88c6a9a9cfb270aeca98cf2cbdfc6f8d03608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5c3f39042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48944635bbb890fd08e79baae5523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef7ade9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587d82e838b378fbcd81a2aa7be721b39cc8c406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7eb1c0a3da45f5be4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ce5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357ed6d9cd388db0a086c165a4fdf8a3d87f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c877165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81bab3f027acbecb251449958991c430e2e4f7b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aefa7484d41426
fcac7bd01a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaef3f30abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5dfe6a36ba9
```

```
NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true
```

C8000V IPsec Testbed - test evidence

```
2bbcd825ab5152edf65454b7ab79bde2ffad60703003bf05fd372b55c6598a7edececf536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acc114f2efc9c842fde25af53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebb07f01f9ffd45e6fb29ef8f9eac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdede9990e1d2ab506b0cb8e915f9e5b37d553f38e991971986ec070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836c4d83314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd550b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfc1cfcfc88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbe0d2965d0cedde29f5e6919fa5f14ad44ce1b2ffc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bf23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3231 more lines
```

Teardown (suite) Close Trap Collector, Close All Connections

16.10 PASS Trap Payloads Are Encrypted (0.2s, 3 commands)

With privacy in force the scoped PDU arrives as an opaque OCTET STRING. If it were a readable SEQUENCE the varbinds would be on the wire in clear.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- `#{encrypted}` holds (checked 3×)

How it was checked

NMS `sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true`

```
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd140e2704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d66d8c3bf10781cd8fcab6521f98448783a6bd9bf665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbbccc0607f9fe235937749231d4e94bb8fddcc059dcffbb8a30d801e015c85863d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcbca
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d3535538a2851e16b3bc0d297168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfcc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aedd6db
b3ee8cb9bfc314d080afa0b0f48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dc3c312cc01027c101b15d
95d74b6c51ef9faf06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e8fac890bae9434f944d06cc273d3d6bb9f842b28c44aa4b6f7723acfc5a8d378b7f6d6019f1c750dbd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68cf0554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a3c15acfa8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea50dc4c1aab31cc9b7f8cfff78355da4f4fcfa92bddd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9893019f437a968d65cf1641aaec7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cb8c2aaec80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9ea11abc6a118939fad85eb0735991d6b9d8e891ccf0bd9cb99abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaaef04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aaef04a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5cfc3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48944635bbb890fd08e79baae5523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587d829e838b378fbcd81aea77b6721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7ebbc1c0a3da45f5be4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034e2610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fd8a3d87f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c877165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c581bab3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
```

1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aeaf7484d41426
fcac7bd01a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaef3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cf3cb1f5df6e6a36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbdc6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc868123ae12ab5d5157c513e3981ae8abd5e8564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcd825ab5152edf65455b7ab79bde2ffad6f0703003bf05fd372b55c6598a7edecfcfd536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fd25a5fe53f39a555ecb3dcfd7d27a08432cd9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebb07f01f9f9fd45e6fb29ef8feac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdcd969900d12ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290b8e1cb30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836cd483314
b637ad7fc13ded93b704de011795cd6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd550b0799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd3df77a9a6185cfb1cfcf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945d43386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbeb0d2965d0cedde29f5e6919fa5f14ad44ce1b2fffc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bfdb23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3231 more lines

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d66d8c3bf10781cd8fcab6521f98448783a6d9bf665ade
b66e773f6cb948e6c84fbc1c22baffabca9a7c820adbcc0607f9fe235937749231d4e94bb8fcdcc059dcffbbba30d801e015c858637
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcba
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040cd280cb8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeb771b44c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fafa0f5d353558a2851e16b3bc0d2979168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da01062640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9daeed6db
b3ee8cb9bfc314d080aafa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dc3c312cc01027c101b15d
95d7f4b6c51ef9faf06c0670841620af82d566719918aab054f980d541c32b68a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e8fca890bae9434f944d06cc273d3d6bb9f842b28c44aa4b6f7723acfc5a8d378bf7f6d6019f1c750bd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68cf0554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ae63a33c15acfa8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf874e439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cfff78355da44f4cfa92bddd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9893019f437a968d65cf16414aaec7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8bcb82e0408a7c7be9c6efe40590481a3944f05c35a695eb698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900ddda1de7d41080b83bf95c9c0743949db5c4af9ea11abc0a118939fad85eb0735991d6b9d8e891ccf0bdc9b99abf172
805a89b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722e67de7e6baabfe3aae5f497444f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aaef04a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5cf3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48944635bbb890fd08e79baaef5523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6fa0f7f93b069d08bdf4dc46c97074970481a33116ac4348d5c39ad428f96d78
e74d155c5cc9bfba42fe9fdadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587dd829e838b378fbc81aeea7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316cd766a27f4300e3b40e92dcf8449782b483b7eb1c0a3da45f7be4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ec5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fd83a38d7f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9139b77165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d736bfad8165bf
d95c8ff1fe7981815276c5c81bab3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aeaf7484d41426
fcac7bd01a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaef3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5

```
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5df6e6a36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbd6c6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625Feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
0201020200a204066c61626d6f6e040cd0e347d7a518a7f37c1b0408a7c7be9c6fe405d0482018cd8efa54000ad401bbc326d
2bbcd825ab5152edf654545b7ab79bde2ffadf60703003bf05fd372b55c6598a7edececfd536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25afe53f39a555ecb3dcfd7d27a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4c0e0eb07f1f91fffd45e6fb29ef8feac58621e67b6b9235f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdcd96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d6985b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbb0562387f969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca80228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559030e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836cd483314
b637ad7fc13ded93b704de011795cd6883a9036f15a8f96224a3162abd83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd5500b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfc1cfcfcf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4abf6a7517db34fbe0d2965d0cedde29f5e9a919fa5f14ad44ce1b2ffc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea219ad6b4f73721c87b7d23da00a98478bc9f8f206e82d8a3606be7431
... 3232 more lines
```

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

```
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c9330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d66d8c3bf10781cd8fca6521f98448783a6db9fb665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbcbccc0607f9fe235937749231d4e94bb8fdcc059dcffbb8a30d801e015c85863d7
158e72f510620b1c9e484b7417bd43a185d046ea549f3642f787698207c3f818a4b10c5927a8e880fcb8
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeb771b4c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d3535358a2851e16b3bc0d29719168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c1a06b8620cf2bdfae08224d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aed6db
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9faF06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266ba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a338399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8ba6788d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844e8facc890bae9434f944d06cc273d36bb9bf842b28c44aa4b6f7723acfc5a8d378b7f6d6019f1c750dbd
2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68cf0554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e94031213bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea6b3a3c15acfa8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cfff78355da4f4fcfa92bdd9281133bec7f8ae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9893019f437a968d653c16414aaec7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cb8c2aaec80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e8b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9ea11abc6a118939fad85eb0735991d6b9d8e891ccf0bdf9cab99abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aeae0f4a
dcaabcf43bd1c13a51d4087e88c6a9a9c9bf270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5cf3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe4846635bbb890df08e79baaef5523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a0f7f93b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587dd829e838b378fbcd81aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7eb1b1c0a3da45f5be4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ec561d0408a7c7be9c6efe405b0481a3fa3381e2249898d509d8e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fdd8a3d87f9bb9b1854ba187a1984c45dbbf58adca5541a5485c344
583a562913db9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c8717165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81bab3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aeaf7484d41426
fcac7bd01a45e729fb041e4e0053bfc6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc2d24b299f7257f7f9aaa3362d185225a4037aefee8a1fb964fcd2e3cf759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaef3f3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5df6e6a36ba9
061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbd6c6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625Feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
```

```
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcd825ab5152edf654545b7ab79bde2ffad6f60703003bf05fd372b55c6598a7edececf536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25af5e53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebb07f01f9fffd45e6fb29ef8feac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdcd96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836cd483314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd550b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df7f9a6185cfb1cfecf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbeb0d2965d0cedde29f5e6919fa5f14ad44ce1b2fffc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bfd23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3232 more lines
```

Teardown (suite) Close Trap Collector, Close All Connections

16.11 PASS snmptrapd Decrypts Traps From Every Router (0.2s, 3 commands)

The strongest single statement this suite makes: a real SNMP manager, holding only the configured user and each router's engine ID, authenticated and decrypted the traps. That cannot happen unless the keys, the engine IDs and the privacy protocol all match on both sides.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- **{entries}** is not empty (checked 3×)
- **{oids}** is not empty (checked 3×)

How it was checked

NMS `sudo cat /var/log/lab/snmptrapd.log 2>/dev/null || true`

```
NET-SNMP version 5.9.4.pre2
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.21 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.95 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:34.92 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.35 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:36.09 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.06 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
... 6479 more lines
```

NMS `sudo cat /var/log/lab/snmptrapd.log 2>/dev/null || true`

```
NET-SNMP version 5.9.4.pre2
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.21 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.95 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:34.92 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
```

```

iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.35          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:36.09          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.06          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
... 6479 more lines

```

NMS `sudo cat /var/log/lab/snmptrapd.log 2>/dev/null || true`

```

NET-SNMP version 5.9.4.pre2
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.21          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.95          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:34.92          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.26 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.26 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.26 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.26 "lab"
2026-09-07 22:17:21 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.35          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:36.09          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:0:03:35.06          iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.27 1      iso.3.6.1.4.1.9.9.43.1.1.6.1.4.27 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.27 2      iso.3.6.1.4.1.9.9.43.1.1.6.1.8.27 "lab"
2026-09-07 22:17:22 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
... 6481 more lines

```

Teardown (suite) Close Trap Collector, Close All Connections

16.12 PASS One Raw Listener Receives Every Router (0.1s, 1 commands)

The property the per-router-port workaround existed to dodge: a single socket now serves all three senders.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- output contains `#{R1_OOB_IP}`
- output contains `#{R2_OOB_IP}`
- output contains `#{R3_OOB_IP}`

How it was checked

NMS `sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true`

```

1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d66d8c3bf10781cd8fcab6521f98448783a6d9bf665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbcbccc0607f9fe235937749231d4e94bb8fdcc059dcffbb8a380d801e015c85863d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcba
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d3535538a2851e16b3bc0d2979168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aed6db
b3ee8cb9bfc314d080a4fab0b0f48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9faf06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266ba89add3ddb3176843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a

```

fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a784b512b0558a7215ca4ba9844e8fac890bae9434f944d06cc273d3d6bb9f842b28c44aa4b6f7723acfc5a8d378b7f6d6019f1c750dbd2b44a96e3e05c10c5df1deb3e7c8f3b1022054494304e4456fad68cf0554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c80201020102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acfa87a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79efea50d0c4c1aab31cc9b7f8cfff78355da4f4cfa92bddd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152dcbea7abdb77818b788f02536a47b9893019f437a968d65cf16414aaec7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c80301020102020200a204066c61626d6f6e040c97f59d812586c8bcb82aeecc80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9ea11abc6a118939fad85eb0735991d6b9d8e891ccf0bd9cb99abf172805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c80101020102020200a204066c61626d6f6e040cc9e7d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aeae04adcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6fd803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7f7fad9d835a5cf3f9042d5c74a4e898d39833cc1dbe05202b505f5d02dbbe48944635bbb890fd08e79baaeaf5523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d02014020205dc04010302010304373035040c800000090300525400c80201020102020200a204066c61626d6f6e040cd6f8a0f7f93b0690d06759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78e74d155c5cc9bffa42fe9fdadacbc9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd17b912bab7415c3068dc730665587dd829e838b378fbc8d1aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f18921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7ebbc1c0a3da45fbc424622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c80301020102020200a204066c61626d6f6e040c3bb1f3582527a19034ec5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4dfd8a3d87f9bb961854ba187a1984c45dbbf58adca5541a5485c344583a562913d9b44704b325f128a9b0c3c74d18b4c3bd08fc9130c877165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bfd95c8ff1fe7981815276c581bab3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c80101020102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aeaf7484d41426fcac7bd01a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2ef9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9bcaf86df01c6728b43aa549379361193e7dccaef3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d020144020205dc04010302010304373035040c800000090300525400c80201020102020200a204066c61626d6f6e040c22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5dfe6a36ba9061eb6d5f8e4cea2b22f8283e04ff27fe21962da8a88d91b1c4fbdca65d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625feded62ba54a93598fd3604d189683a1634613822d0d45f3a52b61fdeb71554fcc5d3fa447cd8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301020102020200a204066c61626d6f6e040cd0c9e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d2bbcd825ab5152edf654545b7ab79bde2ffad6f0703003bf05fd372b55c6598a7edecfcfd536ad432095fb9260748bd46f1cc973fce7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25afae53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb07970a2510babd3db4f4ce0ebb07f01f9ff4d5e6fb29ef8feac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ffe5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecded96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af94330b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b934af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b8798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39ea45e822985914ea2cb93b21d583ae4f38bbbb56238f969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319baaef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c80101020102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b55903b6e6e04256f62203359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836cd483314b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8d6719b4b8a6db27cd5500b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c80201020102020200a204066c61626d6f6e040c3df77a9a6185cfc1cfcfc88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbe0d2965d0cedde29f5e6919fa5f14ad44ce1b2ffc828265b33e24d5f8c4f415511af6b9294f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bfd23d6a00a98a878bc9f8f2c6e82d8a3606be17431
... 3233 more lines

Teardown (suite) Close Trap Collector, Close All Connections

16.13 PASS Each Router Identifies Itself By Its Own Engine ID (0.3s, 6 commands)

The engine ID in the received trap must match the one the router reports, and must differ between routers -- that is what lets a collector attribute a trap to a device.

Setup (suite) Start Snmp Collectors

Acceptance criteria

- **#{local}** is not empty (checked 3x)
 - **#{ids}** has exactly 1 entries (checked 3x)
 - **#{ids}[0]** equals **#{expected}** (checked 3x)
 - **#{distinct}** equals 3
- the three routers did not present three distinct engine IDs: **#{seen}**

How it was checked

Local SNMP engineID: 8000000090300525400C80101

```
NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true
```

```
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
```

```
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
```

```
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
```

```
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
```

```
1788819442.056 192.168.99.3 3081f1020103300d02013c020205dc04010302010304373035040c8000000090300525400c8030102
```

```
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
```

```
1788819442.267 192.168.99.2 3081f1020103300d020142020205dc04010302010304373035040c8000000090300525400c8020102
```

1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102

1788819442 482 192 168 99 1 3081f1020103300d02013c020205dc04010302010304373035040c8000000090300525400c8010102

1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c8000000090300525400c8010102
01030202000c204066c61626d6f6c040c73c76bc40c5f52acbd08f64d04080b184cfeb1b20c21c0481c2b1c6078d7875ccfc7484d41426

69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fccc5d2f2447dc8681224e12ab5d5157c513e20812e82bd5c8e564fc102accfc7bd4560acf

2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981ae8abd5e8e564fe10aecfc7bd4560ef
1700010110_550_100_100_00_0_000001db000100000d000110000005d=01010000010001070005010-00000000000505100-0000

[illegible]

ea45e822985914ea2cb93b21d583ae4f38bbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba

0102020200a204066c61626d6f6e040c3df77a9a6185cfb1cfecf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e

```
R2 show snmp engineID | include Local
```

Local SNMP engineID: 8000000090300525400C80201

C8000V IPsec Testbed - test evidence

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

```
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836037965026c2d246d66d8c3bf10781cd8fcbab6521f98448783a6d9bf665ade
b66e773f6cb948e6c84fbc1c22baffabc9a7c820adbcbccc0607f9fe235937749231d4e94bb8fdcc059dcffbbba830d801e015c85863d7
158e72f510620b1c9e484b7417b4da185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcbab
1788819441.768 192.168.99.2 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6ddaf4b7ba8b009f4cb725b19f5e751850a70e9cd62e9471b527848f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d3535538a2851e16b3bc0d2979168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bc8d2abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aeddddb
b3ee8cb9bfc314d080a9fcb0b48addca5f604a787508df6374629f81b9fc95e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9faf06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3dbd31f76843bbfc92d3de40fb901ba83f7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 3081f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8baf88d7959b126d7f786e1521239899f10d3d27949f04880309d9a8e456a78
4b521b0558a7215ca4ba9844e8fac890bae9434f944d06cc273d3d6bb9fd842b28c4aa4b6f7723acfc5a8d378b7f6d6019f1c750dbd
2b44a96c8e05c10c5df1deb3e7c8f3b1022054494304e4456fad68c0f554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 3081f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acf8a
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf87439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cfff78355da4f4fcfa92bd9d9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b893019f437a968d65cf16414aaec7588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8c8c2aaec80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399db882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e879e00d9dda1de7d41080b83bf95c9c0743949bd5c4f9ea11abc6a118939fad85eb0735991d6b9d8e891ccf0bd9c9b9abf172
805a8c9b5e5d778a279e1a0384713bb102e8ba0b0be1d56a952f722e030de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 3081f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8eab0caaaef04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aaef04a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdf68f0c6083608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5c3f3f9042d5c74a4e898d39833cc1dbe052
02b505f5d02dbbe48944635bb9890fd08e79baae5f523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a07f793b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bfafa2f9f7adadacbc9f298c97a79d1335fef72ad9631dc12834db86976c08bc0949678ce7926afec969d51ff59beb6fd1
7b912bab7415c3068dc730665587dd829e838b378fbc81aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a316c7d6a8d7f4300e3b40e92dcf8449782b483bf7eb1b0c6435f5be4c24622a7d600f36d7023
1788819442.306 192.168.99.3 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c6b3f3582527a19034ac5d610408a7c7be9c6efe405b0481a3fa3381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357ed6d93cd388db0d86c165a4f7d8a3087f9bb961854ba187a1984c45dbbf58adca5541a9bc99930a11e
583a562913d9b44704b325f28a9b0c3c74d18b4c3bd08fc9130c877165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81ba3f027acbecb251449958991c430e2e4f57b98530410546f515e98124
1788819442.482 192.168.99.1 3081f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aefa7484d41426
fcac7b0d1a45e729fb041e4e0053bcf6e1e7b4453849a0950cb51754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2f5f556ab286affc47b6299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549c793b1193ef7dcca3f3f0abd1c6f25b5308b169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 3081f1020103300d02014a020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5df6e6a36ba9
061eb6d5f8e4cea2b22f8283a045cd72fe21962da8a8d91b1c4fbd6ca5d339e9dd070feed2193e628e3bdc3aaeaa01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625feded62ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554f4cc5d3fa447dc8681234e12ab5d5157c513e3981ae8ab4d5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020139020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcde825ab5152edf654545b7ab79bde2ffad6f0703003bf05fd372b55c6598a7edececfd536ad432095f9b260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25a7fe53f39a555ecb3dcf7d72a08432dc9340b766d913d297b4bb
07970a2510babd3db4f4ce0ebb07f01f9ffdd45e6fb29ef8f8eac58621e67b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95bdec7dd7039dd603bf20ecdcd96990e1d2ab506b0cb8e915f9e5b37d553f38e99197198e6c070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f0eaf8b439f8b798ee860408950a0e0a5c9d4a79f2784d07c6aca87f839a
ea45e822985914ea2cb93b21d583ae4f38bbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 3081f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d9b251f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836c4d83314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6bd27cd5500b799d76f31678bbff35288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 3081bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfb1cfef88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4deb7fa517d3b4fbed02965d0cedde29f56919fa5f14ad44ce1b2ffc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197ad6b4e73721c87bfd23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3233 more lines
```

R3 show snmp engineID | include Local

Local SNMP engineID: 800000090300525400C80301

NMS sudo cat /var/log/lab/traps-raw.log 2>/dev/null || true

```
1788819441.732 192.168.99.1 3081f1020103300d020136020205dc04010302010304373035040c800000090300525400c8010102
```

0102020200a204066c61626d6f6e040c0330a96d73b02577bd14002704089b184efb1b39c2180481a31e0cb257972ac1650a9c016737
d7c3450c8b69b1810963c1c351af94e662bb62948440836307965026c2d246d6d8c3bf10781cd8fcab6521f98448783a6d9bf665ade
b66ef773f6cb948e6c84fbc1c22baffabc9a7c820adbbccc0607f9fe235937749231d4e94bb8fdcc059dcffbbba830d801e015c85863d7
158e72f510620b1c9e484b7417b4d3a185d046ea549f3642f878698207c3f818a4b10c5927a8e880fcb
1788819441.768 192.168.99.2 308f1f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8020102
0102020200a104066c61626d6f6e040c280bc8173afb140f39665d400408bdf4dc46c97074930481a3485df5849e5eeeb771b44c093a
ef6ddaf4fb7ba8b009f4cb725b19f5e751850a70e9cd62e9471b57284f3350df4234902e59c6ba9cd696e552e207ef62af971e8908ef
ae317dcaed8d6702a20fa8a0f5d3535538a2851e16b3bc0d2979168bf60354d2878e5cd7ac03c1daa98fd24eb8a451e70e624bdfc96
8ee7b7c9e197db97da0102a62640bcd82abf526e9a3bd5db09b0713ae471d14774a711e1c49770a339c6
1788819441.806 192.168.99.3 308f1f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8030102
0102020200a104066c61626d6f6e040c1a06b8620cf2bdfae082242d0408a7c7be9c6efe40570481a3f13563f7a9d2b23f9d6aeddb
b3ee8cb9bfc314d080afa0b0fb48addca5f604a787508df6374629f81bf9c5e8ed322c4fbc9fd5daf2e665dcbc312cc01027c101b15d
95d74b6c51ef9faf06c0670481620af82d566719918aab054f908d5415c32688a26757db8041390a1fd440c938835bf8a171ee3321ef
59f0d1a550a2e55083266bba89add3dbb3176843bbfc92d3de40fb901ba83bf7d8c7124f27c7fe6db1dce
1788819441.982 192.168.99.1 308f1f1020103300d020138020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c54e0b089dfb6d3286639954d04089b184efb1b39c21a0481a38399f66019ba392443b719d26a
fd64cb17b4f7e47e6efc18540d7a161bb4df34a5d637d8ba87959b1b5748f786e152123899f10d3d27949f04880309d9a8e456a78
4b512b0558a7215ca4ba9844efac890bae9434f944d06cc273d3d6bb9fd842b28c44aa4b6f7723acfc5a8d378b7f6d6019f1c750dbd
2b44a96e3e05c10c5df1deb3e7c8fb1022054494304e4456fad68c0f554b6016aa90535c790e85d921b
1788819442.019 192.168.99.2 308f1f1020103300d020140020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cc5e940312135bbb74315f07f0408bdf4dc46c97074950481a3d122cd69208ea63a33c15acfa8
7a45102a3d13ff4011a6fe0077d1190d97e78309f972e8bd391feaf8f439f142fa831bc51566d9eb8017d4cb97e7436f0ff3c8ef79ef
ea5d0c4c1aab31cc9b7f8cfff78355da4f4fcfa92bddd9281133bec7fae933da59e755762b226e899cb3c6998c3fb887f3397554d5152
dcbea7abdb77818b788f02536a47b9893019f437a968d65cf16414aaecf588c7acf31617d6f2d26c240f
1788819442.056 192.168.99.3 308f1f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c97f59d812586c8cb82aeec80408a7c7be9c6efe40590481a3944f05c35a695e8ab698a77fc0
679d4817a25d2867b284b3553e5b9560d1abeb0194ef14399d882e9fa2c2b7a2e5a3a8776478141012d370690d28f11c26bfc8aa1fd
53215e87e900d9dda1de7d41080b83bf95c9c0743949bd5c4af9ea11abc6a118939fad85eb0735991d6b9d8e891ccf0bd9cb99abf172
805a8cb5e5d778a279e1a0384713bb102e8ba0b0be1d56a9527722ef00de7e6baabfe3aae5f497a44f4
1788819442.233 192.168.99.1 308f1f1020103300d02013a020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040ce97d7d93c11dac8ea0caaafe04089b184efb1b39c21c0481a3ee52a2e7caf58003f3aaef04a
dcaabcf43bd1c13a51d4087e88c6a9a9cfb270aec98cf2cbdfc6f803608b8bc6591cde59384e91da399d6f1080102f98fe25152158b
139ebf2f59507f8016a328a4c7a9d1b80a4219982fe2f74978cda2b2ef1bf7d7faf9d835a5c3f3f9042d5c744ae898d39833cc1dbe052
02b505f5d02dbbe48944635bb890fd08e79baae5523fd4bd8e7aa0f86d71427b43736a5d9d7bef4403
1788819442.267 192.168.99.2 308f1f1020103300d020142020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040cd6f8a07f793b069d069759170408bdf4dc46c97074970481a33116ac4348d5c39ada28f96d78
e74d155c5cc9bf7fa42f9fddadcbcf9f298c97a79d1335ef72ad9631dc12834db86976c08bc0949e78ce7926afec969d51ff59b6bf01
7b912bab7415c3068dc730665587dd829e838b378fbc81aeaa7be721b39cc8ec406c7f91f5bf3e02ef0f84d884b62698b64590b35f1
8921e3a8316c7d66a27f4300e3b40e92dcf8449782b483b7eb1b1c0a3da45fbc424622a7d600f36d7023
1788819442.306 192.168.99.3 308f1f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8030102
0102020200a204066c61626d6f6e040c3bb1f3582527a19034ec5d610408a7c7be9c6efe405b0481a3fa381e2249898d509d85e1d9b
3389b3128c7d34aaa0145cd77854357e6d69cd388db0d86c165a4fdf8a3d87f9bb961854ba187a1984c45dbbf58adca5541a5485c344
583a5c2913d9b4470b4325f28a9b0c3c74d18b4c3bd08fc9130c71b7165dc4c6d22a6e4226cd8546bac4ed78bd313ac2d76bfad8165bf
d95c8ff1fe7981815276c5c81ba3f027acbecb251449958991c430e2af57b98530410546f515e98124
1788819442.482 192.168.99.1 308f1f1020103300d02013c020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040c73a76bc49e552aab0d08f64d04089b184efb1b39c21e0481a3b1a6978d7875aefa7484d41426
fcac7bd01a45e729fb041e4e0053bcf6e1e7b4453849a0950b3cf16754d5aa8bb1e683b91e18dedd70c8eeb400fd5392669c3139475a2e
f9cea2e5f556ab286affc24b299f7257a7f9aaa3362d185225a4037aef8e61fb964fcd2e3f759405bf4911bb9c8e340b9c3c32a39f9b
caf86df01c6728b43aa549379361193e7dccaec3f3f0abd1c6f25b53985eb169cb05adfaa725d29e505e5
1788819442.518 192.168.99.2 308f1f1020103300d020144020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040ce22c3e1cccc3a0816b2de3090408bdf4dc46c97074990481a362ccc6cfc3fcb1f5df6e6a36ba9
061eb6d5f8e4cea2b22f8283c04ff27fe21962da8a88d91b1c4fbdc6a5d339e9dd070feed2193e628e3bdc3aeaea01f49bc99930a11e
69a68b57bc34e6500c2a923e4766fa1263512636869017b82cec5982625feded2ba54a93598fd3604d189683a16346138220d45f3a5
2b61fdeb71554fcc5d3fa447dc8681234e12ab5d5157c513e3981a8abd5e8e564fe10aecfc7bd4560ef
1788819442.556 192.168.99.3 308201db020103300d020140020205dc04010302010304373035040c800000090300525400c80301
020102020200a204066c61626d6f6e040cd0e347d7a518a7d9e2f37c1b0408a7c7be9c6efe405d0482018cd8efa54000ad401bbc326d
2bbcde825ab5152b6f654545b7ab79bde2ffad760703003bf05fd372b55c6598a7edececf536ad432095fb9260748bd46f1cc973fce
7d0c5d461a74567d653f8915b5eb8f3625a9acd114f2efc9c842fde25afe53f39a555ecb3dcf7d27a08432dc9340b766d913d297b4bb
07970a2510babd3bd4f4ce0ebb07fd019f9fd45e6fb29ef8feac58621e676b92935f9ce739373e633a53e74e506575e6f46825bb060ff
e5b0c8526d79831062a4e95dbd7fd07039dd603bf20ecd96990e12ab506b0cb8e915f9e5b37d553f38e991971986ec070324af943
30b1625bd961d67078f27e4290be8c1b30f9fdd4f9da38629eaf2dd334b0e0a26532c0549a3fc8782afe71d694abf3ac5084fb3ae4b9
34af1b612e329beb9c7e1163aa36dc290f9784b5cc2f25a844f00d69d85b798ee860408950a0e0a5c9d4a79f2784d07c6aca87f8a39
ea45e822985914ea2cb93b21d583ae4f38bbbb056238ff969149d9ebbe2171e6f569e3e2f1e75f5a94e133e9fca802228704d2f319ba
aef92a4fd087aa
1788819442.733 192.168.99.1 308f1f1020103300d02013e020205dc04010302010304373035040c800000090300525400c8010102
0102020200a204066c61626d6f6e040cf1375d27c9b13e3bc630dda704089b184efb1b39c2200481a30198f4b559036be6e04256f622
03359df9f4b249e253bfc47820d97178378d92b51f24de8d8455b5342f2d76797f484d9471253faea500058a89ac76482836c4d83314
b637ad7fc13ded93b704de011795c6d883a9036f15a8f96224a3162a8d83a10fe88c1e9da55743953b410a155c88ebec8dc5ed1f85e8
d6719b4b8a6db27cd5500b799d76f31678bbff135288e19a3de00a02a2b05ec9f77a51e2e82d417f4fd9
1788819442.769 192.168.99.2 30811bb020103300d020146020205dc04010302010304373035040c800000090300525400c8020102
0102020200a204066c61626d6f6e040c3df77a9a6185cfb1cfecf88a0408bdf4dc46c970749b046ef296014ded7c0ce032945da3386e
1ebd3a6f6a183b3c2e4ebf6a7517d3b4fbed02965d0cedde29f5e6919fa5f14ad44ce1b2f2fc828265b33e24d5f8c4f415511af6b9294
f9d44b5f12d56f7e84a1eea2197adb64e73721c87bfd23d6a00a98a878bc9f8f206e82d8a3606be17431
... 3233 more lines

Teardown (suite) Close Trap Collector, Close All Connections

17 Snmp Polling

17.01 **PASS** The NMS Runs Real Net-SNMP Tooling (0.1s, 2 commands)

The point of this VM: unlike the cirros hosts it has a genuine SNMP client, so the polling below is the real thing rather than something hand rolled for the test.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- output contains **NET-SNMP version**
- output contains **snmpget**
- output contains **snmpwalk**

How it was checked

NMS `snmpget --version 2>&1 | head -2; snmpwalk --version 2>&1 | head -1`

```
NET-SNMP version: 5.9.4.pre2
NET-SNMP version: 5.9.4.pre2
```

NMS `command -v snmpget snmpwalk snmptrapd`

```
/usr/bin/snmpget
/usr/bin/snmpwalk
/usr/sbin/snmptrapd
```

Teardown (suite) Close Nms, Close All Connections

17.02 **PASS** Every Router Answers An SNMPv3 authPriv Poll (0.2s, 3 commands)

The agent must be reachable and must accept the credentials the provisioner configured.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

NMS `snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1 1.3.6.1.2.1.1.5.0`

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"
```

NMS `snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2 1.3.6.1.2.1.1.5.0`

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

NMS `snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3 1.3.6.1.2.1.1.5.0`

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r3.lab.local"
```

Teardown (suite) Close Nms, Close All Connections

17.03 **PASS** Polled sysName Matches The Router's Own Hostname (0.4s, 6 commands)

Cross-check: the value SNMP returns is compared against what the device says on its CLI, so a plausible-looking answer from the wrong box cannot pass.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- **`\${polled}`** starts with **`\${expected}`[0]** (checked 3×)
- `msg=SNMP sysName `${polled}` does not match CLI hostname `${expected}`[0]`

How it was checked

NMS `snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1 1.3.6.1.2.1.1.5.0`

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"
```

R1 `show running-config | include ^hostname`

```
hostname c8000v-r1
```

NMS `snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2 1.3.6.1.2.1.1.5.0`

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

```
R2 show running-config | include ^hostname
hostname c8000v-r2
```

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r3.lab.local"
```

```
R3 show running-config | include ^hostname
hostname c8000v-r3
```

Teardown (suite) Close Nms, Close All Connections

17.04 PASS Polled sysDescr Identifies The Platform (0.2s, 6 commands)

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- output matches Cisco IOS[-]XE Software|Cisco IOS Software \[IOSXE] (checked 3×)

How it was checked

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1
1.3.6.1.2.1.1.1.0
.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
```

R1 show version | include Version

```
Cisco IOS XE Software, Version 17.15.06
Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-UNIVERSALK9-M), Version 17.15.6, RELEASE
SOFTWARE (fc2)
licensed under the GNU General Public License ("GPL") Version 2.0. The
software code licensed under GPL Version 2.0 is free software that comes
GPL code under the terms of GPL Version 2.0. For more details, see the
```

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.1.0
.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
```

R2 show version | include Version

```
Cisco IOS XE Software, Version 17.15.06
Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-UNIVERSALK9-M), Version 17.15.6, RELEASE
SOFTWARE (fc2)
licensed under the GNU General Public License ("GPL") Version 2.0. The
software code licensed under GPL Version 2.0 is free software that comes
GPL code under the terms of GPL Version 2.0. For more details, see the
```

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3
1.3.6.1.2.1.1.1.0
.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
```

R3 show version | include Version

```
Cisco IOS XE Software, Version 17.15.06
Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-UNIVERSALK9-M), Version 17.15.6, RELEASE
SOFTWARE (fc2)
licensed under the GNU General Public License ("GPL") Version 2.0. The
software code licensed under GPL Version 2.0 is free software that comes
GPL code under the terms of GPL Version 2.0. For more details, see the
```

Teardown (suite) Close Nms, Close All Connections

17.05 PASS sysUpTime Advances Between Two Polls (5.1s, 2 commands)

Proves the answers come from a live agent rather than a cached or replayed response.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- \${second} > \${first} holds

How it was checked

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1
1.3.6.1.2.1.1.3.0
.1.3.6.1.2.1.1.3.0 = Timeticks: (512734) 1:25:27.34
```

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1
1.3.6.1.2.1.1.3.0
.1.3.6.1.2.1.1.3.0 = Timeticks: (513236) 1:25:32.36
```

Teardown (suite) Close Nms, Close All Connections

17.06 PASS Walking The Interface Table Returns Every Interface The CLI Shows (0.2s, 6 commands)

A walk, not a get: the agent must return the whole subtree. Every physical interface named by the CLI must appear in it.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- `#{walked}` contains `#{intf}` (checked 12×)
msg=#{r}: ifDescr walk is missing `#{intf}`

How it was checked

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1
1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

R1 show ip interface brief

Interface	IP-Address	OK?	Method	Status	Protocol
GigabitEthernet1	10.0.2.15	YES	DHCP	up	up
GigabitEthernet2	100.64.0.1	YES	TFTP	up	up
GigabitEthernet3	192.168.10.1	YES	TFTP	up	up
GigabitEthernet4	192.168.99.1	YES	TFTP	up	up
Loopback0	172.16.1.1	YES	TFTP	up	up
Loopback1	10.20.1.1	YES	manual	up	up
Tunnel0	172.20.0.1	YES	manual	up	up

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

R2 show ip interface brief

Interface	IP-Address	OK?	Method	Status	Protocol
GigabitEthernet1	10.0.2.15	YES	DHCP	up	up
GigabitEthernet2	100.64.0.2	YES	TFTP	up	up
GigabitEthernet3	192.168.20.1	YES	TFTP	up	up
GigabitEthernet4	192.168.99.2	YES	TFTP	up	up
Loopback0	172.16.2.1	YES	TFTP	up	up
Loopback1	10.20.2.1	YES	manual	up	up
Tunnel0	172.20.0.2	YES	manual	up	up

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3
1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

R3 show ip interface brief

Interface	IP-Address	OK?	Method	Status	Protocol
GigabitEthernet1	10.0.2.15	YES	DHCP	up	up
GigabitEthernet2	100.64.0.3	YES	TFTP	up	up
GigabitEthernet3	192.168.30.1	YES	TFTP	up	up
GigabitEthernet4	192.168.99.3	YES	TFTP	up	up
Loopback0	172.16.3.1	YES	TFTP	up	up
Loopback1	10.20.3.1	YES	manual	up	up
Tunnel0	172.20.0.3	YES	manual	up	up

Teardown (suite) Close Nms, Close All Connections

17.07 PASS Polled Interface Count Agrees With The Interface Table (0.3s, 6 commands)

ifNumber is a scalar the agent maintains separately from the table, so the two disagreeing would mean a broken agent.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- **\${number}** equals **\${rows}** (checked 3×)

msg=\${r}: ifNumber says \${number} but the table has \${rows} rows

How it was checked

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1
1.3.6.1.2.1.2.1.0
```

```
.1.3.6.1.2.1.2.1.0 = INTEGER: 9
```

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1
1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.2.1.0
```

```
.1.3.6.1.2.1.2.1.0 = INTEGER: 9
```

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3
1.3.6.1.2.1.2.1.0
```

```
.1.3.6.1.2.1.2.1.0 = INTEGER: 9
```

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3
1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

Teardown (suite) Close Nms, Close All Connections

17.08 PASS The LAN Interface Is Reported Up By Both SNMP And The CLI (0.4s, 9 commands)

ifOperStatus 1 is up(1). Checked against the CLI line protocol state for the same interface.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- `${index}` differs from **-1** (checked 3×)
msg=\${r}: no Gi3 in the walk
- output contains **1** (checked 3×)
msg=\${r}: SNMP says Gi3 is not up
- output contains **line protocol is up** (checked 3×)

How it was checked

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1 1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"  
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"  
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"  
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"  
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"  
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"  
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"  
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"  
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1 1.3.6.1.2.1.2.2.1.8
```

```
.1.3.6.1.2.1.2.2.1.8.1 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.2 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.3 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.4 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.5 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.6 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.7 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.8 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.9 = INTEGER: 1
```

R1 show interfaces GigabitEthernet3 | include line protocol

GigabitEthernet3 is up, line protocol is up

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2 1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"  
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"  
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"  
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"  
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"  
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"  
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"  
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"  
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2 1.3.6.1.2.1.2.2.1.8
```

```
.1.3.6.1.2.1.2.2.1.8.1 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.2 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.3 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.4 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.5 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.6 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.7 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.8 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.9 = INTEGER: 1
```

R2 show interfaces GigabitEthernet3 | include line protocol

GigabitEthernet3 is up, line protocol is up

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3 1.3.6.1.2.1.2.2.1.2
```

```
.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"  
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"  
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"  
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"  
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"  
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"  
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"  
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"  
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"
```

```
NMS snmpwalk -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3 1.3.6.1.2.1.2.2.1.8
```

```
.1.3.6.1.2.1.2.2.1.8.1 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.2 = INTEGER: 1  
.1.3.6.1.2.1.2.2.1.8.3 = INTEGER: 1
```

```
.1.3.6.1.2.1.2.2.1.8.4 = INTEGER: 1
.1.3.6.1.2.1.2.2.1.8.5 = INTEGER: 1
.1.3.6.1.2.1.2.2.1.8.6 = INTEGER: 1
.1.3.6.1.2.1.2.2.1.8.7 = INTEGER: 1
.1.3.6.1.2.1.2.2.1.8.8 = INTEGER: 1
.1.3.6.1.2.1.2.2.1.8.9 = INTEGER: 1
```

R3 show interfaces GigabitEthernet3 | include line protocol

```
GigabitEthernet3 is up, line protocol is up
```

Teardown (suite) Close Nms, Close All Connections

17.09 PASS Spokes Are Polled Across The Encrypted Tunnel (1.2s, 16 commands)

The NMS shares a LAN with the hub only. Traffic to R2 and R3 crosses the IPsec tunnels, so a burst of polling must show up on the ESP counters at both ends.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- **`\${a_enc} >= \${expected}** holds
- **`\${a_dec} >= \${expected}** holds
- **`\${b_enc} >= \${expected}** holds
- **`\${b_dec} >= \${expected}** holds

How it was checked

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 79927, #pkts encrypt: 79927, #pkts digest: 79927
  #pkts decaps: 43120, #pkts decrypt: 43120, #pkts verify: 43120
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

R2 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 52413, #pkts encrypt: 52413, #pkts digest: 52413
  #pkts decaps: 28013, #pkts decrypt: 28013, #pkts verify: 28013
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2

1.3.6.1.2.1.1.5.0

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2

1.3.6.1.2.1.1.5.0

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2

1.3.6.1.2.1.1.5.0

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2

1.3.6.1.2.1.1.5.0

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2

1.3.6.1.2.1.1.5.0

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

```

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

```

R1 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 79935, #pkts encrypt: 79935, #pkts digest: 79935
  #pkts decaps: 43126, #pkts decrypt: 43126, #pkts verify: 43126
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines

```

R1 show crypto ipsec sa

```

interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.2

protected vrf: (none)
local ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.3/255.255.255.255/47/0)
current_peer 100.64.0.3 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 52418, #pkts encrypt: 52418, #pkts digest: 52418
  #pkts decaps: 28018, #pkts decrypt: 28018, #pkts verify: 28018
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines

```

Teardown (suite) Close Nms, Close All Connections

17.10 PASS A Wrong Authentication Password Is Refused (0.1s, 2 commands)

Negative control. The agent answers the correct credentials first, so a refusal here cannot be a dead router.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

```

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A NotTheRightPassword -x AES -X LabPrivPass123 -t 2 -r 0
192.168.99.1 1.3.6.1.2.1.1.5.0
snmpget: Authentication failure (incorrect password, community or key)

```

Teardown (suite) Close Nms, Close All Connections

17.11 PASS A Wrong Privacy Password Is Refused (2.2s, 3 commands)

Authentication succeeds but the payload will not decrypt, so the router drops the request silently and the client times out. Bracketed by a good poll to prove it is still alive.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1 1.3.6.1.2.1.1.5.0
```

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"
```

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X NotTheRightPassword -t 2 -r 0 192.168.99.1 1.3.6.1.2.1.1.5.0
```

```
Timeout: No Response from 192.168.99.1.
```

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1 1.3.6.1.2.1.1.5.0
```

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"
```

Teardown (suite) Close Nms, Close All Connections

17.12 PASS Polling Without Privacy Is Refused By Every Router (0.3s, 6 commands)

The group is configured "v3 priv". Correct credentials at a lower security level must still be denied, otherwise the privacy requirement is decorative.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

```
NMS snmpget -On -v3 -l noAuthNoPriv -u labmon -t 2 -r 0 192.168.99.1 1.3.6.1.2.1.1.5.0
```

```
Error in packet
```

```
Reason: authorizationError (access denied to that object)
```

```
NMS snmpget -On -v3 -l authNoPriv -u labmon -a SHA -A LabAuthPass123 -t 2 -r 0 192.168.99.1 1.3.6.1.2.1.1.5.0
```

```
Error in packet
```

```
Reason: authorizationError (access denied to that object)
```

```
NMS snmpget -On -v3 -l noAuthNoPriv -u labmon -t 2 -r 0 192.168.99.2 1.3.6.1.2.1.1.5.0
```

```
Error in packet
```

```
Reason: authorizationError (access denied to that object)
```

```
NMS snmpget -On -v3 -l authNoPriv -u labmon -a SHA -A LabAuthPass123 -t 2 -r 0 192.168.99.2 1.3.6.1.2.1.1.5.0
```

```
Error in packet
```

```
Reason: authorizationError (access denied to that object)
```

```
NMS snmpget -On -v3 -l noAuthNoPriv -u labmon -t 2 -r 0 192.168.99.3 1.3.6.1.2.1.1.5.0
```

```
Error in packet
```

```
Reason: authorizationError (access denied to that object)
```

```
NMS snmpget -On -v3 -l authNoPriv -u labmon -a SHA -A LabAuthPass123 -t 2 -r 0 192.168.99.3 1.3.6.1.2.1.1.5.0
```

```
Error in packet
```

```
Reason: authorizationError (access denied to that object)
```

Teardown (suite) Close Nms, Close All Connections

17.13 PASS An Unknown User Is Refused (0.1s, 1 commands)

Only the provisioned user exists in the USM table.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

```
NMS snmpget -On -v3 -l authPriv -u intruder -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 2 -r 0 192.168.99.1 1.3.6.1.2.1.1.5.0
```

```
snmpget: Unknown user name
```

Teardown (suite) Close Nms, Close All Connections

17.14 PASS SNMPv2c Gets No Answer At The Wire (6.3s, 6 commands)

Suite 16 asserts no community is configured. This asserts the consequence on the network: a v2c poll gets nothing back, while a v3 poll to the same address succeeds.

Setup (suite) Open All Routers, Open Nms

Acceptance criteria

- output contains **Timeout** (checked 3×)

How it was checked

NMS `snmpget -On -v2c -c public -t 2 -r 0 192.168.99.1 1.3.6.1.2.1.1.5.0`

Timeout: No Response from 192.168.99.1.

NMS `snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1 1.3.6.1.2.1.1.5.0`

.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"

NMS `snmpget -On -v2c -c public -t 2 -r 0 192.168.99.2 1.3.6.1.2.1.1.5.0`

Timeout: No Response from 192.168.99.2.

NMS `snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2 1.3.6.1.2.1.1.5.0`

.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

NMS `snmpget -On -v2c -c public -t 2 -r 0 192.168.99.3 1.3.6.1.2.1.1.5.0`

Timeout: No Response from 192.168.99.3.

NMS `snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3 1.3.6.1.2.1.1.5.0`

.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r3.lab.local"

Teardown (suite) Close Nms, Close All Connections

18 Mtu

18.01 PASS Every Tunnel Reports The Expected Transport MTU (0.3s, 9 commands)

The tunnel MTU must be below the physical one by the ESP overhead. Equal would mean encryption costs nothing, which would mean it is not happening.

Setup (suite) Open All Routers, Open All Hosts

Acceptance criteria

- `${tunnels}` is not empty (checked 3×)
- output contains `${TUNNEL_MTU} bytes` (checked 3×)
- output contains `MTU is ${TUNNEL_MTU} bytes` (checked 3×)
- `${TUNNEL_MTU} < ${PHYSICAL_MTU}` holds

How it was checked

```
R1 show ip interface brief | include ^Tunnel
Tunnel0          172.20.0.1      YES manual up
R1 show interfaces Tunnel0 | include Tunnel transport MTU
Tunnel transport MTU 1472 bytes
R1 show ip interface Tunnel0 | include MTU
MTU is 1472 bytes
R2 show ip interface brief | include ^Tunnel
Tunnel0          172.20.0.2      YES manual up
R2 show interfaces Tunnel0 | include Tunnel transport MTU
Tunnel transport MTU 1472 bytes
R2 show ip interface Tunnel0 | include MTU
MTU is 1472 bytes
R3 show ip interface brief | include ^Tunnel
Tunnel0          172.20.0.3      YES manual up
R3 show interfaces Tunnel0 | include Tunnel transport MTU
Tunnel transport MTU 1472 bytes
R3 show ip interface Tunnel0 | include MTU
MTU is 1472 bytes
```

Teardown (suite) Close All Connections

18.02 PASS The Overhead Is What GRE With A Tunnel Key Costs (0.0s, 0 commands)

Records the number rather than assuming it: 20 bytes of outer IP, 4 of GRE and 4 for the tunnel key. If the encapsulation changes -- dropping the key, or moving IPsec from transport to tunnel mode -- this is the test that should fail first.

Setup (suite) Open All Routers, Open All Hosts

Acceptance criteria

- `${overhead}` equals 28

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Close All Connections

18.03 PASS A Packet Exactly At The Tunnel MTU Crosses With DF Set (0.1s, 2 commands)

The permissive half of the boundary. Sourced from Loopback1 so the traffic is inside the protected selector. Warmed up first: the first packet between two spokes is consumed establishing the shortcut and its security association, so a cold measurement here reports 80 percent and says nothing about the MTU. That first-packet loss is DMVPN working, not failing.

Setup (suite) Open All Routers, Open All Hosts

Acceptance criteria

- output contains **Success rate is 100 percent**
a packet of exactly the tunnel MTU (`${TUNNEL_MTU}`) did not cross

How it was checked

```
R2 ping 10.20.3.1 source Loopback1 repeat 5
```

```
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.20.3.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.2.1
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/3 ms
```

R2 ping 10.20.3.1 source Loopback1 size 1472 df-bit repeat 5

```
Type escape sequence to abort.
Sending 5, 1472-byte ICMP Echos to 10.20.3.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.2.1
Packet sent with the DF bit set
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/3 ms
```

Teardown (suite) Close All Connections

18.04 **PASS** One Byte Over The Tunnel MTU Does Not Cross With DF Set (10.0s, 1 commands)

The restrictive half. Without this the test above would pass just as well against a tunnel with no MTU limit at all.

Setup (suite) Open All Routers, Open All Hosts

Acceptance criteria

- output contains **Success rate is 0 percent**
a packet one byte over the tunnel MTU crossed with DF set

How it was checked

R2 ping 10.20.3.1 source Loopback1 size 1473 df-bit repeat 5

```
Type escape sequence to abort.
Sending 5, 1473-byte ICMP Echos to 10.20.3.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.2.1
Packet sent with the DF bit set
.....
Success rate is 0 percent (0/5)
```

Teardown (suite) Close All Connections

18.05 **PASS** Oversize Traffic Still Crosses When Fragmentation Is Allowed (0.1s, 2 commands)

Distinguishes an MTU limit from a blackhole: the same sizes that fail with DF set must succeed without it.

Setup (suite) Open All Routers, Open All Hosts

Acceptance criteria

- output contains **Success rate is 100 percent** (checked 2×)
a \${size}-byte packet failed even with fragmentation allowed

How it was checked

R2 ping 10.20.3.1 source Loopback1 size 1500 repeat 5

```
Type escape sequence to abort.
Sending 5, 1500-byte ICMP Echos to 10.20.3.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.2.1
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/3 ms
```

R2 ping 10.20.3.1 source Loopback1 size 2000 repeat 5

```
Type escape sequence to abort.
Sending 5, 2000-byte ICMP Echos to 10.20.3.1, timeout is 2 seconds:
Packet sent with a source address of 10.20.2.1
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
```

Teardown (suite) Close All Connections

18.06 **PASS** Hosts Pass Sub-MTU Traffic With DF Set (4.0s, 1 commands)

End to end across two encrypt/decrypt hops, from machines that know nothing about the tunnel.

Setup (suite) Open All Routers, Open All Hosts

Acceptance criteria

- output contains **0% packet loss**
a host could not pass \${HOST_PAYLOAD} bytes with DF set

How it was checked

```
H2 ping -c 5 -M do -s 1444 192.168.30.10
PING 192.168.30.10 (192.168.30.10) 1444(1472) bytes of data.
1452 bytes from 192.168.30.10: icmp_seq=1 ttl=62 time=1.48 ms
1452 bytes from 192.168.30.10: icmp_seq=2 ttl=62 time=1.43 ms
1452 bytes from 192.168.30.10: icmp_seq=3 ttl=62 time=1.36 ms
1452 bytes from 192.168.30.10: icmp_seq=4 ttl=62 time=1.33 ms
1452 bytes from 192.168.30.10: icmp_seq=5 ttl=62 time=1.50 ms

--- 192.168.30.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.329/1.421/1.503/0.066 ms
```

Teardown (suite) Close All Connections

18.07 **PASS** An End Host Learns The Tunnel Path MTU (2.0s, 1 commands)

The test that matters most in practice. The host is two hops and an encryption boundary away from the constraint, yet it must end up knowing the real limit -- otherwise a client retransmits into a black hole instead of backing off. The host reporting the exact tunnel MTU is proof that path MTU discovery survived the tunnel.

Setup (suite) Open All Routers, Open All Hosts

Acceptance criteria

- output contains **mtu=\${TUNNEL_MTU}**
the host did not learn the \${TUNNEL_MTU}-byte path MTU: \${out}

How it was checked

```
H2 ping -c 2 -M do -s 1472 192.168.30.10
PING 192.168.30.10 (192.168.30.10) 1472(1500) bytes of data.
From 192.168.20.1 icmp_seq=1 Frag needed and DF set (mtu = 1472)
ping: local error: message too long, mtu=1472

--- 192.168.30.10 ping statistics ---
2 packets transmitted, 0 received, +2 errors, 100% packet loss, time 1005ms
```

Teardown (suite) Close All Connections

18.08 **PASS** Hosts Pass Oversize Traffic Without DF Set (4.0s, 1 commands)

The counterpart: the same payload that was refused with DF set gets through when it may be fragmented.

Setup (suite) Open All Routers, Open All Hosts

Acceptance criteria

- output contains **0% packet loss**
oversize host traffic failed even with fragmentation allowed

How it was checked

```
H2 ping -c 5 -s 1472 192.168.30.10
PING 192.168.30.10 (192.168.30.10) 1472(1500) bytes of data.
1480 bytes from 192.168.30.10: icmp_seq=1 ttl=62 time=1.47 ms
1480 bytes from 192.168.30.10: icmp_seq=2 ttl=62 time=1.46 ms
1480 bytes from 192.168.30.10: icmp_seq=3 ttl=62 time=2.01 ms
1480 bytes from 192.168.30.10: icmp_seq=4 ttl=62 time=1.57 ms
1480 bytes from 192.168.30.10: icmp_seq=5 ttl=62 time=1.41 ms

--- 192.168.30.10 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.414/1.582/2.008/0.218 ms
```

Teardown (suite) Close All Connections

19 Oob

19.01 PASS Every Router Has A Management VRF (0.0s, 3 commands)

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- output contains **MGMT_VRF** (checked 3×)
- output contains **ipv4** (checked 3×)

How it was checked

R1 show vrf

Name	Default RD	Protocols	Interfaces
MGMT	<not set>	ipv4	Gi4

R2 show vrf

Name	Default RD	Protocols	Interfaces
MGMT	<not set>	ipv4	Gi4

R3 show vrf

Name	Default RD	Protocols	Interfaces
MGMT	<not set>	ipv4	Gi4

Teardown (suite) Restore Tunnels, Close Nms, Close Collector, Close All Connections

19.02 PASS Only The OOB Interface Is In The Management VRF (0.1s, 3 commands)

A VRF containing a data interface would defeat the point, so this asserts membership is exactly one interface.

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- output contains **short** (checked 3×)
- output does not contain **data** (checked 9×)

How it was checked

R1 show vrf MGMT

Name	Default RD	Protocols	Interfaces
MGMT	<not set>	ipv4	Gi4

R2 show vrf MGMT

Name	Default RD	Protocols	Interfaces
MGMT	<not set>	ipv4	Gi4

R3 show vrf MGMT

Name	Default RD	Protocols	Interfaces
MGMT	<not set>	ipv4	Gi4

Teardown (suite) Restore Tunnels, Close Nms, Close Collector, Close All Connections

19.03 PASS Every Router Holds Its OOB Address On The Flat Network (0.1s, 3 commands)

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- output contains **OOB_IP** (checked 3×)
- output contains **up** (checked 3×)

How it was checked

R1 show ip interface brief | include GigabitEthernet4

GigabitEthernet4	192.168.99.1	YES	TFTP	up	up
------------------	--------------	-----	------	----	----

R2 show ip interface brief | include GigabitEthernet4

GigabitEthernet4	192.168.99.2	YES	TFTP	up	up
------------------	--------------	-----	------	----	----

R3 show ip interface brief | include GigabitEthernet4

GigabitEthernet4	192.168.99.3	YES	TFTP	up	up
------------------	--------------	-----	------	----	----

Teardown (suite) Restore Tunnels, Close Nms, Close Collector, Close All Connections

19.04 PASS The Management VRF Routing Table Holds Only The Flat Network (0.1s, 3

commands)

The isolation, stated as routing: the VRF must know how to reach the management network and nothing else. A default route or a data prefix here would be a leak.

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- output contains **#{OOB_NET}** (checked 3×)
- output does not contain **#{data}** (checked 12×)

How it was checked

R1 show ip route vrf MGMT

Routing Table: MGMT

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
& - replicated local route overrides by connected

... 5 more lines

R2 show ip route vrf MGMT

Routing Table: MGMT

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
& - replicated local route overrides by connected

... 5 more lines

R3 show ip route vrf MGMT

Routing Table: MGMT

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR
& - replicated local route overrides by connected

... 5 more lines

Teardown (suite) Restore Tunnels, Close Nms, Close Collector, Close All Connections

19.05 PASS The Global Table Cannot Reach The Management Network (0.1s, 3 commands)

The other direction. Traffic in the global table must have no path to the OOB network, otherwise the VRF is decorative.

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- output contains **not in table** (checked 3×)

How it was checked

```
R1 show ip route 192.168.99.0
% Network not in table

R2 show ip route 192.168.99.0
% Network not in table

R3 show ip route 192.168.99.0
% Network not in table
```

Teardown (suite) Restore Tunnels, Close Nms, Close Collector, Close All Connections

19.06 PASS Every Router Answers SNMP On Its OOB Address (0.3s, 6 commands)

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- `${name}` starts with `${expected}[0]` (checked 3×)
- polling `${OOB_IP}${r}` answered as `'${name}'`, not `${r}`

How it was checked

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.1
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"

R1 show running-config | include ^hostname
hostname c8000v-r1

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"

R2 show running-config | include ^hostname
hostname c8000v-r2

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r3.lab.local"

R3 show running-config | include ^hostname
hostname c8000v-r3
```

Teardown (suite) Restore Tunnels, Close Nms, Close Collector, Close All Connections

19.07 PASS Management Traffic Never Touches The Data Path (3.2s, 28 commands)

The negative property that makes this out-of-band. Polling a spoke used to cross an IPsec tunnel and was asserted to advance the ESP counters; now it must do the opposite. The comparison is against an idle window of the same length, because BGP and BFD tick those counters continuously regardless -- so an absolute delta proves nothing.

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- `${attributable} < ${POLL_BURST}` holds

How it was checked

```
R1 show crypto ipsec sa
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

  protected vrf: (none)
  local ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
  remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
  current_peer 100.64.0.2 port 500
    PERMIT, flags={origin_is_acl,}
    #pkts encaps: 80145, #pkts encrypt: 80145, #pkts digest: 80145
    #pkts decaps: 43337, #pkts decrypt: 43337, #pkts verify: 43337
    #pkts compressed: 0, #pkts decompressed: 0
    #pkts not compressed: 0, #pkts compr. failed: 0
    #pkts not decompressed: 0, #pkts decompress failed: 0
    #send errors 0, #recv errors 0
  ... 78 more lines

NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

[illegible]

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.3
1.3.6.1.2.1.1.5.0
```

```
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r3.lab.local"
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local  ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 80151, #pkts encrypt: 80151, #pkts digest: 80151
  #pkts decaps: 43343, #pkts decrypt: 43343, #pkts verify: 43343
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local  ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 80151, #pkts encrypt: 80151, #pkts digest: 80151
  #pkts decaps: 43343, #pkts decrypt: 43343, #pkts verify: 43343
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

R1 show crypto ipsec sa

```
interface: Tunnel0
  Crypto map tag: Tunnel0-head-0, local addr 100.64.0.1

protected vrf: (none)
local  ident (addr/mask/prot/port): (100.64.0.1/255.255.255.255/47/0)
remote ident (addr/mask/prot/port): (100.64.0.2/255.255.255.255/47/0)
current_peer 100.64.0.2 port 500
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 80165, #pkts encrypt: 80165, #pkts digest: 80165
  #pkts decaps: 43356, #pkts decrypt: 43356, #pkts verify: 43356
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0
  #pkts not decompressed: 0, #pkts decompress failed: 0
  #send errors 0, #recv errors 0
... 78 more lines
```

Teardown (suite) Restore Tunnels, Close Nms, Close Collector, Close All Connections

19.08 PASS Syslog Reaches The Collector From The OOB Address (12.2s, 4 commands)

rsyslog files are named for the sender. A file named after a LAN address would mean the router is logging from the data path despite the configuration. Each router is made to emit a marked message rather than waiting on ambient traffic: whether a router happens to have logged recently is not what this test is about, and depending on it makes the result a matter of timing.

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- output contains `${OOB_IP}${r}` (checked 3×)
- `${n} > 0` holds (checked 3×)
- output does not contain `${r}_LAN_IP.log` (checked 3×)

How it was checked

```
NMS sudo grep -c -- 'LAB00B-SRC-R1-193959' /var/log/lab/192.168.99.1.log 2>/dev/null || echo 0
1
```

```
NMS sudo grep -c -- 'LAB00B-SRC-R2-193959' /var/log/lab/192.168.99.2.log 2>/dev/null || echo 0
1
```

```
NMS sudo grep -c -- 'LAB00B-SRC-R3-193959' /var/log/lab/192.168.99.3.log 2>/dev/null || echo 0
```

1

```
NMS sudo ls -l /var/log/lab
total 3412
-rw-r--r-- 1 syslog syslog 162978 Sep  7 23:40 192.168.99.1.log
-rw-r--r-- 1 syslog syslog 204503 Sep  7 23:40 192.168.99.2.log
-rw-r--r-- 1 syslog syslog 127160 Sep  7 23:40 192.168.99.3.log
-rw-r--r-- 1 root  root 1136638 Sep  7 23:39 snmptrapd.log
-rw-r--r-- 1 root  root 1832337 Sep  7 23:39 traps-raw.log
```

Teardown (suite) Restore Tunnels, Close Nms, Close Collector, Close All Connections

19.09 PASS A Spoke Stays Manageable With Its Tunnel Down (14.4s, 15 commands)

The reason out-of-band management exists. Shutting R2's tunnel removes every data path between the hub and the spoke -- BGP drops, the LAN becomes unreachable -- and the spoke must still answer SNMP and keep logging, because none of that ever used the tunnel.

Setup (suite) Open All Routers, Open Nms, Open Collector

Acceptance criteria

- output contains **not in table** (checked 2×)
the hub can still reach R2's LAN, so the data path is not down yet
- **#{before}** equals **#{after}**
R2 stopped answering SNMP once its tunnel went down, so management is not out-of-band
- **#{n} > 0** holds
- output matches **#{peer}ls+4ls+#{peer_asn}(ls+ld+){5}ls+Sls+ld+** (checked 2×)

How it was checked

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 interface Tunnel0

#{output} =

R2 shutdown

#{output} =

R2 end

#{output} =

R1 show ip route 192.168.20.0

```
Routing entry for 192.168.20.0/24
  Known via "bgp 65001", distance 20, metric 0
  Tag 65002, type external
  Last update from 172.20.0.2 00:08:27 ago
  Routing Descriptor Blocks:
  * 172.20.0.2, from 172.20.0.2, 00:08:27 ago
    opaque_ptr 0x747B4EAD55B8
    Route metric is 0, traffic share count is 1
    AS Hops 1
    Route tag 65002
    MPLS label: none
```

R1 show ip route 192.168.20.0

% Network not in table

```
NMS snmpget -On -v3 -l authPriv -u labmon -a SHA -A LabAuthPass123 -x AES -X LabPrivPass123 -t 3 -r 1 192.168.99.2
1.3.6.1.2.1.1.5.0
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
```

```
NMS sudo grep -c -- 'LAB00B-194017' /var/log/lab/192.168.99.2.log 2>/dev/null || echo 0
1
```

R2 configure terminal

Enter configuration commands, one per line. End with CNTL/Z.

R2 interface Tunnel0

#{output} =

R2 no shutdown

#{output} =

R2 end

#{output} =

R1 show bgp ipv4 unicast summary

BGP router identifier 172.16.1.1, local AS number 65001

```

BGP table version is 13, main routing table version 13
6 network entries using 1488 bytes of memory
6 path entries using 816 bytes of memory
4/4 BGP path/bestpath attribute entries using 1184 bytes of memory
1 BGP AS-PATH entries using 24 bytes of memory
3 BGP community entries using 72 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 3584 total bytes of memory
BGP activity 189/183 prefixes, 195/189 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (01:06:22.165 ago)

Neighbor      V          AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

```

R1 show bgp ipv4 unicast summary

```

BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 16, main routing table version 16
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
3 BGP route-map cache entries using 216 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5936 total bytes of memory
BGP activity 192/183 prefixes, 198/189 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (01:06:27.205 ago)

Neighbor      V          AS MsgRcvd MsgSent  TblVer  InQ OutQ Up/Down  State/PfxRcd
... 2 more lines

```

Teardown (this test) Restore Tunnels

20 Tacacs

20.01 **PASS** The TACACS Server Runs On The NMS (0.1s, 2 commands)

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- `${state}` equals **active**
tac_plus is not running on the NMS
- output contains `:${TAC_PORT}`
- output contains **tac_plus**

How it was checked

```
NMS systemctl is-active tacacs-lab
active
```

```
NMS sudo ss -ltnp | grep ':49 ' || echo NONE
LISTEN 0      128          0.0.0.0:49      0.0.0.0:*      users: (("tac_plus",pid=3254,fd=4))
LISTEN 0      128          [::]:49         [::]:*         users: (("tac_plus",pid=3254,fd=5))
```

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.02 **PASS** The Server Holds Both Remote Users And The Automation Account (0.1s, 1 commands)

The automation account has to exist on the server as well as locally on each router. Without it the first router to get AAA becomes unmanageable by this very test suite, while the server sits there perfectly healthy.

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- output contains `${ADMIN_USER}`
 - output contains `${OPS_USER}`
 - output contains `${USERNAME}`
- the automation account is missing from the server, which would lock the suite out

How it was checked

```
NMS sudo grep -oE '^user = [A-Za-z0-9_-]+' /etc/tacacs+/tac_plus.conf
user = netadmin
user = netops
user = lab
```

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.03 **PASS** Every Router Points At The Server Through The Management VRF (0.4s, 3 commands)

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- output contains **aaa new-model** (checked 3×)
- output contains **address ipv4 \${NMS_OOB_IP}** (checked 3×)
- output contains **ip vrf forwarding \${MGMT_VRF}** (checked 3×)
- output contains **ip tacacs source-interface \${OOB_INTF}[\${r}]** (checked 3×)

How it was checked

```
R1 show running-config | include ^aaa|^tacacs server|^ address ipv4|^ ip vrf forwarding|^ ip tacacs source
aaa new-model
aaa group server tacacs+ LABTACGRP
ip vrf forwarding MGMT
ip tacacs source-interface GigabitEthernet4
aaa authentication login default group LABTACGRP local
aaa authentication enable default group LABTACGRP enable
aaa authorization exec default group LABTACGRP local if-authenticated
aaa accounting exec default start-stop group LABTACGRP
```

```
aaa accounting commands 15 default start-stop group LABTACGRP
aaa session-id common
tacacs server LAB-TAC
address ipv4 192.168.99.10
```

R2 `show running-config | include ^aaa|^tacacs server|^ address ipv4|^ ip vrf forwarding|^ ip tacacs source`

```
aaa new-model
aaa group server tacacs+ LABTACGRP
ip vrf forwarding MGMT
ip tacacs source-interface GigabitEthernet4
aaa authentication login default group LABTACGRP local
aaa authentication enable default group LABTACGRP enable
aaa authorization exec default group LABTACGRP local if-authenticated
aaa accounting exec default start-stop group LABTACGRP
aaa accounting commands 15 default start-stop group LABTACGRP
aaa session-id common
tacacs server LAB-TAC
address ipv4 192.168.99.10
```

R3 `show running-config | include ^aaa|^tacacs server|^ address ipv4|^ ip vrf forwarding|^ ip tacacs source`

```
aaa new-model
aaa group server tacacs+ LABTACGRP
ip vrf forwarding MGMT
ip tacacs source-interface GigabitEthernet4
aaa authentication login default group LABTACGRP local
aaa authentication enable default group LABTACGRP enable
aaa authorization exec default group LABTACGRP local if-authenticated
aaa accounting exec default start-stop group LABTACGRP
aaa accounting commands 15 default start-stop group LABTACGRP
aaa session-id common
tacacs server LAB-TAC
address ipv4 192.168.99.10
```

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.04 **PASS** Every Method List Falls Back To The Local Database (0.3s, 3 commands)

A method list with no local fallback locks the lab out the moment the server is unreachable -- including from the console, which is the one way back in.

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- output contains **login default group \${TAC_GROUP} local** (checked 3×)
- output contains **exec default group \${TAC_GROUP} local** (checked 3×)

How it was checked

R1 `show running-config | include ^aaa authentication login|^aaa authorization exec`

```
aaa authentication login default group LABTACGRP local
aaa authorization exec default group LABTACGRP local if-authenticated
```

R2 `show running-config | include ^aaa authentication login|^aaa authorization exec`

```
aaa authentication login default group LABTACGRP local
aaa authorization exec default group LABTACGRP local if-authenticated
```

R3 `show running-config | include ^aaa authentication login|^aaa authorization exec`

```
aaa authentication login default group LABTACGRP local
aaa authorization exec default group LABTACGRP local if-authenticated
```

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.05 **PASS** Every Router Reports The Server Alive (0.1s, 3 commands)

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- output contains **Server Status: Alive** (checked 3×)
- output contains **\${NMS_OOB_IP}** (checked 3×)

How it was checked

R1 `show tacacs`

```
Tacacs+ Server - public :
Server name: LAB-TAC
Server address: 192.168.99.10
Server port: 49
```

```

        Socket opens:      1279
        Socket closes:    1279
        Socket aborts:    0
        Socket errors:    0
        Socket Timeouts:  0
    Failed Connect Attempts: 0
    Total Packets Sent:    1348
    Total Packets Recv:    1348
        Server Status: Alive
    Continous Authc fail count: 3
    ... 1 more lines

```

R2 show tacacs

```

Tacacs+ Server - public :
    Server name: LAB-TAC
    Server address: 192.168.99.10
    Server port: 49
        Socket opens:      1974
        Socket closes:    1974
        Socket aborts:    0
        Socket errors:    0
        Socket Timeouts:  0
    Failed Connect Attempts: 0
    Total Packets Sent:    2010
    Total Packets Recv:    2010
        Server Status: Alive
    Continous Authc fail count: 2
    ... 1 more lines

```

R3 show tacacs

```

Tacacs+ Server - public :
    Server name: LAB-TAC
    Server address: 192.168.99.10
    Server port: 49
        Socket opens:      733
        Socket closes:    733
        Socket aborts:    0
        Socket errors:    0
        Socket Timeouts:  0
    Failed Connect Attempts: 0
    Total Packets Sent:    799
    Total Packets Recv:    799
        Server Status: Alive
    Continous Authc fail count: 2
    ... 1 more lines

```

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.06 PASS A Remote Administrator Authenticates And Is Given Privilege 15 (0.2s, 0 commands)

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- `$_{priv}` equals `$_{ADMIN_PRIV}` (checked 3×)

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.07 PASS A Remote Operator Authenticates And Is Held At Privilege 1 (0.3s, 0 commands)

The pair that proves the level comes from the server. Two users, same router, same method list, different levels -- which cannot happen if the router is applying a default.

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- `$_{priv}` equals `$_{OPS_PRIV}` (checked 3×)

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.08 PASS A Wrong Password Is Refused (2.1s, 0 commands)

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.09 PASS An Unknown User Is Refused (2.1s, 0 commands)

The server rejects the user and the router honours that rather than quietly trying the local database.

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.10 PASS The Server Records Authentication In Its Accounting Log (0.1s, 1 commands)

Accounting is what makes remote authentication auditable; without it the router knows who logged in and nobody else ever finds out.

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

```
NMS sudo tail -200 /var/log/tac_plus.acct 2>/dev/null || true
Sep  7 23:37:39 192.168.99.1 lab      tty434 10.0.2.2      stop    task_id=4959      timezone=UTC
service=shell  start_time=1788824259 priv-lvl=15 cmd=show monitor capture POOLCAP buffer brief <cr>
Sep  7 23:37:41 192.168.99.1 lab      tty434 10.0.2.2      stop    task_id=4960      timezone=UTC
service=shell  start_time=1788824261 priv-lvl=15 cmd=no monitor capture POOLCAP <cr>
Sep  7 23:37:41 192.168.99.2 lab      tty434 10.0.2.2      stop    task_id=5649      timezone=UTC
service=shell  start_time=1788824172 disc-cause=1 disc-cause-ext=9 pre-session-time=0
elapsed_time=89 stop_time=1788824261
Sep  7 23:37:42 192.168.99.3 lab      tty434 10.0.2.2      stop    task_id=4434      timezone=UTC
service=shell  start_time=1788824172 disc-cause=1 disc-cause-ext=9 pre-session-time=0
elapsed_time=90 stop_time=1788824262
Sep  7 23:37:42 192.168.99.1 lab      tty435 10.0.2.2      start   task_id=4962      timezone=UTC
service=shell  start_time=1788824262
Sep  7 23:37:42 192.168.99.1 lab      tty434 10.0.2.2      stop    task_id=4941      timezone=UTC
service=shell  start_time=1788824172 disc-cause=1 disc-cause-ext=9 pre-session-time=0
elapsed_time=90 stop_time=1788824262
Sep  7 23:37:42 192.168.99.2 lab      tty435 10.0.2.2      start   task_id=5657      timezone=UTC
service=shell  start_time=1788824262
Sep  7 23:37:42 192.168.99.3 lab      tty434 10.0.2.2      start   task_id=4440      timezone=UTC
service=shell  start_time=1788824262
Sep  7 23:37:42 192.168.99.1 lab      tty435 10.0.2.2      stop    task_id=4962      timezone=UTC
service=shell  start_time=1788824262 priv-lvl=15 cmd=show running-config <cr>
Sep  7 23:37:42 192.168.99.2 lab      tty435 10.0.2.2      stop    task_id=5657      timezone=UTC
service=shell  start_time=1788824262 priv-lvl=15 cmd=show running-config <cr>
Sep  7 23:37:42 192.168.99.3 lab      tty434 10.0.2.2      stop    task_id=4440      timezone=UTC
service=shell  start_time=1788824262 priv-lvl=15 cmd=show running-config <cr>
Sep  7 23:37:45 192.168.99.1 lab      tty435 10.0.2.2      stop    task_id=4962      timezone=UTC
service=shell  start_time=1788824262 disc-cause=1 disc-cause-ext=9 pre-session-time=0
elapsed_time=3 stop_time=1788824265
Sep  7 23:37:45 192.168.99.2 lab      tty435 10.0.2.2      stop    task_id=5657      timezone=UTC
service=shell  start_time=1788824262 disc-cause=1 disc-cause-ext=9 pre-session-time=0
elapsed_time=3 stop_time=1788824265
Sep  7 23:37:45 192.168.99.1 lab      tty434 10.0.2.2      start   task_id=4964      timezone=UTC
service=shell  start_time=1788824265
... 186 more lines
```

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.11 PASS Accounting Records Carry The Privilege Level And Come From The OOB Address (0.1s, 1 commands)

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- output contains **service=shell**
- output contains **\${R3_OOB_IP}**

the record did not come from R3's out-of-band address

How it was checked

NMS `sudo tail -200 /var/log/tac_plus.acct 2>/dev/null || true`

```
Sep  7 23:37:39 192.168.99.1 lab      tty434 10.0.2.2      stop    task_id=4959    timezone=UTC
service=shell  start_time=1788824259  priv-lvl=15  cmd=show monitor capture POOLCAP buffer brief <cr>
Sep  7 23:37:41 192.168.99.1 lab      tty434 10.0.2.2      stop    task_id=4960    timezone=UTC
service=shell  start_time=1788824261  priv-lvl=15  cmd=no monitor capture POOLCAP <cr>
Sep  7 23:37:41 192.168.99.2 lab      tty434 10.0.2.2      stop    task_id=5649    timezone=UTC
service=shell  start_time=1788824172  disc-cause=1  disc-cause-ext=9  pre-session-time=0
elapsed_time=89 stop_time=1788824261
Sep  7 23:37:42 192.168.99.3 lab      tty434 10.0.2.2      stop    task_id=4434    timezone=UTC
service=shell  start_time=1788824172  disc-cause=1  disc-cause-ext=9  pre-session-time=0
elapsed_time=90 stop_time=1788824262
Sep  7 23:37:42 192.168.99.1 lab      tty435 10.0.2.2      start   task_id=4962    timezone=UTC
service=shell  start_time=1788824262
Sep  7 23:37:42 192.168.99.1 lab      tty434 10.0.2.2      stop    task_id=4941    timezone=UTC
service=shell  start_time=1788824172  disc-cause=1  disc-cause-ext=9  pre-session-time=0
elapsed_time=90 stop_time=1788824262
Sep  7 23:37:42 192.168.99.2 lab      tty435 10.0.2.2      start   task_id=5657    timezone=UTC
service=shell  start_time=1788824262
Sep  7 23:37:42 192.168.99.3 lab      tty434 10.0.2.2      start   task_id=4440    timezone=UTC
service=shell  start_time=1788824262
Sep  7 23:37:42 192.168.99.1 lab      tty435 10.0.2.2      stop    task_id=4962    timezone=UTC
service=shell  start_time=1788824262  priv-lvl=15  cmd=show running-config <cr>
Sep  7 23:37:42 192.168.99.2 lab      tty435 10.0.2.2      stop    task_id=5657    timezone=UTC
service=shell  start_time=1788824262  priv-lvl=15  cmd=show running-config <cr>
Sep  7 23:37:42 192.168.99.3 lab      tty434 10.0.2.2      stop    task_id=4440    timezone=UTC
service=shell  start_time=1788824262  priv-lvl=15  cmd=show running-config <cr>
Sep  7 23:37:45 192.168.99.1 lab      tty435 10.0.2.2      stop    task_id=4962    timezone=UTC
service=shell  start_time=1788824262  disc-cause=1  disc-cause-ext=9  pre-session-time=0
elapsed_time=3 stop_time=1788824265
Sep  7 23:37:45 192.168.99.2 lab      tty435 10.0.2.2      stop    task_id=5657    timezone=UTC
service=shell  start_time=1788824262  disc-cause=1  disc-cause-ext=9  pre-session-time=0
elapsed_time=3 stop_time=1788824265
Sep  7 23:37:45 192.168.99.1 lab      tty434 10.0.2.2      start   task_id=4964    timezone=UTC
service=shell  start_time=1788824265
... 186 more lines
```

Teardown (suite) Restore Oob Interfaces, Close Tacacs Server, Close All Connections

20.12 PASS The Local Account Still Works When The Server Is Unreachable (19.6s, 21

commands)

The resilience property. R2's out-of-band interface is shut, which is the only path to the server, so TACACS becomes unreachable rather than merely unwilling. The automation account must still get in through the local database, and a remote-only user must not -- it exists nowhere else. The precondition is a ping inside the VRF, not "show tacacs". That field reports cached state -- it keeps saying Alive until a transaction actually fails -- so waiting on it would either hang or, worse, let this test run with the server still reachable and prove nothing.

Setup (suite) Open All Routers, Open Tacacs Server

Acceptance criteria

- output matches **Success rate is 0 percent|does not have a usable source address**
 - **\${priv}** equals **15**
- the local account could not get in with the server unreachable
- output contains **Success rate is 100 percent** (checked 4x)

How it was checked

R2 `configure terminal`

Enter configuration commands, one per line. End with CNTL/Z.

R2 `interface GigabitEthernet4`

`${output}` =

R2 `shutdown`

`${output}` =

R2 `end`

`${output}` =

```

R2 ping vrf MGMT 192.168.99.10 repeat 2
% VRF MGMT does not have a usable source address

R1 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.

R1 interface GigabitEthernet4
${output} =

R1 no shutdown
${output} =

R1 end
${output} =

R2 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.

R2 interface GigabitEthernet4
${output} =

R2 no shutdown
${output} =

R2 end
${output} =

R3 configure terminal
Enter configuration commands, one per line. End with CNTL/Z.

R3 interface GigabitEthernet4
${output} =

R3 no shutdown
${output} =

R3 end
${output} =

R2 ping vrf MGMT 192.168.99.10 repeat 5
% VRF MGMT does not have a usable source address

R2 ping vrf MGMT 192.168.99.10 repeat 5
% VRF MGMT does not have a usable source address

R2 ping vrf MGMT 192.168.99.10 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.99.10, timeout is 2 seconds:
.!!!!
Success rate is 80 percent (4/5), round-trip min/avg/max = 1/1/1 ms

R2 ping vrf MGMT 192.168.99.10 repeat 5
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 192.168.99.10, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms

```

Teardown (this test) Restore Oob Interfaces

21 Vty Acl

21.01 **PASS** Every Router Applies The ACL Inbound On All VTY Lines (0.3s, 3 commands)

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria

- output contains **access-class \${VTY_ACL} in vrf-also** (checked 3×)

How it was checked

R1 show running-config | section ^line vty

```
line vty 0 4
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
line vty 5 15
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
```

R2 show running-config | section ^line vty

```
line vty 0 4
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
line vty 5 15
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
```

R3 show running-config | section ^line vty

```
line vty 0 4
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
line vty 5 15
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
```

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

21.02 **PASS** Only SSH Is Accepted On The VTY Lines (0.3s, 3 commands)

An ACL restricting who may connect is worth less if telnet is still an option for those who may.

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria

- output contains **transport input ssh** (checked 3×)
- output does not contain **transport input all** (checked 3×)
- output does not contain **transport input telnet** (checked 3×)

How it was checked

R1 show running-config | section ^line vty

```
line vty 0 4
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
line vty 5 15
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
```

R2 show running-config | section ^line vty

```
line vty 0 4
  access-class VTY-MGMT in vrf-also
```

```

exec-timeout 0 0
activation-character 13
transport input ssh
line vty 5 15
access-class VTY-MGMT in vrf-also
exec-timeout 0 0
activation-character 13
transport input ssh

```

R3 show running-config | section ^line vty

```

line vty 0 4
access-class VTY-MGMT in vrf-also
exec-timeout 0 0
activation-character 13
transport input ssh
line vty 5 15
access-class VTY-MGMT in vrf-also
exec-timeout 0 0
activation-character 13
transport input ssh

```

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

21.03 PASS The ACL Permits The Management Network And Denies The Rest (0.1s, 3 commands)

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria

- output contains **permit** **`\${OOB\_NET}`**, wildcard bits **0.0.0.255** (checked 3×)
 - output contains **deny** (checked 3×)
- any log

How it was checked

R1 show ip access-lists VTY-MGMT

```

Standard IP access list VTY-MGMT
 10 permit 192.168.99.0, wildcard bits 0.0.0.255 (4 matches)
 20 permit 10.0.2.0, wildcard bits 0.0.0.255 (186 matches)
 30 deny any log (6 matches)

```

R2 show ip access-lists VTY-MGMT

```

Standard IP access list VTY-MGMT
 10 permit 192.168.99.0, wildcard bits 0.0.0.255
 20 permit 10.0.2.0, wildcard bits 0.0.0.255 (212 matches)
 30 deny any log (2 matches)

```

R3 show ip access-lists VTY-MGMT

```

Standard IP access list VTY-MGMT
 10 permit 192.168.99.0, wildcard bits 0.0.0.255
 20 permit 10.0.2.0, wildcard bits 0.0.0.255 (184 matches)
 30 deny any log (2 matches)

```

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

21.04 PASS The Documented Exception Is Present And Is Only The Hypervisor Path (0.1s, 3 commands)

Pinned deliberately. This permit is the one concession in the policy, so it should be visible in a test rather than only in a comment -- and widening it should break something.

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria

- output contains **permit** **`\${MGMT\_NAT\_NET}`**, wildcard bits **0.0.0.255** (checked 3×)
- **`\${permits}`** has exactly **2** entries (checked 3×)

How it was checked

R1 show ip access-lists VTY-MGMT

```

Standard IP access list VTY-MGMT
 10 permit 192.168.99.0, wildcard bits 0.0.0.255 (4 matches)
 20 permit 10.0.2.0, wildcard bits 0.0.0.255 (186 matches)
 30 deny any log (6 matches)

```

R2 show ip access-lists VTY-MGMT

```
Standard IP access list VTY-MGMT
10 permit 192.168.99.0, wildcard bits 0.0.0.255
20 permit 10.0.2.0, wildcard bits 0.0.0.255 (212 matches)
30 deny any log (2 matches)
```

R3 show ip access-lists VTY-MGMT

```
Standard IP access list VTY-MGMT
10 permit 192.168.99.0, wildcard bits 0.0.0.255
20 permit 10.0.2.0, wildcard bits 0.0.0.255 (184 matches)
30 deny any log (2 matches)
```

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

21.05 PASS SSH From The Management Network Is Allowed (0.0s, 1 commands)

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria

- `${banner}` starts with SSH-

How it was checked

NMS python3 -c "import socket,sys

```
s=socket.socket()
s.settimeout(6)
s.bind(('192.168.99.10',0))
try:
    s.connect(('192.168.99.1',22))
    print(s.recv(64).decode(errors='replace').strip() or 'EMPTY')
except Exception as e:
    print(f'REFUSED {type(e).__name__}: {e}')
"
```

SSH-2.0-Cisco-1.25

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

21.06 PASS SSH From Outside The Management Network Is Refused (0.1s, 1 commands)

The same machine, a different source address, and a target it is directly connected to -- so nothing but the ACL can account for the difference. Before the access-class was applied this path returned a banner just like the one above.

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

NMS python3 -c "import socket,sys

```
s=socket.socket()
s.settimeout(6)
s.bind(('192.168.10.20',0))
try:
    s.connect(('192.168.10.1',22))
    print(s.recv(64).decode(errors='replace').strip() or 'EMPTY')
except Exception as e:
    print(f'REFUSED {type(e).__name__}: {e}')
"
```

REFUSED ConnectionRefusedError: [Errno 111] Connection refused

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

21.07 PASS Every Router Refuses A Login From Outside The Management Network (0.2s, 3 commands)

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked

NMS python3 -c "import socket,sys

```
s=socket.socket()
s.settimeout(6)
```

```
s.bind(('192.168.10.20',0))
try:
    s.connect(('192.168.10.1',22))
    print(s.recv(64).decode(errors='replace').strip() or 'EMPTY')
except Exception as e:
    print(f'REFUSED {type(e).__name__}: {e}')
"
REFUSED ConnectionRefusedError: [Errno 111] Connection refused
```

NMS python3 -c "import socket,sys

```
s=socket.socket()
s.settimeout(6)
s.bind(('192.168.10.20',0))
try:
    s.connect(('192.168.20.1',22))
    print(s.recv(64).decode(errors='replace').strip() or 'EMPTY')
except Exception as e:
    print(f'REFUSED {type(e).__name__}: {e}')
"
REFUSED ConnectionRefusedError: [Errno 111] Connection refused
```

NMS python3 -c "import socket,sys

```
s=socket.socket()
s.settimeout(6)
s.bind(('192.168.10.20',0))
try:
    s.connect(('192.168.30.1',22))
    print(s.recv(64).decode(errors='replace').strip() or 'EMPTY')
except Exception as e:
    print(f'REFUSED {type(e).__name__}: {e}')
"
REFUSED ConnectionRefusedError: [Errno 111] Connection refused
```

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

21.08 PASS The Refusal Is Logged And Reaches The Collector (0.1s, 2 commands)

"deny any log" makes a rejected connection auditable rather than merely blocked, and the message travels the OOB network to the collector like every other log.

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria

- output matches **SEC-6-IPACCESSLOGS***
no access-list denial logged by \${router} reached the collector

How it was checked

NMS python3 -c "import socket,sys

```
s=socket.socket()
s.settimeout(6)
s.bind(('192.168.10.20',0))
try:
    s.connect(('192.168.10.1',22))
    print(s.recv(64).decode(errors='replace').strip() or 'EMPTY')
except Exception as e:
    print(f'REFUSED {type(e).__name__}: {e}')
"
REFUSED ConnectionRefusedError: [Errno 111] Connection refused
```

NMS sudo cat /var/log/lab/192.168.99.1.log 2>/dev/null || true

```
<189>207: 000203: *Sep 7 22:17:21.168 UTC: %SSH-5-SSH2_SESSION: SSH2 Session request from 10.0.2.2 (tty =
0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>208: 000204: *Sep 7 22:17:21.214 UTC: %SEC_LOGIN-5-LOGIN_SUCCESS: Login Success [user: lab] [Source:
10.0.2.2] [localport: 22] at 22:17:21 UTC Mon Sep 7 2026
<189>209: 000205: *Sep 7 22:17:21.214 UTC: %SSH-5-SSH2_USERAUTH: User 'lab' authentication for SSH2 Session
from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<190>210: 000206: *Sep 7 22:17:56.590 UTC: %SYS-6-LOGOUT: User lab has exited tty session 434(10.0.2.2)
<189>211: 000207: *Sep 7 22:17:56.591 UTC: %SSH-5-SSH2_CLOSE: SSH2 Session from 10.0.2.2 (tty = 0) for user
' using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' closed
<189>212: 000208: *Sep 7 22:18:27.361 UTC: %SSH-5-SSH2_SESSION: SSH2 Session request from 10.0.2.2 (tty =
0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>213: 000209: *Sep 7 22:18:27.410 UTC: %SEC_LOGIN-5-LOGIN_SUCCESS: Login Success [user: lab] [Source:
10.0.2.2] [localport: 22] at 22:18:27 UTC Mon Sep 7 2026
<189>214: 000210: *Sep 7 22:18:27.410 UTC: %SSH-5-SSH2_USERAUTH: User 'lab' authentication for SSH2 Session
from 10.0.2.2 (tty = 0) using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' Succeeded
<189>215: 000211: *Sep 7 22:18:27.605 UTC: %SYS-5-CONFIG_I: Configured from console by lab on vty0
(10.0.2.2)
<190>216: 000212: *Sep 7 22:18:27.747 UTC: %SYS-6-LOGOUT: User lab has exited tty session 434(10.0.2.2)
<189>217: 000213: *Sep 7 22:18:27.747 UTC: %SSH-5-SSH2_CLOSE: SSH2 Session from 10.0.2.2 (tty = 0) for user
```

```

'' using crypto cipher 'aes128-ctr', hmac 'hmac-sha2-256' closed
<187>218: 000214: *Sep  7 22:19:26.134 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.3 NBMA: 100.64.0.1)
<187>219: 000215: *Sep  7 22:19:26.227 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.2 NBMA: 100.64.0.1)
<187>220: 000216: *Sep  7 22:19:26.906 UTC: %DMVPN-3-DMVPN_NHRP_ERROR: Tunnel0: Recieved wrong
authentication string for Registration Request , Reason: authentication failure (11) on (Tunnel:
172.20.0.3 NBMA: 100.64.0.1)
... 1098 more lines

```

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

21.09 PASS The Harness Path Still Works (0.1s, 3 commands)

The reason the second permit exists. If this fails the lab is unreachable by every other suite, so it is asserted here rather than discovered in the next run. Asserted from the ACL's own hit counter rather than from "show users". That column prints a resolved name when reverse DNS answers -- inside the packaged appliance the same session shows as "_gateway" instead of 10.0.2.2 -- so matching on the rendered address made this depend on name resolution rather than on the thing being tested. A hit on that ACE means a session was admitted by exactly the permit under discussion.

Setup (suite) Open All Routers, Open Tacacs Server, Open Collector

Acceptance criteria

- `${hits}` is not empty (checked 3×)
- `${hits}[0] > 0` holds (checked 3×)

How it was checked

R1 show ip access-lists VTY-MGMT

```

Standard IP access list VTY-MGMT
 10 permit 192.168.99.0, wildcard bits 0.0.0.255 (6 matches)
 20 permit 10.0.2.0, wildcard bits 0.0.0.255 (186 matches)
 30 deny any log (9 matches)

```

R2 show ip access-lists VTY-MGMT

```

Standard IP access list VTY-MGMT
 10 permit 192.168.99.0, wildcard bits 0.0.0.255
 20 permit 10.0.2.0, wildcard bits 0.0.0.255 (212 matches)
 30 deny any log (3 matches)

```

R3 show ip access-lists VTY-MGMT

```

Standard IP access list VTY-MGMT
 10 permit 192.168.99.0, wildcard bits 0.0.0.255
 20 permit 10.0.2.0, wildcard bits 0.0.0.255 (184 matches)
 30 deny any log (3 matches)

```

Teardown (suite) Close Tacacs Server, Close Collector, Close All Connections

22 Banner

22.01 **PASS** Every Router Has A Login Banner Configured (0.3s, 3 commands)

Setup (suite) Open All Routers

Acceptance criteria

- output contains **banner login** (checked 3×)

How it was checked

R1 `show running-config | include ^banner`
banner login ^C

R2 `show running-config | include ^banner`
banner login ^C

R3 `show running-config | include ^banner`
banner login ^C

Teardown (suite) Close All Connections

22.02 **PASS** The Banner Is Presented Before Authentication (6.2s, 0 commands)

Captured from a login that is refused, so the banner demonstrably reaches an unauthenticated client.

Setup (suite) Open All Routers

Acceptance criteria

- `${banner}` is not empty (checked 3×)

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Close All Connections

22.03 **PASS** The Presented Banner Matches The Source File Exactly (6.3s, 0 commands)

Line for line, not a substring match: a device carrying a stale or truncated copy should fail rather than pass on one memorable phrase still being present.

Setup (suite) Open All Routers

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Close All Connections

22.04 **PASS** The Banner States The Warning It Exists To Give (2.1s, 0 commands)

A banner that does not actually warn is decoration. These are the elements that make it one: restricted access, a statement of monitoring, and consent following from use.

Setup (suite) Open All Routers

Acceptance criteria

- output contains `${phrase}` (checked 4×)
the banner does not state: `${phrase}`

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Close All Connections

22.05 **PASS** The Banner Discloses Nothing About The Platform (6.2s, 0 commands)

An unauthenticated visitor should learn that they are not welcome, and nothing else. A banner naming the vendor, model, software or hostname helps whoever should not be there more than it helps anyone who should.

Setup (suite) Open All Routers

Acceptance criteria none asserted directly — this test captures state for the record, and is checked by the tests that read it

How it was checked no device commands of its own; the assertion read output captured earlier in the suite

Teardown (suite) Close All Connections

22.06 **PASS** The Banner Survives A Configuration Save (0.1s, 3 commands)

Guards the case where a banner is applied to the running configuration and never written -- present until the next reload, and absent exactly when it would be needed.

Setup (suite) Open All Routers

Acceptance criteria

- output contains **banner login** (checked 3×)

How it was checked

R1 `show startup-config | include ^banner`
banner login ^C

R2 `show startup-config | include ^banner`
banner login ^C

R3 `show startup-config | include ^banner`
banner login ^C

Teardown (suite) Close All Connections

Appendix — captured device state

Written by suite *05 Capture State* during the run. Routing tables and protocol state first, then what the NMS sees for each router -- polled over SNMPv3, and received as syslog and traps -- then the full running configuration of each router.

R1 — ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PFR
& - replicated local route overrides by connected

Gateway of last resort is 10.0.2.2 to network 0.0.0.0

```
S* 0.0.0.0/0 [254/0] via 10.0.2.2
10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
C 10.0.2.0/24 is directly connected, GigabitEthernet1
L 10.0.2.15/32 is directly connected, GigabitEthernet1
C 10.20.1.1/32 is directly connected, Loopback1
B 10.20.2.1/32 [20/0] via 172.20.0.2, 00:03:08
B 10.20.3.1/32 [20/0] via 172.20.0.3, 00:15:29
S 10.30.1.0/24 is directly connected, Null0
B 10.30.2.0/24 [20/0] via 172.20.0.2, 00:03:08
B 10.30.3.0/24 [20/0] via 172.20.0.3, 00:15:29
100.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 100.64.0.0/24 is directly connected, GigabitEthernet2
L 100.64.0.1/32 is directly connected, GigabitEthernet2
172.16.0.0/32 is subnetted, 1 subnets
C 172.16.1.1 is directly connected, Loopback0
172.20.0.0/16 is variably subnetted, 2 subnets, 2 masks
C 172.20.0.0/24 is directly connected, Tunnel0
L 172.20.0.1/32 is directly connected, Tunnel0
192.168.10.0/24 is variably subnetted, 2 subnets, 2 masks
C 192.168.10.0/24 is directly connected, GigabitEthernet3
L 192.168.10.1/32 is directly connected, GigabitEthernet3
B 192.168.20.0/24 [20/0] via 172.20.0.2, 00:03:08
B 192.168.30.0/24 [20/0] via 172.20.0.3, 00:15:29
```

R2 — ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PFR
& - replicated local route overrides by connected

Gateway of last resort is 10.0.2.2 to network 0.0.0.0

```
S* 0.0.0.0/0 [254/0] via 10.0.2.2
10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
C 10.0.2.0/24 is directly connected, GigabitEthernet1
L 10.0.2.15/32 is directly connected, GigabitEthernet1
B 10.20.1.1/32 [20/0] via 172.20.0.1, 00:03:09
C 10.20.2.1/32 is directly connected, Loopback1
B 10.20.3.1/32 [20/0] via 172.20.0.3, 00:03:09
B 10.30.1.0/24 [20/0] via 172.20.0.1, 00:03:09
S 10.30.2.0/24 is directly connected, Null0
B 10.30.3.0/24 [20/0] via 172.20.0.3, 00:03:09
100.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 100.64.0.0/24 is directly connected, GigabitEthernet2
L 100.64.0.2/32 is directly connected, GigabitEthernet2
172.16.0.0/32 is subnetted, 1 subnets
```

```

C      172.16.2.1 is directly connected, Loopback0
      172.20.0.0/16 is variably subnetted, 2 subnets, 2 masks
C      172.20.0.0/24 is directly connected, Tunnel0
L      172.20.0.2/32 is directly connected, Tunnel0
B      192.168.10.0/24 [20/0] via 172.20.0.1, 00:03:09
      192.168.20.0/24 is variably subnetted, 2 subnets, 2 masks
C      192.168.20.0/24 is directly connected, GigabitEthernet3
L      192.168.20.1/32 is directly connected, GigabitEthernet3
B      192.168.30.0/24 [20/0] via 172.20.0.3, 00:03:09

```

R3 — ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
H - NHRP, G - NHRP registered, g - NHRP registration summary
o - ODR, P - periodic downloaded static route, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from Pfr
& - replicated local route overrides by connected

Gateway of last resort is 10.0.2.2 to network 0.0.0.0

```

S*    0.0.0.0/0 [254/0] via 10.0.2.2
      10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
C      10.0.2.0/24 is directly connected, GigabitEthernet1
L      10.0.2.15/32 is directly connected, GigabitEthernet1
B      10.20.1.1/32 [20/0] via 172.20.0.1, 00:15:29
B      10.20.2.1/32 [20/0] via 172.20.0.2, 00:02:46
C      10.20.3.1/32 is directly connected, Loopback1
B      10.30.1.0/24 [20/0] via 172.20.0.1, 00:15:29
B      10.30.2.0/24 [20/0] via 172.20.0.2, 00:02:46
S      10.30.3.0/24 is directly connected, Null0
      100.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      100.64.0.0/24 is directly connected, GigabitEthernet2
L      100.64.0.3/32 is directly connected, GigabitEthernet2
      172.16.0.0/32 is subnetted, 1 subnets
C      172.16.3.1 is directly connected, Loopback0
      172.20.0.0/16 is variably subnetted, 2 subnets, 2 masks
C      172.20.0.0/24 is directly connected, Tunnel0
L      172.20.0.3/32 is directly connected, Tunnel0
B      192.168.10.0/24 [20/0] via 172.20.0.1, 00:15:29
B      192.168.20.0/24 [20/0] via 172.20.0.2, 00:02:46
      192.168.30.0/24 is variably subnetted, 2 subnets, 2 masks
C      192.168.30.0/24 is directly connected, GigabitEthernet3
L      192.168.30.1/32 is directly connected, GigabitEthernet3

```

R1 — bgp summary

BGP router identifier 172.16.1.1, local AS number 65001
BGP table version is 28, main routing table version 28
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 48 bytes of memory
6 BGP community entries using 144 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5720 total bytes of memory
BGP activity 136/127 prefixes, 139/130 paths, scan interval 60 secs
22 networks peaked at 22:33:59 Sep 7 2026 UTC (00:48:55.594 ago)

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
172.20.0.2	4	65002	26	29	28	0	0	00:03:08	3
172.20.0.3	4	65003	106	115	28	0	0	00:15:40	3

R2 — bgp summary

BGP router identifier 172.16.2.1, local AS number 65002
BGP table version is 46, main routing table version 46
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory

2 BGP AS-PATH entries using 64 bytes of memory
6 BGP community entries using 144 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5736 total bytes of memory
BGP activity 160/151 prefixes, 162/153 paths, scan interval 60 secs
31 networks peaked at 22:34:42 Sep 7 2026 UTC (00:48:12.674 ago)

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
172.20.0.1	4	65001	29	26	46	0	0	00:03:08	6

R3 — bgp summary

BGP router identifier 172.16.3.1, local AS number 65003
BGP table version is 146, main routing table version 146
9 network entries using 2232 bytes of memory
9 path entries using 1224 bytes of memory
7/7 BGP path/bestpath attribute entries using 2072 bytes of memory
2 BGP AS-PATH entries using 64 bytes of memory
6 BGP community entries using 144 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 5736 total bytes of memory
BGP activity 72/63 prefixes, 77/68 paths, scan interval 60 secs
9 networks peaked at 22:15:22 Sep 7 2026 UTC (01:07:32.746 ago)

Neighbor	V	AS	MsgRcvd	MsgSent	TblVer	InQ	OutQ	Up/Down	State/PfxRcd
172.20.0.1	4	65001	115	106	146	0	0	00:15:41	6

R1 — bgp table

BGP table version is 28, local router ID is 172.16.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 10.20.1.1/32	0.0.0.0	0		32768	i
*> 10.20.2.1/32	172.20.0.2	0		0	65002 i
*> 10.20.3.1/32	172.20.0.3	0		0	65003 i
*> 10.30.1.0/24	0.0.0.0	0		32768	i
*> 10.30.2.0/24	172.20.0.2	0		0	65002 i
*> 10.30.3.0/24	172.20.0.3	0		0	65003 i
*> 192.168.10.0	0.0.0.0	0		32768	i
*> 192.168.20.0	172.20.0.2	0		0	65002 i
*> 192.168.30.0	172.20.0.3	0		0	65003 i

R2 — bgp table

BGP table version is 46, local router ID is 172.16.2.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-stale,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

Network	Next Hop	Metric	LocPrf	Weight	Path
*> 10.20.1.1/32	172.20.0.1	0		0	65001 i
*> 10.20.2.1/32	0.0.0.0	0		32768	i
*> 10.20.3.1/32	172.20.0.3	0		0	65001 65003 i
*> 10.30.1.0/24	172.20.0.1	0		0	65001 i
*> 10.30.2.0/24	0.0.0.0	0		32768	i
*> 10.30.3.0/24	172.20.0.3	0		0	65001 65003 i
*> 192.168.10.0	172.20.0.1	0		0	65001 i
*> 192.168.20.0	0.0.0.0	0		32768	i
*> 192.168.30.0	172.20.0.3	0		0	65001 65003 i

R3 — bgp table

BGP table version is 146, local router ID is 172.16.3.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,

```

r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
x best-external, a additional-path, c RIB-compressed,
t secondary path, L long-lived-state,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found

```

	Network	Next Hop	Metric	LocPrf	Weight	Path
*>	10.20.1.1/32	172.20.0.1	0	0	65001	i
*>	10.20.2.1/32	172.20.0.2		0	65001	65002 i
*>	10.20.3.1/32	0.0.0.0	0	32768	i	
*>	10.30.1.0/24	172.20.0.1	0	0	65001	i
*>	10.30.2.0/24	172.20.0.2		0	65001	65002 i
*>	10.30.3.0/24	0.0.0.0	0	32768	i	
*>	192.168.10.0	172.20.0.1	0	0	65001	i
*>	192.168.20.0	172.20.0.2		0	65001	65002 i
*>	192.168.30.0	0.0.0.0	0	32768	i	

R1 — crypto ikev2 sa

IPv4 Crypto IKEv2 SA

Tunnel-id	Local	Remote	fvr/f/ivrf	Status
1	100.64.0.1/500	100.64.0.2/500	none/none	READY
Encr: AES-CBC, keysize: 256, PRF: SHA256, Hash: SHA256, DH Grp:14, Auth sign: PSK, Auth verify: PSK				
Life/Active Time: 86400/100 sec				
CE id: 1029, Session-id: 26				
Local spi: 674CC240C9A38803 Remote spi: 6B960B9A3952A45C				

Tunnel-id	Local	Remote	fvr/f/ivrf	Status
2	100.64.0.1/500	100.64.0.3/500	none/none	READY
Encr: AES-CBC, keysize: 256, PRF: SHA256, Hash: SHA256, DH Grp:14, Auth sign: PSK, Auth verify: PSK				
Life/Active Time: 86400/100 sec				
CE id: 1030, Session-id: 27				
Local spi: C7ABC0CAC6503940 Remote spi: 54006597FF55CAD2				

IPv6 Crypto IKEv2 SA

R2 — crypto ikev2 sa

IPv4 Crypto IKEv2 SA

Tunnel-id	Local	Remote	fvr/f/ivrf	Status
1	100.64.0.2/500	100.64.0.1/500	none/none	READY
Encr: AES-CBC, keysize: 256, PRF: SHA256, Hash: SHA256, DH Grp:14, Auth sign: PSK, Auth verify: PSK				
Life/Active Time: 86400/101 sec				
CE id: 1029, Session-id: 24				
Local spi: 6B960B9A3952A45C Remote spi: 674CC240C9A38803				

IPv6 Crypto IKEv2 SA

R3 — crypto ikev2 sa

IPv4 Crypto IKEv2 SA

Tunnel-id	Local	Remote	fvr/f/ivrf	Status
1	100.64.0.3/500	100.64.0.1/500	none/none	READY
Encr: AES-CBC, keysize: 256, PRF: SHA256, Hash: SHA256, DH Grp:14, Auth sign: PSK, Auth verify: PSK				
Life/Active Time: 86400/101 sec				
CE id: 1026, Session-id: 26				
Local spi: 54006597FF55CAD2 Remote spi: C7ABC0CAC6503940				

IPv6 Crypto IKEv2 SA

H1 — ip addr

```

1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue qlen 1000
   link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
   inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
   inet6 ::1/128 scope host
       valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
   link/ether 52:54:00:aa:01:01 brd ff:ff:ff:ff:ff:ff
   inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0
       valid_lft 82334sec preferred_lft 71534sec

```

```

inet6 fec0::5054:ff:feaa:101/64 scope site dynamic noprefixroute flags 100
    valid_lft 86212sec preferred_lft 14212sec
inet6 fe80::5054:ff:feaa:101/64 scope link
    valid_lft forever preferred_lft forever
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:01:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.10.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.229.55/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.12/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.13/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.14/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.15/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.16/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.17/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.18/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.19/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.64/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.65/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.66/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.67/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.68/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.69/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.70/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.71/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.72/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.73/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.74/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.75/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.76/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.77/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.78/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.79/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.80/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.81/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.82/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.83/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.84/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.85/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.86/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.87/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.88/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.89/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.10.90/24 scope global secondary eth1

```

```

    valid_lft forever preferred_lft forever
inet 192.168.10.91/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.10.92/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.10.93/24 scope global secondary eth1
    valid_lft forever preferred_lft forever

```

H1 — ip route

```

default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.10.1 dev eth1
169.254.0.0/16 dev eth1 scope link src 169.254.229.55 metric 1003
192.168.10.0/24 dev eth1 scope link src 192.168.10.10
192.168.20.0/24 via 192.168.10.1 dev eth1
192.168.30.0/24 via 192.168.10.1 dev eth1

```

H2 — ip addr

```

1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:02:01 brd ff:ff:ff:ff:ff:ff
    inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0
        valid_lft 82337sec preferred_lft 71537sec
    inet6 fec0::5054:ff:feaa:201/64 scope site dynamic noprefixroute flags 100
        valid_lft 86083sec preferred_lft 14083sec
    inet6 fe80::5054:ff:feaa:201/64 scope link
        valid_lft forever preferred_lft forever
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:02:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.20.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.199.41/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.12/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.13/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.14/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.15/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.16/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.17/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.18/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.19/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.64/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.65/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.66/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.67/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.68/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.69/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.70/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.71/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.72/24 scope global secondary eth1
        valid_lft forever preferred_lft forever
    inet 192.168.20.73/24 scope global secondary eth1
        valid_lft forever preferred_lft forever

```

```

inet 192.168.20.74/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.75/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.76/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.77/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.78/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.79/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.80/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.81/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.82/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.83/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.84/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.85/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.86/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.87/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.88/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.89/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.90/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.91/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.92/24 scope global secondary eth1
    valid_lft forever preferred_lft forever
inet 192.168.20.93/24 scope global secondary eth1
    valid_lft forever preferred_lft forever

```

H2 — ip route

```

default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.20.1 dev eth1
192.168.30.10 via 192.168.20.1 dev eth1
169.254.0.0/16 dev eth1 scope link src 169.254.199.41 metric 1003
192.168.10.0/24 via 192.168.20.1 dev eth1
192.168.30.10 via 192.168.20.1 dev eth1
192.168.20.0/24 dev eth1 scope link src 192.168.20.10
192.168.30.0/24 via 192.168.20.1 dev eth1
192.168.30.10 via 192.168.20.1 dev eth1

```

H3 — ip addr

```

1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:03:01 brd ff:ff:ff:ff:ff:ff
    inet 10.0.2.15/24 brd 10.0.2.255 scope global dynamic noprefixroute eth0
        valid_lft 82336sec preferred_lft 71536sec
    inet6 fec0::5054:ff:feaa:301/64 scope site dynamic noprefixroute flags 100
        valid_lft 86292sec preferred_lft 14292sec
    inet6 fe80::5054:ff:feaa:301/64 scope link
        valid_lft forever preferred_lft forever
3: eth1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 52:54:00:aa:03:02 brd ff:ff:ff:ff:ff:ff
    inet 192.168.30.10/24 scope global eth1
        valid_lft forever preferred_lft forever
    inet 169.254.207.242/16 brd 169.254.255.255 scope global noprefixroute eth1
        valid_lft forever preferred_lft forever
    inet 192.168.30.11/24 scope global secondary eth1
        valid_lft forever preferred_lft forever

```

[illegible]

H3 — ip route

```
default via 10.0.2.2 dev eth0 src 10.0.2.15 metric 1002
```

```
10.0.2.0/24 dev eth0 scope link src 10.0.2.15 metric 1002
10.30.0.0/16 via 192.168.30.1 dev eth1
169.254.0.0/16 dev eth1 scope link src 169.254.207.242 metric 1003
192.168.10.0/24 via 192.168.30.1 dev eth1
192.168.20.0/24 via 192.168.30.1 dev eth1
192.168.30.0/24 dev eth1 scope link src 192.168.30.10
```

NMS — network

```
lo UNKNOWN 127.0.0.1/8 ::1/128
ens3 UP 10.0.2.15/24 metric 100 fec0::5054:ff:febb:101/64 fe80::5054:ff:febb:101/64
ens4 UP 192.168.10.20/24 fe80::5054:ff:febb:102/64
ens5 UP 192.168.99.10/24 fe80::5054:ff:febb:103/64
default via 10.0.2.2 dev ens3 proto dhcp src 10.0.2.15 metric 100
10.0.2.0/24 dev ens3 proto kernel scope link src 10.0.2.15 metric 100
10.0.2.2 dev ens3 proto dhcp scope link src 10.0.2.15 metric 100
10.0.2.3 dev ens3 proto dhcp scope link src 10.0.2.15 metric 100
10.30.0.0/16 via 192.168.10.1 dev ens4
192.168.10.0/24 dev ens4 proto kernel scope link src 192.168.10.20
192.168.20.0/24 via 192.168.10.1 dev ens4
192.168.30.0/24 via 192.168.10.1 dev ens4
192.168.99.0/24 dev ens5 proto kernel scope link src 192.168.99.10
```

NMS — snmp version

NET-SNMP version: 5.9.4.pre2

NMS — collectors

active
active
active

NMS — collector files

```
total 2660
-rw-r--r-- 1 syslog syslog 128123 Sep 7 23:22 192.168.99.1.log
-rw-r--r-- 1 syslog syslog 159924 Sep 7 23:22 192.168.99.2.log
-rw-r--r-- 1 syslog syslog 105045 Sep 7 23:22 192.168.99.3.log
-rw-r--r-- 1 root root 881546 Sep 7 23:22 snmptrapd.log
-rw-r--r-- 1 root root 1416130 Sep 7 23:22 traps-raw.log
```

NMS — R1 syslog received

tail: cannot open '/var/log/lab/192.168.10.1.log' for reading: No such file or directory

NMS — R2 syslog received

tail: cannot open '/var/log/lab/192.168.20.1.log' for reading: No such file or directory

NMS — R3 syslog received

tail: cannot open '/var/log/lab/192.168.30.1.log' for reading: No such file or directory

NMS — snmptrapd

```
2026-09-07 23:22:26 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:39.57 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.7
iso.3.6.1.4.1.9.9.171.1.3.2.1.9.29 3600 iso.3.6.1.4.1.9.9.171.1.3.2.1.8.29 4608000
iso.3.6.1.4.1.9.9.171.1.3.3.1.3.29.1 1 iso.3.6.1.4.1.9.9.171.1.3.3.1.4.29.1 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.5.29.1 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.3.3.1.9.29.1 1
iso.3.6.1.4.1.9.9.171.1.3.3.1.10.29.1 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.3.3.1.11.29.1 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.6.29.1 47 iso.3.6.1.4.1.9.9.171.1.3.3.1.7.29.1 0
2026-09-07 23:22:26 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:40.66 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.7
iso.3.6.1.4.1.9.9.171.1.3.2.1.9.29 3600 iso.3.6.1.4.1.9.9.171.1.3.2.1.8.29 4608000
iso.3.6.1.4.1.9.9.171.1.3.3.1.3.29.1 1 iso.3.6.1.4.1.9.9.171.1.3.3.1.4.29.1 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.3.3.1.5.29.1 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.3.3.1.9.29.1 1
iso.3.6.1.4.1.9.9.171.1.3.3.1.10.29.1 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.3.3.1.11.29.1 "64 40 00 03 "
```

iso.3.6.1.4.1.9.9.171.1.3.3.1.6.29.1 47 iso.3.6.1.4.1.9.9.171.1.3.3.1.7.29.1 0
2026-09-07 23:22:27 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:40.41 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.137.0.1
iso.3.6.1.4.1.9.10.137.1.2.1.8.1708049 0 iso.3.6.1.4.1.9.10.137.1.2.1.8.1708049 0
iso.3.6.1.2.1.2.2.1.1.8 8
2026-09-07 23:22:27 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.50 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.137.0.1
iso.3.6.1.4.1.9.10.137.1.2.1.8.1708035 0 iso.3.6.1.4.1.9.10.137.1.2.1.8.1708035 0
iso.3.6.1.2.1.2.2.1.1.8 8
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.80 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.62.2.0.4
iso.3.6.1.4.1.9.10.62.1.2.3.1.1.2.14.84.117.110.110.101.108.48.45.104.101.97.100.45.48 3
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.71 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.2
iso.3.6.1.4.1.9.9.171.1.2.2.1.6.1.4.100.64.0.3.1.4.100.64.0.2.29 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.2.2.1.7.1.4.100.64.0.3.1.4.100.64.0.2.29 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.2.3.1.1.6.29 2 iso.3.6.1.4.1.9.9.171.1.4.2.1.1.2.29 4
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.80 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.8
iso.3.6.1.4.1.9.9.171.1.3.2.1.1.10.29 213 iso.3.6.1.4.1.9.9.171.1.4.3.1.1.12.28 213
iso.3.6.1.4.1.9.9.171.1.4.3.1.1.10.28 3600 iso.3.6.1.4.1.9.9.171.1.4.3.1.1.9.28 4608000
iso.3.6.1.4.1.9.9.171.1.4.3.1.1.2.28 1 iso.3.6.1.4.1.9.9.171.1.4.3.2.1.5.28 1
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.11.28 1 iso.3.6.1.4.1.9.9.171.1.4.3.2.1.6.28 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.7.28 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.4.3.2.1.12.28 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.13.28 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.4.3.2.1.8.28 47
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.9.28 0
2026-09-07 23:22:28 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.72 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.8
iso.3.6.1.4.1.9.9.171.1.3.2.1.10.29 214 iso.3.6.1.4.1.9.9.171.1.4.3.1.1.12.28 214
iso.3.6.1.4.1.9.9.171.1.4.3.1.1.10.28 3600 iso.3.6.1.4.1.9.9.171.1.4.3.1.1.9.28 4608000
iso.3.6.1.4.1.9.9.171.1.4.3.1.1.2.28 1 iso.3.6.1.4.1.9.9.171.1.4.3.2.1.5.28 1
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.11.28 1 iso.3.6.1.4.1.9.9.171.1.4.3.2.1.6.28 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.7.28 "64 40 00 03 " iso.3.6.1.4.1.9.9.171.1.4.3.2.1.12.28 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.13.28 "64 40 00 02 " iso.3.6.1.4.1.9.9.171.1.4.3.2.1.8.28 47
iso.3.6.1.4.1.9.9.171.1.4.3.2.1.9.28 0
2026-09-07 23:22:29 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.80 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.137.0.2
iso.3.6.1.4.1.9.10.137.1.2.1.8.987139 3 iso.3.6.1.4.1.9.10.137.1.2.1.8.987139 3 iso.3.6.1.2.1.2.2.1.1.8 8
2026-09-07 23:22:29 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.72 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.62.2.0.4
iso.3.6.1.4.1.9.10.62.1.2.3.1.1.2.14.84.117.110.110.101.108.48.45.104.101.97.100.45.48 3
2026-09-07 23:22:29 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.81 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.171.2.0.2
iso.3.6.1.4.1.9.9.171.1.2.2.1.6.1.4.100.64.0.2.1.4.100.64.0.3.29 "64 40 00 02 "
iso.3.6.1.4.1.9.9.171.1.2.2.1.7.1.4.100.64.0.2.1.4.100.64.0.3.29 "64 40 00 03 "
iso.3.6.1.4.1.9.9.171.1.2.3.1.16.29 2 iso.3.6.1.4.1.9.9.171.1.4.2.1.1.2.29 6
2026-09-07 23:22:29 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:41.72 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.10.137.0.2
iso.3.6.1.4.1.9.10.137.1.2.1.8.987153 3 iso.3.6.1.4.1.9.10.137.1.2.1.8.987153 3 iso.3.6.1.2.1.2.2.1.1.8 8
2026-09-07 23:22:29 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:43.64 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.41.2.0.1
iso.3.6.1.4.1.9.9.41.1.2.3.1.2.59 "DMVPN" iso.3.6.1.4.1.9.9.41.1.2.3.1.3.59 4
iso.3.6.1.4.1.9.9.41.1.2.3.1.4.59 "DMVPN_NHRP_ERROR" iso.3.6.1.4.1.9.9.41.1.2.3.1.5.59 " Tunnel0: NHRP
Encap Error for Purge Reply , Reason: protocol generic error (7) on (Tunnel: 172.20.0.2 NBMA: 100.64.0.2)"
iso.3.6.1.4.1.9.9.41.1.2.3.1.6.59 0:1:08:43.64
2026-09-07 23:22:29 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:42.55 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.41.2.0.1
iso.3.6.1.4.1.9.9.41.1.2.3.1.2.50 "DMVPN" iso.3.6.1.4.1.9.9.41.1.2.3.1.3.50 4
iso.3.6.1.4.1.9.9.41.1.2.3.1.4.50 "DMVPN_NHRP_ERROR" iso.3.6.1.4.1.9.9.41.1.2.3.1.5.50 " Tunnel0: NHRP
Encap Error for Purge Request , Reason: protocol generic error (7) on (Tunnel: 172.20.0.3 NBMA:
100.64.0.3)" iso.3.6.1.4.1.9.9.41.1.2.3.1.6.50 0:1:08:42.55
2026-09-07 23:22:38 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:52.91 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.0.1
iso.3.6.1.4.1.9.2.9.3.1.1.435.1 6 iso.3.6.1.2.1.6.13.1.1.10.0.2.15.22.10.0.2.2.57102 8
iso.3.6.1.4.1.9.2.6.1.1.5.10.0.2.15.22.10.0.2.2.57102 3555
iso.3.6.1.4.1.9.2.6.1.1.1.10.0.2.15.22.10.0.2.2.57102 3504
iso.3.6.1.4.1.9.2.6.1.1.2.10.0.2.15.22.10.0.2.2.57102 52339 iso.3.6.1.4.1.9.2.9.2.1.18.435 "lab"
2026-09-07 23:22:38 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:51.84 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.0.1
iso.3.6.1.4.1.9.2.9.3.1.1.434.1 6 iso.3.6.1.2.1.6.13.1.1.10.0.2.15.22.10.0.2.2.55618 8
iso.3.6.1.4.1.9.2.6.1.1.5.10.0.2.15.22.10.0.2.2.55618 3547
iso.3.6.1.4.1.9.2.6.1.1.1.10.0.2.15.22.10.0.2.2.55618 2784
iso.3.6.1.4.1.9.2.6.1.1.2.10.0.2.15.22.10.0.2.2.55618 29731 iso.3.6.1.4.1.9.2.9.2.1.18.434 "lab"
2026-09-07 23:22:38 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:52.21 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.0.1
iso.3.6.1.4.1.9.2.9.3.1.1.435.1 6 iso.3.6.1.2.1.6.13.1.1.10.0.2.15.22.10.0.2.2.36348 8
iso.3.6.1.4.1.9.2.6.1.1.5.10.0.2.15.22.10.0.2.2.36348 3571
iso.3.6.1.4.1.9.2.6.1.1.1.10.0.2.15.22.10.0.2.2.36348 2688
iso.3.6.1.4.1.9.2.6.1.1.2.10.0.2.15.22.10.0.2.2.36348 28707 iso.3.6.1.4.1.9.2.9.2.1.18.435 "lab"
2026-09-07 23:22:41 <UNKNOWN> [UDP: [192.168.99.1]:54980->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:08:55.08 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1

```

iso.3.6.1.4.1.9.9.43.1.1.6.1.3.174 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.174 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.174 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.174 "lab"
2026-09-07 23:22:46 <UNKNOWN> [UDP: [192.168.99.2]:49602->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:09:00.46 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.387 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.387 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.387 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.387 "lab"
2026-09-07 23:22:50 <UNKNOWN> [UDP: [192.168.99.3]:50049->[192.168.99.10]:162]:
iso.3.6.1.2.1.1.3.0 0:1:09:03.74 iso.3.6.1.6.3.1.1.4.1.0 iso.3.6.1.4.1.9.9.43.2.0.1
iso.3.6.1.4.1.9.9.43.1.1.6.1.3.127 1 iso.3.6.1.4.1.9.9.43.1.1.6.1.4.127 3
iso.3.6.1.4.1.9.9.43.1.1.6.1.5.127 2 iso.3.6.1.4.1.9.9.43.1.1.6.1.8.127 "lab"

```

NMS — R1 polled over SNMPv3: snmp system

```

.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (415000) 1:09:10.00
.1.3.6.1.2.1.1.4.0 = ""
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r1.lab.local"
.1.3.6.1.2.1.1.6.0 = ""
.1.3.6.1.2.1.1.7.0 = INTEGER: 78
.1.3.6.1.2.1.1.8.0 = Timeticks: (0) 0:00:00.00

```

NMS — R1 polled over SNMPv3: snmp interfaces

```

.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"

```

NMS — R2 polled over SNMPv3: snmp system

```

.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (415086) 1:09:10.86
.1.3.6.1.2.1.1.4.0 = ""
.1.3.6.1.2.1.1.5.0 = STRING: "c8000v-r2.lab.local"
.1.3.6.1.2.1.1.6.0 = ""
.1.3.6.1.2.1.1.7.0 = INTEGER: 78
.1.3.6.1.2.1.1.8.0 = Timeticks: (0) 0:00:00.00

```

NMS — R2 polled over SNMPv3: snmp interfaces

```

.1.3.6.1.2.1.2.2.1.2.1 = STRING: "GigabitEthernet1"
.1.3.6.1.2.1.2.2.1.2.2 = STRING: "GigabitEthernet2"
.1.3.6.1.2.1.2.2.1.2.3 = STRING: "GigabitEthernet3"
.1.3.6.1.2.1.2.2.1.2.4 = STRING: "GigabitEthernet4"
.1.3.6.1.2.1.2.2.1.2.5 = STRING: "VoIP-Null0"
.1.3.6.1.2.1.2.2.1.2.6 = STRING: "Null0"
.1.3.6.1.2.1.2.2.1.2.7 = STRING: "Loopback0"
.1.3.6.1.2.1.2.2.1.2.8 = STRING: "Tunnel0"
.1.3.6.1.2.1.2.2.1.2.9 = STRING: "Loopback1"

```

NMS — R3 polled over SNMPv3: snmp system

```

.1.3.6.1.2.1.1.1.0 = STRING: "Cisco IOS Software [IOSXE], Virtual XE Software (X86_64_LINUX_IOSD-
UNIVERSALK9-M), Version 17.15.6, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2026 by Cisco Systems, Inc.
Compiled Wed 22-Jul-26 03:39 b"
.1.3.6.1.2.1.1.2.0 = OID: .1.3.6.1.4.1.9.1.3004
.1.3.6.1.2.1.1.3.0 = Timeticks: (414990) 1:09:09.90

```

NMS — R3 polled over SNMPv3: snmp interfaces

R1 — running config

3000V IPsec Testbed - test evidence

C8000V IPsec Testbed - test evidence

```

604EDCDE FF4FED2B 77FC460E CD636FDB DD44681E 3A5673AB 9093D3B1 6C9E3D8B
D98987BF E40CBD9E 1AECA0C2 2189BB5C 8FA85686 CD98B646 5575B146 8DFC66A8
467A3DF4 4D565700 6ADF0F0D CF835015 3C04FF7C 21E878AC 11BA9CD2 55A9232C
7CA7B7E6 C1AF74F6 152E99B7 B1FCF9BB E973DE7F 5BDDEB86 C71E3B49 1765308B
5FB0DA06 B92AFE7F 494E8A9E 07B85737 F3A58BE1 1A48A229 C37C1E69 39F08678
80DDCD16 D6BACECA EEBC7CF9 8428787B 35202CDC 60E4616A B623CDBD 230E3AFB
418616A9 4093E049 4D10AB75 27E86F73 932E35B5 8862FDAE 0275156F 719BB2F0
D697DF7F 28
quit
!
!
!
!
!
!
!
!
!
license udi pid C8000V sn 9VRWIY571LW
license boot level network-premier addon dna-premier
memory free low-watermark processor 31774
diagnostic bootstrap level minimal
!
!
spanning-tree extend system-id
!
!
enable secret 9 $9$uia9E1anibovxE$Qyklcz.SLvH8epz2w2TjV6d9TggTO3p9KSxEGgTTD2
username lab privilege 15 secret 9 $9$kSVY7W/rHjFg0.$AdIeocLbIuwaSOCYSowG0l/6LNagQ58URyynu0Dbtq6
!
redundancy
!
!
!
crypto ikev2 proposal LAB-PROP
 encryption aes-cbc-256
 integrity sha256
 group 14
!
crypto ikev2 policy LAB-POL
 proposal LAB-PROP
!
crypto ikev2 keyring LAB-KR
 peer ANY
 address 0.0.0.0 0.0.0.0
 pre-shared-key LabPreSharedKey123
!
!
!
crypto ikev2 profile LAB-PROF
 match identity remote address 0.0.0.0
 authentication remote pre-share
 authentication local pre-share
 keyring local LAB-KR
!
!
!
!
!
!
!
!
!
!
crypto ipsec transform-set LAB-TS esp-aes 256 esp-sha256-hmac
 mode transport
!
crypto ipsec profile LAB-IPSEC
 set transform-set LAB-TS
 set ikev2-profile LAB-PROF
!
!
!
!
!
!
```

```

!
!
!
interface Loopback0
  description Protected endpoint
  ip address 172.16.1.1 255.255.255.255
!
interface Loopback1
  description BGP-advertised prefix
  ip address 10.20.1.1 255.255.255.255
!
interface Tunnel0
  description DMVPN hub
  ip address 172.20.0.1 255.255.255.0
  no ip redirects
  ip nat outside
  ip nhrp authentication LabNhrp
  ip nhrp network-id 100
  ip nhrp holdtime 300
  ip nhrp redirect
  ip tcp adjust-mss 1360
  bfd interval 500 min_rx 500 multiplier 3
  tunnel source GigabitEthernet2
  tunnel mode gre multipoint
  tunnel key 100
  tunnel protection ipsec profile LAB-IPSEC
!
interface GigabitEthernet1
  description MGMT - QEMU user-mode net (DHCP)
  ip address dhcp
  negotiation auto
!
interface GigabitEthernet2
  description WAN - shared provider segment, DMVPN underlay
  ip address 100.64.0.1 255.255.255.0
  negotiation auto
!
interface GigabitEthernet3
  description LAN toward the local host
  ip address 192.168.10.1 255.255.255.0
  ip nat inside
  negotiation auto
!
interface GigabitEthernet4
  description OOB management - NTP, syslog, SNMP
  vrf forwarding MGMT
  ip address 192.168.99.1 255.255.255.0
  negotiation auto
!
router bgp 65001
  bgp router-id 172.16.1.1
  bgp log-neighbor-changes
  neighbor 172.20.0.2 remote-as 65002
  neighbor 172.20.0.2 password LabBgpSecret
  neighbor 172.20.0.2 timers 10 30
  neighbor 172.20.0.2 fall-over bfd
  neighbor 172.20.0.3 remote-as 65003
  neighbor 172.20.0.3 password LabBgpSecret
  neighbor 172.20.0.3 timers 10 30
  neighbor 172.20.0.3 fall-over bfd
!
address-family ipv4
  network 10.20.1.1 mask 255.255.255.255
  network 10.30.1.0 mask 255.255.255.0
  network 192.168.10.0
  neighbor 172.20.0.2 activate
  neighbor 172.20.0.2 send-community both
  neighbor 172.20.0.2 route-map RM-IN-R2 in
  neighbor 172.20.0.2 route-map RM-OUT-R2 out
  neighbor 172.20.0.2 maximum-prefix 15 80
  neighbor 172.20.0.3 activate
  neighbor 172.20.0.3 send-community both
  neighbor 172.20.0.3 route-map RM-IN-R3 in
  neighbor 172.20.0.3 route-map RM-OUT-R3 out
  neighbor 172.20.0.3 maximum-prefix 15 80
exit-address-family
!
ip forward-protocol nd
!
ip bgp-community new-format
ip community-list standard CL-VALID permit 65001:1

```

```

ip community-list standard CL-VALID permit 65001:2
ip community-list standard CL-VALID permit 65001:3
ip community-list standard CL-VALID permit 65002:1
ip community-list standard CL-VALID permit 65002:2
ip community-list standard CL-VALID permit 65002:3
ip community-list standard CL-VALID permit 65003:1
ip community-list standard CL-VALID permit 65003:2
ip community-list standard CL-VALID permit 65003:3
ip as-path access-list 10 permit ^65002$
ip as-path access-list 20 permit ^65003$
no ip http server
ip http secure-server
ip route 10.30.1.0 255.255.255.0 Null0
ip nat pool SITE-POOL 10.30.1.100 10.30.1.129 prefix-length 24
ip nat inside source static 192.168.10.10 10.30.1.10 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.11 10.30.1.11 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.12 10.30.1.12 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.13 10.30.1.13 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.14 10.30.1.14 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.15 10.30.1.15 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.16 10.30.1.16 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.17 10.30.1.17 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.18 10.30.1.18 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.10.19 10.30.1.19 route-map NAT-TO-DOMAIN
ip nat inside source list NAT-POOL-SRC pool SITE-POOL
ip ssh bulk-mode 131072
ip ssh server algorithm authentication password
!
ip prefix-list PL-FAR-R2 seq 40 permit 10.20.2.1/32
ip prefix-list PL-FAR-R2 seq 45 permit 10.30.2.0/24
ip prefix-list PL-FAR-R2 seq 50 permit 192.168.20.0/24
!
ip prefix-list PL-FAR-R3 seq 40 permit 10.20.3.1/32
ip prefix-list PL-FAR-R3 seq 45 permit 10.30.3.0/24
ip prefix-list PL-FAR-R3 seq 50 permit 192.168.30.0/24
!
ip prefix-list PL-OWN-LAN seq 5 permit 192.168.10.0/24
!
ip prefix-list PL-OWN-L0 seq 5 permit 10.20.1.1/32
!
ip prefix-list PL-OWN-NAT seq 5 permit 10.30.1.0/24
!
ip access-list standard VTY-MGMT
 10 remark out-of-band management network
 10 permit 192.168.99.0 0.0.0.255
 20 remark hypervisor user-mode NAT: how the harness reaches these devices
 20 permit 10.0.2.0 0.0.0.255
 30 deny any log
!
ip access-list extended NAT-DOMAIN
 10 permit ip host 192.168.10.10 10.30.0.0 0.0.255.255
 20 permit ip host 192.168.10.11 10.30.0.0 0.0.255.255
 30 permit ip host 192.168.10.12 10.30.0.0 0.0.255.255
 40 permit ip host 192.168.10.13 10.30.0.0 0.0.255.255
 50 permit ip host 192.168.10.14 10.30.0.0 0.0.255.255
 60 permit ip host 192.168.10.15 10.30.0.0 0.0.255.255
 70 permit ip host 192.168.10.16 10.30.0.0 0.0.255.255
 80 permit ip host 192.168.10.17 10.30.0.0 0.0.255.255
 90 permit ip host 192.168.10.18 10.30.0.0 0.0.255.255
100 permit ip host 192.168.10.19 10.30.0.0 0.0.255.255
ip access-list extended NAT-POOL-SRC
 10 permit ip 192.168.10.64 0.0.0.31 10.30.0.0 0.0.255.255
logging source-interface GigabitEthernet4 vrf MGMT
logging host 192.168.99.10 vrf MGMT
route-map RM-OUT-R2 permit 10
  description R1's own L0, tagged 65001:1
  match ip address prefix-list PL-OWN-L0
  set community 65001:1
!
route-map RM-OUT-R2 permit 20
  description R1's own NAT, tagged 65001:2
  match ip address prefix-list PL-OWN-NAT
  set community 65001:2
!
route-map RM-OUT-R2 permit 30
  description R1's own LAN, tagged 65001:3
  match ip address prefix-list PL-OWN-LAN
  set community 65001:3
!
route-map RM-OUT-R2 permit 55
  description re-advertise R3, preserving its communities

```

```

match ip address prefix-list PL-FAR-R3
!
route-map RM-OUT-R3 permit 10
description R1's own LO, tagged 65001:1
match ip address prefix-list PL-OWN-LO
set community 65001:1
!
route-map RM-OUT-R3 permit 20
description R1's own NAT, tagged 65001:2
match ip address prefix-list PL-OWN-NAT
set community 65001:2
!
route-map RM-OUT-R3 permit 30
description R1's own LAN, tagged 65001:3
match ip address prefix-list PL-OWN-LAN
set community 65001:3
!
route-map RM-OUT-R3 permit 55
description re-advertise R2, preserving its communities
match ip address prefix-list PL-FAR-R2
!
route-map NAT-TO-DOMAIN permit 10
match ip address NAT-DOMAIN
!
route-map RM-IN-R2 permit 10
description accept only known communities on an AS path R2 can produce
match as-path 10
match community CL-VALID
!
route-map RM-IN-R3 permit 10
description accept only known communities on an AS path R3 can produce
match as-path 20
match community CL-VALID
!
snmp-server group LABGRP v3 priv read LABVIEW notify LABVIEW
snmp-server view LABVIEW iso included
snmp-server trap-source GigabitEthernet4
snmp-server enable traps snmp authentication linkdown linkup coldstart warmstart
snmp-server enable traps vrrp
snmp-server enable traps flowmon
snmp-server enable traps pfr
snmp-server enable traps ds1
snmp-server enable traps sdwan security policy system omp bfd
snmp-server enable traps entity-perf throughput-notif
snmp-server enable traps call-home message-send-fail server-fail
snmp-server enable traps tty
snmp-server enable traps ospf state-change
snmp-server enable traps ospf errors
snmp-server enable traps ospf retransmit
snmp-server enable traps ospf lsa
snmp-server enable traps ospf cisco-specific state-change nssa-trans-change
snmp-server enable traps ospf cisco-specific state-change shamlink interface
snmp-server enable traps ospf cisco-specific state-change shamlink neighbor
snmp-server enable traps ospf cisco-specific errors
snmp-server enable traps ospf cisco-specific retransmit
snmp-server enable traps ospf cisco-specific lsa
snmp-server enable traps eigrp
snmp-server enable traps casa
snmp-server enable traps xgcp
snmp-server enable traps cef resource-failure peer-state-change peer-fib-state-change inconsistency
snmp-server enable traps smart-license
snmp-server enable traps diameter
snmp-server enable traps entity-qfp mem-res-thresh throughput-notif
snmp-server enable traps entity-state
snmp-server enable traps ethernet cfm cc mep-up mep-down cross-connect loop config
snmp-server enable traps ethernet cfm crosscheck mep-missing mep-unknown service-up
snmp-server enable traps ether-oam
snmp-server enable traps ethernet evc status create delete
snmp-server enable traps aaa_server
snmp-server enable traps config-copy
snmp-server enable traps config
snmp-server enable traps config-ctid
snmp-server enable traps memory bufferpeak
snmp-server enable traps fru-ctrl
snmp-server enable traps entity-sensor
snmp-server enable traps resource-policy
snmp-server enable traps flash insertion removal lowspace
snmp-server enable traps hsrp
snmp-server enable traps entity
snmp-server enable traps ip local pool
snmp-server enable traps cpu threshold

```

```

snmp-server enable traps auth-framework sec-violation
snmp-server enable traps atm subif
snmp-server enable traps frame-relay
snmp-server enable traps frame-relay subif
snmp-server enable traps bgp state-changes all backward-trans limited updown-limited
snmp-server enable traps bgp threshold prefix
snmp-server enable traps bgp cbgp2 state-changes all backward-trans limited updown-limited
snmp-server enable traps bgp cbgp2 threshold prefix
snmp-server enable traps pim neighbor-change rp-mapping-change invalid-pim-message
snmp-server enable traps ipmulticast
snmp-server enable traps msdp
snmp-server enable traps mvpn
snmp-server enable traps rsvp
snmp-server enable traps isis
snmp-server enable traps dhcp
snmp-server enable traps nhrp nhs
snmp-server enable traps nhrp nhc
snmp-server enable traps nhrp nhp
snmp-server enable traps nhrp quota-exceeded
snmp-server enable traps ipsla
snmp-server enable traps bfd
snmp-server enable traps cnpd
snmp-server enable traps event-manager
snmp-server enable traps dlsw
snmp-server enable traps ospfv3 state-change
snmp-server enable traps ospfv3 errors
snmp-server enable traps pppoe
snmp-server enable traps l2tun session
snmp-server enable traps l2tun pseudowire status
snmp-server enable traps l2tun tunnel
snmp-server enable traps pki
snmp-server enable traps pimstdmib neighbor-loss invalid-register invalid-join-prune rp-mapping-change
interface-election
snmp-server enable traps adslline
snmp-server enable traps entity-diag boot-up-fail hm-test-recover hm-thresh-reached scheduled-test-fail
snmp-server enable traps vdsl2line
snmp-server enable traps vtp
snmp-server enable traps vlancreate
snmp-server enable traps vlandelete
snmp-server enable traps port-security
snmp-server enable traps isdn call-information
snmp-server enable traps isdn layer2
snmp-server enable traps isdn chan-not-avail
snmp-server enable traps isdn ietf
snmp-server enable traps c3g
snmp-server enable traps LTE
snmp-server enable traps lisp
snmp-server enable traps firewall serverstatus
snmp-server enable traps ike policy add
snmp-server enable traps ike policy delete
snmp-server enable traps ike tunnel start
snmp-server enable traps ike tunnel stop
snmp-server enable traps ipsec cryptomap add
snmp-server enable traps ipsec cryptomap delete
snmp-server enable traps ipsec cryptomap attach
snmp-server enable traps ipsec cryptomap detach
snmp-server enable traps ipsec tunnel start
snmp-server enable traps ipsec tunnel stop
snmp-server enable traps ipsec too-many-sas
snmp-server enable traps gdoi gm-start-registration
snmp-server enable traps gdoi gm-registration-complete
snmp-server enable traps gdoi gm-re-register
snmp-server enable traps gdoi gm-rekey-rcvd
snmp-server enable traps gdoi gm-rekey-fail
snmp-server enable traps gdoi ks-rekey-pushed
snmp-server enable traps gdoi gm-incomplete-cfg
snmp-server enable traps gdoi ks-no-rsa-keys
snmp-server enable traps gdoi ks-new-registration
snmp-server enable traps gdoi ks-reg-complete
snmp-server enable traps gdoi ks-role-change
snmp-server enable traps gdoi ks-gm-deleted
snmp-server enable traps gdoi ks-peer-reachable
snmp-server enable traps gdoi ks-peer-unreachable
snmp-server enable traps mpls rfc ldp
snmp-server enable traps mpls ldp
snmp-server enable traps mpls rfc traffic-eng
snmp-server enable traps mpls traffic-eng
snmp-server enable traps mpls fast-reroute protected
snmp-server enable traps otn
snmp-server enable traps pw vc
snmp-server enable traps frame-relay multilink bundle-mismatch

```

```

snmp-server enable traps dial
snmp-server enable traps dsp card-status
snmp-server enable traps dsp oper-state
snmp-server enable traps dsp video-usage
snmp-server enable traps dsp video-out-of-resource
snmp-server enable traps syslog
snmp-server enable traps sbc adj-status
snmp-server enable traps sbc blacklist
snmp-server enable traps sbc congestion-alarm
snmp-server enable traps sbc h248-ctrlr-status
snmp-server enable traps sbc media-source
snmp-server enable traps sbc radius-conn-status
snmp-server enable traps sbc sla-violation
snmp-server enable traps sbc sla-violation-rev1
snmp-server enable traps sbc svc-state
snmp-server enable traps sbc qos-statistics
snmp-server enable traps bulkstat collection transfer
snmp-server enable traps ethernet cfm alarm
snmp-server enable traps alarms informational
snmp-server enable traps transceiver all
snmp-server enable traps rf
snmp-server enable traps vrfmib vrf-up vrf-down vnet-trunk-up vnet-trunk-down
snmp-server enable traps ccme
snmp-server enable traps srst
snmp-server enable traps mpls vpn
snmp-server enable traps mpls rfc vpn
snmp-server enable traps voice
snmp-server host 192.168.99.10 vrf MGMT version 3 priv labmon udp-port 1162
snmp-server host 192.168.99.10 vrf MGMT version 3 priv labmon
tacacs server LAB-TAC
  address ipv4 192.168.99.10
  key LabTacacsKey123
!
!
!
!
!
control-plane
!
!
mgcp behavior rsip-range tgcp-only
mgcp behavior comedia-role none
mgcp behavior comedia-check-media-src disable
mgcp behavior comedia-sdp-force disable
!
mgcp profile default
!
!
!
!
!
banner login ^C
*****
                        AUTHORISED ACCESS ONLY

Access to this device is restricted to authorised personnel. If you are not
an authorised user, disconnect now.

All activity is monitored, logged and audited. Continued use of this system
constitutes consent to that monitoring.

Unauthorised access or use may result in disciplinary action and civil or
criminal penalties.
*****
^C
!
line con 0
  exec-timeout 0 0
  activation-character 13
  logging synchronous
  stopbits 1
line aux 0
  activation-character 13
line vty 0 4
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
line vty 5 15
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0

```



```

!
interface Loopback0
description Protected endpoint
ip address 172.16.2.1 255.255.255.255
!
interface Loopback1
description BGP-advertised prefix
ip address 10.20.2.1 255.255.255.255
!
interface Tunnel0
description DMVPN spoke
ip address 172.20.0.2 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
ip tcp adjust-mss 1360
bfd interval 500 min_rx 500 multiplier 3
tunnel source GigabitEthernet2
tunnel mode gre multipoint
tunnel key 100
tunnel protection ipsec profile LAB-IPSEC
!
interface GigabitEthernet1
description MGMT - QEMU user-mode net (DHCP)
ip address dhcp
negotiation auto
!
interface GigabitEthernet2
description WAN - shared provider segment, DMVPN underlay
ip address 100.64.0.2 255.255.255.0
negotiation auto
!
interface GigabitEthernet3
description LAN toward the local host
ip address 192.168.20.1 255.255.255.0
ip nat inside
negotiation auto
!
interface GigabitEthernet4
description OOB management - NTP, syslog, SNMP
vrf forwarding MGMT
ip address 192.168.99.2 255.255.255.0
negotiation auto
!
router bgp 65002
bgp router-id 172.16.2.1
bgp log-neighbor-changes
neighbor 172.20.0.1 remote-as 65001
neighbor 172.20.0.1 password LabBgpSecret
neighbor 172.20.0.1 timers 10 30
neighbor 172.20.0.1 fall-over bfd
!
address-family ipv4
network 10.20.2.1 mask 255.255.255.255
network 10.30.2.0 mask 255.255.255.0
network 192.168.20.0
neighbor 172.20.0.1 activate
neighbor 172.20.0.1 send-community both
neighbor 172.20.0.1 route-map RM-IN-R1 in
neighbor 172.20.0.1 route-map RM-OUT-R1 out
neighbor 172.20.0.1 maximum-prefix 15 80
exit-address-family
!
ip forward-protocol nd
!
ip bgp-community new-format
ip community-list standard CL-VALID permit 65001:1
ip community-list standard CL-VALID permit 65001:2
ip community-list standard CL-VALID permit 65001:3
ip community-list standard CL-VALID permit 65002:1
ip community-list standard CL-VALID permit 65002:2
ip community-list standard CL-VALID permit 65002:3
ip community-list standard CL-VALID permit 65003:1
ip community-list standard CL-VALID permit 65003:2
ip community-list standard CL-VALID permit 65003:3
ip as-path access-list 10 permit ^65001$
ip as-path access-list 10 permit ^65001_65003$
no ip http server

```

```

ip http secure-server
ip route 10.30.2.0 255.255.255.0 Null0
ip nat pool SITE-POOL 10.30.2.100 10.30.2.129 prefix-length 24
ip nat inside source static 192.168.20.10 10.30.2.10 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.11 10.30.2.11 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.12 10.30.2.12 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.13 10.30.2.13 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.14 10.30.2.14 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.15 10.30.2.15 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.16 10.30.2.16 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.17 10.30.2.17 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.18 10.30.2.18 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.20.19 10.30.2.19 route-map NAT-TO-DOMAIN
ip nat inside source list NAT-POOL-SRC pool SITE-POOL
ip ssh bulk-mode 131072
ip ssh server algorithm authentication password
!
ip prefix-list PL-OWN-LAN seq 5 permit 192.168.20.0/24
!
ip prefix-list PL-OWN-LO seq 5 permit 10.20.2.1/32
!
ip prefix-list PL-OWN-NAT seq 5 permit 10.30.2.0/24
!
ip access-list standard VTY-MGMT
 10 remark out-of-band management network
 10 permit 192.168.99.0 0.0.0.255
 20 remark hypervisor user-mode NAT: how the harness reaches these devices
 20 permit 10.0.2.0 0.0.0.255
 30 deny any log
!
ip access-list extended NAT-DOMAIN
 10 permit ip host 192.168.20.10 10.30.0.0 0.0.255.255
 20 permit ip host 192.168.20.11 10.30.0.0 0.0.255.255
 30 permit ip host 192.168.20.12 10.30.0.0 0.0.255.255
 40 permit ip host 192.168.20.13 10.30.0.0 0.0.255.255
 50 permit ip host 192.168.20.14 10.30.0.0 0.0.255.255
 60 permit ip host 192.168.20.15 10.30.0.0 0.0.255.255
 70 permit ip host 192.168.20.16 10.30.0.0 0.0.255.255
 80 permit ip host 192.168.20.17 10.30.0.0 0.0.255.255
 90 permit ip host 192.168.20.18 10.30.0.0 0.0.255.255
100 permit ip host 192.168.20.19 10.30.0.0 0.0.255.255
ip access-list extended NAT-POOL-SRC
 10 permit ip 192.168.20.64 0.0.0.31 10.30.0.0 0.0.255.255
logging source-interface GigabitEthernet4 vrf MGMT
logging host 192.168.99.10 vrf MGMT
route-map RM-OUT-R1 permit 10
 description R2's own LO, tagged 65002:1
 match ip address prefix-list PL-OWN-LO
 set community 65002:1
!
route-map RM-OUT-R1 permit 20
 description R2's own NAT, tagged 65002:2
 match ip address prefix-list PL-OWN-NAT
 set community 65002:2
!
route-map RM-OUT-R1 permit 30
 description R2's own LAN, tagged 65002:3
 match ip address prefix-list PL-OWN-LAN
 set community 65002:3
!
route-map NAT-TO-DOMAIN permit 10
 match ip address NAT-DOMAIN
!
route-map RM-IN-R1 permit 10
 description accept only known communities on an AS path R1 can produce
 match as-path 10
 match community CL-VALID
!
snmp-server group LABGRP v3 priv read LABVIEW notify LABVIEW
snmp-server view LABVIEW iso included
snmp-server trap-source GigabitEthernet4
snmp-server enable traps snmp authentication linkdown linkup coldstart warmstart
snmp-server enable traps vrrp
snmp-server enable traps flowmon
snmp-server enable traps pfr
snmp-server enable traps ds1
snmp-server enable traps sdwan security policy system omp bfd
snmp-server enable traps entity-perf throughput-notif
snmp-server enable traps call-home message-send-fail server-fail
snmp-server enable traps tty
snmp-server enable traps ospf state-change

```

```

snmp-server enable traps ospf errors
snmp-server enable traps ospf retransmit
snmp-server enable traps ospf lsa
snmp-server enable traps ospf cisco-specific state-change nssa-trans-change
snmp-server enable traps ospf cisco-specific state-change shamlink interface
snmp-server enable traps ospf cisco-specific state-change shamlink neighbor
snmp-server enable traps ospf cisco-specific errors
snmp-server enable traps ospf cisco-specific retransmit
snmp-server enable traps ospf cisco-specific lsa
snmp-server enable traps eigrp
snmp-server enable traps casa
snmp-server enable traps xgcp
snmp-server enable traps cef resource-failure peer-state-change peer-fib-state-change inconsistency
snmp-server enable traps smart-license
snmp-server enable traps diameter
snmp-server enable traps entity-qfp mem-res-thresh throughput-notif
snmp-server enable traps entity-state
snmp-server enable traps ethernet cfm cc mep-up mep-down cross-connect loop config
snmp-server enable traps ethernet cfm crosscheck mep-missing mep-unknown service-up
snmp-server enable traps ether-oam
snmp-server enable traps ethernet evc status create delete
snmp-server enable traps aaa_server
snmp-server enable traps config-copy
snmp-server enable traps config
snmp-server enable traps config-ctid
snmp-server enable traps memory bufferpeak
snmp-server enable traps fru-ctrl
snmp-server enable traps entity-sensor
snmp-server enable traps resource-policy
snmp-server enable traps flash insertion removal lowspace
snmp-server enable traps hsrp
snmp-server enable traps entity
snmp-server enable traps ip local pool
snmp-server enable traps cpu threshold
snmp-server enable traps auth-framework sec-violation
snmp-server enable traps atm subif
snmp-server enable traps frame-relay
snmp-server enable traps frame-relay subif
snmp-server enable traps bgp state-changes all backward-trans limited updown-limited
snmp-server enable traps bgp threshold prefix
snmp-server enable traps bgp cbgp2 state-changes all backward-trans limited updown-limited
snmp-server enable traps bgp cbgp2 threshold prefix
snmp-server enable traps pim neighbor-change rp-mapping-change invalid-pim-message
snmp-server enable traps ipmulticast
snmp-server enable traps msdp
snmp-server enable traps mvpn
snmp-server enable traps rsvp
snmp-server enable traps isis
snmp-server enable traps dhcp
snmp-server enable traps nhrp nhs
snmp-server enable traps nhrp nhc
snmp-server enable traps nhrp nhp
snmp-server enable traps nhrp quota-exceeded
snmp-server enable traps ipsla
snmp-server enable traps bfd
snmp-server enable traps cnpd
snmp-server enable traps event-manager
snmp-server enable traps dlsw
snmp-server enable traps ospfv3 state-change
snmp-server enable traps ospfv3 errors
snmp-server enable traps pppoe
snmp-server enable traps l2tun session
snmp-server enable traps l2tun pseudowire status
snmp-server enable traps l2tun tunnel
snmp-server enable traps pki
snmp-server enable traps pimstdmib neighbor-loss invalid-register invalid-join-prune rp-mapping-change
interface-election
snmp-server enable traps adslline
snmp-server enable traps entity-diag boot-up-fail hm-test-recover hm-thresh-reached scheduled-test-fail
snmp-server enable traps vdsl2line
snmp-server enable traps vtp
snmp-server enable traps vlancreate
snmp-server enable traps vlandelete
snmp-server enable traps port-security
snmp-server enable traps isdn call-information
snmp-server enable traps isdn layer2
snmp-server enable traps isdn chan-not-avail
snmp-server enable traps isdn ietf
snmp-server enable traps c3g
snmp-server enable traps LTE
snmp-server enable traps lisp

```

```

snmp-server enable traps firewall serverstatus
snmp-server enable traps ike policy add
snmp-server enable traps ike policy delete
snmp-server enable traps ike tunnel start
snmp-server enable traps ike tunnel stop
snmp-server enable traps ipsec cryptomap add
snmp-server enable traps ipsec cryptomap delete
snmp-server enable traps ipsec cryptomap attach
snmp-server enable traps ipsec cryptomap detach
snmp-server enable traps ipsec tunnel start
snmp-server enable traps ipsec tunnel stop
snmp-server enable traps ipsec too-many-sas
snmp-server enable traps gdoi gm-start-registration
snmp-server enable traps gdoi gm-registration-complete
snmp-server enable traps gdoi gm-re-register
snmp-server enable traps gdoi gm-rekey-rcvd
snmp-server enable traps gdoi gm-rekey-fail
snmp-server enable traps gdoi ks-rekey-pushed
snmp-server enable traps gdoi gm-incomplete-cfg
snmp-server enable traps gdoi ks-no-rsa-keys
snmp-server enable traps gdoi ks-new-registration
snmp-server enable traps gdoi ks-reg-complete
snmp-server enable traps gdoi ks-role-change
snmp-server enable traps gdoi ks-gm-deleted
snmp-server enable traps gdoi ks-peer-reachable
snmp-server enable traps gdoi ks-peer-unreachable
snmp-server enable traps mpls rfc ldp
snmp-server enable traps mpls ldp
snmp-server enable traps mpls rfc traffic-eng
snmp-server enable traps mpls traffic-eng
snmp-server enable traps mpls fast-reroute protected
snmp-server enable traps otn
snmp-server enable traps pw vc
snmp-server enable traps frame-relay multilink bundle-mismatch
snmp-server enable traps dial
snmp-server enable traps dsp card-status
snmp-server enable traps dsp oper-state
snmp-server enable traps dsp video-usage
snmp-server enable traps dsp video-out-of-resource
snmp-server enable traps syslog
snmp-server enable traps sbc adj-status
snmp-server enable traps sbc blacklist
snmp-server enable traps sbc congestion-alarm
snmp-server enable traps sbc h248-ctrlr-status
snmp-server enable traps sbc media-source
snmp-server enable traps sbc radius-conn-status
snmp-server enable traps sbc sla-violation
snmp-server enable traps sbc sla-violation-rev1
snmp-server enable traps sbc svc-state
snmp-server enable traps sbc qos-statistics
snmp-server enable traps bulkstat collection transfer
snmp-server enable traps ethernet cfm alarm
snmp-server enable traps alarms informational
snmp-server enable traps transceiver all
snmp-server enable traps rf
snmp-server enable traps vrfmib vrf-up vrf-down vnet-trunk-up vnet-trunk-down
snmp-server enable traps ccme
snmp-server enable traps srst
snmp-server enable traps mpls vpn
snmp-server enable traps mpls rfc vpn
snmp-server enable traps voice
snmp-server host 192.168.99.10 vrf MGMT version 3 priv labmon udp-port 1162
snmp-server host 192.168.99.10 vrf MGMT version 3 priv labmon
tacacs server LAB-TAC
  address ipv4 192.168.99.10
  key LabTacacsKey123
!
!
!
!
!
control-plane
!
!
mgcp behavior rsip-range tgcp-only
mgcp behavior comedia-role none
mgcp behavior comedia-check-media-src disable
mgcp behavior comedia-sdp-force disable
!
mgcp profile default
!

```

```

!
!
!
!
banner login ^C
*****
                        AUTHORISED ACCESS ONLY

Access to this device is restricted to authorised personnel. If you are not
an authorised user, disconnect now.

All activity is monitored, logged and audited. Continued use of this system
constitutes consent to that monitoring.

Unauthorised access or use may result in disciplinary action and civil or
criminal penalties.
*****
^C
!
line con 0
  exec-timeout 0 0
  activation-character 13
  logging synchronous
  stopbits 1
line aux 0
  activation-character 13
line vty 0 4
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
line vty 5 15
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
!
ntp source GigabitEthernet4
ntp server vrf MGMT 192.168.99.10
!
!
!
!
!
!
netconf-yang
restconf
end

```

R3 — running config

Building configuration...

```

Current configuration : 19832 bytes
!
! Last configuration change at 23:21:14 UTC Mon Sep 7 2026 by lab
!
version 17.15
service timestamps debug datetime msec
service timestamps log datetime msec show-timezone
service sequence-numbers
platform qfp utilization monitor load 80
platform sslvpn use-pd
platform console serial
!
hostname c8000v-r3
!
boot-start-marker
boot-end-marker
!
!
vrf definition MGMT
  description out-of-band management
  !
  address-family ipv4
  exit-address-family
!
aaa new-model
!
!

```

C8000V IPsec Testbed - test evidence

```
D92847C4 D87D6F8 C7D48A2 D1B8826A 822083B9 88DDD430 2DFA57EA FD22715D
D73197D0 5A6C3582 5D12968B 56DE28B1 1D162D61 119BB282 E2239093 D96D95DD
D1122D35 0BF5780D 0FD3EB53 EF40D3D1 61693953 E97694CD C6F369F8 6B010182
D4978C4B 9316184D FDCDF993 82047F48 557B580A 8AFDB4D8 AB1CBD94 80E67D03
EB61EACC 075A9CDF F272A80F 02544535 24886FBF 500A61CC D2F56993 9457B80D
C3C63E80 359E03A4 1256F1C9 7F905BBA 20E341AD B99A8BC8 02C5B9FC 96C55D7B
66EE9989 ABC1C984 101DE474 631A5848 E41FB71A 9654FF7A 0302C615 EF5E298B
A2C2F138 17AE6A7D 9B630B20 26159088 5AF665AF

quit
crypto pki certificate chain SLA-TrustPoint
certificate ca 01
30820321 30820209 A0030201 02020101 300D0609 2A864886 F70D0101 0B050030
32310E30 0C060355 040A1305 43697363 6F312030 1E060355 04031317 43697363
6F204C69 63656E73 696E6720 526F6F74 20434130 1E170D31 33303533 30313934
3834375A 170D3338 30353330 31393438 34375A30 32310E30 0C060355 040A1305
43697363 6F312030 1E060355 04031317 43697363 6F204C69 63656E73 696E6720
526F6F74 20434130 82012230 0D06092A 864886F7 0D010101 05000382 010F0030
82010A02 82010100 A6BCBD96 131E05F7 145EA72C 2CD686E6 17222EA1 F1EFF64D
CBB4C798 212AA147 C655D8D7 9471380D 8711441E 1AAF071A 9CAE6388 8A38E520
1C394D78 462EF239 C659F715 B98C0A59 5BBB5CBD 0CFEBEA3 700A8BF7 D8F256EE
4AA4E80D DB6FD1C9 60B1FD18 FFC69C96 6FA68957 A2617DE7 104FDC5F EA2956AC
7390A3EB 2B5436AD C847A2C5 DAB553EB 69A9A535 58E9F3E3 C0BD23CF 58BD7188
68E69491 20F320E7 948E71D7 AE3BCC84 F10684C7 4BC8E00F 539BA42B 42C68BB7
C7479096 B4BC2D62 EA2F505D C7B062A4 6811D95B E8250FC4 5D5D5FB8 8F27D191
C55F0D76 61F9A4CD 3D992327 A8BB03BD 4E6D7069 7CBADF8B DF5F4368 95135E44
DFC7C6CF 04DD7FD1 02030100 01A34230 40300E06 03551D0F 0101FF04 04030201
06300F06 03551D13 0101FF04 05300301 01FF301D 0603551D 0E041604 1449DC85
4B3D31E5 1B3E6A17 606AF333 3D3B4C73 E8300D06 092A8648 86F70D01 010B0500
03820101 00507F24 D3932A66 86025D9F E838AE5C 6D4DF6B0 49631C78 240DA905
604EDCDE FF4FED2B 77FC460E CD636FDB DD44681E 3A5673AB 9093D3B1 6C9E3D8B
D98987BF E40CBD9E 1AEA0C2 2189BB5C 8FA85686 CD98B646 5575B146 8DFC66A8
467A3DF4 D4565700 6ADF0F0D CF835015 3C04FF7C 21E878AC 11BA9CD2 55A9232C
7CA7B7E6 C1AF74F6 152E99B7 B1FCF9BB E973DE7F 5BDD8B86 C71E3B49 1765308B
5FB0DA06 B92AFE7F 494E8A9E 07B85737 F3A58BE1 1A48A229 C37C1E69 39F08678
80DDCD16 D6BACECA EEB7CF9F 8428787B 35202CDC 60E4616A B623CDBD 230E3AFB
418616A9 4093E049 4D10AB75 27E86F73 932E35B5 8862FDAE 0275156F 719BB2F0
D697DF7F 28

quit
!
!
!
!
!
!
!
!
!
!
license udi pid C8000V sn 98WSPSI3CQ2
license boot level network-premier addon dna-premier
memory free low-watermark processor 31774
diagnostic bootstrap level minimal
!
!
!
spanning-tree extend system-id
!
!
!
enable secret 9 $9$Bw47UP1ye/.yVU$K5CSpZusnABYfZykCttzeySotiNrBY/frbuYNtoXY2
!
username lab privilege 15 secret 9 $9$nTmPdPnmf5C6Nk$TZUyweyM6Pgquck3KoKrRbcfdLyeESXbTbt75p43gz7g
!
redundancy
!
!
!
!
crypto ikev2 proposal LAB-PROP
 encryption aes-cbc-256
 integrity sha256
 group 14
!
crypto ikev2 policy LAB-POL
 proposal LAB-PROP
!
crypto ikev2 keyring LAB-KR
 peer ANY
 address 0.0.0.0 0.0.0.0
 pre-shared-key LabPreSharedKey123
!
!
!
crypto ikev2 profile LAB-PROF
 match identity remote address 0.0.0.0
```

```

authentication remote pre-share
authentication local pre-share
keyring local LAB-KR
!
!
!
!
!
!
!
!
!
!
!
crypto ipsec transform-set LAB-TS esp-aes 256 esp-sha256-hmac
mode transport
!
crypto ipsec profile LAB-IPSEC
set transform-set LAB-TS
set ikev2-profile LAB-PROF
!
!
!
!
!
!
!
!
!
interface Loopback0
description Protected endpoint
ip address 172.16.3.1 255.255.255.255
!
interface Loopback1
description BGP-advertised prefix
ip address 10.20.3.1 255.255.255.255
!
interface Tunnel0
description DMVPN spoke
ip address 172.20.0.3 255.255.255.0
no ip redirects
ip nat outside
ip nhrp authentication LabNhrp
ip nhrp network-id 100
ip nhrp holdtime 300
ip nhrp nhs 172.20.0.1 nbma 100.64.0.1 multicast
ip tcp adjust-mss 1360
bfd interval 500 min_rx 500 multiplier 3
tunnel source GigabitEthernet2
tunnel mode gre multipoint
tunnel key 100
tunnel protection ipsec profile LAB-IPSEC
!
interface GigabitEthernet1
description MGMT - QEMU user-mode net (DHCP)
ip address dhcp
negotiation auto
!
interface GigabitEthernet2
description WAN - shared provider segment, DMVPN underlay
ip address 100.64.0.3 255.255.255.0
negotiation auto
!
interface GigabitEthernet3
description LAN toward the local host
ip address 192.168.30.1 255.255.255.0
ip nat inside
negotiation auto
!
interface GigabitEthernet4
description OOB management - NTP, syslog, SNMP
vrf forwarding MGMT
ip address 192.168.99.3 255.255.255.0
negotiation auto
!
router bgp 65003
bgp router-id 172.16.3.1
bgp log-neighbor-changes

```

```

neighbor 172.20.0.1 remote-as 65001
neighbor 172.20.0.1 password LabBgpSecret
neighbor 172.20.0.1 timers 10 30
neighbor 172.20.0.1 fall-over bfd
!
address-family ipv4
network 10.20.3.1 mask 255.255.255.255
network 10.30.3.0 mask 255.255.255.0
network 192.168.30.0
neighbor 172.20.0.1 activate
neighbor 172.20.0.1 send-community both
neighbor 172.20.0.1 route-map RM-IN-R1 in
neighbor 172.20.0.1 route-map RM-OUT-R1 out
neighbor 172.20.0.1 maximum-prefix 15 80
exit-address-family
!
ip forward-protocol nd
!
ip bgp-community new-format
ip community-list standard CL-VALID permit 65001:1
ip community-list standard CL-VALID permit 65001:2
ip community-list standard CL-VALID permit 65001:3
ip community-list standard CL-VALID permit 65002:1
ip community-list standard CL-VALID permit 65002:2
ip community-list standard CL-VALID permit 65002:3
ip community-list standard CL-VALID permit 65003:1
ip community-list standard CL-VALID permit 65003:2
ip community-list standard CL-VALID permit 65003:3
ip as-path access-list 10 permit ^65001$
ip as-path access-list 10 permit ^65001_65002$
no ip http server
ip http secure-server
ip route 10.30.3.0 255.255.255.0 Null0
ip nat pool SITE-POOL 10.30.3.100 10.30.3.129 prefix-length 24
ip nat inside source static 192.168.30.10 10.30.3.10 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.11 10.30.3.11 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.12 10.30.3.12 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.13 10.30.3.13 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.14 10.30.3.14 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.15 10.30.3.15 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.16 10.30.3.16 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.17 10.30.3.17 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.18 10.30.3.18 route-map NAT-TO-DOMAIN
ip nat inside source static 192.168.30.19 10.30.3.19 route-map NAT-TO-DOMAIN
ip nat inside source list NAT-POOL-SRC pool SITE-POOL
ip ssh bulk-mode 131072
ip ssh server algorithm authentication password
!
ip prefix-list PL-OWN-LAN seq 5 permit 192.168.30.0/24
!
ip prefix-list PL-OWN-L0 seq 5 permit 10.20.3.1/32
!
ip prefix-list PL-OWN-NAT seq 5 permit 10.30.3.0/24
!
ip access-list standard VTY-MGMT
10 remark out-of-band management network
10 permit 192.168.99.0 0.0.0.255
20 remark hypervisor user-mode NAT: how the harness reaches these devices
20 permit 10.0.2.0 0.0.0.255
30 deny any log
!
ip access-list extended NAT-DOMAIN
10 permit ip host 192.168.30.10 10.30.0.0 0.0.255.255
20 permit ip host 192.168.30.11 10.30.0.0 0.0.255.255
30 permit ip host 192.168.30.12 10.30.0.0 0.0.255.255
40 permit ip host 192.168.30.13 10.30.0.0 0.0.255.255
50 permit ip host 192.168.30.14 10.30.0.0 0.0.255.255
60 permit ip host 192.168.30.15 10.30.0.0 0.0.255.255
70 permit ip host 192.168.30.16 10.30.0.0 0.0.255.255
80 permit ip host 192.168.30.17 10.30.0.0 0.0.255.255
90 permit ip host 192.168.30.18 10.30.0.0 0.0.255.255
100 permit ip host 192.168.30.19 10.30.0.0 0.0.255.255
ip access-list extended NAT-POOL-SRC
10 permit ip 192.168.30.64 0.0.0.31 10.30.0.0 0.0.255.255
logging source-interface GigabitEthernet4 vrf MGMT
logging host 192.168.99.10 vrf MGMT
route-map RM-OUT-R1 permit 10
description R3's own L0, tagged 65003:1
match ip address prefix-list PL-OWN-L0
set community 65003:1
!

```

```

route-map RM-OUT-R1 permit 20
description R3's own NAT, tagged 65003:2
match ip address prefix-list PL-OWN-NAT
set community 65003:2
!
route-map RM-OUT-R1 permit 30
description R3's own LAN, tagged 65003:3
match ip address prefix-list PL-OWN-LAN
set community 65003:3
!
route-map NAT-T0-DOMAIN permit 10
match ip address NAT-DOMAIN
!
route-map RM-IN-R1 permit 10
description accept only known communities on an AS path R1 can produce
match as-path 10
match community CL-VALID
!
snmp-server group LABGRP v3 priv read LABVIEW notify LABVIEW
snmp-server view LABVIEW iso included
snmp-server trap-source GigabitEthernet4
snmp-server enable traps snmp authentication linkdown linkup coldstart warmstart
snmp-server enable traps vrrp
snmp-server enable traps flowmon
snmp-server enable traps pfr
snmp-server enable traps ds1
snmp-server enable traps sdwan security policy system omp bfd
snmp-server enable traps entity-perf throughput-notif
snmp-server enable traps call-home message-send-fail server-fail
snmp-server enable traps tty
snmp-server enable traps ospf state-change
snmp-server enable traps ospf errors
snmp-server enable traps ospf retransmit
snmp-server enable traps ospf lsa
snmp-server enable traps ospf cisco-specific state-change nssa-trans-change
snmp-server enable traps ospf cisco-specific state-change shamlink interface
snmp-server enable traps ospf cisco-specific state-change shamlink neighbor
snmp-server enable traps ospf cisco-specific errors
snmp-server enable traps ospf cisco-specific retransmit
snmp-server enable traps ospf cisco-specific lsa
snmp-server enable traps eigrp
snmp-server enable traps casa
snmp-server enable traps xgcp
snmp-server enable traps cef resource-failure peer-state-change peer-fib-state-change inconsistency
snmp-server enable traps smart-license
snmp-server enable traps diameter
snmp-server enable traps entity-qfp mem-res-thresh throughput-notif
snmp-server enable traps entity-state
snmp-server enable traps ethernet cfm cc mep-up mep-down cross-connect loop config
snmp-server enable traps ethernet cfm crosscheck mep-missing mep-unknown service-up
snmp-server enable traps ether-oam
snmp-server enable traps ethernet evc status create delete
snmp-server enable traps aaa_server
snmp-server enable traps config-copy
snmp-server enable traps config
snmp-server enable traps config-ctid
snmp-server enable traps memory bufferpeak
snmp-server enable traps fru-ctrl
snmp-server enable traps entity-sensor
snmp-server enable traps resource-policy
snmp-server enable traps flash insertion removal lowspace
snmp-server enable traps hsrp
snmp-server enable traps entity
snmp-server enable traps ip local pool
snmp-server enable traps cpu threshold
snmp-server enable traps auth-framework sec-violation
snmp-server enable traps atm subif
snmp-server enable traps frame-relay
snmp-server enable traps frame-relay subif
snmp-server enable traps bgp state-changes all backward-trans limited updown-limited
snmp-server enable traps bgp threshold prefix
snmp-server enable traps bgp cbgp2 state-changes all backward-trans limited updown-limited
snmp-server enable traps bgp cbgp2 threshold prefix
snmp-server enable traps pim neighbor-change rp-mapping-change invalid-pim-message
snmp-server enable traps ipmulticast
snmp-server enable traps msdp
snmp-server enable traps mvpn
snmp-server enable traps rsvp
snmp-server enable traps isis
snmp-server enable traps dhcp
snmp-server enable traps nhrp nhs

```

```

snmp-server enable traps nhrp nhc
snmp-server enable traps nhrp nhp
snmp-server enable traps nhrp quota-exceeded
snmp-server enable traps ipsla
snmp-server enable traps bfd
snmp-server enable traps cnpd
snmp-server enable traps event-manager
snmp-server enable traps dlsr
snmp-server enable traps ospfv3 state-change
snmp-server enable traps ospfv3 errors
snmp-server enable traps pppoe
snmp-server enable traps l2tun session
snmp-server enable traps l2tun pseudowire status
snmp-server enable traps l2tun tunnel
snmp-server enable traps pki
snmp-server enable traps pimstdmib neighbor-loss invalid-register invalid-join-prune rp-mapping-change
interface-election
snmp-server enable traps adslline
snmp-server enable traps entity-diag boot-up-fail hm-test-recover hm-thresh-reached scheduled-test-fail
snmp-server enable traps vdsl2line
snmp-server enable traps vtp
snmp-server enable traps vlancreate
snmp-server enable traps vlandelete
snmp-server enable traps port-security
snmp-server enable traps isdn call-information
snmp-server enable traps isdn layer2
snmp-server enable traps isdn chan-not-avail
snmp-server enable traps isdn ietf
snmp-server enable traps c3g
snmp-server enable traps LTE
snmp-server enable traps lisp
snmp-server enable traps firewall serverstatus
snmp-server enable traps ike policy add
snmp-server enable traps ike policy delete
snmp-server enable traps ike tunnel start
snmp-server enable traps ike tunnel stop
snmp-server enable traps ipsec cryptomap add
snmp-server enable traps ipsec cryptomap delete
snmp-server enable traps ipsec cryptomap attach
snmp-server enable traps ipsec cryptomap detach
snmp-server enable traps ipsec tunnel start
snmp-server enable traps ipsec tunnel stop
snmp-server enable traps ipsec too-many-sas
snmp-server enable traps gdoi gm-start-registration
snmp-server enable traps gdoi gm-registration-complete
snmp-server enable traps gdoi gm-re-register
snmp-server enable traps gdoi gm-rekey-rcvd
snmp-server enable traps gdoi gm-rekey-fail
snmp-server enable traps gdoi ks-rekey-pushed
snmp-server enable traps gdoi gm-incomplete-cfg
snmp-server enable traps gdoi ks-no-rsa-keys
snmp-server enable traps gdoi ks-new-registration
snmp-server enable traps gdoi ks-reg-complete
snmp-server enable traps gdoi ks-role-change
snmp-server enable traps gdoi ks-gm-deleted
snmp-server enable traps gdoi ks-peer-reachable
snmp-server enable traps gdoi ks-peer-unreachable
snmp-server enable traps mpls rfc ldp
snmp-server enable traps mpls ldp
snmp-server enable traps mpls rfc traffic-eng
snmp-server enable traps mpls traffic-eng
snmp-server enable traps mpls fast-reroute protected
snmp-server enable traps otn
snmp-server enable traps pw vc
snmp-server enable traps frame-relay multilink bundle-mismatch
snmp-server enable traps dial
snmp-server enable traps dsp card-status
snmp-server enable traps dsp oper-state
snmp-server enable traps dsp video-usage
snmp-server enable traps dsp video-out-of-resource
snmp-server enable traps syslog
snmp-server enable traps sbc adj-status
snmp-server enable traps sbc blacklist
snmp-server enable traps sbc congestion-alarm
snmp-server enable traps sbc h248-ctrlr-status
snmp-server enable traps sbc media-source
snmp-server enable traps sbc radius-conn-status
snmp-server enable traps sbc sla-violation
snmp-server enable traps sbc sla-violation-rev1
snmp-server enable traps sbc svc-state
snmp-server enable traps sbc qos-statistics

```

```

snmp-server enable traps bulkstat collection transfer
snmp-server enable traps ethernet cfm alarm
snmp-server enable traps alarms informational
snmp-server enable traps transceiver all
snmp-server enable traps rf
snmp-server enable traps vrfmib vrf-up vrf-down vnet-trunk-up vnet-trunk-down
snmp-server enable traps ccme
snmp-server enable traps srst
snmp-server enable traps mpls vpn
snmp-server enable traps mpls rfc vpn
snmp-server enable traps voice
snmp-server host 192.168.99.10 vrf MGMT version 3 priv labmon udp-port 1162
snmp-server host 192.168.99.10 vrf MGMT version 3 priv labmon
tacacs server LAB-TAC
  address ipv4 192.168.99.10
  key LabTacacsKey123
!
!
!
!
!
control-plane
!
!
mgcp behavior rsip-range tgcp-only
mgcp behavior comedia-role none
mgcp behavior comedia-check-media-src disable
mgcp behavior comedia-sdp-force disable
!
mgcp profile default
!
!
!
!
!
banner login ^C
*****
                        AUTHORISED ACCESS ONLY

Access to this device is restricted to authorised personnel. If you are not
an authorised user, disconnect now.

All activity is monitored, logged and audited. Continued use of this system
constitutes consent to that monitoring.

Unauthorised access or use may result in disciplinary action and civil or
criminal penalties.
*****
^C
!
line con 0
  exec-timeout 0 0
  activation-character 13
  logging synchronous
  stopbits 1
line aux 0
  activation-character 13
line vty 0 4
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
line vty 5 15
  access-class VTY-MGMT in vrf-also
  exec-timeout 0 0
  activation-character 13
  transport input ssh
!
ntp source GigabitEthernet4
ntp server vrf MGMT 192.168.99.10
!
!
!
!
!
!
netconf-yang
restconf
end

```