


SRv6 WAN core lab — topology

Four VyOS PEs (one per data centre) dual-homed to a VyOS P-router triangle; IS-IS level-2 IPv6-only underlay carrying the SRv6 locators; BGP VPNv4 over SRv6 (End.DT4) reflected by p1; a VyOS CE per data centre speaking eBGP into VRF tenant-a; a CirrOS host behind each CE. 15 VMs on one libvirt/KVM host, ≈12 GiB RAM. — core link (IPv6 /64, IS-IS, SRv6) — access link (IPv4)



Addressing

Node	Role	OOB	Loopback	Router-id	IS-IS NET	SRv6 locator	AS
pe1	pe	10.3.0.11	fd00:a::1	10.255.0.1	49.0001.0000.0000.0001.00	fd00:c:1::/64	65000
pe2	pe	10.3.0.12	fd00:a::2	10.255.0.2	49.0001.0000.0000.0002.00	fd00:c:2::/64	65000
pe3	pe	10.3.0.13	fd00:a::3	10.255.0.3	49.0001.0000.0000.0003.00	fd00:c:3::/64	65000
pe4	pe	10.3.0.14	fd00:a::4	10.255.0.4	49.0001.0000.0000.0004.00	fd00:c:4::/64	65000
p1	p (RR)	10.3.0.21	fd00:a::11	10.255.0.11	49.0001.0000.0000.0011.00	fd00:c:11::/64	65000
p2	p	10.3.0.22	fd00:a::12	10.255.0.12	49.0001.0000.0000.0012.00	fd00:c:12::/64	-
p3	p	10.3.0.23	fd00:a::13	10.255.0.13	49.0001.0000.0000.0013.00	fd00:c:13::/64	-
ce1	ce	10.3.0.31	-	172.20.1.1	-	-	65001
ce2	ce	10.3.0.32	-	172.20.2.1	-	-	65002
ce3	ce	10.3.0.33	-	172.20.3.1	-	-	65003
ce4	ce	10.3.0.34	-	172.20.4.1	-	-	65004
h1	host	10.3.0.41	-	-	-	-	-
h2	host	10.3.0.42	-	-	-	-	-
h3	host	10.3.0.43	-	-	-	-	-
h4	host	10.3.0.44	-	-	-	-	-

Links: core fd00:b:0:<ab>::/64 (first end ::1), PE-CE 172.16.n.0/30 (PE .1), CE-host 172.20.n.0/24 (CE .1 = gateway). OOB network srv6-oob 10.3.0.0/24 (host 10.3.0.1), consoles 127.0.0.1:5301-5315. VRF tenant-a: table 100, RT 65000:100, RD 65000:<pe#>.

Generated from lab.conf by docs/topology.py · <https://github.com/dcantor/srv6-core>

Packet walk: h1 → h3 (dc1 → dc3)

- h1** 172.20.1.2 sends to 172.20.3.2 via its gateway **ce1** (172.20.1.1).
 - ce1** has 172.20.3.0/24 from pe1 over eBGP → forwards to **pe1** 172.16.1.1 (VRF tenant-a).
 - pe1**: VRF route 172.20.3.0/24 = encap seg6 segs 1 [fd00:c:3:0:X::] — the End.DT4 SID pe3 exported with the VPNv4 route (RD 65000:3, RT 65000:100, next hop fd00:a::3) via the route reflector p1. Outer IPv6 fd00:a::1 → fd00:c:3:0:X:: + SRH.
 - p2** (the only shortest path west→east) forwards plain IPv6 towards pe3's locator fd00:c:3::/64 learned from IS-IS — no VRF, no IPv4 knowledge.
 - pe3**: local SID seg6local End.DT4 vrf table tenant-a decapsulates and looks the inner packet up in the VRF → **ce3** 172.16.3.2 → **h3**.
 - Reply mirrors the path with pe1's SID. Forwarded packets need the locator block leaked into the VRF table (static route6 fd00:c::/40 ... vrf default) because Linux scopes the encapsulation's outer lookup to the ingress VRF.

Local SIDs on a PE (pe1)

SID	Behaviour	Installed by
fd00:c:1::	End (node SID)	IS-IS
fd00:c:1:0:X::	End.X per core adjacency (eth1 → p1, eth2 → p2)	IS-IS
fd00:c:1:0:Y::	End.DT4 → VRF tenant-a	BGP (sid vpn export auto)

Locator structure: block 40 bits · node 24 bits · function 16 bits; function values are allocated by FRR at run time.