

Homework

David Cyncynates
dcc57@case.edu

June 29, 2016

1 Scalar Modes

In the following, lower case denotes a quantity in position space while capital letters denote their components in Fourier space.

Denote the displacement field $u(\vec{x}, t) = \nabla\phi(\vec{x}, t) + \nabla \times a(\vec{x}, t)$. The linearized (acoustic) wave equation for ϕ is then

$$\alpha^2 \nabla^2 \phi = \partial_t^2 \phi, \quad (1)$$

where $\alpha^2 = \frac{\lambda+2\mu}{\rho}$. We may write

$$\phi(\vec{x}, t) = \int \frac{d^3k}{(2\pi)^3} \Phi(\vec{k}, \omega) e^{i(\vec{k} \cdot \vec{x} - \omega t)}, \quad (2)$$

from which we obtain the dispersion relation $\alpha k = \omega$, and hence the solution

$$\phi(\vec{x}, t) = \int \frac{d^3k}{(2\pi)^3} \Phi(\vec{k}, \omega) e^{i(\vec{k} \cdot \vec{x} - \alpha k t)}. \quad (3)$$

We now impose the constraint equation

$$\sigma_{ij} = \delta_{ij} \lambda \nabla \cdot u + \mu (u_{i,j} + u_{j,i}) \quad (4)$$

which, for the scalar modes becomes

$$\sigma_{ij} = \delta_{ij} \lambda \nabla^2 \phi + 2\mu \partial_i \partial_j \phi \quad (5)$$

and whose trace is

$$-p = K \nabla^2 \phi, \quad (6)$$

where $K = \lambda + \frac{2}{3}\mu$ is the bulk modulus and $p = -\frac{1}{3} \text{tr} \sigma_{ij}$. We take this constraint as an initial condition at $t = 0$. In Fourier space

$$P(\vec{k}) = K k^2 \Phi(\vec{k}), \quad (7)$$

from which we obtain the displacement field components

$$U(\vec{k}) = i \frac{P(\vec{k})}{K} \frac{\vec{k}}{k^2}, \quad (8)$$

and hence

$$u(\vec{x}, t) = \int \frac{d^3k}{(2\pi)^3} i \frac{P(\vec{k})}{K} \frac{\vec{k}}{k^2} e^{i(\vec{k} \cdot \vec{x} - \alpha k t)}, \quad (9)$$

The equation for the energy of the compressional modes is

$$E = \frac{1}{2} \int_V d^3x \left(\rho |\partial_t u|^2 + (\lambda + 2\mu) |\nabla \cdot u|^2 \right), \quad (10)$$

$$= \frac{\lambda + 2\mu}{K^2} \int \frac{d^3k}{(2\pi)^3} |P(\vec{k})|^2 \quad (11)$$

In the case that P depends only on the frequency

$$E = 4\pi \frac{\lambda + 2\mu}{K^2} \int \frac{d\tilde{\lambda}}{\tilde{\lambda}^4} |P(\tilde{\lambda})|^2. \quad (12)$$

Now consider the case of a step function type pressure source - a cylinder of height h and radius r_X

$$p(\vec{x}, 0) = p_0 \theta(r_X - r) [\theta(z + h/2) - \theta(z - h/2)], \quad (13)$$

whose Fourier components are

$$P(\vec{k}) = \frac{4\pi r_X p_0}{\sqrt{k_x^2 + k_y^2} k_z} J_1 \left(\sqrt{k_x^2 + k_y^2} r_X \right) \sin \left(\frac{h}{2} k_z \right), \quad (14)$$

which, in polar k -space is

$$P(k, \varphi, \theta) = \frac{4\pi r_X p_0}{k^2 \sin \theta \cos \theta} J_1(r_X k \sin \theta) \sin \left(\frac{h}{2} k \cos \theta \right), \quad (15)$$

Directly integrating in Mathematica (over θ first) yields

$$E_{\text{total}} = \frac{\lambda + 2\mu}{K^2} 4\pi^2 p_0^2 \sigma_X h \quad (16)$$

where $\sigma_X = \pi r_X^2$. To calculate the energy deposition into the low frequency spectrum, we integrate k from 0 to k_0 . Observe, we can make the following approximation

$$P(\vec{k}) \approx_{k \ll r_X} \frac{2\pi r_X p_0}{k^2 \cos \theta \sin \theta} r_X k \sin \theta \sin \left(\frac{h}{2} k \cos \theta \right), \quad (17)$$

$$= \frac{2\pi r_X^2 p_0}{k \cos \theta} \sin \left(\frac{h}{2} k \cos \theta \right). \quad (18)$$

From this we obtain the portion of the energy relegated to the long wavelength spectrum

$$E_{\text{propagated}} = \frac{\lambda + 2\mu}{K^2} \int \frac{d^3k}{(2\pi)^3} \left| \frac{2\pi r_X^2 p_0}{k \cos \theta} \sin \left(\frac{h}{2} k \cos \theta \right) \right|^2, \quad (19)$$

$$= \left[\frac{1}{2h} (r_X^2 p_0)^2 \frac{\lambda + 2\mu}{K^2} \right] [hk_0 \cos(hk_0) + \sin(hk_0) + hk_0 (-2 + hk_0 \text{Si}(hk_0))], \quad (20)$$

$$= \left[(r_X^2 p_0)^2 \frac{\lambda + 2\mu}{K^2} \right] \left[\frac{\pi}{\lambda_0} \cos \left(\frac{2\pi h}{\lambda_0} \right) + \sin \left(\frac{2\pi h}{\lambda_0} \right) + \left(\frac{\pi}{\lambda_0} \right) \left(-2 + \left(\frac{2\pi h}{\lambda_0} \right) \text{Si} \left(\frac{2\pi h}{\lambda_0} \right) \right) \right], \quad (21)$$

$$\approx_{h \gg \lambda_0 \gg 1} \left[(r_X^2 p_0)^2 \frac{\lambda + 2\mu}{K^2} \right] \left[\frac{\pi^3 h}{\lambda_0^2} \right], \quad (22)$$

$$= \left[(\sigma_X p_0)^2 \frac{\lambda + 2\mu}{K^2} \right] \left[\frac{\pi h}{\lambda_0^2} \right]. \quad (23)$$

From this we obtain the fractional energy deposition into the unattenuated wavelengths

$$\Xi = \frac{\sigma_X}{4\pi\lambda_0^2}. \quad (24)$$

This approximation holds for $\lambda_0^2 \gg \sigma_X$, which is appropriate for the case that λ_0 is on the order of kilometers and σ_X is on the order of centimeters squared.

2 Vector Modes

The following is the equation of motion for the vector potential a without body force:

$$\mu \nabla^2 a - \rho \ddot{a} = \mu \nabla (\nabla \cdot a) - \mu \nabla \times (\nabla \times a) - \rho \ddot{a} = 0, \quad (25)$$

where the leftmost term is the vector laplacian. This gives us three wave equations for the three components of a . The constraint equation takes the form

$$\sigma_{ij} = \lambda \delta_{ij} \nabla \cdot \nabla \times a + \mu (\partial_j (\nabla \times a)_i + \partial_i (\nabla \times a)_j), \quad (26)$$

$$= \mu (\partial_j (\nabla \times a)_i + \partial_i (\nabla \times a)_j), \quad (27)$$

$$= \mu \begin{pmatrix} 2\partial_x(\partial_y a_z - \partial_z a_y) & (\partial_y^2 - \partial_x^2)a_z + \partial_z(\partial_x a_x - \partial_y a_y) & (\partial_x^2 - \partial_z^2)a_y + \partial_y(\partial_z a_z - \partial_x a_x) \\ & 2\partial_y(\partial_z a_x - \partial_x a_z) & (\partial_z^2 - \partial_y^2)a_x + \partial_x(\partial_y a_y - \partial_z a_z) \\ & & 2\partial_z(\partial_x a_y - \partial_y a_x) \end{pmatrix}. \quad (28)$$

We now write a_i in terms of its Fourier components

$$a_i(\vec{x}, t) = \int \frac{d^3 k}{(2\pi)^3} A_i(\vec{k}, \omega) e^{i(\vec{k} \cdot \vec{x} - \omega t)}. \quad (29)$$

Observe the dispersion relation $\beta k = \omega$, which holds for each component a_i , and that $\beta = \frac{\mu}{\rho}$. Thus, the solutions to the wave equation are

$$a_i(\vec{x}, t) = \int \frac{d^3 k}{(2\pi)^3} A_i(\vec{k}, \omega) e^{i(\vec{k} \cdot \vec{x} - \beta k t)}. \quad (30)$$

We now use the constraint equation to write down the initial vector potential in terms of the initial stress. Note, we will obtain three equations constraining the possible initial stresses (i.e., we will be able to eliminate three components of σ from the equations), and three equations writing A_i in terms of Σ_{ij} .

In Fourier space we have

$$-\Sigma_{xx} = 2k_x(k_y A_z - k_z A_y), \quad (31)$$

$$-\Sigma_{yy} = 2k_y(k_z A_x - k_x A_z), \quad (32)$$

$$-\Sigma_{zz} = 2k_z(k_x A_y - k_y A_x), \quad (33)$$

$$-\Sigma_{xy} = (k_y^2 - k_x^2)A_z + k_z(k_x A_x - k_y A_y), \quad (34)$$

$$-\Sigma_{yz} = (k_z^2 - k_y^2)A_x + k_x(k_y A_y - k_z A_z), \quad (35)$$

$$-\Sigma_{zx} = (k_x^2 - k_z^2)A_y + k_y(k_z A_z - k_x A_x). \quad (36)$$

The first constraint on Σ_{ij} is

$$0 = \Sigma_{xx} + \Sigma_{yy} + \Sigma_{zz}. \quad (37)$$

Now observe that

$$-\frac{\Sigma_{xx}}{2k_x} = k_y A_z - k_z A_y, \quad (38)$$

$$-\frac{\Sigma_{yy}}{2k_y} = k_z A_x - k_x A_z, \quad (39)$$

$$-\frac{\Sigma_{zz}}{2k_z} = k_x A_y - k_y A_x, \quad (40)$$

$$(41)$$

from which we see

$$-\frac{\Sigma_{xx}}{2k_x} - \frac{\Sigma_{yy}}{2k_y} = (k_y - k_x)A_z + k_z(A_x - A_y), \quad (42)$$

$$= -\frac{1}{k_x + k_y} (\Sigma_{xy} + k_z(k_x A_x - k_y A_y)) + k_z(A_x - A_y), \quad (43)$$

$$(44)$$

$$-(k_x + k_y) \left(\frac{\Sigma_{xx}}{2k_x} + \frac{\Sigma_{yy}}{2k_y} \right) = -(\Sigma_{xy} + k_z(k_x A_x - k_y A_y)) + k_z((k_x + k_y)A_x - (k_x + k_y)A_y), \quad (45)$$

$$= -(\Sigma_{xy} + k_z(k_x A_x - k_y A_y)) + k_z((k_x + k_y)A_x - (k_x + k_y)A_y), \quad (46)$$

$$= -\Sigma_{xy} + k_z(k_y A_x - k_x A_y). \quad (47)$$

Hence

$$(k_x + k_y) \left(\frac{\Sigma_{xx}}{k_x} + \frac{\Sigma_{yy}}{k_y} \right) = 2\Sigma_{xy} + \Sigma_{zz}, \quad (48)$$

$$= 2\Sigma_{xy} - \Sigma_{xx} - \Sigma_{yy}, \quad (49)$$

$$(50)$$

i.e.

$$\left(2 + \frac{k_y}{k_x} \right) \Sigma_{xx} + \left(2 + \frac{k_x}{k_y} \right) \Sigma_{yy} = 2\Sigma_{xy}, \quad (51)$$

$$\left(2 + \frac{k_z}{k_y} \right) \Sigma_{yy} + \left(2 + \frac{k_y}{k_z} \right) \Sigma_{zz} = 2\Sigma_{yz}, \quad (52)$$

$$\left(2 + \frac{k_x}{k_z} \right) \Sigma_{zz} + \left(2 + \frac{k_z}{k_x} \right) \Sigma_{xx} = 2\Sigma_{zx}. \quad (53)$$

Thus, we have

$$\Sigma_{zz} = \frac{k_x(k_y + 2k_z)(k_x + 2k_y)\Sigma_{xy} - k_y(k_y + 2k_z)(k_y + 2k_x)\Sigma_{yz} + k_z(k_y + 2k_z)(k_z + 2k_y)\Sigma_{zx}}{6(k_x + k_y + k_z)(k_y k_z + k_z k_x + k_x k_y)}, \quad (54)$$

etc. But this is wrong! We need to check over all this work.