

**Beyond modelocking: High repetition-rate frequency
combs derived from a continuous-wave laser**

by

Daniel C. Cole

B.S., Washington University in St. Louis, 2012

M.S., University of Colorado, 2015

A thesis submitted to the
Faculty of the Graduate School of the
University of Colorado in partial fulfillment
of the requirements for the degree of
Doctor of Philosophy
Department of Physics

2018

This thesis entitled:
Beyond modelocking: High repetition-rate frequency combs derived from a continuous-wave laser
written by Daniel C. Cole
has been approved for the Department of Physics

Scott A. Diddams

Reader Two

Date _____

The final copy of this thesis has been examined by the signatories, and we find that both the content and the form meet acceptable presentation standards of scholarly work in the above mentioned discipline.

Cole, Daniel C. (Ph.D., Physics)

Beyond modelocking: High repetition-rate frequency combs derived from a continuous-wave laser

Thesis directed by Dr. Scott A. Diddams

Optical frequency combs based on modelocked lasers have revolutionized precision metrology by facilitating measurements of optical frequencies, with implications both for fundamental scientific questions and for applications such as fast, broadband spectroscopy. In this thesis, I describe advances in the generation of frequency combs without modelocking in platforms with smaller footprints and higher repetition rates, with the ultimate goal of bringing frequency combs to new applications in a chip-integrated package. I discuss two approaches for comb generation: parametric frequency conversion in Kerr microresonators and active electro-optic modulation of a continuous-wave laser. After introducing microresonator-based frequency combs (microcombs), I discuss two specific developments in microcomb technology: First, I describe a new, extremely reliable method for generation of soliton pulses through the use of a phase-modulated pump laser. This technique eliminates the dependence on initial conditions that was formerly a universal feature of these experiments, presenting a solution to a significant technical barrier to the practical application of microcombs. Second, I present observations of *soliton crystal* states with highly structured ‘fingerprint’ optical spectra that correspond to ordered pulse trains exhibiting crystallographic defects. These pulse trains arise through interaction of solitons with avoided mode-crossings in the resonator spectrum. I also discuss generation of Kerr soliton combs in the Fabry-Perot (FP) geometry, with a focus on the differences between the FP geometry and the ring geometry that has been the choice of most experimenters to date. Next, I discuss combs based on electro-optic modulation. I introduce the operational principle, and then describe the first self-referencing of a frequency comb of this kind and a proof-of-principle application experiment. Finally, I discuss a technique for reducing the repetition rate of a high repetition-rate frequency comb, which will be a necessary post-processing step for some applications.

Contents

A	Derivation of the Lugiato-Lefever equation from the nonlinear Schrodinger equation	1
A.1	<i>A posteriori</i> confirmation that $L_D \gg L$ and $L_{NL} \gg L$ for LLE solitons	4
A.2	Normalization of the Ikeda map	5
	References	6

Figures

Appendix A

Derivation of the Lugiato-Lefever equation from the nonlinear Schrodinger equation

Here we show how the Lugiato-Lefever equation can be obtained by modeling propagation in a high-finesse ring cavity with the nonlinear Schrodinger equation and periodically applying an operator that implements in-coupling and out-coupling, including the effects of the round-trip phase shift associated with the detuning of the pump laser from a cavity mode. To my knowledge, the derivation given here was first performed by Haelterman, Trillo, and Wabnitz [57]. We use the NLSE for a pulse of restricted bandwidth such that higher-order nonlinearities are unimportant, but this derivation may also be carried out using a generalized nonlinear Schrodinger equation to include higher-order effects (e.g. Raman and self-steepening) in the LLE. Our equation is:

$$\frac{\partial A}{\partial z} = -\frac{\alpha_\ell}{2} A + i\gamma|A|^2 A - i\frac{k''}{2} \frac{\partial^2 A}{\partial T^2}. \quad (\text{A.1})$$

This equation is ubiquitous in the study of pulse propagation in Kerr-nonlinear media, and a derivation of it is provided, for example, in Ref. [39]. As discussed in Sec. ??, it describes the evolution of a pulse envelope A in a ‘fast-time’ reference frame parametrized by T as it propagates in a Kerr-nonlinear medium, where the propagation distance is parametrized by the variable z . Here $\gamma = \frac{2\pi}{\lambda} \frac{n_2}{A_{eff}}$ is the nonlinear coefficient of the medium, where n_2 is the Kerr index, A_{eff} is the effective nonlinear mode area, λ the wavelength of the carrier wave, and $k'' = \frac{\partial^2}{\partial \omega^2} \frac{n_{eff}(\omega)\omega}{c}$ is the GVD parameter. Propagation loss described by the coefficient α_ℓ has been included in Eq. A.1, with α_ℓ the loss coefficient in power (i.e. $\partial P/\partial z = -\alpha_\ell P$, where $P = |A|^2$).

The dynamics in a ring resonator constructed of a Kerr medium can be described by evolving the field envelope A over a round trip of length L and then applying an operator that accounts for out-coupling of the circulating field A and in-coupling of a pump field A_{in} , as well as a round-trip phase shift ϕ_{RT} associated with the detuning of the carrier frequency from a cavity mode. This allows us to advance the field at the end of the n^{th} round trip $A_n(L, T)$ to the field $A_{n+1}(0, T)$ at the beginning of the $n + 1^{\text{th}}$ as:

$$A_{n+1}(0, T) = e^{i\phi_{RT}} \left(1 - \frac{T_{RT}}{2\tau_{ext}} \right) A_n(L, T) + \sqrt{\frac{T_{RT}}{\tau_{ext}}} A_{in}, \quad (\text{A.2})$$

where τ_{ext} describes in- and out-coupling as explained in Sec. ?? and $T_{RT} = L/v_g$ is the round-trip time. If we define an operator $G_L(A)$ that advances the field over a distance L according to Eq. A.1 as $A(z + L, T) = G_L(A)A(z, T)$, then we have:

$$A_{n+1}(0, T) = e^{i\phi_{RT}} \left(1 - \frac{T_{RT}}{2\tau_{ext}} \right) G_L[A_n(0, T)] A_n(0, T) + \sqrt{\frac{T_{RT}}{\tau_{ext}}} A_{in}. \quad (\text{A.3})$$

The description of the field envelope in a Kerr-nonlinear ring cavity according to Eq. A.3 through iterated evolution according to the NLSE and then application of the in- and out-coupling operator is referred to as an Ikeda map [148]. We obtain the LLE by assuming that the operator $G_L(A) \approx 1$, that is, that the field does not evolve much over the round-trip length. This is equivalent to the assumption that the cavity length L is much less than the loss, nonlinear, and dispersion length scales $L_\ell = 1/\alpha_\ell$, $L_{NL} = 1/\gamma P_0$, and $L_D = T_0^2/|k''|$ over which the terms on the right-hand side of Eq. A.1 lead to appreciable evolution of the pulse envelope [39]. Here P_0 and T_0 are the peak power and temporal width, respectively, of a localized excitation in the pulse envelope A .

We can write the operator G_L explicitly as:

$$G_L(A) = \left[1 + L \left(-\alpha_\ell/2 + i\gamma|A|^2 - i\frac{k''}{2} \frac{\partial^2}{\partial T^2} \right) \right]. \quad (\text{A.4})$$

We assume that each term in this operator besides the identity term is small. If we note that the round-trip phase shift ϕ_{RT} must also be small in a high-finesse cavity for appreciable build-up to occur, then we can expand the first term on the right-hand side of Eq. A.3 and retain only first

order terms to find:

$$A_{n+1}(0, T) = \left(1 - \frac{T_{RT}}{2\tau_{ext}} + i\phi_{RT} - \frac{L\alpha_\ell}{2} + iL\gamma|A|^2 - iL\frac{k''}{2}\frac{\partial^2}{\partial T^2} \right) A_n(0, T) + \sqrt{\frac{T_{RT}}{\tau_{ext}}} A_{in}. \quad (\text{A.5})$$

By replacing n with the slow time $t = nT_{RT}$ and allowing t to vary continuously we arrive at a Lugiato-Lefever equation, albeit in a different form from the one presented in Eq. ??:

$$T_{RT}\frac{\partial A}{\partial t} = \left(-T_{RT}/2\tau_{ext} + i\phi_{RT} - L\alpha_\ell/2 + iL\gamma|A|^2 - iL\frac{k''}{2}\frac{\partial^2}{\partial T^2} \right) A + \sqrt{\frac{T_{RT}}{\tau_{ext}}} A_{in}. \quad (\text{A.6})$$

To recast this equation in the standard form used in the body of this thesis, we first pass to the normalized temporal and spatial variables τ and θ and the parameters α and β_2 . We note that $L\alpha_\ell/2 = T_{RT}/2\tau_{int}$ (as each describes the intrinsic loss over one round trip), and we define $\theta = 2\pi T/T_{RT}$, so that $\frac{\partial^2}{\partial T^2} = \left(\frac{2\pi}{T_{RT}} \right)^2 \frac{\partial^2}{\partial \theta^2}$. We divide by T_{RT} and obtain:

$$\frac{\partial A}{\partial t} = -\frac{\Delta\omega}{2}A + \frac{1}{T_{RT}} (i\phi_{RT} + iL\gamma|A|^2) A - i\frac{L}{T_{RT}} \left(\frac{2\pi}{T_{RT}} \right)^2 \frac{k''}{2} \frac{\partial^2 A}{\partial \theta^2} + A_{in}/\sqrt{T_{RT}\tau_{ext}} \quad (\text{A.7})$$

Dividing this by $\Delta\omega/2$ brings us to the normalized temporal variable $\tau = t/2\tau_{ph} = \Delta\omega t/2$. The quantity ϕ_{RT}/T_{RT} is exactly the frequency detuning $\sigma = \omega_p - \omega_0$ between the pump laser and the cavity resonance frequency, so that the quantity $2\phi_{RT}/T_{RT}\Delta\omega$ that results from division by $\Delta\omega/2$ is simply equal to the normalized detuning term $-\alpha = 2\sigma/\Delta\omega$. Further, recalling from Sec. ?? that $D_1 = 2\pi/T_{RT} = 2\pi v_g/L$ and $D_2 = -D_1^2 v_g k''$, we have:

$$\frac{L}{T_{RT}} \left(\frac{2\pi}{T_{RT}} \right)^2 \frac{k''}{2} = -D_2/2. \quad (\text{A.8})$$

Using the definition of the normalized dispersion for the LLE $\beta_2 = -2D_2/\Delta\omega$ and combining these relations, we have:

$$\frac{\partial A}{\partial \tau} = -(1 + i\alpha)A + i\frac{2L\gamma}{T_{RT}\Delta\omega}|A|^2 A - i\frac{\beta_2}{2}\frac{\partial^2 A}{\partial \theta^2} + \sqrt{\frac{4\Delta\omega_{ext}}{T_{RT}\Delta\omega^2}} A_{in}, \quad (\text{A.9})$$

where we recall the definition $\Delta\omega_{ext} = 1/\tau_{ext}$. By defining $\psi = \sqrt{\frac{2L\gamma}{T_{RT}\Delta\omega}} A$, we arrive at the LLE as presented in Eq. ??:

$$\frac{\partial \psi}{\partial \tau} = -(1 + i\alpha)\psi + i|\psi|^2\psi - i\frac{\beta_2}{2}\frac{\partial^2 \psi}{\partial \theta^2} + F. \quad (\text{A.10})$$

Here the pump term has been normalized as:

$$F = A_{in} \sqrt{\frac{8L\gamma\Delta\omega_{ext}}{T_{RT}^2\Delta\omega^3}} \quad (\text{A.11})$$

$$= A_{in} \sqrt{\frac{8g_0\Delta\omega_{ext}}{\Delta\omega^3} \frac{1}{\hbar\omega_p}}, \quad (\text{A.12})$$

with

$$g_0 = n_2 c \hbar \omega_p^2 / n_g^2 V_0 \quad (\text{A.13})$$

as defined in Sec. ??, where $V_0 = LA_{eff}$. Assuming that A_{in} is real simply fixes the phase of ψ , which is otherwise arbitrary. With this assumption we have $A_{in} = \sqrt{P_{in}}$, and we recover the normalization from Sec. ??:

$$F = \sqrt{\frac{8g_0\Delta\omega_{ext}}{\Delta\omega^3} \frac{P_{in}}{\hbar\omega_p}}. \quad (\text{A.14})$$

A.1 *A posteriori* confirmation that $L_D \gg L$ and $L_{NL} \gg L$ for LLE solitons

The analytical approximation to the soliton solution of the LLE presented in Eq. ?? has θ -width $\sqrt{\frac{-\beta}{2\alpha}}$, and therefore temporal width $T_0 = \frac{T_{RT}}{2\pi} \sqrt{\frac{-\beta}{2\alpha}}$, and has approximate peak power 2α . Using the expressions presented above, one can calculate that for an LLE soliton the nonlinear length $L_{NL} = 1/\gamma P_0$ and the dispersion length $L_D = T_0/|k''|$ are the same, and depend on the detuning α :

$$L_{NL} = L_D = \frac{v_g \tau_{ph}}{\alpha}. \quad (\text{A.15})$$

Using the definition of the cavity finesse $\mathcal{F} = 2\pi\tau_{ph}/T_{RT}$, we find that the ratio of these characteristic lengths to the cavity length is:

$$\frac{L_{NL}}{L} = \frac{L_D}{L} = \frac{\mathcal{F}}{2\pi\alpha}, \quad (\text{A.16})$$

and therefore that the assumption $G_L \approx 1$ clearly holds for LLE solitons, since $\mathcal{F} \gg 1$ for a high-finesse cavity and α is of order 1 or 10.

A.2 Normalization of the Ikeda map

For direct comparison of numerical results between the Ikeda map and the LLE, and also possibly for future work involving simulations of Kerr-combs outside of the high-finesse limit, it is useful to normalize the Ikeda map given in Eq. A.3 in the same way that the LLE is normalized. To conduct an Ikeda map calculation that corresponds to the LLE with parameters α , β_2 , and F , it is natural to describe the Ikeda-map system by specifying two additional parameters: the resonator finesse \mathcal{F} and the coupling ratio $\eta = \Delta\omega_{ext}/\Delta\omega$. Then the following representations of the operators in Eq. A.3 can be used:

$$1 - \frac{T_{RT}}{2\tau_{ext}} = 1 - \frac{\pi\eta}{\mathcal{F}}, \quad (\text{A.17})$$

$$\sqrt{\frac{T_{RT}}{\tau_{ext}}} = \sqrt{\frac{2\pi\eta}{\mathcal{F}}}, \quad (\text{A.18})$$

$$e^{i\phi_{RT}} = e^{-i\frac{\pi}{\mathcal{F}}\alpha}, \quad (\text{A.19})$$

$$\frac{L\alpha_\ell}{2} = \frac{T_{RT}}{2\tau_{int}} = \frac{\pi(1-\eta)}{\mathcal{F}}. \quad (\text{A.20})$$

Using a normalized distance $s = z \cdot \pi/\mathcal{F}L$ we define the operator G_1 that advances the field $\psi(s, \theta)$ a distance $\Delta s = \pi/\mathcal{F}$ as $\psi(s + \pi/\mathcal{F}, \theta) = G_1\psi(s, \theta)$ according to a nonlinear Schrodinger equation of the form:

$$\frac{\partial\psi}{\partial s} = -(1-\eta)\psi + i|\psi|^2\psi - i\frac{\beta_2}{2}\frac{\partial^2\psi}{\partial\theta^2}, \quad (\text{A.21})$$

where in general the operation is now performed continuously and not approximated as a single step as in the operator G_L above. The Ikeda map that is equivalent to the LLE with parameters α , β_2 and F in the limit of high finesse is:

$$\psi_{n+1}(0, \theta) = e^{-i\frac{\pi}{\mathcal{F}}\alpha} \left(1 - \frac{\pi\eta}{\mathcal{F}}\right) G_1[\psi_n(0, \theta)] \psi_n(0, \theta) + \sqrt{\frac{\pi}{2\mathcal{F}\eta}} F. \quad (\text{A.22})$$

References

- [1] S. A. Diddams, D. J. Jones, J. Ye, S. T. Cundiff, J. L. Hall, J. K. Ranka, R. S. Windeler, R. Holzwarth, T. Udem, and T. W. Hänsch. Direct link between microwave and optical frequencies with a 300 THz femtosecond laser comb. *Physical Review Letters*, 84 (22), **2000**, 5102–5105. DOI: 10.1103/PhysRevLett.84.5102.
- [2] D. J. Jones, S. A. Diddams, J. K. Ranka, A. Stentz, R. S. Windeler, J. L. Hall, and S. T. Cundiff. Carrier-Envelope Phase Control of Femtosecond Mode-Locked Lasers and Direct Optical Frequency Synthesis. *Science*, 288 (5466), **2000**, 635–639.
- [3] T. Udem, R. Holzwarth, and T. W. Hänsch. Optical frequency metrology. *Nature*, 416 (6877), **2002**, 233–237. DOI: 10.1038/416233a.
- [4] J. L. Hall. Nobel lecture: Defining and measuring optical frequencies. *Reviews of Modern Physics*, 78 (4), **2006**, 1279–1295. DOI: 10.1103/RevModPhys.78.1279.
- [5] T. W. Hänsch. Nobel lecture: Passion for precision. *Reviews of Modern Physics*, 78 (4), **2006**, 1297–1309. DOI: 10.1103/RevModPhys.78.1297.
- [6] J. K. Ranka, R. S. Windeler, and A. J. Stentz. Visible continuum generation in airsilica microstructure optical fibers with anomalous dispersion at 800 nm. *Optics Letters*, 25 (1), **2000**, 25. DOI: 10.1364/OL.25.000025.
- [7] S. A. Diddams, T. Udem, J. C. Bergquist, E. A. Curtis, R. E. Drullinger, L. Hollberg, W. M. Itano, W. D. Lee, C. W. Oates, K. R. Vogel, and D. J. Wineland. An Optical Clock Based on a Single Trapped 199 Hg⁺ Ion. *Science (New York, N.Y.)*, 293, **2001**, 825–828. DOI: 10.1126/science.1061171.
- [8] T. M. Fortier, M. S. Kirchner, F. Quinlan, J. Taylor, J. C. Bergquist, T. Rosenband, N. Lemke, A. Ludlow, Y. Jiang, C. W. Oates, and S. A. Diddams. Generation of ultrastable microwaves via optical frequency division. *Nature Photonics*, 5 (7), **2011**, 425–429. DOI: 10.1038/nphoton.2011.121. arXiv: 1101.3616.
- [9] S. A. Diddams, L. Hollberg, and V. Mbele. Molecular fingerprinting with the resolved modes of a femtosecond laser frequency comb. *Nature*, 445 (7128), **2007**, 627–630. DOI: 10.1038/nature05524.
- [10] I. Coddington, N. Newbury, and W. Swann. Dual-comb spectroscopy. *Optica*, 3 (4), **2016**, 414–426. DOI: 10.1364/OPTICA.3.000414.

- [11] S. T. Cundiff and A. M. Weiner. Optical arbitrary waveform generation. *Nature Photonics*, 4 (11), **2010**, 760–766. DOI: 10.1038/nphoton.2010.196.
- [12] T. Steinmetz, T. Wilken, C. Araujo-Hauck, R. Holzwarth, T. W. Hänsch, L. Pasquini, A. Manescau, S. D’Odorico, M. T. Murphy, T. Kentischer, W. Schmidt, and T. Udem. Laser frequency combs for astronomical observations. *Science*, 321 (5894), **2008**, 1335–7. DOI: 10.1126/science.1161030.
- [13] B. R. Washburn, S. A. Diddams, N. R. Newbury, J. W. Nicholson, M. F. Yan, and C. G. Jørgensen. Phase-locked, erbium-fiber-laser-based frequency comb in the near infrared. *Optics Letters*, 29 (3), **2004**, 250–252. DOI: 10.1364/OL.29.000250.
- [14] C. Gohle, T. Udem, M. Herrmann, J. Rauschenberger, R. Holzwarth, H. A. Schuessler, F. Krausz, and T. W. Hänsen. A frequency comb in the extreme ultraviolet. *Nature*, 436 (7048), **2005**, 234–237. DOI: 10.1038/nature03851.
- [15] S. A. Diddams. The evolving optical frequency comb [Invited]. *Journal of the Optical Society of America B*, 27 (11), **2010**, B51–B62. DOI: 10.1364/JOSAB.27.000B51.
- [16] J. Faist, G. Villares, G. Scalari, M. Rosch, C. Bonzon, A. Hugi, and M. Beck. Quantum Cascade Laser Frequency Combs. *Nanophotonics*, 5 (2), **2016**, 272–291. DOI: 10.1515/nanoph-2016-0015. arXiv: 1510.09075.
- [17] D. T. Spencer, T. Drake, T. C. Briles, J. Stone, L. C. Sinclair, C. Fredrick, Q. Li, D. Westly, B. R. Ilic, A. Bluestone, N. Volet, T. Komljenovic, L. Chang, S. H. Lee, D. Y. Oh, T. J. Kippenberg, E. Norberg, L. Theogarajan, M.-g. Suh, K. Y. Yang, H. P. Martin, K. Vahala, N. R. Newbury, K. Srinivasan, J. E. Bowers, S. A. Diddams, and S. B. Papp. An optical-frequency synthesizer using integrated photonics. *Nature*, 557, **2018**, 81–85. DOI: 10.1038/s41586-018-0065-7.
- [18] T. C. Briles, J. R. Stone, T. E. Drake, D. T. Spencer, C. Frederick, Q. Li, D. A. Westly, B. R. Illic, K. Srinivasan, S. A. Diddams, and S. B. Papp. Kerr-microresonator solitons for accurate carrier-envelope-frequency stabilization. *arXiv*, **2017**, 1711.06251. URL: <http://arxiv.org/abs/1711.06251>. arXiv: 1711.06251.
- [19] R. W. Boyd. **Nonlinear Optics**. San Diego, CA: Elsevier, 2003.
- [20] T. M. Fortier, D. J. Jones, and S. T. Cundiff. Phase stabilization of an octave-spanning Ti:sapphire laser. *Opt. Lett.*, 28 (22), **2003**, 2198–2200. DOI: 10.1364/OL.28.002198.
- [21] D. R. Carlson, D. D. Hickstein, A. Lind, S. Droste, D. Westly, N. Nader, I. Coddington, N. R. Newbury, K. Srinivasan, S. A. Diddams, and S. B. Papp. Self-referenced frequency combs using high-efficiency silicon-nitride waveguides. 42 (12), **2017**, 2314–2317. DOI: 10.1364/OL.42.002314. arXiv: 1704.03909.
- [22] D. S. Hum and M. M. Fejer. Quasi-phasematching. *Comptes Rendus Physique*, 8 (2), **2007**, 180–198. DOI: 10.1016/j.crhy.2006.10.022.

- [23] P Del’Haye, A Schliesser, O Arcizet, T Wilken, R Holzwarth, and T. J. Kippenberg. Optical frequency comb generation from a monolithic microresonator. *Nature*, 450 (7173), **2007**, 1214–1217. DOI: 10.1038/nature06401.
- [24] T. J. Kippenberg, R Holzwarth, and S. A. Diddams. Microresonator-Based Optical Frequency Combs. *Science (New York, N.Y.)*, 332 (6029), **2011**, 555–559. DOI: 10.1126/science.1193968.
- [25] A. A. Savchenkov, A. B. Matsko, and L Maleki. On Frequency Combs in Monolithic Resonators. *Nanophotonics*, 5, **2016**, 363–391. DOI: 10.1515/nanoph-2016-0031.
- [26] Y. K. Chembo. Kerr optical frequency combs: Theory, applications and perspectives. *Nanophotonics*, 5 (2), **2016**, 214–230. DOI: 10.1515/nanoph-2016-0013.
- [27] A. Pasquazi, M. Peccianti, L. Razzari, D. J. Moss, S. Coen, M. Erkintalo, Y. K. Chembo, T. Hansson, S. Wabnitz, P. Del’Haye, X. Xue, A. M. Weiner, and R. Morandotti. Micro-combs: A novel generation of optical sources. *Physics Reports*, 729, **2017**, 1–81. DOI: 10.1016/j.physrep.2017.08.004.
- [28] H. Lee, T. Chen, J. Li, K. Y. Yang, S. Jeon, O. Painter, and K. J. Vahala. Chemically etched ultrahigh-Q wedge-resonator on a silicon chip. *Nature Photonics*, 6 (6), **2012**, 369–373. DOI: 10.1038/nphoton.2012.109. arXiv: 1112.2196.
- [29] X. Yi, Q.-F. Yang, K. Y. Yang, M.-G. Suh, and K. Vahala. Soliton frequency comb at microwave rates in a high-Q silica microresonator. *Optica*, 2 (12), **2015**, 1078–1085.
- [30] P. Del’Haye, S. A. Diddams, and S. B. Papp. Laser-machined ultra-high-Q microrod resonators for nonlinear optics. *Applied Physics Letters*, 102, **2013**, 221119.
- [31] W Liang, A. A. Savchenkov, A. B. Matsko, V. S. Ilchenko, D Seidel, and L Maleki. Generation of near-infrared frequency combs from a MgF₂ whispering gallery mode resonator. *Optics Letters*, 36 (12), **2011**, 2290–2292. DOI: 10.1364/OL.36.002290.
- [32] A. a. Savchenkov, A. B. Matsko, V. S. Ilchenko, I. Solomatine, D. Seidel, and L. Maleki. Tunable optical frequency comb with a crystalline whispering gallery mode resonator. *Physical Review Letters*, 101 (9), **2008**, 1–4. DOI: 10.1103/PhysRevLett.101.093902. arXiv: 0804.0263.
- [33] Y. Okawachi, K. Saha, J. S. Levy, Y. H. Wen, M. Lipson, and A. L. Gaeta. Octave-spanning frequency comb generation in a silicon nitride chip. *Optics Letters*, 36 (17), **2011**, 3398–3400. DOI: 10.1364/OL.36.003398. arXiv: 1107.5555.
- [34] D. J. Moss, R Morandotti, A. L. Gaeta, and M Lipson. New CMOS-compatible platforms based on silicon nitride and Hydex for nonlinear optics. *Nature Photonics*, 7 (July), **2013**, 597–607. DOI: 10.1038/nphoton.2013.183.
- [35] D. Braje, L. Hollberg, and S. Diddams. Brillouin-Enhanced Hyperparametric Generation of an Optical Frequency Comb in a Monolithic Highly Nonlinear Fiber Cavity Pumped by a cw Laser. *Physical Review Letters*, 102 (19), **2009**, 193902. DOI: 10.1103/PhysRevLett.102.193902.

- [36] E. Obrzud, S. Lecomte, and T. Herr. Temporal solitons in microresonators driven by optical pulses. *Nature Photonics*, 11 (August), **2017**, 600–607. DOI: 10.1038/nphoton.2017.140. arXiv: 1612.08993.
- [37] V. S. Ilchenko and A. B. Matsko. Optical resonators with whispering-gallery modes - Part II: Applications. *IEEE Journal on Selected Topics in Quantum Electronics*, 12 (1), **2006**, 15–32. DOI: 10.1109/JSTQE.2005.862943.
- [38] K. Y. Yang, K. Beha, D. C. Cole, X. Yi, P. Del’Haye, H. Lee, J. Li, D. Y. Oh, S. A. Diddams, S. B. Papp, and K. J. Vahala. Broadband dispersion-engineered microresonator on a chip. *Nature Photonics*, 10 (March), **2016**, 316–320. DOI: 10.1038/nphoton.2016.36.
- [39] G. P. Agrawal. **Nonlinear Fiber Optics**. 4th. Burlington, MA: Elsevier, 2007 (cited on pages 1, 2).
- [40] M. L. Calvo and V. Lakshminarayanan, eds. **Optical Waveguides: From Theory to Applied Technologies**. Boca Raton, FL: Taylor & Francis, 2007.
- [41] A. N. Oraevsky. Whispering-gallery waves. *Quantum Electronics*, 32 (42), **2002**, 377–400. DOI: 10.1070/QE2001v031n05ABEH002205. arXiv: arXiv:1011.1669v3.
- [42] H. A. Haus. **Waves and Fields in Optoelectronics**. Englewood Cliffs: Prentice-Hall, 1984.
- [43] J. C. Knight, G. Cheung, F. Jacques, and T. A. Birks. Phase-matched excitation of whispering-gallery-mode resonances by a fiber taper. *Optics Letters*, 22 (15), **1997**, 1129. DOI: 10.1364/OL.22.001129.
- [44] S. M. Spillane, T. J. Kippenberg, O. J. Painter, and K. J. Vahala. Ideality in a Fiber-Taper-Coupled Microresonator System for Application to Cavity Quantum Electrodynamics. *Physical review letters*, 91 (4), **2003**, 043902. DOI: 10.1103/PhysRevLett.91.043902.
- [45] E. Shah Hosseini, S. Yegnanarayanan, A. H. Atabaki, M. Soltani, and A. Adibi. Systematic design and fabrication of high-Q single-mode pulley-coupled planar silicon nitride microdisk resonators at visible wavelengths. *Optics Express*, 18 (3), **2010**, 2127. DOI: 10.1364/OE.18.002127.
- [46] T. Carmon, L. Yang, and K. J. Vahala. Dynamical thermal behavior and thermal self-stability of microcavities. *Optics Express*, 12 (20), **2004**, 4742–4750. URL: <http://www.ncbi.nlm.nih.gov/pubmed/19484026><http://www.opticsinfobase.org/oe/abstract.cfm?uri=oe-12-20-4742>.
- [47] R. del Coso and J. Solis. Relation between nonlinear refractive index and third-order susceptibility in absorbing media. *Journal of the Optical Society of America B*, 21 (3), **2004**, 640. DOI: 10.1364/JOSAB.21.000640.
- [48] T. Kippenberg, S. Spillane, and K. Vahala. Kerr-Nonlinearity Optical Parametric Oscillation in an Ultrahigh-Q Toroid Microcavity. *Physical Review Letters*, 93 (8), **2004**, 083904. DOI: 10.1103/PhysRevLett.93.083904.

- [49] A. A. Savchenkov, A. B. Matsko, D. Strekalov, M. Mohageg, V. S. Ilchenko, and L. Maleki. Low threshold optical oscillations in a whispering gallery mode CaF₂ resonator. *Physical Review Letters*, 93 (24), **2004**, 2–5. DOI: 10.1103/PhysRevLett.93.243905.
- [50] I. H. Agha, Y. Okawachi, M. A. Foster, J. E. Sharping, and A. L. Gaeta. Four-wave-mixing parametric oscillations in dispersion-compensated high-Q silica microspheres. *Physical Review A - Atomic, Molecular, and Optical Physics*, 76 (4), **2007**, 1–4. DOI: 10.1103/PhysRevA.76.043837.
- [51] T. Herr, V. Brasch, J. D. Jost, C. Y. Wang, N. M. Kondratiev, M. L. Gorodetsky, and T. J. Kippenberg. Temporal solitons in optical microresonators. *arXiv*, **2012**, 1211.0733. DOI: 10.1038/nphoton.2013.343. arXiv: 1211.0733.
- [52] T. Herr, V. Brasch, J. D. Jost, C. Y. Wang, N. M. Kondratiev, M. L. Gorodetsky, and T. J. Kippenberg. Temporal solitons in optical microresonators. *Nature Photonics*, 8 (2), **2014**, 145–152. DOI: 10.1109/CLEOE-IQEC.2013.6801769. arXiv: 1211.0733.
- [53] F. Leo, S. Coen, P. Kockaert, S.-P. Gorza, P. Emplit, and M. Haelterman. Temporal cavity solitons in one-dimensional Kerr media as bits in an all-optical buffer. *Nature Photonics*, 4 (7), **2010**, 471–476. DOI: 10.1038/nphoton.2010.120.
- [54] T. Herr, K. Hartinger, J. Riemensberger, C. Y. Wang, E. Gavartin, R. Holzwarth, M. L. Gorodetsky, and T. J. Kippenberg. Universal formation dynamics and noise of Kerr-frequency combs in microresonators. *Nature Photonics*, 6 (7), **2012**, 480–487. DOI: 10.1038/nphoton.2012.127.
- [55] Y. K. Chembo and C. R. Menyuk. Spatiotemporal Lugiato-Lefever formalism for Kerr-comb generation in whispering-gallery-mode resonators. *Physical Review A*, 87, **2013**, 053852. DOI: 10.1103/PhysRevA.87.053852.
- [56] S. Coen, H. G. Randle, T. Sylvestre, and M. Erkintalo. Modeling of octave-spanning Kerr frequency combs using a generalized mean-field Lugiato-Lefever model. *Optics letters*, 38 (1), **2013**, 37–39. URL: <http://www.ncbi.nlm.nih.gov/pubmed/23282830>.
- [57] M. Haelterman, S. Trillo, and S. Wabnitz. Dissipative modulation instability in a nonlinear dispersive ring cavity. *Optics Communications*, 91 (5-6), **1992**, 401–407. DOI: 10.1016/0030-4018(92)90367-Z (cited on page 1).
- [58] T. Hansson, M. Bernard, and S. Wabnitz. Modulational Instability of Nonlinear Polarization Mode Coupling in Microresonators. 35 (4), **2018**. URL: <https://arxiv.org/pdf/1802.04535.pdf>. arXiv: arXiv:1802.04535v1.
- [59] Y. K. Chembo, I. S. Grudinin, and N. Yu. Spatiotemporal dynamics of Kerr-Raman optical frequency combs. *Physical Review A*, 92 (4), **2015**, 4. DOI: 10.1103/PhysRevA.92.043818.
- [60] C. Godey, I. V. Balakireva, A. Coillet, and Y. K. Chembo. Stability analysis of the spatiotemporal Lugiato-Lefever model for Kerr optical frequency combs in the anomalous and normal dispersion regimes. *Physical Review A*, 89 (6), **2014**, 063814. DOI: 10.1103/PhysRevA.89.063814.

- [61] I. V. Barashenkov and Y. S. Smirnov. Existence and stability chart for the ac-driven, damped nonlinear Schrödinger solitons. *Physical Review E - Statistical Physics, Plasmas, Fluids, and Related Interdisciplinary Topics*, 54 (5), **1996**, 5707–5725. DOI: 10.1103/PhysRevE.54.5707.
- [62] A Coillet and Y. K. Chembo. Routes to spatiotemporal chaos in Kerr optical frequency combs. *Chaos*, 24 (1), **2014**, 5. DOI: 10.1063/1.4863298. arXiv: arXiv:1401.0927v1.
- [63] L. A. Lugiato and R Lefever. Spatial Dissipative Structures in Passive Optical Systems. *Physical Review Letters*, 58 (21), **1987**, 2209–2211.
- [64] L. Lugiato and R Lefever. Diffraction stationary patterns in passive optical systems. *Interaction of Radiation with Matter*, **1987**.
- [65] W. H. Renninger and P. T. Rakich. Closed-form solutions and scaling laws for Kerr frequency combs. *Scientific Reports*, 6 (1), **2016**, 24742. DOI: 10.1038/srep24742. arXiv: 1412.4164.
- [66] J. S. Russell. Report on Waves. *Fourteenth meeting of the British Association for the Advancement of Science*, **1844**, 311–390.
- [67] M. Brambilla, L. A. Lugiato, F. Prati, L. Spinelli, and W. J. Firth. Spatial soliton pixels in semiconductor devices. *Physical Review Letters*, 79 (11), **1997**, 2042–2045. DOI: 10.1103/PhysRevLett.79.2042.
- [68] S. Minardi, F. Eilenberger, Y. V. Kartashov, A. Szameit, U. Röpke, J. Kobelke, K. Schuster, H. Bartelt, S. Nolte, L. Torner, F. Lederer, A. Tünnermann, and T. Pertsch. Three-dimensional light bullets in arrays of waveguides. *Physical Review Letters*, 105 (26), **2010**, 1–4. DOI: 10.1103/PhysRevLett.105.263901. arXiv: 1101.0734.
- [69] F. X. Kärtner, I. D. Jung, and U. Keller. Soliton mode-locking with saturable absorbers. *IEEE Journal on Selected Topics in Quantum Electronics*, 2 (3), **1996**, 540–556. DOI: 10.1109/2944.571754.
- [70] P. Grelu and N. Akhmediev. Dissipative solitons for mode-locked lasers. *Nature Photonics*, 6 (February), **2012**, 84–92. DOI: 10.1109/PGC.2010.5706017.
- [71] L. F. Mollenauer and J. P. Gordon. **Solitons in Optical Fibers**. Academic Press, 2006, p. 296.
- [72] A. Hasegawa and Y. Kodama. **Solitons in Optical Communications**. Academic Press, 1995.
- [73] H. A. Haus and W. S. Wong. Solitons in optical communications. *Reviews of Modern Physics*, 68 (2), **1996**, 423–444. DOI: 10.1103/RevModPhys.68.423.
- [74] S. Coen and M. Erkintalo. Universal scaling laws of Kerr frequency combs. *Optics letters*, 38 (11), **2013**, 1790–1792. DOI: 10.1364/OL.38.001790. arXiv: arXiv:1303.7078v1.
- [75] H. Guo, M. Karpov, E. Lucas, A. Kordts, M. H. Pfeiffer, V. Brasch, G. Lihachev, V. E. Lobanov, M. L. Gorodetsky, and T. J. Kippenberg. Universal dynamics and deterministic switching of dissipative Kerr solitons in optical microresonators. *Nature Physics*, 13 (1), **2017**, 94–102. DOI: 10.1038/nphys3893. arXiv: 1601.05036.

- [76] N. J. Zabusky and M. D. Kruskal. Interaction of "solitons" in a collisionless plasma and the recurrence of initial states. *Physical Review Letters*, 15 (6), **1965**, 240.
- [77] J. P. Gordon. Interaction forces among solitons in optical fibers. *Optics Letters*, 8 (11), **1983**, 596. DOI: 10.1364/OL.8.000596.
- [78] B. A. Malomed. Bound solitons in the nonlinear Schrodinger-Ginzburg-Landau equation. *Physical Review A*, 44 (10), **1991**, 6954–6957. DOI: 10.1103/PhysRevA.44.6954.
- [79] J. K. Jang, M. Erkintalo, S. G. Murdoch, and S. Coen. Ultraweak long-range interactions of solitons observed over astronomical distances. *Nature Photonics*, 7 (8), **2013**, 657–663. DOI: 10.1038/nphoton.2013.157. arXiv: arXiv:1305.6670v1.
- [80] P. Parra-Rivas, D. Gomila, P. Colet, and L. Gelens. Interaction of solitons and the formation of bound states in the generalized Lugiato-Lefever equation. *European Physical Journal D*, 71 (7), **2017**, 198. DOI: 10.1140/epjd/e2017-80127-5. arXiv: arXiv:1705.02619v1.
- [81] Y. Wang, F. Leo, J. Fatome, M. Erkintalo, S. G. Murdoch, and S. Coen. Universal mechanism for the binding of temporal cavity solitons, **2017**, 1–10. URL: <http://arxiv.org/abs/1703.10604>. arXiv: 1703.10604.
- [82] V. Brasch, T. Herr, M. Geiselmann, G. Lihachev, M. H. P. Pfeiffer, M. L. Gorodetsky, and T. J. Kippenberg. Photonic chip-based optical frequency comb using soliton Cherenkov radiation. *Science*, 351 (6271), **2016**, 357. DOI: 10.1364/CLEO_SI.2015.STh4N.1. arXiv: 1410.8598.
- [83] J. R. Stone, T. C. Briles, T. E. Drake, D. T. Spencer, D. R. Carlson, S. A. Diddams, and S. B. Papp. Thermal and Nonlinear Dissipative-Soliton Dynamics in Kerr Microresonator Frequency Combs. *arXiv*, **2017**, 1708.08405. URL: <http://arxiv.org/abs/1708.08405>. arXiv: 1708.08405.
- [84] V. E. Lobanov, G. V. Lihachev, N. G. Pavlov, A. V. Cherenkov, T. J. Kippenberg, and M. L. Gorodetsky. Harmonization of chaos into a soliton in Kerr frequency combs. *Optics Express*, 24 (24), **2016**, 27382. DOI: 10.1126/science.aah4243. arXiv: 1607.08222.
- [85] C. Joshi, J. K. Jang, K. Luke, X. Ji, S. A. Miller, A. Klenner, Y. Okawachi, M. Lipson, and A. L. Gaeta. Thermally controlled comb generation and soliton modelocking in microresonators. *Optics Letters*, 41 (11), **2016**, 2565–2568. DOI: 10.1364/OL.41.002565. arXiv: 1603.08017.
- [86] W. Wang, Z. Lu, W. Zhang, S. T. Chu, B. E. Little, L. Wang, X. Xie, M. Liu, Q. Yang, L. Wang, J. Zhao, G. Wang, Q. Sun, Y. Liu, Y. Wang, and W. Zhao. Robust soliton crystals in a thermally controlled microresonator. *Optics Letters*, 43 (9), **2018**, 2002–2005. DOI: 10.1364/OL.43.002002.
- [87] J. K. Jang, M. Erkintalo, S. G. Murdoch, and S. Coen. Writing and erasing of temporal cavity solitons by direct phase modulation of the cavity driving field. *Optics Letters*, 40 (20), **2015**, 4755–4758. DOI: 10.1364/OL.40.004755. arXiv: 1501.05289.

- [88] J. K. Jang, M. Erkintalo, S. Coen, and S. G. Murdoch. Temporal tweezing of light through the trapping and manipulation of temporal cavity solitons. *Nature Communications*, 6, **2015**, 7370. DOI: 10.1038/ncomms8370. arXiv: 1410.4836.
- [89] Y. Wang, B. Garbin, F. Leo, S. Coen, M. Erkintalo, and S. G. Murdoch. Writing and Erasure of Temporal Cavity Solitons via Intensity Modulation of the Cavity Driving Field. *arXiv*, **2018**, 1802.07428. arXiv: 1802.07428.
- [90] S. B. Papp, K. Beha, P. Del’Haye, F. Quinlan, H. Lee, K. J. Vahala, and S. A. Diddams. Microresonator frequency comb optical clock. *Optica*, 1 (1), **2014**, 10–14. DOI: 10.1364/OPTICA.1.000010. arXiv: 1309.3525.
- [91] M. G. Suh, Q. F. Yang, K. Y. Yang, X. Yi, and K. J. Vahala. Microresonator soliton dual-comb spectroscopy. *Science*, 354 (6312), **2016**, 1–5. DOI: 10.1126/science.aah6516. arXiv: 1607.08222.
- [92] P. Marin-Palomo, J. N. Kemal, M. Karpov, A. Kordts, J. Pfeifle, M. H. Pfeiffer, P. Trocha, S. Wolf, V. Brasch, M. H. Anderson, R. Rosenberger, K. Vijayan, W. Freude, T. J. Kippenberg, and C. Koos. Microresonator-based solitons for massively parallel coherent optical communications. *Nature*, 546 (7657), **2017**, 274–279. DOI: 10.1038/nature22387. arXiv: 1610.01484.
- [93] J. D. Jost, T. Herr, C. Lecaplain, V. Brasch, M. H. P. Pfeiffer, and T. J. Kippenberg. Counting the cycles of light using a self-referenced optical microresonator. *Optica*, 2 (8), **2015**, 706–711. DOI: 10.1364/OPTICA.2.000706. arXiv: 1411.1354.
- [94] P. Del’Haye, A. Coillet, T. Fortier, K. Beha, D. C. Cole, K. Y. Yang, H. Lee, K. J. Vahala, S. B. Papp, and S. A. Diddams. Phase-coherent microwave-to-optical link with a self-referenced microcomb. *Nature Photonics*, 10 (June), **2016**, 1–5. DOI: 10.1038/nphoton.2016.105.
- [95] V. Brasch, E. Lucas, J. D. Jost, M. Geiselmann, and T. J. Kippenberg. Self-referenced photonic chip soliton Kerr frequency comb. *Light: Science & Applications*, 6 (1), **2017**, e16202. DOI: 10.1038/lsa.2016.202. arXiv: 1605.02801.
- [96] H. Taheri, A. A. Eftekhar, K. Wiesenfeld, and A. Adibi. Soliton formation in whispering-gallery-mode resonators via input phase modulation. *IEEE Photonics Journal*, 7 (2), **2015**, 2200309. DOI: 10.1109/JPHOT.2015.2416121.
- [97] M. Zajnulina, M. Böhm, D. Bodenmüller, K. Blow, J. C. Boggio, A. Rieznik, and M. Roth. Characteristics and stability of soliton crystals in optical fibres for the purpose of optical frequency comb generation. *Optics Communications*, 393 (November 2016), **2017**, 95–102. DOI: 10.1016/j.optcom.2017.02.035.
- [98] A. Haboucha, H. Leblond, M. Salhi, A. Komarov, and F. Sanchez. Coherent soliton pattern formation in a fiber laser. *Optics Letters*, 33 (5), **2008**, 524–526. DOI: 10.1364/OL.33.000524.
- [99] F. Amrani, M. Salhi, P. Grelu, H. Leblond, and F. Sanchez. Universal soliton pattern formations in passively mode-locked fiber lasers. *Optics letters*, 36 (9), **2011**, 1545–1547. DOI: 10.1364/OL.36.001545.

- [100] A. Haboucha, H. Leblond, M. Salhi, A. Komarov, and F. Sanchez. Analysis of soliton pattern formation in passively mode-locked fiber lasers. *Physical Review A*, 78, **2008**, 043806. DOI: 10.1103/PhysRevA.78.043806.
- [101] B. A. Malomed, A Schwache, and F Mitschke. Soliton lattice and gas in passive fiber-ring resonators. *Fiber and Integrated Optics*, 17 (4), **1998**, 267–277. DOI: 10.1080/014680398244867.
- [102] F. Mitschke and A. Schwache. Soliton ensembles in a nonlinear resonator. *Journal of Optics B: Quantum and Semiclassical Optics*, 10 (6), **1998**, 779–788.
- [103] A. Schwache and F. Mitschke. Properties of an optical soliton gas. *Physical Review E*, 55 (6), **1997**, 7720–7725. DOI: 10.1103/PhysRevE.55.7720.
- [104] H. A. Haus and W. Huang. Coupled-Mode Theory. *Proceedings of the IEEE*, 79 (10), **1991**, 1505–1518. DOI: 10.1109/5.104225.
- [105] A. A. Savchenkov, A. B. Matsko, W Liang, V. S. Ilchenko, D Seidel, and L Maleki. Kerr frequency comb generation in overmoded resonators. *Opt Express*, 20 (24), **2012**, 27290–27298. DOI: 10.1364/OE.20.027290\rr10.1364/OE.20.027290.. arXiv: arXiv:1201.1959v1.
- [106] T. Herr, V. Brasch, J. D. Jost, I. Mirgorodskiy, G. Lihachev, M. L. Gorodetsky, and T. J. Kippenberg. Mode Spectrum and Temporal Soliton Formation in Optical Microresonators. *Physical Review Letters*, 113 (12), **2014**, 123901. DOI: 10.1103/PhysRevLett.113.123901.
- [107] Y. Liu, Y. Xuan, X. Xue, P.-H. Wang, S. Chen, A. J. Metcalf, J. Wang, D. E. Leaird, M. Qi, and A. M. Weiner. Investigation of mode coupling in normal-dispersion silicon nitride microresonators for Kerr frequency comb generation. *Optica*, 1 (3), **2014**, 137–144. DOI: 10.1364/OPTICA.1.000137.
- [108] X. Xue, Y. Xuan, Y. Liu, P.-H. Wang, S. Chen, J. Wang, D. E. Leaird, M. Qi, and A. M. Weiner. Mode-locked dark pulse Kerr combs in normal-dispersion microresonators. *Nat Photon*, 9 (9), **2015**, 594–600. DOI: 10.1038/nphoton.2015.137.
- [109] C. Bao, Y. Xuan, D. E. Leaird, S. Wabnitz, M. Qi, and A. M. Weiner. Spatial mode-interaction induced single soliton generation in microresonators. *Optica*, 4 (9), **2017**, 1011. DOI: 10.1364/OPTICA.4.001011.
- [110] T. Hansson and S. Wabnitz. Bichromatically pumped microresonator frequency combs. *Physical Review A*, 90, **2014**, 013811. DOI: 10.1103/PhysRevA.90.013811. arXiv: 1404.2792.
- [111] D. V. Skryabin and W. J. Firth. Interaction of cavity solitons in degenerate optical parametric oscillators. *Optics letters*, 24 (15), **1999**, 1056–1058. DOI: 10.1364/OL.24.001056. arXiv: 9906004 [patt-sol].
- [112] S. Wabnitz. Control of soliton train transmission, storage, and clock recovery by cw light injection. *Journal of the Optical Society of America B*, 13 (12), **1996**, 2739–2749. URL: <http://www.scopus.com/inward/record.url?eid=2-s2.0-0030378988\&partnerID=tZ0tx3y1>.
- [113] J. A. Barker and D. Henderson. What is "liquid"? Understanding the states of matter. *Reviews of Modern Physics*, 48 (4), **1976**, 587–671. DOI: 10.1103/RevModPhys.48.587.

- [114] T. Egami and S. Billinge. **Underneath the Bragg Peaks**. 2nd. Oxford, UK: Elsevier, 2012, p. 422.
- [115] N. W. Ashcroft and D. N. Mermin. **Solid State Physics**. 1st ed. Belmont, CA: Brooks/Cole, 1976, p. 826.
- [116] A. Weiner. **Ultrafast Optics**. 1st ed. Hoboken, NJ: Wiley, 2009, p. 598.
- [117] T. Kobayashi, T. Sueta, Y. Cho, and Y. Matsuo. High-repetition-rate optical pulse generator using a Fabry-Perot electro-optic modulator. *Applied Physics Letters*, 21 (8), **1972**, 341–343. DOI: 10.1063/1.1654403.
- [118] M. Kourogi, K. Nakagawa, and M. Ohtsu. Wide-Span Optical Frequency Comb Generator for. 29 (10), **1993**.
- [119] H. Murata, A. Morimoto, T. Kobayashi, and S. Yamamoto. Optical pulse generation by electrooptic-modulation method and its application to integrated ultrashort pulse generators. *IEEE Journal of Selected Topics in Quantum Electronics*, 6 (6), **2000**, 1325–1331. DOI: 10.1109/2944.902186.
- [120] T. Sakamoto, T. Kawanishi, and M. Izutsu. Asymptotic formalism for ultraflat optical frequency comb generation using a Mach-Zehnder modulator. *Optics letters*, 32 (11), **2007**, 1515–1517. DOI: 10.1364/OL.32.001515.
- [121] I. Morohashi, T. Sakamoto, H. Sotobayashi, T. Kawanishi, I. Hosako, and M. Tsuchiya. Widely repetition-tunable 200 fs pulse source using a Mach-Zehnder-modulator-based flat comb generator and dispersion-flattened dispersion-decreasing fiber. *Optics letters*, 33 (11), **2008**, 1192–1194. DOI: 10.1364/OL.33.001192.
- [122] A. Ishizawa, T. Nishikawa, A. Mizutori, H. Takara, S. Aozasa, A. Mori, H. Nakano, A. Takada, and M. Koga. Octave-spanning frequency comb generated by 250 fs pulse train emitted from 25 GHz externally phase-modulated laser diode for carrier-envelope-offset-locking. *Electronics Letters*, 46 (19), **2010**, 1343. DOI: 10.1049/el.2010.2228.
- [123] R. Wu, V. R. Supradeepa, C. M. Long, D. E. Leaird, and A. M. Weiner. Generation of very flat optical frequency combs from continuous-wave lasers using cascaded intensity and phase modulators driven by tailored radio frequency waveforms. *Optics Letters*, 35 (19), **2010**, 3234. DOI: 10.1364/OL.35.003234. arXiv: 1005.5373.
- [124] V. R. Supradeepa and A. M. Weiner. Bandwidth scaling and spectral flatness enhancement of optical frequency combs from phase-modulated continuous-wave lasers using cascaded four-wave mixing. *Optics Letters*, 37 (15), **2012**, 3066. DOI: 10.1364/OL.37.003066.
- [125] A. J. Metcalf, V. Torres-company, D. E. Leaird, S. Member, A. M. Weiner, and A. Broadband. High-Power Broadly Tunable Electrooptic Frequency Comb Generator. *IEEE Journal of Selected Topics in Quantum Electronics*, 19 (6), **2013**, 3500306. URL: <http://ieeexplore.ieee.org/stamp/stamp.jsp?arnumber=06553388>.
- [126] R. Wu, V. Torres-company, D. E. Leaird, and A. M. Weiner. Optical Frequency Comb Generation. 21 (5), **2013**, 6045–6052. DOI: 10.1364/OE.21.006045.

- [127] J. M. Dudley, G. G. Genty, and S. Coen. Supercontinuum generation in photonic crystal fiber. *Reviews of Modern Physics*, 78 (4), **2006**, 1135–1184. DOI: 10.1103/RevModPhys.78.1135.
- [128] A. M. Weiner. Femtosecond pulse shaping using spatial light modulators. *Review of Scientific Instruments*, 71 (5), **2000**, 1929–1960. DOI: 10.1063/1.1150614.
- [129] K. Beha, D. C. Cole, P. Del’Haye, A. Coillet, S. A. Diddams, and S. B. Papp. Electronic synthesis of light. *Optica*, 4 (4), **2017**, 406–411. DOI: 10.1364/OPTICA.4.000406.
- [130] a. a. Amorim, M. V. Tognetti, P. Oliveira, J. L. Silva, L. M. Bernardo, F. X. Kärtner, and H. M. Crespo. Sub-two-cycle pulses by soliton self-compression in highly nonlinear photonic crystal fibers. *Optics letters*, 34 (24), **2009**, 3851–3853. DOI: 10.1364/OL.34.003851.
- [131] G. Di Domenico, S. Schilt, and P. Thomann. Simple approach to the relation between laser frequency noise and laser line shape. *Applied optics*, 49 (25), **2010**, 4801–4807. DOI: 10.1364/AO.49.004801.
- [132] D. R. Carlson, D. D. Hickstein, D. C. Cole, S. A. Diddams, and S. B. Papp. Dual-comb interferometry via repetition-rate switching of a single frequency comb. *arXiv*, **2018**, 1806.05311. URL: <http://arxiv.org/abs/1806.05311>. arXiv: 1806.05311.
- [133] A. J. Metcalf, C. Bender, S. Blakeslee, W. Brand, D. Carlson, S. A. Diddams, C. Fredrick, S. Halverson, F. Hearty, D. Hickstein, J. Jennings, S. Kanodia, K. Kaplan, E. Lubar, S. Mahadevan, A. Monson, J. Ninan, C. Nitroy, S. Papp, L. Ramsey, P. Robertson, A. Roy, C. Schwab, K. Srinivasan, G. K. Stefansson, and R. Terrien. Infrared Astronomical Spectroscopy for Radial Velocity Measurements with 10 cm/s Precision. In: **Conference on Lasers and Electro-Optics**. 2018, JTh5A.1.
- [134] S. Backus, C. G. Durfee, M. M. Murnane, and H. C. Kapteyn. High power ultrafast lasers. *Review of Scientific Instruments*, 69 (3), **1998**, 1207. DOI: 10.1063/1.1148795.
- [135] A. Baltuska, M. Uiberacker, E. Goulielmakis, R. Kienberger, V. S. Yakovlev, T. Udem, T. W. Hänsch, and F. Krausz. Phase-Controlled Amplification of Few-Cycle Laser Pulses. *IEEE Journal of Selected Topics in Quantum Electronics*, 9 (4), **2003**, 972–989.
- [136] C. Gohle, J. Rauschenberger, T. Fuji, T. Udem, A. Apolonski, F. Krausz, and T. W. Hänsch. Carrier envelope phase noise in stabilized amplifier systems. 30 (18), **2005**, 2487–2489.
- [137] J. Rauschenberger, T. Fuji, M. Hentschel, A.-J. Verhoef, T. Udem, C. Gohle, T. W. Hänsch, and F. Krausz. Carrier-envelope phase-stabilized amplifier system. *Laser Physics Letters*, 3 (1), **2006**, 37–42. DOI: 10.1002/lapl.200510053.
- [138] M. E. Fermann, V. I. Kruglov, B. C. Thomsen, J. M. Dudley, and J. D. Harvey. Self-similar propagation and amplification of parabolic pulses in optical fibers. *Physical review letters*, 84 (26 Pt 1), **2000**, 6010–3. URL: <http://www.ncbi.nlm.nih.gov/pubmed/10991111>.
- [139] M. Hirano, T. Nakanishi, T. Okuno, and M. Onishi. Silica-Based Highly Nonlinear Fibers and Their Application. *Sel. Top. Quantum Electron.*, 15 (1), **2009**, 103–113. DOI: 10.1109/JSTQE.2008.2010241.

- [140] D. Mandridis, I. Ozdur, F. Quinlan, M. Akbulut, J. J. Plant, P. W. Juodawlkis, and P. J. Delfyett. Low-noise, low repetition rate, semiconductor-based mode-locked laser source suitable for high bandwidth photonic analog digital conversion. *Applied Optics*, 49 (15), **2010**, 2850–2857.
- [141] H.-A. Bachor and P. J. Manson. Practical Implications of Quantum Noise. *Journal of Modern Optics*, 37 (11), **1990**, 1727–1740. DOI: 10.1080/09500349014551951.
- [142] F. Quinlan, T. M. Fortier, H. Jiang, and S. a. Diddams. Analysis of shot noise in the detection of ultrashort optical pulse trains. *Journal of the Optical Society of America B*, 30 (6), **2013**, 1775. DOI: 10.1364/JOSAB.30.001775.
- [143] D. C. Cole, K. M. Beha, S. A. Diddams, and S. B. Papp. Octave-spanning supercontinuum generation via microwave frequency multiplication. *Proceedings of the 8th Symposium on Frequency Standards and Metrology 2015, Journal of Physics: Conference Series*, 723, **2016**, 012035. DOI: 10.1088/1742-6596/723/1/012035.
- [144] A. M. Heidt. Efficient Adaptive Step Size Method for the Simulation of Supercontinuum Generation in Optical Fibers. *Journal of Lightwave Technology*, 27 (18), **2009**, 3984–3991.
- [145] J. Hult. A Fourth-Order Runge-Kutta in the Interaction Picture Method for Simulating Supercontinuum Generation in Optical Fibers. *Journal of Lightwave Technology*, 25 (12), **2007**, 3770–3775. DOI: 10.1109/JLT.2007.909373.
- [146] R. Driad, J. Rosenzweig, R. E. Makon, R. Lösch, V. Hurm, H. Walcher, and M. Schlechtweg. InP DHBT-Based IC Technology for 100-Gb / s Ethernet. *IEEE Trans. on Electron. Devices*, 58 (8), **2011**, 2604–2609.
- [147] D. Ferenci, M. Grozing, M. Berroth, R. Makon, R. Driad, and J. Rosenzweig. A 25 GHz Analog Demultiplexer with a Novel Track and Hold Circuit for a 50 GS / s A / D-Conversion System in InP DHBT Technology. In: **Microwave Symposium Digest**. 2012, pp. 1–3.
- [148] K. Ikeda. Multiple-valued stationary state and its instability of the transmitted light by a ring cavity system. *Optics Communications*, 30 (2), **1979**, 257–261. DOI: 10.1016/0030-4018(79)90090-7 (cited on page 2).
- [149] K. J. Blow and D Wood. Theoretical description of transient stimulated Raman scattering in optical fibers. *Quantum Electronics, IEEE Journal of*, 25 (12), **1989**, 2665–2673. DOI: 10.1109/3.40655.