

Chapter 3 Exercises

Derek Chiu

July 20, 2016

3.1.7 Exercises

1. Fix each of the following common data frame subsetting errors:

```
mtcars[mtcars$cyl = 4, ]
mtcars[-1:4, ]
mtcars[mtcars$cyl <= 5]
mtcars[mtcars$cyl == 4 | 6, ]
```

2. Why does `x <- 1:5; x[NA]` yield five missing values? (Hint: why is it different from `x[NA_real_]`?)
3. What does `upper.tri()` return? How does subsetting a matrix with it work? Do we need any additional subsetting rules to describe its behaviour?

```
x <- outer(1:5, 1:5, FUN = "*")
x[upper.tri(x)]
```
4. Why does `mtcars[1:20]` return an error? How does it differ from the similar `mtcars[1:20,]`?
5. Implement your own function that extracts the diagonal entries from a matrix (it should behave like `diag(x)` where `x` is a matrix).
6. What does `df[is.na(df)] <- 0` do? How does it work?

3.2.4 Exercises

1. Given a linear model, e.g., `mod <- lm(mpg ~ wt, data = mtcars)`, extract the residual degrees of freedom. Extract the R squared from the model summary (`summary(mod)`)

3.4.9 Exercises

1. How would you randomly permute the columns of a data frame? (This is an important technique in random forests.) Can you simultaneously permute the rows and columns in one step?
2. How would you select a random sample of m rows from a data frame? What if the sample had to be contiguous (i.e., with an initial row, a final row, and every row in between)?
3. How could you put the columns in a data frame in alphabetical order?