

# Attempt

Dylan Johnson

May 1, 2016

## Introduction

This is another attempt to write a language; this one will compile for the JVM. I decided to compile to the JVM so that a lot of difficult details, such as garbage collection and heap allocation can be abstracted away. I may change the target the environment to LLVM and write my own garbage collector in the future. However, that is just speculation at this point. Lets get things done one at a time. It is going to be named Attempt because that is likely all this will turn out to be. In this document will reside the specification for the language.

## Feature Plan

### Current Plan

- enforce proper whitespace indentation and formatting
- all the standard control flow tools; loops, if else blocks, ect
- classes with internal member variables and methods; polymorphism via interfaces and data encapsulation
- add the basic built in types, strings, arrays, integers, bools, floats, ect
- strong type system
- all the proper operators for builtin types; +, -, =+, [], ect
- integration with Java stdlib
- scopes
- compile to executable class files
- a proper namespace and module system

## And Beyond

- port to LLVM
- write a garbage collector
- stdlib
- switch to using impractical unicode symbols such as  $\lambda$  or  $\rightarrow$

## Specification

### Formatting

#### Whitespace

The only valid whitespace is the one true whitespace: spaces. Spaces and only spaces will be allowed. This is because spaces are the purest of all whitespaces and they stay firm to their indentation from one editor to the next. All indentation must be in multiples of a given power of two; in other words, you cannot mix indentation that indents by one space or two spaces. If you choose and indentation of one space, you must stick with it or you will suffer. Your program wont compile.

### Statements

Each line of code makes up a statement that can contain one or more expressions. Each expression is delimited by a semicolon. The end of each line does not require a semicolon.

```
# the following expressions are equivalent
let x: i32 = 3; x += 1
# or
let x: i32 = 3
x += 1
```

### Code Blocks

The `:` symbol will be used to state that a new code block will be starting on the next line. The `:` symbol must be used in conjunction with specific language constructs. For example, defining the body of a method, if statement, or for loop. They can be nested and can be use in a solitary fashion as well. When used in a variable declaration, it is used to specify the type. Each block defines its own lexical scope.

```
if <expression>:
  <expression>
```

```

else:
    <expression>

# the for loop contains 3 expressions
for let x: i32 = 0; x < 20; x += 1:
    <expression>

func foo() -> i32:
    <expression>
    return 3

<expression>
: # defines a new block.
    <expressing>

```