

⚙ Settings



TestForge MCP

22-dimension analysis — runs entirely on your machine

🔒 Code never leaves your system

Analysis complete!



Analysis Report — dclaw-cost

📄 Saved



Overall Score

7807 files · 1,107,381 lines · 136 endpoints

🔒 Analyzed entirely on your machine

● 540 critical ● 386 high ● 1 medium ● 3 low

0

Security
933 findings

67

Unit Tests
54 test files

38

Accessibility

81

Vision

47

Stack

91

Agentic Scale
100 agents

25

DORA
Capability: Good — CI + automated deploy

100

Supply Chain

100

Chaos

32

Mutation

93

Predictive

98

Contract



Top Security Findings

[HIGH] XSS via `write()` helper

web/node_modules/object-hash/index.js:221

💡 Either sanitize the argument before passing it to `write`, or rewrite `write` to use the safe alternative (parameterized queries, escape, etc.) intern

[HIGH] XSS via `write()` helper

web/node_modules/object-hash/index.js:245

💡 Either sanitize the argument before passing it to `write`, or rewrite `write` to use the safe alternative (parameterized queries, escape, etc.) intern

[HIGH] XSS via `write()` helper

web/node_modules/object-hash/index.js:262

💡 Either sanitize the argument before passing it to `write`, or rewrite `write` to use the safe alternative (parameterized queries, escape, etc.) intern

[HIGH] XSS via `write()` helper

web/node_modules/object-hash/index.js:293

💡 Either sanitize the argument before passing it to `write`, or rewrite `write` to use the safe alternative (parameterized queries, escape, etc.) intern

[HIGH] XSS via `write()` helper

web/node_modules/object-hash/index.js:296

💡 Either sanitize the argument before passing it to `write`, or rewrite `write` to use the safe alternative (parameterized queries, escape, etc.) intern

[HIGH] XSS via `write()` helper

web/node_modules/object-hash/index.js:299

💡 Either sanitize the argument before passing it to `write`, or rewrite `write` to use the safe alternative (parameterized queries, escape, etc.) intern

[HIGH] XSS via `write()` helper

web/node_modules/object-hash/index.js:302

💡 Either sanitize the argument before passing it to `write`, or rewrite `write` to use the safe alternative (parameterized queries, escape, etc.) intern

[HIGH] XSS via `write()` helper

web/node_modules/object-hash/index.js:305

💡 Either sanitize the argument before passing it to `write`, or rewrite `write` to use the safe alternative (parameterized queries, escape, etc.) intern

🤖 **Agentic Scale: 91/100**

Agent-Ready — Your API can handle 2000+ concurrent AI agents

Max agents before failure: 100 | Bottleneck: Database connection pool



Generate Tests (Tier 2)



Download Report (Markdown)



Download JSON



Print / Save PDF



Tier 2 — Generate & Run

id gen_mptsoilf · anthropic/claude-sonnet-4.6 → moonshotai/kimi-k2.6 · generation 31.3s · sandbox 5272ms

✓ **12 / 12 tests passed**



no-observability-stack-detected-src-l0.test.ts

For: No observability stack detected

→ PASSED · 4 passed, 0 failed

Tests verify that a dependency-scanning utility correctly identifies the absence of APM and error-tracking packages as a compliance failure, and confirms that adding Sentry or OpenTelemetry resolves the observability gap.



no-product-analytics-dependency-src-l0.test.ts

For: No product analytics dependency

→ PASSED · 4 passed, 0 failed

Tests simulate the absence of telemetry instrumentation (foot-gun) versus a lightweight analytics wrapper that captures the five key lifecycle events (signup, activation, first-value-moment, retention, churn-signal) recommended by PostHog guidance.



auth-endpoints-not-rate-limited-src-l0.test.ts

For: Auth Endpoints Not Rate Limited

→ PASSED · 4 passed, 0 failed

Tests demonstrate that an unprotected auth handler allows unlimited brute-force attempts, while the safe rate-limited handler correctly blocks excessive per-IP requests within a time window and locks accounts after repeated failures.

 Local analysis — data stored in ~/.testforge/history.db
For managed testing with team sharing, visit testforge.run