
step length at the fork, as a multiple of the reference branch's at the same position — one curve per constraint rule, the mean over n = 100 source games of that game's own ratio; bands are a 95% percentile bootstrap CI over games



shared prefix: branches identical, ratio = 1 by construction
reference (the game as played), the line at 1
R1 placement (mean of 2)
R2 bracketing (mean of 3)
R3 turn (mean of 1)
95% percentile bootstrap CI of the mean over games
control: another legal move (null)
control 2: a third legal move (null)

one step spans 4 plies: positions are sampled every 2 plies at t_0's parity (fork_plane.positions), the fork family's convention. ../rule_curvature samples every ply instead, where the same layer-5 legal corpus steps 29.2 against 18.9 here (../theta_comparability) — the two conventions measure different quantities and must never share an axis.
within ÷ between-rule spread of the drawn ratio over $t \geq t_0$, in raw layer 5, per game over 100 games: median 0.866 [IQR 0.728–1.021], above 1 in 29% of them.
Near 1 the three curves are a label rather than a finding; the nine spaces' values are in README.md.
the two grey curves are two draws of one null — a different legal token at t_0, measured exactly as the illegal branches are. Neither is a divisor here (the reference is), so the gap between them is the size of a difference that means nothing, and each panel's number is that rule minus control_legal on the same games, not two point estimates side by side.
the first 100 of the 1696 branch-complete games forking at t_0 = 20, ascending by game id: no game-level criterion enters this figure, and game 1235 — the argmax the single-game figure draws — is in it as one ordinary member of 100 (README).
R1 placement (2): square holds the mover's disc · square holds the opponent's disc
R2 bracketing (3): empty, touches no discs · empty, touches only the mover's discs · empty, touches opponent discs, no line closes
R3 turn (1): flips only for the opponent (turn confusion)