TNE30019/TNE80014 – Unix for Telecommunications

DHCP - Dynamic Host Configuration Protocol

Dr. Jason But

Swinburne University

Dr. Jason But

TNE30019/TNE80014 - DHCP

DHCP - Dynamic Host Configuration Protocol

- Allows hosts to request (via broadcast) host configuration information
- Server will respond with network configuration information
- Primarily for IP address, subnet mask, gateway, and DNS server information
- Also can provide other information, e.g. time server


Outline

- Dynamic Host Configuration Protocol (DHCP)
- ISC DHCP server for Unix
- Server configuration
- Static IP addresses in DHCP
- Running the server
- Lease database

Dr. Jason But

TNE30019/TNE80014 - DHCP

DHCP - Dynamic Host Configuration Protocol



Blue arrows denote IP broadcast packets

DHCP - Dynamic Host Configuration Protocol

- Standard protocol, IETF RFC 2131
- Uses UDP/IP as transport
- Several implementations to choose from
- Most common: ISC (Internet Software Consortium) DHCP Server version 3¹

FreeBSD Install

```
cd /usr/ports/net/isc-dhcp3-server
make && make install
```

Configuration File

/usr/local/etc/dhcpd.conf

TNE30019/TNE80014 - DHCP

ISC DHCP - Lease/Group Configuration Options

- Specific options for particular group of leases or single host
- Options from Global Section may be repeated (overridden)

Common Lease/Group Options

```
subnet a.b.c.d netmask e.f.g.h {
  range a.b.c.x1 a.b.c.x2;
  option any_local_options;
};
```

- Assigns free IP address in specified range to querying host
- Assigns specified subnet mask

ISC DHCP - Global Configuration Options

- Options/Settings common to all leases
- Default lease timeout values
- Details of DNS Server to communicate with

Common Global Options

```
option domain-name "company.com";
option domain-name-servers "list of dns servers";
option routers "default gateway";
default-lease-time seconds;
max-lease-time seconds:
authoritative:
```

Many other options are available

Dr. Jason But

TNE30019/TNE80014 - DHCP

ISC DHCP - Static IP Address Configuration

Configuring static IP address

```
host host_name {
  hardware ethernet 00:01:02:03:04:05;
  fixed-address a.b.c.d;
  option host-name "advertised name";
};
```

- Specify host_name for labelling purposes
- Host with specified MAC address is always assigned fixed-address
- Host requesting lease and advertising itself as "advertised name" is always assigned fixed-address
- Advertised names must be configured in OS of requesting workstation

TNE30019/TNE80014 - DHCP

¹http://www.isc.org/products/DHCP

Running ISC DHCP on FreeBSD

/etc/rc.conf

dhcpd_enable="YES"
dhcpd_ifaces="if0 if1"

Startup script (for dhcpcd):

- Daemon started by /usr/local/etc/rc.d/isc-dhcpd
- Listening for lease requests on specified network interfaces

Lease Database

- Assigned leases and expiry times are stored in simple text file (/var/db/dhcpd.leases)
- Allows dhcpd to remember assigned leases after restart
- File periodically re-created to remove expired leases and ensure it doesn't get too big

Dr. Jason But

TNE30019/TNE80014 - DHCP