



# Product Specification

AU OPTRONICS CORPORATION

M201EW02 V8

( V ) Preliminary Specification

( ) Final Specification

|            |                             |
|------------|-----------------------------|
| Module     | 20.1"W WSXGA+ Color TFT-LCD |
| Model Name | M201EW02 V8                 |

|   |       |
|---|-------|
| Customer  | Date  |
| _____   | _____ |
| Approved by   |       |
| _____   | _____ |
| Note: This Specification is subject to change without notice. |       |

|   |       |
|---|-------|
| Checked & Approved by                                     | Date  |
|   | _____ |
| Prepared by   |       |
|   | _____ |
| Desktop Display Business Group / AU Optronics corporation |       |



## Contents

|  |           |
|--|-----------|
| <b>1. Handling Precautions .....</b>           | <b>6</b>  |
| <b>2. General Description.....</b>             | <b>8</b>  |
| 2.1 Display Characteristics .....              | 8         |
| 2.2 Optical Characteristics.....               | 10        |
| <b>3. Functional Block Diagram.....</b>        | <b>18</b> |
| <b>4. Absolute Maximum Ratings .....</b>       | <b>20</b> |
| 4.1 TFT LCD Module .....                       | 20        |
| 4.2 Backlight Unit .....                       | 20        |
| 4.3 Absolute Ratings of Environment .....      | 20        |
| <b>5. Electrical characteristics.....</b>      | <b>22</b> |
| 5.1 TFT LCD Module .....                       | 22        |
| 5.1.1 Power Specification .....                | 22        |
| 5.1.2 Signal Electrical Characteristics.....   | 24        |
| 5.2 Backlight Unit .....                       | 26        |
| <b>6. Signal Characteristic .....</b>          | <b>29</b> |
| 6.1 Pixel Format Image .....                   | 29        |
| 6.2 The input data format .....                | 29        |
| 6.3 Signal Description .....                   | 30        |
| 6.4 Timing Characteristics .....               | 33        |
| 6.4.1 Timing Characteristics .....             | 34        |
| 6.4.2Timing diagram .....                      | 35        |
| 6.5 Power ON/OFF Sequence .....                | 37        |
| <b>7. Connector &amp; Pin Assignment .....</b> | <b>39</b> |
| 7.1 TFT LCD Module .....                       | 39        |
| 7.1.1 Connector .....                          | 39        |
| 7.1.2 Pin Assignment.....                      | 39        |
| 7.2 Backlight Unit .....                       | 41        |
| 7.2.1 Signal for Lamp connector .....          | 41        |
| <b>8. Reliability.....</b>                     | <b>42</b> |
| <b>9 Shipping Label .....</b>                  | <b>44</b> |
| <b>10. Mechanical Characteristics.....</b>     | <b>45</b> |



## Record of Revision

| Version and Date | Page | Old description | New Description | Remark |
|------------------|------|-----------------|-----------------|--------|
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |
|                  |      |                 |                 |        |



## 1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open or modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) In case if a Module has to be put back into the packing container slot after once it was taken out from the container, do not press the center of the CCFL reflector edge. Instead, press at the far ends of the CCFL Reflector edge softly. Otherwise the TFT Module may be damaged.
- 10) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) After installation of the TFT Module into an enclosure, do not twist nor bend the TFT Module even momentary. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 12) Cold cathode fluorescent lamp in LCD contains a small amount of mercury. Please follow local ordinances or regulations for disposal.
- 13) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 14) The LCD module is designed so that the CCFL in it is supplied by Limited Current Circuit (IEC60950 or UL1950). Do not connect the CCFL in Hazardous Voltage Circuit.



## 2. General Description

This specification applies to the 20.1 inch-wide Color TFT-LCD Module M201EW02 v.8.

The display supports the WSXGA+ (1680(H) x 1050(V)) screen format and 16.7M colors (RGB 6-bits+Hi-RFC data).

All input signals are 2 Channel LVDS interface compatible.

This module does not contain an inverter card for backlight.

### 2.1 Display Characteristics

The following items are characteristics summary on the table under 25 °C condition:

| ITEMS                                       | Unit                 | SPECIFICATIONS                          |
|---|----------------------|---|
| Screen Diagonal                             | [mm]                 | 511.13 (20.1"Wide)                      |
| Active Area                                 | [mm]                 | 433.44 (H) x 270.90(V)                  |
| Pixels H x V                                |                      | 1680(x3) x 1050                         |
| Pixel Pitch                                 | [mm]                 | 0.258 (per one triad) x 0.258           |
| Pixel Arrangement                           |                      | R.G.B. Vertical Stripe                  |
| Display Mode                                |                      | Normally White                          |
| White Luminance ( Center )                  | [cd/m <sup>2</sup> ] | 300cd/m <sup>2</sup> @ 7.5mA (Typ)      |
| Contrast Ratio                              |                      | TBD                                     |
| Optical Response Time                       | [msec]               | TBD (Typ, on/off)                       |
| Nominal Input Voltage VCC                   | [Volt]               | +5.0 V                                  |
| Power Consumption<br>(VCC line + CCFL line) | [Watt]               | TBD                                     |
| Weight                                      | [Grams]              | 2500 (Typ)                              |
| Physical Size                               | [mm]                 | 459.4(W) x 296.4(H) x 16.6(D) (Typ)     |
| Electrical Interface                        |                      | Dual Channel LVDS                       |
| Support Color                               |                      | 16.7M colors (RGB 6-bits+Hi-FRC data )  |
| Temperature Range                           |                      |   |
| Operating                                   | [°C]                 | 0 to +50                                |
| Storage (Shipping)                          | [°C]                 | -20 to +60                              |
| Surface Treatment                           |                      | Hard-coating (3H), Anti-Glare treatment |
| RoHS  |                      | RoHS compliance                         |



## 2.2 Optical Characteristics


The optical characteristics are measured under stable conditions at 25°C:

| Item  | Unit                 | Conditions         | Min.  | Typ.  | Max.  | Note |
|---|----------------------|--------------------|-------|-------|-------|------|
| Viewing Angle                                     | [degree]             | Horizontal (Right) | 75    | 80    | -     | 1    |
|   | [degree]             | CR = 10 (Left)     | 75    | 80    | -     |      |
|   | [degree]             | Vertical (Up)      | 75    | 80    | -     |      |
|   | [degree]             | CR = 10 (Down)     | 75    | 80    | -     |      |
| Luminance Uniformity                              | [%]                  |                    | 75    | 80    | -     | 2,3  |
| Response Time                                     | [msec]               | Rising Time        | -     | TBD   | TBD   | 4,6  |
|   | [msec]               | Falling Time       | -     | TBD   | TBD   |      |
|   | [msec]               | Rising + Falling   | -     | TBD   | TBD   |      |
| Color / Chromaticity<br>Coordinates<br>(CIE 1931) |                      | Red x              | 0.610 | 0.640 | 0.670 | 4    |
|   |                      | Red y              | 0.322 | 0.352 | 0.382 |      |
|   |                      | Green x            | 0.258 | 0.288 | 0.318 |      |
|   |                      | Green y            | 0.598 | 0.628 | 0.658 |      |
|   |                      | Blue x             | 0.117 | 0.147 | 0.177 |      |
|   |                      | Blue y             | 0.040 | 0.070 | 0.100 |      |
|   |                      | White x            | 0.283 | 0.313 | 0.343 |      |
|   |                      | White y            | 0.299 | 0.329 | 0.359 |      |
| White Luminance at CCFL<br>7.5mA (central point)  | [cd/m <sup>2</sup> ] |                    | 240   | 300   | -     | 4    |
| Contrast ratio                                    |                      | Normal Direction   | 800   | TBD   | -     | 4    |
| Crosstalk (in75Hz)                                | [%]                  |                    |       |       | 1.5   | 5    |
| Flicker   | [dB]                 |                    |       |       | -20   | 7    |


Optical Equipment: BM-5A, BM-7, PR880, or equivalent

## Note 1: Definition of viewing angle

Viewing angle is the measurement of contrast ratio  $\geq 10$ , at the screen center, over a  $180^\circ$  horizontal and  $180^\circ$  vertical range (off-normal viewing angles). The  $180^\circ$  viewing angle range is broken down as follows;  $90^\circ$  ( $\theta$ ) horizontal left and right and  $90^\circ$  ( $\Phi$ ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



## Note 2: 9 points position




Note 3: The luminance uniformity of 9 points is defined by dividing the maximum luminance values by the minimum test point luminance

$$\delta_{w9} = \frac{\text{Minimum Luminance of 9 points}}{\text{Maximum Luminance of 9 points}}$$

## Note 4: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room.




## Note 5: Definition of Cross Talk (CT)

$$CT = | Y_B - Y_A | / Y_A \times 100 (\%)$$

Where

$Y_A$  = Luminance of measured location without gray level 0 pattern (cd/m<sup>2</sup>)


$Y_B$  = Luminance of measured location with gray level 0 pattern (cd/m<sup>2</sup>)






Note 6: Definition of response time:


The output signals of photo detector are measured when the input signals are changed from “Full Black” to “Full White” (rising time), and from “Full White” to “Full Black ”(falling time), respectively. The response time is interval between the 10% and 90% of amplitudes. Please refer to the figure as below.



Note 7: Subchecker Pattern




Method: Record dBV & DC value with (WESTAR)TRD-100



$$\text{Flicker (dB)} = 20 \log \frac{\text{AC Level(at 30 Hz)}}{\text{DC Level}}$$

## 3. Functional Block Diagram

The following diagram shows the functional block of the 20.1 inches wide Color TFT/LCD Module:



I/F + X-PCB

JAE FI-XB30SSRL-HF16

YEONHO35001HS-02L

## 4. Absolute Maximum Ratings

Absolute maximum ratings of the module is as following:

### 4.1 TFT LCD Module

| Item            | Symbol | Min  | Max | Unit   | Conditions      |
|-----------------|--------|------|-----|--------|-----------------|
| Logic/LCD Drive | VIN    | -0.3 | 6   | [Volt] | <b>Note 1,2</b> |

### 4.2 Backlight Unit

| Item         | Symbol | Min | Max | Unit     | Conditions      |
|--------------|--------|-----|-----|----------|-----------------|
| CCFL Current | ICFL   | -   | 8   | [mA] rms | <b>Note 1,2</b> |


### 4.3 Absolute Ratings of Environment

| Item                | Symbol | Min | Max | Unit  | Conditions    |
|---------------------|--------|-----|-----|-------|---------------|
| Operating Humidity  | HOP    | 5   | 90  | [%RH] | <b>Note 3</b> |
| Storage Temperature | TST    | -20 | +60 | [°C]  |               |
| Storage Humidity    | HST    | 5   | 90  | [%RH] |               |

**Note 1:** With in Ta (25°C )

**Note 2:** Permanent damage to the device may occur if exceed maximum values


**Note 3:** For quality performance, please refer to AUO IIS (Incoming Inspection Standard).



Operating Range



Storage Range



## 5. Electrical characteristics


### 5.1 TFT LCD Module

#### 5.1.1 Power Specification

Input power specifications are as follows;

| Symbol | Parameter               | Min | Typ | Max | Units  | Condition                           |
|--------|-------------------------|-----|-----|-----|--------|-------------------------------------|
| VCC    | Logic/LCD Drive Voltage | 4.5 | 5   | 5.5 | [Volt] | $\pm 10\%$                          |
| ICC    | VCC current             | -   | TBD | TBD | [mA]   | Vin=5V , All Black Pattern, at 60Hz |
| Irush  | LCD Inrush Current      | -   | -   | TBD | [A]    | <b>Note</b>                         |
| PCC    | VCC Power               | -   | TBD | TBD | [Watt] | Vin=5V , All Black Pattern, at 60Hz |

**Note:** Measurement conditions:



Vin rising time

## 5.1.2 Signal Electrical Characteristics


Input signals shall be low or Hi-Z state when Vin is off

It is recommended to refer the specifications of SN75LVDS82DGG (Texas Instruments) in detail.

Each signal characteristics are as follows;

| Symbol | Parameter                              | Min  | Typ  | Max  | Units | Condition                       |
|--------|--|------|------|------|-------|---------------------------------|
| VTH    | Differential Input High Threshold      | -    | -    | +100 | [mV]  | VICM = 1.2V<br><b>Note</b>      |
| VTL    | Differential Input Low Threshold       | -100 | -    | -    | [mV]  | VICM = 1.2V<br><b>Note</b>      |
| VID    | Input Differential Voltage             | 100  | 400  | 600  | [mV]  | <b>Note</b>                     |
| VICM   | Differential Input Common Mode Voltage | +1.0 | +1.2 | +1.5 | [V]   | VTH/VTL = ±100mV<br><b>Note</b> |

**Note:** LVDS Signal Waveform



## 5.2 Backlight Unit

Parameter guideline for CCFL Inverter

| Symbol         | Parameter  | Min.   | Typ.          | Max. | Unit          | Condition                 |
|----------------|--|--------|---------------|------|---------------|---------------------------|
| ISCFL          | CCFL standard current  | 7      | 7.5           | 8    | [mA]<br>rms   | (Ta=25°C) <b>Note 2</b>   |
| IRCFL          | CCFL operation range   | 3      | 7.5           | 8    | [mA]<br>rms   | (Ta=25°C) <b>Note 2</b>   |
| FCFL           | CCFL Frequency   | 40     | 55            | 60   | [KHz]         | (Ta=25°C) <b>Note 3,4</b> |
| ViCFL<br>(0°C) | CCFL Ignition Voltage<br>(End of the lamp wire<br>connector) | 1700   | -             |      | [Volt]<br>rms | (Ta=0°C) <b>Note 5</b>    |
| ViCF<br>(25°C) | CCFL Ignition Voltage<br>(End of the lamp wire<br>connector) | 1300   | -             |      | [Volt]<br>rms | (Ta=25°C) <b>Note 5</b>   |
| VCFL           | CCFL Operation Voltage                                       | TBD    | 750<br>@7.5mA | TBD  | [Volt]<br>rms | (Ta=25°C) <b>Note 6</b>   |
| PCFL           | CCFL Power consumption (for<br>reference)                    | -      | TBD           | -    | [Watt]        | (Ta=25°C) <b>Note 6</b>   |
| LTCFL          | CCFL life Time   | 50,000 | 55,000        | -    | [Hour]        | (Ta=25°C) <b>Note 7</b>   |

Note 1: Typ. are AUO recommended design points.

- \*1 All of characteristics listed are measured under the condition using the AUO test inverter.
- \*2 In case of using an inverter other than listed, it is recommended to check the inverter carefully. Sometimes, interfering noise stripes appear on the screen, and substandard luminance or flicker at low power may happen.
- \*3 In designing an inverter, it is suggested to check safety circuit very carefully. Impedance of CCFL, for instance, becomes more than 1 [M ohm] when CCFL is damaged.
- \*4 Generally, CCFL has some amount of delay time after applying kick-off voltage. It is recommended to keep on applying kick-off voltage for 1 [Sec] until discharge.
- \*5 Reducing CCFL current increases CCFL discharge voltage and generally increases CCFL discharge frequency. So all the parameters of an inverter should be carefully designed so as not to produce too much leakage current from high-voltage output of the inverter.

Note 2: It should be employed the inverter which has "Duty Dimming", if IRCFL is less than 4mA.

Note 3: CCFL discharge frequency should be carefully determined to avoid interference between inverter and TFT LCD.

Note 4: The frequency range will not affect to lamp life and reliability characteristics.

Note 5: CCFL inverter should be able to give out a power that has a generating capacity of over 1,500 voltage. Lamp units need 1,500 voltage minimum for ignition.

Note 6: The variance of CCFL power consumption is  $\pm 10\%$ . Calculator value for reference (ISCFL  $\times$  VCFL  $\times$  4 = PCFL

Note 7: Definition of Life time: Brightness becomes 50%. The typical life time CCFL in on the condition at 7.5 m A lamp current.


## 6. Signal Characteristic

## 6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.

|           | 1  |   |   | 2  |   |   |  |  |  |  |  |  |  |  |  |  |  |  | 1679   |   |   | 1680   |   |   |
|-----------|--|---|---|--|---|---|--|--|--|--|--|--|--|--|--|--|--|--|--|---|---|--|---|---|
| 1st Line  | R  | G | B | R  | G | B | · · · · ·                                      |  |  |  |  |  |  |  |  |  |  |  | R  | G | B | R  | G | B |
|           | ·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>· |   |   | ·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>· |   |   | ·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>· |  |  |  |  |  |  |  |  |  |  |  | ·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>· |   |   | ·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>·<br>· |   |   |
| 1050 Line | R  | G | B | R  | G | B | · · · · ·                                      |  |  |  |  |  |  |  |  |  |  |  | R  | G | B | R  | G | B |

## 6.2 The input data format



**Note 1:** R/G/B data 7:MSB, R/G/B data 0:LSB

O = "First Pixel Data"

E = "Second Pixel Data"




## 6.3 Signal Description

The module using one LVDS receiver SN75LVDS82(Texas Instruments) or compatible. LVDS is a differential signal technology for LCD interface and high speed data transfer device. Transmitter shall be SN75LVDS83(negative edge sampling) or compatible. The first LVDS port(RxOxxx) transmits odd pixels while the second LVDS port(RxExxx) transmits even pixels.

| PIN # | SIGNAL NAME | DESCRIPTION  |
|-------|-------------|--|
| 1     | RxO0-       | Negative LVDS differential data input (Odd data)                       |
| 2     | RxO0+       | Positive LVDS differential data input (Odd data)                       |
| 3     | RxO1-       | Negative LVDS differential data input (Odd data)                       |
| 4     | RxO1+       | Positive LVDS differential data input (Odd data)                       |
| 5     | RxO2-       | Negative LVDS differential data input (Odd data, H-Sync,V-Sync,DSPTMG) |
| 6     | RxO2+       | Positive LVDS differential data input (Odd data, H-Sync,V-Sync,DSPTMG) |
| 7     | GND         | Power Ground   |
| 8     | RxOC-       | Negative LVDS differential clock input (Odd clock)                     |
| 9     | RxOC+       | Positive LVDS differential clock input (Odd clock)                     |
| 10    | RxO3-       | Negative LVDS differential data input (Odd data)                       |
| 11    | RxO3+       | Positive LVDS differential data input (Odd data)                       |
| 12    | RxE0-       | Negative LVDS differential data input (Even clock)                     |
| 13    | RxE0+       | Positive LVDS differential data input (Even data)                      |
| 14    | GND         | Power Ground   |
| 15    | RxE1-       | Positive LVDS differential data input (Even data)                      |
| 16    | RxE1+       | Negative LVDS differential data input (Even data)                      |
| 17    | GND         | Power Ground   |
| 18    | RxE2-       | Negative LVDS differential data input (Even data)                      |
| 19    | RxE2+       | Positive LVDS differential data input (Even data)                      |
| 20    | RxEC-       | Negative LVDS differential clock input (Even clock)                    |
| 21    | RxEC+       | Positive LVDS differential clock input (Even clock)                    |
| 22    | RxE3-       | Negative LVDS differential data input (Even data)                      |
| 23    | RxE3+       | Positive LVDS differential data input (Even data)                      |
| 24    | GND         | Power Ground   |
| 25    | GND         | Power Ground   |
| 26    | NC          | No contact (For AUO test only)   |
| 27    | GND         | Power Ground   |
| 28    | VCC         | +5.0V Power Supply   |
| 29    | VCC         | +5.0V Power Supply   |
| 30    | VCC         | +5.0V Power Supply   |



**Note1:** Start from left side



**Note2:** Input signals of odd and even clock shall be the same timing.

## 6.4 Timing Characteristics


### 6.4.1 Timing Characteristics

Basically, interface timings described here is not actual input timing of LCD module but output timing of SN75LVDS82DGG (Texas Instruments) or equivalent.

| Signal             | Item       | Symbol                            | Min   | Typ   | Max   | Unit |
|--------------------|------------|-----------------------------------|-------|-------|-------|------|
| Vertical Section   | Period     | $T_v$                             | 1060  | 1066  | 2048  | Th   |
|                    | Active     | $T_{disp(v)}$                     | 1050  | 1050  | 1050  | Th   |
|                    | Blanking   | $T_{bp(v)} + T_{fp(v)} + PW_{vs}$ | 10    | 16    | 998   | Th   |
| Horizontal Section | Period     | $T_h$                             | 890   | 1128  | 2408  | Tclk |
|                    | Active     | $T_{disp(h)}$                     | 840   | 840   | 840   | Tclk |
|                    | Blanking   | $T_{bp(h)} + T_{fp(h)} + PW_{hs}$ | 50    | 288   | 1208  | Tclk |
| Clock              | Period     | $T_{clk}$                         | 12.5  | 13.86 | 16.67 | ns   |
|                    | Frequency  | Freq                              | 47.17 | 72.1  | 80    | MHz  |
| Frame rate         | Frame rate | F                                 | 50    | 60    | 75    | Hz   |


**Note :** DE mode only

## 6.4.2 Timing diagram



## 6.5 Power ON/OFF Sequence

Vin power and lamp on/off sequence is as follows. Interface signals are also shown in the chart. Signals from any system shall be Hi-Z state or low level when Vin is off.



| Symbol | Values |     |     | Unit |
|--------|--------|-----|-----|------|
|        | Min    | Typ | Max |      |
| T1     | 0.5    | -   | 10  | [ms] |
| T2     | 0.5    | 40  | 50  | [ms] |
| T3     | 300    | -   | -   | [ms] |
| T4     | 300    | -   | -   | [ms] |
| T5     | 0.5    | 16  | 50  | [ms] |
| T6     | -      | -   | 100 | [ms] |
| T7     | 1000   | -   | -   | [ms] |

## 7. Connector & Pin Assignment

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

### 7.1 TFT LCD Module

#### 7.1.1 Connector

|                              |                                      |
|------------------------------|--------------------------------------|
| Connector Name / Designation | Interface Connector / Interface card |
| Manufacturer                 | JAE or compatible                    |
| Type Part Number             | FI-XB30SSRL-HF16                     |
| Mating Housing Part Number   | FI-X30S-H                            |

#### 7.1.2 Pin Assignment

| Pin# | Signal Name | Pin# | Signal Name |
|------|-------------|------|-------------|
| 1    | RxO0-       | 2    | RxO0+       |
| 3    | RxO1-       | 4    | RxO1+       |
| 5    | RxO2-       | 6    | RxO2+       |
| 7    | GND         | 8    | RxOC-       |
| 9    | RxOC+       | 10   | RxO3-       |
| 11   | RxO3+       | 12   | RxE0-       |
| 13   | RxE0+       | 14   | GND         |
| 15   | RxE1-       | 16   | RxE1+       |
| 17   | GND         | 18   | RxE2-       |
| 19   | RxE2+       | 20   | RxEC-       |
| 21   | RxEC+       | 22   | RxE3-       |
| 23   | RxE3+       | 24   | GND         |
| 25   | GND         | 26   | NC          |
| 27   | GND         | 28   | VCC         |
| 29   | VCC         | 30   | VCC         |



## 7.2 Backlight Unit

|                              |  |
|------------------------------|--|
| Connector Name / Designation | Lamp Connector / Backlight lamp                |
| Manufacturer                 | YEONHO   |
| Type Part Number             | 35001HS-02L (CN3/CN4)<br>35001HS-02L (CN2/CN5) |
| Mating Type Part Number      | SM02B-BHSS-1-TB (2pin)                         |

### 7.2.1 Signal for Lamp connector

|       | Connector No. | Pin No. | Color | Function              |
|-------|---------------|---------|-------|-----------------------|
| Upper | CN2           | 1       | Pink  | High Voltage (Lamp 1) |
|       |               | 2       | White | Low Voltage (Lamp 1)  |
|       | CN3           | 1       | Pink  | High Voltage (Lamp 2) |
|       |               | 2       | White | Low Voltage (Lamp 2)  |
| Upper | CN4           | 1       | Pink  | High Voltage (Lamp 3) |
|       |               | 2       | White | Low Voltage (Lamp 3)  |
|       | CN5           | 1       | Pink  | High Voltage (Lamp 4) |
|       |               | 2       | White | Low Voltage (Lamp 4)  |

## 8. Reliability

Reliability test condition

| Items                             | Required Condition  | Note |
|-----------------------------------|---|------|
| Temperature Humidity Bias (THB)   | Ta= 50°C , 80%RH, 300hours  |      |
| High Temperature Operation (HTO)  | Ta= 50°C , 50%RH, 300hours  |      |
| Low Temperature Operation (LTO)   | Ta= 0°C , 300hours  |      |
| High Temperature Storage (HTS)    | Ta= 60°C , 300hours   |      |
| Low Temperature Storage (LTS)     | Ta= -20°C , 300hours  |      |
| Vibration Test<br>(Non-operation) | Acceleration: 1.5 G<br>Wave: Random<br>Frequency: 10 - 200 - 10 Hz<br>Sweep: 30 Minutes each Axis (X, Y, Z)   |      |
| Shock Test<br>(Non-operation)     | Acceleration: 50 G<br>Wave: Half-sine<br>Active Time: 20 ms<br>Direction: ±X, ±Y, ±Z (one time for each Axis) |      |
| Drop Test                         | Height: 60 cm, package test   |      |
| Thermal Shock Test (TST)          | -20°C/30min, 60°C/30min, 100 cycles   | 1    |
| On/Off Test                       | On/10sec, Off/10sec, 30,000 cycles  |      |
| ESD (ElectroStatic Discharge)     | Contact Discharge: ± 8KV, 150pF(330Ω ) 1sec,<br>8 points, 25 times/ point.                                    | 2    |
|                                   | Air Discharge: ± 15KV, 150pF(330Ω ) 1sec<br>8 points, 25 times/ point.  |      |
| Altitude Test                     | Operation:10,000 ft   |      |


Note 1: The TFT-LCD module will not sustain damage after being subjected to 100 cycles of rapid temperature change. A cycle of rapid temperature change consists of varying the temperature from -20°C to 60°C, and back again. Power is not applied during the test. After temperature cycling, the unit is placed in normal room ambient for at least 4 hours before power on.

Note 2: According to EN61000-4-2 , ESD class B: Some performance degradation allowed. No data lost. Self-recoverable. No hardware failures.



## 9 Shipping Label

The label is on the panel as shown below:



## 10. Mechanical Characteristics

