Doc. Version	0.c
Total Page	43
Date	2007/10/23

Product Specifications

3.5" COLOR TFT-LCD MODULE

MODEL NAME: A035QN03 V0

< □ >Preliminary Specification

< >Final Specification

Note: The content of this specification is subject to change.

Record of Revision

Version	Revise Date	Page	Content
0.0	2007/01/19		First draft.
0.1	2007/01/25	6	Change the 50th pin from NC to VCOM
		30	Update the connector property and pin assignment
0.2	2007/02/08	6	Change the 27th pin from AVDD to NC
		8	Change the LED typical current from 20mA to 25mA and typical voltage from 19.2V to 19.8V.
		28	Modify the Module outline drawing.
		30	Update the pin assignment
0.3	2007/02/15	7	Change the VCI min. from 2.5 to 3.0
		8	
0.3a	2007/03/01	22~23	Correct optical remark
		24	Correct Reliability Test Items
0.4	2007/03/26	31, 32	Add power on/ off and STB sequence
		8	Modify the typical DCLK to 24.54 MHz
0.5	2007/03/28	4	Correct module thickness from 4 to 4.32
		7	Correct LED reverse voltage from 2V to 5V.
		22	Updated response time
0.6	2007/04/16	8	Modify the absolute maximum rating table
		10	Modify the electrical characteristic table
		10~13	Modify the AC timing tables and diagrams
		14~19	Modify the register timing, tables, and description
		27	Change C14 to 10 uF
		29~31	Add recommend power on/ off settings
		32	Add notes for ESD protection
0.7	2007/05/22	6	Move AGND, DGND, VCC, and VIO to pin31~34 respectively
		6	Add GRB to pin35
		7	Remove temperature operation/storage range
		7	Update LED limit curve
		26	Update the pin assignment in application circuit
0.8	2007/06/20	5, 21	Update Touch panel FPC pin assignment
0.9	2007/07/18	24	Update FPC outline dimension in drawing
0.a	2007/07/10	10	Modify the electrical characteristics

		12	Modify the minimum value of V-blanking in UPS051
		17~23	Modify the SPI settings
		33	Add GRB into power-on sequence
		37~42	Add recommended register settings
0.b	2007/08/15	11	Add general input timing
0.c	2007/10/23	25	Update response time spec

Contents:

A. General Description 5
B. Features 5
C. Physical Specifications 6
D. Electrical Specifications 7
1. Pin Assignment 7
2. Absolute Maximum Ratings 9
3. Electrical Characteristics 10
a. TFT- LCD Panel (GND=0V) 10
b. Backlight Driving Conditions 10
4. AC Timing 11
a. General input timing 11
b. UPS051 compatible input timing 12
c. UPS052 compatible input timing 13
d. CCIR656 15
e. YUV640/YUV720 16
5. Command Register Map 18
a. Command Timing: Serial Peripheral Interface 18
b. SPI timing diagram 19
c. Serial setting map 19
d. SPI AC specification 20
e. Description of serial control data 21
E. VCOM AC DC level definition Optical specifications (Note 1, 2) 25
F. Reliability Test Items 27
G. Touch Screen Panel Specifications 28
1. FPC Pin Assignment 28
2. Electrical Characteristics 28
3. Mechanical Characteristics 28
4. Life test Condition 29
5. Attention 29
H. Outline Dimension 31
I. Packing Form 32
J. Application Note 33
1. Application circuit 33

2. Power on/ off sequence 34
3. Standby timing 35
4. Recommand UPS052 320RGB (24.54MHz) Register Settings 36
5. Recommand UPS051 Register Settings 37
6. Recommand UPS052 360RGB (27MHz) Register Settings 38
7. Recommand YUV Mode A 640Y 320CrCb (24.54MHz) Register Settings 39
8. Recommand YUV Mode A 720Y 360CrCb (27MHz) Register Settings 40
9. Recommand YUV Mode B 640Y 320CrCb (24.54MHz) Register Settings 41
10. Recommand YUV Mode B 720Y 360CrCb (27MHz) Register Settings 42
11. Recommand CCIR656 720Y 360CrCb (27MHz) Register Settings 43
12. Recommand ESD Protection 44

A. General Description

A035QN03 V0 is an amorphous transmissive type Thin Film Transistor Liquid crystal Display (TFT-LCD). This model is composed of a TFT-LCD, a driver, an FPC (flexible printed circuit), a backlight unit and a touch panel.

B. Features

- 3.5-inch display with touch panel
- QVGA resolution in RGB stripe dot arrangement
- DC/DC integrated
- High brightness
- 3-wire register setting
- Digital 8-bit serial interface
- Wide viewing angle
- Integrated touch screen panel (resistive type)
- 3-in-1 FPC for LCD signals, backlight LED power and touch panel
- Green design

C. Physical Specifications

NO.	Item	Unit	Specification	Remark
1	Display Resolution	dot	320 RGB (H)×240(V)	
2	Active Area	mm	70.08(H)×52.56(V)	
3	Screen Size	inch	3.5(Diagonal)	
4	Dot Pitch	mm	0.073(H)×0.219(V)	
5	Color Configuration	--	R. G. B. Stripe	Note 1
6	Color Depth	--	16.7M Colors	
7	Overall Dimension	mm	76.9(H) × 63.9(V) × 4.32(T)	Note 2
8	Weight	g	39.8	
9	Panel surface treatment	--	Hard coating 3H	

Note 1: Below figure shows dot stripe arrangement.



Note 2: Not including FPC. Refer to the drawing next page for further information.

D. Electrical Specifications

1. Pin Assignment

Pin no.	Symbol	I/O	Description	Remarks
1	R	I/O	Touch panel right electrode	
2	B	I/O	Touch panel bottom electrode	
3	L	I/O	Touch panel left electrode	
4	U	I/O	Touch panel upper electrode	
5	NC		NC pin	
6	VCOM	I	VCOM	
7	VGL	C	Capacitor of charge pumping circuit	
8	VGH	C	Capacitor of charge pumping circuit	
9	C3P	C	Capacitor of charge pumping circuit	
10	C3M	C	Capacitor of charge pumping circuit	
11	V_10	C	Capacitor of charge pumping circuit	
12	V_5	C	Capacitor of charge pumping circuit	
13	VINT2	C	Capacitor of charge pumping circuit	
14	C2P	C	Capacitor of charge pumping circuit	
15	C2M	C	Capacitor of charge pumping circuit	
16	VCAC	C	Capacitor of VCOMAC circuit	
17	FRP	O	Frame polarity	
18	VINT1	C	Capacitor of charge pumping circuit	
19	C1BP	C	Capacitor of charge pumping circuit	
20	C1AP	C	Capacitor of charge pumping circuit	
21	C1BM	C	Capacitor of charge pumping circuit	
22	C1AM	C	Capacitor of charge pumping circuit	
23	AGND	G	Analog ground	
24	DGND	G	Digital ground	

25	NC		NC pin	
26	PVDD	PI	Analog power input, 3.0~3.6V is recommended.	
27	NC		NC pin	
28	GMA_H	C	Stabilizing capacitor for analog power	
29	LED_-	I	LED back light cathode	
30	LED_+	I	LED back light anode	
31	AGND	G	Analog ground	
32	DGND	G	Digital ground	
33	VCC	C	Digital power supply	
34	VIO	PI	Digital power input	
35	GRB	I	Global reset	
36	CS	I	Chip enable of serial interface	
37	SDA	IO	Serial data input and output of serial interface	
38	SCL	I	Clock of serial interface	
39	HSYNC	I	Horizontal synchronous signal	
40	VSYNC	I	Vertical synchronous signal	
41	DCLK	I	Dot clock	
42	DATA 7	I	Data of serial RGB input (MSB)	
43	DATA 6	I	Data of serial RGB input	
44	DATA 5	I	Data of serial RGB input	
45	DATA 4	I	Data of serial RGB input	
46	DATA 3	I	Data of serial RGB input	
47	DATA 2	I	Data of serial RGB input	
48	DATA 1	I	Data of serial RGB input	
49	DATA0	I	Data of serial RGB input (LSB)	
50	VCOM	I	VCOM	

I: Digital signal input, O: Digital signal output, IO: Digital inout pin, G: GND, PI: Power input

C: Power set capacitor connect pin.

2. Absolute Maximum Ratings

Items	Symbol	Values		Unit	Condition
		Min.	Max.		
Power Voltage	VIO	-0.5	7	V	
	AVDD	-0.5	7	V	
LED Reverse Voltage	Vr		5	V	One LED
LED Forward Current	If		30	mA	One LED, Note 2

Note 1.If the operating condition exceeds the absolute maximum ratings, the TFT-LCD module may be damaged permanently. Also, if the module operated with the absolute maximum ratings for a long time, its reliability may drop.

Note 2. If LED current exceeds the limit curve, the lifetime will drop dramatically.



Note 3. 90% RH maximum humidity when temp. ≤60°C.

If temp. >60°C, the maximum humidity shall be less than 90% RH.

3. Electrical Characteristics

The following items are measured under stable condition and suggested application circuit.

a. TFT- LCD Panel (GND=0V)

Parameter	Symbol	Min	Typ	Max	Unit	Notes
Digital Power Supply	VIO	1.8	3.3	3.6	V	
Analog Power Supply	PVDD	3.0	3.3	3.6	V	
Input Signal Voltage	Vi	0		0.2 x VIO	V	
	VI	0.8 x VIO		VIO	V	
Frame Frequency	f_{Frame}		60		Hz	
Dot Data Clock	DCLK		24.54		MHz	
VCOM	VCOMDC	0.4	1.0	1.66	V	
	VCOMAC	3.6	4.2	5	V	
Power Stand-by Current	$ISTB_{PVDD}$		25	50	uA	PVDD=3.3V
Power Operating Current	I_{PVDD}		10	20	mA	VIO=3.3V

Note 1. Panel surface temperature should be kept less than content of section 3.2. “Absolute maximum ratings"

b. Backlight Driving Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark
LED Supply Current	I_L		25		mA	single serial
LED Supply Voltage	V_L		19.8		V	single serial
LED Life Time	L_L	10,000	---	---	Hr	Note 2, 3

Note 1: LED backlight is six LEDs serial type.



Note 2: The ”LED Supply Voltage” is defined by the number of LED at Ta=25°C, I_L=20mA. In the case of 6 pcs LED, V_L=3.3*6=19.8V

Note 3: The ”LED life time” is defined as the time for the module brightness to decrease to 50% of the initial value at Ta=25°C, I_L=25mA

Note 4: The LED lifetime could be decreased if operating $I_L$is larger than 25mA

4. AC Timing

a. General input timing



Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
CLK pulse duty	Tcw		40	50	60	%
Delay between Hsync and DCLK	Thc		-	-	1	DCLK
Hsync width	Twh		1	-	-	DCLK
Hsync period	Th		60	63.56	67	us
Hsync setup time	Thst		15	-	-	ns
Hsync hold time	Thhd		15	-	-	ns
Vsync width	Twv		1	-	-	Hsync
Vsync setup time	Tvst		15	-	-	ns
Vsync hold time	Tvhd		15	-	-	ns
Data set-up time	Tdsu	D0~D7 to DCLK	15	-	-	ns
Data hold time	Tdhd	D0~D7 to DCLK	15	-	-	ns

b. UPS051 compatible input timing

Vertical Timing



Horizontal Timing



Timing specification

Parameter		Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK Frequency		$1/t_{DCLK}$	13.5	27	27.19	MHz	
Hsync	Period	t_H	1024	1716	1728	t_{DCLK}	
	Display period	t_{hdisp}	960			t_{DCLK}	
	Back porch	t_{hbp}	50	70	255	t_{DCLK}	
	Front porch	t_{hfp}	14	686	718	t_{DCLK}	

	Pulse width		t_{hsw}	1	1	-	t_{DCLK}	
Vsync	Period	Odd	t_V	241	262.5	-	t_H	
		Even						
	Display period	Odd	t_{vdisp}	240			t_H	
		Even						
	Back porch	Odd	t_{vbp}	13	20	28	t_H	
		Even		13.5	20.5	28.5		
	Front porch	Odd	t_{vfp}	0	4.5	-	t_H	
		Even		0	5	-		
	Pulse width		t_{vsw}	1	1	-	t_H	

c. UPS052 compatible input timing

Vertical Timing



Odd Field

Even Field

Horizontal Timing



Timing specification

NTSC:

Parameter			Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK Frequency			$1/t_{DCLK}$	-	24.535	-	MHz	
Hsync	Period		t_H	-	1560	-	t_{DCLK}	
	Display period		t_{hdisp}		1280		t_{DCLK}	
	Back porch		t_{hbp}	-	241	-	t_{DCLK}	
	Front porch		t_{hfp}	0	28	-	t_{DCLK}	
	Pulse width		t_{hsw}	1	1	-	t_{DCLK}	
Vsync	Period	Odd	t_V	-	262.5	-	t_H	
		Even						
	Display period	Odd	t_{vdisp}		240		t_H	
		Even						
	Back porch	Odd	t_{vbp}	-	21	-	t_H	
		Even		-	21.5	-		
	Pulse width		t_{vsw}	1	1	-	t_H	

PAL:

Parameter		Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK Frequency		$1/t_{DCLK}$	-	24.375	-	MHz	
Hsync	Period	t_H	-	1560	-	t_{DCLK}	
	Display period	t_{hdisp}		1280		t_{DCLK}	
	Back porch	t_{hbp}	-	241	-	t_{DCLK}	

	Front porch		t_{hfp}	0	28	-	t_{DCLK}	
	Pulse width		t_{hsw}	1	1	-	t_{DCLK}	
Vsync	Period	Odd	t_V	-	312.5	-	t_H	
		Even						
	Display period	Odd	t_{vdisp}	288			t_H	
		Even						
	Back porch	Odd	t_{vbp}	-	24	-	t_H	
		Even		-	24.5	-		
	Pulse width		t_{vsw}	1	1	-	t_H	

d. CCIR656

Timing format



Timing specification

Parameter			Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK Frequency			$1/t_{DCLK}$	-	27	-	MHz	
Hsync	Period		t_H	-	1716	-	t_{DCLK}	
	Display period		t_{hdisp}	1440			t_{DCLK}	
	Back porch		t_{hbp}	-	273	-	t_{DCLK}	
	Front porch		t_{hfp}	4	4	4	t_{DCLK}	
	Pulse width		t_{hsw}	1	-	-	t_{DCLK}	
Vsync	Period	Odd	t_V		262.5		t_H	
		Even						
	Display period	Odd	t_{vdisp}	240			t_H	
		Even						
	Back porch	Odd	t_{vbp}	-	18	-	t_H	
		Even		-	17.5	-		
	Front porch	Odd	t_{vfp}	0	4.5	-	t_H	
		Even		0	5	-		
	Pulse width	Odd	t_{vsw}	1	-	-	t_{DCLK}	
		Even						

e. YUV640/YUV720

YUV640 mode A horizontal timing



YUV640 mode B horizontal timing



YUV720 mode A horizontal timing



YUV720 mode B horizontal timing



Timing specification

YUV640 mode

NTSC:

Parameter			Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK Frequency			$1/t_{DCLK}$	-	24.535	-	MHz	
Hsync	Period		t_H	-	1560	-	t_{DCLK}	
	Display period		t_{hdisp}	1280			t_{DCLK}	
	Back porch		t_{hbp}	-	241	-	t_{DCLK}	
	Front porch		t_{hfp}	0	1	-	t_{DCLK}	
	Pulse width		t_{hsw}	1	1	-	t_{DCLK}	
Vsync	Period	Odd	t_V	-	262.5	-	t_H	
		Even						
	Display period	Odd	t_{vdisp}	240			t_H	
		Even						
	Back porch	Odd	t_{vbp}	-	21	-	t_H	
		Even		-	21.5	-		

PAL:

Parameter			Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK Frequency			$1/t_{DCLK}$	-	24.375	-	MHz	
Hsync	Period		t_H	-	1560	-	t_{DCLK}	
	Display period		t_{hdisp}	1280			t_{DCLK}	
	Back porch		t_{hbp}	-	241	-	t_{DCLK}	
	Front porch		t_{hfp}	0	1	-	t_{DCLK}	
	Pulse width		t_{hsw}	1	1	-	t_{DCLK}	
Vsync	Period	Odd	t_V	-	312.5	-	t_H	
		Even						
	Display period	Odd	t_{vdisp}	288			t_H	
		Even						
	Back porch	Odd	t_{vbp}	-	24	-	t_H	
		Even		-	24.5	-		

YUV 720 mode

NTSC:

Parameter			Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK Frequency			$1/t_{DCLK}$	-	27	-	MHz	
Hsync	Period		t_H	-	1716	-	t_{DCLK}	
	Display period		t_{hdisp}		1440		t_{DCLK}	
	Back porch		t_{hbp}	-	241	-	t_{DCLK}	
	Front porch		t_{hfp}	0	1	-	t_{DCLK}	
	Pulse width		t_{hsw}	1	1	-	t_{DCLK}	
Vsync	Period	Odd	t_V	-	262.5	-	t_H	
		Even						
	Display period	Odd	t_{vdisp}		240		t_H	
		Even						
	Back porch	Odd	t_{vbp}	-	21	-	t_H	
		Even		-	21.5	-		

PAL:

Parameter			Symbol	Min.	Typ.	Max.	Unit.	Remark
DCLK Frequency			$1/t_{DCLK}$	-	27	-	MHz	
Hsync	Period		t_H	-	1728	-	t_{DCLK}	
	Display period		t_{hdisp}		1440		t_{DCLK}	
	Back porch		t_{hbp}	-	241	-	t_{DCLK}	
	Front porch		t_{hfp}	0	1	-	t_{DCLK}	
	Pulse width		t_{hsw}	1	1	-	t_{DCLK}	
Vsync	Period	Odd	t_V	-	312.5	-	t_H	
		Even						
	Display period	Odd	t_{vdisp}		288		t_H	
		Even						
	Back porch	Odd	t_{vbp}	-	24	-	t_H	
		Even		-	24.5	-		

5. Command Register Map

a. Command Timing: Serial Peripheral Interface

Configuration of serial data at SDA terminal

MSB LSB

D15	D14	D13	D12	D11	D10	D9	D8	D7	D6	D5	D4	D3	D2	D1	D0
Register address				R/W	DATA										

Note: R/W = '0' ➔ Write mode R/W = '1' ➔ Read mode

Write mode waveform



Read mode waveform



b. SPI timing diagram

AC serial interface write mode timings



AC serial interface read mode timings



c. Serial setting map

Reg N°	ADDRESS				CONTENT											
	D15	D14	D13	D12	D11	D10	D9	D8	D7	D6	D5	D4	D3	D2	D1	D0

R0	0	0	0	0	R/W	-	-	*		*	U/D	SHL	GRB	STB	SHDB	SHCB
R1	0	0	0	1	R/W	-	-	-	-	*	PARAL	PALM	PAL	SEL		
R2	0	0	1	0	R/W	-	-	DDL_E	DDL							
R3	0	0	1	1	R/W	-	-	-	-	-	*		HDL			
R4	0	1	0	0	R/W	-	-	-	-	*	*			*	*	*
R5	0	1	0	1	R/W	-	-	-	-	-	-	-	CONTRAST			
R6	0	1	1	0	R/W	-	-	-	-	BRIGHTNESS						
R7	0	1	1	1	R/W	-	-	-	-	-	-	-	-	-	-	-
R8	1	0	0	0	R/W	-	-	-	-	-	-	-	VCOM_AC			
R9	1	0	0	1	R/W	-	-	-	-	VDCE	VCOM_DC					
R10	1	0	1	0	R/W	-	-	-	-	1	1	0	*		*	

Reg N°	ADDRESS				DEFAULT VALUES											
	D15	D14	D13	D12	D11	D10	D9	D8	D7	D6	D5	D4	D3	D2	D1	D0
R0	0	0	0	0	R/W	-	-	(00)		(0)	(1)	(1)	(1)	(1)	(0)	(1)
R1	0	0	0	1	R/W	-	-	-	-	(0)	(0)	(1)	(0)	(001)		
R2	0	0	1	0	R/W	-	-	(0)	(46h)							
R3	0	0	1	1	R/W	-	-	-	-	-	(01)		(7h)			
R4	0	1	0	0	R/W	-	-	-	-	(1)	(010)			(0)	(1)	(1)
R5	0	1	0	1	R/W	-	-	-	-	-	-	-	(8h)			
R6	0	1	1	0	R/W	-	-	-	-	(40h)						
R7	0	1	1	1	R/W	-	-	-	-	-	-	-	-	-	-	-
R8	1	0	0	0	R/W	-	-	-	-	-	-	-	(7h)			
R9	1	0	0	1	R/W	-	-	-	-	(1)	(2Dh)					
R10	1	0	1	0	R/W	-	-	-	-	(1)	(1)	(0)	(01)		(10)	

* Reserved

Note: Register R0/(D8,D7) must be (01)

d. SPI AC specification

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
Serial clock period	Tsck	320	-	-	ns
Serial clock duty cycle	Tscw	40	50	60	%
Serial clock width low/high	Tssw	120	-	-	ns
Serial data setup time	Tist	120	-	-	ns
Serial data hold time	Tihd	120	-	-	ns
Serial data output delay	Tid	-	-	60	ns

CSB setup time	Tcst	120	-	-	ns
CSB data hold time	Tchd	120	-	-	ns
Chip select distinguish	Tcd	1	-	-	us
Delay between CSB and Vsync	Tcv	1	-	-	us

- Each serial command consists of 16 bits of data which is loaded one bit a time at the **rising edge** of serial clock SCL.
- Command loading operation starts from the falling edge of CS and is completed at the next rising edge of CS.
- The serial control block is operational after power on reset, but commands are established by the **Vsync** signal. If command is transferred multiple times for the same register, **the last command before the Vsync signal is valid.**
- If less than 16 bits of SCL are input while CS is low, the transferred data is ignored.
- If 16 bits or more of SCL are input while CS is low, the previous 16 bits of transferred data before the rising edge of CS pulse are valid data.
- Serial block operates with the SCL clock
- Serial data can be accepted in the power save mode.

e. Description of serial control data

R0: System settings

Address	Bit	Description		Default
0000	[5..0]	Bit5(U/D)	Vertical shift direction selection.	0_0011_1101b
		Bit4(SHL)	Horizontal shift direction selection.	
		Bit3(GRB)	Global reset.	
		Bit2(STB)	Standby mode setting.	
		Bit1(SHDB)	DC-DC converter shutdown setting.	
		Bit0(SHCB)	Charge Pump shutdown setting.	

Bit5	UD function
0	Flip vertically
1	**(default)**

Bit4	SHL function
0	Flip horizontally
1	**(default)**

Bit3	GRB function
0	The controller is reset, the charge pump and DCDC are off. Reset all registers to default value.
1	Normal operation. **(default)**

Bit2	STB function
0	T-CON, source driver and DC-DC converter are off. All outputs are High-Z.
1	Normal operation. **(default)**

Bit1	SHDB function
0	DC-DC converter is off. **(default)**
1	DC-DC converter is on. DC-DC controlled by STB and power on/off sequence.

Bit0	SHCB function
0	Charge Pump converter is off.
1	Charge Pump converter is on. **(default)** Charge Pump controls by STB and power on/off sequence.

R1: Timings settings

Address	**Bit**	**Description**		**Default**
0001	[4..0]	Bit4(PALM)	PAL 1/6, PAL1/6,8 selection.	001_0001b
		Bit3(PAL)	PAL/NTSC selection.	
		Bit2-0(SEL)	Input data format selection.	

Bit4	PALM function
0	Manual PAL/NTSC selection
1	Automatic PAL/NTSC detection **(default)**

Bit3	PAL function
0	NTSC Input format (240 active line). **(default)**
1	PAL Input format (288 active line).

Bit2-0	SEL function
000	UPS051 path, special data format: DDX.

001	UPS052 320RGB 24.54MHz data format. **(default)**
010	UPS052 360RGB 27MHz data format.
011	YUV mode A 640Y 320CrCb 24.54MHz data format.
100	YUV mode A 720Y 360CrCb 27MHz data format.
101	YUV mode B 640Y 320CrCb 24.54MHz data format.
110	YUV mode B 720Y 360CrCb 27MHz data format.
111	CCIR 656 720Y 360CrCb 27MHz data format.

R2: Data delay settings

Address	Bit	Description		Default
0010	[8..0]	Bit8(DDL_E)	DDL setting selection.	0_0100_0110b
		Bit7-0(DDL)	Horizontal Data start delay selection.	

DDL_E	DDL	T_{HS}	Unit	Remark
X	00h	0	DCLK	UPS051
X	46h	70 (Default)	DCLK	
X	FFh	255	DCLK	
0	XXh	241(fixed)	DCLK	UPS051/YUV
1	00h~FFh	64~319	DCLK	
0	XXh	61(fixed)	DCLK	Parallel RGB
1	00h~FFh	0~255	DCLK	



R3: Vertical delay settings

Address	Bit	Description		Default
0011	[5..0]	Bit5-4(OEA)	Odd Even advance selection.	01_0111b
		Bit3-0(HDL)	Vertical delay selection.	

Bit5-4	OEA function (only in CCIR mode)
00	Display start @T_{VS} delay for Odd and Even field.

01	Display start @ T_{VS} delay for Odd field and @ T_{VS} +1 for Even field. **(default)**
1X	Display start @ T_{VS} +1 delay for Odd field and @ T_{VS} for Even field.

Bit3-0	HDL function
0000	TSTV=TVStyp - 7 Hsync period
0111	TSTV=TVStyp - 0 Hsync period. **(default)**
1111	TSTV=TVStyp + 8 Hsync period

R9: VCOM DC settings

Address	Bit	Description		Default
1001	[6..0]	Bit6(VDCE)	VCOM DC Enable signal.	110_1101b
		Bit5-0(VCOM_DC)	VCOM DC level adjustment. Step 20mV/LSB.	

Bit6	VDCE function
0	VCOM DC function disables VCOM pin HighZ. VCOM_DC=VCOM_AC/2.
1	DC voltage of VCOM follows VCOM_DC settings.**(default)**

Bit5-0	VCOM DC level	
	MVA/Normal LC	Low Voltage LC
00h	1.4V	0.4V
2Dh	2.30V **(default)**	1.30V **(default)**
3Fh	2.66V	1.66V

VOL_{VCOM}= VCOM_DC-VCOM_AC/2

VOH_{VCOM}= VCOM_DC+VCOM_AC/2



E. VCOM AC DC level definition Optical specifications (Note 1, 2)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Response Time							
Rise	Tr	θ =0°	-	7	10	ms	Note 4
Fall	Tf		-	28	40	ms	
Contrast ratio	CR	At optimized viewing angle	200	300	-		Note 5, 6
Viewing Angle							
Top			35	50	-		
Bottom		CR≧10	40	55	-	deg.	Note 7
Left			45	60	-		
Right			45	60	-		
Brightness (w/ TP)	Y_L	θ =0°	200	250	-	cd/m^2	Note 8
White Chromaticity	X	θ =0°	0.26	0.31	0.36		
	y	θ =0°	0.28	0.33	0.38		

Note 1 Ambient temperature = 25□.

Note 2 Measured in the dark room

Note 3 Measured on the center area of panel with a field angle of 1° by Topcon luminance meter BM-7, after 10 minutes operation.

Note 4 Definition of response time:

Output signals of photo detector are measured when the input signals are changed from “black” to “white” (falling time) and from “white” to “black” (rising time), respectively.

Response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to the figure as follows.



Note 5 Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Photo detector output when LCD is at “White” state}}{\text{Photo detector output when LCD is at “Black” state}}$$

Note 6 White Vi = V_{i50} ⊣ 1.5V

Black Vi = V_{i50} ± 2.0V

“±” means that the analog input signal swings in phase with COM signal.

“⊣” means that the analog input signal swings out of phase with COM signal.

$V_{i50:}$ The analog input voltage when transmission is 50%

100% transmission is defined as the transmission of LCD panel when all the input terminals of module are electrically opened.

Note 7 Definition of viewing angle:

Refer to the figure as follows.



Note 8 Measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.

F. Reliability Test Items

No.	Test items	Conditions	Remark
1	High temperature storage	Ta = 80□ 240Hrs	
2	Low temperature storage	Ta = -25□ 240Hrs	
3	High temperature operation	Ta = 60□ 240Hrs	
4	Low temperature operation	Ta = 0□ 240Hrs	
5	High temperature and high humidity	Ta = 60□. 90% RH 240Hrs	Operation
6	Heat shock	-25□~80□, 50 cycles, 2Hrs/cycle	Non-operation
7	Electrostatic discharge	± 200V,200pF (0Ω), once for each terminal	Non-operation
8	Vibration (with carton)	Random vibration: 0.015G^2/Hz from 5~200Hz –6dB/Octave from 200~500Hz	IEC 68-34
9	Drop (with carton)	Height: 60cm 1 corner, 3 edges, 6 surfaces	

Note 1: Ta: Ambient temperature.

G. Touch Screen Panel Specifications

1. FPC Pin Assignment

Pin No.	Symbol	I/O
1	R	I/O
2	B	I/O
3	L	I/O
4	U	I/O



2. Electrical Characteristics

Item		Min.	Max.	Unit	Remark
Rate DC Voltage			7	V	
Resistance	X (Film)	350	950	Ω	At connector
	Y (Glass)	150	800		
Linearity		-1.5%	1.5%	--	Note 1, test by 250 gf
Chattering			10	ms	At connector pin
Insulation Resistance		10M		Ω	DC 25V

Note 1: Measurement condition of Linearity: difference between actual voltage & theoretical voltage is an error at any points. Linearity is the value max. error voltage divided by voltage difference on active area.



3. Mechanical Characteristics

Item	Min.	Max.	Unit	Remark
Hardness of Surface	3	--	H	JIS K-5400
Operation Force (Pen or Finger)	--	50	gf	Note 1

Note 1: Within ”guaranteed active area”, but not on the edge and dot-spacer.

4. Life test Condition

Item	Min.	Max.	Unit	Remark
Notes Life	10^5	--	words	Note 1, 2
Input Life	10^6	--	times	Note 1, 3

Note 1: Measurement condition of Operation Force: Within "guaranteed active area". Resistance, Insulation resistance, and operation force should be under 5.2 & 5.3 condition. When user pushes down on the film, resistance between X & Y axis must be equal or lower than 2kΩ. Below is test figure.



Note 2: Notes Life test condition (by pen): Notes area for pen notes life test is 10×9 mm. Size of word is 7.5×6.75mm. Word is any A.B.C….. letter. Writing speed is 60mm/s. Center of each word is changed at random in notes area.



Note 3: Input Life test condition(by finger): By silicone rubber tapping at same point. Tapping Load is 200g, and tapping frequency is 5Hz.

5. Attention

Please pay attention for below matters at mounting design of touch panel of LCD module.

1. Do not design enclosure pressing the view area to prevent from miss input.
2. Enclosure support must not touch with view area.
3. Use elastic or non-conductive material to enclosure touch panel.

4. Do not bond film of touch panel with enclosure.
5. The touch panel edge is conductive. Do not touch it with any conductive part after mounting.
6. If user wants to cleaning touch panel by air gun, pressure 2kg/cm2 below is suggested. Not to blow glass from FPC site to prevent FPC peeled off.

7. Do not put a heavy shock or stress on touch panel and film surface. Ex. Don't lift the panel by film face with vacuum.
8. Do not lift LCD module by FPC.
9. Please use dry cloth or soft cloth with neutral detergent (after wring dry) or one with ethanol at cleaning. Do not use any organic solvent, acid or alkali liquor.
10. Do not pile touch panel. Do not put heavy goods on touch panel.

Recommendation of the cushion area:





H. Outline Dimension



I. Packing Form



MAX. CAPACITY:160 MODULES
MAX. WEIGHT: 12Kg
MEAS. 520mm*340mm*250mm

J. Application Note

1. Application circuit

The folowing drawing is the application circuit recommended.



Table of Capacitors

Item	Quantity	Reference	Part
1	7	C1,C2,C3,C4,C11,C12,C13	1uF/10V/X7R
2	4	C5,C6,C7,C8	2.2uF/10V/X7R
3	2	C9,C10	1uF/25V/X7R
4	1	C14	10 uF/10V/X7R

2. Power on/ off sequence

POWER ON



POWER OFF



3. Standby timing



4. Recommand UPS052 320RGB (24.54MHz) Register Settings





5. Recommand UPS051 Register Settings



6. Recommand UPS052 360RGB (27MHz) Register Settings



7. Recommand YUV Mode A 640Y 320CrCb (24.54MHz) Register Settings



8. Recommand YUV Mode A 720Y 360CrCb (27MHz) Register Settings



9. Recommand YUV Mode B 640Y 320CrCb (24.54MHz) Register Settings



10. Recommand YUV Mode B 720Y 360CrCb (27MHz) Register Settings



11. Recommand CCIR656 720Y 360CrCb (27MHz) Register Settings



12. Recommand ESD Protection

- In order to recover from register corruption cause from ESD, AUO suggests that registers should be set repeatedly.
- AUO suggests the bezel connects to system GND to enhance ESD protection ability.