

1. OVERVIEW

CLAA141XC01(with LVDS interface) is 14.1" color TFT-LCD (Thin Film Transistor Liquid Crystal Display) module composed of LCD panel , driver ICs , control circuit , and backlight.

By applying 6 bits digital data, 1024× 768, 262K color images are displayed on the 14.1" diagonal screen. Input power voltage is single 3.3V for LCD driving.

Inverter for backlight is not included in this module. General specifications are summarized in the following table:

| ITEM | SPECIFICATION |
|--------------------------------|--|
| Display Area(mm) | 285.696(H) x 214.272(V) (14.1-inch diagonal) |
| Number of Pixels | 1024(H) x 768(V) |
| Pixel Pitch(mm) | 0.279(H) x 0.279(V) |
| Color Pixel Arrangement | RGB vertical stripe |
| Display Mode | normally white TN |
| Number of Colors | 262144 colors |
| Optimum Viewing Angle | 6 o'clock |
| Brightness(cd/m ²) | 150 |
| Power consumption(W) | 4.7 |
| Module Size(mm) | 298.5(W) x 227.5(H) x 5.8(D) |
| Module Weight(g) | 550 _{typ} |
| Backlight Unit | CCFL , 1 tube |

The LCD Products listed on this document are not suitable for use of aerospace equipment, submarine cables, nuclear reactor control system and life support systems. If customers intend to use these LCD products for above application or not listed in "Standard" as follows , please contact our sales people in advance.

Standard: Computer, Office equipment, Communication equipment, Test and Measurement equipment , Machine tool , Industrial robot , Audio and Visual equipment , Other consumer products.

2. ABSOLUTE MAXIMUM RATINGS

| ITEM | SYMBOL | MIN. | MAX. | UNIT |
|------------------------------|-------------------|------|---------|------|
| Power Supply Voltage for LCD | VCC | -0.3 | 4.0 | V |
| LVDS input Voltage | VI | -0.3 | VCC+0.3 | V |
| Static Electricity *1) | VESDt | -250 | 250 | V |
| | VESDc | -15 | 15 | KV |
| ICC Rush Current *2) | I _{RUSH} | | 3.75 | A |
| Operation Temperature *3) | Top | 0 | 50 | °C |
| Storage Temperature *3) | Tstg | -20 | 60 | °C |
| Starting Lamp Voltage | V _{SL} | 0 | 2000 | V |

[Note] : *1) Test Condition: IEC 1000-4-2 ,

VESDt : Contact discharge to input connector

VESDc : Contact discharge to module

*2) 50 μ sec , If Vcc rise time increase then I_{RUSH} decrease.

*3) Humidity \leq 85% RH. without condensation.

3. ELECTRICAL CHARACTERISTICS

(1)TFT-LCD

Ta = 25°C

| ITEM | SYMBOL | MIN | TYP | MAX | UNIT | Remark |
|---------------------------------|----------------------------|-----|-------|-----|-------|----------------|
| Power Supply Voltage for LCD | VCC | 3.0 | 3.3 | 3.6 | V | [Note 1] |
| Power Supply Current for LCD | ICC | - | 450 | 800 | mA | [Note 2] |
| Logic input Voltage [Note 3] | Input Voltage | VIN | 0 | - | VCC | V |
| | Common Mode Voltage | VCM | 1.125 | - | 1.375 | V |
| | Differential Input Voltage | VID | 250 | 345 | 450 | mV |
| | Threshold Voltage(High) | VTH | - | - | 100 | mV |
| | Threshold Voltage(Low) | VTL | -100 | - | - | mV |
| Tolerance of VID | Δ VID | - | - | 35 | mV | When VCM=+1.2V |
| Tolerance of VCM | Δ VCM | - | - | 35 | mV | |


[Note 1]

● VCC turn on conditions :

$$t1 \leq 10 \text{ ms}$$

$$0\text{ms} < t2 \leq 50\text{ms}$$

$$0\text{ms} \leq t3 \leq 50\text{ms}$$




● VCC dip conditions :

1) When $2.4\text{V} \leq \text{VCC} < 3.0\text{V}$, $t_d \leq 15 \text{ ms}$

2) When $\text{VCC} < 2.4\text{V}$

VCC dip conditions should follow VCC turn on conditions.



[Note 2]

● Typical value is measured when displaying horizontal gray scale line pattern



64 gray level

768 line mode

VCC = +3.3V

[Note 3]

● LVDS Signal definition :



$$\text{VID} = \text{VIN}_+ - \text{VIN}_-$$

$$\Delta \text{VCM} = | \text{VCM}_+ - \text{VCM}_- |$$

$$\Delta \text{VID} = | \text{VID}_+ - \text{VID}_- |$$

$$\text{VID}_+ = | \text{VIH}_+ - \text{VIH}_- |$$

$$\text{VID}_- = | \text{VIL}_+ - \text{VIL}_- |$$

$$\text{VCM} = (\text{VIN}_+ - \text{VIN}_-) / 2$$

$$\text{VCM}_+ = (\text{VIH}_+ - \text{VIH}_-) / 2$$

$$\text{VCM}_- = (\text{VIL}_+ - \text{VIL}_-) / 2$$

VIN₊ = Positive differential DATA & CLK Input

VIN₋ = Negative differential DATA & CLK Input

Ta = 25°C

| ITEM | SYMBOL | MIN | TYP | MAX | UNIT |
|---------------------------|-----------|-------|-----|------|------|
| Lamp Voltage | VL | 630 | 700 | 770 | V |
| Lamp Current <i>*1)</i> | IL | 3.0 | 5.0 | 6.0 | mA |
| Inverter Frequency | FI | 40 | 50 | 60 | KHz |
| Lamp life time <i>*2)</i> | Life L | 10000 | - | - | hr |
| Starting Lamp Voltage | Ta = 25°C | Vs | - | 1000 | V |
| | Tb = 0°C | | - | 1300 | |

[Note]*1) Standard inverter : IM 4201 , typical luminance = 150 cd/m² .

*2) The time that module luminance reduced to 50% of initial value .

Base on Vs = 1000 V , Ta = 25°C , IL=5.0 mA continuous.

4. INTERFACE CONNECTION

(1) CN1 (INTERFACE SIGNAL)

- Connector type : FI-SEB20P-HF13 (JAE made)
- Corresponding connector type : (reference)
FI-SE20M (JAE made , FPC type) , FI-S20S (JAE made , wire)

| pin | Symbol | Function |
|-----|---------|---|
| 1 | VCC | +3.3V power supply |
| 2 | VCC | +3.3V power supply |
| 3 | GND | |
| 4 | GND | |
| 5 | Link 0- | R0, R1, R2, R3, R4, R5,G0 [Note] |
| 6 | Link 0+ | R0, R1, R2, R3, R4, R5,G0 [Note] |
| 7 | GND | |
| 8 | Link 1- | G1, G2, G3, G4, G5,B0,B1 [Note] |
| 9 | Link 1+ | G1, G2, G3, G4, G5,B0,B1 [Note] |
| 10 | GND | |
| 11 | Link 2- | B2, B3, B4, B5,HD,VD,DENA [Note] |
| 12 | Link 2+ | B2, B3, B4, B5,HD,VD,DENA [Note] |
| 13 | GND | |
| 14 | CLKIN- | Clock- |
| 15 | CLKIN+ | Clock+ |
| 16 | GND | |
| 17 | TEST | Should be open during operation |
| 18 | TEST | Should be open during operation |
| 19 | GND | |
| 20 | GND | |

[Note] Refer to page 4 , 5 , 6 (Data Mapping)

(2) CN2 (BACK LIGHT)


- Backlight-side connector : BHSR-02VS-1(JST made)
- Inverter-side connector : SM02B-BHSS-1(JST made)

| Pin No. | Symbol | Function |
|---------|--------|--------------------|
| 1 | CTH | VLH (High voltage) |
| 2 | CTL | VL (Low voltage) |

[Note] VLH-VL = VL


5. Input Signal Timing

(1) LVDS (Rx) Input Signal Timing Chart




| Cell | IN *) | DATA |
|------|---------|------|
| POC1 | TxIN 0 | R0 |
| POC2 | TxIN 1 | R1 |
| POC3 | TxIN 2 | R2 |
| POC4 | TxIN 3 | R3 |
| POC5 | TxIN 4 | R4 |
| POC6 | TxIN 6 | R5 |
| POC7 | TxIN 7 | G0 |
| P1C1 | TxIN 8 | G1 |
| P1C2 | TxIN 9 | G2 |
| P1C3 | TxIN 12 | G3 |
| P1C4 | TxIN 13 | G4 |

| Cell | IN *) | DATA |
|---------|----------|------|
| P1C5 | TxIN 14 | G5 |
| P1C6 | TxIN 15 | B0 |
| P1C7 | TxIN 18 | B1 |
| P2C1 | TxIN 19 | B2 |
| P2C2 | TxIN 20 | B3 |
| P2C3 | TxIN 21 | B4 |
| P2C4 | TxIN 22 | B5 |
| P2C5 | TxIN 24 | HD |
| P2C6 | TxIN 25 | VD |
| P2C7 | TxIN 26 | DENA |
| Ref-CLK | TxCLK IN | DCLK |




Parallel TTL Data Mapped to LVDS Receiver Inputs—DS90CF384A

*)DS90C383(N.S.) LVDS Transmitter Pin Diagram




Receiver LVDS Input Strobe Position



Receiver LVDS Input Skew Margin

(2) LCD (Tx) Input Signal Timing Chart : (= Rx output)



(3)Timing Specifications

| ITEM | | | SYMBOL | MIN | TYP | MAX | UNIT |
|--|----------------------------------|------------------------|--------|------|------|------|------|
| LVDS Input Timing | CLK frequency | | FCLKin | - | 65 | 66.6 | MHz |
| | CLK period | | tCLKin | 15 | 15.4 | - | ns |
| | LVDS High to Low transition time | | LLHT | - | 0.75 | 1.5 | ns |
| | LVDS Low to High transition time | | LHLT | - | 0.75 | 1.5 | ns |
| | Strobe position of Bit 0 | f = 65MHz | Rsp0 | 0.7 | 1.1 | 1.4 | ns |
| | Strobe position of Bit 1 | | Rsp1 | 2.9 | 3.3 | 3.6 | ns |
| | Strobe position of Bit 2 | | Rsp2 | 5.1 | 5.5 | 5.8 | ns |
| | Strobe position of Bit 3 | | Rsp3 | 7.3 | 7.7 | 8.0 | ns |
| | Strobe position of Bit 4 | | Rsp4 | 9.5 | 9.9 | 10.2 | ns |
| | Strobe position of Bit 5 | | Rsp5 | 11.7 | 12.1 | 12.4 | ns |
| | Strobe position of Bit 6 | | Rsp6 | 13.9 | 14.3 | 14.6 | ns |
| | RxIN Skew Margin | | RSKM | 400 | - | - | ps |
| LCD input signal (LVDS Tx Input , Rx output) | DENA | Low width | tWDL | 100 | 320 | - | tCLK |
| | | Horizontal Front Porch | tHFP | 10 | 24 | - | TCLK |
| | | Horizontal Back Porch | tHBP | 4 | 296 | - | TCLK |
| | | Vertical Front Porch | tVFP | 2 | 3 | - | TH |
| | | Vertical Back Porch | tVBP | 1 | 35 | - | tH |
| | HD | Frequency | fH | - | 48.5 | 55.9 | kHz |
| | | Period | tH | 1100 | 1340 | - | tCLK |
| | | Low width | tWHL | 1 | 136 | - | tCLK |
| | VD | Frequency | fV | - | 60 | 62 | Hz |
| | | Period | tV | 772 | 806 | - | tH |
| | | Low width | tWVL | 1 | 6 | - | tH |

[Note]

- 1) Polarities of HD and VD are negative in this specification.
- 2) DENA (Data Enable) should always be positive polarity as shown in the timing specification.
- 3) CLKIN should appear during all invalid period, and HD should appear during invalid period of frame cycle.
- 4) LVDS Receiver model : DS90C384(NS made).

(4) Color data definition

| COLOR | INPUT DATA | R DATA | | | | | | G DATA | | | | | | B DATA | | | | | |
|-------------|------------|-----------|----|----|----|----|-----------|-----------|----|----|----|----|-----------|-----------|----|----|----|----|-----------|
| | | R5 MSB | R4 | R3 | R2 | R1 | R0 LSB | G5 MSB | G4 | G3 | G2 | G1 | G0 LSB | B5 MSB | B4 | B3 | B2 | B1 | B0 LSB |
| Basic Color | BLACK | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | RED(63) | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | GREEN(63) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | BLUE(63) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
| | CYAN | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| | MAGENTA | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
| | YELLOW | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | WHITE | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| RED | RED(0) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | RED(1) | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | RED(2) | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / |
| | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / |
| | RED(62) | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | RED(63) | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| GREEN | GREEN(0) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | GREEN(1) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | GREEN(2) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / |
| | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / |
| | GREEN(62) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | GREEN(63) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| BLUE | BLUE(0) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | BLUE(1) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| | BLUE(2) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 |
| | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / |
| | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / | / |
| | BLUE(62) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 |
| | BLUE(63) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |

[Note]


(1) Definition of gray scale:

Color(n) : n means level of gray scale .

Bigger n means brighter level.


(2) Data : 1= High , 0 = Low

6. BLOCK DIAGRAM




7. MECHANICAL DIMENSION

(1) Front side



(2) Rear side

Unit : mm





8. OPTICAL CHARACTERISTICS

$T_a = 25^{\circ}\text{C}$, $V_{cc}=3.3\text{V}$

| ITEM | SYMBOL | CONDITION | MIN. | TYP. | MAX. | UNIT |
|----------------------------|-------------|--------------------------------|-------|----------|-------|-----------------|
| Contrast Ratio | CR | $\varphi = \theta = 0^{\circ}$ | | 200 | - | - |
| Luminance ^{*)} | L | $\varphi = \theta = 0^{\circ}$ | 120 | 150 | - | cd/m^2 |
| Luminance Uniformity | ΔL | ^{*)} | - | - | 30 | % |
| Contrast Ratio Uniformity | ΔCR | ^{*)} | - | - | 70 | % |
| Response Time | tr | $\varphi = \theta = 0^{\circ}$ | - | 10 | 20 | ms |
| | tf | $\varphi = \theta = 0^{\circ}$ | - | 20 | 40 | ms |
| Viewing Angle | Horizontal | φ | - | -45 ~ 45 | - | $^{\circ}$ |
| | Vertical | θ | - | -30 ~ 10 | - | $^{\circ}$ |
| Image Sticking | tis | 2 hrs | - | - | 2 | sec |
| Crosstalk modulation Ratio | CMR | ^{*)} | 0 | - | 5 | % |
| Color Coordinate | Red | X | 0.548 | 0.578 | 0.608 | - |
| | | y | 0.311 | 0.341 | 0.371 | |
| | Green | x | 0.270 | 0.300 | 0.330 | |
| | | y | 0.505 | 0.535 | 0.565 | |
| | Blue | x | 0.110 | 0.140 | 0.170 | |
| | | y | 0.109 | 0.139 | 0.169 | |
| | White | x | 0.271 | 0.301 | 0.331 | |
| | | y | 0.302 | 0.332 | 0.362 | |


[Note]

- These items are measured by BM-5A(TOPCON) or LCD-7000 (Otsuak Electronic) in the dark room .(no ambient light).
- Brightness conditions : IL= 5.0 mA , HIU-742A CCFL (Harison made)
- Definition of these measurement items are as follows:
 (a) Definition of Viewing Angle(θ , φ) (b) Definition of Response Time



- Definition of luminance and CR measured positions :
 (a) Measure White Luminance on the below 5 points and take the average value.
 (b) CR : measures the same 5 points and take the average value. The Definition of Contrast Ratio is as follows:

$$\text{CR} = (\text{White})\text{Luminance of ON} / (\text{Black})\text{Luminance OFF}$$



- Definition of Contrast Ratio Uniformity

$$\Delta CR = [CR(MAX) / CR(MIN) - 1] \times 100$$


- Definition of Luminance Uniformity

$$\Delta L = [L(MAX) / L(MIN) - 1] \times 100$$

- Definition of Cross talk Modulation Ratio

$$CMR = \text{MAX} ((| (Lb1 - La) / Lc |) \times 100 , (| (Lb2 - La) / Lc |) \times 100)$$

Back ground : 32 gray level



9. RELIABILITY TEST CONDITIONS

(1) Temperature and Humidity

| TEST ITEMS | CONDITIONS |
|---|--|
| HIGH TEMPERATURE OPERATION | 50°C, 240h |
| HIGH TEMPERATURE STORAGE | 60°C, 240h and 65°C, 48h |
| LOW TEMPERATURE OPERATION | 0°C, 240h |
| LOW TEMPERATURE STORAGE | -20°C, 240h |
| HIGH TEMPERATURE HIGH HUMIDITY OPERATION | 50°C, 90%RH, 240h |
| HIGH TEMPERATURE HIGH HUMIDITY STORAGE | 60°C, 90%RH(Max), 48h |
| LOW PRESSURE STORAGE | 260 hPa, 24 h |
| THERMAL SHOCK(No operation) | BETWEEN -20°C (1h) AND 60°C (1h), 100 CYCLES |

(2) Shock & Vibration

| ITEMS | CONDITIONS |
|------------------------------|--|
| SHOCK (NON-OPERATION) | <ul style="list-style-type: none"> ● Shock level: 1764 m/s² (180G) ● Waveform: half sinusoidal wave, 2ms ● Number of shocks: one shock input in each direction of three mutually perpendicular axes for a total of six shock inputs. |
| VIBRATION (NON-OPERATION) | <ul style="list-style-type: none"> ● Vibration level: 9.8 m/s² (1.0G) , perpendicular axis(each x,y,z axis: 1hr , total 3 hrs) ● Frequency range: 5 to 500 Hz ● Sweep speed : 9 Hz / min |

(3) Judgment standard

The judgment of the above test should be made as follow:

Pass: Normal display image with no obvious non-uniformity and no line defect.

Partial transformation of the module parts should be ignored.

Fail: No display image, obvious non-uniformity, or line defects.

10. Specification of Optical-Mechanical defects

(1) Inspection condition is as follows :

Viewing distance is approximately 35cm.

Viewing angle is normal to the LCD panel.

Ambient temperature is approximately 25°C

Ambient light is from 300 to 500 lux


(2) Bright Dot is defined as “ Visible through 5% transmission ND filter “ .

| DEFECT TYPE | | LIMIT | |
|---------------|-------------|---|------------|
| VISUAL DEFECT | SCRATCH | $0.01\text{mm} \leq W \leq 0.05\text{mm}$ $L \leq 10\text{mm}$ | $N \leq 4$ |
| | | $0.01\text{mm} \leq W$ $10\text{mm} < L$ | $N = 0$ |
| | | $0.05\text{mm} < W$ | $N = 0$ |
| | DENT | $0.15\text{mm} \leq \varphi \leq 0.4\text{mm}$ | $N \leq 4$ |
| | | $0.4\text{mm} < \varphi$ | $N = 0$ |
| | BLACK SPOT | $0.15\text{mm} \leq \varphi \leq 0.5\text{mm}$ | $N \leq 4$ |
| | | $0.5\text{mm} < \varphi$ | $N = 0$ |
| | LINT | $L \leq 3\text{mm}$ | $N \leq 4$ |
| | | $3\text{mm} < L$ | $N = 0$ |
| NEWTON RINGS | NOT ALLOWED | | |

| | | |
|----------------------|--|--|
| ELECTRICAL DEFECT | BRIGHT DOT | $N \leq 8$ |
| | DARK DOT | $N \leq 8$ |
| | TOTAL DOT | $N \leq 10$ |
| | TWO ADJACENT DOT BRIGHT DOT DARK DOT | ≤ 2 PAIRS ≤ 2 PAIRS |
| | THREE OR MORE ADJACENT DOT | NOT ALLOWED |
| | DISTANCE BETWEEN DEFECTS BRIGHT DOT DARK DOT | $\geq 15\text{mm}$ $\geq 15\text{mm}$ |
| | LINE DEFECT | NOT ALLOWED |

*1) W: width , L:Lenth , N:number

*2) Definition of adjacent dots :



The defects that are not defined above and considered to be problem shall be reviewed and discussed by both parties.

11. HANDLING PRECAUTIONS FOR TFT-LCD MODULE

Please pay attention to the followings in handling- TFT-LCD products;

(A) ASSEMBLY PRECAUTION

- (1) Please use the mounting hole on the module side in installing and do not beading or wrenching LCD in assembling. And please do not drop, bend or twist LCD module in handling.
- (2) Please design display housing in accordance with the following guide lines.
 - (2.1) Housing case must be destined carefully so as not to put stresses on LCD all sides and not to wrench module. The stresses may cause non-uniformity even if there is no non-uniformity statically.
 - (2.2) Keep sufficient clearance between LCD module back surface and housing when the LCD module is mounted. Approximately 1.0 mm of the clearance in the design is recommended taking into account the tolerance of LCD module thickness and mounting structure height on the housing.
 - (2.3) When some parts, such as, FPC cable and ferrite plate, are installed underneath the LCD module, still sufficient clearance is required, such as 0.5mm. This clearance is, especially, to be reconsidered when the additional parts are implemented for EMI countermeasure.
 - (2.4) Design the inverter location and connector position carefully so as not to give stress to lamp cable, or not to interface the LCD module by the lamp cable.
 - (2.5) Keep sufficient clearance between LCD module and the others parts, such as inverter and speaker so as not to interface the LCD module. Approximately

1.0mm of the clearance in the design is recommended.

- (3) Please do not push or scratch LCD panel surface with any-thing hard. And do not soil LCD panel surface by touching with bare hands. (Polarizer film, surface of LCD panel is easy to be flawed.)
- (4) Please do not press any parts on the rear side such as source TCP, gate TCP, control circuit board and FPCs during handling LCD module. If pressing rear part is unavoidable, handle the LCD module with care not to damage them.
- (5) Please wipe out LCD panel surface with absorbent cotton or soft cloth in case of it being soiled.
- (6) Please wipe out drops of adhesives like saliva and water on LCD panel surface immediately. They might damage to cause panel surface variation and color change.
- (7) Please do not take a LCD module to pieces and reconstruct it. Resolving and reconstructing modules may cause them not to work well.
- (8) Please do not touch metal frames with bare hands and soiled gloves. A color change of the metal frames can happen during a long preservation of soiled LCD modules.
- (9) Please pay attention to handling lead wire of backlight so that it is not tugged in connecting wit inverter.

(B) OPERATING PRECAUTIONS

- (1) Please be sure to turn off the power supply before connecting and disconnecting signal input cable.
- (2) Please do not change variable resistance settings in LCD module. They are adjusted to the most suitable value. If they are changed, it might happen LCD does not satisfy the characteristics specification.
- (3) Please consider that LCD backlight takes longer time to become stable of radiation characteristics in low temperature than in room temperature.
- (4) A condensation might happen on the surface and inside of LCD module in case of sudden charge of ambient temperature.
- (5) Please pay attention to displaying the same pattern for very long time. Image might stick on LCD. If then, time going on can make LCD work well.
- (6) Please obey the same caution descriptions as ones that need to pay attention to ordinary electronic parts.

(C) PRECAUTIONS WITH ELECTROSTATICS

- (1) This LCD module use CMOS-IC on circuit board and TFT-LCD panel, and so it is easy to be affected by electrostatics. Please be careful with electrostatics by the way of your body connecting to the ground and so on.
- (2) Please remove protection film very slowly on the surface of LCD module to prevent from electrostatics occurrence.

(D) STORAGE PRECAUTIONS

- (1) When you store LCDs for a long time, it is recommended to keep the temperature between 0°C-40°C without the exposure of sunlight and to keep the humidity less than 90%RH.
- (2) Please do not leave the LCDs in the environment of high humidity and high temperature such as 60°C 90%RH.
- (3) Please do not leave the LCDs in the environment of low temperature; below -20°C.

(E) SAFETY PRECAUTIONS

- (1) When you waste LCDs, it is recommended to crush damaged or unnecessary LCDs into pieces and wash them off with solvents such as acetone and ethanol, which should later be burned.
- (2) If any liquid leaks out of a damaged-glass cell and comes in contact with the hands,

wash off thoroughly with soap and water.

(F) OTHERS

- (1) A strong incident light into LCD panel might cause display characteristics' changing inferior because of polarizer film, color filter, and other materials becoming inferior. Please do not expose LCD module direct sunlight and strong UV rays.
- (2) Please pay attention to a panel side of LCD module not to contact with other materials in preserving it alone.
- (3) For the packaging box, please pay attention to the followings:
 - (3.1) Packaging box and inner case for LCD are designed to protect the LCDs from the damage or scratching during transportation. Please do not open except picking LCDs up from the box.
 - (3.2) Please do not pile them up more than 5 boxes. (They are not designed so.) And please do not turn over.
 - (3.3) Please handle packaging box with care not to give them sudden shock and vibrations. And also please do not throw them up.
 - (3.4) Packing box and inner case for LCDs are made of cardboard. So please pay attention not to get them wet. (Such like keeping them in high humidity or wet place can occur getting them wet.)