



Document Title	HSD100IFW2-A Formal specification	Page No.	1/23
Document No.	DC140-000609	Revision	3.1

TO :

Date : Jul., 20, 2011

# **HannStar Product Specification** **(Formal)**

**Model: HSD100IFW2**  
**-A00**

Note: 1.Please contact HannStar Display Corp. before designing your product based on this module specification.  
2.The information contained herein is presented merely to indicate the characteristics and performance of our products. No responsibility is assumed by HannStar for any intellectual property claims or other problems that may result from application based on the module described herein.

Document Title	HSD100IFW2-A Formal specification	Page No.	2/23
Document No.	DC140-000609	Revision	3.1

## Record of Revisions

Rev.	Date	Sub-Model	Description of change
1.0	Mar., 06, 2009	A00	Formal Product Specification was first released



Document Title	HSD100IFW2-A Formal specification	Page No.	3/23
Document No.	DC140-000609	Revision	3.1

## Contents

1.0	General description .....	p.4
2.0	Absolute maximum ratings.....	p.5
3.0	Optical characteristics.....	p.6
4.0	Block diagram .....	p.10
5.0	Interface pin connection .....	p.12
6.0	Electrical characteristics .....	p.14
7.0	Reliability test items .....	p.18
8.0	Outline dimension .....	p.19
9.0	Lot mark .....	p.20
10.0	Package specification .....	p.21
11.0	General precaution .....	p.22

Document Title	HSD100IFW2-A Formal specification	Page No.	4/23
Document No.	DC140-000609	Revision	3.1

## 1.0 GENERAL DESCRIPTION

### 1.1 Introduction

HannStar Display model HSD100IFW2-A00 is a color active matrix thin film transistor (TFT) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. This model is composed of a TFT LCD panel, a driving circuit and a back light system. This TFT LCD has a 10.1 (17:10) inch diagonally measured active display area with WSVGA (1024 horizontal by 600 vertical pixel) resolution.

### 1.2 Features

- 10.1 (17:10 diagonal) inch configuration
- One channel LVDS interface
- 262K color by 6 bit R.G.B signal input
- RoHS Compliance
- Halogen Free

### 1.3 Applications

- Mobile NB
- Digital Photo frame
- Display terminal for AV application

### 1.4 General information

Item		Specification	Unit
Outline Dimension		235 x 145.8 x 4.8 (Typ.)	mm
Display area		220.42(H) x 129.15(V)	mm
Number of Pixel		1024 RGB (H) x 600(V)	pixels
Pixel pitch		0.2153(H) x 0.2153(V)	mm
Pixel arrangement		RGB Vertical stripe	
Display mode		Normally white	
Surface treatment		Antiglare, Hard-Coating (3H) with EWV film	
Weight		185(typ)	g
Back-light		Single LED (Side-Light type)	
Power Consumption	Logic System	0.7(Max.)	W
	B/L System	2.0(Max.)	W

### 1.5 Mechanical Information

Item		Min.	Typ.	Max.	Unit
Module Size	Horizontal (H)	234.7	235	235.3	mm
	Vertical (V)	145.5	145.8	146.1	mm
	Depth (D)	—	4.8	5.1	mm
Weight		—	185	195	g

Document Title	HSD100IFW2-A Formal specification	Page No.	5/23
Document No.	DC140-000609	Revision	3.1

## 2.0 ABSOLUTE MAXIMUM RATINGS

### 2.1 Electrical Absolute Rating

#### 2.1.1 TFT LCD Module

Item	Symbol	Min.	Max.	Unit	Note
LED Power Supply voltage	$V_{LED}$	-0.3	6.0	V	GND=0
Logic Supply voltage	$V_{DD}$	-0.3	6.0	V	

### 2.2 Environment Absolute Rating

Item	Symbol	Min.	Max.	Unit	Note
Operating Temperature	$T_{opa}$	0	50	°C	
Storage Temperature	$T_{stg}$	-20	60	°C	

Document Title	HSD100IFW2-A Formal specification	Page No.	6/23
Document No.	DC140-000609	Revision	3.1

### 3.0 OPTICAL CHARACTERISTICS

#### 3.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast		CR	$\Theta=0$ Normal viewing angle	400	500	—		(1)(2)
Response time		Tr		—	3	6	msec	(1)(3)
		Tf			9	18		
White luminance (5 points)		Y <sub>L</sub>		160	200	—	cd/m <sup>2</sup>	(1)(4)(5)
Color chromaticity (CIE1931)	Red	R <sub>x</sub>		0.553	0.603	0.653		
		R <sub>y</sub>		0.302	0.352	0.302		
	Green	G <sub>x</sub>		0.260	0.310	0.360		
		G <sub>y</sub>		0.496	0.546	0.596		
	Blue	B <sub>x</sub>		0.099	0.149	0.199		
		B <sub>y</sub>		0.059	0.109	0.159		
	White	W <sub>x</sub>		0.260	0.310	0.360		
		W <sub>y</sub>		0.280	0.330	0.380		
Viewing angle	Hor.	Θ <sub>L</sub>	CR>10	60	70	—		(1)(4)
		Θ <sub>R</sub>		60	70	—		
	Ver.	Θ <sub>U</sub>		40	50	—		
		Θ <sub>D</sub>		50	60	—		
Brightness uniformity		B <sub>UNI</sub>	Θ=0 (5points)	—	—	1.25		(6)
Brightness uniformity		B <sub>UNI</sub>	Θ=0 (13points)	—	—	1.5		(6)

#### 3.2 Measuring Condition


- Measuring surrounding : dark room
- Ambient temperature : 25±2°C
- 15min. warm-up time.

Document Title	HSD100IFW2-A Formal specification	Page No.	7/23
Document No.	DC140-000609	Revision	3.1

### 3.3 Measuring Equipment

- FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.
- Measuring spot size : 20 ~ 21 mm

**Note (1)** Definition of Viewing Angle:




**Note (2)** Definition of Contrast Ratio (CR) :  
measured at the center point of panel


$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

Document Title	HSD100IFW2-A Formal specification	Page No.	8/23
Document No.	DC140-000609	Revision	3.1

**Note (3)** Definition of Response Time : Sum of  $T_R$  and  $T_F$



**Note (4)** Definition of optical measurement setup






Document Title	HSD100IFW2-A Formal specification	Page No.	9/23
Document No.	DC140-000609	Revision	3.1

**Note (5)** Definition of Average Luminance Uniformity of White (5 Point)

$$\text{Average Luminance Uniformity} = \frac{Y_1 + Y_2 + Y_3 + Y_4 + Y_5}{5}$$



**Note (6)** Definition of brightness uniformity


$$\text{Luminance uniformity} = \frac{(\text{Max Luminance of 5 points})}{(\text{Min Luminance of 5 points})}$$

$$\text{Luminance uniformity} = \frac{(\text{Max Luminance of 13 points})}{(\text{Min Luminance of 13 points})}$$


Document Title	HSD100IFW2-A Formal specification	Page No.	10/23
Document No.	DC140-000609	Revision	3.1

## 4.0 BLOCK DIAGRAM

### 4.1 TFT LCD Module:



### 4.2 Pixel Format



Document Title	HSD100IFW2-A Formal specification	Page No.	11/23
Document No.	DC140-000609	Revision	3.1

### 4.3 Relationship Between Displayed Color and Input

	Display	MSB						LSB						MSB						LSB						Gray scale level
		R5	R4	R3	R2	R1	R0	G5	G4	G3	G2	G1	G0	B5	B4	B3	B2	B1	B0							
Basic color	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	-						
	Blue	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	-						
	Green	L	L	L	L	L	L	H	H	H	H	H	H	L	L	L	L	L	L	-						
	Light Blue	L	L	L	L	L	L	H	H	H	H	H	H	H	H	H	H	H	H	-						
	Red	H	H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	-						
	Purple	H	H	H	H	H	H	L	L	L	L	L	L	L	H	H	H	H	H	-						
	Yellow	H	H	H	H	H	H	H	H	H	H	H	H	L	L	L	L	L	L	-						
	White	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	-						
Gray scale of Red	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0						
	Dark ↑ ↓ Light	L	L	L	L	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L1						
		L	L	L	L	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L2						
		⋮						⋮						⋮						L3...L60						
		H	H	H	H	L	H	L	L	L	L	L	L	L	L	L	L	L	L	L61						
		H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	L	L62						
	Red	H	H	H	H	H	H	L	L	L	L	L	L	L	L	L	L	L	L	Red L63						
Gray scale of Green	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0						
	Dark ↑ ↓ Light	L	L	L	L	L	L	L	L	L	L	L	H	L	L	L	L	L	L	L1						
		L	L	L	L	L	L	L	L	L	L	H	L	L	L	L	L	L	L	L2						
		⋮						⋮						⋮						L3...L60						
		L	L	L	L	L	L	H	H	H	H	L	H	L	L	L	L	L	L	L61						
		L	L	L	L	L	L	H	H	H	H	H	L	L	L	L	L	L	L	L62						
	Green	L	L	L	L	L	L	H	H	H	H	H	H	L	L	L	L	L	L	Green L63						
Gray scale of Blue	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0						
	Dark ↑ ↓ Light	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	H	L1						
		L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	H	L	L2						
		⋮						⋮						⋮						L3...L60						
		L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	L	H	L61						
		L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	L	L62						
	Blue	L	L	L	L	L	L	L	L	L	L	L	L	H	H	H	H	H	H	Blue L63						
Gray scale of White & Black	Black	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L	L0						
	Dark ↑ ↓ Light	L	L	L	L	L	H	L	L	L	L	L	H	L	L	L	L	L	H	L1						
		L	L	L	L	L	H	L	L	L	L	H	L	L	L	L	L	H	L	L2						
		⋮						⋮						⋮						L3...L60						
		H	H	H	H	L	H	H	H	H	L	H	H	H	H	H	L	H	L61							
		H	H	H	H	H	L	H	H	H	H	H	L	H	H	H	H	H	L	L62						
	White	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	White L63						

Document Title	HSD100IFW2-A Formal specification	Page No.	12/23
Document No.	DC140-000609	Revision	3.1

## 5.0 INTERFACE PIN CONNECTION

### 5.1 TFT LCD Module :

Connector CN1 is used for electronics interface. The recommended model is FI-XB30SRL-HF10 manufactured by JAE or other equivalent.

Pin No.	Signal	Description
1	GND	Ground
2	VDD	Power Supply, 3.3V (typical)
3	VDD	Power Supply, 3.3V (typical)
4	V_EDID	EDID 3.3V power
5	ADJ	Adjust for LED backlight brightness
6	CLK_EDID	EDID Clock
7	DATA_EDID	EDID Data
8	RXIN0-	- LVDS differential data input (R0-R5, G0)
9	RXIN0+	+ LVDS differential data input (R0-R5, G0)
10	GND	Ground
11	RXIN1-	- LVDS differential data input (G1-G5, B0-B1)
12	RXIN1+	+ LVDS differential data input (G1-G5, B0-B1)
13	GND	Ground
14	RXIN2-	- LVDS differential data input (B2-B5, HS, VS, DE)
15	RXIN2+	+ LVDS differential data input (B2-B5, HS, VS, DE)
16	GND	Ground
17	RXCLKIN-	- LVDS differential clock input
18	RXCLKIN+	+ LVDS differential clock input
19	GND	Ground
20	NC	NC
21	NC	NC
22	GND	Ground
23	GND	Ground
24	VLED	LED Power Supply, 5V
25	VLED	LED Power Supply, 5V
26	VLED	LED Power Supply, 5V
27	NC	NC
28	NC	NC
29	NC	NC
30	NC	NC

**Note :** The brightness of LCD panel could be changed by adjusting ADJ

Document Title	HSD100IFW2-A Formal specification	Page No.	13/23
Document No.	DC140-000609	Revision	3.1


**[Note]**

**(1) ADJ can adjust brightness to control Pin. Pulse duty the bigger the brighter.**



**(2) ADJ Signal=0~3.3V , Operation Conditions :**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
ADJ Logic-High Level	$V_{ADJH}$		1.8	3.3	3.6	V
ADJ Logic-Low Level	$V_{ADJL}$		0	0	0.4	V
Dimming Frequency	$F_{ADJ}$		18	20	22	kHz
Dimming Duty Cycle	D		20	--	100	%



$$D = t_{on} / T_s \times 100\%$$

$$F_{ADJ} = 1 / T_s$$

Document Title	HSD100IFW2-A Formal specification	Page No.	14/23
Document No.	DC140-000609	Revision	3.1

## 6.0 ELECTRICAL CHARACTERISTICS


### 6.1 TFT LCD Module

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Supply Voltage	V <sub>DD</sub>	3.0	3.3	3.6	V	Note (1)
	V <sub>LED</sub>	4.7	5.0	5.3	V	
Current of power supply	I <sub>DD</sub>	-	0.192	-	A	V <sub>DD</sub> = 3.3V 、L0 pattern

**Note** : (1) V<sub>DD</sub>-dip condition :

When V<sub>DD</sub> operating within  $2.7V \leq V_{DD} < 3.0V$  ,  $t_d \leq 10ms$  , the display may momentarily become abnormal .

V<sub>DD</sub> < 2.7V, V<sub>DD</sub> dip condition should also follow the Power On/Off conditions for supply voltage.




Document Title	HSD100IFW2-A Formal specification	Page No.	15/23
Document No.	DC140-000609	Revision	3.1

## 6.2 Switching Characteristics for LVDS Receiver

Item	Symbol	Min.	Typ.	Max.	Unit	Conditions
Differential Input High Threshold	$V_{th}$	—	—	100	mV	$V_{CM}=1.2V$
Differential Input Low Threshold	$V_{tl}$	-100	—	—	mV	
Input Current	$I_{IN}$	-10	—	+10	$\mu A$	
Differential input Voltage	$ V_{ID} $	0.1	—	0.6	V	
Common Mode Voltage Offset	$V_{CM}$	$( V_{ID} /2)$	1.25	$1.8-0.4-( V_{ID} /2)$	V	

## 6.3 Bit Mapping & Interface Definition



LVDS Receiver Input Timing Definition  
for 6bits LVDS input


Document Title	HSD100IFW2-A Formal specification	Page No.	16/23
Document No.	DC140-000609	Revision	3.1

#### 6.4 Interface Timing (DE mode)


Item	Symbol	Min.	Typ.	Max.	Unit
Frame Rate	--	55	60	65	Hz
Frame Period	t1	612	625	638	line
Vertical Display Time	t2	600	600	600	line
Vertical Blanking Time	t3	12	25	38	line
1 Line Scanning Time	t4	1160	1200	1240	clock
Horizontal Display Time	t5	1024	1024	1024	clock
Horizontal Blanking Time	t6	136	176	216	clock
Clock Rate	t7	39	45	51.42	MHz

#### Timing Diagram of Interface Signal (DE mode)

(1) Vertical




(2) Horizontal





Document Title	HSD100IFW2-A Formal specification	Page No.	17/23
Document No.	DC140-000609	Revision	3.1

## 6.5 Power On / Off Sequence



Item	Min.	Typ.	Max.	Unit	Remark
TP1	0.5	--	10	msec	
TP2	0	--	50	msec	
TP3	0	--	50	msec	
TP4	500	--	--	msec	
TP5	200	--	--	msec	
TP6	200	--	--	msec	


- Note: (1) The supply voltage of the external system for the module input should be the same as the definition of  $V_{DD}$ .
- (2) Apply the lamp voltage within the LCD operation range. When the back-light turns on before the LCD operation or the LCD turns off before the back-light turns off, the display may momentarily become white.
- (3) In case of  $V_{DD}$  = off level, please keep the level of input signal on the low or keep a high impedance.
- (4) TP4 should be measured after the module has been fully discharged between power off and on period.
- (5) Interface signal shall not be kept at high impedance when the power is on.

Document Title	HSD100IFW2-A Formal specification	Page No.	18/23
Document No.	DC140-000609	Revision	3.1

## 7.0 Reliability test items

No.	Item	Conditions	Remark
1	High Temperature Storage	Ta=+60°C, 240hrs	
2	Low Temperature Storage	Ta=-20°C, 240hrs	
3	High Temperature Operation	Ta=+50°C, 300hrs	
4	Low Temperature Operation	Ta=0°C, 300hrs	
5	Thermal Cycling Test (non operation)	-20°C(30min)→+60°C(30min),100 cycles	
6	Vibration	Sine Wave 1.5G, 5~500Hz, XYZ 30min/each direction	
7	Shock	Half-Sine, 200G, 2ms, ±XYZ, 1time	

### Storage / Operating temperature




**Note** .Max wet bulb temp.=39°C

Document Title	HSD100IFW2-A Formal specification	Page No.	19/23
Document No.	DC140-000609	Revision	3.1



## 8.0 OUTLINE DIMENSION

### 8.1 Front View Outline Dimension

Unit : mm



### 8.2 Front View Outline Dimension



BM Assembly Tolerance

 $|A-A'| \leq 1.0 \text{ (mm)}$ 
 $|B-B'| \leq 1.0 \text{ (mm)}$

Document Title	HSD100IFW2-A Formal specification	Page No.	20/23
Document No.	DC140-000609	Revision	3.1

## 9.0 LOT MARK

### 9.1 Lot Mark

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----

Code 1,2,3,4,5,6: HannStar internal flow control code.

Code 7: production location.

Code 8: production year.

Code 9: production month.

Code 10,11,12,13,14,15: serial number.

#### Note (1) Production Year


Year	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015
Mark	6	7	8	9	0	1	2	3	4	5

#### Note (2) Production Month

Month	Jan.	Feb.	Mar.	Apr.	May.	Jun.	Jul.	Aug.	Sep.	Oct.	Nov.	Dec.
Mark	1	2	3	4	5	6	7	8	9	A	B	C

### 9.2 Location of Lot Mark

- (1) Location : The label is attached to the backside of the LCD module. See Product back view. ( Section 8.0 : OUTLINE DIMENSION )
- (2) Detail of the Mark : As attached below
- (3) This is subject to change without prior notice.




Document Title	HSD100IFW2-A Formal specification	Page No.	21/23
Document No.	DC140-000609	Revision	3.1

## 10.0 PACKAGE SPECIFICATION

### 10.1 Packing form

LCM Model	LCM Qty. in the box	Inner Box Size (mm)	Notice
HSD100IFW2-A	50 pcs/box	460 x 316 x 321 <sup>H</sup>	

### 10.2 Packing assembly drawings



HSD100IFW2-A00	Material	Notice
Box	Corrugated Paper Board	(AB Flute)
Partition/Pad	Corrugated Paper Board	(B Flute)
Corner Pad	Corrugated Paper Board	(AB Flute)
ESD bag	PE	--

Document Title	HSD100IFW2-A Formal specification	Page No.	22/23
Document No.	DC140-000609	Revision	3.1

## 11.0 GENERAL PRECAUTION

### 11.1 Use Restriction

This product is not authorized for use in life supporting systems, aircraft navigation control systems, military systems and any other application where performance failure could be life-threatening or otherwise catastrophic.

### 11.2 Disassembling or Modification

Do not disassemble or modify the module. It may damage sensitive parts inside LCD module, and may cause scratches or dust on the display. HannStar does not warrant the module, if customers disassemble or modify the module.

### 11.3 Breakage of LCD Panel

11.3.1. If LCD panel is broken and liquid crystal spills out, do not ingest or inhale liquid crystal, and do not contact liquid crystal with skin.

11.3.2. If liquid crystal contacts mouth or eyes, rinse out with water immediately.

11.3.3. If liquid crystal contacts skin or cloths, wash it off immediately with alcohol and rinse thoroughly with water.

11.3.4. Handle carefully with chips of glass that may cause injury, when the glass is broken.

### 11.4 Electric Shock

11.4.1. Disconnect power supply before handling LCD module.

11.4.2. Do not pull or fold the LED cable.

11.4.3. Do not touch the parts inside LCD modules and the fluorescent LED's connector or cables in order to prevent electric shock.

### 11.5 Absolute Maximum Ratings and Power Protection Circuit

11.5.1. Do not exceed the absolute maximum rating values, such as the supply voltage variation, input voltage variation, variation in parts' parameters, environmental temperature, etc., otherwise LCD module may be damaged.

11.5.2. Please do not leave LCD module in the environment of high humidity and high temperature for a long time.

11.5.3. It's recommended to employ protection circuit for power supply.

### 11.6 Operation

11.6.1 Do not touch, push or rub the polarizer with anything harder than HB pencil lead.

11.6.2 Use fingerstalls of soft gloves in order to keep clean display quality, when persons handle the LCD module for incoming inspection or assembly.

11.6.3 When the surface is dusty, please wipe gently with absorbent cotton or other soft material.

Document Title	HSD100IFW2-A Formal specification	Page No.	23/23
Document No.	DC140-000609	Revision	3.1

11.6.4 Wipe off saliva or water drops as soon as possible. If saliva or water drops contact with polarizer for a long time, they may causes deformation or color fading.

11.6.5 When cleaning the adhesives, please use absorbent cotton wetted with a little petroleum benzine or other adequate solvent.

#### 11.7 Mechanism

Please mount LCD module by using mounting holes arranged in four corners tightly.

#### 11.8 Static Electricity

11.8.1 Protection film must remove very slowly from the surface of LCD module to prevent from electrostatic occurrence.

11.8.2 Because LCD module use CMOS-IC on circuit board and TFT-LCD panel, it is very weak to electrostatic discharge. Please be careful with electrostatic discharge. Persons who handle the module should be grounded through adequate methods.

#### 11.9 Strong Light Exposure

The module shall not be exposed under strong light such as direct sunlight. Otherwise, display characteristics may be changed.

#### 11.10 Disposal

When disposing LCD module, obey the local environmental regulations.