

Doc. Number :

- ☐ Tentative Specification
☐ Preliminary Specification
☒ Approval Specification

MODEL NO.: M156BGE
 SUFFIX: L20

Customer: Common

APPROVED BY

SIGNATURE

Name / Title _____

Note

Product Version C1

 Please return 1 copy for your confirmation with your signature and comments.

Approved By	Checked By	Prepared By
吳柏勳	梁永祥	陳有成

CONTENTS

1. GENERAL DESCRIPTION	5
1.1 OVERVIEW.....	5
1.2 GENERAL SPECIFICATIONS	5
2. MECHANICAL SPECIFICATIONS.....	5
3. ABSOLUTE MAXIMUM RATINGS	6
3.1 ABSOLUTE RATINGS OF ENVIRONMENT	6
3.2 ELECTRICAL ABSOLUTE RATINGS	6
3.2.1 TFT LCD MODULE	6
3.2.2 BACKLIGHT UNIT.....	7
4. ELECTRICAL SPECIFICATIONS	7
4.1 FUNCTION BLOCK DIAGRAM.....	7
4.2. INTERFACE CONNECTIONS	8
4.3 ELECTRICAL CHARACTERISTICS	9
4.3.1 LCD ELETRONICS SPECIFICATION	9
4.3.2 Vcc Power Dip Condition.....	12
4.3.3 BACKLIGHT UNIT	12
4.3.4 LIGHTBAR Connector Pin Assignment	13
4.4 LVDS INPUT SIGNAL SPECIFICATIONS.....	14
4.4.1 LVDS DATA MAPPING TABLE	14
4.4.2 COLOR DATA INPUT ASSIGNMENT	15
4.5 DISPLAY TIMING SPECIFICATIONS	16
4.6 POWER ON/OFF SEQUENCE.....	18
5. OPTICAL CHARACTERISTICS	19
5.1 TEST CONDITIONS	19
5.2 OPTICAL SPECIFICATIONS	19
6. RELIABILITY TEST ITEM.....	22
7. PACKING	23
7.1 PACKING SPECIFICATIONS	23
7.2 PACKING METHOD.....	23
7.3 PALLET	24
8. CMI MODULE LABEL	25
9. PRECAUTIONS	26
9.1 ASSEMBLY AND HANDLING PRECAUTIONS.....	26
9.2 STORAGE PRECAUTIONS.....	26
9.3 OPERATION PRECAUTIONS	26

9.4 SAFETY PRECAUTIONS	27
9.5 SAFETY STANDARDS	27
9.6 OTHER	27
Appendix. OUTLINE DRAWING	27

REVISION HISTORY

Version	Date	Page	Description
2.0	Sep.8th, 2011	All	Spec Ver.2.0 was first issued.

1. GENERAL DESCRIPTION

1.1 OVERVIEW

M156BGE-L20 is a 15.6" TFT Liquid Crystal Display module with WLED Backlight unit and 30 pins 1ch-LVDS interface. This module supports 1366 x 768 WXGA mode and can display up to 16.7M colors. The converter module for Backlight is not built in.

1.2 GENERAL SPECIFICATIONS

Item	Specification	Unit	Note
Screen Size	15.6" real diagonal		
Driver Element	a-si TFT active matrix	-	-
Pixel Number	1366 x R.G.B. x 768	pixel	-
Pixel Pitch	0.252 (H) x 0.252 (V)	mm	-
Pixel Arrangement	RGB vertical stripe	-	-
Display Colors	16.7M	color	-
Transmissive Mode	Normally white	-	-
Surface Treatment	AG type, 3H hard coating, Haze 25	-	-
Luminance, White	250	Cd/m2	
Color Gamut	65 % of NTSC(Typ.)	-	-
TCO	TCO 5.0 compliance		
Power Consumption	9.304W		(1)

Note (1) The specified power consumption : Total= cell (reference 4.3.1)+BL (reference 4.3.3)

2. MECHANICAL SPECIFICATIONS

Item		Min.	Typ.	Max.	Unit	Note
Module Size	Horizontal (H)	363.3	363.8	364.3	mm	(1)
	Vertical (V)	215.42	215.92	216.42	mm	
	Thickness (T)	9.95	10.45	10.95	mm	
Bezel Area	Horizontal	347.23	347.53	347.83	mm	
	Vertical	196.53	196.83	197.13	mm	
Active Area	Horizontal	-	344.232	-	mm	
	Vertical	-	193.536	-	mm	
Weight		-	1030	1100	g	

Note (1) Please refer to the attached drawings for more information of front and back outline dimensions.

3. ABSOLUTE MAXIMUM RATINGS

3.1 ABSOLUTE RATINGS OF ENVIRONMENT

Item	Symbol	Value		Unit	Note
		Min.	Max.		
Storage Temperature	TST	-20	60	°C	(1)
Operating Ambient Temperature	TOP	0	50	°C	(1), (2)


Note (1)

(a) 90 %RH Max. ($T_a \leq 40^\circ\text{C}$).

(b) Wet-bulb temperature should be 39°C Max. ($T_a > 40^\circ\text{C}$).

(c) No condensation.

Note (2) The temperature of panel surface should be 0°C min. and 60°C max.



3.2 ELECTRICAL ABSOLUTE RATINGS

3.2.1 TFT LCD MODULE

Item	Symbol	Value		Unit	Note
		Min.	Max.		
Power Supply Voltage	VCCS	-0.3	6.0	V	(1)
Logic Input Voltage	VIN	-0.3	3.6	V	

3.2.2 BACKLIGHT UNIT


Item	Symbol	Value			Unit	Note
		Min.	Typ	Max.		
LED Forward Current Per Input Pin	IF	0	65	69	mA	(1), (2) Duty=100%
LED Pulse Forward Current Per Input Pin	IP	---	---	150	mA	(1), (2) Pulse Width ≤ 10msec. and Duty ≤ 30%

Note (1) Permanent damage to the device may occur if maximum values are exceeded. Function operation should be restricted to the conditions described under Normal Operating Conditions.

Note (2) Specified values are for input pin of LED light bar at $T_a=25\pm2\text{ }^{\circ}\text{C}$ (Refer to 4.3.3 and 4.3.4 for further information).

4. ELECTRICAL SPECIFICATIONS

4.1 FUNCTION BLOCK DIAGRAM



4.2. INTERFACE CONNECTIONS

PIN ASSIGNMENT

Pin	Name	Description
1	NC	Not connection, this pin should be open.
2	NC	Not connection, this pin should be open.
3	NC	Not connection, this pin should be open.
4	GND	Ground
5	RX0-	Negative LVDS differential data input. Channel 0
6	RX0+	Positive LVDS differential data input. Channel 0
7	GND	Ground
8	RX1-	Negative LVDS differential data input. Channel 1
9	RX1+	Positive LVDS differential data input. Channel 1
10	GND	Ground
11	RX2-	Negative LVDS differential data input. Channel 2
12	RX2+	Positive LVDS differential data input. Channel 2
13	GND	Ground
14	RXCLK-	Negative LVDS differential clock input.
15	RXCLK+	Positive LVDS differential clock input.
16	GND	Ground
17	RX3-	Negative LVDS differential data input. Channel 3
18	RX3+	Positive LVDS differential data input. Channel 3
19	GND	Ground
20	NC	Not connection, this pin should be open.
21	NC	Not connection, this pin should be open.
22	AGMODE	AGMODE should be tied to ground or open.
23	GND	Ground
24	GND	Ground
25	GND	Ground
26	Vcc	+5.0V power supply
27	Vcc	+5.0V power supply
28	Vcc	+5.0V power supply
29	Vcc	+5.0V power supply
30	Vcc	+5.0V power supply

Note (1) Connector Part No.:

GS23301-0321R-7H(FOXCONN) or WF13-422-3033(Fullconn) or 187098-30091(P-TWO) or equivalent.


Note (2) User's connector Part No:

Mating Wire Cable Connector Part No.: FI-X30H(JAE) or FI-X30HL(JAE)

Mating FFC Cable Connector Part No.: 217007-013001 (P-TWO) or JF05X030-1 (JAE).

Note (3) The first pixel is odd.

Note (4) Input signal of even and odd clock should be the same timing.




4.3 ELECTRICAL CHARACTERISTICS

4.3.1 LCD ELETRONICS SPECIFICATION


Parameter		Symbol	Value			Unit	Note
			Min.	Typ.	Max.		
Power Supply Voltage		V _{CC}	4.5	5.0	5.5	V	-
Ripple Voltage		V _{RP}	-	-	150	mV	-
Rush Current		I _{RUSH}	-	-	3	A	(2)
Power Supply Current	White		-	0.22	0.27	A	(3)a
	Black		-	0.36	0.44	A	(3)b
	Vertical Stripe		-	0.41	0.49	A	(3)c
Power Consumption		PLCD	-	2.05	2.45	Watt	(4)
LVDS differential input voltage		V _{id}	200	-	600	mV	
LVDS common input voltage		V _{ic}	-	1.2	-	V	
Logic High Input Voltage		V _{IH}	2.7		3.3	V	
Logic Low Input Voltage		V _{IL}	0		0.7	V	

Note (1) The ambient temperature is $T_a = 25 \pm 2 \text{ }^{\circ}\text{C}$.


Note (2) Measurement Conditions:



Vcc rising time is 470μs




Note (3) The specified power supply current is under the conditions at $V_{cc} = 5.0\text{ V}$, $T_a = 25 \pm 2\text{ }^{\circ}\text{C}$, $F_r = 75\text{ Hz}$, whereas a power dissipation check pattern below is displayed.




Note (4) The power consumption is specified at the pattern with the maximum current.

Note (5) VID waveform condition



4.3.2 Vcc Power Dip Condition




4.3.3 BACKLIGHT UNIT

Parameter	Symbol	Value			Unit	Note
		Min.	Typ.	Max.		
LED Light Bar Input Voltage Per Input Pin	VPIN	---	27.9	30.6	V	(1), Duty=100%, IPIN=65mA
LED Light Bar Current Per Input Pin	IPIN	---	65	69	mA	(1), (2) Duty=100%
LED Life Time	LLED	40000	---	---	Hrs	(3)
Power Consumption	PBL	---	7.254	8.45	W	(1) Duty=100%, IPIN=65mA

Note (1) LED light bar input voltage and current are measured by utilizing a true RMS multimeter as shown below:


Note (2) $PBL(Typ) = IPIN(Typ) \times VPIN(Typ) \times (4)$ $PBL(Max) = IPIN(Max) \times VPIN(Max) \times (4)$ input pins ,

Note (3) The lifetime of LED is defined as the time when LED packages continue to operate under the conditions at $T_a = 25 \pm 2^\circ C$ and $I = (65)mA$ (per chip) until the brightness becomes $\leq 50\%$ of its original value.




4.3.4 LIGHTBAR Connector Pin Assignment

Connector: WM13-406-063N(FCN) or Compatible



CN1

Pin number	Description
1	Cathode of LED string
2	Cathode of LED string
3	VLED
4	VLED
5	Cathode of LED string
6	Cathode of LED string



4.4 LVDS INPUT SIGNAL SPECIFICATIONS

4.4.1 LVDS DATA MAPPING TABLE

LVDS Channel 0	LVDS output	D7	D6	D4	D3	D2	D1	D0
	Data order	G0	R5	R4	R3	R2	R1	R0
LVDS Channel 1	LVDS output	D18	D15	D14	D13	D12	D9	D8
	Data order	B1	B0	G5	G4	G3	G2	G1
LVDS Channel 2	LVDS output	D26	D25	D24	D22	D21	D20	D19
	Data order	DE	NA	NA	B5	B4	B3	B2
LVDS Channel 3	LVDS output	D23	D17	D16	D11	D10	D5	D27
	Data order	NA	B7	B6	G7	G6	R7	R6

4.4.2 COLOR DATA INPUT ASSIGNMENT

The brightness of each primary color (red, green and blue) is based on the 8-bit gray scale data input for the color. The higher the binary input, the brighter the color. The table below provides the assignment of color versus data input.

Color		Data Signal																							
		Red								Green								Blue							
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale Of Red	Red(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(1)	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(2)	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Red(253)	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(254)	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red(255)	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale Of Green	Green(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Green(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	Green(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Green(253)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0
	Green(254)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Green(255)	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0
Gray Scale Of Blue	Blue(0) / Dark	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue(1)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Blue(2)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:
	Blue(253)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1
	Blue(254)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue(255)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1

Note (1) 0: Low Level Voltage, 1: High Level Voltage


4.5 DISPLAY TIMING SPECIFICATIONS

The input signal timing specifications are shown as the following table and timing diagram.


Signal	Item	Symbol	Min.	Typ.	Max.	Unit	Note
LVDS Clock	Frequency	F _c	63	76	96	MHz	-
	Period	T _c		13		ns	
	Input cycle to cycle jitter	T _{rcl}	TC -200		TC +200	ns	(1)
	Input Clock to data skew	TLVCCS			400	ps	(2)
	Spread spectrum modulation range	F _{clkin_mod}	FC*97%		FC*103%	MHz	(3)
	Spread spectrum modulation frequency	F _{SSM}			200	KHz	
Vertical Display Term	Frame Rate	Fr	50	60	76	Hz	T _v =T _{vd} +T _{vb}
	Total	T _v	800	806	815	Th	-
	Active Display	T _{vd}	768	768	768	Th	-
	Blank	T _{vb}	32	38	47	Th	-
Horizontal Display Term	Total	T _h	1500	1560	1570	T _c	T _h =T _{hd} +T _{hb}
	Active Display	T _{hd}	1366	1366	1366	T _c	-
	Blank	T _{hb}	134	194	204	T _c	-

Note: Because this module is operated by DE only mode, Hsync and Vsync input signals are ignored.


INPUT SIGNAL TIMING DIAGRAM




Note (1) The input clock cycle-to-cycle jitter is defined as below figures. $Trcl = |T_1 - T_1|$



Note (2) Input Clock to data skew is defined as below figures.




Note (3) The SSCG (Spread spectrum clock generator) is defined as below figures.



4.6 POWER ON/OFF SEQUENCE

The power sequence specifications are shown as the following table and diagram.



Timing Specifications:

Parameters	Values			Units
	Min	Typ.	Max	
T1	0.5		10	ms
T2	0	30	50	ms
T3	200	250		ms
T4	100	250		ms
T5	0	20	50	ms
T6	0.1		50	ms
T7	1000			ms

Note (1) The supply voltage of the external system for the module input should be the same as the definition of Vcc.

Note (2) When the backlight turns on before the LCD operation of the LCD turns off, the display may momentarily become abnormal screen.

Note (3) In case of VCC = off level, please keep the level of input signals on the low or keep a high impedance.

Note (4) T4 should be measured after the module has been fully discharged between power off and on period.

Note (5) Interface signal shall not be kept at high impedance when the power is on.

Note (6) CMI won't take any responsibility for the products which are damaged by the customers not following the Power Sequence.

Note (7) There might be slight electronic noise when LCD is turned off (even backlight unit is also off). To avoid this symptom, we suggest "Vcc falling timing" to follow "t6 spec".

5. OPTICAL CHARACTERISTICS

5.1 TEST CONDITIONS


Item	Symbol	Value	Unit
Ambient Temperature	Ta	25±2	°C
Ambient Humidity	Ha	50±10	%RH
Supply Voltage	VCC	5	V
Input Signal	According to typical value in "3. ELECTRICAL CHARACTERISTICS"		
LED Light Bar Input Current Per Input Pin	IPIN	65 ±1.95	mADC
PWM Duty Ratio	D	100	%
LED Light Bar Test Converter	CMI 35-D065452		

5.2 OPTICAL SPECIFICATIONS

The relative measurement methods of optical characteristics are shown in 5.2. The following items should be measured under the test conditions described in 5.1 and stable environment shown in Note (5).

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Color Chromaticity (CIE 1931)	Red	R _x	$\theta_x=0^\circ, \theta_Y=0^\circ$ CS-2000 R=G=B=255 Gray scale	Typ – 0.03	0.629	Typ + 0.03	-	(1), (5)
		R _y			0.341			
	Green	G _x			0.320			
		G _y			0.601			
	Blue	B _x			0.157			
		B _y			0.072			
	White	W _x			0.313			
		W _y			0.329			
	Center Luminance of White (Center of Screen)				L _C			
Contrast Ratio		CR		350	500	-	-	(2), (5)
Response Time		T _R	$\theta_x=0^\circ, \theta_Y=0^\circ$	-	2	4	ms	(3)
		T _F		-	6	12		
White Variation		W	$\theta_x=0^\circ, \theta_Y=0^\circ$	75	-	-	%	(5), (6)
Viewing Angle	Horizontal	$\theta_{x-} + \theta_{x+}$	CR ≥ 5	90	100	-	Deg.	(1), (5)
	Vertical	$\theta_{y-} + \theta_{y+}$		70	80	-		
Viewing Angle	Horizontal	$\theta_{x-} + \theta_{x+}$	CR ≥ 10	80	90	---	Deg.	(1), (5)
	Vertical	$\theta_{y-} + \theta_{y+}$		55	65	---		

Note (1) Definition of Viewing Angle (θ_x, θ_y):



Note (2) Definition of Contrast Ratio (CR):

The contrast ratio can be calculated by the following expression.

$$\text{Contrast Ratio (CR)} = L_{255} / L_0$$


L255: Luminance of gray level 255

L 0: Luminance of gray level 0

$$\text{CR} = \text{CR} (5)$$

CR (X) is corresponding to the Contrast Ratio of the point X at Figure in Note (6).

Note (3) Definition of Response Time (T_R, T_F):



Note (4) Definition of Luminance of White (L_c):


Measure the luminance of gray level 255 at center point

$$L_c = L(5)$$

$L(x)$ is corresponding to the luminance of the point X at Figure in Note (6).

Note (5) Measurement Setup:


The LCD module should be stabilized at given temperature for 40 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 40 minutes in a windless room.



Note (6) Definition of White Variation (δW):

Measure the luminance of gray level 255 at 9 points

$$\delta W = (\text{Minimum } [L(1) \sim L(9)] / \text{Maximum } [L(1) \sim L(9)]) * 100\%$$



6. RELIABILITY TEST ITEM


Items	Required Condition	Note
Temperature Humidity Bias (THB)	Ta= 50°C , 80%RH, 240hours	
High Temperature Operation (HTO)	Ta= 50°C , 50%RH , 240hours	
Low Temperature Operation (LTO)	Ta= 0°C , 240hours	
High Temperature Storage (HTS)	Ta= 60°C , 240hours	
Low Temperature Storage (LTS)	Ta= -20°C , 240hours	
Vibration Test (Non-operation)	Acceleration: 1.5 Grms Wave: Half-sine Frequency: 10 - 300 Hz Sweep: 30 Minutes each Axis (X, Y, Z)	
Shock Test (Non-operation)	Acceleration: 50 G Wave: Half-sine Active Time: 11 ms Direction : $\pm X, \pm Y, \pm Z$. (one time for each Axis)	
Thermal Shock Test (TST)	-20°C/30min , 60°C / 30min , 100 cycles	
On/Off Test	25°C , On/10sec , Off /10sec , 30,000 cycles	
ESD (Electro Static Discharge)	Contact Discharge: $\pm 8KV, 150pF(330\Omega)$	
	Air Discharge: $\pm 15KV, 150pF(330\Omega)$	
Altitude Test	Operation:10,000 ft / 24hours Non-Operation:30,000 ft / 24hours	

Note (1) criteria : Normal display image with no obvious non-uniformity and no line defect.

Note (2) Evaluation should be tested after storage at room temperature for more than two hour

Note (3) At testing Vibration and Shock, the fixture in holding the module has to be hard and rigid enough so that the module would not be twisted or bent by the fixture.

The fixing condition is shown as below:



7. PACKING

7.1 PACKING SPECIFICATIONS

- (1) 12 LCD modules / 1 Box
- (2) Box dimensions: 490(L) X 325(W) X 320(H) mm
- (3) Weight: approximately: 15.7kg (12 modules per box)

7.2 PACKING METHOD

- (1) Carton Packing should have no failure in the following reliability test items.

Test Item	Test Conditions	Note
Vibration	ISTA STANDARD Random, Frequency Range: 1 – 200 Hz Top & Bottom: 30 minutes (+Z), 10 min (-Z), Right & Left: 10 minutes (X) Back & Forth 10 minutes (Y)	Non Operation
Dropping Test	1 Corner , 3 Edge, 6 Face, 61cm	Non Operation





Figure. 7-1 Packing method

7.3 PALLET

For ocean shipping

Sea / Land Transportation (40ft Container)



For air transport

Air transportation




Figure. 7-2 Packing method

8. CMI MODULE LABEL

The barcode nameplate is pasted on each module as illustration, and its definitions are as following explanation.



(a) Model Name: M156BGE-L20

(b) Revision: Rev. XX, for example: A0, A1... B1, B2... or C1, C2...etc.

(c) CMI barcode definition:

Serial ID: XX-XX-X-XX-YMD-L-NNNN

Code	Meaning	Description
XX	CMI internal use	-
XX	Revision	Cover all the change
X	CMI internal use	-
XX	CMI internal use	-
YMD	Year, month, day	Year: 0~9, 2001=1, 2002=2, 2003=3...2010=0, 2011=1, 2012=2... Month: 1~12=1, 2, 3, ~, 9, A, B, C Day: 1~31=1, 2, 3, ~, 9, A, B, C, ~, W, X, Y, exclude I, O, and U.
L	Product line #	Line 1=1, Line 2=2, Line 3=3, ...
NNNN	Serial number	Manufacturing sequence of product

(d) Customer's barcode definition:

Serial ID: CM-F6E20-X-X-X-XX-L-XX-L-YMD-NNNN

Code	Meaning	Description
CM	Supplier code	CMI=CM
F6E20	Model number	M156BGE-L20= F6E20
X	Revision code	Non ZBD: 1,2,~,8,9 / ZBD: A~Z
X	Source driver IC code	Century=1, CLL=2, Demos=3, Epson=4, Fujitsu=5, Himax=6, Hitachi=7, Hynix=8, LDI=9, Matsushita=A, NEC=B, Novatec=C, OKI=D, Philips=E, Renesas=F, Samsung=G, Sanyo=H, Sharp=I, TI=J, Topro=K, Toshiba=L, Windbond=M, ILITEK=Q, Fiti=Y, None IC =Z
X	Gate driver IC code	
XX	Cell location	Tainan Taiwan=TN, Ningbo China=CN, Hsinchu Taiwan=SC
L	Cell line #	1,2,~,9,A,B,~,Y,Z
XX	Module location	Tainan, Taiwan=TN ; Ningbo China=NP, Shenzhen China=SH
L	Module line #	1,2,~,9,A,B,~,Y,Z
YMD	Year, month, day	Year: 0~9, 2001=1, 2002=2, 2003=3...2010=0, 2011=1, 2012=2... Month: 1~12=1, 2, 3, ~, 9, A, B, C Day: 1~31=1, 2, 3, ~, 9, A, B, C, ~, T, U, V
NNNN	Serial number	By LCD supplier

(e) FAB ID(UL Factory ID):

Region	Factory ID
TWCM1	GEMN
NBCMI	LEOO
NBCME	CANO
NHCM1	CAPG

9. PRECAUTIONS

9.1 ASSEMBLY AND HANDLING PRECAUTIONS

- (1) Do not apply rough force such as bending or twisting to the module during assembly.
- (2) To assemble or install module into user's system can be only in clean working areas. The dust and oil may cause electrical short or worsen the polarizer.
- (3) It's not permitted to have pressure or impulse on the module because the LCD panel and Backlight will be damaged.
- (4) Always follow the correct power sequence when LCD module is connecting and operating. This can prevent damage to the CMOS LSI chips during latch-up.
- (5) Do not pull the I/F connector in or out while the module is operating.
- (6) Do not disassemble the module.
- (7) Use a soft dry cloth without chemicals for cleaning, because the surface of polarizer is very soft and easily scratched.
- (8) It is dangerous that moisture come into or contacted the LCD module, because moisture may damage LCD module when it is operating.
- (9) High temperature or humidity may reduce the performance of module. Please store LCD module within the specified storage conditions.
- (10) When ambient temperature is lower than 10°C may reduce the display quality. For example, the response time will become slowly.

9.2 STORAGE PRECAUTIONS

- (1) Do not leave the module in high temperature, and high humidity for a long time. It is highly recommended to store the module with temperature from 0°C to 35°C and relative humidity of less than 70%
- (2) Do not store the TFT – LCD module in direct sunlight
- (3) The module should be stored in dark place. It is prohibited to apply sunlight or fluorescent light in storing

9.3 OPERATION PRECAUTIONS

- (1) The LCD product should be operated under normal condition.

Normal condition is defined as below :

Temperature : 20±15°C

Humidity: 65±20%

Display pattern : continually changing pattern(Not stationary)

- (2) If the product will be used in extreme conditions such as high temperature, high humidity, high altitude, display pattern or operation time etc... It is strongly recommended to contact CMI for application engineering advice. Otherwise, its reliability and function may not be guaranteed.

9.4 SAFETY PRECAUTIONS

- (1) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.
- (2) After the module's end of life, it is not harmful in case of normal operation and storage.

9.5 SAFETY STANDARDS

The LCD module should be certified with safety regulations as follows:

- (1) UL60950-1 or updated standard.
- (2) IEC60950-1 or updated standard.


9.6 OTHER


When fixed patterns are displayed for a long time, remnant image is likely to occur.

Appendix. OUTLINE DRAWING

NOTES:
1.outline tolerance:0.5mm
2.side mount hole rotational torque must be MAX.5kgf-cm



ITEM NO.	GENERAL TYPICAL TOLERANCE	②③ C/PK DIMENSION	②④ CONTROL DIMENSION	DATE	SCALE	UNIT								
DRAWING	LEVEL													
0 - 8	0.05 0.1 0.2	2	APPROVED	Gene Chang	MT 68B 20901	PART NUMBER OF THIS DRAWING	DATE							
8 - 18	0.1 0.2 0.3						CHECKED	Robin Feag	Module Assembly	DESIGNED				
18 - 30	0.1 0.2 0.3									Small Ho	CHIMEI INNOVA	SIZE		
30 - 50	0.2 0.4 0.6											GENERAL TYPICAL TOLERANCE	LEVEL	TYPICAL
50 - 63	0.2 0.4 0.6													
63 - 125	0.2 0.4 0.6	0.1 0.2 0.3	0.2 0.3 0.4	0.3 0.4 0.6										
125 - 250	0.4 0.6 0.8				0.2 0.3 0.4	0.3 0.4 0.6	0.4 0.6 0.8							
250 - 500	0.6 0.8 1.0							0.3 0.4 0.6	0.4 0.6 0.8	0.6 0.8 1.0				
500 - 1000	0.8 1.0 1.2										0.4 0.6 0.8	0.6 0.8 1.0	0.8 1.0 1.2	
1000 - 2000	1.0 1.2 1.5													0.6 0.8 1.0
2000 - 5000	1.2 1.5 2.0	0.8 1.0 1.2	1.0 1.2 1.5	1.2 1.5 2.0										
5000 - 10000	1.5 2.0 2.5				1.0 1.2 1.5	1.2 1.5 2.0	1.5 2.0 2.5							
10000 - 20000	2.0 2.5 3.0							1.2 1.5 2.0	1.5 2.0 2.5	2.0 2.5 3.0				
20000 - 50000	2.5 3.0 3.5										1.5 2.0 2.5	2.0 2.5 3.0	2.5 3.0 3.5	
50000 - 100000	3.0 3.5 4.0													1.5 2.0 2.5
100000 - 200000	3.5 4.0 4.5	2.0 2.5 3.0	2.5 3.0 3.5	3.0 3.5 4.0										
200000 - 500000	4.0 4.5 5.0				2.5 3.0 3.5	3.0 3.5 4.0	3.5 4.0 4.5							
500000 - 1000000	4.5 5.0 5.5							3.0 3.5 4.0	3.5 4.0 4.5	4.0 4.5 5.0				
1000000 - 2000000	5.0 5.5 6.0										3.5 4.0 4.5	4.0 4.5 5.0	4.5 5.0 5.5	
2000000 - 5000000	5.5 6.0 6.5													4.0 4.5 5.0
5000000 - 10000000	6.0 6.5 7.0	4.5 5.0 5.5	5.0 5.5 6.0	5.5 6.0 6.5										
10000000 - 20000000	6.5 7.0 7.5				5.0 5.5 6.0	5.5 6.0 6.5	6.0 6.5 7.0							
20000000 - 50000000	7.0 7.5 8.0							5.5 6.0 6.5	6.0 6.5 7.0	6.5 7.0 7.5				
50000000 - 100000000	7.5 8.0 8.5										6.0 6.5 7.0	6.5 7.0 7.5	7.0 7.5 8.0	
100000000 - 200000000	8.0 8.5 9.0													6.5 7.0 7.5
200000000 - 500000000	8.5 9.0 9.5	7.0 7.5 8.0	7.5 8.0 8.5	8.0 8.5 9.0										
500000000 - 1000000000	9.0 9.5 10.0				7.5 8.0 8.5	8.0 8.5 9.0	8.5 9.0 9.5							
1000000000 - 2000000000	9.5 10.0 10.5							8.0 8.5 9.0	8.5 9.0 9.5	9.0 9.5 10.0				
2000000000 - 5000000000	10.0 10.5 11.0										8.5 9.0 9.5	9.0 9.5 10.0	9.5 10.0 10.5	
5000000000 - 10000000000	10.5 11.0 11.5													9.0 9.5 10.0
10000000000 - 20000000000	11.0 11.5 12.0	9.5 10.0 10.5	10.0 10.5 11.0	10.5 11.0 11.5										
20000000000 - 50000000000	11.5 12.0 12.5				10.0 10.5 11.0	10.5 11.0 11.5	11.0 11.5 12.0							
50000000000 - 100000000000	12.0 12.5 13.0							10.5 11.0 11.5	11.0 11.5 12.0	11.5 12.0 12.5				
100000000000 - 200000000000	12.5 13.0 13.5										11.0 11.5 12.0	11.5 12.0 12.5	12.0 12.5 13.0	
200000000000 - 500000000000	13.0 13.5 14.0													11.5 12.0 12.5
500000000000 - 1000000000000	13.5 14.0 14.5	12.0 12.5 13.0	12.5 13.0 13.5	13.0 13.5 14.0										
1000000000000 - 2000000000000	14.0 14.5 15.0				12.5 13.0 13.5	13.0 13.5 14.0	13.5 14.0 14.5							
2000000000000 - 5000000000000	14.5 15.0 15.5							13.0 13.5 14.0	13.5 14.0 14.5	14.0 14.5 15.0				
5000000000000 - 10000000000000	15.0 15.5 16.0										13.5 14.0 14.5	14.0 14.5 15.0	14.5 15.0 15.5	
10000000000000 - 20000000000000	15.5 16.0 16.5													14.0 14.5 15.0
20000000000000 - 50000000000000	16.0 16.5 17.0	14.5 15.0 15.5	15.0 15.5 16.0	15.5 16.0 16.5										
50000000000000 - 100000000000000	16.5 17.0 17.5				15.0 15.5 16.0	15.5 16.0 16.5	16.0 16.5 17.0							
100000000000000 - 200000000000000	17.0 17.5 18.0							15.5 16.0 16.5	16.0 16.5 17.0	16.5 17.0 17.5				
200000000000000 - 500000000000000	17.5 18.0 18.5										16.0 16.5 17.0	16.5 17.0 17.5	17.0 17.5 18.0	
500000000000000 - 1000000000000000	18.0 18.5 19.0													16.5 17.0 17.5
1000000000000000 - 2000000000000000	18.5 19.0 19.5	17.0 17.5 18.0	17.5 18.0 18.5	18.0 18.5 19.0										
2000000000000000 - 5000000000000000	19.0 19.5 20.0				17.5 18.0 18.5	18.0 18.5 19.0	18.5 19.0 19.5							
5000000000000000 - 10000000000000000	19.5 20.0 20.5							18.0 18.5 19.0	18.5 19.0 19.5	19.0 19.5 20.0				
10000000000000000 - 20000000000000000	20.0 20.5 21.0										18.5 19.0 19.5	19.0 19.5 20.0	19.5 20.0 20.5	
20000000000000000 - 50000000000000000	20.5 21.0 21.5													19.0 19.5 20.0
50000000000000000 - 100000000000000000	21.0 21.5 22.0	19.5 20.0 20.5	20.0 20.5 21.0	20.5 21.0 21.5										
100000000000000000 - 200000000000000000	21.5 22.0 22.5				20.0 20.5 21.0	20.5 21.0 21.5	21.0 21.5 22.0							
200000000000000000 - 500000000000000000	22.0 22.5 23.0							20.5 21.0 21.5	21.0 21.5 22.0	21.5 22.0 22.5				
500000000000000000 - 1000000000000000000	22.5 23.0 23.5										21.0 21.5 22.0	21.5 22.0 22.5	22.0 22.5 23.0	
1000000000000000000 - 2000000000000000000	23.0 23.5 24.0													21.5 22.0 22.5
2000000000000000000 - 5000000000000000000	23.5 24.0 24.5	22.0 22.5 23.0	22.5 23.0 23.5	23.0 23.5 24.0										
5000000000000000000 - 10000000000000000000	24.0 24.5 25.0				22.5 23.0 23.5	23.0 23.5 24.0	23.5 24.0 24.5							
10000000000000000000 - 20000000000000000000	24.5 25.0 25.5							23.0 23.5 24.0	23.5 24.0 24.5	24.0 24.5 25.0				
20000000000000000000 - 50000000000000000000	25.0 25.5 26.0										23.5 24.0 24.5	24.0 24.5 25.0	24.5 25.0 25.5	
50000000000000000000 - 100000000000000000000	25.5 26.0 26.5													24.0 24.5 25.0
100000000000000000000 - 200000000000000000000	26.0 26.5 27.0	24.5 25.0 25.5	25.0 25.5 26.0	25.5 26.0 26.5										
200000000000000000000 - 500000000000000000000	26.5 27.0 27.5				25.0 25.5 26.0	25.5 26.0 26.5	26.0 26.5 27.0							
500000000000000000000 - 1000000000000000000000	27.0 27.5 28.0							25.5 26.0 26.5	26.0 26.5 27.0	26.5 27.0 27.5				
1000000000000000000000 - 2000000000000000000000	27.5 28.0 28.5										26.0 26.5 27.0	26.5 27.0 27.5	27.0 27.5 28.0	
2000000000000000000000 - 5000000000000000000000	28.0 28.5 29.0													26.5 27.0 27.5
5000000000000000000000 - 10000000000000000000000	28.5 29.0 29.5	27.0 27.5 28.0	27.5 28.0 28.5	28.0 28.5 29.0										
10000000000000000000000 - 20000000000000000000000	29.0 29.5 30.0				27.5 28.0 28.5	28.0 28.5 29.0	28.5 29.0 29.5							
20000000000000000000000 - 50000000000000000000000	29.5 30.0 30.5							28.0 28.5 29.0	28.5 29.0 29.5	29.0 29.5 30.0				
50000000000000000000000 - 100000000000000000000000	30.0 30.5 31.0										28.5 29.0 29.5	29.0 29.5 30.0	29.5 30.0 30.5	
100000000000000000000000 - 200000000000000000000000	30.5 31.0 31.5													29.0 29.5 30.0
200000000000000000000000 - 500000000000000000000000	31.0 31.5 32.0	29.5 30.0 30.5	30.0 30.5 31.0	30.5 31.0 31.5										
500000000000000000000000 - 1000000000000000000000000	31.5 32.0 32.5				30.0 30.5 31.0	30.5 31.0 31.5	31.0 31.5 32.0							
1000000000000000000000000 - 2000000000000000000000000	32.0 32.5 33.0							30.5 31.0 31.5	31.0 31.5 32.0	31.5 32.0 32.5				
2000000000000000000000000 - 5000000000000000000000000	32.5 33.0 33.5										31.0 31.5 32.0	31.5 32.0 32.5	32.0 32.5 33.0	
5000000000000000000000000 - 10000000000000000000000000	33.0 33.5 34.0													31.5 32.0 32.5
10000000000000000000000000 - 20000000000000000000000000	33.5 34.0 34.5	32.0 32.5 33.0	32.5 33.0 33.5	33.0 33.5 34.0										
20000000000000000000000000 - 50000000000000000000000000	34.0 34.5 35.0				32.5 33.0 33.5	33.0 33.5 34.0	33.5 34.0 34.5							
50000000000000000000000000 - 100000000000000000000000000	34.5 35.0 35.5							33.0 33.5 34.0	33.5 34.0 34.5	34.0 34.5 35.0				
100000000000000000000000000 - 200000000000000000000000000	35.0 35.5 36.0										33.5 34.0 34.5	34.0 34.5 35.0	34.5 35.0 35.5	
200000000000000000000000000 - 500000000000000000000000000	35.5 36.0 36.5													34.0 34.5 35.0
500000000000000000000000000 - 1000000000000000000000000000	36.0 36.5 37.0	34.5 35.0 35.5	35.0 35.5 36.0	35.5 36.0 36.5										
1000000000000000000000000000 - 2000000000000000000000000000	36.5 37.0 37.5				35.0 35.5 36.0	35.5 36.0 36.5	36.0 36.5 37.0							
2000000000000000000000000000 - 5000000000000000000000000000	37.0 37.5 38.0							35.5 36.0 36.5	36.0 36.5 37.0	36.5 37.0 37.5				
5000000000000000000000000000 - 10000000000000000000000000000	37.5 38.0 38.5										36.0 36.5 37.0	36.5 37.0 37.5	37.0 37.5 38.0	
10000000000000000000000000000 - 20000000000000000000000000000	38.0 38.5 39.0													36.5 37.0 37.5
20000000000000000000000000000 - 50000000000000000000000000000	38.5 39.0 39.5	37.0 37.5 38.0	37.5 38.0 38.5	38.0 38.5 39.0										
50000000000000000000000000000 - 100000000000000000000000000000	39.0 39.5 40.0				37.5 38.0 38.5	38.0 38.5 39.0	38.5 39.0 39.5							
100000000000000000000000000000 - 200000000000000000000000000000	39.5 40.0 40.5							38.0 38.5 39.0	38.5 39.0 39.5	39.0 39.5 40.0				
200000000000000000000000000000 - 500000000000000000000000000000	40.0 40.5 41.0										38.5 39.0 39.5	39.0 39.5 40.0	39.5 40.0 40.5	
500000000000000000000000000000 - 1000000000000000000000000000000	40.5 41.0 41.5													39.0 39.5 40.0
1000000000000000000000000000000 - 2000000000000000000000000000000	41.0 41.5 42.0	39.5 40.0 40.5	40.0 40.5 41.0	40.5 41.0 41.5										
2000000000000000000000000000000 - 5000000000000000000000000000000	41.5 42.0 42.5				40.0 40.5 41.0	40.5 41.0 41.5	41.0 41.5 42.0							
5000000000000000000000000000000 - 10000000000000000000000000000000	42.0 42.5 43.0							40.5 41.0 41.5	41.0 41.5 42.0	41.5 42.0 42.5				
10000000000000000000000000000000 - 20000000000000000000000000000000	42.5 43.0 43.5										41.0 41.5 42.0	41.5 42.0 42.5	42.0 42.5 43.0	
20000000000000000000000000000000 - 50000000000000000000000000000000	43.0 43.5 44.0													41.5 42.0 42.5
50000000000000000000000000000000 - 100000000000000000000000000000000	43.5 44.0 44.5	42.0 42.5 43.0	42.5 43.0 43.5	43.0 43.5 44.0										
100000000000000000000000000000000 - 200000000000000000000000000000000	44.0 44.5 45.0				42.5 43.0 43.5	43.0 43.5 44.0	43.5 44.0 44.5							
200000000000000000000000000000000 - 500000000000000000000														



REV	EC NUMBER	DESCRIPTION	DATE
1	000000	000000	0000/00/00

REV	EC NUMBER	DESCRIPTION	DATE
1	000000	000000	0000/00/00

APPROVED	Gene Chang	DATE	2012.01.12
CHECKED	Robin Feng	DATE	2012.01.12
DESIGNED	Robin Feng	DATE	2012.01.12

CHIMEI INNOVEX	AI
----------------	----