

All information is subject to change without notice. Please read bottom notes.**FEATURES**

- (1) 13.3XGA(1024x768 pixels) display size for notebook PC
- (2) LVDS interface system (H-Sync, V-Sync)
- (3) RoHS directive conformance

TENTATIVE**MECHANICAL SPECIFICATIONS**

Item	Specifications
Dimensional Outline (typ.)	284.0(W) x 214.5 (H) x 5.5max(D) mm
Number of Pixels	1024(W) x 768(H) pixels
Active Area	270.336(W) x 202.752(H) mm
Pixel Pitch	0.264(W) x 0.264(H)
Weight (approximately)	350g max.
Backlight	Single CCFL, Sidelight type

ABSOLUTE MAXIMUM RATINGS

Item	Min.	Max.	Unit
Supply Voltage	(V _{DD})	-0.3	4.0
	(V _{FL})	0	2.0
FL Driving Frequency (f _{FL})	-	100	kHz
Input Signal Voltage (V _{IN})	-0.3	V _{DD} +0.3	V
Operating Temperature	0	50	°C
Storage Temperature	-20	60	°C
Storage Humidity	10	90	%(RH)

ELECTRICAL SPECIFICATION

Item		Min.	Typ.	Max.	Unit	Remarks
Supply Voltage	(V _{DD})	3.0	3.3	3.6	V	
	(V _{FL})	---	(650)	---	V(rms)	I _{FL} =6.0 mA(rms)
FL Start Voltage (Ta=0°C)		1500	---	---	V(rms)	
Differential Input Voltage	(V _{ID})	100	---	600	mV	
Comon Mode Input Voltage	(V _{CM})	1.0	---	2.4-V _{ID} /2	V	
Current Consumption	*2 (I _{DD})	---	(240)	---	mA	
	*3 (I _{FL})	---	6.0	---	mA(rms)	
*2 *3 Power Consumption		---	(4.7)	---	W	I _{FL} =6.0 mA(rms)

*1 : Refer to THC63LVDF84A-85 Specification by THine Electronics,Inc.

*2 : 8 color bars pattern

*3 : Excepting the efficiency FL inverter

*4 : V_{OS} : Offset Mode Voltage**OPTICAL SPECIFICATION (Ta=25°C)**


Item	Min.	Typ.	Max.	Unit	Remarks
Contrast Ratio (CR)	150	250	---	---	
Response Time	(t _{ON})+(t _{OFF})	---	50	ms	
Luminance (L)	---	(200)	---	cd/m ²	I _{FL} =6.0mA(rms)

*The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by Toshiba or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Toshiba or others.



*The information contained herein may be changed without prior notice. It is therefore advisable to contact Toshiba before proceeding with the design of equipment incorporating this product.

TENTATIVE


Standard tolerance : ± 0.5



BLOCK DIAGRAM



TIMING CHART



TIMING SPECIFICATION ^{1) 2) 3) 4) 5) 6) 7)}

Item	Symbol	min.	typ.	max.	unit
Horizontal Scanning Term	th	1334 x tc	1344 x tc	-	clock
H-sync Pulse Width	thw	4 x tc	136 x tc	-	clock
Horizontal Front Porch	thfp	4 x tc	24 x tc	-	clock
Horizontal Back Porch	thbp	24 x tc	160 x tc	-	clock
Horizontal Data Sync Period	thds	32 x tc	296 x tc	-	clock
Horizontal Display Term	thd	1024 x tc	1024 x tc	1024 x tc	clock
Frame Period	tv	778 x th	806 x th	860 x th	line
V-sync Pulse Width	tvw	2 x th	6 x th	-	line
V-sync Set Up Time (to H-sync)	tvsu	8 x tc	-	-	clock
V-sync Hold Time	tvhd	(thbp+16) x tc	-	-	clock
Vertical Front Porch	tvfp	1 x th	3 x th	-	line
Vertical Back Porch	tvbp	2 x th	29 x th	-	line
Vertical Data Sync Period	tvds	8 x th	35 x th	-	line
Vertical Display Term	tvd	768 x th	768 x th	768 x th	line
Clock Period	tc	15.0	15.38	-	ns

Note 1) Refer to "Timing Chart" and LVDS (THC63LVDF84A-85) specifications by THine Electronics, Inc.

Note 2) If DE is fixed to "H" or "L" level for certain period while NCLK is supplied, the panel displays black with some flicker.

Note 3) If NCLK is fixed to "H" or "L" level for certain period while DE is supplied, the panel may be damaged.

Note 4) Please adjust LCD operating signal timing and FL driving frequency, to optimize the display quality.

There is a possibility that flicker is observed by the interference of LCD operating signal timing and FL driving condition (especially driving frequency), even if the condition satisfies above timing specifications and recommended operating conditions shown in 3.

Note5) Do not make tv, tvhd and tvds fluctuate.

If tv, tvhd, and tvds are fluctuate, the panel displays black.

Note6) In case of using the long frame period, the deterioration of display quality, noise etc. may be occurred.

Note7) NCLK count of each Horizontal Scanning Time should be always the same.

V-Blanking period should be "n" X "Horizontal Scanning Time". (n: integer)

Frame period should be always the same.

CONNECTOR PIN ASSIGNMENT FOR INTERFACE

CN1 INPUT SIGNAL

CN1 INPUT SIGNAL (DF19L-20P-1H / HIROSE ELECTRIC CO., LTD.)

Mating Connector : DF19G-20S-1F (FPC), DF19G-20S-1C (Cable)

Terminal No.	Symbol	Function
1	V _{DD}	Power Supply : +3.3V
2	V _{DD}	Power Supply : +3.3V
3	V _{SS}	GND
4	V _{SS}	GND
5	RxIN0-	Negative LVDS differential data input (R0-R5,G0)
6	RxIN0+	Positive LVDS differential data input (R0-R5,G0)
7	V _{SS}	GND
8	RxIN1-	Negative LVDS differential data input (G1-G5, B0-B1)
9	RxIN1+	Positive LVDS differential data input (G1-G5, B0-B1)
10	V _{SS}	GND
11	RxIN2-	Negative LVDS differential data input (B2-B5, HS, VS, DE)
12	RxIN2+	Positive LVDS differential data input (B2-B5, HS, VS, DE)
13	V _{SS}	GND
14	CLK-	Clock Signal(-)
15	CLK+	Clock Signal(+)
16	V _{SS}	GND
17	NC	NC
18	NC	NC
19	V _{SS}	GND
20	V _{SS}	GND

Note 1) Please connect GND pin to ground. Don't use it as no-connect nor connection with high impedance.

CN2 CCFL POWER SOURCE

Connector : BHSR-02VS-1 / JAPAN SOLDERLESS TERMINAL MFG CO., LTD.

Mating Connector : SM02B-BHS-1 / JAPAN SOLDERLESS TERMINAL MFG CO., LTD.


Terminal No.	Symbol	Function
1	V _{FLH}	CCFL Power Supply (high voltage)
2	V _{FLL}	CCFL Power Supply (low voltage)

RECOMMENDED TRANSMITTER (DS90CF363) TO LTD133ECKS INTERFACE ASSIGNMENT

Case1: 6bit Transmitter

DS90CF363				LTD133ECKS Interface (CN1)	
Input Terminal No.		Input Signal (Graphics controller output signal)		Output Signal Symbol	
Symbol	Terminal	Symbol	Function		Terminal Symbol
TIN0	44	R0	Red Pixels Display Data (LSB)	TOUT0- TOUT0+	No.5 No.6 IN0- IN0+
TIN1	45	R1	Red Pixels Display Data		
TIN2	47	R2	Red Pixels Display Data		
TIN3	48	R3	Red Pixels Display Data		
TIN4	1	R4	Red Pixels Display Data		
TIN5	3	R5	Red Pixels Display Data (MSB)	TOUT1- TOUT1+	No.8 No.9 IN1- IN1+
TIN6	4	G0	Green Pixels Display Data (LSB)		
TIN7	6	G1	Green Pixels Display Data		
TIN8	7	G2	Green Pixels Display Data		
TIN9	9	G3	Green Pixels Display Data		
TIN10	10	G4	Green Pixels Display Data	TOUT2- TOUT2+	No.11 No.12 IN2- IN2+
TIN11	12	G5	Green Pixels Display Data (MSB)		
TIN12	13	B0	Blue Pixels Display Data (LSB)		
TIN13	15	B1	Blue Pixels Display Data		
TIN14	16	B2	Blue Pixels Display Data		
TIN15	18	B3	Blue Pixels Display Data	TOUT2- TOUT2+	No.11 No.12 IN2- IN2+
TIN16	19	B4	Blue Pixels Display Data		
TIN17	20	B5	Blue Pixels Display Data (MSB)		
TIN18	22	HSYNC	H-Sync		
TIN19	23	VSYNC	V-Sync		
TIN20	25	DE	Compound Synchronization Signal	TCLK OUT- TCLK OUT+	No.14 No.15 CLK- CLK+
CLK IN	26	CLK	Data Sampling Clock		

Note 1) Please connect NC pin to nothing. Don't connect it to ground nor to other signal input.




RECOMMENDED TRANSMITTER (DS90CF383) TO LTD133ECKS INTERFACE ASSIGNMENT

Case2: 8bit Transmitter

DS90CF383				LTD133ECKS Interface (CN1)	
Input Terminal No.		Input Signal (Graphics controller output signal)		Output Signal Symbol	Terminal
Symbol	Terminal	Symbol	Function		Symbol
TIN0	51	R0	Red Pixels Display Data (LSB)	TOUT0- TOUT0+	No.5 No.6
TIN1	52	R1	Red Pixels Display Data		
TIN2	54	R2	Red Pixels Display Data		
TIN3	55	R3	Red Pixels Display Data		
TIN4	56	R4	Red Pixels Display Data		
TIN6	3	R5	Red Pixels Display Data (MSB)	TOUT1- TOUT1+	No.8 No.9
TIN7	4	G0	Green Pixels Display Data(LSB)		
TIN8	6	G1	Green Pixels Display Data		
TIN9	7	G2	Green Pixels Display Data		
TIN12	11	G3	Green Pixels Display Data		
TIN13	12	G4	Green Pixels Display Data	TOUT2- TOUT2+	No.11 No.12
TIN14	14	G5	Green Pixels Display Data(MSB)		
TIN15	15	B0	Blue Pixels Display Data (LSB)		
TIN18	19	B1	Blue Pixels Display Data		
TIN19	20	B2	Blue Pixels Display Data		
TIN20	22	B3	Blue Pixels Display Data	TOUT3- TOUT3+	
TIN21	23	B4	Blue Pixels Display Data		
TIN22	24	B5	Blue Pixels Display Data (MSB)		
TIN24	27	HSYNC	H-Sync		
TIN25	28	VSYNC	V-Sync		
TIN26	30	DE	Compound Synchronization Signal	TCLK OUT- TCLK OUT+	No.14 No.15
TIN27	50	NC	Non Connection (open)		
TIN5	2	NC	Non Connection (open)		
TIN10	8	NC	Non Connection (open)		
TIN11	10	NC	Non Connection (open)		
TIN16	16	NC	Non Connection (open)		
TIN17	18	NC	Non Connection (open)		
TIN23	25	NC	Non Connection (open)		
CLK IN	31	CLK	Data Sampling Clock		

Note 1) Please connect NC pin to nothing. Don't connect it to ground nor to other signal input.



256k (k=1024) COLORS COMBINATION TABLE

	Display	R5 R4 R3 R2 R1 R0	G5 G4 G3 G2 G1 G0	B5 B4 B3 B2 B1 B0	Gray Scale Level		
Basic Color	Black	L L L L L L L	L L L L L L L	L L L L L L L	-		
	Blue	L L L L L L L	L L L L L L L	H H H H H H H	-		
	Green	L L L L L L L	H H H H H H H	L L L L L L L	-		
	Light Blue	L L L L L L L	H H H H H H H	H H H H H H H	-		
	Red	H H H H H H H	L L L L L L L	L L L L L L L	-		
	Purple	H H H H H H H	L L L L L L L	H H H H H H H	-		
	Yellow	H H H H H H H	H H H H H H H	L L L L L L L	-		
	White	H H H H H H H	H H H H H H H	H H H H H H H	-		
Gray Scale of Red	Black	L L L L L L L	L L L L L L L	L L L L L L L	L 0		
	Dark ↑ ↓ Light	L L L L L H L	L L L L L L L	L L L L L L L	L 1		
		L L L L L H L	L L L L L L L	L L L L L L L	L 2		
		⋮		⋮		⋮	
		⋮		⋮		L3... L60	
	Light	H H H H L H	L L L L L L L	L L L L L L L	L61		
		H H H H H L	L L L L L L L	L L L L L L L	L62		
	Red	H H H H H H	L L L L L L L	L L L L L L L	Red	L63	
Gray Scale of Green	Black	L L L L L L L	L L L L L L L	L L L L L L L	L 0		
	Dark ↑ ↓ Light	L L L L L L L	L L L L L L H	L L L L L L L	L 1		
		L L L L L L L	L L L L L H L	L L L L L L L	L 2		
		⋮		⋮		⋮	
		⋮		⋮		L3... L60	
	Light	L L L L L L L	H H H H L H	L L L L L L L	L61		
		L L L L L L L	H H H H H L	L L L L L L L	L62		
	Green	L L L L L L L	H H H H H H	L L L L L L L	Green	L63	
Gray Scale of Blue	Black	L L L L L L L	L L L L L L L	L L L L L L L	L 0		
	Dark ↑ ↓ Light	L L L L L L L	L L L L L L L	L L L L L H	L 1		
		L L L L L L L	L L L L L L L	L L L L H L	L 2		
		⋮		⋮		⋮	
		⋮		⋮		L3... L60	
	Light	L L L L L L L	L L L L L L L	H H H H L H	L61		
		L L L L L L L	L L L L L L L	H H H H H L	L62		
	Blue	L L L L L L L	L L L L L L L	H H H H H H	Blue	L63	
Gray Scale of White & Black	Black	L L L L L L L	L L L L L L L	L L L L L L L	L 0		
	Dark ↑ ↓ Light	L L L L L H	L L L L L H	L L L L L H	L 1		
		L L L L H L	L L L L H L	L L L L H L	L 2		
		⋮		⋮		⋮	
		⋮		⋮		L3... L60	
	Light	H H H H L H	H H H H L H	H H H H L H	L61		
		H H H H H L	H H H H H L	H H H H H L	L62		
	White	H H H H H H	H H H H H H	H H H H H H	white	L63	

**FOR SAFETY**

LCD module is generally designed with precise parts to achieve light weighted thin mechanical dimensions.
In using our Modules, make certain that you fully understand and put into practice the warnings and safety precautions detailed in Engineering Information No.EE-D-001A,"CAUTIONS AND INSTRUCTIONS FOR TOSHIBA LCD MODULES".
Refer to individual specifications and TECHNICAL DATA sheets (hereinafter called "TD") for more detailed technical information.

1) SPECIAL PURPOSES

A) Toshiba Matsushita Display Technology's Standard LCD Modules have not been customized for operation in extreme environments or for use in applications where performance failures could be life-threatening or otherwise catastrophic.

B) Since Toshiba Matsushita Display Technology 's Standard LCD Modules have not been designed for operation in extreme environments, they must never be used in devices that will be exposed to abnormally high levels of vibration or shock which exceed Toshiba Matsushita Display Technology's published specification limits.

C) In addition, since Toshiba Matsushita Display Technology Standard LCD Modules have not been designed for use in applications where performance failures could be life-threatening or catastrophic, they must never be installed in aircraft navigation control systems (such as, but not limited to Traffic Collision Avoidance System and Air Traffic Indicator), in military defense or weapons systems, in critical industrial process-control systems (e.g., those involved in the production of nuclear energy), or in critical medical device or patient life-support systems.

2) DISASSEMBLING OR MODIFICATION

DO NOT DISASSEMBLE OR MODIFY the module. It may damage sensitive parts inside LCD module, and may cause scratches or dust on the display.

Toshiba Matsushita Display Technology does not warrant the module, if customer disassembled or modified it.

3) BREAKAGE OF LCD PANEL

DO NOT INGEST liquid crystal material, DO NOT INHALE this material, and DO NOT CONTACT the material with skin, if LCD panel is broken and liquid crystal material spills out.

If liquid crystal material comes into mouth or eyes, rinse mouth or eyes out with water immediately.

If this material contact with skin or cloths, wash it off immediately with alcohol and rinse thoroughly with water.

4) GLASS OF LCD PANEL

BE CAREFUL WITH CHIPS OF GLASS that may cause injuring fingers or skin, when the glass is broken.

5) ELECTRIC SHOCK

DISCONNECT POWER SUPPLY before handling LCD module.

DO NOT TOUCH the parts inside LCD module and the fluorescent lamp's connector or cables in order to prevent electric shock, because high voltage is supplied to these parts from the inverter unit while power supply is turned on.

6) ABSOLUTE MAXIMUM RATINGS AND POWER PROTECTION CIRCUIT

DO NOT EXCEED the absolute maximum rating values under the worst probable conditions caused by the supply voltage variation, input voltage variation, variation in parts' constants, environmental temperature, etc., otherwise LCD module may be damaged.

Employ protection circuit for power supply, whenever the specification or TD specifies it.

Suitable protection circuit should be applied for each system design.

7) DISPOSAL

When dispose LCD module, obey to the applicable environmental regulations.