




Product Specification

AU OPTRONICS CORPORATION

() Preliminary Specifications

(V) Final Specifications

Module	13.3"(13.26") FHD 16:9 Color TFT-LCD with LED Backlight design
Model Name	B133HAN06.2 (HW:0A)
Note ()	<i>LED Backlight with driving circuit design</i>

Customer	Date
Checked & Approved by	Date
Note: This Specification is subject to change without notice.	

Approved by	Date
<u>Jo YC Cheng</u>	<u>07/06/2018</u>
Prepared by	Date
<u>Henry CH Chen</u>	<u>07/06/2018</u>
AU Optronics corporation	



Contents

1. Handling Precautions	4
2. General Description	5
2.1 General Specification.....	5
2.3 Optical Characteristics	7
3. Functional Block Diagram	12
4. Absolute Maximum Ratings.....	13
4.1 Absolute Ratings of TFT LCD Module.....	13
4.2 Absolute Ratings of Environment.....	13
5. Electrical Characteristics.....	14
5.1 TFT LCD Module	14
5.2 Backlight Unit.....	17
6. Signal Interface Characteristic.....	18
6.1 Pixel Format Image.....	18
6.2 Integration Interface Requirement.....	19
6.3 Interface Timing	22
6.4 Power ON/OFF Sequence	23
7. Panel Reliability Test	26
7.1 Vibration Test	26
7.2 Shock Test	26
7.3 Reliability Test.....	26
8. Mechanical Characteristics.....	27
8.1 Total Solution Outline Dimension	27
9. Shipping and Package	29
9.1 Shipping Label Format.....	29
9.2 Carton Package	30
9.3 Shipping Package of Palletizing Sequence.....	30
10. Appendix: EDID Description	31



Product Specification

AU OPTRONICS CORPORATION

Record of Revision

Version and Date	Page	Old description	New Description	Remark
0.1 2017/10/06	All	First Edition for Customer		
0.2 2018/01/22	29	Shipping Label Format		
0.3 2018/01/22	31	Appendix: EDID Description		
0.4 2018/01/22	29	Shipping Label Format		
0.4 2018/01/22	31	Appendix: EDID Description		
0.5 2018/07/06	5	General Specification		
0.5 2018/07/06	17	LED characteristics		
0.5 2018/07/06	27-28	Mechanical Characteristics		
0.5 2018/07/06	29	Shipping Label Format		



1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 10) After installation of the TFT Module into an enclosure (Notebook PC Bezel, for example), do not twist nor bend the TFT Module even momentarily. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 11) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 12) Disconnecting power supply before handling LCD modules, it can prevent electric shock, DO NOT TOUCH the electrode parts, cables, connectors and LED circuit part of TFT module that a LED light bar build in as a light source of back light unit. It can prevent electrostatic breakdown.



2. General Description

B133HAN06.2 is a Color Active Matrix Liquid Crystal Display composed of a TFT LCD panel, a driver circuit, and LED backlight system. The screen format is intended to support the 16:9 FHD, 1920(H) x1080(V) screen and 262k colors (RGB 6-bits data driver) with LED backlight driving circuit. All input signals are eDP (Embedded DisplayPort) interface compatible.

B133HAN06.2 is designed for a display unit of notebook style personal computer and industrial machine.

2.1 General Specification

The following items are characteristics summary on the table at 25 °C condition:

Items	Unit	Specifications			
Screen Diagonal	[mm]	336.71			
Active Area	[mm]	293.76x165.24			
Pixels H x V		1920x3(RGB) x 1080			
Pixel Pitch	[mm]	0.153 x 0.153			
Pixel Format		R.G.B. Vertical Stripe			
Display Mode		Normally Black (AHVA)			
White Luminance (ILED=24mA) (Note: ILED is LED current)	[cd/m ²]	220 typ. (5 points average) 187 min. (5 points average)			
Luminance Uniformity		1.25 max. (5 points)			
Contrast Ratio		500 typ			
Response Time	[ms]	27 typ / 35 Max			
Nominal Input Voltage VDD	[Volt]	+3.3 typ.			
Power Consumption	[Watt]	3.5 max (Include Logic and Blu power)			
Weight	[Grams]	210g max			
Physical Size	[mm]		Min.	Typ.	Max.
		Length	299.96	300.26	300.56
		Width	187.49	187.99	188.49
		Thickness	-	-	2.5 w/PCBA
Electrical Interface		2 Lane eDP 1.2			
Glass Thickness	[mm]	0.3/0.3			
Surface Treatment		HC			



Product Specification

AU OPTRONICS CORPORATION

Support Color		262K colors (RGB 6-bit)
Temperature Range Operating Storage (Non-Operating)	[°C] [°C]	0 to +50 -20 to +60
RoHS Compliance		RoHS Compliance



Product Specification


AU OPTRONICS CORPORATION

2.3 Optical Characteristics


The optical characteristics are measured under stable conditions at 25°C (Room Temperature) :

Item		Symbol	Conditions	Min.	Typ.	Max.	Unit	Note
White Luminance ILED=TBD (Base Panel Only)			5 points average	187	220	-	cd/m2	1, 4, 5.
Viewing Angle		θR θL	Horizontal (Right) CR = 10 (Left)	80 80	85 85	- -	degree	4, 9
		ψH ψL	Vertical (Upper) CR = 10 (Lower)	80 80	85 85	- -		
Luminance Uniformity		δ5P	5 Points	-	-	1.25		1, 3, 4
Luminance Uniformity		δ13P	13 Points	-	-	1.6		2, 3, 4
Contrast Ratio		CR		400	500	-		4, 6
Cross talk		%				4		4, 7
Response Time		TRT	Rising + Falling	-	27	35		
Color / Chromaticity Coodinates	Red	Rx	CIE 1931	0.542	0.572	0.602	-	4
		Ry		0.315	0.345	0.375		
	Green	Gx		0.318	0.348	0.378		
		Gy		0.535	0.565	0.595		
	Blue	Bx		0.130	0.160	0.190		
		By		0.083	0.113	0.143		
	White	Wx		0.283	0.313	0.343		
		Wy		0.299	0.329	0.359		
NTSC		%			45	-		

Note 1: 5 points position (Ref: Active area)



Note 2: 13 points position (Ref: Active area)



Note 3: The luminance uniformity of 5 or 13 points is defined by dividing the maximum luminance values by the minimum test point luminance


$$\delta_{W5} = \frac{\text{Maximum Brightness of five points}}{\text{Minimum Brightness of five points}}$$

$$\delta_{W13} = \frac{\text{Maximum Brightness of thirteen points}}{\text{Minimum Brightness of thirteen points}}$$

Note 4: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting

Backlight for 30 minutes in a stable, windless and dark room, and it should be measured in the center of screen.



Note 5 : Definition of Average Luminance of White (Y_L):

Measure the luminance of gray level 63 at 5 points , $Y_L = [L(1) + L(2) + L(3) + L(4) + L(5)] / 5$

$L(x)$ is corresponding to the luminance of the point X at Figure in Note (1).

Note 6 : Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$


Note 7 : Definition of Cross Talk (CT)

$$CT = |Y_B - Y_A| / Y_A \times 100 (\%)$$

Where


Y_A = Luminance of measured location without gray level 0 pattern (cd/m^2)

Y_B = Luminance of measured location with gray level 0 pattern (cd/m^2)




Note 8: Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are changed from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval between the 10% and 90% of amplitudes. Refer to figure as below.




Note 9. Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° (θ) horizontal left and right and 90° (ϕ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



3. Functional Block Diagram

The following diagram shows the functional block of the 13.3 inches wide Color TFT/LCD 30 Pin



4. Absolute Maximum Ratings

An absolute maximum rating of the module is as following:

4.1 Absolute Ratings of TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	Vin	-0.3	4	[Volt]	Note 1,2

4.2 Absolute Ratings of Environment

Item	Symbol	Min	Max	Unit	Conditions
Operating Temperature	TOP	0	+50	[°C]	Note 4
Operation Humidity	HOP	5	95	[%RH]	Note 4
Storage Temperature	TST	-20	+60	[°C]	Note 4
Storage Humidity	HST	5	95	[%RH]	Note 4

Note 1: At Ta (25°C)

Note 2: Permanent damage to the device may occur if exceed maximum values


Note 3: LED specification refer to section 5.2

Note 4: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).

Note 5: The packing material of system forbid to involve ammonium component

Note 6: The reliability test conditions of system do not exceed the verified conditions of TFT module

Note 7: Be sure the panel test condition do not exceed the component limitation of TFT module(TN Liquid crystal , for example)



5.1.2 Signal Electrical Characteristics


Signal electrical characteristics are as follows;

Display Port main link signal:

Differential pair VD+ , VD-
Which is one Display port
Main link

VCM of Display port
Main link

$$V_{diffP-P} = [(VD+) - (VD-)] \times 2$$




Display port main link					
		Min	Typ	Max	unit
VCM	RX input DC Common Mode Voltage		0		V
VDiff _{P-P}	Peak-to-peak Voltage at a receiving Device	150		1320	mV

Follow as VESA display port standard V1.3

Display Port AUX_CH signal:

Differential AUX+ , AUX-
Which is Display port AUX_CH





Product Specification

AU OPTRONICS CORPORATION

Display port AUX_CH					
		Min	Typ	Max	unit
VCM	AUX DC Common Mode Voltage		0		V
VDiff _{P-P}	AUX Peak-to-peak Voltage at a receiving Device	270		800	mV

Follow as VESA display port standard V1.3

Display Port VHPD signal:

Display port VHPD					
		Min	Typ	Max	unit
VHPD	HPD Voltage	2.25	-	3.6	V

Follow as VESA display port standard V1.3



Product Specification

AU OPTRONICS CORPORATION

5.2 Backlight Unit

5.2.1 LED characteristics

Parameter	Symbol	Min	Typ	Max	Units	Condition
Backlight Power Consumption	PLED	-	-	2.3	[Watt]	(Ta=25°C), Note 1
LED Life-Time	N/A	15,000	-	-	Hour	(Ta=25°C), Note 2 I _F =17.4 mA

Note 1: Calculator value for reference $P_{LED} = V_F$ (Normal Distribution) * I_F (Normal Distribution) / Efficiency

Note 2: The LED life-time define as the estimated time to 50% degradation of initial luminous.

5.2.2 Backlight input signal characteristics

Parameter	Symbol	Min	Typ	Max	Units	Remark
LED Power Supply	VLED (Note 1)	5.0	12.0	21.0	[Volt]	Define as Connector Interface (Ta=25°C)
LED Enable Input High Level	VLED_EN	2.2	-	5.5	[Volt]	
LED Enable Input Low Level		-	-	0.6	[Volt]	
PWM Logic Input High Level	VPWM_EN	2.2	-	5.5	[Volt]	
PWM Logic Input Low Level		-	-	0.6	[Volt]	
PWM Input Frequency	FPWM	200	-	10K	Hz	
PWM Duty Ratio	Duty	5 (Note 2)	--	100	%	

Note 1 : Recommend system pull up/down resistor no bigger than 10kohm


Note 2 : If the PWM duty ratio(min) is set between 5% to 1% , the PWM input frequency should be set below 1KHz .

The brightness-duty characteristic might not be able to keep in it's linearity if the dimming control is operated in 1% to 5% range.

6. Signal Interface Characteristic

6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.



6.2 Integration Interface Requirement

6.2.1 Connector Description

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

Connector Name / Designation	For Signal Connector
Manufacturer	IPEX or compatible
Type / Part Number	IPEX 20455-030E or Compatible
Mating Housing/Part Number	IPEX 20453-030T-11 or Compatible

6.2.2 Pin Assignment


PIN NO	Symbol	Function
1	DCR	DCR enable
2	H_GND	High Speed Ground
3	Lane1_N (2 Lane)	Comp Signal Link Lane 1
4	Lane1_P (2 Lane)	True Signal Link Lane 1
5	H_GND	High Speed Ground
6	Lane0_N	Comp Signal Link Lane 0
7	Lane0_P	True Signal Link Lane 0
8	H_GND	High Speed Ground
9	AUX_CH_P	True Signal Auxiliary Ch.
10	AUX_CH_N	Comp Signal Auxiliary Ch.
11	H_GND	High Speed Ground
12	LCD_VCC	LCD logic and driver power
13	LCD_VCC	LCD logic and driver power
14	LCD_Self_Test	LCD Panel Self Test Enable
15	LCD_GND	LCD logic and driver ground
16	LCD_GND	LCD logic and driver ground
17	HPD	HPD signal pin
18	BL_GND	Backlight_ground
19	BL_GND	Backlight_ground
20	BL_GND	Backlight_ground
21	BL_GND	Backlight_ground
22	BL_Enable	Backlight On / Off
23	BL_PWM_DIM	System PWM signal Input
24	NC	Reverse for AUO TEST only



Product Specification


AU OPTRONICS CORPORATION

25	NC	Reverse for AUO TEST only
26	BL_PWR	Backlight power (6V~21V)
27	BL_PWR	Backlight power (6V~21V)
28	BL_PWR	Backlight power (6V~21V)
29	BL_PWR	Backlight power (6V~21V)
30	NC	No Connect



Note1: Start from right side.

Note2: Input signals shall be low or High-impedance state when VDD is off.
Internal circuit of **eDP inputs** are as following.



6.3 Interface Timing

6.3.1 Timing Characteristics

Basically, interface timings should match the 1920x1080 /60Hz manufacturing guide line timing.

Parameter		Symbol	Min.	Typ.	Max.	Unit
Frame Rate		-		60	-	Hz
Clock frequency		1/ T _{Clock}		141		MHz
Vertical Section	Period	T _V	1100	1116	1080+A	T _{Line}
	Active	T _{VD}	1080			
	Blanking	T _{VB}	20	36	A	
Horizontal Section	Period	T _H	2080	2104	1920+B	T _{Clock}
	Active	T _{HD}	1920			
	Blanking	T _{HB}	160	184	B	


Note 1 : The above is as optimized setting

Note 2 : The maximum clock frequency = $(1920+B) \times (1080+A) \times 60 < 149.1 \text{ MHz}$

6.4 Power ON/OFF Sequence


Power on/off sequence is as follows. Interface signals and LED on/off sequence are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off

Display Port panel power sequence:



Display port interface power up/down sequence, normal system operation

Display Port AUX_CH transaction only:



Display port interface power up/down sequence, AUX_CH transaction only



Product Specification

AU OPTRONICS CORPORATION

Display Port panel power sequence timing parameter:

Timing parameter	Description	Reqd. by	Limits			Notes
			Min.	Typ.	Max.	
T1	power rail rise time, 10% to 90%	source	0.5ms		10ms	
T2	delay from LCDVDD to black video generation	sink	0ms		200ms	prevents display noise until valid video data is received from the source
T3	delay from LCDVDD to HPD high	sink	0ms		200ms	sink AUX_CH must be operational upon HPD high.
T4	delay from HPD high to link training initialization	source				allows for source to read link capability and initialize.
T5	link training duration	source				dependant on source link to read training protocol.
T6	link idle	source				Min accounts for required BS-Idle pattern. Max allows for source frame synchronization.
T7	delay from valid video data from source to video on display	sink	0ms		50ms	max allows sink validate video data and timing.
T8	delay from valid video data from source to backlight enable	source				source must assure display video is stable.
T9	delay from backlight disable to end of valid video data	source				source must assure backlight is no longer illuminated.
T10	delay from end of valid video data from source to power off	source	0ms		500ms	
T11	power rail fall time, 90% to 10%	source			10ms	
T12	power off time	source	500ms			


Note1: The sink must include the ability to generate black video autonomously. The sink must automatically enable black video under the following conditions:

- upon LCDVDD power on (within T2 max)-when the "Novideostream_Flag" (VB-ID Bit 3) is received from the source (at the end of T9).
- when no main link data, or invalid video data, is received from the source. Black video must be displayed within 64ms (typ) from the start of either condition. Video data can be deemed invalid based on MSA and timing information, for example.


Note 2: The sink may implement the ability to disable the black video function, as described in Note 1, above, for system development and debugging purpose.

Note 3: The sink must support AUX_CH polling by the source immediately following LCDVDD power on without causing damage to the sink device (the source can re-try if the sink is not ready). The sink must be able to respond to an AUX_CH transaction with the time specified within T3 max.

Display Port panel B/L power sequence timing parameter:



Note : When the adapter is hot plugged, the backlight power supply sequence is shown as below.



	Min (ms)	Max (ms)
T13	0.2	10
T14	0	-
T15	0	-
T16	0	-
T17	0	-
T18	0.2	10
T19	1 [*]	-
T20	1 [*]	-


Seamless change: $T19/T20 = 5 \times T_{PWM}^*$

$*T_{PWM} = 1/PWM \text{ Frequency}$

Note 1 : If T14,T15,T16,T17<10ms , The display garbage may occur. We suggest T14,T15,T16,T17>10ms to avoid the display garbage.

Note 2 : If T13 or T18<0.5ms , the inrush current may cause the damage of fuse. If T13 or T18<0.5ms , the inrush current I^2t is under typical melt of fuse Spec. , there is no mentioned problem.

Touch Panel Power on Sequence



Timing	Description	Min (ms)
T_{RST}	Reset signal delay time from VTSP (TP power)	1
T_{TPEN}	TP enable signal delay time from reset signal	20

7. Panel Reliability Test

7.1 Vibration Test

Test Spec:

- Test method: Non-Operation
- Acceleration: 1.5 G
- Frequency: 10 - 500Hz Random
- Sweep: 30 Minutes each Axis (X, Y, Z)

7.2 Shock Test

Test Spec:

- Test method: Non-Operation
- Acceleration: 220 G , Half sine wave
- Active time: 2 ms
- Pulse: X,Y,Z .one time for each side

7.3 Reliability Test


Items	Required Condition	Note
Temperature Humidity Bias	Ta= 40°C , 90%RH, 300h	
High Temperature Operation	Ta= 50°C , Dry, 300h	
Low Temperature Operation	Ta=0°C , 300h	
High Temperature Storage	Ta= 60°C , 300h	
Low Temperature Storage	Ta= -20°C , 250h	
Thermal Shock Test	Ta=-20°C(30min) ~60°C(30min), 100cycles condition.	
ESD	Contact : ±8 KV Air : ±15 KV	Note 1


Note1: According to EN 61000-4-2 , ESD class B: Some performance degradation allowed. No data lost
 . Self-recoverable. No hardware failures.

Remark: MTBF (Excluding the LED): 30,000 hours with a confidence level 90%

8. Mechanical Characteristics

8.1 Total Solution Outline Dimension





9. Shipping and Package

9.1 Shipping Label Format


XXXXXXXXXXXXXXXXXXXXX H/W:0A F/W: 0A MADE IN CHINA(Z31)

Manufactured MM/WW
Model No: B133HAN06.2
AU Optronics


CN-ONTRKG-DQS00-
XXX-XXX-A00
Made In China
DP/N ONTRKG


c UL US
E204356


Pb


15

RoHS

AU Optronics
MODEL NO : B133HAN06.2
PART NO : 97.13B44.200
CUSTOMER NO :
CARTON NO :

XXXXX-XXXXXXXXXXXXX

QTY : 45



RoHS

Pb


15

MADE IN CHINA

9.2 Carton Package



9.3 Shipping Package of Palletizing Sequence



10. Appendix: EDID Description

Address	FUNCTION	Value	Value	Value	Note
0	Header	00	00000000	0	
1	Header	FF	11111111	255	
2	Header	FF	11111111	255	
3	Header	FF	11111111	255	
4	Header	FF	11111111	255	
5	Header	FF	11111111	255	
6	Header	FF	11111111	255	
7	Header	00	00000000	0	
8	EISA manufacture code = 3 Character ID	06	00000110	6	
9	EISA manufacture code (Compressed ASCII)	AF	10101111	175	
0A	Panel Supplier Reserved – Product Code	2D	00101101	45	
0B	Panel Supplier Reserved – Product Code	62	01100010	98	
0C	LCD module Serial No - Preferred but Optional (“0” if not used)	00	00000000	0	
0D	LCD module Serial No - Preferred but Optional (“0” if not used)	00	00000000	0	
0E	LCD module Serial No - Preferred but Optional (“0” if not used)	00	00000000	0	
0F	LCD module Serial No - Preferred but Optional (“0” if not used)	00	00000000	0	
10	Week of manufacture	31	00110001	49	
11	Year of manufacture	1C	00011100	28	
12	EDID structure version # = 1	01	00000001	1	
13	EDID revision # = 4	04	00000100	4	
14	Video I/P definition	95	10010101	149	
15	Max H image size = ?? cm(Rounded to cm)	1D	00011101	29	
16	Max V image size = ?? cm(Rounded to cm)	11	00010001	17	
17	Display gamma = (gamma ×100)-100 = Example: (2.2×100) – 100 = 120	78	01111000	120	
18	Feature support	02	00000010	2	
19	Red/Green Low bit (RxRy/GxGy)	93	10010011	147	
1A	Blue/White Low bit (BxBY/WxWy)	05	00000101	5	
1B	Red X Rx = 0.???	92	10010010	146	
1C	Red Y Ry = 0.???	58	01011000	88	
1D	Green X Rx = 0.???	59	01011001	89	
1E	Green Y Ry = 0.???	90	10010000	144	
1F	Blue X Rx = 0.???	29	00101001	41	
20	Blue Y Ry = 0.???	1D	00011101	29	
21	White X Rx = 0.???	50	01010000	80	
22	White Y Ry = 0.???	54	01010100	84	
23	Established timings 1 (00h if not used)	00	00000000	0	
24	Established timings 2 (00h if not used)	00	00000000	0	
25	Manufacturer’s timings (00h if not used)	00	00000000	0	
26	Standard timing ID1 (01h if not used)	01	00000001	1	

27	Standard timing ID1 (01h if not used)	01	00000001	1	
28	Standard timing ID2 (01h if not used)	01	00000001	1	
29	Standard timing ID2 (01h if not used)	01	00000001	1	
2A	Standard timing ID3 (01h if not used)	01	00000001	1	
2B	Standard timing ID3 (01h if not used)	01	00000001	1	
2C	Standard timing ID4 (01h if not used)	01	00000001	1	
2D	Standard timing ID4 (01h if not used)	01	00000001	1	
2E	Standard timing ID5 (01h if not used)	01	00000001	1	
2F	Standard timing ID5 (01h if not used)	01	00000001	1	
30	Standard timing ID6 (01h if not used)	01	00000001	1	
31	Standard timing ID6 (01h if not used)	01	00000001	1	
32	Standard timing ID7 (01h if not used)	01	00000001	1	
33	Standard timing ID7 (01h if not used)	01	00000001	1	
34	Standard timing ID8 (01h if not used)	01	00000001	1	
35	Standard timing ID8 (01h if not used)	01	00000001	1	
36	Pixel Clock/10,000 (LSB)	14	00010100	20	
37	Pixel Clock/10,000 (MSB)	37	00110111	55	
38	Horizontal Active = ??? pixels (lower 8 bits)	80	10000000	128	
39	Horizontal Blanking (Thbp) = 320 pixels (lower 8 bits)	B8	10111000	184	
3A	Horizontal Active/Horizontal blanking (Thbp) (upper 4:4 bits)	70	01110000	112	
3B	Vertical Active = ??? lines	38	00111000	56	
3C	Vertical Blanking (Tvbp) = ?? lines (DE Blanking typ. for DE only panels)	24	00100100	36	
3D	Vertical Active : Vertical Blanking (Tvbp) (upper 4:4 bits)	40	01000000	64	
3E	Horizontal Sync, Offset (Thfp) = ?? pixels	10	00010000	16	
3F	Horizontal Sync, Pulse Width = ??? pixels	10	00010000	16	
40	Vertical Sync, Offset (Tvfp) = ? lines Sync Width = ? lines	3E	00111110	62	
41	Horizontal Vertical Sync Offset/Width upper 2 bits	00	00000000	0	
42	Horizontal Image Size = ??? mm	25	00100101	37	
43	Vertical image Size = ??? mm	A5	10100101	165	
44	Horizontal Image Size / Vertical image size	10	00010000	16	
45	Horizontal Border = 0 (Zero for Notebook LCD)	00	00000000	0	
46	Vertical Border = 0 (Zero for Notebook LCD)	00	00000000	0	
47	Bit[7] 0: Non-interlace, 1: Interlace Bit[6:5] 00: Normal display, no stereo, see VESA EDID Spec 1.3 Bit[4:3] 00: Analog composite, 01: Bipolar analog composite, 10: Digital composite, 11: Digital separate Bit[2:1] : The interpretation of bits 2 and 1 is dependent on the decode of bits 4 and 3 - see VESA EDID Spec 1.3 Bit[0]: See VESA EDID Spec 1.3==> fix=1A	1A	00011010	26	
48	Pixel Clock/10,000 (LSB)	10	00010000	16	
49	Pixel Clock/10,000 (MSB)	2C	00101100	44	
4A	Horizontal Active = xxxx pixels (lower 8 bits)	80	10000000	128	
4B	Horizontal Blanking (Thbp) = xxxx pixels (lower 8 bits)	B8	10111000	184	

4C	Horizontal Active/Horizontal blanking (Thbp) (upper4:4 bits)	70	01110000	112	
4D	Vertical Active = xxxx lines	38	00111000	56	
4E	Vertical Blanking (Tvbp) = xxxx lines (DE Blanking typ. for DE only panels)	24	00100100	36	
4F	Vertical Active : Vertical Blanking (Tvbp) (upper4:4 bits)	40	01000000	64	
50	Horizontal Sync, Offset (Thfp) = xxxx pixels	10	00010000	16	
51	Horizontal Sync, Pulse Width = xxxx pixels	10	00010000	16	
52	Vertical Sync, Offset (Tvfp) = xx lines Sync Width = xx lines	3E	00111110	62	
53	Horizontal Vertical Sync Offset/Width upper 2 bits	00	00000000	0	
54	Horizontal Image Size =xxx mm	25	00100101	37	
55	Vertical image Size = xxx mm	A5	10100101	165	
56	Horizontal Image Size / Vertical image size	10	00010000	16	
57	Horizontal Border = 0 (Zero for Notebook LCD)	00	00000000	0	
58	Vertical Border = 0 (Zero for Notebook LCD)	00	00000000	0	
59	Bit[7] 0: Non-interlace, 1: Interlace Bit[6:5] 00: Normal display, no strero, see VESA EDID Spec 1.3 Bit[4:3] 00: Analog composite, 01: Bipolar analog composite, 10: Digital composite, 11: Digital separate Bit[2:1] : The interpretation of bits 2 and 1 is dependent on the decode of bits 4 and 3 - see VESA EDID Spec 1.3 Bit[0]: See VESA EDID Spec 1.3==> fix=1A	1A	00011010	26	
5A	Flag	00	00000000	0	
5B	Flag	00	00000000	0	
5C	Flag	00	00000000	0	
5D	Data Type Tag: Alphanumeric Data String (ASCII) ==> fix=FE	FE	11111110	254	
5E	Flag	00	00000000	0	
5F	Dell P/N 1 st Character	4E	01001110	78	
60	Dell P/N 2 nd Character	54	01010100	84	
61	Dell P/N 3 rd Character	52	01010010	82	
62	Dell P/N 4 th Character	4B	01001011	75	
63	Dell P/N 5 th Character	47	01000111	71	
64	EDID Revision Bit[6:0] See charts below Bit[7] 0: X-rev, 1: A-rev	80	10000000	128	
65	Manufacturer P/N	42	01000010	66	
66	Manufacturer P/N	31	00110001	49	
67	Manufacturer P/N	33	00110011	51	
68	Manufacturer P/N	33	00110011	51	
69	Manufacturer P/N	48	01001000	72	
6A	Manufacturer P/N	41	01000001	65	
6B	Manufacturer P/N (If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h)	4E	01001110	78	
6C	Flag	00	00000000	0	
6D	Flag	00	00000000	0	

6E	Flag	00	00000000	0	
6F	Data Type Tag: Manufacturer Specified Data 00 ==>fix=00	00	00000000	0	
70	Flag	00	00000000	0	
71	Color Management	01	00000001	1	
72	Panel Structure	41	01000001	65	
73	Frame Rate	21	00100001	33	
74	Light Controller Interface and Luminance	96	10010110	150	
75	Outdoor Features	01	00000001	1	
76	Multi-Media Features	11	00010001	17	
77	Multi-Media Features	00	00000000	0	
78	Special Features #1	00	00000000	0	
79	Special Features #2	0A	00001010	10	
7A	Special Features #3	01	00000001	1	
7B	(If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h)	0A	00001010	10	
7C	(If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h)	20	00100000	32	
7D	(If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h)	20	00100000	32	
7E	Extension flag (# of optional 128 EDID extension blocks to follow, Typ = 0)	00	00000000	0	
7F	Checksum (The 1-byte sum of all 128 bytes in this EDID block shall = 0)	07	00000111	7	