



Product Specification

M185XTN01.3

AU OPTRONICS CORPORATION

() Preliminary Specification

(V) Final Specification

Module	18.5" Color TFT-LCD
Model Name	M185XTN01.3

Customer	Date
<hr/>	<hr/>
Approved by	
<hr/>	<hr/>
Note: This Specification is subject to change without notice.	

Approved by	Date
<u>Howard Lee</u>	<u>2012/11/8</u>
Prepared by	
<u>Glenn Chan</u>	<u>2012/6/25</u>
Video Solutions Business Group / AU Optronics corporation	



Contents

1.0 Handling Precautions	5
2.0 General Description	6
2.1 Display Characteristics	6
2.2 Optical Characteristics	7
3.0 Functional Block Diagram	11
4.0 Absolute Maximum Ratings	12
4.1 TFT LCD Module	12
4.2 Backlight Unit	12
4.3 Absolute Ratings of Environment	12
5.0 Electrical characteristics	14
5.1 TFT LCD Module	14
5.1.1 Power Specification	14
5.1.2 Signal Electrical Characteristics	15
5.2 Backlight Unit	17
6.0 Signal Characteristic	18
6.1 Pixel Format Image	18
6.2 The input data format	18
6.3 Signal Description	19
6.4 Timing Characteristics	21
6.5 Timing diagram	22
6.6 Power ON/OFF Sequence	23
7.0 Connector & Pin Assignment	24
7.1 TFT LCD Module	24
7.1.1 Pin Assignment	24
7.2 LED Connector on Backlight Unit	25
7.2.1 LED Pin assignment	25
7.2.2 LED Connector dimension	26
7.2.3 LED Mating housing dimension	26
8.0 Reliability Test	27
9.0 Shipping Label	28
10.0 Mechanical Characteristics	29
11. Packing Specification	32



Record of Revision

Version and Date	Page	Old description	New Description	Remark																																																																																																																																																
0.1 2012/06/25		Preliminary Version																																																																																																																																																		
0.2 2012/10/23	22	Revise 6.4 Timing characteristics <table><tr><th>Signal</th><th>Item</th><th>Symbol</th><th>Min</th><th>Typ</th><th>Max</th><th>Unit</th></tr><tr><td rowspan="3"></td><td>Period</td><td>Tv</td><td>776</td><td>808</td><td>1023</td><td>Th</td></tr><tr><td>Active</td><td>Tdisp(v)</td><td>768</td><td>768</td><td>768</td><td>Th</td></tr><tr><td>Blanking</td><td>Tbk(v)</td><td>8</td><td>40</td><td>255</td><td>Th</td></tr><tr><td rowspan="3">V-section</td><td>Period</td><td>Th</td><td>1416</td><td>1606</td><td>2047</td><td>Tclk</td></tr><tr><td>Active</td><td>Tdisp(h)</td><td>1366</td><td>1366</td><td>1366</td><td>Tclk</td></tr><tr><td>Blanking</td><td>Tbk(h)</td><td>50</td><td>240</td><td>681</td><td>Tclk</td></tr><tr><td rowspan="3">H-section</td><td>Period</td><td>Tclk</td><td>-</td><td>12.8</td><td>-</td><td>ns</td></tr><tr><td>Frequency</td><td>Freq</td><td>55</td><td>78</td><td>90</td><td>MHz</td></tr><tr><td>Clock</td><td>Frame Rate</td><td>F</td><td>50</td><td>60</td><td>75</td><td>Hz</td></tr></table>	Signal	Item	Symbol	Min	Typ	Max	Unit		Period	Tv	776	808	1023	Th	Active	Tdisp(v)	768	768	768	Th	Blanking	Tbk(v)	8	40	255	Th	V-section	Period	Th	1416	1606	2047	Tclk	Active	Tdisp(h)	1366	1366	1366	Tclk	Blanking	Tbk(h)	50	240	681	Tclk	H-section	Period	Tclk	-	12.8	-	ns	Frequency	Freq	55	78	90	MHz	Clock	Frame Rate	F	50	60	75	Hz	<table><tr><th>Signal</th><th>Item</th><th>Symbol</th><th>Min</th><th>Typ</th><th>Max</th><th>Unit</th></tr><tr><td rowspan="3">Vertical Section</td><td>Period</td><td>Tv</td><td>788</td><td>808</td><td>1313</td><td>Th</td></tr><tr><td>Active</td><td>Tdisp(v)</td><td>768</td><td>768</td><td>768</td><td>Th</td></tr><tr><td>Blanking</td><td>Tbp(v)+Tfp(v)+PFWvs</td><td>20</td><td>40</td><td>545</td><td>Th</td></tr><tr><td rowspan="3">Horizontal Section</td><td>Period</td><td>Th</td><td>1432</td><td>1606</td><td>2047</td><td>Tclk</td></tr><tr><td>Active</td><td>Tdisp(h)</td><td>1366</td><td>1366</td><td>1366</td><td>Tclk</td></tr><tr><td>Blanking</td><td>Tbp(h)+Tfp(h)+PFWhs</td><td>66</td><td>240</td><td>681</td><td>Tclk</td></tr><tr><td rowspan="2">Clock</td><td>Period</td><td>Tclk</td><td>10.64</td><td>12.8</td><td>17.72</td><td>ns</td></tr><tr><td>Frequency</td><td>Freq</td><td>56.42</td><td>77.86</td><td>94</td><td>MHz</td></tr><tr><td>Frame rate</td><td>Frame rate</td><td>VFreq</td><td>50</td><td>60</td><td>75</td><td>Hz</td></tr><tr><td>Hyync</td><td>Hyync</td><td>HFreq</td><td>39.7</td><td>48.5</td><td>64.8</td><td>KHz</td></tr><tr><td>Frequency</td><td>Frequency</td><td></td><td></td><td></td><td></td><td></td></tr></table>	Signal	Item	Symbol	Min	Typ	Max	Unit	Vertical Section	Period	Tv	788	808	1313	Th	Active	Tdisp(v)	768	768	768	Th	Blanking	Tbp(v)+Tfp(v)+PFWvs	20	40	545	Th	Horizontal Section	Period	Th	1432	1606	2047	Tclk	Active	Tdisp(h)	1366	1366	1366	Tclk	Blanking	Tbp(h)+Tfp(h)+PFWhs	66	240	681	Tclk	Clock	Period	Tclk	10.64	12.8	17.72	ns	Frequency	Freq	56.42	77.86	94	MHz	Frame rate	Frame rate	VFreq	50	60	75	Hz	Hyync	Hyync	HFreq	39.7	48.5	64.8	KHz	Frequency	Frequency						
Signal	Item	Symbol	Min	Typ	Max	Unit																																																																																																																																														
	Period	Tv	776	808	1023	Th																																																																																																																																														
	Active	Tdisp(v)	768	768	768	Th																																																																																																																																														
	Blanking	Tbk(v)	8	40	255	Th																																																																																																																																														
V-section	Period	Th	1416	1606	2047	Tclk																																																																																																																																														
	Active	Tdisp(h)	1366	1366	1366	Tclk																																																																																																																																														
	Blanking	Tbk(h)	50	240	681	Tclk																																																																																																																																														
H-section	Period	Tclk	-	12.8	-	ns																																																																																																																																														
	Frequency	Freq	55	78	90	MHz																																																																																																																																														
	Clock	Frame Rate	F	50	60	75	Hz																																																																																																																																													
Signal	Item	Symbol	Min	Typ	Max	Unit																																																																																																																																														
Vertical Section	Period	Tv	788	808	1313	Th																																																																																																																																														
	Active	Tdisp(v)	768	768	768	Th																																																																																																																																														
	Blanking	Tbp(v)+Tfp(v)+PFWvs	20	40	545	Th																																																																																																																																														
Horizontal Section	Period	Th	1432	1606	2047	Tclk																																																																																																																																														
	Active	Tdisp(h)	1366	1366	1366	Tclk																																																																																																																																														
	Blanking	Tbp(h)+Tfp(h)+PFWhs	66	240	681	Tclk																																																																																																																																														
Clock	Period	Tclk	10.64	12.8	17.72	ns																																																																																																																																														
	Frequency	Freq	56.42	77.86	94	MHz																																																																																																																																														
Frame rate	Frame rate	VFreq	50	60	75	Hz																																																																																																																																														
Hyync	Hyync	HFreq	39.7	48.5	64.8	KHz																																																																																																																																														
Frequency	Frequency																																																																																																																																																			
	14	Revise 5.1.1 IRush Max.: TBD	5.1.1 IRush Max.: 2A																																																																																																																																																	
	25	Revise 7.2 LED Connector on Backlight Unit Part number: 3707K-Q06N-01R	New part number: 3707K-S06N-21R																																																																																																																																																	
	6	Remove “TCO Compliance” <table><tr><td>TCO 6.0 Compliance</td><td>No</td></tr></table>	TCO 6.0 Compliance	No																																																																																																																																																
TCO 6.0 Compliance	No																																																																																																																																																			
	7	Revise color coordinates <table><tr><td rowspan="8">Color / Chromaticity Coordinates (CIE)</td><td>Red x</td><td>TBD</td><td>TBD</td><td>TBD</td><td rowspan="8">5</td></tr><tr><td>Red y</td><td>TBD</td><td>TBD</td><td>TBD</td></tr><tr><td>Green x</td><td>TBD</td><td>TBD</td><td>TBD</td></tr><tr><td>Green y</td><td>TBD</td><td>TBD</td><td>TBD</td></tr><tr><td>Blue x</td><td>TBD</td><td>TBD</td><td>TBD</td></tr><tr><td>Blue y</td><td>TBD</td><td>TBD</td><td>TBD</td></tr><tr><td>White x</td><td>0.283</td><td>0.313</td><td>0.343</td></tr><tr><td>White y</td><td>0.289</td><td>0.329</td><td>0.359</td></tr><tr><td colspan="2">Color Coordinates (CIE) White</td><td>White x</td><td>0.283</td><td>0.313</td><td>0.343</td><td></td></tr><tr><td colspan="2"></td><td>White y</td><td>0.289</td><td>0.329</td><td>0.359</td><td></td></tr></table>	Color / Chromaticity Coordinates (CIE)	Red x	TBD	TBD	TBD	5	Red y	TBD	TBD	TBD	Green x	TBD	TBD	TBD	Green y	TBD	TBD	TBD	Blue x	TBD	TBD	TBD	Blue y	TBD	TBD	TBD	White x	0.283	0.313	0.343	White y	0.289	0.329	0.359	Color Coordinates (CIE) White		White x	0.283	0.313	0.343				White y	0.289	0.329	0.359		<table><tr><td rowspan="8">Color / Chromaticity Coordinates (CIE)</td><td>Red x</td><td>0.616</td><td>0.646</td><td>0.676</td><td rowspan="8">5</td></tr><tr><td>Red y</td><td>0.303</td><td>0.333</td><td>0.363</td></tr><tr><td>Green x</td><td>0.287</td><td>0.317</td><td>0.347</td></tr><tr><td>Green y</td><td>0.595</td><td>0.625</td><td>0.655</td></tr><tr><td>Blue x</td><td>0.124</td><td>0.154</td><td>0.184</td></tr><tr><td>Blue y</td><td>0.031</td><td>0.061</td><td>0.091</td></tr><tr><td>White x</td><td>0.283</td><td>0.313</td><td>0.343</td></tr><tr><td>White y</td><td>0.289</td><td>0.329</td><td>0.359</td></tr><tr><td colspan="2">Color Coordinates (CIE) White</td><td>White x</td><td>0.283</td><td>0.313</td><td>0.343</td><td></td></tr><tr><td colspan="2"></td><td>White y</td><td>0.289</td><td>0.329</td><td>0.359</td><td></td></tr></table>	Color / Chromaticity Coordinates (CIE)	Red x	0.616	0.646	0.676	5	Red y	0.303	0.333	0.363	Green x	0.287	0.317	0.347	Green y	0.595	0.625	0.655	Blue x	0.124	0.154	0.184	Blue y	0.031	0.061	0.091	White x	0.283	0.313	0.343	White y	0.289	0.329	0.359	Color Coordinates (CIE) White		White x	0.283	0.313	0.343				White y	0.289	0.329	0.359																																																		
Color / Chromaticity Coordinates (CIE)	Red x	TBD		TBD	TBD	5																																																																																																																																														
	Red y	TBD		TBD	TBD																																																																																																																																															
	Green x	TBD		TBD	TBD																																																																																																																																															
	Green y	TBD		TBD	TBD																																																																																																																																															
	Blue x	TBD		TBD	TBD																																																																																																																																															
	Blue y	TBD		TBD	TBD																																																																																																																																															
	White x	0.283		0.313	0.343																																																																																																																																															
	White y	0.289	0.329	0.359																																																																																																																																																
Color Coordinates (CIE) White		White x	0.283	0.313	0.343																																																																																																																																															
		White y	0.289	0.329	0.359																																																																																																																																															
Color / Chromaticity Coordinates (CIE)	Red x	0.616	0.646	0.676	5																																																																																																																																															
	Red y	0.303	0.333	0.363																																																																																																																																																
	Green x	0.287	0.317	0.347																																																																																																																																																
	Green y	0.595	0.625	0.655																																																																																																																																																
	Blue x	0.124	0.154	0.184																																																																																																																																																
	Blue y	0.031	0.061	0.091																																																																																																																																																
	White x	0.283	0.313	0.343																																																																																																																																																
	White y	0.289	0.329	0.359																																																																																																																																																
Color Coordinates (CIE) White		White x	0.283	0.313	0.343																																																																																																																																															
		White y	0.289	0.329	0.359																																																																																																																																															
	29	Revise max outline thickness Original: 9.8mm	New: 9.9mm																																																																																																																																																	
	12	Revise: LED forward Voltage variation (per string variation) 3.4V	1.4V																																																																																																																																																	
	17	Revise LED operation current min. <table><tr><th>Symbol</th><th>Description</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th><th>Note</th></tr><tr><td>IRLED1</td><td rowspan="4">LED Operation Current</td><td rowspan="4">67</td><td rowspan="4">70</td><td rowspan="4">73</td><td rowspan="4">[mA]</td><td rowspan="4">Note 1</td></tr><tr><td>IRLED2</td></tr><tr><td>IRLED3</td></tr><tr><td>IRLED4</td></tr></table>	Symbol	Description	Min.	Typ.	Max.	Unit	Note	IRLED1	LED Operation Current	67	70	73	[mA]	Note 1	IRLED2	IRLED3	IRLED4	<table><tr><th>Symbol</th><th>Description</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th><th>Note</th></tr><tr><td>IRLED1</td><td rowspan="4">LED Operation Current</td><td rowspan="4">-</td><td rowspan="4">70</td><td rowspan="4">73</td><td rowspan="4">[mA]</td><td rowspan="4">Note 1</td></tr><tr><td>IRLED2</td></tr><tr><td>IRLED3</td></tr><tr><td>IRLED4</td></tr></table>	Symbol	Description	Min.	Typ.	Max.	Unit	Note	IRLED1	LED Operation Current	-	70	73	[mA]	Note 1	IRLED2	IRLED3	IRLED4																																																																																																															
Symbol	Description	Min.	Typ.	Max.	Unit	Note																																																																																																																																														
IRLED1	LED Operation Current	67	70	73	[mA]	Note 1																																																																																																																																														
IRLED2																																																																																																																																																				
IRLED3																																																																																																																																																				
IRLED4																																																																																																																																																				
Symbol	Description	Min.	Typ.	Max.	Unit	Note																																																																																																																																														
IRLED1	LED Operation Current	-	70	73	[mA]	Note 1																																																																																																																																														
IRLED2																																																																																																																																																				
IRLED3																																																																																																																																																				
IRLED4																																																																																																																																																				
	11	Revise LVDS connector supplier I/F PCB Interface: MSCKT2407P30HB (STM) / AL230F-A0G1D-P (P-TWO) Mating Type: FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)	I/F PCB Interface: MSCKT2407P30HB (STM) / FI-XPB30SRLAHF11 (JAE) Mating Type: FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)																																																																																																																																																	
	24	<table><tr><th>Connector Name / Designation</th><th>Interface Connector / Interface card</th></tr><tr><td>Manufacturer</td><td>STM or P-TWO</td></tr><tr><td>Type Part Number</td><td>MSCKT2407P30HB (STM) / AL230F-A0G1D-P (P-TWO)</td></tr><tr><td>Mating Housing Part Number</td><td>FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)</td></tr></table>	Connector Name / Designation	Interface Connector / Interface card	Manufacturer	STM or P-TWO	Type Part Number	MSCKT2407P30HB (STM) / AL230F-A0G1D-P (P-TWO)	Mating Housing Part Number	FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)	<table><tr><th>Connector Name / Designation</th><th>Interface Connector / Interface card</th></tr><tr><td>Manufacturer</td><td>STM or JAE</td></tr><tr><td>Type Part Number</td><td>MSCKT2407P30HB (STM) / FI-XPB30SRLAHF11 (JAE)</td></tr><tr><td>Mating Housing Part Number</td><td>FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)</td></tr></table>	Connector Name / Designation	Interface Connector / Interface card	Manufacturer	STM or JAE	Type Part Number	MSCKT2407P30HB (STM) / FI-XPB30SRLAHF11 (JAE)	Mating Housing Part Number	FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)																																																																																																																																	
Connector Name / Designation	Interface Connector / Interface card																																																																																																																																																			
Manufacturer	STM or P-TWO																																																																																																																																																			
Type Part Number	MSCKT2407P30HB (STM) / AL230F-A0G1D-P (P-TWO)																																																																																																																																																			
Mating Housing Part Number	FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)																																																																																																																																																			
Connector Name / Designation	Interface Connector / Interface card																																																																																																																																																			
Manufacturer	STM or JAE																																																																																																																																																			
Type Part Number	MSCKT2407P30HB (STM) / FI-XPB30SRLAHF11 (JAE)																																																																																																																																																			
Mating Housing Part Number	FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)																																																																																																																																																			
1.0 Final version		Version code 0.2	Version code 1.0																																																																																																																																																	
1.1	7	Max. Response time not specified.	<table><tr><td rowspan="3">Response Time</td><td rowspan="3">[msec]</td><td>Raising Time (Tr)</td><td>-</td><td>3.6</td><td>5.5</td><td rowspan="3">4</td></tr><tr><td>Falling Time (Trf)</td><td>-</td><td>1.4</td><td>2.5</td></tr><tr><td>Raising + Falling</td><td>-</td><td>5</td><td>8</td></tr></table>	Response Time	[msec]	Raising Time (Tr)	-	3.6	5.5	4	Falling Time (Trf)	-	1.4	2.5	Raising + Falling	-	5	8																																																																																																																																		
Response Time	[msec]	Raising Time (Tr)	-			3.6	5.5	4																																																																																																																																												
		Falling Time (Trf)	-			1.4	2.5																																																																																																																																													
		Raising + Falling	-	5	8																																																																																																																																															

2012/12/25	11	Correct function block diagram input signal annotation 																																																						
	11	Remove I/F PCB Interface in this page																																																						
	20	Revise LVDS pin 1 annotation “RX0IN0-“	“NC”																																																					
	21	Revise annotation of “Symbol” of 6.4 Timing Characteristics <table border="1" data-bbox="365 656 815 732"><thead><tr><th></th><th>Blanking</th><th>Tbp(v)+Ttp(v)+PWvs</th><th>20</th><th>40</th><th>545</th><th>Th</th></tr></thead><tbody><tr><td rowspan="3">Horizontal Section</td><td>Period</td><td>Th</td><td>1432</td><td>1606</td><td>2047</td><td>Tclk</td></tr><tr><td>Active</td><td>Tdisp(h)</td><td>1366</td><td>1366</td><td>1366</td><td>Tclk</td></tr><tr><td>Blanking</td><td>Tbp(h)+Ttp(h)+PWvs</td><td>66</td><td>240</td><td>681</td><td>Tclk</td></tr></tbody></table>		Blanking	Tbp(v)+Ttp(v)+PWvs	20	40	545	Th	Horizontal Section	Period	Th	1432	1606	2047	Tclk	Active	Tdisp(h)	1366	1366	1366	Tclk	Blanking	Tbp(h)+Ttp(h)+PWvs	66	240	681	Tclk	<table border="1" data-bbox="829 591 1302 665"><thead><tr><th></th><th>Blanking</th><th>Tbp(v)+Ttp(v)+PWvs</th><th>20</th><th>40</th><th>545</th><th>Th</th></tr></thead><tbody><tr><td rowspan="3">Horizontal Section</td><td>Period</td><td>Th</td><td>1432</td><td>1606</td><td>2047</td><td>Tclk</td></tr><tr><td>Active</td><td>Tdisp(h)</td><td>1366</td><td>1366</td><td>1366</td><td>Tclk</td></tr><tr><td>Blanking</td><td>Tbp(h)+Ttp(h)+PWvs</td><td>66</td><td>240</td><td>681</td><td>Tclk</td></tr></tbody></table>		Blanking	Tbp(v)+Ttp(v)+PWvs	20	40	545	Th	Horizontal Section	Period	Th	1432	1606	2047	Tclk	Active	Tdisp(h)	1366	1366	1366	Tclk	Blanking	Tbp(h)+Ttp(h)+PWvs	66	240	681	Tclk	
	Blanking	Tbp(v)+Ttp(v)+PWvs	20	40	545	Th																																																		
Horizontal Section	Period	Th	1432	1606	2047	Tclk																																																		
	Active	Tdisp(h)	1366	1366	1366	Tclk																																																		
	Blanking	Tbp(h)+Ttp(h)+PWvs	66	240	681	Tclk																																																		
	Blanking	Tbp(v)+Ttp(v)+PWvs	20	40	545	Th																																																		
Horizontal Section	Period	Th	1432	1606	2047	Tclk																																																		
	Active	Tdisp(h)	1366	1366	1366	Tclk																																																		
	Blanking	Tbp(h)+Ttp(h)+PWvs	66	240	681	Tclk																																																		
	23	Revise Power ON/OFF sequence T6 <table border="1" data-bbox="365 770 815 808"><thead><tr><th></th><th>T6</th><th>5</th><th>-</th><th>100</th><th>[ms]</th><th>Note 1, 2</th></tr></thead><tbody><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>		T6	5	-	100	[ms]	Note 1, 2								<table border="1" data-bbox="829 732 1302 770"><thead><tr><th></th><th>T6</th><th>5</th><th>-</th><th>150</th><th>[ms]</th><th>Note 1, 2</th></tr></thead><tbody><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>		T6	5	-	150	[ms]	Note 1, 2																																
	T6	5	-	100	[ms]	Note 1, 2																																																		
	T6	5	-	150	[ms]	Note 1, 2																																																		
2013/1/17	17	Revise LED current <table border="1" data-bbox="365 837 815 931"><thead><tr><th>Symbol</th><th>Description</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th><th>Note</th></tr></thead><tbody><tr><td>IRLED1</td><td rowspan="4">LED Operation Current</td><td rowspan="4">-</td><td rowspan="4">70</td><td>73</td><td>[mA]</td><td rowspan="4">Note 1</td></tr><tr><td>IRLED2</td></tr><tr><td>IRLED3</td></tr><tr><td>IRLED4</td></tr></tbody></table>	Symbol	Description	Min.	Typ.	Max.	Unit	Note	IRLED1	LED Operation Current	-	70	73	[mA]	Note 1	IRLED2	IRLED3	IRLED4	5.2 Backlight Unit Parameter guideline for LED driving is under stable conditions at 25°C (Room Temperature): <table border="1" data-bbox="829 846 1302 940"><thead><tr><th>Symbol</th><th>Description</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th><th>Note</th></tr></thead><tbody><tr><td>IRLED1</td><td rowspan="4">LED Operation Current</td><td rowspan="4">-</td><td rowspan="4">70</td><td>77</td><td>[mA]</td><td rowspan="4">Note 1</td></tr><tr><td>IRLED2</td></tr><tr><td>IRLED3</td></tr><tr><td>IRLED4</td></tr></tbody></table>	Symbol	Description	Min.	Typ.	Max.	Unit	Note	IRLED1	LED Operation Current	-	70	77	[mA]	Note 1	IRLED2	IRLED3	IRLED4																			
Symbol	Description	Min.	Typ.	Max.	Unit	Note																																																		
IRLED1	LED Operation Current	-	70	73	[mA]	Note 1																																																		
IRLED2																																																								
IRLED3																																																								
IRLED4																																																								
Symbol	Description	Min.	Typ.	Max.	Unit	Note																																																		
IRLED1	LED Operation Current	-	70	77	[mA]	Note 1																																																		
IRLED2																																																								
IRLED3																																																								
IRLED4																																																								
1.2 2013/03/14	17	Revise BLU power Max <table border="1" data-bbox="365 969 815 1046"><thead><tr><th></th><th>VLED</th><th>Light Bar Operation Voltage</th><th>21</th><th>23.1</th><th>25.2</th><th>[Volt]</th><th>Note 2</th></tr></thead><tbody><tr><td>PBLU</td><td>BLU Power Consumption</td><td>5.8</td><td>6.5</td><td>7.4</td><td>[Watt]</td><td>Note 3</td></tr></tbody></table>		VLED	Light Bar Operation Voltage	21	23.1	25.2	[Volt]	Note 2	PBLU	BLU Power Consumption	5.8	6.5	7.4	[Watt]	Note 3	<table border="1" data-bbox="829 940 1302 1028"><thead><tr><th></th><th>VLED</th><th>Light Bar Operation Voltage</th><th>18.6</th><th>23.1</th><th>25.2</th><th>[Volt]</th><th>Note 2</th></tr></thead><tbody><tr><td>PBLU</td><td>BLU Power Consumption</td><td>5.8</td><td>6.5</td><th>7.8</th><td>[Watt]</td><th>Note 3</th></tr></tbody></table>		VLED	Light Bar Operation Voltage	18.6	23.1	25.2	[Volt]	Note 2	PBLU	BLU Power Consumption	5.8	6.5	7.8	[Watt]	Note 3																							
	VLED	Light Bar Operation Voltage	21	23.1	25.2	[Volt]	Note 2																																																	
PBLU	BLU Power Consumption	5.8	6.5	7.4	[Watt]	Note 3																																																		
	VLED	Light Bar Operation Voltage	18.6	23.1	25.2	[Volt]	Note 2																																																	
PBLU	BLU Power Consumption	5.8	6.5	7.8	[Watt]	Note 3																																																		
	24	Revise LVDS connector <table border="1" data-bbox="365 1084 815 1207"><thead><tr><th>Connector Name / Designation</th><th>Interface Connector / Interface card</th></tr></thead><tbody><tr><td>Manufacturer</td><td>STM or JAE</td></tr><tr><td>Type Part Number</td><td>MSCKT2407P30HB (STM) FLXPB30SRJAHF11 (JAE)</td></tr><tr><td>Mating Housing Part Number</td><td>FLX30HL(JAE) (Locked Type) FLX30H (JAE)(Unlocked Type)</td></tr></tbody></table>	Connector Name / Designation	Interface Connector / Interface card	Manufacturer	STM or JAE	Type Part Number	MSCKT2407P30HB (STM) FLXPB30SRJAHF11 (JAE)	Mating Housing Part Number	FLX30HL(JAE) (Locked Type) FLX30H (JAE)(Unlocked Type)	<table border="1" data-bbox="829 1055 1302 1189"><thead><tr><th>Connector Name / Designation</th><th>Interface Connector / Interface card</th></tr></thead><tbody><tr><td>Manufacturer</td><td>STM or P-TWO</td></tr><tr><td>Type Part Number</td><td>MSCKT2407P30HB (STM) ZAL230F-A0G1C-P (P-TWO)</td></tr><tr><td>Mating Housing Part Number</td><td>FLX30HL(JAE) (Locked Type) FLX30H (JAE)(Unlocked Type)</td></tr></tbody></table>	Connector Name / Designation	Interface Connector / Interface card	Manufacturer	STM or P-TWO	Type Part Number	MSCKT2407P30HB (STM) ZAL230F-A0G1C-P (P-TWO)	Mating Housing Part Number	FLX30HL(JAE) (Locked Type) FLX30H (JAE)(Unlocked Type)																																					
Connector Name / Designation	Interface Connector / Interface card																																																							
Manufacturer	STM or JAE																																																							
Type Part Number	MSCKT2407P30HB (STM) FLXPB30SRJAHF11 (JAE)																																																							
Mating Housing Part Number	FLX30HL(JAE) (Locked Type) FLX30H (JAE)(Unlocked Type)																																																							
Connector Name / Designation	Interface Connector / Interface card																																																							
Manufacturer	STM or P-TWO																																																							
Type Part Number	MSCKT2407P30HB (STM) ZAL230F-A0G1C-P (P-TWO)																																																							
Mating Housing Part Number	FLX30HL(JAE) (Locked Type) FLX30H (JAE)(Unlocked Type)																																																							

1.0 Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open or modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) In case if a Module has to be put back into the packing container slot after once it was taken out from the container, do not press the center of the LED lightbar edge. Instead, press at the far ends of the LED light bar edge softly. Otherwise the TFT Module may be damaged.
- 10) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) After installation of the TFT Module into an enclosure, do not twist nor bend the TFT Module even momentarily. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 12) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 13) Please avoid touching COF contact while handling or fitting the TFT module into your system.
- 14) When storing modules as spares for a long time, the following precaution is necessary:
Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.

2.0 General Description

This specification applies to the 18.5 inch-wide Color a-Si TFT-LCD Module M185XTN01. The display supports the WXGA - 1366(H) x 768(V) screen format and 16.7M colors (RGB 6-bits + Hi-FRC data). All input signals are 1-channel LVDS interface and this module doesn't contain an inverter board for backlight.

2.1 Display Characteristics

The following items are characteristics summary on the table under 25°C condition:

ITEMS	Unit	SPECIFICATIONS
Screen Diagonal	[mm]	470.1(18.51")
Active Area	[mm]	409.8 (H) x 230.4 (V)
Pixels H x V		1366(x3) x 768
Pixel Pitch	[um]	300 (per one triad) x 300
Pixel Arrangement		R.G.B. Vertical Stripe
Display Mode		TN Mode, Normally White
White Luminance (Center)	[cd/m ²]	200 cd/m ² (Typ.)
Contrast Ratio		700 (Typ.)
Optical Response Time	[msec]	5ms (Typ., on/off)
Nominal Input Voltage VDD	[Volt]	+5.0 V (Typ)
Power Consumption (VDD line + LED line)	[Watt]	VDD line: PDD (typ)= 1.75W, All black pattern at 60Hz LED line : PBLU (typ) = 6.5 W Total : 8.25 W
Weight	[Grams]	1290 (Typ)
Physical Size	[mm]	430.4 (W) x 254.6 (H) Typ. x 9.9 (D) Typ
Interface		One channel LVDS
Support Color		16.7M colors (RGB 6-bit + Hi_FRC)
Surface Treatment		Anti-Glare, 3H
Temperature Range		
Operating	[°C]	0 to +50
Storage (Shipping)	[°C]	-20 to +60


2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25°C:

Item	Unit	Conditions	Min.	Typ.	Max.	Note
Viewing Angle	[degree]	Horizontal (Right) CR = 10 (Left)	40 40	45 45	- -	2
		Vertical (Up) CR = 10 (Down)	15 40	20 45	- -	
Contrast ratio		Normal Direction	420	700	-	3
Response Time	[msec]	Raising Time (T_{rR})	-	3.6	5.5	4
		Falling Time (T_{rF})	-	1.4	2.5	
		Raising + Falling	-	5	8	
Color / Chromaticity Coordinates (CIE)		Red x	0.616	0.646	0.676	5
		Red y	0.303	0.333	0.363	
		Green x	0.287	0.317	0.347	
		Green y	0.595	0.625	0.655	
		Blue x	0.124	0.154	0.184	
		Blue y	0.031	0.061	0.091	
Color Coordinates (CIE) White		White x	0.283	0.313	0.343	
		White y	0.299	0.329	0.359	
Central Luminance	[cd/m ²]		160	200	-	6
Luminance Uniformity	[%]		75	80	-	7
Crosstalk (in 60Hz)	[%]				1.5	8
Flicker	dB				-20	9


Note 1: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring (at surface 35°C). In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room.



Note 2: Definition of viewing angle measured by ELDIM (EZContrast 88)


Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° (θ) horizontal left and right and 90° (ϕ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



Note 3: Contrast ratio is measured by TOPCON SR-3

Note 4: Definition of Response time measured by Westar TRD-100A

The output signals of photo detector are measured when the input signals are changed from “Full Black” to “Full White” (rising time, T_{rR}), and from “Full White” to “Full Black” (falling time, T_{rF}), respectively. The response time is interval between the 10% and 90% (1 frame at 60 Hz) of amplitudes.




$T_{rR} + T_{rF} = 5$ msec (typ.).

Note 5: Color chromaticity and coordinates (CIE) is measured by TOPCON SR-3

Note 6: Central luminance is measured by TOPCON SR-3

Note 7: Luminance uniformity of these 9 points is defined as below and measured by TOPCON SR-3



$$\text{Uniformity} = \frac{\text{Minimum Luminance in 9 points (1 - 9)}}{\text{Maximum Luminance in 9 Points (1 - 9)}}$$


Note 8: Crosstalk is defined as below and measured by TOPCON SR-3

$$CT = | YB - YA | / YA \times 100 (\%)$$


Where

YA = Luminance of measured location without gray level 0 pattern (cd/m²)


YB = Luminance of measured location with gray level 0 pattern (cd/m²)



Note 9: Test Pattern: Subchecker Pattern measured by TOPCON SR-3




Method: Record dBV & DC value with TRD-100



3.0 Functional Block Diagram

The following diagram shows the functional block of the 18.5 inch Color TFT-LCD Module:



4.0 Absolute Maximum Ratings

Absolute maximum ratings of the module are as following:

4.1 TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	VDD	-0.3	+6.0	[Volt]	Note 1,2

4.2 Backlight Unit

Item	Symbol	Min	Max	Unit	Conditions
LED Forward Current	IRLED1	0	90	[mA]	Note 1,2,5 100% duty
	IRLED2				
	IRLED3				
	IRLED4				
LED Pulse Forward Current	IPLD1	-	150	[mA]	Note 1,2,5 10% duty @100Hz
	IPLD2				
	IPLD3				
	IPLD4				
LED forward Voltage variation (per string variation)	ΔV_f	-	1.4	[Volt]	Note 1,2

4.3 Absolute Ratings of Environment

Item	Symbol	Min.	Max.	Unit	Conditions
Operating Temperature	TOP	0	+50	[°C]	Note 3
Glass surface temperature (operation)	TGS	0	+65	[°C]	Note 3, Note 4
Operation Humidity	HOP	5	90	[%RH]	Note 3
Storage Temperature	TST	-20	+60	[°C]	
Storage Humidity	HST	5	90	[%RH]	

Note 1: With in Ta (25°C)


Note 2: Permanent damage to the device may occur if exceeding maximum values

Note 3: Temperature and relative humidity range are shown as the below figure.

1. 90% RH Max (Ta ≤39°C)
2. Max wet-bulb temperature at 39°C or less. (Ta ≤39°C)
3. No condensation

Note 4: Function Judged only


Note 5: IRLED1,2,3,4 and IPLD1,2,3,4 define as per strings LED current.



Operating Range



Storage Range



5.0 Electrical characteristics

5.1 TFT LCD Module



5.1.1 Power Specification

Input power specifications are as following:

Symbol	Parameter	Min	Typ	Max	Unit	Conditions
VDD	Logic/LCD Drive Voltage	4.5	5.0	5.5	[Volt]	+/-10%
IDD	Input Current	-	0.35	0.42	[A]	VDD= 5.0V, All Black Pattern At 60Hz,
		-	0.42	0.5		VDD= 5.0V, All Black Pattern At 75Hz
PDD	VDD Power	-	1.75	2.1	[Watt]	VDD= 5.0V, All Black Pattern At 60Hz
		-	2.1	2.5		VDD= 5.0V, All Black Pattern At 75Hz
IRush	Inrush Current	-	-	2	[A]	Note 1
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	350	[mV] p-p	VDD= 5.0V, All Black Pattern At 75Hz

Note 1: Measurement conditions:

The duration of rising time of power input is 470us.




5.1.2 Signal Electrical Characteristics

Input signals shall be low or Hi-Z state when VDD is off. Please refer to specifications of SN75LVDS82DGG (Texas Instruments) in detail.

1. DC Characteristics of each signal are as following:


Symbol	Parameter	Min	Typ	Max	Units	Condition
V _{TH}	Differential Input High Threshold	-	-	+100	[mV]	V _{CM} = 1.2V Note 1
V _{TL}	Differential Input Low Threshold	-100	-	-	[mV]	V _{CM} = 1.2V Note 1
V _{ID}	Input Differential Voltage	100	-	600	[mV]	Note 1
V _{CM}	Differential Input Common Mode Voltage	+1.0	+1.2	+1.5	[V]	V _{TH} -V _{TL} = 200mV (max) Note 1

Note 1: LVDS Signal Waveform



2. AC Characteristics

Description	Symbol	Min	Max	Unit	Note
Maximum deviation of input clock frequency during SSC	F_{DEV}	-	± 3	%	
Maximum modulation frequency of input clock during SSC	F_{MOD}	-	200	KHz	



5.2 Backlight Unit

Parameter guideline for LED driving is under stable conditions at 25°C (Room Temperature):

Symbol	Description	Min.	Typ.	Max.	Unit	Note
IRLED1	LED Operation Current	-	70	77	[mA]	Note 1
IRLED2						
IRLED3						
IRLED4						
VLED	Light Bar Operation Voltage	19.6	23.1	25.2	[Volt]	Note 2
PBLU	BLU Power Consumption	--	6.5	7.8	[Watt]	Note 3
LTLED	LED Life Time (Typical)	30,000	-	-	[Hour]	Note 4

Each module consists of 28 pcs LED (4 strings x 7 pcs / string)

Note 1 : The specified current is 100% duty of LED chip input current, IRLED1,2,3,4 define as per strings LED current.

Note 2 : The value showed in the table is one light bar's operation voltage.


Note 3 : $PBLU = VLED * (IRLED1 + IRLED2 + IRLED3 + IRLED4)$

Note 4: Definition of life time: Brightness becomes to 50% of its original value. The minimum life time of LED unit is on the condition of IRLED = 70mA and 25±2°C (Room Temperature).


6.0 Signal Characteristic

6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.



6.2 The input data format




Note1: Normally, DE, VS, HS on EVEN channel are not used.

Note2: 8-bits signal input.

6.3 Signal Description

PIN #	SIGNAL NAME	DESCRIPTION
1	NC	No contact (For AUO internal use)
2	NC	No contact (For AUO internal use)
3	NC	No contact (For AUO internal use)
4	GND	Power Ground
5	RXIN0-	Negative LVDS differential data input (0)
6	RXIN0+	Positive LVDS differential data input (0)
7	GND	Power Ground
8	RXIN1-	Negative LVDS differential data input (1)
9	RXIN1+	Positive LVDS differential data input (1)
10	GND	Power Ground
11	RXIN2-	Negative LVDS differential data input (2)
12	RXIN2+	Positive LVDS differential data input (2)
13	GND	Power Ground
14	RXCLKIN-	Negative LVDS differential clock input (clock)
15	RXCLKIN+	Positive LVDS differential data input (clock)
16	GND	Power Ground
17	RXIN3-	Negative LVDS differential data input (3)
18	RXIN3+	Positive LVDS differential data input (3)
19	GND	Power Ground
20	NC	No contact (For AUO internal use)
21	NC	No contact (For AUO internal use)
22	NC	No contact (For AUO internal use)
23	GND	Power Ground
24	GND	Power Ground
25	GND	Power Ground
26	VDD	+5V power supply
27	VDD	+5V power supply
28	VDD	+5V power supply
29	VDD	+5V power supply
30	VDD	+5V power supply




6.4 Timing Characteristics

Basically, interface timing described here is not actual input timing of LCD module but close to output timing of SN75LVDS82DGG (Texas Instruments) or equivalent.

Signal	Item	Symbol	Min	Typ	Max	Unit
Vertical Section	Period	T_v	788	808	1313	Th
	Active	$T_{disp(v)}$	768	768	768	Th
	Blanking	$T_{blk(v)}+T_{blk(v)}+PW_{vs}$	20	40	545	Th
Horizontal Section	Period	T_h	1432	1606	2047	Tclk
	Active	$T_{disp(h)}$	1366	1366	1366	Tclk
	Blanking	$T_{blk(h)}+T_{blk(h)}+PW_{hs}$	66	240	681	Tclk
Clock	Period	T_{clk}	10.64	12.8	17.72	Ns
	Frequency	Freq	56.42	77.86	94	MHz
Frame rate	Frame rate	V_{freq}	50	60	76	Hz
Hsync Frequency	Hsync Frequency	H_{freq}	39.7	48.5	64.6	KHz


Note1 : DE mode only

6.5 Timing diagram



6.6 Power ON/OFF Sequence

VDD power and lamp on/off sequence are as follows. Interface signals are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off.



Power Sequence Timing

Parameter	Value			Unit
	Min.	Typ.	Max.	
T1	0.5	-	10	[ms]
T2	0	-	50	[ms]
T3	500	-	-	[ms]
T4	100	-	-	[ms]
T5	0		50	[ms] Note1,2
T6	5	-	150	[ms] Note1,2
T7	1000	-	-	[ms]

Note1 : Recommend setting T5 = 0ms to avoid electronic noise when VDD is off.

Note2 : During T5 and T6 period , please keep the level of input LVDS signals with Hi-Z state.

7.0 Connector & Pin Assignment

Physical interface is described as for the connector on module. These connectors are capable of accommodating the following signals and will be following components.

7.1 TFT LCD Module

Connector Name / Designation	Interface Connector / Interface card
Manufacturer	STM or P-TWO
Type Part Number	MSCKT2407P30HB (STM) / AL230F-A0G1D-P (P-TWO)
Mating Housing Part Number	FI-X30HL(JAE) (Locked Type) FI-X30H (JAE)(Unlocked Type)

7.1.1 Pin Assignment

Pin#	Signal Name	Pin#	Signal Name
1	NC	2	NC
3	NC	4	GND
5	RXIN0-	6	RXIN0+
7	GND	8	RXIN1-
9	RXIN1+	10	GND
11	RXIN2-	12	RXIN2+
13	GND	14	RXCLKIN-
15	RXCLKIN+	16	GND
17	RXIN3-	18	RXIN3+
19	GND	20	NC
21	NC	22	NC
23	GND	24	GND
25	GND	26	VDD
27	VDD	28	VDD
29	VDD	30	VDD


7.2 LED Connector on Backlight Unit.

This connector is mounted on LED light-bar.

Connector Name / Designation	Light Bar Connector
Manufacturer	ENTERY (E&T) Corporation
Mating Type Part Number	3707K-S06N-21R (Wire harness)

7.2.1 LED Pin assignment


Pin#	Signal Name
1	IRLED1 (current out)
2	IRLED2 (current out)
3	VLED (voltage in)
4	VLED (voltage in)
5	IRLED3 (current out)
6	IRLED4 (current out)





7.2.2 LED Connector dimension

$H \times V \times D = 13.9 \times 3.00 \times 4.25$, Pitch = 1.0(unit = mm)

$H \times V \times D = 13.9 \times 3.00 \times 4.25$, Pitch = 1.0(unit = mm)



7.2.3 LED Mating housing dimension



8.0 Reliability Test

Environment test conditions are listed as following table.

Items	Required Condition	Note
Temperature Humidity Bias (THB)	Ta= 50℃ , 80%RH, 300hours	
High Temperature Operation (HTO)	Ta= 50℃ , 50%RH, 300hours	
Low Temperature Operation (LTO)	Ta= 0℃ , 300hours	
High Temperature Storage (HTS)	Ta= 60℃ , 300hours	
Low Temperature Storage (LTS)	Ta= -20℃ , 300hours	
Vibration Test (Non-operation)	Acceleration: 1.5 Grms Wave: Random Frequency: 10 - 200 Hz Duration: 30 Minutes each Axis (X, Y, Z)	
Shock Test (Non-operation)	Acceleration: 50 G Wave: Half-sine Active Time: 20 ms Direction: ±X, ±Y, ±Z (one time for each Axis)	
Drop Test	Height: 46 cm, package test	
Thermal Shock Test (TST)	-20℃/30min, 60℃/30min, 100 cycles	1
On/Off Test	On/10sec, Off/10sec, 30,000 cycles	
ESD (Electro Static Discharge)	Contact Discharge: ± 15KV, 150pF(330Ω) 1sec, 15 points, 25 times/ point.	2
	Air Discharge: ± 15KV, 150pF(330Ω) 1sec 15 points, 25 times/ point.	
Altitude Test	Operation:18,000 ft Non-Operation:40,000 ft	

Note 1: The TFT-LCD module will not sustain damage after being subjected to 100 cycles of rapid temperature change. A cycle of rapid temperature change consists of varying the temperature from -20℃ to 60℃, and back again. Power is not applied during the test. After temperature cycling, the unit is placed in normal room ambient for at least 4 hours before power on.

Note 2: EN61000-4-2, ESD class B:

Certain performance degradation allowed


No data lost

Self-recoverable


No hardware failures.

9.0 Shipping Label

The label is on the panel as shown below:




Note 1: For Pb Free products, AUO will add  for identification.


Note 2: For RoHS compatible products, AUO will add  for identification.


Note 3: For China RoHS compatible products, AUO will add  for identification.

Note 4: The Green Mark will be presented only when the green documents have been ready by AUO Internal Green Team.

10.0 Mechanical Characteristics







11. Packing Specification


M185 14片裝:48.5*37.2*34.8cm

料號:


Carton:81.18M02.008 /Cushion:84.18M02.037



將M185模組置入靜電袋中並折疊後
依序放入包裝隔板中



放置14片，放入上蓋緩衝，封箱完成



單層 pallet 打棧示意圖



Product Specification

M185XTN01.3

AU OPTRONICS CORPORATION

Pallet and shipment information

	Item	Specification			Remark
		Q'ty	Dimension	Weight(kg)	
1	Panel	1	430.37(H)mm x 254.6(V)mm x 9.9(D)mm	1.330	
2	Cushion	1	-	1.125	
3	Box	1	485(L)mm x 372(W)mm x 348(H)mm	1.00	without Panel & cushion
4	Packing Box	14 pcs/Box	485(L)mm x 372(W)mm x 348(H)mm	20.745	with panel & cushion
5	Pallet	1	1150(L)mm x 980(W)mm x 138(H)mm	15	
6	Pallet after Packing	24 boxes/pallet	1150(L)mm x 980(W)mm x 138(H)mm	509	