




# Product Specification

AU OPTRONICS CORPORATION

( ) Preliminary Specifications

(✓) Final Specifications

|  |   |
|--|---|
| Module   | 15.6" (15.55") FHD 16:9 Color TFT-LCD with LED Backlight design |
| Model Name   | B156HAN02.2 (H/W:AA)  |
| Note (  ) | LED Backlight with driving circuit design                       |

|   |       |
|---|-------|
| Customer  | Date  |
| _____   | _____ |
| Checked & Approved by   | Date  |
| _____   | _____ |
| Note: This Specification is subject to change without notice. |       |

|   |                   |
|---|-------------------|
| Approved by   | Date              |
| <u>Buffy Chen</u>                                   | <u>2017/03/09</u> |
| Prepared by   | Date              |
| <u>Amy SH Chang</u>                                 | <u>2017/03/09</u> |
| NBBU Marketing Division<br>AU Optronics corporation |                   |



## Contents

|  |           |
|--|-----------|
| <b>1. Handling Precautions .....</b>               | <b>4</b>  |
| <b>2. General Description.....</b>                 | <b>5</b>  |
| 2.1 General Specification .....                    | 5         |
| 2.2 Optical Characteristics .....                  | 6         |
| <b>3. Functional Block Diagram .....</b>           | <b>11</b> |
| <b>4. Absolute Maximum Ratings .....</b>           | <b>12</b> |
| 4.1.1 Absolute Ratings of TFT LCD Module .....     | 12        |
| 4.1.2 Absolute Ratings of Touch Sensor Module..... | 12        |
| 4.2 Absolute Ratings of Environment .....          | 12        |
| <b>5. Electrical Characteristics .....</b>         | <b>13</b> |
| 5.1 TFT LCD Module .....                           | 13        |
| 5.2 Backlight Unit .....                           | 16        |
| <b>6. Signal Interface Characteristic .....</b>    | <b>17</b> |
| 6.1 Pixel Format Image.....                        | 17        |
| 6.2 Integration Interface Requirement.....         | 18        |
| 6.3 Interface Timing.....                          | 20        |
| 6.4 Power ON/OFF Sequence.....                     | 22        |
| <b>7. Panel Reliability Test.....</b>              | <b>25</b> |
| 7.1 Vibration Test.....                            | 25        |
| 7.2 Shock Test.....                                | 25        |
| 7.3 Reliability Test .....                         | 25        |
| <b>8. Mechanical Characteristics .....</b>         | <b>26</b> |
| 8.1 LCM Outline Dimension.....                     | 26        |
| <b>9. Shipping and Package.....</b>                | <b>28</b> |
| 9.1 Shipping Label Format .....                    | 28        |
| 9.3 Shipping Package of Palletizing Sequence.....  | 30        |
| <b>10. Appendix: EDID Description .....</b>        | <b>31</b> |



# Product Specification

AU OPTRONICS CORPORATION

## Record of Revision

| Version and Date | Page | Old description            | New Description | Remark |
|------------------|------|----------------------------|-----------------|--------|
| 1.0 2017/03/09   | All  | Final Edition for Customer |                 |        |
|                  |      |                            |                 |        |
|                  |      |                            |                 |        |
|                  |      |                            |                 |        |
|                  |      |                            |                 |        |



## 1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 10) After installation of the TFT Module into an enclosure (Notebook PC Bezel, for example), do not twist nor bend the TFT Module even momentary. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 11) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 12) Disconnecting power supply before handling LCD modules, it can prevent electric shock, DO NOT TOUCH the electrode parts, cables, connectors and LED circuit part of TFT module that a LED light bar build in as a light source of back light unit. It can prevent electronic breakdown.



# Product Specification

AU OPTRONICS CORPORATION

## 2. General Description

B156HAN02.2 is a Color Active Matrix Liquid Crystal Display composed of a TFT LCD panel, a driver circuit, and LED backlight system. The screen format is intended to support the 16:9 FHD, 1920(H) x 1080(V) screen and 262k colors (RGB 6-bits data driver) with LED backlight driving circuit. All input signals are eDP(Embedded DisplayPort) interface compatible.

B156HAN02.2 is designed for a display unit of notebook style personal computer and industrial machine.

## 2.1 General Specification

The following items are characteristics summary on the table at 25 °C condition:


| Items  | Unit                 | Specifications   |        |        |        |
|--|----------------------|--|--------|--------|--------|
| Screen Diagonal  | [mm]                 | 394.9  |        |        |        |
| Active Area  | [mm]                 | 344.16 x 193.59  |        |        |        |
| Pixels H x V   |                      | 1920 x 3(RGB) x 1080                                       |        |        |        |
| Pixel Pitch  | [mm]                 | 0.17925 x 0.17925  |        |        |        |
| Pixel Format   |                      | R.G.B. Vertical Stripe                                     |        |        |        |
| Display Mode   |                      | Normally Black(AHVA)                                       |        |        |        |
| White Luminance (ILED= 23 mA)<br>(Note: ILED is LED current) | [cd/m <sup>2</sup> ] | 250 typ. (5 points average)<br>212 min. (5 points average) |        |        |        |
| Luminance Uniformity   |                      | 1.25 max. (5 points)                                       |        |        |        |
| Contrast Ratio   |                      | 700:1 typ  |        |        |        |
| Response Time  | [ms]                 | 25 Typ   |        |        |        |
| Nominal Input Voltage VDD                                    | [Volt]               | +3.3 typ.  |        |        |        |
| Power Consumption  | [Watt]               | 4.25 max. (include Logic and BLU power)                    |        |        |        |
| Weight   | [Grams]              | 370 max.   |        |        |        |
| Physical Size  | [mm]                 |  | Min.   | Typ.   | Max.   |
|  |                      | Length   | 350.06 | 350.56 | 351.06 |
|  |                      | Width  | 223.1  | 223.6  | 224.1  |
|  |                      | Thickness  |        |        | 3.2    |
| Electrical Interface   |                      | 2 Lane eDP 1.2   |        |        |        |
| Glass Thickness  | [mm]                 | 0.4  |        |        |        |
| Surface Treatment  |                      | Anti-Glare   |        |        |        |
| Support Color  |                      | 262K colors ( RGB 6-bit )                                  |        |        |        |
| Temperature Range  | [°C]                 | 0 to +50   |        |        |        |
| Operating  | [°C]                 | -20 to +60   |        |        |        |
| Storage (Non-Operating)                                      |                      |  |        |        |        |
| RoHS Compliance  |                      | RoHS Compliance  |        |        |        |

## 2.2 Optical Characteristics


The optical characteristics are measured under stable conditions at 25°C (Room Temperature) :

| Item                                   |       | Symbol           | Conditions         | Min.  | Typ.  | Max.  | Unit   | Note     |    |   |  |  |
|--|-------|------------------|--------------------|-------|-------|-------|--------|----------|----|---|--|--|
| White Luminance<br>ILED=23mA           |       |                  | 5 points average   | 212   | 250   |       | cd/m²  | 1, 4, 5. |    |   |  |  |
| Viewing Angle                          |       | θ <sub>R</sub>   | Horizontal (Right) | 80    | 85    | -     | degree | 4, 9     |    |   |  |  |
|  |       | θ <sub>L</sub>   | CR = 10 (Left)     | 80    | 85    | -     |        |          |    |   |  |  |
|  |       | ψ <sub>H</sub>   | Vertical (Upper)   | 80    | 85    | -     |        |          |    |   |  |  |
|  |       | ψ <sub>L</sub>   | CR = 10 (Lower)    | 80    | 85    | -     |        |          |    |   |  |  |
| Luminance Uniformity                   |       | δ <sub>5P</sub>  | 5 Points           | -     | -     | 1.25  |        | 1, 3, 4  |    |   |  |  |
| Luminance Uniformity                   |       | δ <sub>13P</sub> | 13 Points          | -     | -     | 1.6   |        | 2, 3, 4  |    |   |  |  |
| Contrast Ratio                         |       | CR               |                    | -     | 700   | -     |        | 4, 6     |    |   |  |  |
| Cross talk                             |       | %                |                    |       |       | 4     |        | 4, 7     |    |   |  |  |
| Response Time                          |       | T <sub>RT</sub>  | Rising + Falling   | -     | 25    | 35    |        |          |    |   |  |  |
| Color /<br>Chromaticity<br>Coordinates | Red   | R <sub>x</sub>   | CIE 1931           | 0.548 | 0.578 | 0.608 |        | 4        |    |   |  |  |
|  |       | R <sub>y</sub>   |                    | 0.318 | 0.348 | 0.378 |        |          |    |   |  |  |
|  | Green | G <sub>x</sub>   |                    | 0.319 | 0.349 | 0.379 |        |          |    |   |  |  |
|  |       | G <sub>y</sub>   |                    | 0.541 | 0.571 | 0.601 |        |          |    |   |  |  |
|  | Blue  | B <sub>x</sub>   |                    | 0.128 | 0.158 | 0.188 |        |          |    |   |  |  |
|  |       | B <sub>y</sub>   |                    | 0.086 | 0.116 | 0.146 |        |          |    |   |  |  |
|  | White | W <sub>x</sub>   |                    | 0.283 | 0.313 | 0.343 |        |          |    |   |  |  |
|  |       | W <sub>y</sub>   |                    | 0.299 | 0.329 | 0.359 |        |          |    |   |  |  |
|  | NTSC  |                  |                    | %     |       | -     |        |          | 45 | - |  |  |

**Note 1:** 5 points position (Ref: Active area)



**Note 2:** 13 points position (Ref: Active area)



**Note 3:** The luminance uniformity of 5 or 13 points is defined by dividing the maximum luminance values by the minimum test point luminance


$$\delta_{W5} = \frac{\text{Maximum Brightness of five points}}{\text{Minimum Brightness of five points}}$$

$$\delta_{W13} = \frac{\text{Maximum Brightness of thirteen points}}{\text{Minimum Brightness of thirteen points}}$$

**Note 4:** Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room, and it should be measured in the

center of screen.



**Note 5 :** Definition of Average Luminance of White ( $Y_L$ ):

Measure the luminance of gray level 63 at 5 points ,  $Y_L = [L (1)+ L (2)+ L (3)+ L (4)+ L (5)] / 5$

$L (x)$  is corresponding to the luminance of the point X at Figure in Note (1).

**Note 6 :** Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$

**Note 7 :** Definition of Cross Talk (CT)


$$CT = | YB - YA | / YA \times 100 (\%)$$

Where

$YA$  = Luminance of measured location without gray level 0 pattern (cd/m<sup>2</sup>)


$YB$  = Luminance of measured location with gray level 0 pattern (cd/m<sup>2</sup>)






**Note 8:** Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are changed from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval between the 10% and 90% of amplitudes. Refer to figure as below.




## Note 9. Definition of viewing angle

Viewing angle is the measurement of contrast ratio  $\geq 10$ , at the screen center, over a  $180^\circ$  horizontal and  $180^\circ$  vertical range (off-normal viewing angles). The  $180^\circ$  viewing angle range is broken down as follows;  $90^\circ$  ( $\theta$ ) horizontal left and right and  $90^\circ$  ( $\phi$ ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



## 3. Functional Block Diagram

The following diagram shows the functional block of the 15.6 inches wide Color TFT/LCD 40 Pin (One CH/connector Module)



## 4. Absolute Maximum Ratings

An absolute maximum rating of the module is as following:

### 4.1.1 Absolute Ratings of TFT LCD Module

| Item            | Symbol | Min  | Max  | Unit   | Conditions |
|-----------------|--------|------|------|--------|------------|
| Logic/LCD Drive | Vin    | -0.3 | +4.0 | [Volt] | Note 1,2   |

### 4.1.2 Absolute Ratings of Touch Sensor Module

| Item                              | Symbol | Min  | Max  | Unit   | Conditions |
|-----------------------------------|--------|------|------|--------|------------|
| Touch Sensor Module Power Voltage | VTSP   | -0.3 | +4.0 | [Volt] |            |
| Touch Sensor Module Reset Signal  | RST    | -0.3 | 3.6  | [Volt] |            |
| Touch Sensor Module enable Signal | TP_EN  | -0.3 | 3.6  | [Volt] |            |

### 4.2 Absolute Ratings of Environment

| Item                | Symbol | Min | Max | Unit  | Conditions |
|---------------------|--------|-----|-----|-------|------------|
| Operating           | TOP    | 0   | +50 | [°C]  | Note 4     |
| Operation Humidity  | HOP    | 5   | 95  | [%RH] | Note 4     |
| Storage Temperature | TST    | -20 | +60 | [°C]  | Note 4     |
| Storage Humidity    | HST    | 5   | 95  | [%RH] | Note 4     |

Note 1: At Ta (25°C )

Note 2: Permanent damage to the device may occur if exceed maximum values


Note 3: LED specification refer to section 5.2

Note 4: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).

Note 5: The packing material of system forbid to involve ammonium component

Note 6: The reliability test conditions of system do not exceed the verified conditions of TFT module

Note 7: Be sure the panel test condition do not exceed the component limitation of TFT module(TN Liquid crystal , for example)



## 5. Electrical Characteristics

### 5.1 TFT LCD Module

#### 5.1.1 Power Specification

Input power specifications are as follows;



The power specification are measured under 25°C and frame frequency under 60Hz

| Symble | Parameter                                | Min | Typ | Max  | Units       | Note   |
|--------|--|-----|-----|------|-------------|--------|
| VDD    | Logic/LCD Drive Voltage                  | 3.0 | 3.3 | 3.6  | [Volt]      |        |
| PDD    | VDD Power                                | -   | -   | 1.0  | [Watt]      | Note 1 |
| IDD    | IDD Current                              | -   | -   | 333  | [mA]        | Note 1 |
| IRush  | Inrush Current                           | -   | -   | 1500 | [mA]        | Note 2 |
| VDDrp  | Allowable Logic/LCD Drive Ripple Voltage | -   | -   | 100  | [mV]<br>p-p |        |

Note 1 : Maximum Measurement Condition : Black Pattern at 3.3V driving voltage. ( $P_{max}=V_{3.3} \times I_{black}$ )

Typical Measurement Condition: Mosaic Pattern

Note 2 : Measure Condition



Vin rising time

## 5.1.2 Signal Electrical Characteristics


Signal electrical characteristics are as follows;

### Display Port main link signal:

Differential pair VD+ , VD-  
Which is one Display port  
Main link

VCM of Display port  
Main link

$$V_{diffP-P} = [(VD+) - (VD-)] \times 2$$




| Display port main link |  |     |     |      |      |
|------------------------|--|-----|-----|------|------|
|                        |  | Min | Typ | Max  | unit |
| VCM                    | RX input DC Common Mode Voltage            |     | 0   |      | V    |
| VDiff <sub>P-P</sub>   | Peak-to-peak Voltage at a receiving Device | 150 |     | 1320 | mV   |

Follow as VESA display port standard V1.1a

### Display Port AUX\_CH signal:

Differential AUX+ , AUX-  
Which is Display port AUX\_CH



Display port AUX\_CH



## Product Specification

AU OPTRONICS CORPORATION

|                      |  | Min | Typ | Max | unit |
|----------------------|--|-----|-----|-----|------|
| VCM                  | AUX DC Common Mode Voltage                     |     | 0   |     | V    |
| VDiff <sub>P-P</sub> | AUX Peak-to-peak Voltage at a receiving Device | 270 |     | 800 | mV   |

Follow as VESA display port standard V1.1a.

### Display Port VHPD signal:

| Display port VHPD |             |      |     |     |      |
|-------------------|-------------|------|-----|-----|------|
|                   |             | Min  | Typ | Max | unit |
| VHPD              | HPD Voltage | 2.25 | -   | 3.6 | V    |

Follow as VESA display port standard V1.1a.



## Product Specification

AU OPTRONICS CORPORATION

### 5.2 Backlight Unit

#### 5.2.1 LED characteristics

| Parameter                   | Symbol | Min    | Typ | Max  | Units  | Condition                     |
|-----------------------------|--------|--------|-----|------|--------|-------------------------------|
| Backlight Power Consumption | PLED   | -      | -   | 3.25 | [Watt] | (Ta=25°C), Note 1<br>Vin =12V |
| LED Life-Time               | N/A    | 15,000 | -   | -    | Hour   | (Ta=25°C), Note 2<br>If=23 mA |

**Note 1:** Calculator value for reference  $P_{LED} = V_F$  (Normal Distribution) \*  $I_F$  (Normal Distribution) / Efficiency

**Note 2:** The LED life-time define as the estimated time to 50% degradation of initial luminous.

#### 5.2.2 Backlight input signal characteristics

| Parameter                      | Symbol             | Min | Typ  | Max  | Units  | Remark   |
|--------------------------------|--------------------|-----|------|------|--------|--|
| LED Power Supply               | VLED               | 5.0 | 12.0 | 21.0 | [Volt] | Define as<br>Connector<br>Interface<br>(Ta=25°C) |
| LED Enable Input<br>High Level | VLED_EN<br>*Note 1 | 2.5 | -    | 5.5  | [Volt] |  |
| LED Enable Input<br>Low Level  |                    | -   | -    | 0.5  | [Volt] |  |
| PWM Logic Input<br>High Level  | VPWM_EN<br>*Note 1 | 2.5 | -    | 5.5  | [Volt] |  |
| PWM Logic Input<br>Low Level   |                    | -   | -    | 0.5  | [Volt] |  |
| PWM Input Frequency            | FPWM               | 200 |      | 10K  | Hz     |  |
| PWM Duty Ratio                 | Duty               | 5   | --   | 100  | %      |  |

**Note 1 :** Recommend system pull up/down resistor no bigger than 10kohm


**Note 2 :** If the PWM duty ratio(min) is set between 5% to 1% , the PWM input frequency should be set below 1KHz . The brightness-duty characteristic might not be able to keep in it's linearity if the dimming control is operated in 1% to 5% range.



## 6. Signal Interface Characteristic

### 6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.



## 6.2 Integration Interface Requirement

### 6.2.1 Connector Description

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.


| Connector Name / Designation | For Signal Connector       |
|------------------------------|----------------------------|
| Manufacturer                 | IPEX                       |
| Type / Part Number           | IPEX 20525-040E-02         |
| Mating Housing/Part Number   | IPEX 20523C9 or compatible |

### 6.2.2 Pin Assignment

eDP lane is a differential signal technology for LCD interface and high speed data transfer device.

| PIN NO | Symbol              | Function                              |
|--------|---------------------|---------------------------------------|
| 1      | NC Reserved         | Reserved for LCD supplier             |
| 2      | GND                 | High Speed Ground                     |
| 3      | Lane1_N             | Complement Signal Link Lane 1         |
| 4      | Lane1_P             | True Signal Link Lane 1               |
| 5      | GND                 | High Speed Ground                     |
| 6      | Lane0_N             | Complement Signal Link Lane 0         |
| 7      | Lane0_P             | True Signal Link Lane 0               |
| 8      | GND                 | High Speed Ground                     |
| 9      | AUX_CH_P            | True Signal Auxiliary Channel         |
| 10     | AUX_CH_N            | Complement Signal Auxiliary Channel   |
| 11     | GND                 | High Speed Ground                     |
| 12     | VCC                 | LCD logic                             |
| 13     | VCC                 | LCD logic                             |
| 14     | LCD Self Test or NC | LCD Panel Self Test Enable (Optional) |
| 15     | GND                 | LCD logic and driver ground           |
| 16     | GND                 | LCD logic and driver ground           |
| 17     | HPD                 | HPD signal pin                        |
| 18     | BL_GND              | LED Backlight ground                  |
| 19     | BL_GND              | LED Backlight ground                  |
| 20     | BL_GND              | LED Backlight ground                  |

|    |             |                                      |
|----|-------------|--------------------------------------|
| 21 | BL_GND      | LED Backlight ground                 |
| 22 | BL ENABLE   | LED Backlight control on/off control |
| 23 | BL PWM      | System PWM signal input for dimming  |
| 24 | NC Reserved | Reserved for LCD supplier            |
| 25 | NC Reserved | Reserved for LCD supplier            |
| 26 | VLED        | LED Backlight Power                  |
| 27 | VLED        | LED Backlight Power                  |
| 28 | VLED        | LED Backlight Power                  |
| 29 | VLED        | LED Backlight Powe                   |
| 30 | NC          | NC                                   |
| 31 | NC          | No connect                           |
| 32 | NC          | No connect                           |
| 33 | NC          | No connect                           |
| 34 | NC          | No connect                           |
| 35 | NC          | No connect                           |
| 36 | NC          | No connect                           |
| 37 | NC          | No connect                           |
| 38 | NC          | No connect                           |
| 39 | NC          | No connect                           |
| 40 | NC          | No connect                           |



Note1 : start from right side

Note2 : Input signals shall be low or High-impedance state when VDD is off.

## 6.3 Interface Timing


Basically, interface timings should match the 1920x1080 /60Hz manufacturing guide line timing.

| Parameter <sup>↗</sup>          |                       | Symbol <sup>↗</sup>                      | Min. <sup>↗</sup>  | Typ. <sup>↗</sup> | Max. <sup>↗</sup>   | Unit <sup>↗</sup>                     |
|---------------------------------|-----------------------|--|--------------------|-------------------|---------------------|---------------------------------------|
| Frame Rate <sup>↗</sup>         |                       | - <sup>↗</sup>                           | 48 <sup>↗</sup>    | 60 <sup>↗</sup>   | - <sup>↗</sup>      | Hz <sup>↗</sup>                       |
| Clock frequency <sup>↗</sup>    |                       | 1/ <u>T<sub>clock</sub></u> <sup>↗</sup> | 113.6 <sup>↗</sup> | 142 <sup>↗</sup>  | 150 <sup>↗</sup>    | MHz <sup>↗</sup>                      |
| Vertical Section <sup>↗</sup>   | Period <sup>↗</sup>   | T <sub>V</sub> <sup>↗</sup>              | 1126 <sup>↗</sup>  | 1126 <sup>↗</sup> | 1080+A <sup>↗</sup> | <u>T<sub>line</sub></u> <sup>↗</sup>  |
|                                 | Active <sup>↗</sup>   | T <sub>VD</sub> <sup>↗</sup>             | 1080 <sup>↗</sup>  |                   |                     |                                       |
|                                 | Blanking <sup>↗</sup> | T <sub>VB</sub> <sup>↗</sup>             | 46 <sup>↗</sup>    | 46 <sup>↗</sup>   | A <sup>↗</sup>      |                                       |
| Horizontal Section <sup>↗</sup> | Period <sup>↗</sup>   | T <sub>H</sub> <sup>↗</sup>              | 2100 <sup>↗</sup>  | 2100 <sup>↗</sup> | 1920+B <sup>↗</sup> | <u>T<sub>clock</sub></u> <sup>↗</sup> |
|                                 | Active <sup>↗</sup>   | T <sub>HD</sub> <sup>↗</sup>             | 1920 <sup>↗</sup>  |                   |                     |                                       |
|                                 | Blanking <sup>↗</sup> | T <sub>HB</sub> <sup>↗</sup>             | 180 <sup>↗</sup>   | 180 <sup>↗</sup>  | B <sup>↗</sup>      |                                       |

Note : 1. DE mode only

2. The maximum clock frequency =  $(1920+B) \cdot (1080+A) \cdot 60 < 150 \text{ MHz}$


## 6.3.2 Timing diagram



## 6.4 Power ON/OFF Sequence


Power on/off sequence is as follows. Interface signals and LED on/off sequence are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off

### Display Port panel power sequence:



### Display port interface power up/down sequence, normal system operation

#### Display Port AUX\_CH transaction only:



### Display port interface power up/down sequence, AUX\_CH transaction only



# Product Specification

AU OPTRONICS CORPORATION

Display Port panel power sequence timing parameter:

| Timing parameter | Description   | Reqd. by | Limits |      |       | Notes  |
|------------------|---|----------|--------|------|-------|--|
|                  |   |          | Min.   | Typ. | Max.  |  |
| T1               | power rail rise time, 10% to 90%                            | source   | 0.5ms  |      | 10ms  |  |
| T2               | delay from LCDVDD to black video generation                 | sink     | 0ms    |      | 200ms | prevents display noise until valid video data is received from the source                  |
| T3               | delay from LCDVDD to HPD high                               | sink     | 0ms    |      | 200ms | sink AUX_CH must be operational upon HPD high.   |
| T4               | delay from HPD high to link training initialization         | source   |        |      |       | allows for source to read link capability and initialize.                                  |
| T5               | link training duration                                      | source   |        |      |       | dependant on source link to read training protocol.  |
| T6               | link idle   | source   |        |      |       | Min accounts for required BS-Idle pattern.<br>Max allows for source frame synchronization. |
| T7               | delay from valid video data from source to video on display | sink     | 0ms    |      | 50ms  | max allows sink validate video data and timing.  |
| T8               | delay from valid video data from source to backlight enable | source   |        |      |       | source must assure display video is stable.  |
| T9               | delay from backlight disable to end of valid video data     | source   |        |      |       | source must assure backlight is no longer illuminated.                                     |
| T10              | delay from end of valid video data from source to power off | source   | 0ms    |      | 500ms |  |
| T11              | power rail fall time, 90% to 10%                            | source   |        |      | 10ms  |  |
| T12              | power off time  | source   | 500ms  |      |       |  |

**Note1:** The sink must include the ability to generate black video autonomously. The sink must automatically enable black video under the following conditions:


- upon LCDVDD power on (within T2 max)-when the "Novideostream\_Flag" (VB-ID Bit 3) is received from the source (at the end of T9).

- when no main link data, or invalid video data, is received from the source. Black video must be displayed within 64ms (typ) from the start of either condition. Video data can be deemed invalid based on MSA and timing information, for example.

**Note 2:** The sink may implement the ability to disable the black video function, as described in Note 1, above, for system development and debugging purpose.

**Note 3:** The sink must support AUX\_CH polling by the source immediately following LCDVDD power on without causing damage to the sink device (the source can re-try if the sink is not ready). The sink must be able to respond to an AUX\_CH transaction with the time specified within T3 max.

## Display Port panel B/L power sequence timing parameter:




|            | Min (ms)   | Max (ms) |
|------------|------------|----------|
| <b>T13</b> | <b>0.2</b> | -        |
| <b>T14</b> | <b>0</b>   | -        |
| <b>T15</b> | -          | -        |
| <b>T16</b> | -          | -        |
| <b>T17</b> | <b>0</b>   | -        |
| <b>T18</b> | <b>0</b>   | -        |
| <b>T19</b> | <b>1*</b>  | -        |
| <b>T20</b> | <b>1*</b>  | -        |

Seamless change:  $T19/T20 = 5 \times T_{PWM}^*$

$*T_{PWM} = 1/PWM \text{ Frequency}$

Note: When the adapter is hot plugged, the backlight power supply sequence is shown as below



Note : If  $T19, T20 < 5 \times T_{PWM}^*$ , This flash display may occur. We suggest  $T19, T20 \geq 5 \times T_{PWM}^*$  to realize seamless change display.





# Product Specification

AU OPTRONICS CORPORATION

## 7. Panel Reliability Test

### 7.1 Vibration Test

#### Test Spec:

- Test method: Non-Operation
- Acceleration: 1.5 G
- Frequency: 10 - 500Hz Random
- Sweep: 30 Minutes each Axis (X, Y, Z)

### 7.2 Shock Test

#### Test Spec:

- Test method: Non-Operation
- Acceleration: 220 G , Half sine wave
- Active time: 2 ms
- Pulse: X,Y,Z .one time for each side

### 7.3 Reliability Test

| Items                      | Required Condition                               | Note   |
|----------------------------|--|--------|
| Temperature Humidity Bias  | Ta= 40℃, 90%RH, 300h                             |        |
| High Temperature Operation | Ta= 50℃, Dry, 300h                               |        |
| Low Temperature Operation  | Ta=0℃, 300h                                      |        |
| High Temperature Storage   | Ta= 60℃, 300h                                    |        |
| Low Temperature Storage    | Ta= -20℃, 250h                                   |        |
| Thermal Shock Test         | Ta=-20℃(30min) ~60℃(30min), 100cycles condition. |        |
| ESD                        | Contact : ±8 KV<br>Air : ±15 KV                  | Note 1 |

**Note1:** According to EN 61000-4-2 , ESD class B: Some performance degradation allowed. No data lost . Self-recoverable. No hardware failures.

**Remark:** MTBF (Excluding the LED): 30,000 hours with a confidence level 90%




# Product Specification

AU OPTRONICS CORPORATION

## 8. Mechanical Characteristics

### 8.1 LCM Outline Dimension

#### 8.1.1 Standard Front View






## 8.1.2 Standard Rear View

# Product Specification

AU OPTRONICS CORPORATION











# Product Specification


AU OPTRONICS CORPORATION

## 9. Shipping and Package


### 9.1 Shipping Label Format

|   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|
| <br>*XXXXXXXXXXXX-XXXXXX* H/W:AA | Manufactured MM/WW<br>Model No: B156HAN02.2<br>AU Optronics<br>F/W: 1    MADE IN CHINA(S01) | <br>B156HAN02.2 | c  US<br>E204354 |  |  |  |
|---|---|---|---|---|---|---|

### 9.2 Carton Package



## 9.3 Shipping Package of Palletizing Sequence



單層 pallet 打機示意圖



# Product Specification

AU OPTRONICS CORPORATION

## 10. Appendix: EDID Description

| Address | FUNCTION  | Value | Value    | Value | Note |
|---------|---|-------|----------|-------|------|
| HEX     |   | HEX   | BIN      | DEC   |      |
| 00      | Header  | 00    | 00000000 | 0     |      |
| 01      |   | FF    | 11111111 | 255   |      |
| 02      |   | FF    | 11111111 | 255   |      |
| 03      |   | FF    | 11111111 | 255   |      |
| 04      |   | FF    | 11111111 | 255   |      |
| 05      |   | FF    | 11111111 | 255   |      |
| 06      |   | FF    | 11111111 | 255   |      |
| 07      |   | 00    | 00000000 | 0     |      |
| 08      | EISA Manuf. Code LSB                                  | 06    | 00000110 | 6     |      |
| 09      | Compressed ASCII                                      | AF    | 10101111 | 175   |      |
| 0A      | Product Code  | ED    | 11101101 | 237   |      |
| 0B      | hex, LSB first  | 22    | 00100010 | 34    |      |
| 0C      | 32-bit ser #  | 00    | 00000000 | 0     |      |
| 0D      |   | 00    | 00000000 | 0     |      |
| 0E      |   | 00    | 00000000 | 0     |      |
| 0F      |   | 00    | 00000000 | 0     |      |
| 10      | Week of manufacture                                   | 00    | 00000000 | 0     |      |
| 11      | Year of manufacture                                   | 1A    | 00011010 | 26    |      |
| 12      | EDID Structure Ver.                                   | 01    | 00000001 | 1     |      |
| 13      | EDID revision #                                       | 04    | 00000100 | 4     |      |
| 14      | Video input def. (digital I/P, non-TMDS, CRGB)        | 95    | 10010101 | 149   |      |
| 15      | Max H image size (rounded to cm)                      | 22    | 00100010 | 34    |      |
| 16      | Max V image size (rounded to cm)                      | 13    | 00010011 | 19    |      |
| 17      | Display Gamma (=(gamma*100)-100)                      | 78    | 01111000 | 120   |      |
| 18      | Feature support (no DPMS, Active OFF, RGB, tmg Blk#1) | 02    | 00000010 | 2     |      |
| 19      | Red/green low bits (Lower 2:2:2:2 bits)               | B0    | 10110000 | 176   |      |
| 1A      | Blue/white low bits (Lower 2:2:2:2 bits)              | E5    | 11100101 | 229   |      |
| 1B      | Red x (Upper 8 bits)                                  | 94    | 10010100 | 148   |      |
| 1C      | Red y/ highER 8 bits                                  | 58    | 01011000 | 88    |      |
| 1D      | Green x   | 5A    | 01011010 | 90    |      |
| 1E      | Green y   | 92    | 10010010 | 146   |      |
| 1F      | Blue x  | 28    | 00101000 | 40    |      |
| 20      | Blue y  | 21    | 00100001 | 33    |      |
| 21      | White x   | 50    | 01010000 | 80    |      |
| 22      | White y   | 54    | 01010100 | 84    |      |
| 23      | Established timing 1                                  | 00    | 00000000 | 0     |      |
| 24      | Established timing 2                                  | 00    | 00000000 | 0     |      |
| 25      | Established timing 3                                  | 00    | 00000000 | 0     |      |
| 26      | Standard timing #1                                    | 01    | 00000001 | 1     |      |
| 27      |   | 01    | 00000001 | 1     |      |
| 28      | Standard timing #2                                    | 01    | 00000001 | 1     |      |



# Product Specification

AU OPTRONICS CORPORATION

|    |  |    |          |     |  |
|----|--|----|----------|-----|--|
| 29 |  | 01 | 00000001 | 1   |  |
| 2A | Standard timing #3                                   | 01 | 00000001 | 1   |  |
| 2B |  | 01 | 00000001 | 1   |  |
| 2C | Standard timing #4                                   | 01 | 00000001 | 1   |  |
| 2D |  | 01 | 00000001 | 1   |  |
| 2E | Standard timing #5                                   | 01 | 00000001 | 1   |  |
| 2F |  | 01 | 00000001 | 1   |  |
| 30 | Standard timing #6                                   | 01 | 00000001 | 1   |  |
| 31 |  | 01 | 00000001 | 1   |  |
| 32 | Standard timing #7                                   | 01 | 00000001 | 1   |  |
| 33 |  | 01 | 00000001 | 1   |  |
| 34 | Standard timing #8                                   | 01 | 00000001 | 1   |  |
| 35 |  | 01 | 00000001 | 1   |  |
| 36 | Pixel Clock/10000 LSB                                | 78 | 01111000 | 120 |  |
| 37 | Pixel Clock/10000 USB                                | 37 | 00110111 | 55  |  |
| 38 | Horz active Lower 8bits                              | 80 | 10000000 | 128 |  |
| 39 | Horz blanking Lower 8bits                            | B4 | 10110100 | 180 |  |
| 3A | HorzAct:HorzBlnk Upper 4:4 bits                      | 70 | 01110000 | 112 |  |
| 3B | Vertical Active Lower 8bits                          | 38 | 00111000 | 56  |  |
| 3C | Vertical Blanking Lower 8bits                        | 2E | 00101110 | 46  |  |
| 3D | Vert Act : Vertical Blanking (upper 4:4 bit)         | 40 | 01000000 | 64  |  |
| 3E | HorzSync. Offset                                     | 6C | 01101100 | 108 |  |
| 3F | HorzSync.Width                                       | 30 | 00110000 | 48  |  |
| 40 | VertSync.Offset : VertSync.Width                     | AA | 10101010 | 170 |  |
| 41 | Horz&Vert Sync Offset/Width Upper 2bits              | 00 | 00000000 | 0   |  |
| 42 | Horizontal Image Size Lower 8bits                    | 58 | 01011000 | 88  |  |
| 43 | Vertical Image Size Lower 8bits                      | C1 | 11000001 | 193 |  |
| 44 | Horizontal & Vertical Image Size (upper 4:4 bits)    | 10 | 00010000 | 16  |  |
| 45 | Horizontal Border (zero for internal LCD)            | 00 | 00000000 | 0   |  |
| 46 | Vertical Border (zero for internal LCD)              | 00 | 00000000 | 0   |  |
| 47 | Signal (non-intr, norm, no stero, sep sync, neg pol) | 18 | 00011000 | 24  |  |
| 48 | Detailed timing/monitor                              | 00 | 00000000 | 0   |  |
| 49 | descriptor #2  | 00 | 00000000 | 0   |  |
| 4A |  | 00 | 00000000 | 0   |  |
| 4B |  | 0F | 00001111 | 15  |  |
| 4C |  | 00 | 00000000 | 0   |  |
| 4D |  | 00 | 00000000 | 0   |  |
| 4E |  | 00 | 00000000 | 0   |  |
| 4F |  | 00 | 00000000 | 0   |  |
| 50 |  | 00 | 00000000 | 0   |  |
| 51 |  | 00 | 00000000 | 0   |  |
| 52 |  | 00 | 00000000 | 0   |  |
| 53 |  | 00 | 00000000 | 0   |  |
| 54 |  | 00 | 00000000 | 0   |  |
| 55 |  | 00 | 00000000 | 0   |  |





## Product Specification

AU OPTRONICS CORPORATION

|    |                         |    |          |     |   |
|----|-------------------------|----|----------|-----|---|
| 56 |                         | 00 | 00000000 | 0   |   |
| 57 |                         | 00 | 00000000 | 0   |   |
| 58 |                         | 00 | 00000000 | 0   |   |
| 59 |                         | 20 | 00100000 | 32  |   |
| 5A | Detailed timing/monitor | 00 | 00000000 | 0   |   |
| 5B | descriptor #3           | 00 | 00000000 | 0   |   |
| 5C |                         | 00 | 00000000 | 0   |   |
| 5D |                         | FE | 11111110 | 254 |   |
| 5E |                         | 00 | 00000000 | 0   |   |
| 5F | Manufacture             | 41 | 01000001 | 65  | A |
| 60 | Manufacture             | 55 | 01010101 | 85  | U |
| 61 | Manufacture             | 4F | 01001111 | 79  | O |
| 62 |                         | 0A | 00001010 | 10  |   |
| 63 |                         | 20 | 00100000 | 32  |   |
| 64 |                         | 20 | 00100000 | 32  |   |
| 65 |                         | 20 | 00100000 | 32  |   |
| 66 |                         | 20 | 00100000 | 32  |   |
| 67 |                         | 20 | 00100000 | 32  |   |
| 68 |                         | 20 | 00100000 | 32  |   |
| 69 |                         | 20 | 00100000 | 32  |   |
| 6A |                         | 20 | 00100000 | 32  |   |
| 6B |                         | 20 | 00100000 | 32  |   |
| 6C | Detailed timing/monitor | 00 | 00000000 | 0   |   |
| 6D | descriptor #4           | 00 | 00000000 | 0   |   |
| 6E |                         | 00 | 00000000 | 0   |   |
| 6F |                         | FE | 11111110 | 254 |   |
| 70 |                         | 00 | 00000000 | 0   |   |
| 71 | Manufacture P/N         | 42 | 01000010 | 66  | B |
| 72 | Manufacture P/N         | 31 | 00110001 | 49  | 1 |
| 73 | Manufacture P/N         | 35 | 00110101 | 53  | 5 |
| 74 | Manufacture P/N         | 36 | 00110110 | 54  | 6 |
| 75 | Manufacture P/N         | 48 | 01001000 | 72  | H |
| 76 | Manufacture P/N         | 41 | 01000001 | 65  | A |
| 77 | Manufacture P/N         | 4E | 01001110 | 78  | N |
| 78 | Manufacture P/N         | 30 | 00110000 | 48  | 0 |
| 79 | Manufacture P/N         | 32 | 00110010 | 50  | 2 |
| 7A | Manufacture P/N         | 2E | 00101110 | 46  | . |
| 7B | Manufacture P/N         | 32 | 00110010 | 50  | 2 |
| 7C |                         | 20 | 00100000 | 32  |   |
| 7D |                         | 0A | 00001010 | 10  |   |
| 7E | Extension Flag          | 00 | 00000000 | 0   |   |
| 7F | Checksum                | 1A | 00011010 | 26  |   |