LG Display

SPECIFICATION
FOR
APPROVAL

(◆) **Preliminary Specification**

(   ) **Final Specification**

Title	14.0" HD TFT LCD

Customer	
MODEL	

SUPPLIER	LG Display Co., Ltd.
*MODEL	LP140WH8
Suffix	TLA1

*When you obtain standard approval,
 please use the above model name without suffix

APPROVED BY	SIGNATURE
/	
/	
/	

Please return 1 copy for your confirmation with your signature and comments.

APPROVED BY	SIGNATURE
J. Y. Lee / Manager	
REVIEWED BY	
J. S. Park / Manager	
PREPARED BY	
Y. G. Jeon / Engineer	
J. S. Kim / Engineer	
H. J. Lee / Engineer	

**Products Engineering Dept.
LG Display Co., Ltd**

Contents

Record of Revisions

Revision No	Revision Date	Page	Description	EDID version
0.0	Jan. 06. 2014	All	First Draft (Preliminary Specification)	0.0

Product Specification

1. General Description

 The LP140WH8 is a Color Active Matrix Liquid Crystal Display with an integral LED backlight system. The matrix employs a-Si Thin Film Transistor as the active element. It is a transmissive type display operating in the normally white mode. This TFT-LCD has 14.0 inches diagonally measured active display area with HD resolution (1366 horizontal by 768 vertical pixel array). Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 6-bit gray scale signal for each dot, thus, presenting a palette of more than 262,144 colors. The LP140WH8 has been designed to apply the interface method that enables low power, high speed, low EMI. The LP140WH8 is intended to support applications where thin thickness, low power are critical factors and graphic displays are important. In combination with the vertical arrangement of the sub-pixels, the LP140WH8 characteristics provide an excellent flat display for office automation products such as Notebook PC.

General Features

Active Screen Size	14.0 inches diagonal
Outline Dimension	320.4(H, typ) × 198.6(V, typ) × 3.6(D,max) [mm] (with PCB Board)
Pixel Pitch	0.2265mm × 0.2265 mm
Pixel Format	1366 horiz. by 768 vert. Pixels RGB strip arrangement
Color Depth	6-bit, 262,144 colors
Luminance, White	200 cd/m^2(Typ.)
Power Consumption	Total TBD (Typ.) Logic : TBDW (Typ.@ Mosaic), B/L : TBDW (Typ.@ VLED 12V)
Weight	310g (Max.)
Display Operating Mode	Normally white
Surface Treatment	Glare treatment of the front Polarizer
RoHS Compliance	Yes
BFR / PVC / As Free	Yes for all

Product Specification

2. Absolute Maximum Ratings

The following are maximum values which, if exceeded, may cause faulty operation or damage to the unit.

Table 1. ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Values		Units	Notes
		Min	Max		
Power Input Voltage	VCC	-0.3	4.0	V_{DC}	at 25 $\pm$ 2°C
Operating Temperature	TOP	0	50	°C	1
Storage Temperature	HST	-20	60	°C	1
Operating Ambient Humidity	HOP	10	90	%RH	1
Storage Humidity	HST	10	90	%RH	1

Note : 1. Temperature and relative humidity range are shown in the figure below.
     Wet bulb temperature should be 39°C Max, and no condensation of water.
Note : 2. Storage Condition is guaranteed under packing condition.

3-1. LCD Electrical Characteristics

Table 2. LCD ELECTRICAL CHARACTERISTICS

Parameter		Symbol	Min	Typ	Max	Unit	Notes
Power Supply Input Voltage		Vcc	3.0	3.3	3.6	V	1
Permissive Power Supply Input Ripple		VCCrp	-	-	100	mV$_{p-p}$	
Power Supply Input Current	Mosaic	Icc	-	TBD	TBD	mA	2
Power Consumption		Pcc	-	TBD	TBD	W	
Power Supply Inrush Current		Icc_P	-	-	1.5	A	3
Differential Impedance		Z$_{LVDS}$	90	100	110	Ω	

Note)
1. The measuring position is the connector of LCM and the test conditions are under 25℃, fv = 60Hz
2. The specified I$_{CC}$ current and power consumption are under the V$_{CC}$ = 3.3V , 25℃, fv = 60Hz condition and Mosaic pattern.

3. The V$_{CC}$ rising time is same as the minimum of T1 at Power on sequence.

Rising time
V$_{CC}$ 3.3V 90% 0V 10% 0.5ms

3-2. LED Backlight Electrical Characteristics

Table 3. LED B/L ELECTRICAL CHARACTERISTICS

Parameter		Symbol	Values			Unit	Notes
			Min	Typ	Max		
LED Power Input Voltage		V_{LED}	5.5	12.0	21.0	V	1
LED Power Input Current		I_{LED}	-	TBD	TBD	mA	2
LED Power Consumption		P_{LED}	-	TBD	TBD	W	
LED Power Inrush Current		I_{LED_P}	-	-	1.5	A	3
PWM Duty Ratio			5	-	100	%	4
PWM Jitter			0	-	0.2	%	5
PWM Frequency		F_{PWM}	200	-	1000	Hz	6
PWM	High Level Voltage	V_{PWM_H}	2.5	-	3.6	V	
	Low Level Voltage	V_{PWM_L}	0	-	0.3	V	
LED_EN	High Voltage	$V_{LED\_EN\_H}$	2.5	-	3.6	V	
	Low Voltage	$V_{LED\_EN\_L}$	0	-	0.3	V	
Life Time			12,000	-	-	Hrs	7

Note)

1. The measuring position is the connector of LCM and the test conditions are under 25℃.

2. The current and power consumption with LED Driver are under the V_{LED} = 12.0V , 25℃, PWM Duty 100% and White pattern with the normal frame frequency operated(60Hz).

3. The V_{LED} rising time is same as the minimum of T13 at Power on sequence.

12.0V

Rising time
VLED   90%

0V   10%

0.5ms

4. The operation of LED Driver below minimum dimming ratio may cause flickering or reliability issue.

5. If Jitter of PWM is bigger than maximum, it may induce flickering.

6. This Spec. is not effective at 100% dimming ratio as an exception because it has DC level equivalent to 0Hz. In spite of acceptable range as defined, the PWM Frequency should be fixed and stable for more consistent brightness control at any specific level desired.

7. The life time is determined as the time at which brightness of LCD is 50% compare to that of minimum value specified in table 7. under general user condition.

3-3. Interface Connections

Table 4. MODULE CONNECTOR PIN CONFIGURATION (CN1)

| Pin	Symbol	Description	Notes
1	NC Reserved	Reserved for LCD manufacturer's use	
2	VCC	LCD Logic and driver power (3.3V Typical)	
3	VCC	LCD Logic and driver power (3.3V Typical)	
4	V EDID	DDC power (3.3V)	
5	LCD Self Test or NC	LCD panel self test enable (optional) or No connection	
6	CLK EDID	DDC clock	
7	DATA EDID	DDC data	
8	X0-	Negative LVDS differential data input for pixel	
9	X0+	Positive LVDS differential data input for pixel	
10	GND	High speed ground	
11	X1-	Negative LVDS differential data input for pixel	
12	X1+	Positive LVDS differential data input for pixel	[Connector]
13	GND	High speed ground	Hirose, KN38-40S-0.5H
14	X2-	Negative LVDS differential data input for pixel	LSM, GT05Q-40S-H10
15	X2+	Positive LVDS differential data input for pixel	or equivalent
16	GND	High speed ground	
17	XC-	Negative LVDS differential clock input for pixel	
18	XC+	Positive LVDS differential clock input for pixel	[Connector pin arrangement]
19	GND or CEE	High speed ground (Color engine enable optional)	Pin 40 Pin 1
20	NC	No connection	
21	NC	No connection	
22	NC	No connection	
23	NC	No connection	
24	NC	No connection	
25	NC	No connection	
26	NC	No connection	
27	NC	No connection	[EDID & LGD P-Vcom Share pin]
28	NC	No connection	1. Pin for EDID & P-Vcom : #6, #7
29	NC	No connection	2. P-Vcom Address : 0101000x
30	NC	No connection	
31	BL_GND	LED Backlight ground	
32	BL_GND	LED Backlight ground	
33	BL_GND	LED Backlight ground	
34	NC Reserved	Reserved for LCD manufacture's use	
35	BL PWM	System PWM signal input for dimming	
36	BL ENABLE	LED Backlight on/off control	
37	DBC or NC	Dynamic Backlight control or No connection	
38	VLED	LED Backlight power (12V Typical)	
39	VLED	LED Backlight power (12V Typical)	
40	VLED	LED Backlight power (12V Typical)	

3-3. LVDS Signal Timing Specifications

3-3-1. DC Specification

Description	Symbol	Min	Typ	Max	Unit	Notes
LVDS Differential Voltage	$|V_{ID}|$	100	-	600	mV	-
LVDS Common mode Voltage	V_{CM}	$|V_{ID}|$ /2	1.2	VDD- $|V_{ID}|$/2	V	-
LVDS Input Voltage Range	V_{IN}	0.3	-	VDD	V	-

3-3-2. AC Specification

Description	Symbol	Min	Max	Unit	Notes
LVDS Clock to Data Skew Margin	t_{SKEW}	- 400	+ 400	ps	85MHz > Fclk ≥ 65MHz
	t_{SKEW}	- 600	+ 600	ps	65MHz > Fclk ≥ 25MHz
LVDS Clock to Clock Skew Margin (Even to Odd)	t_{SKEW_EO}	- 1/7	+ 1/7	T_{clk}	-
Maximum deviation of input clock frequency during SSC	F_{DEV}	-	± 3	%	-
Maximum modulation frequency of input clock during SSC	F_{MOD}	-	200	KHz	-

Product Specification

< Clock skew margin between channel >

< Spread Spectrum >

3-3-3. Data Format

1) LVDS 1 Port

< LVDS Data Format >

3-4. Signal Timing Specifications

This is the signal timing required at the input of the User connector. All of the interface signal timing should be satisfied with the following specifications and specifications of LVDS Tx/Rx for its proper operation.

Table 4. TIMING TABLE

| ITEM	Symbol		Min	Typ	Max	Unit	Note
DCLK	Frequency	f_{CLK}	-	76.3	-	MHz	
Hsync	Period	t_{HP}	1594	1610	1626	tCLK	
	Width	t_{WH}	24	32	40		
	Width-Active	t_{WHA}	1366	1366	1366		
Vsync	Period	t_{VP}	787	790	793	tHP	
	Width	t_{WV}	4	5	6		
	Width-Active	t_{WVA}	768	768	768		
Data Enable	Horizontal back porch	t_{HBP}	160	164	168	tCLK	
	Horizontal front porch	t_{HFP}	44	48	52		
	Vertical back porch	t_{VBP}	13	14	15	tHP	
	Vertical front porch	t_{VFP}	2	3	4		

Appendix) all reliabilities are specified for timing specification based on refresh rate of 60Hz. However, LP140WH8 has a good actual performance even at lower refresh rate (e.g. 40Hz or 50Hz) for power saving mode, whereas LP140WH8 is secured only for function under lower refresh rate. 60Hz at Normal mode, 50Hz, 40Hz at Power save mode. Don't care Flicker level (power save mode).

3-5. Signal Timing Waveforms

Condition : VCC =3.3V

Product Specification

3-6. Color Input Data Reference

The brightness of each primary color (red, green and blue) is based on the 6-bit gray scale data input for the color ; the higher the binary input, the brighter the color. The table below provides a reference for color versus data input.

Table 5. COLOR DATA REFERENCE

Color		Input Color Data																		
		RED						GREEN						BLUE						
		MSB					LSB	MSB					LSB	MSB					LSB
		R 5	R 4	R 3	R 2	R 1	R 0	G 5	G 4	G 3	G 2	G 1	G 0	B 5	B 4	B 3	B 2	B 1	B 0
Basic Color	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
RED	RED (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (01)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	…			…						…						…			
	RED (62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
GREEN	GREEN (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	GREEN (01)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	...			…						…						…			
	GREEN (62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	GREEN (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
BLUE	BLUE (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	BLUE (01)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	…			…						…						…			
	BLUE (62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	BLUE (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

3-7. Power Sequence

Power Supply Input
VCC

Interface Signal, V_i
LVDS

**LED BL
On/Off Control Signal**
LED_EN

**LED BL
Dimming Control Signal**
PWM

LED Driver Input Voltage
VLED

Table 6. POWER SEQUENCE TABLE

Symbol	Value			Units	Symbol	Value			Units
	Min	Typ	Max			Min	Typ	Max	
T_1	0.5	-	10	ms	T_8	10	-	-	ms
T_2	0	-	50	ms	T_9	0	-	-	ms
T_3	0	-	50	ms	T_{10}	0	-	-	ms
T_4	500	-	-	ms	T_{11}	10	-	-	ms
T_5	200	-	-	ms	T_{12}	0.5	-	10	ms
T_6	200	-	-	ms	T_{13}	0.5	-	10	ms
T_7	0.5	-	10	ms					

Note)
 1. Do not insert the mating cable when system turn on.
 2. Valid Data have to meet "3-3. LVDS Signal Timing Specifications"
 3. LVDS, LED_EN and PWM need to be on pull-down condition on invalid status.
 4. LGD recommend the rising sequence of VLED after the Vcc and valid status of LVDS turn on.

4. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable for approximately 20 minutes in a dark environment at 25°C. The values specified are at an approximate distance 50cm from the LCD surface at a viewing angle of Φ and Θ equal to 0°.

FIG. 1 presents additional information concerning the measurement equipment and method.

### FIG. 1 Optical Characteristic Measurement Equipment and Method

Optical Stage(x,y)　　**LCD Module**　　　　　　**Equipment**

1°

500mm±50mm

Table 7. OPTICAL CHARACTERISTICS

Ta=25°C, VCC=3.3V, fv=60Hz

Parameter		Symbol	Values			Units	Notes
			Min	**Typ**	**Max**		
Contrast Ratio		CR	400	500	-		1
Surface Luminance, white		L$_{WH}$	170	200	-	cd/m^2	2
Luminance Variation		δ WHITE (5P)	-	1.2	1.4	-	3
		δ WHITE(13P)	-	1.4	1.6		
Response Time		Tr + Tf	-	16	25	ms	4
Color Coordinates	RED	Rx		TBD			
		Ry		TBD			
	GREEN	Gx		TBD			
		Gy	Typical - 0.03	TBD	Typical + 0.03		
	BLUE	Bx		TBD			
		By		TBD			
	WHITE	Wx		0.313			
		Wy		0.329			
Viewing Angle	x axis, right(Φ=0°)	Θr	40	-	-	Degree	5
	x axis, left (Φ=180°)	Θl	40	-	-		
	y axis, up (Φ=90°)	Θu	10	-	-		
	y axis, down (Φ=270°)	Θd	30	-	-		
Gray Scale							6

G LG Display

Product Specification

Note)

1. It should be measured in the center of screen(1 Point). Contrast Ratio(CR) is defined mathematically as

$$\text{Contrast Ratio(1 Point)} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

2. Surface luminance is the average of 5 point across the LCD surface 50cm from the surface with all pixels displaying white. For more information see FIG 2.

$$L_{WH} = \text{Average}(1,2, \ldots 5 \text{ Point})$$

3. The variation in surface luminance , The panel total variation (δ WHITE) is determined by measuring N at each test position 1 through 13 and then defined as following numerical formula. For more information see FIG 2.

$$\delta \text{ WHITE (5P)} = \frac{\text{Maximum } (1,2, \ldots 5 \text{ Point})}{\text{Minimum } (1,2, \ldots 5 \text{ Point})} \qquad \delta \text{ WHITE (13P)} = \frac{\text{Maximum } (1,2, \ldots 13 \text{ Point})}{\text{Minimum } (1,2, \ldots 13 \text{ Point})}$$

4. Response time is the time required for the display to transition from white to black (rise time, Tr) and from black to white (falling time, Tf). For additional information see FIG 3.

5. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 4.

6. Gray scale specification

Gray Level	Luminance [%] (Typ)
L0	TBD
L7	TBD
L15	TBD
L23	TBD
L31	TBD
L39	TBD
L47	TBD
L55	TBD
L63	100

FIG. 2 Luminance

<Measuring point for Average Luminance & measuring point for Luminance variation>


H,V : ACTIVE AREA
A : H/4 mm
B : V/4 mm
POINTS: 13 POINTS

FIG. 3 Response Time

The response time is defined as the following figure and shall be measured by switching the input signal for "black" and "white".

**FIG. 4 Viewing angle**

<Dimension of viewing angle range>

$\phi = 90°$, Up
$\phi = 180°$ Left'
$\phi = 0°$ Right'
$\phi = 270°$ Down'

5. Mechanical Characteristics

The contents provide general mechanical characteristics for the model LP140WH8. In addition the figures in the next page are detailed mechanical drawing of the LCD.

Outline Dimension	Horizontal	320.4 ± 0.5mm
	Vertical	198.6 ± 0.5mm (With PCB)
	Thickness	3.6mm (max)
Bezel Area	Horizontal	312.60 ± 0.5mm
	Vertical	177.10 ± 0.5mm
Active Display Area	Horizontal	309.40 mm
	Vertical	173.95 mm
Weight	310g (Max.)	
Surface Treatment	Hard Coating(3H), Glare treatment of the front polarizer	

<Outline Dimension : With PCB Board>

Product Specification

<FRONT VIEW>   Note) Unit:[mm], General tolerance: ± 0.5mm

LG Display

Product Specification

<REAR VIEW>   Note) Unit:[mm], General tolerance: ± 0.5mm

 - This model is produced from both site, LGD NJ, eMPS. Label format in this page represents EMPS products.

6. Reliability

Environment test condition

No.	Test Item	Conditions
1	High temperature storage test	Ta= 60°C, 240h
2	Low temperature storage test	Ta= -20°C, 240h
3	High temperature operation test	Ta= 50°C, 50%RH, 240h
4	Low temperature operation test	Ta= 0°C, 240h
5	Vibration test (non-operating)	Random, 1.0Grms, 10 ~ 300Hz(PSD 0.0035) 3 axis, 30min/axis
6	Shock test (non-operating)	- No functional or cosmetic defects following a shock to all 6 sides delivering at least 180 G in a half sine pulse no longer than 2 ms to the display module - No functional defects following a shock delivering at least 200 g in a half sine pulse no longer than 2 ms to each of 6 sides. Each of the 6 sides will be shock tested with one each display, for a total of 6 displays
7	Altitude operating storage / shipment	0 ~ 10,000 feet (3,048m) 24Hr 0 ~ 40,000 feet (12,192m) 24Hr

{ Result Evaluation Criteria }
There should be no change which might affect the practical display function when the display quality test is conducted under normal operating condition.

G LG Display

7. International Standards

7-1. Safety

    a) UL 60950-1, Underwriters Laboratories Inc.
      Information Technology Equipment - Safety - Part 1 : General Requirements.
    b) CAN/CSA-C22.2 No. 60950-1-07, Canadian Standards Association.
      Information Technology Equipment - Safety - Part 1 : General Requirements.
    c) EN 60950-1, European Committee for Electro technical Standardization (CENELEC).
      Information Technology Equipment - Safety - Part 1 : General Requirements.
    d) IEC 60950-1, The International Electro technical Commission (IEC).
      Information Technology Equipment - Safety - Part 1 : General Requirements

7-2. Environment

    a) RoHS, Directive 2011/65/EU of the European Parliament and of the council of 8 June 2011

Product Specification

8. Packing

8-1. Designation of Lot Mark

a) Lot Mark

A	B	C	D	E	F	G	H	I	J	K	L	M

A,B,C : SIZE(INCH)   D : YEAR

E : MONTH   F ~ M : SERIAL NO.

Note

1. YEAR

Year	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020
Mark	A	B	C	D	E	F	G	H	J	K

2. MONTH

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Mark	1	2	3	4	5	6	7	8	9	A	B	C

b) Location of Lot Mark

  Serial No. is printed on the label. The label is attached to the backside of the LCD module.
This is subject to change without prior notice.

8-2. Packing Form

a) Package quantity in one box : 30pcs

b) Box Size : 478mm X 365mm X 288mm

9. PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD module.

9-1. MOUNTING PRECAUTIONS

(1) You must mount a module using holes arranged in four corners or four sides.
(2) You should consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
(3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to the resist external force.
(4) You should adopt radiation structure to satisfy the temperature specification.
(5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
(6) Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment.
  Do not touch the surface of polarizer for bare hand or greasy cloth.(Some cosmetics are detrimental to the polarizer.)
(7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
(8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
(9) Do not open the case because inside circuits do not have sufficient strength.
(10) When handling the LCD module, it needs to handle with care not to give mechanical stress to the PCB and Mounting Hole area."

9-2. OPERATING PRECAUTIONS

(1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage :
  V=± 200mV(Over and under shoot voltage)

(2) Response time depends on the temperature.(In lower temperature, it becomes longer.)
(3) Brightness depends on the temperature. (In lower temperature, it becomes lower.)
  And in lower temperature, response time(required time that brightness is stable after turned on) becomes longer.
(4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
(5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
(6) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference.

9-3. ELECTROSTATIC DISCHARGE CONTROL

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

9-4. PRECAUTIONS FOR STRONG LIGHT EXPOSURE

Strong light exposure causes degradation of polarizer and color filter.

9-5. STORAGE

When storing modules as spares for a long time, the following precautions are necessary.

(1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
(2) The polarizer surface should not come in contact with any other object.
   It is recommended that they be stored in the container in which they were shipped.

9-6. HANDLING PRECAUTIONS FOR PROTECTION FILM

(1) When the protection film is peeled off, static electricity is generated between the film and polarizer.
   This should be peeled off slowly and carefully by people who are electrically grounded and with well
   ion-blown equipment or in such a condition, etc.
(2) The protection film is attached to the polarizer with a small amount of glue. If some stress is applied
   to rub the protection film against the polarizer during the time you peel off the film, the glue is apt to
   remain on the polarizer.
   Please carefully peel off the protection film without rubbing it against the polarizer.
(3) When the module with protection film attached is stored for a long time, sometimes there remains a
   very small amount of glue still on the polarizer after the protection film is peeled off.
(4) You can remove the glue easily. When the glue remains on the polarizer surface or its vestige is
   recognized, please wipe them off with absorbent cotton waste or other soft material like chamois
   soaked with normal-hexane.

9-7. THE LGD QA RESPONSIBILITY WILL BE AVOIDED IN CASE OF BELOW

(1) When the customer attaches TSM(Touch Sensor Module) on LCM without Supplier's approval.
(2) When the customer attaches cover glass on LCM without Supplier's approval.
(3) When the LCMs were repaired by 3rd party without Supplier's approval.
(4) When the LCMs were treated like Disassemble and Rework by the Customer and/or Customer's
   representatives without supplier's approval.

Product Specification

LGD Proposal for system cover design.(Appendix)

1	Gap check for securing the enough gap between LCM and System back cover.

◆ **a : min 0mm**
◆ **b : min 0.3mm, Max 1.0mm**

Define	1.Rear side of LCM is sensitive against external stress, and previous check about interference is highly needed.
	2.In case there is something from system cover comes into the boundary above,mechanical interference may cause the FOS defects. (Eg: Ripple, White spot..)

2	Check if antenna cable is sufficiently apart from T-CON of LCD Module.

OK **NG**

| Define	1.If system antenna is overlapped with T-CON,it might be cause the noise

LGD Proposal for system cover design.(Appendix)

3	Checking the path of the System wire

Wire

NG

OK

Define	1.If Wire path overlapped with LCM, it is happened white spot, COF problem, etc.
	2.OK ➔ Wire path design to system side. NG ➔ Wire path overlapped with LCM.

4	Add pad to Prevent panel crack against external load (push)

Pad   Back cover

Boss

flange

LCM

PAD

boss

Back cover

push

Pad   boss

Back cover

OK

push

crack   boss

Back cover

NG

Define	1. At flat type LCM, panel is easily cracked at flange area during push, assemble.
	2. Add pad, it prevent panel crack

LGD Proposal for system cover design.(Appendix)

5	Check the rib or Bracket on back cover

LCM
Back cover
OK
Rib

LCM
Back cover
OK
Bracket

LCM
Back cover
NG

LCM
Back cover
CO

Define	1.It is necessary that the height of back cover rib or bracket is higher than LCM height. It can prevent direct compression of panel at LCM edge.
	2."¬" shape bracket is stronger than "I" shape one.

6	Check the gap between front cover and LCM(glass)

a
Front cover

LCM

Back cover

[OK] a ≥ 0.3mm
[CO] 0.3mm ≥ a ≥ 0.1mm
[NG] a ≤ 0.1mm

Define	1. Ripple can be happened by little gap between glass and front cover.

Product Specification

LGD Proposal for system cover design.(Appendix)

7	Check the rib or Bracket on back cover

OK **NG**

Define	1.If it is possible, shrink to apply front cover of white color.
	2. White color can caused light leakage

8	Check the wire position(path)

OK

NG

Define	1. It is necessary that wire is posited out of hook, not posited near hook,.
	2. If wire is posited near hook, it can be happened assemble error and panel crack during assemble front cover

LGD Proposal for system cover design.(Appendix)

9	Check mouse pad (touch pad) depth and shape of edge

Mouse pad

a

[OK] a ≤ 0.3mm
[CO] 0.5mm ≥ a ≥ 0.3mm
[NG] a ≥ 0.5mm

OK   NG

Define	1.Mouse pad step is deep, it is caused panel crack by external load.
	2. The edge shape must be smooth.

10	Check the step of keyboard area

Keyboard

Keyboard

push

push

crack

OK   NG

Define	1. The step of keyboard at the side edge of main body, it is caused panel crack

Product Specification

APPENDIX A. LGD Proposal for system cover design

11	Check the gap [PCB ~ system]

a ≥ 0.5mm [at max dimension of design]
a ≥ 1.0mm [at typical dimension of design]

Define	1. Gap is too small, FPC is easily cracked by interference and repetitive bending. (circuit is opened) .
	2. Gap is must be kept more than 0.5mm(max dim.) and 1.0mm(typ dim.) .

12	System rib (on A cover)

OK

NG

a ≥ 0.5mm [at max dimension of design]
a ≥ 1.0mm [at typical dimension of design]

Define	1. Gap is too small and rib is too short, panel is easily cracked by external stress.
	2. Gap is must be kept more than 0.5mm(max dim.) and 1.0mm(typ dim.) .
	3. The figure of rib is continuous or fully long.

Product Specification

APPENDIX C. Enhanced Extended Display Identification Data (EEDID™) 1/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments	Value (Hex)	Value (Bin)
Header	0	00	Header	00	00000000
	1	01	Header	FF	11111111
	2	02	Header	FF	11111111
	3	03	Header	FF	11111111
	4	04	Header	FF	11111111
	5	05	Header	FF	11111111
	6	06	Header	FF	11111111
	7	07	Header	00	00000000
Vendor / Product EDID Version	8	08	ID Manufacture Name LGD	30	00110000
	9	09	ID Manufacture Name	E4	11100100
	10	0A	ID Product Code 033Fh	3F	00111111
	11	0B	(Hex. LSB first)	03	00000011
	12	0C	ID Serial No. - Optional ("00h" If not used, Number Only and LSB First)	00	00000000
	13	0D	ID Serial No. - Optional ("00h" If not used, Number Only and LSB First)	00	00000000
	14	0E	ID Serial No. - Optional ("00h" If not used, Number Only and LSB First)	00	00000000
	15	0F	ID Serial No. - Optional ("00h" If not used, Number Only and LSB First)	00	00000000
	16	10	Week of Manufacture - Optinal 00 weeks	00	00000000
	17	11	Year of Manufacture 2014 years	18	00011000
	18	12	EDID structure version # = 1	01	00000001
	19	13	EDID revision # = 4	04	00000100
Display Parameters	20	14	Video input Definition = Input is a Digital Video signal Interface , Colo Bit Depth : 6 Bits per Primary Color , Digital Video Interface Standard Supported: Digital Interface is not defined	90	10010000
	21	15	Horizontal Screen Size (Rounded cm) = 31 cm	1F	00011111
	22	16	Vertical Screen Size (Rounded cm) = 17 cm	11	00010001
	23	17	Display Transfer Characteristic (Gamma) = (gamma*100)-100 = Example:(2.2*100)-100=120	78	01111000
	24	18	Feature Support [Display Power Management(DPM) : Standby Mode is supported, Suspend Mode is not supported, Active Off = Very Low Power is supported ,Supportted Color Encoding Formats : RGB 4:4:4 & YCrCb 4:4:4 ,Other Feature Support Flags : No_sRGB, Preferred Timing Mode, No_Display is continuous frequency (Multi-mode_Base EDID and Extension Block).]	EA	11101010
Panel Color Coordinates	25	19	Red/Green Low Bits (RxRy/GxGy)	00	00000000
	26	1A	Blue/White Low Bits (BxBy/WxWy)	05	00000101
	27	1B	Red X Rx = 00	00	00000000
	28	1C	Red Y Ry = 00	00	00000000
	29	1D	Green X Gx = 00	00	00000000
	30	1E	Green Y Gy = 00	00	00000000
	31	1F	Blue X Bx = 00	00	00000000
	32	20	Blue Y By = 00	00	00000000
	33	21	White X Wx = 0.313	50	01010000
	34	22	White Y Wy = 0.329	54	01010100
Established Timings	35	23	Established timing 1 (Optional_00h if not used)	00	00000000
	36	24	Established timing 2 (Optional_00h if not used)	00	00000000
	37	25	Manufacturer's timings (Optional_00h if not used)	00	00000000
Standard Timing ID	38	26	Standard timing ID1 (Optional_01h if not used)	01	00000001
	39	27	Standard timing ID1 (Optional_01h if not used)	01	00000001
	40	28	Standard timing ID2 (Optional_01h if not used)	01	00000001
	41	29	Standard timing ID2 (Optional_01h if not used)	01	00000001
	42	2A	Standard timing ID3 (Optional_01h if not used)	01	00000001
	43	2B	Standard timing ID3 (Optional_01h if not used)	01	00000001
	44	2C	Standard timing ID4 (Optional_01h if not used)	01	00000001
	45	2D	Standard timing ID4 (Optional_01h if not used)	01	00000001
	46	2E	Standard timing ID5 (Optional_01h if not used)	01	00000001
	47	2F	Standard timing ID5 (Optional_01h if not used)	01	00000001
	48	30	Standard timing ID6 (Optional_01h if not used)	01	00000001
	49	31	Standard timing ID6 (Optional_01h if not used)	01	00000001
	50	32	Standard timing ID7 (Optional_01h if not used)	01	00000001
	51	33	Standard timing ID7 (Optional_01h if not used)	01	00000001
	52	34	Standard timing ID8 (Optional_01h if not used)	01	00000001
	53	35	Standard timing ID8 (Optional_01h if not used)	01	00000001

Product Specification

APPENDIX C. Enhanced Extended Display Identification Data (EEDID™)   2/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
Timing Descriptor #1	54	36	Pixel Clock/10,000 (LSB)	76.3 MHz @ 60 Hz	CE	11001110
	55	37	Pixel Clock/10,000 (MSB)		1D	00011101
	56	38	Horizontal Active (HA) (lower 8 bits)	1366 pixels	56	01010110
	57	39	Horizontal Blanking (HB) (lower 8 bits)	244 pixels	F4	11110100
	58	3A	Horizontal Active (HA) / Horizontal Blanking (HB) (upper 4:4bits)		50	01010000
	59	3B	Vertical Avtive (VA)	768 lines	00	00000000
	60	3C	Vertical Blanking (VB) (DE Blanking typ.for DE only panels)	22 lines	16	00010110
	61	3D	Vertical Active (VA) / Vertical Blanking (VB) (upper 4:4bits)		30	00110000
	62	3E	Horizontal Front Porch in pixels (HF) (lower 8 bits)	48 pixels	30	00110000
	63	3F	Horizontal Sync Pulse Width in pixels (HS) (lower 8 bits)	32 pixels	20	00100000
	64	40	Vertical Front Porch in lines (VF) : Vertical Sync Pluse Width in lines (VS) (lower 4 bits) 3 lines : 5 lines		35	00110101
	65	41	Horizontal Front Porch/ Sync Pulse Width/ Vertical Front Porch/ Sync Pulse Width (upper 2bits)		00	00000000
	66	42	Horizontal Vedio Image Size (mm) (lower 8 bits)	310 mm	36	00110110
	67	43	Vertical Vedio Image Size (mm) (lower 8 bits)	174 mm	AE	10101110
	68	44	Horizontal Image Size / Vertical Image Size (upper 4 bits)		10	00010000
	69	45	Horizontal Border = 0 (Zero for Notebook LCD)		00	00000000
	70	46	Vertical Border = 0 (Zero for Notebook LCD)		00	00000000
	71	47	Non-Interlace, Normal display, no stereo, Digital Separate [Vsync_NEG, Hsync_NEG (outside of V-sync)]		19	00011001
Timing Descriptor #2	72	48	Flag		00	00000000
	73	49	Flag		00	00000000
	74	4A	Flag		00	00000000
	75	4B	Data Type Tag (Descriptor Defined by manufacturer)		00	00000000
	76	4C	Flag		00	00000000
	77	4D	Descriptor Defined by manufacturer		00	00000000
	78	4E	Descriptor Defined by manufacturer		00	00000000
	79	4F	Descriptor Defined by manufacturer		00	00000000
	80	50	Descriptor Defined by manufacturer		00	00000000
	81	51	Descriptor Defined by manufacturer		00	00000000
	82	52	Descriptor Defined by manufacturer		00	00000000
	83	53	Descriptor Defined by manufacturer		00	00000000
	84	54	Descriptor Defined by manufacturer		00	00000000
	85	55	Descriptor Defined by manufacturer		00	00000000
	86	56	Descriptor Defined by manufacturer		00	00000000
	87	57	Descriptor Defined by manufacturer		00	00000000
	88	58	Descriptor Defined by manufacturer		00	00000000
	89	59	Descriptor Defined by manufacturer		00	00000000
Timing Descriptor #3	90	5A	Flag		00	00000000
	91	5B	Flag		00	00000000
	92	5C	Flag		00	00000000
	93	5D	Data Type Tag (Alphanumeric Data String (ASCII String))		FE	11111110
	94	5E	Flag		00	00000000
	95	5F	Alphanumeric Data String (ASCII String)	L	4C	01001100
	96	60	Alphanumeric Data String (ASCII String)	G	47	01000111
	97	61	Alphanumeric Data String (ASCII String)		20	00100000
	98	62	Alphanumeric Data String (ASCII String)	D	44	01000100
	99	63	Alphanumeric Data String (ASCII String)	i	69	01101001
	100	64	Alphanumeric Data String (ASCII String)	s	73	01110011
	101	65	Alphanumeric Data String (ASCII String)	p	70	01110000
	102	66	Alphanumeric Data String (ASCII String)	l	6C	01101100
	103	67	Alphanumeric Data String (ASCII String)	a	61	01100001
	104	68	Alphanumeric Data String (ASCII String)	y	79	01111001
	105	69	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		0A	00001010
	106	6A	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		20	00100000
	107	6B	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		20	00100000

Product Specification

APPENDIX C. Enhanced Extended Display Identification Data (EEDID™)   3/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
Timing Descriptor #4	108	6C	Flag		00	00000000
	109	6D	Flag		00	00000000
	110	6E	Flag		00	00000000
	111	6F	Data Type Tag (Alphanumeric Data String (ASCII String))		FE	11111110
	112	70	Flag		00	00000000
	113	71	Alphanumeric Data String (ASCII String)	L	4C	01001100
	114	72	Alphanumeric Data String (ASCII String)	P	50	01010000
	115	73	Alphanumeric Data String (ASCII String)	1	31	00110001
	116	74	Alphanumeric Data String (ASCII String)	4	34	00110100
	117	75	Alphanumeric Data String (ASCII String)	0	30	00110000
	118	76	Alphanumeric Data String (ASCII String)	W	57	01010111
	119	77	Alphanumeric Data String (ASCII String)	H	48	01001000
	120	78	Alphanumeric Data String (ASCII String)	8	38	00111000
	121	79	Alphanumeric Data String (ASCII String)	-	2D	00101101
	122	7A	Alphanumeric Data String (ASCII String)	T	54	01010100
	123	7B	Alphanumeric Data String (ASCII String)	L	4C	01001100
	124	7C	Alphanumeric Data String (ASCII String)	A	41	01000001
	125	7D	Alphanumeric Data String (ASCII String)	1	31	00110001
Checksum	126	7E	Extension flag (# of optional 128 panel ID extension block to follow, Typ = 0)		00	00000000
	127	7F	Check Sum (The 1-byte sum of all 128 bytes in this panel ID block shall = 0)		45	01000101