



Doc. Version	0.0
Total Page	18
Date	2011/05/18

# Product Specification

## 7" COLOR TFT-LCD MODULE

**MODEL NAME: C070VW04 VB**

< ◆ > Preliminary Specification

<   > Final Specification

Note: The content of this specification is subject to change.

© 2011 AU Optronics  
All Rights Reserved,  
Do Not Copy.



Version 0.0

Page: 2/18

## Record of Revision

Version	Revise Date	Page	Content
0.0	2011/5/18		First draft.

For Zihuan Internal Use Only

## Contents

<b>A. General Description .....</b>	<b>4</b>
<b>B. Features .....</b>	<b>4</b>
<b>C. Physical Specifications.....</b>	<b>5</b>
<b>D. Outline Dimension –.....</b>	<b>6</b>
<b>E. Electrical Specifications .....</b>	<b>7</b>
1. Pin Assignment .....	7
Connector= HRS FH28D-60S-0.5SH(05) .....	7
2. Absolute Maximum Ratings.....	8
3. Electrical Characteristics .....	8
a. TFT- LCD Panel .....	8
b. Backlight Driving Conditions (Note 1) .....	9
4. AC Timing .....	10
a. Power on/off sequence.....	10
b. Timing Condition .....	11
c. Timing Diagram (DE Mode) .....	12
d. Timing Diagram (HV Mode) .....	13
<b>F. Optical specifications (Note 1, 2).....</b>	<b>14</b>
<b>G. Reliability Test Items (Note 2).....</b>	<b>16</b>
<b>H. Packing Form .....</b>	<b>17</b>

## A. General Description

C070VW04 VB is an a-Si type Thin Film Transistor Liquid crystal Display (TFT-LCD) with AMVA-Mobile (Advanced MVA) technology. This model is composed of a TFT-LCD, a driver, an FPC (flexible printed circuit), and a backlight unit . TCON (timing controller) is also embedded in source driver.


## B. Features

- 7-inch (15:9) display
- 800RGB x 480 resolution in RGB stripe dot arrangement
- High brightness
- Interfaces: parallel RGB 18-bit
- Advanced MVA -- wide view technology
- RoHs compliance

## C. Physical Specifications

NO.	Item	Unit	Specification	Remark
1	Display Resolution	dot	800 RGB (H)×480(V)	
2	Active Area	mm	152.4(H)×91.44(V)	
3	Screen Size	inch	7(Diagonal)	
4	Dot Pitch	mm	0.0635(H)×RGBx0.1905(V)	
5	Color Configuration	--	R. G. B. Stripe	Note 1
6	Color Depth	--	262K Colors	
7	Overall Dimension	mm	164.55(H) × 105.01(V) × 6.67(T)	Note 2
8	Weight	g	146	
9	Display Mode	--	Normally Black	
10	Surface Treatment		AG	

Note 1: Below figure shows dot stripe arrangement.



Note 2: Not including FPC. Please refer to the drawing in page 6 for further information.



## E. Electrical Specifications

### 1. Pin Assignment

Connector=HRS FH28D-60S-0.5SH(05)

No.	Pin Name	I/O	Description	Remarks
1	VCOM	PI	Common electrode driving voltage	
2	VGH	PI	Positive power supply voltage for TFT	
3	VGL	PI	Negative power supply voltage for TFT	
4	VDD	PI	Digital power supply voltage.	
5	GND	G	Ground	
6	V1	I	Gamma correction voltage	
7	V2	I	Gamma correction voltage	
8	V3	I	Gamma correction voltage	
9	V4	I	Gamma correction voltage	
10	V5	I	Gamma correction voltage	
11	V6	I	Gamma correction voltage	
12	V7	I	Gamma correction voltage	
13	V8	I	Gamma correction voltage	
14	V9	I	Gamma correction voltage	
15	V10	I	Gamma correction voltage	
16	V11	I	Gamma correction voltage	
17	V12	I	Gamma correction voltage	
18	V13	I	Gamma correction voltage	
19	V14	I	Gamma correction voltage	
20	AVDD	PI	Analog power supply voltage	
21	AVDD	PI	Analog power supply voltage	
22	GND	G	Ground	
23	VS	I	Vertical Sync input	
24	HS	I	Horizontal Sync input	
25	DE	I	Data Enable Input (High Active)	
26	DCLK	I	Data clock Input	
27	GND	G	Ground	
28	DB5	I	Blue data input(MSB)	
29	DB4	I	Blue data input	
30	DB3	I	Blue data input	
31	DB2	I	Blue data input	
32	DB1	I	Blue data input	
33	DB0	I	Blue data input(LSB)	
34	DG5	I	Green data input (MSB)	
35	DG4	I	Green data Input	
36	DG3	I	Green data Input	
37	DG2	I	Green data Input	
38	DG1	I	Green data Input	
39	DG0	I	Green data Input (LSB)	
40	DR5	I	Red data input (MSB)	
41	DR4	I	Red data input	
42	DR3	I	Red data Input	
43	DR2	I	Red data Input	
44	DR1	I	Red data Input	
45	DR0	I	Red data Input (LSB)	
46	Mode	I	DE/SYNC mode selection. "H" for DE mode. "L" for HV mode.	
47	STBYB	I	Standby mode. "H" for normal operation. "L" for standby mode.	
48	RSTB	I	Global reset pin. (low active)	
49	GND	G	Ground	
50	V-COM	PI	Common electrode driving voltage	
51	GND	G	Ground	

52	GND	G	Ground	
53	GND	G	Ground	
54	GND	G	Ground	
55	GND	G	Ground	
56	GND	G	Ground	
57	GND	G	Ground	
58	GND	G	Ground	
59	GND	G	Ground	
60	GND	G	Ground	

I: Digital signal input, O: Digital signal output, G: GND, PI: Power input

## 2. Absolute Maximum Ratings

Items	Symbol	Values		Unit	Condition
		Min.	Max.		
Power Voltage	VDD	-0.3	4.5	V	
	AVDD	-0.5	13.5	V	
	VGH	-0.3	20	V	
	VGL	-15	0.3	V	
	VGH-VGL	0	35	V	
Input Signal Voltage	Vi	-0.3	Vdd+ 0.3	V	
	Vref(V1~V7)	0.4AVDD	AVDD-0.3	V	
	Vref(V8~V14)	0.1	0.6AVDD	V	
	VCOM	-0.3	10	V	
Operation Temperature	Topa	-30	+85	°C	Ambient
Storage Temperature	Tstg	-40	+95	°C	Ambient
LED	Vf	-0.5	16	V	
	If	0	90	mA	

Note 1: Functional operation should be restricted under normal ambient temperature.

## 3. Electrical Characteristics

The following items are measured under stable condition and suggested application circuit.

### a. TFT- LCD Panel

Parameter	Symbol	Min	Typ	Max	Unit	Notes
Power Supply	VDD	3.1	3.3	3.5	V	
	IVDD	--	6.7	8.7	mA	
	AVDD	V1+0.1	12.5	13.5	V	
	IAVDD	-	26	34	mA	
	VGH	14.5	15	15.5	V	
	IVGH	-	0.15	0.2	mA	
	VGL	-9.5	-9	-8.5	V	
	IVGL	-	0.2	0.3	mA	
	VCOM	5.22	5.42	5.62	V	
	IVCOM	-	0.3	0.65	uA	
Input Signal Voltage	Vi	-0.3	-	Vdd+ 0.3	V	
	Vref(V1~V7)	0.4AVdd	-	AVdd-0.3	V	
	Vref(V8~V14)	0.1	-	0.6AVdd	V	
Input high voltage	Vh	0.7Vdd	-	Vdd	V	
Input low voltage	VI	0	-	0.3Vdd	V	
Vertical cycle	f <sub>V</sub>	50	60	80	Hz	
Horizontal cycle	f <sub>H</sub>	28.9	31.5	42	kHz	
Dot Frequency	f <sub>DCLK</sub>		33.3	45	MHz	



## b. Recommend Gamma Voltage

Parameter	Symbol	Min	Typ	Max	Unit	Notes
Gamma Voltage	V1	-	12.23	-	V	
	V2	-	11.70	-	V	
	V3	-	10.46	-	V	
	V4	-	9.84	-	V	
	V5	-	9.41	-	V	
	V6	-	8.65	-	V	
	V7	-	6.80	-	V	
	V8	-	6.40	-	V	
	V9	-	4.45	-	V	
	V10	-	3.68	-	V	
	V11	-	3.16	-	V	
	V12	-	2.49	-	V	
	V13	-	1.07	-	V	
	V14	-	0.27	-	V	

## c. Backlight Driving Conditions (Note 1)


Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark
LED Supply Current	$I_L$	-	80	85	mA	single serial (Note 3)
LED Supply Voltage	$V_L$	-	(14)	16	V	Note 3
LED Life Time	$L_L$	10000	---	---	Hr	Note 2

Note 1: LED backlight is 12 LEDs (3strings,4pcs for each string).

Note 2: The LED lifetime 10000hrs means , after normal use at 80mA, under +25 ° C, the brightness decreases to 50% of original level.

Note 3: The LED supply power is for 3 string of LED.

Note 4: The voltage capacity of LED driver IC must be over max. of LED Voltage




## 4. AC Timing

### a. Power on/off sequence

The LCD adopts high voltage driver IC, so it could be permanently damaged under a wrong power on/off sequence. The suggested LCD power sequence is below:


**Power on sequence:**

**VDD -> GRB -> STBYB -> Digital input (Data/DCLK/DE) -> AVDD -> VGL -> VGH -> BLKEN**



### Power-Off

**STBYB -> BLKEN -> VGH -> VGL -> Digital input (Data/DCLK/DE)&Power(VDD/AVDD)**



**DEN** : Defined a frame period and created internally by DE. It is similar vertical sync.

**GRB** : Global reset ,normally pulled high.

Suggest to connecting with an RC reset circuit for stability .Normally pull high.

**STBYB** : Standby mode, normally pulled high.


STBYB ="1" , normal operation

STBYB="0",timing controller, source driver will turn off, all output are High-Z


## b. Timing Condition

Item	Symbol	Min	Typ	Max	Unit	Remark
Clock frequency	dclk	-	33.3	45	MHZ	
DCLK cycle time	Tdclk	22	30	-	ns	
DCLK pulse duty	Tcwh	40	50	60	%	
Vertical display area	Tvd	480	480	480	H	
Vertical period area	Tv	522	525	762	H	
Vertical blanking area	Tvb	42	45	282	H	
Vertical pulse width	Tvw	-	3	-	H	
Vertical back porch	Tve	-	32	-	H	
Vertical front porch	Tvf	10	13	250	H	
Horizontal display area	Thd	800	800	800	dclk	
Horizontal period area	Th	910	1056	1138	dclk	
Horizontal blanking area	Thb	110	256	338	dclk	
Horizontal pulse width	Thw	1	1	-	dclk	
Horizontal back porch	The	88	88	88	dclk	
Horizontal front porch	Thf	22	168	250	dclk	
Data setup time	Tds	8	-	-	ns	
Data hold time	Tdh	8	-	-	ns	


### c. Timing Diagram (DE Mode) Vertical Timing of Input



### Horizontal Timing of Input




### Clock and Data Timing of Input




#### d. Timing Diagram (HV Mode)

##### Vertical Timing of Input



##### Horizontal Timing of Input



## F. Optical specifications (Note 1, 2)


Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Response Time Rise Fall	Tr Tf	$\theta = 0^\circ$	- -	10 25	15 30	ms ms	Note 3
Contrast ratio	CR	At optimized viewing angle	800	1500	-		Note 4, 5, 6
Viewing Angle Top Bottom Left Right		$CR \geq 10$	75 75 75 75	80 80 80 80	- - - -	deg.	Note 7, 8
Brightness	$Y_L$	$\theta = 0^\circ$	390	450	-	cd/m <sup>2</sup>	Note 9
White Chromaticity	X	$\theta = 0^\circ$	0.268	0.318	0.368		Note 8
	Y	$\theta = 0^\circ$	0.273	0.323	0.373		
Uniformity		-	80	-	-	%	Note 10

Note 1: Measurement should be performed in the dark room, optical ambient temperature  $\approx 25^\circ\text{C}$ , and backlight current  $I_L = 80\text{ mA}$

Note 2: To be measured on the center area of panel with a field angle of  $1^\circ$  by Topcon luminance meter BM-7, after 10 minutes operation.

Note 3: Definition of response time:

The output signals of photo detector are measured when the input signals are changed from "black" to "white" ( $T_r$ , Rising time) and from "white" to "black" ( $T_f$ , Falling time), respectively.



Note 4: From liquid crystal characteristics, response time will become slower and the color of panel will become darker when ambient temperature is below  $25^\circ\text{C}$ .

$$\text{Contrast ratio} = \frac{\text{Photo detector output when LCD is at "White" state}}{\text{Photo detector output when LCD is at "Black" state}}$$

Note 5: Contrast ratio is calculated with the following formula.

Note 6: White  $V_i = V_{i50} \mp 1.5\text{V}$

Black  $V_i = V_{i50} \pm 2.0\text{V}$


“±” means that the analog input signal swings in phase with COM signal.

“∓” means that the analog input signal swings out of phase with COM signal.

Vi50 :The analog input voltage when transmission is 50%

The 100% transmission is defined as the transmission of LCD panel when all the input terminals of module are electrically opened.


Note 7. Definition of viewing angle: refer to figure as below.



Note 8. The viewing angles are measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.

Note 9. Brightness is measured at the center of the display with white pattern in 80mA.

Note 10. Luminance Uniformity is defined as following within the 9 measurements (L1~L9),  
Luminance Uniformity(%) = Minimum luminance(brightness)/Maximum luminance(brightness)



## G. Reliability Test Items (Note 2)

No.	Test items	Conditions		Remark
1	High temperature storage	Ta= 95℃	240Hrs	Note1
2	Low temperature storage	Ta= -40℃	240Hrs	
3	High temperature operation	Ta= 85℃	240Hrs	
4	Low temperature operation	Ta= -30℃	240Hrs	Note1, 3
5	High temperature and high humidity	Ta= 60℃ , 90% RH	240Hrs	Operation
6	Heat shock	-30℃~85℃/100 cycles 1Hrs/cycle		Non-operation
7	Electrostatic discharge	Contact = ± 8 kV, class B (R=330Ω ,C=150pF) Air = ± 15 kV, class B (R=330Ω ,C=150pF) ,10 times for each terminal		Operation (Note 4)
8	Vibration	Frequency range	8~33.3Hz	JIS D1601,A10 Condition A
		Stoke	1.3mm	
		Sweep	2.9G, 33.3~400Hz	
		Cycle	15min.	
		2 hours for each direction of X, Z 4 hours for Y direction		
9	Mechanical shock	100G, 6ms, ±X,±Y,±Z 3 times for each direction		
10	Vibration (with carton)	Random vibration: 0.015G <sup>2</sup> /Hz from 5~200Hz -6dB/Octave from 200~500Hz		IEC 68-34
11	Drop (with carton)	Height: 60cm 1 corner, 3 edges, 6 surfaces		

Note 1: Ta: Ambient temperature.

Note 2: In the standard condition, there is not display function NG issue occurred. All the cosmetic specification is judged before the reliability stress.



Note 3: Short time operation between -40℃~-30℃ doesn't provide full performance but a correct image on the LCD. The LCD is guaranteed to suffer no permanent damage.

Note 4: Test techniques follow IEC61000-4-2 standard




## H. Packing Form and Marking

### 1. Packing Form



MAX. CAPACITY: 40 MODULES  
MAX. WEIGHT: 15 kg  
CARTON MEAS. 520mm\*340mm\*250mm



## 2. Module/Panel Label Information

The module/panel (collectively called as the "Product") will be attached with a label of Shipping Number which represents the identification of the Product at a specific location. Refer to the Product outline drawing for detailed location and size of the label. The label is composed of a 22-digit serial number with the following definition:

### ABCDEFGHIJKLMNQRSTU

- For internal system usage and production serial numbers.
- AUO Module or Panel factory code, represents the final production factory to complete the Product
- Product version code, ranging from 0~9 or A~Z (for Version after 9)
- Week Code, the production week when the product is finished at its production process

Example:

501M06ZL06123456781Z05:

Product Manufacturing Week Code: WK50

Product Version: Version 1

Product Manufacturing Factory: L3A (The manufacturing site at Taiwan)

Note:

1. M06: The manufacturing site in Taiwan
2. S16: The manufacturing site in Xiamen

## 3. Carton Label Information

The packing carton will be attached with a carton label where packing Q'ty, AUO Model Name, AUO Part Number, Customer Part Number (Optional) and a series of Carton Number in 13 or 14 digits are printed. The Carton Number is appearing in the following format:

### ABC-DEFG-HIJK-LMN

- DEFG appear after first "-" represents the packing date of the carton
  - Date from 01 to 31
  - Month, ranging from 1~9, A~C. A for Oct, B for Nov and C for Dec.
  - A.D. year, ranging from 1~9 and 0. The single digit code represents the last number of the year

Refer to the drawing of packing format for the location and size of the carton label.