

**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF BOE BJ AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE BJ AND MUST BE RETURNED TO BOE BJ UPON ITS REQUEST

SPEC. NUMBER
S8-64-8B-027

PRODUCT GROUP
TFT-LCD

Rev.
P3

ISSUE DATE
2018.12.21

PAGE
1 OF 29

EV156FHM-N10
Product Specification
Rev. P3

HEFEI XINSHENG OPTOELECTRONICS TECHNOLOGY CO.,LTD

BOE	PRODUCT GROUP		REV	ISSUE DATE
	TFT- LCD PRODUCT		P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification			PAGE 2 OF 29
REVISION HISTORY				
REV.	ECN No.	DESCRIPTION OF CHANGES	DATE	PREPARED
P0	-	Initial Release	2016.6.7	杨通/何宗泽
P1	-	Update Optical Specifications	2016.7.22	杨通/何宗泽
P2	-	Correct Reliability Test Table & Power consumption	2016.8.4	杨通/何宗泽
P3	-	Update Reliability Test Table	2018.12.21	LI

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 3 OF 29	

Contents


No.	Items	Page
	REVISION HISTORY	2
	CONTENTS	3
1.0	General Description	4
2.0	Absolute Maximum ratings	6
3.0	Electrical specifications.	7
4.0	Optical specifications.	10
5.0	Interface Connection	15
6.0	Signal Timing Specification	18
7.0	Input Signals, Display Colors & Gray Scale of Colors	20
8.0	Power Sequence	21
9.0	Connector description	22
10.0	Mechanical Characteristics	23
11.0	Reliability Test	24
12.0	Handling & Cautions.	24
13.0	Label	25
14.0	Packing information	27
15.0	Mechanical Outline Dimension	28
16.0	EDID Table	30

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 4 OF 29	

1.0 GENERAL DESCRIPTION

1.1 Introduction

EV156FHM-N10 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 15.6 inch diagonally measured active area with FHD resolutions (1920 horizontal by 1080vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical Stripe and this module can display 16,777,216 colors. The TFT-LCD panel used for this module is a low reflection and higher color type. Therefore, this module is suitable for Notebook PC. The LED Driver for back-light driving is built in this model. All input signals are eDP1.2 interface compatible.



1.2 Features

- I 2 lane eDP Interface with 2.7Gbps Link Rates
- I Thin and light weight
- I 6-bit + Hi-FRC color depth, display 16.7M colors
- I Single LED Lighting Bar. (Down side/Horizontal Direction)
- I Green Product (RoHS & Halogen free product)
- I On board LED Driving circuit
- I Low driving voltage and low power consumption
- I On board EDID chip

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 5 OF 29	

1.3 Application

I Notebook PC (Wide type)

1.4 General Specification

The followings are general specifications at the model EV156FHM-N10-5850 . (listed in Table 1.)

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	344.16 (H) × 193.59 (V)	mm	
Number of pixels	1920 (H) × 1080 (V)	pixels	
Pixel pitch	0.17925 (H) X 0.17925 (V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	16.7M	colors	
Display mode	Normally Black		
Dimensional outline	363.8(H)(Typ)*215.9V) (Typ)(W/PCB)*9.9(Max)	mm	
Weight	850 (max)	g	
Surface treatment	AG		
Back-light	Lower Down side, 1-LED Lighting Bar type		
Power consumption	P _D : 2.3 (max)	W	@RGB Pattern
	P _{BL} :5.7 (max)	W	
	P _{total} :8.0(max)	W	

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 6 OF 29	

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings>

Ta=25+/-2°C

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	-0.3	4.0	V	Note 1
Logic Supply Voltage	V _{IN}	V _{SS} -0.3	V _{DD} +0.3	V	
Operating Temperature	T _{OP}	0	+60	°C	Note 2
Storage Temperature	T _{ST}	-20	+60	°C	

- Notes : 1. Permanent damage to the device may occur if maximum values are exceeded functional operation should be restricted to the condition described under normal operating conditions.
2. Temperature and relative humidity range are shown in the figure below.
95 % RH Max. (40 °C ≥ Ta)
Maximum wet - bulb temperature at 39 °C or less. (Ta > 40 °C) No condensation.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 7 OF 29	

3.0 ELECTRICAL SPECIFICATIONS

3.1 Electrical Specifications

< Table 3. Electrical specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	3.0	3.3	3.6	V	Note 1
Permissible Input Ripple Voltage	V _{RF}	-	-	100	mV	At V _{DD} = 3.3V
Power Supply Current	I _{DD}	-	300	-	mA	Note 1
Differential Input Voltage	V _{ID}	200	-	600	mV	
Power Consumption	P _D	-	1.0	2.3	W	Note 1
	P _{BL}	-	-	5.7	W	Note 2
	P _{total}	-	-	8.0	W	

Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.
The current draw and power consumption specified is for 3.3V at 25°C.

a) Typ : Mosaic Pattern

b) Max : R/G/B Pattern



2. Calculated value for reference (V_{LED} × I_{LED})

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 8 OF 29	

3.2 Backlight Unit

< Table 4. LED Driving guideline specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
LED Forward Voltage	V _F	-	3.0	3.2	V	-
LED Forward Current	I _F	-	50	-	mA	-
LED Power Consumption	P _{LED}		-	5.7	W	Note 1
LED Life-Time	N/A	50,000	-	-	Hour	Note2
Power supply voltage for LED Driver	V _{LED}	10.8	12	13.2	V	
EN Control Level	Backlight on	2.5		5.0	V	
	Backlight off	0		0.8	V	
PWM Control Level	PWM High Level	2.5		5.0	V	
	PWM Low Level	0		0.8	V	
PWM Control Frequency	F _{PWM}	120	-	1,000	Hz	
Duty Ratio	-	10	-	100	%	


Notes : 1. Power supply voltage 12V for LED Driver

Calculator Value for reference $I_F \times V_F \times 32 / \text{efficiency} = P_{LED}$

2. The LED Life-time define as the estimated time to 50% degradation of initial luminous@25°C。

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification		PAGE 9 OF 29

3.3 LED structure



BOE	PRODUCT GROUP		REV	ISSUE DATE
	TFT- LCD PRODUCT		P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification			PAGE 10 OF 29

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25 \pm 2^\circ\text{C}$) with the equipment of Luminance meter system (Goniometer system and PR730) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and ϕ equal to 0° . We refer to $\theta\phi=0$ ($=\theta_3$) as the 3 o'clock direction (the "right"), $\theta\phi=90$ ($=\theta_{12}$) as the 12 o'clock direction ("upward"), $\theta\phi=180$ ($=\theta_9$) as the 9 o'clock direction ("left") and $\theta\phi=270$ ($=\theta_6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or ϕ , the center of the measuring spot on the Display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be $3.3 \pm 0.3\text{V}$ at 25°C . Optimum viewing angle direction is 6 'clock.

4.2 Optical Specifications

<Table 5. Optical Specifications>

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	Θ_3	CR > 10	-	85	-	Deg.	Note 1
		Θ_9		-	85	-	Deg.	
	Vertical	Θ_{12}		-	85	-	Deg.	
		Θ_6		-	85	-	Deg.	
Luminance Contrast ratio		CR	$\Theta = 0^\circ$	-	800			Note 2
Luminance of White	9 Points	Y_w	$\Theta = 0^\circ$ $I_{LED} = 50mA$	425	500	-	cd/m ²	Note 3
White Luminance uniformity	9 Points	$\Delta Y9$		75	80	-		Note 4
White Chromaticity		x_w	$\Theta = 0^\circ$	0.283	0.313	0.343		Note 5
		y_w		0.299	0.329	0.359		
Reproduction of color	Red	x_R	$\Theta = 0^\circ$	-0.03	0.616	+0.03		
		y_R			0.339			
		x_G			0.313			
	Green	y_G			0.582			
		Blue			x_B		0.156	
	y_B				0.134			
	Gamut							
Response Time (Rising + Falling)		T_{RT}	Ta= 25° C $\Theta = 0^\circ$	-	30	35	ms	Note 6
Cross Talk		CT	$\Theta = 0^\circ$	-	-	2.0	%	Note 7

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 11 OF 29	

Notes :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).

2. Contrast measurements shall be made at viewing angle of $\Theta = 0$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state .
(see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

4. The White luminance uniformity on LCD surface is then expressed as : $\Delta Y = \text{Minimum Luminance of 9 points} / \text{Maximum Luminance of 9 points}$.
(see FIGURE 2).

5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.


6. The electro-optical response time measurements shall be made as FIGURE 3 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_r , and 90% to 10% is T_d .

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark.
(See FIGURE 4).

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 12 OF 29	


4.3 Optical measurements

Figure 1. Measurement Set Up



Optical characteristics measurement setup


Figure 2. White Luminance and Uniformity Measurement Locations (9 points)



Center Luminance of white is defined as luminance values of center 9 points across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 13 OF 29	


Figure 3. Response Time Testing



The electro-optical response time measurements shall be made as shown in FIGURE 3 by switching the “data” input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is Td and 90% to 10% is Tr.

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification		PAGE 14 OF 29

Figure 4. Cross Modulation Test Description



Where:

Y_A = Initial luminance of measured area (cd/m²)

Y_B = Subsequent luminance of measured area (cd/m²)

The location measured will be exactly the same in both patterns

Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (YB) of that same area when any adjacent area is driven dark (Refer to FIGURE 4).

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 15 OF 29	

5.0 INTERFACE CONNECTION.

5.1 Electrical Interface Connection


The electronics interface connector is STM MSAK24025P30 or Compatible.
The connector interface pin assignments are listed in Table 6.

<Table 6. Pin Assignments for the Interface Connector>

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	NC	No Connection
2	H_GND	Ground
3	LANE1_N	eDP RX channel 1 negative
4	LANE1_P	eDP RX channel 1 positive
5	H_GND	Ground
6	LANE0_N	eDP RX channel 0 negative
7	LANE0_P	eDP RX channel 0 positive
8	H_GND	Ground
9	AUX_CH_P	eDP AUX CH positive
10	AUX_CH_N	eDP AUX CH negative
11	H_GND	Ground
12	LCD_VCC	Power Supply, 3.3V (typ.)
13	LCD_VCC	Power Supply, 3.3V (typ.)
14	LCD_Self_Test	Panel self test enable
15	H_GND	Ground
16	H_GND	Ground
17	HPD	Hot plug detect output
18	BL_GND	LED Ground
19	BL_GND	LED Ground
20	BL_GND	LED Ground
21	BL_GND	LED Ground
22	BL_ENABLE	LED enable pin(+3.3V Input)
23	BL_PWM	System PWM Signal Input
24	NC	No Connection
25	NC	No Connection
26	BL_POWER	LED Power Supply 12V
27	BL_POWER	LED Power Supply 12V
28	BL_POWER	LED Power Supply 12V
29	BL_POWER	LED Power Supply 12V
30	NC	No Connection

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 16 OF 29	

5-2. eDP Interface



Note. Transmitter : HX8876-G04 or equivalent.
Transmitter is not contained in Module.

5.3.eDP Input signal

Lane 0	Lane 1
R0-5:0 G0-5:4	R1-5:0 G1-5:4
G0-3:0 B0-5:2	G1-3:0 B1-5:2
B0-1:0 R2-5:0	B1-1:0 R3-5:0
G2-5:0 B2-5:4	G3-5:0 B3-5:4
B2-3:0 R4-5:2	B3-3:0 R5-5:2
R4-1:0 G4-5:0	R5-1:0 G5-5:0
B4-5:0 R6-5:4	B5-5:0 R7-5:4
R6-3:0 G6-5:2	R7-3:0 G7-5:2
R6-1:0 G6-5:0	R7-1:0 G7-5:0

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 17 OF 29	

5.4 Back-light & LCM Interface Connection

Interface Connector: **STM MSA24046P6E**

<Table 7. Pin Assignments for the BLU & LCM Connector>

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	LEDP	LED anode connection	6	LED4	LED cathode connection
2	LEDP	LED anode connection	-	-	-
3	LED1	LED cathode connection	-	-	-
4	LED2	LED cathode connection	-	-	-
5	LED3	LED cathode connection	-	-	-

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 18 OF 29	

6.0 SIGNAL TIMING SPECIFICATION

6.1 The EV156FHM-N10 is operated by the DE only.

Item		Symbols	Min	Typ	Max	Unit
Clock	Frequency	1/Tc	100	141.4	160	MHz
	High Time	Tch	-	4/7	-	Tc
	Low Time	Tcl	-	3/7	-	Tc
Frame Period		Tv	1090	1100	1238	lines
			-	60	-	Hz
			-	16.7	-	ms
Vertical Display Period		Tvd	-	1080	-	lines
One line Scanning Period		Th	2080	2142	2400	clocks
Horizontal Display Period		Thd	-	1920	-	clocks

Note※: This Module can support low frame refresh rate 50Hz & 40Hz.


BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 19 OF 29	

6.2 eDP Rx Interface Timing Parameter

The specification of the eDP Rx interface timing parameter is shown in Table 8.

<Table 8. eDP Rx Interface Timing Specification>

Item	Symbol	Min	Typ	Max	Unit	Remark
Spread spectrum clock	ssc		0.5		%	
Differential peak-to-peak input voltage at package pins	VRX-DIFFp-p	100	0	1320	mV	
Rx input DC common mode voltage	VRX_DC_CM	-	GND	-	V	
Differential termination resistance	RRX-DIFF	80	-	100	Ω	
Single-ended termination resistance	RRX-SE	40	-	60	Ω	
Rx short circuit current limit	IRX_SHORT	-	-	20	mA	
Intra-pair skew at Rx package pins (HBR) RX intra-pair skew tolerance at HBR	LRX_SKEW_INTRA_PAIR	-	-	150	ps	



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 20 OF 29	


7.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

	Colors & Gray scale	Data signal																	
		R0	R1	R2	R3	R4	R5	G0	G1	G2	G3	G4	G5	B0	B1	B2	B3	B4	B5
Basic colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Light Blue	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Purple	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray scale of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△ ▽	↑ ↓						↑ ↓						↑ ↓					
	Brighter	1	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	▽	0	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Gray scale of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0
	△ ▽	↑ ↓						↑ ↓						↑ ↓					
	Brighter	0	0	0	0	0	0	1	0	1	1	1	1	0	0	0	0	0	0
	▽	0	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Gray scale of Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0
	△ ▽	↑ ↓						↓ ↓						↑ ↓					
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
Gray scale of White & Black	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0
	Darker	0	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0
	△ ▽	↑ ↓						↑ ↓						↑ ↓					
	Brighter	1	0	1	1	1	1	1	0	1	1	1	1	1	0	1	1	1	1
	▽	0	1	1	1	1	1	0	1	1	1	1	1	0	1	1	1	1	1
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 21 OF 29	

8.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



- 0.5ms ≤ T1 ≤ 10 ms
- 0ms ≤ T2 ≤ 200 ms
- 0ms ≤ T3 ≤ 200 ms
- 0ms ≤ T13
- 0ms ≤ T14
- 0ms ≤ T17
- 0ms ≤ T7 ≤ 50ms
- 0ms ≤ T10 ≤ 500 ms
- 0 ms ≤ T11 ≤ 10 ms
- 150ms ≤ T12
- 0ms ≤ T15
- 0ms ≤ T16
- 0ms ≤ T18

Notes:

- When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
- Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 22 OF 29	

9.0 Connector Description

Physical interface is described as for the connector on LCM.

These connectors are capable of accommodating the following signals and will be following components.

9.1 TFT LCD Module

Connector Name /Description	For Signal Connector
Manufacturer	STM
Type/ Part Number	MSAK24025P30
Mating housing/ Part Number	I-PEX 20454-030T

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 23 OF 29	

10.0 MECHANICAL CHARACTERISTICS

10.1 Dimensional Requirements

FIGURE 6 shows mechanical outlines for the model EV156FHM-N10-5850 .
Other parameters are shown in Table 9.

<Table 9. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	344.16 (H) × 193.59(V)	
Number of pixels	1920 (H) X 1080 (V) (1 pixel = R + G + B dots)	
Pixel pitch	0.17925 (H) X 0.17925 (V)	mm
Pixel arrangement	RGB Vertical stripe	
Display colors	16.7M	
Display mode	Normally Black	
Dimensional outline	363.8(H)(Typ)*215.9(V)(Typ) (W/PCB)*9.9(Max)	mm
Weight	850(Max)	gram
Back Light	Connector :7083k-F06N-04L	
	LED, Horizontal-LED Array type	

10.2 Mounting

See FIGURE 6.

10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an AG coating to minimize reflection and a coating to reduce scratching.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 24 OF 29	

11.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 10. Reliability test>

No	Test Items	Conditions
1	High temperature storage test	Ta = 60 °C , 240 hrs
2	Low temperature storage test	Ta = -20 °C , 240 hrs
3	High temperature & high humidity operation test	Ta = 50 °C , 80%RH, 240 hrs
4	High temperature operation test	Ta =60 °C , 240 hrs
5	Low temperature operation test	Ta = 0 °C , 240 hrs
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle
7	Vibration test (non-operating)	1.5G, 10~500Hz,Half Sine X,Y,Z / Sweep rate : 1 hour
8	Shock test (non-operating)	220G, Half Sine Wave 2msec ± X, ± Y, ± Z Once for each direction
9	Electro-static discharge test (non-operating)	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV

12.0 HANDLING & CAUTIONS

(1) Cautions when taking out the module

Ỗ Pick the pouch only, when taking out module from a shipping package.

(2) Cautions for handling the module

Ỗ As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.

Ỗ As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.

Ỗ As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.

Ỗ Do not pull the interface connector in or out while the LCD module is operating.

Ỗ Put the module display side down on a flat horizontal plane.

Ỗ Handle connectors and cables with care.

(3) Cautions for the operation

Ỗ When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.

Ỗ Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 25 OF 29	

(4) Cautions for the atmosphere

Y Dew drop atmosphere should be avoided.

Y Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.

(5) Cautions for the module characteristics

Y Do not apply fixed pattern data signal to the LCD module at product aging.

Y Applying fixed pattern for a long time may cause image sticking.

(6) Other cautions

Y Do not disassemble and/or re-assemble LCD module.

Y Do not re-adjust variable resistor or switch etc.

Y When returning the module for repair or etc., Please pack the module not to be broken.
We recommend to use the original shipping packages.

13.0 LABEL


(1) MDL label



Digit Code	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
Code	S	L	S	5	1	2	3	5	9	4	2	0	0	0	1	D	B
Description	Model Code /GBN		Grade	Line	Year		Month	Model Extension Code (Last 4 Digits Of FGCD)				Serial No 00001-ZZZZZZ					

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 26 OF 29	

(2) High voltage caution label

	HIGH VOLTAGE CAUTION	COLD CATHODE FLUORESCENT LAMP IN LCD PANEL CONTAINS A SMALL AMOUNT OF MERCURY. PLEASE FOLLOW LOCAL OR- DINANCES OR REGULATIONS FOR DISPOSAL.
	RISK OF ELECTRIC SHOCK. DISCONNECT THE ELECTRIC POWER BEFORE SERVICING	

(3) Box label

Label Size: 110 mm (L) × 55 mm (W)

Contents

Model: EV156FHM-N10

Q`ty: Module Q`ty in one box

Serial No.: Box Serial No.

Date: Packing Date

Internal use of Product


HEFEI XINSHENG OPTOELECTRONICS TECHNOLOGY Co., LTD													
MODEL:	XXXXXXXX-XXX	①	QTY:	XX	②								
SERIAL NO:	XXXXXXXXXXXXXX	③	DATE:	XXXXXX/XX	④								
<div>Box ID bar code</div>													
XXXX-XXXXXX	⑤	XXXX	⑥	XXXX	⑦	<div>(QA)</div>							

Digit	1	2	3	4	5	6	7	8	9	10	11	12	13
Code	S	L	S	5	1	2	3	D	0	0	0	6	8
Description	Products GBN		Grade	Line	Year		Month	Revision Code	SerialNo				

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 27 OF 29	

15.0 PACKING INFORMATION


15.1 Packing order



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 28 OF 29	

16.0 MECHANICAL OUTLINE DIMENSION

Figure 6. TFT-LCD Module Outline Dimension (Front View)



<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P3	2018.12.21
SPEC. NUMBER S8-64-8B-027	SPEC. TITLE EV156FHM-N10 Product Specification	PAGE 29 OF 29	

Figure 7. TFT-LCD Module Outline Dimensions (Rear view)

