




Product Specification

AU OPTRONICS CORPORATION

() Preliminary Specifications

(V) Final Specifications

Module	14.0"(13.97") HD 16:9 Color TFT-LCD with LED Backlight design
Model Name	B140XTT01.2 (HW:0A)
Note ()	<i>e-TP Display</i> (LCM : B140XTN06.2 + TP : I140FGT04.1 CT40)

Customer	Date
Checked & Approved by	Date
Note: This Specification is subject to change without notice.	

Approved by	Date
<u>Jonken Fan</u>	<u>08/15/2014</u>
Prepared by	Date
<u>AmandaHJLiao</u>	<u>08/15/2014</u>
NBBU Marketing Division AU Optronics corporation	



Contents

1. Handling Precautions.....	4
2. General Description.....	5
2.1 General Specification.....	5
2.2 General Touch Specification	7
2.3 Optical Characteristics	8
3. Functional Block Diagram.....	13
4. Absolute Maximum Ratings.....	14
4.1 Absolute Ratings of TFT LCD Module	14
4.2 Absolute Ratings of Touch Sensor.....	14
4.3 Absolute Ratings of Environment.....	14
5. Electrical Characteristics.....	15
5.1 TFT LCD Module	15
5.2 Backlight Unit.....	18
5.3 Touch Sensor.....	19
6. Signal Interface Characteristic	21
6.1 Pixel Format Image.....	21
6.2 Integration Interface Requirement	22
6.3 Interface Timing	25
6.4 Power ON/OFF Sequence	27
7. Panel Reliability Test.....	30
7.1 Vibration Test	30
7.2 Shock Test	30
7.3 Reliability Test.....	30
8. Mechanical Characteristics	31
8.1 Total Solution Outline Dimension	31
9. Shipping and Package	33
9.1 Shipping Label Format.....	33
9.2 Carton Package	33
9.3 Shipping Package of Palletizing Sequence	34
10. Appendix: EDID Description	35



Product Specification

AU OPTRONICS CORPORATION

Record of Revision

Version and Date	Page	Old description	New Description	Remark
1.0 2014/08/15	All	Final Spec		



1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 10) After installation of the TFT Module into an enclosure (Notebook PC Bezel, for example), do not twist nor bend the TFT Module even momentarily. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 11) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 12) Disconnecting power supply before handling LCD modules, it can prevent electric shock, DO NOT TOUCH the electrode parts, cables, connectors and LED circuit part of TFT module that a LED light bar build in as a light source of back light unit. It can prevent electrostatic breakdown.

2. General Description

B140XTT01.2 is a Color Active Matrix Liquid Crystal Display composed of a TFT LCD panel, a driver circuit, and LED backlight system. The screen format is intended to support the 16:9 HD, 1366(H) x 768(V) screen and 262k colors (RGB 6-bits data driver) with LED backlight driving circuit. All input signals are eDP interface compatible.

B140XTT01.2 is designed for a display unit of notebook style personal computer and industrial machine.

2.1 General Specification

The following items are characteristics summary on the table at 25 °C condition:

Items	Unit	Specifications			
Screen Diagonal	[mm]	354.95			
Active Area	[mm]	309.4 x 173.95			
Pixels H x V		1366x3(RGB) x 768			
Pixel Pitch	[mm]	0.2265 x 0.2265			
Pixel Format		R.G.B. Vertical Stripe			
Display Mode		A Normally White			
White Luminance (ILED=23mA) (Note: ILED is LED current)	[cd/m ²]	200 typ. (5 points average) 170 min. (5 points average)			
Luminance Uniformity		1.25 max. (5 points)			
Contrast Ratio		500 typ			
Response Time	[ms]	8 typ / 16 Max			
Nominal Input Voltage VDD	[Volt]	+3.3 typ.			
Power Consumption	[Watt]	3.4max (Include Logic at Black pattern and Blu power)			
Weight	[Grams]	295g max (Panel Only) 405g max (Total Solution) ¹			
Physical Size	[mm]		Min.	Typ.	Max.
		Length	325.93	326.18	326.43
		Width	204.60	205.10	205.60
		Thickness	-	-	3.0 (Panel Side) 3.0 (PCBA Side)

¹ Total solution max weight includes touch sensor FPCA and OGS.



Product Specification

AU OPTRONICS CORPORATION

Total solution [Note: OGS Touch module]	[mm]		Min.	Typ.	Max.
		Length	325.93	326.18	326.43
		Width	204.60	205.10	205.60 (206.94 with FPCA)
		Thickness	-	-	3.95 (Panel Side) 3.8 (PCBA Side) 5.0 (Total)
Electrical Interface		1 Lane eDP 1.2			
Glass Thickness	[mm]	0.4			
Surface Treatment		Glare, Hardness 3H			
Support Color		262K colors (RGB 6-bit)			
Temperature Range	[°C] [°C]	-20 to +60			
Operating		-20 to +60			
Storage (Non-Operating)					
RoHS Compliance		RoHS Compliance			



2.2 General Touch Specification

Item	Spec	Unit
Type of Touch Sensor	Projective Capacitive (OGS)	
Panel Size	14.0'	
Outline Dimension	321.10 X 185.9 typ	mm
Total Thickness	0.7 typ	mm
Total Weight	120 max	g
TP View Area	310.40 X 174.95 typ	mm
TP Active Area	311.40 X 175.93 typ	mm
Interface	USB	
Report Rate	Follow win8 – 100Hz	Hz
Multi-Touch Point	10 points	
Input method	Finger	
Touch panel sensor IC	Elan (eKTH3915)	
Channel	72 x 41	
Distance between 2 point	Follow win8 – 13	mm
Surface hardness	7	H
TP F/W version	Q3915S-DH011USC(11.12)	
TP Power Consumption	Active Mode: 162	mW
	Idle Mode: 108	mW
	Sleep Mode: 1	mW



Product Specification


AU OPTRONICS CORPORATION

2.3 Optical Characteristics


The optical characteristics are measured under stable conditions at 25°C (Room Temperature) :

Item		Symbol	Conditions	Min.	Typ.	Max.	Unit	Note
White Luminance ILED=23mA (Base Panel Only)			5 points average	170	200	-	cd/m2	1, 4, 5.
Viewing Angle		θR	Horizontal (Right) CR = 10 (Left)	40	45	-	degree	4, 9
		θL		40	45	-		
		ψH	Vertical (Upper) CR = 10 (Lower)	10	15	-		
ψL	30	35		-				
Luminance Uniformity		δ5P	5 Points	-	-	1.25		1, 3, 4
Luminance Uniformity		δ13P	13 Points	-	-	1.6		2, 3, 4
Contrast Ratio		CR		400	500	-		4, 6
Cross talk		%				4		4, 7
Response Time		TRT	Rising + Falling	-	8	16		
Color / Chromaticity Coodinates	Red	Rx	CIE 1931	0.55	0.58	0.61		4
		Ry		0.305	0.335	0.365		
	Green	Gx		0.3	0.33	0.36		
		Gy		0.535	0.565	0.595		
	Blue	Bx		0.125	0.155	0.185		
		By		0.11	0.14	0.17		
	White	Wx		0.283	0.313	0.343		
		Wy		0.299	0.329	0.359		
		NTSC		%	-	45		

Note 1: 5 points position (Ref: Active area)



Note 2: 13 points position (Ref: Active area)



Note 3: The luminance uniformity of 5 or 13 points is defined by dividing the maximum luminance values by the minimum test point luminance


$$\delta_{W5} = \frac{\text{Maximum Brightness of five points}}{\text{Minimum Brightness of five points}}$$

$$\delta_{W13} = \frac{\text{Maximum Brightness of thirteen points}}{\text{Minimum Brightness of thirteen points}}$$

Note 4: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting

Backlight for 30 minutes in a stable, windless and dark room, and it should be measured in the center of screen.



Note 5 : Definition of Average Luminance of White (Y_L):

Measure the luminance of gray level 63 at 5 points , $Y_L = [L(1) + L(2) + L(3) + L(4) + L(5)] / 5$

$L(x)$ is corresponding to the luminance of the point X at Figure in Note (1).

Note 6 : Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$


Note 7 : Definition of Cross Talk (CT)

$$CT = |Y_B - Y_A| / Y_A \times 100 (\%)$$

Where


Y_A = Luminance of measured location without gray level 0 pattern (cd/m²)

Y_B = Luminance of measured location with gray level 0 pattern (cd/m²)




Note 8: Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are changed from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval between the 10% and 90% of amplitudes. Refer to figure as below.




Note 9. Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° (θ) horizontal left and right and 90° (Φ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



3. Functional Block Diagram



4. Absolute Maximum Ratings

An absolute maximum rating of the module is as following:

4.1 Absolute Ratings of TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	Vin	-0.3	+4.0	[Volt]	Note 1,2

4.2 Absolute Ratings of Touch Sensor

Item	Symbol	Rating	Unit	Conditions
Voltage from VCCIO to AGND and DGND	-	+4.0	[Volt]	-
Voltage from any pin to AGND and DGND	-	+4.0	[Volt]	-

4.3 Absolute Ratings of Environment


Item	Symbol	Min	Max	Unit	Conditions
Operating Temperature	TOP	0	+50	[°C]	Note 4
Operation Humidity	HOP	5	95	[%RH]	Note 4
Storage Temperature	TST	-20	+60	[°C]	Note 4
Storage Humidity	HST	10	90	[%RH]	Note 4

Note 1: At Ta (25°C)

Note 2: Permanent damage to the device may occur if exceed maximum values

Note 3: LED specification refer to section 5.2

Note 4: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).



5. Electrical Characteristics

5.1 TFT LCD Module

5.1.1 Power Specification


Input power specifications are as follows;

The power specification are measured under 25°C and frame frequency under 60Hz

Symble	Parameter	Min	Typ	Max	Units	Note
VDD	Logic/LCD Drive Voltage	3.0	3.3	3.6	[Volt]	
PDD	VDD Power	-	0.6	--	[Watt]	Note 1
IDD	IDD Current	-	0.2	--	[mA]	Note 1
IRush	Inrush Current	-	-	1500	[mA]	Note 2
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	100	[mV] p-p	

Note 1 : Maximum Measurement Condition : White Pattern at 3.3V driving voltage. ($P_{max}=V_{3.3} \times I_{white}$)

Note 2 : Measure Condition



5.1.2 Signal Electrical Characteristics


Signal electrical characteristics are as follows;

Display Port main link signal:

Differential pair VD+ , VD-
Which is one Display port
Main link

VCM of Display port
Main link

$$V_{diffP-P} = [(V_{D+}) - (V_{D-})] \times 2$$




Display port main link					
		Min	Typ	Max	unit
VCM	RX input DC Common Mode Voltage		GND		V
VDiff _{P-P}	Peak-to-peak Voltage at a receiving Device	100		1320	mV

Follow as VESA display port standard V1.1a

Display Port AUX_CH signal:

Differential AUX+ , AUX-
Which is Display port AUX_CH





Product Specification

AU OPTRONICS CORPORATION

Display port AUX_CH					
		Min	Typ	Max	unit
VCM	AUX DC Common Mode Voltage		GND		V
VDiff _{P-P}	AUX Peak-to-peak Voltage at a receiving Device	320	--	1360	mV

Follow as VESA display port standard V1.1a.

Display Port VHPD signal:

Display port VHPD					
		Min	Typ	Max	unit
VHPD	HPD Voltage	2.25	--	3.6	V

Follow as VESA display port standard V1.1a.

5.2 Backlight Unit

5.2.1 LED characteristics

Parameter	Symbol	Min	Typ	Max	Units	Condition
Backlight Power Consumption	PLED	-	2.0	--	[Watt]	(Ta=25°C), Note 1
LED Life-Time	N/A	15,000	-	-	Hour	(Ta=25°C), Note 2

Note 1: Calculator value for reference $P_{LED} = V_F$ (Normal Distribution) * I_F (Normal Distribution) / Efficiency

Note 2: The LED life-time define as the estimated time to 50% degradation of initial luminous.

5.2.2 Backlight input signal characteristics

Parameter	Symbol	Min	Typ	Max	Units	Remark
LED Power Supply	VLED (Note 1)	5.5	12	21	[Volt]	Define as Connector Interface (Ta=25°C)
LED Enable Input High Level	VLED_EN	1.8	--	--	[Volt]	
LED Enable Input Low Level		--	--	0.5	[Volt]	
PWM Logic Input High Level	VPWM_EN	1.8	--	--	[Volt]	
PWM Logic Input Low Level		--	--	0.5	[Volt]	
PWM Input Frequency	FPWM	200	--	10000	Hz	
PWM Duty Ratio	Duty	1	--	100	%	

Note 1 : Recommend system pull up/down resistor no bigger than 10kohm

Note 2 : measured in panel VIN

Note 3 : If the PWM duty ratio(min) is set between 5% to 1% , the PWM input frequency should be set below 1KHz .

The brightness-duty characteristic might not be able to keep in it's linearity if the dimming control is operated in 1% to 5% range.

5.3 Touch Sensor

5.3.1 Power Specification

Items	Symbol	Specifications			Unit	Notes
		Min.	Typ.	Max.		
Touch Panel Power Supply	VTSP	4.5	5	5.5	V	Ripple <100mV
Touch Panel Power Voltage	VCCIO	1.8	3.3	3.6	V	
Input voltage	VIH	$VCCIO \times 0.7$	-	VCCIO	V	
	VIL	0	-	$VCCIO \times 0.3$	V	
Normal mode Current consumption @ Report rate 100Hz	INORMAL	-	-	45	mA	
Idle mode Current consumption	IIDLE	-	-	30	mA	
Sleep mode Current consumption	ISLEEP	-	60	130	uA	


Note:



5.3.2 Touch Sensor TP_EN

TP_EN	TP Function
H	Ok
L	No function
NC	Ok

5.3.3 Touch Power off and then Power on Sequence



During power off, the VTSP must be lower than 0.5V for at least 10us ($T_g > 10\mu s$) to make sure the touch controller be correctly reset.

6.2 Integration Interface Requirement

6.2.1 Connector Description

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

Connector Name / Designation	For Signal Connector
Manufacturer	I-PEX or compatible
Type / Part Number	20455-040E-12R or compatible
Mating Housing/Part Number	20453-040T-01 or compatible

6.2.2 Pin Assignment (with Touch Sensor Pin Assignment)


PIN NO	Symbol	Function
1	NC	No Connect (Reserved for DCR)
2	H_GND	High Speed Ground
3	NC	No connect
4	NC	No connect
5	H_GND	High Speed Ground
6	Lane0_N	Comp Signal Link Lane 0
7	Lane0_P	True Signal Link Lane 0
8	H_GND	High Speed Ground
9	AUX_CH_P	True Signal Auxiliary Ch.
10	AUX_CH_N	Comp Signal Auxiliary Ch.
11	H_GND	High Speed Ground
12	LCD_VCC	LCD logic and driver power
13	LCD_VCC	LCD logic and driver power
14	LCD_Self_Test	LCD Panel Self Test Enable
15	LCD_GND	LCD logic and driver ground
16	LCD_GND	LCD logic and driver ground



Product Specification


AU OPTRONICS CORPORATION

17	HPD	HPD signal pin
18	BL_GND	Backlight ground
19	BL_GND	Backlight ground
20	BL_GND	Backlight ground
21	BL_GND	Backlight ground
22	BL_Enable	Backlight On / Off
23	BL_PWM_DIM	System PWM signal Input
24	NC	No connect (Reverse for AUO TEST only)
25	NC	No connect (Reverse for AUO TEST only)
26	BL_PWR	Backlight power (6V~21V)
27	BL_PWR	Backlight power (6V~21V)
28	BL_PWR	Backlight power (6V~21V)
29	BL_PWR	Backlight power (6V~21V)
30	NC	No Connect (Reserved for CM)
31	TP_D-	USB Data- for Touch
32	TP_D+	USB Data+ for Touch
33	GND	Ground—Shield
34	VTSP	Touch panel power supply (5V)
35	VTSP	Touch panel power supply (5V)
36	NC/TP_EN	No Connection (Reserve for Touch function enable)
37	TP_CLK	I2C Clock for Touch (NC for USB input)
38	TP_Data	I2C Clock for Touch (NC for USB input)
39	INT	Interrupt for Touch (NC for USB input)
40	RST	Reset for Touch (NC for USB input)



Note1: Start from right side.

Note2: Input signals shall be low or High-impedance state when VDD is off.
Internal circuit of **eDP inputs** are as following.



6.3 Interface Timing

6.3.1 Timing Characteristics


Basically, interface timings should match the 1366x768 /60Hz manufacturing guide line timing.

Parameter		Symbol	Min.	Typ.	Max.	Unit
Frame Rate		-	-	60	-	Hz
Clock frequency		1/ T _{Clock}	66.9	72	80	MHz
Vertical Section	Period	T _V	788	824	768+A	T _{Line}
	Active	T _{VD}	768			
	Blanking	T _{VB}	20	56	A	
Horizontal Section	Period	T _H	1416	1456	1366+B	T _{Clock}
	Active	T _{HD}	1366			
	Blanking	T _{HB}	50	90	B	

Note : 1. DE mode only

2. The maximum clock frequency = (1366+B)*(768+A)*60 < 80MHz


6.3.2 Timing diagram



6.4 Power ON/OFF Sequence


Power on/off sequence is as follows. Interface signals and LED on/off sequence are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off

Display Port panel power sequence:



Display port interface power up/down sequence, normal system operation

Display Port AUX_CH transaction only:



Display port interface power up/down sequence, AUX_CH transaction only



Product Specification

AU OPTRONICS CORPORATION

Display Port Panel Power Sequence Timing Parameters

Timing parameter	Description	Reqd. by	Limits			Notes
			Min.	Typ.	Max.	
T1	power rail rise time, 10% to 90%	source	0.5ms		10ms	
T2	delay from LCDVDD to black video generation	sink	0ms		200ms	prevents display noise until valid video data is received from the source
T3	delay from LCDVDD to HPD high	sink	0ms		200ms	sink AUX_CH must be operational upon HPD high.
T4	delay from HPD high to link training initialization	source				allows for source to read link capability and initialize.
T5	link training duration	source				dependant on source link to read training protocol.
T6	link idle	source				Min accounts for required BS-Idle pattern. Max allows for source frame synchronization.
T7	delay from valid video data from source to video on display	sink	0ms		50ms	max allows sink validate video data and timing.
T8	delay from valid video data from source to backlight enable	source				source must assure display video is stable.
T9	delay from backlight disable to end of valid video data	source				source must assure backlight is no longer illuminated.
T10	delay from end of valid video data from source to power off	source	0ms		500ms	
T11	power rail fall time, 90% to 10%	source			10ms	
T12	power off time	source	500ms			


Note1: The sink must include the ability to generate black video autonomously. The sink must automatically enable black video under the following conditions:

- upon LCDVDD power on (within T2 max)-when the "Novideostream_Flag" (VB-ID Bit 3) is received from the source (at the end of T9).
- when no main link data, or invalid video data, is received from the source. Black video must be displayed within 64ms (typ) from the start of either condition. Video data can be deemed invalid based on MSA and timing information, for example.


Note 2: The sink may implement the ability to disable the black video function, as described in Note 1, above, for system development and debugging purpose.

Note 3: The sink must support AUX_CH polling by the source immediately following LCDVDD power on without causing damage to the sink device (the source can re-try if the sink is not ready). The sink must be able to respond to an AUX_CH transaction with the time specified within T3 max.

Display Port panel B/L power sequence timing parameter:



Note : When the adapter is hot plugged, the backlight power supply sequence is shown as below.



	Min (ms)	Max (ms)
T13	0.5	10
T14	10	-
T15	10	-
T16	10	-
T17	10	-
T18	0.5	10
T19	1*	-
T20	1*	-

Seamless change: $T19/T20 = 5 \times T_{PWM}^*$

* $T_{PWM} = 1/PWM \text{ Frequency}$

7. Panel Reliability Test

7.1 Vibration Test

Test Spec:

- Test method: Non-Operation
- Acceleration: 1.5 G
- Frequency: 10 - 500Hz Random
- Sweep: 30 Minutes each Axis (X, Y, Z)

7.2 Shock Test

Test Spec:

- Test method: Non-Operation
- Acceleration: 220 G , Half sine wave
- Active time: 2 ms
- Pulse: X,Y,Z .one time for each side

7.3 Reliability Test

Items	Required Condition	Note
Temperature Humidity Bias	Ta= 40°C, 90%RH, 240h	
High Temperature Operation	Ta= 60°C, Dry, 240h	
Low Temperature Operation	Ta= 0°C, 240h	
High Temperature Storage	Ta= 60°C, 240h	
Low Temperature Storage	Ta= -20°C, 240h	
Thermal Shock Test	Ta=-20°C(30min) ~60°C(30min), 20cycles condition.	
ESD	Contact : ±8 KV Air : ±15 KV	Note 1

Note1: According to EN 61000-4-2 , ESD class B: Some performance degradation allowed. No data lost


. Self-recoverable. No hardware failures.

Remark: MTBF (Excluding the LED): 30,000 hours with a confidence level 90%









Product Specification

AU OPTRONICS CORPORATION





9. Shipping and Package

9.1 Shipping Label Format

 xxxxxxxxxxxx-xxxxx		Manufactured Model No: B140XTT01.2 AU Optronics MADE IN China (S01)	C  US E204356	
	CN- 0HFJH8 -72090-932- 0123- A00 Made In China DP/N 0HFJH8			
	H/W: 0A F/W:1			

9.2 Carton Package



9.3 Shipping Package of Palletizing Sequence

10. Appendix: EDID Description

Byte (hex)	FUNCTION	Value (hex)	Value (binary)	Value (DEC)
0	Header	00	00000000	0
1	Header	FF	11111111	255
2	Header	FF	11111111	255
3	Header	FF	11111111	255
4	Header	FF	11111111	255
5	Header	FF	11111111	255
6	Header	FF	11111111	255
7	Header	00	00000000	0
8	EISA manufacture code = 3 Character ID	06	00000110	6
9	EISA manufacture code (Compressed ASCII)	AF	10101111	175
0A	Panel Supplier Reserved – Product Code	3C	00111100	60
0B	Panel Supplier Reserved – Product Code	12	00010010	18
0C	LCD module Serial No - Preferred but Optional (“0” if not used)	00	00000000	0
0D	LCD module Serial No - Preferred but Optional (“0” if not used)	00	00000000	0
0E	LCD module Serial No - Preferred but Optional (“0” if not used)	00	00000000	0
0F	LCD module Serial No - Preferred but Optional (“0” if not used)	00	00000000	0
10	Week of manufacture	00	00000000	0
11	Year of manufacture	17	00010111	23
12	EDID structure version # = 1	01	00000001	1
13	EDID revision # = 4	04	00000100	4
14	Video I/P definition	95	10010101	149
15	Max H image size = ?? cm(Rounded to cm)	1F	00011111	31
16	Max V image size = ?? cm(Rounded to cm)	11	00010001	17
17	Display gamma = (gamma ×100)-100 = Example: (2.2×100) – 100 = 120	78	01111000	120
18	Feature support	02	00000010	2
19	Red/Green Low bit (RxRy/GxGy)	BB	10111011	187
1A	Blue/White Low bit (BxBY/WxWy)	F5	11110101	245
1B	Red X Rx = 0.???	94	10010100	148
1C	Red Y Ry = 0.???	55	01010101	85
1D	Green X Rx = 0.???	54	01010100	84
1E	Green Y Ry = 0.???	90	10010000	144
1F	Blue X Rx = 0.???	27	00100111	39
20	Blue Y Ry = 0.???	23	00100011	35
21	White X Rx = 0.???	50	01010000	80



Product Specification

AU OPTRONICS CORPORATION

22	White Y Ry = 0.???	54	01010100	84
23	Established timings 1 (00h if not used)	00	00000000	0
24	Established timings 2 (00h if not used)	00	00000000	0
25	Manufacturer's timings (00h if not used)	00	00000000	0
26	Standard timing ID1 (01h if not used)	01	00000001	1
27	Standard timing ID1 (01h if not used)	01	00000001	1
28	Standard timing ID2 (01h if not used)	01	00000001	1
29	Standard timing ID2 (01h if not used)	01	00000001	1
2A	Standard timing ID3 (01h if not used)	01	00000001	1
2B	Standard timing ID3 (01h if not used)	01	00000001	1
2C	Standard timing ID4 (01h if not used)	01	00000001	1
2D	Standard timing ID4 (01h if not used)	01	00000001	1
2E	Standard timing ID5 (01h if not used)	01	00000001	1
2F	Standard timing ID5 (01h if not used)	01	00000001	1
30	Standard timing ID6 (01h if not used)	01	00000001	1
31	Standard timing ID6 (01h if not used)	01	00000001	1
32	Standard timing ID7 (01h if not used)	01	00000001	1
33	Standard timing ID7 (01h if not used)	01	00000001	1
34	Standard timing ID8 (01h if not used)	01	00000001	1
35	Standard timing ID8 (01h if not used)	01	00000001	1
36	Pixel Clock/10,000 (LSB)	A6	10100110	166
37	Pixel Clock/10,000 (MSB)	1D	00011101	29
38	Horizontal Active = ???? pixels (lower 8 bits)	56	01010110	86
39	Horizontal Blanking (Thbp) = 320 pixels (lower 8 bits)	D0	11010000	208
3A	Horizontal Active/Horizontal blanking (Thbp) (upper 4:4 bits)	50	01010000	80
3B	Vertical Active = ??? lines	00	00000000	0
3C	Vertical Blanking (Tvbp) = ?? lines (DE Blanking typ. for DE only panels)	23	00100011	35
3D	Vertical Active : Vertical Blanking (Tvbp) (upper 4:4 bits)	30	00110000	48
3E	Horizontal Sync, Offset (Thfp) = ?? pixels	26	00100110	38
3F	Horizontal Sync, Pulse Width = ??? pixels	16	00010110	22
40	Vertical Sync, Offset (Tvfp) = ? lines Sync Width = ? lines	36	00110110	54
41	Horizontal Vertical Sync Offset/Width upper 2 bits	00	00000000	0
42	Horizontal Image Size = ??? mm	35	00110101	53



Product Specification

AU OPTRONICS CORPORATION

43	Vertical image Size = ??? mm	AD	10101101	173
44	Horizontal Image Size / Vertical image size	10	00010000	16
45	Horizontal Border = 0 (Zero for Notebook LCD)	00	00000000	0
46	Vertical Border = 0 (Zero for Notebook LCD)	00	00000000	0
47	Bit[7] 0: Non-interlace, 1: Interlace Bit[6:5] 00: Normal display, no stereo, see VESA EDID Spec 1.3 Bit[4:3] 00: Analog composite, 01: Bipolar analog composite, 10: Digital composite, 11: Digital separate Bit[2:1] : The int	1A	00011010	26
48	Pixel Clock/10,000 (LSB)	A6	10100110	166
49	Pixel Clock/10,000 (MSB)	1D	00011101	29
4A	Horizontal Active = xxxx pixels (lower 8 bits)	56	01010110	86
4B	Horizontal Blanking (Thbp) = xxxx pixels (lower 8 bits)	5A	01011010	90
4C	Horizontal Active/Horizontal blanking (Thbp) (upper 4:4 bits)	52	01010010	82
4D	Vertical Active = xxxx lines	00	00000000	0
4E	Vertical Blanking (Tvbp) = xxxx lines (DE Blanking typ. for DE only panels)	23	00100011	35
4F	Vertical Active : Vertical Blanking (Tvbp) (upper 4:4 bits)	30	00110000	48
50	Horizontal Sync, Offset (Thfp) = xxxx pixels	26	00100110	38
51	Horizontal Sync, Pulse Width = xxxx pixels	16	00010110	22
52	Vertical Sync, Offset (Tvfp) = xx lines Sync Width = xx lines	36	00110110	54
53	Horizontal Vertical Sync Offset/Width upper 2 bits	00	00000000	0
54	Horizontal Image Size = xxx mm	35	00110101	53
55	Vertical image Size = xxx mm	AD	10101101	173
56	Horizontal Image Size / Vertical image size	10	00010000	16
57	Horizontal Border = 0 (Zero for Notebook LCD)	00	00000000	0
58	Vertical Border = 0 (Zero for Notebook LCD)	00	00000000	0



Product Specification

AU OPTRONICS CORPORATION

	Bit[7] 0: Non-interlace, 1: Interlace Bit[6:5] 00: Normal display, no strero, see VESA EDID Spec 1.3 Bit[4:3] 00: Analog composite, 01: Bipolar analog composite, 10: Digital composite, 11: Digital separate			
59	Bit[2:1] : The int	1A	00011010	26
5A	Flag	00	00000000	0
5B	Flag	00	00000000	0
5C	Flag	00	00000000	0
5D	Data Type Tag: Alphanumeric Data String (ASCII) ==> fix=FE	FE	11111110	254
5E	Flag	00	00000000	0
5F	Dell P/N 1 st Character	48	01001000	72
60	Dell P/N 2 nd Character	46	01000110	70
61	Dell P/N 3 rd Character	4A	01001010	74
62	Dell P/N 4 th Character	48	01001000	72
63	Dell P/N 5 th Character	38	00111000	56
	EDID Revision Bit[6:0] See charts below Bit[7] 0: X-rev, 1: A-rev			
64		80	10000000	128
65	Manufacturer P/N	42	01000010	66
66	Manufacturer P/N	31	00110001	49
67	Manufacturer P/N	34	00110100	52
68	Manufacturer P/N	30	00110000	48
69	Manufacturer P/N	58	01011000	88
6A	Manufacturer P/N	54	01010100	84
6B	Manufacturer P/N (If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h)	54	01010100	84
6C	Flag	00	00000000	0
6D	Flag	00	00000000	0
6E	Flag	00	00000000	0
6F	Data Type Tag: Manufacturer Specified Data 00 ==>fix=00	00	00000000	0
70	Flag	00	00000000	0
71	Color Management	00	00000000	0
72	Panel Structure	41	01000001	65
73	Frame Rate	22	00100010	34
74	Light Controller Interface and Luminance	96	10010110	150
75	Outdoor Features	01	00000001	1
76	Multi-Media Features	11	00010001	17
77	Multi-Media Features	00	00000000	0



Product Specification

AU OPTRONICS CORPORATION

78	Special Features #1	00	00000000	0
79	Special Features #2	09	00001001	9
7A	Special Features #3	01	00000001	1
7B	(If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h)	0A	00001010	10
7C	(If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h)	20	00100000	32
7D	(If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h)	20	00100000	32
7E	Extension flag (# of optional 128 EDID extension blocks to follow, Typ = 0)	00	00000000	0
7F	Checksum (The 1-byte sum of all 128 bytes in this EDID block shall = 0)	81	10000001	129