Product Specification

SPECIFICATION
FOR
APPROVAL

(●) **Preliminary Specification**

(   ) **Final Specification**

Title	12.5" HD TFT LCD

BUYER	LENOVO
MODEL	

SUPPLIER	LG Display Co., Ltd.
*MODEL	LP125WH2
Suffix	TLB1

*When you obtain standard approval,
 please use the above model name without suffix

APPROVED BY	**SIGNATURE**
/	
/	
/	

Please return 1 copy for your confirmation with your signature and comments.

APPROVED BY	**SIGNATURE**
S. R. Kim / G.Manager	
REVIEWED BY	
N. J. Seong / Manager	
PREPARED BY	
J. T. Kim / Engineer	
S. M. Woo / Engineer	

**Products Engineering Dept.
LG Display Co., Ltd**

Contents

Product Specification

RECORD OF REVISIONS

Revision No	Revision Date	Page	Description	EDID ver
0.0	2. Jun. 2010	-	First Specification	-
0.1	23. Aug. 2010	6	Update the Electrical Characteristics	0.0
		9	Update the DC Specification of the LVDS Signal Timing Spec.	
		18, 19	Update the Drawing	
		22	Update the Packing Form	
		25 ~ 27	Update the EDID data	
0.2	26. Aug. 2010	13	Update T7 time of the Power Sequence (3ms → 0ms)	0.0
0.3	02. Dec. 2010	14	Update the Color Coordination	0.2
		15	Update the Gray scale specification	
		22	Update the Packing form	
			-. Change the Packing quantity (30pcs → 20pcs)	
			-. Change the Box size (473X364X338 → 422X340X257)	
		25~27	Update the EDID Data (Checksum: 4B → 94)	
			-. Update the Color Coordination	
0.4	21. Jan. 2011	6	Change the PWM Duty Ratio (5% → 1%)	0.3
		11	Update the Signal Timing Specifications (DCLK 74.8Mhz)	
		14	Add the Typ. Value of Viewing Angle,	
		18~19	Update the Front & Back View of Drawing	
		22~23	Update the Packing Information	
		26~28	Update the EDID Data (Checksum : 94 → F7)	
1.0	09. Feb. 2011	4, 17	Update the Outline Dimension (Thickness 3.6 →3.7D,Max.)	1.0
		6	Change the Backlight PWM High Level Voltage (Min 3.0 → 2.7)	
			Change the Backlight LED_EN High Level Voltage (Min 3.0 → 2.7)	
		8	Delete "or Equivalent" at Connector	
		11	Change the Timing Description	
		14	Update the Luminance Variation 5point	
		18-19	Update the Drawing of Front view, Rear view	
		23	Update Label Description	

Product Specification

1. General Description

The LP125WH2 is a Color Active Matrix Liquid Crystal Display with an integral LED backlight system. The matrix employs a-Si Thin Film Transistor as the active element. It is a transmissive type display operating in the normally white mode. This TFT-LCD has 12.5 inches diagonally measured active display area with HD resolution (1366 horizontal by 768 vertical pixel array). Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 6-bit gray scale signal for each dot, thus, presenting a palette of more than 262,144 colors. The LP125WH2 has been designed to apply the interface method that enables low power, high speed, low EMI. The LP125WH2 is intended to support applications where thin thickness, low power are critical factors and graphic displays are important. In combination with the vertical arrangement of the sub-pixels, the LP125WH2 characteristics provide an excellent flat display for office automation products such as Notebook PC.

General Features

| Active Screen Size	12.5 inches diagonal
Outline Dimension	290.5(H, Typ.) × 179.5(V, Typ.) × 3.7(D, Max.) mm
Pixel Pitch	0.2025 X 0.2025 mm
Pixel Format	1366 horiz. by 768 vert. Pixels RGB strip arrangement
Color Depth	6-bit, 262,144 colors
Luminance, White	200 cd/m^2 (Typ.5 point @ PWM Duty = 100%)
Power Consumption	Total 3.9 W (Typ.) Logic : 1.1 W (Typ.@ Mosaic), B/L : 2.8W (Typ.@ VLED 12V)
Weight	270g (Max.)
Display Operating Mode	Transmissive mode, normally white
Surface Treatment	Anti-glare treatment of the front Polarizer
RoHS Compliance	Yes
BFR / PVC / As Free	Yes for all

2. Absolute Maximum Ratings

The following are maximum values which, if exceeded, may cause faulty operation or damage to the unit.

Table 1. ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Values		Units	Notes
		Min	Max		
Power Input Voltage	VCC	-0.3	4.0	Vdc	at 25 ± 5°C
Operating Temperature	TOP	0	50	°C	1
Storage Temperature	HST	-20	60	°C	1
Operating Ambient Humidity	HOP	10	90	%RH	1
Storage Humidity	HST	10	90	%RH	1

Note : 1. Temperature and relative humidity range are shown in the figure below.
Wet bulb temperature should be 39°C Max, and no condensation of water.

3. Electrical Specifications

3-1. Electrical Characteristics

The LP33WH2 requires two power inputs. The first logic is employed to power the LCD electronics and to drive the TFT array and liquid crystal. The second backlight is the input about LED BL.with LED Driver.

Table 2. ELECTRICAL CHARACTERISTICS

Parameter		Symbol	Values			Unit	Notes
			Min	Typ	Max		
LOGIC :							
Power Supply Input Voltage		V_{CC}	3.0	3.3	3.6	V	1
Power Supply Input Current	Mosaic	I_{CC}	-	330	380	mA	2
Power Consumption		P_{CC}	-	1.1	1.3	W	3
Power Supply Inrush Current		I_{CC_P}	-		2000	mA	4
LVDS Impedance		Z_{LVDS}	90	100	110	Ω	5
BACKLIGHT : (with LED Driver)							
LED Power Input Voltage		V_{LED}	7.0	12.0	21.0	V	6
LED Power Input Current		I_{LED}	-	235	250	mA	7
LED Power Consumption		P_{LED}	-	2.8	3.0	W	7
LED Power Inrush Current		I_{LED_P}	-		2000	mA	8
PWM Duty Ratio			1	-	100	%	9
PWM Jitter		-	0	-	0.2	%	10
PWM Impedance		Z_{PWM}	20	40	60	kΩ	
PWM Frequency		F_{PWM}	200	-	1000	Hz	11
PWM High Level Voltage		V_{PWM_H}	2.7	-	3.6	V	
PWM Low Level Voltage		V_{PWM_L}	0	-	0.3	V	
LED_EN Impedance		Z_{PWM}	20	40	60	kΩ	
LED_EN High Voltage		$V_{LED\_EN\_H}$	2.7	-	3.6	V	
LED_EN Low Voltage		$V_{LED\_EN\_L}$	0	-	0.3	V	
Life Time			12,000	-	-	Hrs	12

⦿ LG Display

Product Specification

Note)
1. The measuring position is the connector of LCM and the test conditions are under 25℃, fv = 60Hz, Black pattern.
2. The specified Icc current and power consumption are under the Vcc = 3.3V , 25℃, fv = 60Hz condition and Mosaic pattern.

3. This Power Consumption Spec. is measured for the Mosaic Pattern condition.
4. The below figures are the measuring Vcc condition and the Vcc control block LGD used.
   The Vcc condition is same as the minimum of T1 at Power on sequence.

Rising time Vcc 3.3V 90% 0V 10% 0.5ms

5. This impedance value is needed for proper display and measured form LVDS Tx to the mating connector.
6. The measuring position is the connector of LCM and the test conditions are under 25℃.
7. The current and power consumption with LED Driver are under the Vled = 12.0V , 25℃, Dimming of Max luminance and White pattern with the normal frame frequency operated(60Hz).
8. The below figures are the measuring Vled condition and the Vled control block LGD used.
   VLED control block is same with Vcc control block.

Rising time V_{LED} 12.0V 90% 0V 10% 0.5ms

9. The operation of LED Driver below minimum dimming ratio may cause flickering or reliability issue.
10. If Jitter of PWM is bigger than maximum, it may induce flickering.
11. This Spec. is not effective at 100% dimming ratio as an exception because it has DC level equivalent to 0Hz. In spite of acceptable range as defined, the PWM Frequency should be fixed and stable for more consistent brightness control at any specific level desired.
12. The life time is determined as the sum of the continuous operation time at which brightness of LCD at the typical LED current is 50% compare to that of minimum value specified in table 7 under general user condition.

3-2. Interface Connections

This LCD employs two interface connections, a 40 pin connector is used for the module electronics interface and the other connector is used for the integral backlight system.
The electronics interface connector is a model GT05Q-40S-H10 manufactured by LSMtron.

Table 3. MODULE CONNECTOR PIN CONFIGURATION (CN1)

Pin	Symbol	Description	Notes
1	NC	No Connection	**[Interface Chip]**
2	VCC	LCD Logic and driver power (3.3V Typ.)	1. LCD :
3	VCC	LCD Logic and driver power (3.3V Typ.)	SiW, SW0641(LCD Controller)
4	V EEDID	DDC Power (3.3V)	Including LVDS Receiver.
5	NC	No Connection	2. System : SiW LVDSRx or equivalent
6	Clk EEDID	DDC Clock	* Pin to Pin compatible with LVDS
7	DATA EEDID	DDC Data	
8	ORX0-	Negative LVDS differential data input	**[Connector]**
9	ORX0+	Positive LVDS differential data input	LSMtron GT05Q-40S-H10
10	GND	High Speed Ground	
11	ORX1-	Negative LVDS differential data input	**[Mating Connector]**
12	ORX1+	Positive LVDS differential data input	20345-#40E-## series or equivalent
13	GND	High Speed Ground	
14	ORX2-	Negative LVDS differential data input	
15	ORX2+	Positive LVDS differential data input	**[Connector pin arrangement]**
16	GND	High Speed Ground	
17	ORXC-	Negative LVDS differential clock input	
18	ORXC+	Positive LVDS differential clock input	
19	VSS	Ground	
20	NC	No Connection	
21	NC	No Connection	
22	GND	Ground	
23	NC	No Connection	
24	NC	No Connection	
25	GND	Ground	
26	NC	No Connection	
27	NC	No Connection	
28	GND	Ground	
29	NC	No Connection	
30	NC	No Connection	
31	GND	LED Backlight Ground	
32	GND	LED Backlight Ground	
33	GND	LED Backlight Ground	
34	NC	No Connection	
35	PWM	System PWM Signal input for dimming	
36	LED_EN	LED Backlight On/Off	
37	NC	Reserved	
38	VLED	LED Backlight Power (7V-21V)	
39	VLED	LED Backlight Power (7V-21V)	
40	VLED	LED Backlight Power (7V-21V)	

3-3. LVDS Signal Timing Specifications

3-3-1. DC Specification

$|V_{ID}| = |(LVDS+) - (LVDS-)|$
$V_{CM} = \{(LVDS+) + (LVDS-)\}/2$

VDD=1.8V

Description	Symbol	Min	Typ	Max	Unit	Notes
LVDS Differential Voltage	$|V_{ID}|$	100	-	600	mV	-
LVDS Common mode Voltage	V_{CM}	$|V_{ID}|$ /2	1.2	VDD- $|V_{ID}|$/2	V	-
LVDS Input Voltage Range	V_{IN}	0.3	-	VDD	V	-

3-3-2. AC Specification

t_{SKEW} ($F_{clk} = 1/T_{clk}$)
1) 85MHz > Fclk ≥ 65MHz : -400 ~ +400
2) 65MHz > Fclk ≥ 25MHz : -600 ~ +600

Description	Symbol	Min	Max	Unit	Notes
LVDS Clock to Data Skew Margin	t_{SKEW}	- 400	+ 400	ps	85MHz > Fclk ≥ 65MHz
	t_{SKEW}	- 600	+ 600	ps	65MHz > Fclk ≥ 25MHz
LVDS Clock to Clock Skew Margin (Even to Odd)	t_{SKEW_EO}	- 1/7	+ 1/7	T_{clk}	-
Maximum deviation of input clock frequency during SSC	F_{DEV}	-	± 3	%	-
Maximum modulation frequency of input clock during SSC	F_{MOD}	-	200	KHz	-

Product Specification

< Clock skew margin between channel >

< Spread Spectrum >

3-3-3. Data Format
1) LVDS 1 Port

< LVDS Data Format >

Product Specification

3-4. Signal Timing Specifications

This is the signal timing required at the input of the User connector. All of the interface signal timing should be satisfied with the following specifications and specifications of LVDS Tx/Rx for its proper operation.

Table 4. TIMING TABLE

ITEM	Symbol		Min.	Typ.	Max.	Unit	Note
DCLK	Frequency	f_{CLK}	-	74.8	-	MHz	
Hsync	Period	t_{HP}	1430	1578	1884	tCLK	
	Width	t_{WH}	24	32	48		
	Width-Active	tw_{HA}	1366	1366	1366		
Vsync	Period	t_{VP}	783	790	799	tHP	
	Width	t_{WV}	2	5	6		
	Width-Active	tw_{VA}	768	768	768		
Data Enable	Horizontal back porch	t_{HBP}	16	132	438	tCLK	
	Horizontal front porch	t_{HFP}	32	48	64		
	Vertical back porch	t_{VBP}	4	15	21	tHP	
	Vertical front porch	t_{VFP}	1	2	3		

Appendix) All reliabilities are specified for timing specification based on refresh rate of 60Hz.

However, LP125WH2 has a good actual performance even at lower refresh rate (e.g. 50Hz)

for power saving mode, whereas LP125WH2 is secured only for function under lower refresh rate.

60Hz at Normal mode, 50Hz at Power save mode. Don't care Flicker level (power save mode).

3-5. Signal Timing Waveforms

Condition : V_{CC} =3.3V

Product Specification

3-6. Color Input Data Reference

The brightness of each primary color (red,green and blue) is based on the 6-bit gray scale data input for the color ; the higher the binary input, the brighter the color. The table below provides a reference for color versus data input.

Table 5. COLOR DATA REFERENCE

Color		Input Color Data																		
		RED						GREEN						BLUE					
		MSB					LSB	MSB					LSB	MSB					LSB
		R 5	R 4	R 3	R 2	R 1	R 0	G 5	G 4	G 3	G 2	G 1	G 0	B 5	B 4	B 3	B 2	B 1	B 0
Basic Color	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
RED	RED (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (01)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	…			…						…						…			
	RED (62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
GREEN	GREEN (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	GREEN (01)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	...			…						…						…			
	GREEN (62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	GREEN (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
BLUE	BLUE (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	BLUE (01)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	…			…						…						…			
	BLUE (62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	BLUE (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

Product Specification

3-7. Power Sequence

Power Supply Input
VCC

Interface Signal, V_i
LVDS

LED BL
On/Off Control Signal
LED_EN

LED BL
Dimming Control Signal
PWM

LED Driver Input Voltage
VLED

Table 6. POWER SEQUENCE TABLE

Logic Parameter	Value			Units	LED Parameter	Value			Units
	Min.	Typ.	Max.			Min.	Typ.	Max.	
T_1	0.5	-	10	ms	T_8	10	-	-	ms
T_2	0	-	50	ms	T_9	0	-	-	ms
T_3	0	-	50	ms	T_{10}	0	-	-	ms
T_4	400	-	-	ms	T_{11}	10	-	-	ms
T_5	200	-	-	ms	T_{12}	0.5	-	-	ms
T_6	200	-	-	ms	T_{13}	0	-	5000	ms
T_7	0	-	10	ms					

Note)

1. Do not insert the mating cable when system turn on.
2. Valid Data have to meet "3-3. LVDS Signal Timing Specifications"
3. LVDS, LED_EN and PWM need to be on pull-down condition on invalid status.
4. LGD recommend the rising sequence of VLED after the Vcc and valid status of LVDS turn on.

4. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable for approximately 30 minutes in a dark environment at 25°C. The values specified are at an approximate distance 50cm from the LCD surface at a viewing angle of Φ and Θ equal to 0°.
FIG. 1 presents additional information concerning the measurement equipment and method.

### FIG. 1 Optical Characteristic Measurement Equipment and Method

Optical Stage(x,y)　**LCD Module**　**Pritchard 880 or equivalent**

1°

50cm

Table 9. OPTICAL CHARACTERISTICS

Ta=25°C, Vcc=3.3V, fv=60Hz, f$_{CLK}$= 74.8MHz, V$_{LED}$ = 12V, PWM Duty = 100%

Parameter	Symbol	Values			Units	Notes
		Min	Typ	Max		
Contrast Ratio	CR	200	300	-		1
Surface Luminance, white	L$_{WH}$	170	200	-	cd/m^2	2
Luminance Variation	δ$_{WHITE\_5P.}$	70	-	-	%	3
	δ$_{WHITE\_13P}$	60	70	-	%	
Response Time	Tr$_R$+ Tr$_D$	-	16	25	ms	4
Color Coordinates						
RED	RX	0.556	0.586	0.616		
	RY	0.315	0.345	0.375		
GREEN	GX	0.310	0.340	0.370		
	GY	0.529	0.559	0.589		
BLUE	BX	0.128	0.158	0.188		
	BY	0.097	0.127	0.157		
WHITE	WX	0.283	0.313	0.343		
	WY	0.299	0.329	0.359		
Viewing Angle						5
x axis, right(Φ=0°)	Θr	40	45	-	degree	
x axis, left (Φ=180°)	Θl	40	45	-	degree	
y axis, up (Φ=90°)	Θu	10	15	-	degree	
y axis, down (Φ=270°)	Θd	30	35	-	degree	
Gray Scale						6

Product Specification

Note)
1. Contrast Ratio(CR) is defined mathematically as

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

2. Surface luminance is the average of 5 point across the LCD surface 50cm from the surface with all pixels displaying white. For more information see FIG 1.

$$L_{WH} = \text{Average}(L_1, L_2, \dots L_5)$$

3. The variation in surface luminance , The panel total variation (δ_{WHITE}) is determined by measuring L_N at each test position 1 through 13 and then defined as followed numerical formula. For more information see FIG 2.

$$\delta_{WHITE} = \frac{\text{Maximum}(L_1, L_2, \dots L_{13})}{\text{Minimum}(L_1, L_2, \dots L_{13})}$$

4. Response time is the time required for the display to transition from white to black (rise time, Tr_R) and from black to white(Decay Time, Tr_D). For additional information see FIG 3.

5. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are   determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 4.

6. Gray scale specification   * f_V = 60Hz

Gray Level	Luminance [%] (Typ)
L0	0.16
L7	1.45
L15	5.36
L23	12.21
L31	21.01
L39	34.82
L47	52.49
L55	74.17
L63	100

Product Specification

FIG. 2 Luminance

<Measuring point for Average Luminance & measuring point for Luminance variation>

H

A

10mm

10mm

B

V

6   7   8

2   3

9   1   10

11   4   12   5   13

H,V : ACTIVE AREA
**A : H/4 mm**
B : V/4 mm
POINTS: 13 POINTS

Active Area

FIG. 3 Response Time

The response time is defined as the following figure and shall be measured by switching the input signal for "black" and "white".

Tr_R

Tr_D

%

100
90

Optical

Response

10
0   white   white

black

FIG. 4 Viewing angle

Normal

Eye

Y

$\phi = 90°$, Up

<Dimension of viewing angle range>

$\phi = 180°$ Left'

θ

ϕ

$\phi = 0°$ Right'

$\phi = 270°$ Down'

5. Mechanical Characteristics

The contents provide general mechanical characteristics for the model LP133WH2.
In addition the figures in the next page are detailed mechanical drawing of the LCD.

Outline Dimension	Horizontal	290.5 $\pm$ 0.50mm
	Vertical	179.5 $\pm$ 0.50mm
	Depth	3.7mm(Max.)
Bezel Area	Horizontal	280.62 mm
	Vertical	159.32 mm
Active Display Area	Horizontal	276.620mm
	Vertical	155.520mm
Weight	270g(Max.)	
Surface Treatment	Anti-glare treatment of the front Polarizer	

Product Specification

<FRONT VIEW>   Note) Unit:[mm], General tolerance: ± 0.5mm

Product Specification

<Rear VIEW>   Note) Unit:[mm], General tolerance: ± 0.5mm

LG Display

Product Specification

6. Reliability

Environment test condition

No.	Test Item	Conditions
1	High temperature storage test	Ta= 60°C, 240h
2	Low temperature storage test	Ta= -20°C, 240h
3	High temperature operation test	Ta= 50°C, 50%RH, 240h
4	Low temperature operation test	Ta= 0°C, 240h
5	Vibration test (non-operating)	Sine wave, 10 ~ 500 ~ 10Hz, 1.5G, 0.37oct/min 3 axis, 1hour/axis
6	Shock test (non-operating)	Half sine wave, 180G, 2ms one shock of each six faces(I.e. run 180G 2ms for all six faces)
7	Altitude operating storage / shipment	0 ~ 10,000 feet (3,048m) 24Hr 0 ~ 40,000 feet (12,192m) 24Hr

{ Result Evaluation Criteria }
 There should be no change which might affect the practical display function when the display quality test is conducted under normal operating condition.

7. International Standards

7-1. Safety

a) UL 60950-1, Second Edition, Underwriters Laboratories Inc.
   Information Technology Equipment - Safety - Part 1 : General Requirements.

b) CAN/CSA C22.2 No.60950-1-07, Second Edition, Canadian Standards Association.
   Information Technology Equipment - Safety - Part 1 : General Requirements.

c) EN 60950-1:2006 + A11:2009, European Committee for Electrotechnical Standardization (CENELEC).
   Information Technology Equipment - Safety - Part 1 : General Requirements.

d) IEC 60950-1:2005, Second Edition, The International Electrotechnical Commission (IEC).
   Information Technology Equipment - Safety - Part 1 : General Requirements.

7-2. EMC

a) ANSI C63.4 "American National Standard for Methods of Measurement of Radio-Noise
   Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."
   American National Standards Institute (ANSI), 2003.

b) CISPR 22 "Information technology equipment – Radio disturbance characteristics – Limit and
   methods of measurement." International Special Committee on Radio Interference
   (CISPR), 2005.

c) CISPR 13 "Sound and television broadcast receivers and associated equipment – Radio disturbance
   characteristics – Limits and method of measurement." International Special Committee on Radio
   Interference (CISPR), 2006.

7-3. Environment

a) RoHS, Directive 2002/95/EC of the European Parliament and of the council of 27 January 2003

8. Packing

8-1. Designation of Lot Mark

a) Lot Mark

A	B	C	D	E	F	G	H	I	J	K	L	M

A,B,C : SIZE(INCH)   D : YEAR
E : MONTH   F ~ M : SERIAL NO.

Note
1. YEAR

Year	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020
Mark	A	B	C	D	E	F	G	H	J	K

2. MONTH

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Mark	1	2	3	4	5	6	7	8	9	A	B	C

b) Location of Lot Mark

Serial No. is printed on the label. The label is attached to the backside of the LCD module.
This is subject to change without prior notice.

8-2. Packing Form

a) Package quantity in one box : 20 pcs

b) Box Size : 422X340X257

Product Specification

8-3. Label Description

Model Name

LP125WH2.(TL)(B1).

11S93P5672Z1ZHDC000001 005

Lenovo CODE

c ᴹ US

P/N:93P5672   FRU:93P5673

RoHS Verified

Factory ID : LGDNJ

LG Display

XXXXXXXXXXXXX XXX

LGD CODE

Lot Mark

LGD Code

(1) Model Name : **L P 1 2 5 W H 2 - T L B 1**

Revision Code
Product Type
Display Mode
Basic Model Serial No.
Resolution : HD
Size (inch) : 12.5"
Application : NBPC
LGPL Brand Initial: L

(2) Lot Mark   : **1 2 5 A 1 0 0 0 0 0 0 0 1**

SERIAL NO.

MONTH
YEAR
SIZE

Lenovo Code

1)P/N : 93P5672

2)FRU : 93P5673

9. PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD module.

9-1. MOUNTING PRECAUTIONS

(1) You must mount a module using holes arranged in four corners or four sides.
(2) You should consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
(3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to the resist external force.
(4) You should adopt radiation structure to satisfy the temperature specification.
(5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
(6) Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment.
Do not touch the surface of polarizer for bare hand or greasy cloth.(Some cosmetics are detrimental to the polarizer.)
(7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
(8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
(9) Do not open the case because inside circuits do not have sufficient strength.

9-2. OPERATING PRECAUTIONS

(1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage :
V=$\pm$ 200mV(Over and under shoot voltage)

(2) Response time depends on the temperature.(In lower temperature, it becomes longer.)
(3) Brightness depends on the temperature. (In lower temperature, it becomes lower.)
And in lower temperature, response time(required time that brightness is stable after turned on) becomes longer.
(4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
(5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
(6) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference.

9-3. ELECTROSTATIC DISCHARGE CONTROL

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

9-4. PRECAUTIONS FOR STRONG LIGHT EXPOSURE

Strong light exposure causes degradation of polarizer and color filter.

9-5. STORAGE

When storing modules as spares for a long time, the following precautions are necessary.

(1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
(2) The polarizer surface should not come in contact with any other object.
   It is recommended that they be stored in the container in which they were shipped.

9-6. HANDLING PRECAUTIONS FOR PROTECTION FILM

(1) When the protection film is peeled off, static electricity is generated between the film and polarizer.
   This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
(2) The protection film is attached to the polarizer with a small amount of glue. If some stress is applied to rub the protection film against the polarizer during the time you peel off the film, the glue is apt to remain on the polarizer.
   Please carefully peel off the protection film without rubbing it against the polarizer.
(3) When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the polarizer after the protection film is peeled off.
(4) You can remove the glue easily. When the glue remains on the polarizer surface or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.

APPENDIX A. Enhanced Extended Display Identification Data (EEDID™) 1/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
Header	0	00	Header		00	00000000
	1	01	Header		FF	11111111
	2	02	Header		FF	11111111
	3	03	Header		FF	11111111
	4	04	Header		FF	11111111
	5	05	Header		FF	11111111
	6	06	Header		FF	11111111
	7	07	Header		00	00000000
EDID	8	08	EISA manufacture code (3 Character ID)	LGD	30	00110000
	9	09	EISA manufacture code (Compressed ASCⅡ)		E4	11100100
	10	0A	Panel Supplier Reserved - Product Code	02D3h	D3	11010011
	11	0B	(Hex. LSB first)		02	00000010
Vendor / Product Version	12	0C	LCD Module Serial No - Preferred but Optional ("0" If not used)		00	00000000
	13	0D	LCD Module Serial No - Preferred but Optional ("0" If not used)		00	00000000
	14	0E	LCD Module Serial No - Preferred but Optional ("0" If not used)		00	00000000
	15	0F	LCD Module Serial No - Preferred but Optional ("0" If not used)		00	00000000
	16	10	Week of Manufacture	00 weeks	00	00000000
	17	11	Year of Manufacture	2011 years	15	00010101
	18	12	EDID structure version # = 1		01	00000001
	19	13	EDID revision # = 3		03	00000011
Display Parameters	20	14	Video input Definition = Digital signal		80	10000000
	21	15	Max H image size (Rounded cm) = 28 cm		1C	00011100
	22	16	Max V image size (Rounded cm) = 16 cm		10	00010000
	23	17	Display gamma = (gamma*100)-100 = Example:(2.2*100)-100=120 = 2.2 Gamma		78	01111000
	24	18	Feature Support (Standby, Suspend, Active Off/Very Low Power, RGB color display, Timing BLK 1,no_GTF)		EA	11101010
Panel Color Coordinates	25	19	Red/Green Low Bits (RxRy/GxGy)		10	00010000
	26	1A	Blue/White Low Bits (BxBy/WxWy)		A5	10100101
	27	1B	Red X Rx = 0.586		96	10010110
	28	1C	Red Y Ry = 0.345		58	01011000
	29	1D	Green X Gx = 0.340		57	01010111
	30	1E	Green Y Gy = 0.559		8F	10001111
	31	1F	Blue X Bx = 0.158		28	00101000
	32	20	Blue Y By = 0.127		20	00100000
	33	21	White X Wx = 0.313		50	01010000
	34	22	White Y Wy = 0.329		54	01010100
Established Timings	35	23	Established timing 1 (00h if not used)		00	00000000
	36	24	Established timing 2 (00h if not used)		00	00000000
	37	25	Manufacturer's timings (00h if not used)		00	00000000
Standard Timing ID	38	26	Standard timing ID1 (01h if not used)		01	00000001
	39	27	Standard timing ID1 (01h if not used)		01	00000001
	40	28	Standard timing ID2 (01h if not used)		01	00000001
	41	29	Standard timing ID2 (01h if not used)		01	00000001
	42	2A	Standard timing ID3 (01h if not used)		01	00000001
	43	2B	Standard timing ID3 (01h if not used)		01	00000001
	44	2C	Standard timing ID4 (01h if not used)		01	00000001
	45	2D	Standard timing ID4 (01h if not used)		01	00000001
	46	2E	Standard timing ID5 (01h if not used)		01	00000001
	47	2F	Standard timing ID5 (01h if not used)		01	00000001
	48	30	Standard timing ID6 (01h if not used)		01	00000001
	49	31	Standard timing ID6 (01h if not used)		01	00000001
	50	32	Standard timing ID7 (01h if not used)		01	00000001
	51	33	Standard timing ID7 (01h if not used)		01	00000001
	52	34	Standard timing ID8 (01h if not used)		01	00000001
	53	35	Standard timing ID8 (01h if not used)		01	00000001

APPENDIX A. Enhanced Extended Display Identification Data (EEDID™) 2/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
Timing Descriptor #1	54	36	Pixel Clock/10,000 (LSB)	74.8 MHz @ 60Hz	38	00111000
	55	37	Pixel Clock/10,000 (MSB)		1D	00011101
	56	38	Horizontal Active (lower 8 bits)	1366 Pixels	56	01010110
	57	39	Horizontal Blanking(Thp-HA) (lower 8 bits)	212 Pixels	D4	11010100
	58	3A	Horizontal Active / Horizontal Blanking(Thp-HA) (upper 4:4bits)		50	01010000
	59	3B	Vertical Avtive	768 Lines	00	00000000
	60	3C	Vertical Blanking (Tvp-HA) (DE Blanking typ.for DE only panels)	22 Lines	16	00010110
	61	3D	Vertical Active : Vertical Blanking (Tvp-HA) (upper 4:4bits)		30	00110000
	62	3E	Horizontal Sync. Offset (Thfp)	48 Pixels	30	00110000
	63	3F	Horizontal Sync Pulse Width (HSPW)	32 Pixels	20	00100000
	64	40	Vertical Sync Offset(Tvfp) : Sync Width (VSPW)	2 Lines : 5 Lines	25	00100101
	65	41	Horizontal Vertical Sync Offset/Width (upper 2bits)		00	00000000
	66	42	Horizontal Image Size (mm)	277 mm	15	00010101
	67	43	Vertical Image Size (mm)	156 mm	9C	10011100
	68	44	Horizontal Image Size / Vertical Image Size		10	00010000
	69	45	Horizontal Border = 0 (Zero for Notebook LCD)		00	00000000
	70	46	Vertical Border = 0 (Zero for Notebook LCD)		00	00000000
	71	47	Non-Interlace, Normal display, no stereo, Digital Separate (Vsync_NEG, Hsync_POS), DE only note : LSB is set to '1' if panel is DE-timing only. H/V can be ignored.		1B	00011011
Timing Descriptor #2	72	48	Flag		00	00000000
	73	49	Flag		00	00000000
	74	4A	Flag		00	00000000
	75	4B	Data Type Tag (Descriptor Defined by manufacturer)		00	00000000
	76	4C	Flag		00	00000000
	77	4D	Descriptor Defined by manufacturer		00	00000000
	78	4E	Descriptor Defined by manufacturer		00	00000000
	79	4F	Descriptor Defined by manufacturer		00	00000000
	80	50	Descriptor Defined by manufacturer		00	00000000
	81	51	Descriptor Defined by manufacturer		00	00000000
	82	52	Descriptor Defined by manufacturer		00	00000000
	83	53	Descriptor Defined by manufacturer		00	00000000
	84	54	Descriptor Defined by manufacturer		00	00000000
	85	55	Descriptor Defined by manufacturer		00	00000000
	86	56	Descriptor Defined by manufacturer		00	00000000
	87	57	Descriptor Defined by manufacturer		00	00000000
	88	58	Descriptor Defined by manufacturer		00	00000000
	89	59	Descriptor Defined by manufacturer		00	00000000
Timing Descriptor #3	90	5A	Flag		00	00000000
	91	5B	Flag		00	00000000
	92	5C	Flag		00	00000000
	93	5D	Data Type Tag (ASCII String)		FE	11111110
	94	5E	Flag		00	00000000
	95	5F	ASCII String	L	4C	01001100
	96	60	ASCII String	G	47	01000111
	97	61	ASCII String		20	00100000
	98	62	ASCII String	D	44	01000100
	99	63	ASCII String	i	69	01101001
	100	64	ASCII String	s	73	01110011
	101	65	ASCII String	p	70	01110000
	102	66	ASCII String	l	6C	01101100
	103	67	ASCII String	a	61	01100001
	104	68	ASCII String	y	79	01111001
	105	69	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		0A	00001010
	106	6A	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		20	00100000
	107	6B	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		20	00100000

Product Specification

APPENDIX A. Enhanced Extended Display Identification Data (EEDID^TM) 3/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments	Value (Hex)	Value (Bin)
Timing Descriptor #4	108	6C	Flag	00	00000000
	109	6D	Flag	00	00000000
	110	6E	Flag	00	00000000
	111	6F	Data Type Tag (ASCII String)	FE	11111110
	112	70	Flag	00	00000000
	113	71	ASCII String L	4C	01001100
	114	72	ASCII String P	50	01010000
	115	73	ASCII String 1	31	00110001
	116	74	ASCII String 2	32	00110010
	117	75	ASCII String 5	35	00110101
	118	76	ASCII String W	57	01010111
	119	77	ASCII String H	48	01001000
	120	78	ASCII String 2	32	00110010
	121	79	ASCII String -	2D	00101101
	122	7A	ASCII String T	54	01010100
	123	7B	ASCII String L	4C	01001100
	124	7C	ASCII String B	42	01000010
	125	7D	ASCII String 1	31	00110001
Chec	126	7E	Extension flag (# of optional 128 panel ID extension block to follow, Typ = 0)	00	00000000
	127	7F	Check Sum (The 1-byte sum of all 128 bytes in this panel ID block shall = 0)	F7	11110111