



Product Specification

AU OPTRONICS CORPORATION

- () Preliminary Specifications
(V) Final Specifications

Module	10.1”(10.01”) WXGA 16:10 Color TFT-LCD
Model Name	B101EAN02.0 (H/W: 0A) LCM
Note	<i>LED Backlight without driving circuit design</i>

Customer

Date

Checked &
Approved by

Date

Note: This Specification is subject to change without notice.

Approved by

Date

YW Lee

2015/07/30

Prepared by

Owen YW Chu

2015/07/30

MPBU Marketing Division
AU Optronics corporation



Contents

1. Handling Precautions	4
2. General Description	5
2.1 General Specification.....	5
2.2 Optical Characteristics	6
3. Functional Block Diagram	11
4. Absolute Maximum Ratings	12
4.1 Absolute Ratings of TFT LCD Module	12
4.2 Absolute Ratings of Environment.....	12
5. Electrical Characteristics	13
5.1 TFT LCD Module	13
5.2 Backlight Unit.....	20
6. Signal Interface Characteristic	21
6.1 Pixel Format Image.....	21
6.2 Integration Interface Requirement	21
6.3 MIPI Interface Timing	24
6.4 Power ON(Wake Up)/OFF(Stand-by) sequence	25
7. Panel Reliability Test.....	27
7.1 Vibration Test.....	27
7.2 Shock Test.....	27
7.3 Reliability Test	27
8. Mechanical Characteristics	28
8.1 LCM Outline Dimension	28
9. Shipping and Package	30
9.1 Shipping Label Format	30
9.2 Carton Label Format	30



Product Specification

AU OPTRONICS CORPORATION

Record of Revision

Version and Date	Page	Old description	New Description	Remark
0.0 2014/12/15	All	First Edition for Customer		
0.1 2015/03/06	30		Add label information	
0.1 2015/03/06	5		Update Screen diagonal	
0.1 2015/03/06	5		Update Pixed pitch	
0.1 2015/03/06	5		Update White Luminance	
0.1 2015/03/06	5		Update Luminance Uniformity	
0.1 2015/03/06	6		Update Contrast Ratio	
0.1 2015/03/06	6		Update Chromaticity Coordinates	
0.1 2015/03/06	22		Update Pin define of Pin 31 & 32	
0.1 2015/03/06	28, 29		Update LCM outline dimension	
0.1 2015/03/11	20		Update LED characteristics	
0.2 2015/04/08	5, 28		Update thickness	
0.3 2015/07/08	30	Shipping label	Add Z31 site	

1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) After installation of the TFT Module into an enclosure (Notebook PC Bezel, for example), do not twist nor bend the TFT Module even momentarily. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 12) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 13) Disconnecting power supply before handling LCD modules, it can prevent electric shock, DO NOT TOUCH the electrode parts, cables, connectors and LED circuit part of TFT module that a LED light bar build in as a light source of back light unit. It can prevent electrostatic breakdown.



2. General Description

B101EAN02.0 is a Color Active Matrix Liquid Crystal Display composed of a TFT LCD panel, a driver circuit, and LED backlight system. The screen format is intended to support the 16:10 WXGA, 800(H) x1280(V) screen and 16.7M colors (Real 8 bits) without LED backlight driving circuit. All input signals are MIPI interface compatible.

B101EAN02.0 is designed for a display unit of notebook style personal computer and industrial machine.

2.1 General Specification

The following items are characteristics summary on the table at 25 °C condition:

Items	Unit	Specifications			
Screen Diagonal	[mm]	255.397			
Active Area	[mm]	135.36(H) x 216.576(V)			
Pixels H x V		800 x 3(RBG) x 1280			
Pixel Pitch	[mm]	0.1692 X 0.1692			
Pixel Format		R.G.B. Vertical Stripe			
Display Mode		AHVA, Normally Black			
White Luminance	[cd/m2]	400 typ. (center point)			
Luminance Uniformity	$\bar{\delta}_{5P}$ $\bar{\delta}_{13P}$	5P Max. 1.25 13P Max. 1.42			
Contrast Ratio		Typ. 1000:1, min 800:1			
Response Time	[ms]	Typ. 30			
Nominal Input Voltage VDD	[Volt]	3.3V typ			
Power Consumption	[Watt]	Logic: 0.4 W @ full white pattern BLU: 1.66 W max. , w/o effi.			
Weight	[Grams]	134.65g Max			
Physical Size	[mm]		Min.	Typ.	Max.
		Length	227.926	228.226	228.526
		Width	141.06	141.36	141.66
		Thickness	---	---	2.4 (Panel side) 4.23 (PCBA side)
Electrical Interface		MIPI			
Surface Treatment		Glare			
Support Color		16.7M colors (Real 8 bits)			



Product Specification

AU OPTRONICS CORPORATION


Temperature Range Operating Storage (Non-Operating)	[°C] [°C]	0 to +50 -20 to +60
RoHS Compliance		RoHS Compliance

2.2 Optical Characteristics


The optical characteristics are measured under stable conditions at 25°C (Room Temperature) :

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit	Note
White Luminance		5 points average	340	400	---	cd/m ²	1, 4, 5.
Viewing Angle	θ_R θ_L	Horizontal (Right) CR \geq 10 (Left)	80 80	85 85	---	degree	4, 9
	ψ_H ψ_L	Vertical (Upper) CR \geq 10 (Lower)	80 80	85 85	---		
Luminance Uniformity	δ_{5P}	5 Points	---	---	1.25		1, 3, 4
Luminance Uniformity	δ_{13P}	13 Points	---	---	1.42		2, 3, 4
Contrast Ratio	CR		800	1000	---		4, 6
Cross talk	%		---	---	2		4, 7
Response Time	T _{RT}	Rising + Falling	---	30	35	msec	4, 8
Color / Chromaticity Coordinates	Red	R _x	0.578	0.608	0.638		4
		R _y	0.325	0.355	0.385		
	Green	G _x	0.309	0.339	0.369		
		G _y	0.568	0.598	0.628		
	Blue	B _x	0.125	0.155	0.185		
		B _y	0.057	0.087	0.117		
	White	W _x	0.275	0.305	0.335		
		W _y	0.290	0.320	0.350		
	NTSC		-	60			

Note 1: 5 points position (Ref: Active area)



Note 2: 13 points position (Ref: Active area)




Note 3: The luminance uniformity of 5 or 13 points is defined by dividing the maximum luminance values by the minimum test point luminance

$$\delta_{W5} = \frac{\text{Maximum Brightness of five points}}{\text{Minimum Brightness of five points}}$$

$$\delta_{W13} = \frac{\text{Maximum Brightness of thirteen points}}{\text{Minimum Brightness of thirteen points}}$$

Note 4: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room, and it should be measured in the center of screen.



Note 5 : Definition of Average Luminance of White (Y_L):

Measure the luminance of gray level 63 at 5 points , $Y_L = [L(1) + L(2) + L(3) + L(4) + L(5)] / 5$

$L(x)$ is corresponding to the luminance of the point X at Figure in Note (1).

Note 6 : Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$


Note 7 : Definition of Cross Talk (CT)

$$CT = |Y_B - Y_A| / Y_A \times 100 (\%)$$

Where


Y_A = Luminance of measured location without gray level 0 pattern (cd/m²)

Y_B = Luminance of measured location with gray level 0 pattern (cd/m²)




Note 8: Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are changed from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval between the 10% and 90% of amplitudes. Refer to figure as below.




Note 9. Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° (θ) horizontal left and right and 90° (Φ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



3. Functional Block Diagram

The following diagram shows the functional block of the 10.1 inches wide Color TFT/LCD 39 Pin one channel Module



4. Absolute Maximum Ratings

An absolute maximum rating of the module is as following:

4.1 Absolute Ratings of TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	Vin	-0.3	+4.0	[Volt]	Note 1,2


4.2 Absolute Ratings of Environment

Item	Symbol	Min	Max	Unit	Conditions
Operating Temperature	TOP	0	+50	[°C]	Note 3
Operation Humidity	HOP	5	95	[%RH]	Note 3
Storage Temperature	TST	-20	+60	[°C]	Note 3
Storage Humidity	HST	5	95	[%RH]	Note 3


Note 1: At Ta (25°C)

Note 2: Permanent damage to the device may occur if exceed maximum values

Note 3: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).



Operating Range 

Storage Range  + 

5. Electrical Characteristics

5.1 TFT LCD Module

5.1.1 Power Specification


Input power specifications are as follows. The power specification are measured under 25°C and frame frequency under 60Hz

Symble	Parameter	Min	Typ	Max	Units	Note
VDD	Logic/LCD Drive Voltage	1.7	1.8	1.9	[Volt]	
PDD	VDD Power	-	0.036		[Watt]	
IDD	IDD Current	-	-		[mA]	

Symble	Parameter	Min	Typ	Max	Units	Note
VDD	Logic/LCD Drive Voltage	3.0	3.3	3.6	[Volt]	
PDD	VDD Power	-	-	0.4	[Watt]	Note 1
IDD	IDD Current	-	-	121	[mA]	Note 1
IRush	Inrush Current	-	-	1500	[mA]	Note 2
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	100	[mV] p-p	

Note 1 : Maximum Measurement Condition : White Pattern at 3.3V driving voltage. ($P_{max} = V_{3.3} \times I_{white}$)

Note 2 : Measure Condition




5.1.2 Signal Electrical Characteristics

Input signals shall be low or High-impedance state when VDD is off.

MIPI DC characteristics are as follows:

Parameter	Symbol	Conditions	Specification			Unit
			MIN	TYP	MAX	
Power supply voltage for MIPI Interface						
Power supply voltage for MIPI interface	VDDAM	-	1.75	2.8	6.0	V
	LVDSVDD	-	1.15	1.2	1.375	V
LPDT Input Characteristics						
Pad signal voltage range	VI	-	-50	-	1350	mV
Ground Shift	VGND SH	-	-50	-	50	mV
Logic 0 input threshold	VIL	-	0	-	550	mV
Logic 1 input threshold	VIH	-	880	-	LVDSVDD	mV
Input hysteresis	VHYST	-	25	-	-	mV
LPDT Output Characteristics						
Output low level	VOL	-	-50	-	50	mV
Output high level	VOH	-	1.1	1.2	1.3	V
Logic 1 contention threshold	VIHCD,MIN	-	450	-	LVDSVDD	mV
Logic 0 contention threshold	VILCD,MAX	-	0	-	200	mV
Output impedance of LPDT	ZOLP	-	80	100	125	ohm
Hi-speed Input/Output Characteristics						
Single-end input low voltage	VILHS	-	-40	-	-	mV
Single-end input high voltage	VIHHS	-	-	-	460	mV
Common mode voltage	VCMRXDC	-	70	-	330	mV
Hi-speed transmit voltage	VOD	-	140	200	250	mV
Differential input impedance	ZID	-	80	100	125	ohm



IC Interface Characteristics




Table: I2C Interface Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
f_{SCLK}	SCL clock frequency	-	DC	-	400	KHz
T_{LOW}	SCL clock LOW period	-	1.3	-	-	#s
T_{HIGH}	SCL clock HIGH period	-	0.6	-	-	#s
$T_{SU;DATA}$	data set-up time	-	100	-	-	ns
$T_{HD;DATA}$	data hold time	-	0	-	0.9	#s
T_r	SCL and SDA rise time	Note 2	$20+0.1C_b$	-	300	ns
T_f	SCL and SDA fall time	Note 2	$20+0.1C_b$	-	300	ns
T_f	SDA fall time for read out	-	$20+0.1C_b$	-	1000	ns
C_b	Capacitive load represented by each bus line	-	-	-	400	pF
$T_{SU;STA}$	Setup time for a repeated START condition	-	0.6	-	-	#s
$T_{HD;STA}$	START condition hold time	-	0.6	-	-	#s
$T_{SU;STO}$	Setup time for STOP condition	-	0.6	-	-	#s
T_{SW}	Tolerable spike width on bus	Note 1	-	-	50	ns
T_{BUF}	BUS free time between a STOP and START condition	-	1.3	-	-	#s




Note1: The device inputs SDA and SCL are filtered and will reject spikes on the bus lines of width $< t_{SW(max)}$.

Note2: The rise and fall times specified here refer to the driver device and are part of the general fast I^2C -bus specification. C_b = capacitive load per bus line.

Note3: All timing values are valid within the operating supply voltage and ambient temperature ranges and are referenced to V_{IL} and V_{IH} with an input voltage swing of V_{SS} to V_{DDI}

MIPI High-Speed Data-clock Timing


Parameter	Symbol	Parameter	Specification			Unit
			MIN	TYP	MAX	
High Speed Mode						
DSI-CLK+/-	2xUI _{INST}	Double UI instantaneous	2.22	-	25	ns
DSI-CLK+/-	UI _{INSTA} , UI _{INSTB}	UI instantaneous Halfs	1.11	-	12.5	ns
DSI-Dn+/-	t _{DS}	Data to clock setup time	0.15	-	-	UI
DSI-Dn+/-	t _{DH}	Data to clock hold time	0.15	-	-	UI
DSI-CLK+/-	t _{DRTCLK}	Differential rise time for clock	150	-	0.3UI	ps
DSI-Dn+/-	t _{DRTDATA}	Differential rise time for data	150	-	0.3UI	ps
DSI-CLK+/-	t _{DFTCLK}	Differential fall time for clock	150	-	0.3UI	ps
DSI-Dn+/-	t _{DFTDATA}	Differential fall time for data	150	-	0.3UI	ps



The timing definitions are listed in below:


Parameter	Symbol	Parameter	Specification			Unit
			MIN	TYP	MAX	
High Speed Data Transmission Bursts						
DSI-Dn+/-	T _{LPX}	Length of any low-power state period	50	-	-	ns
DSI-Dn+/-	T _{HS-PREPARE}	Time to drive LP-00 to prepare for HS transmission	40ns + 4UI	-	85ns + 6UI	ns
DSI-Dn+/-	T _{HS-PREPARE} + T _{HS-ZERO}	T _{HS-PREPARE} + time to drive HS-0 before the sync sequence	145ns + 10UI	-	-	ns
DSI-Dn+/-	T _{D-TERM-EN}	Time to enable Data Lane receiver line termination measured from when Dn crosses V _{IL(max)}	Time for Dn to reach V _{TERM-EN}	-	35ns + 4UI	ns
DSI-Dn+/-	T _{HS-SKIP}	Time-out at RX to ignore transition period of EoT	40	-	55ns + 4UI	ns
DSI-Dn+/-	T _{HS-TRAIL}	Time to drive flipped differential state after last payload data bit of a HS transmission burst	max (8UI, 60ns+4UI)	-	-	ns
DSI-Dn+/-	T _{HS-EXIT}	Time to drive LP-11 after HS burst	100	-	-	ns
DSI-Dn+/-	T _{EoT}	Time from start of T _{HS-TRAIL} period to start of LP-11 state	-	-	105ns + 12UI	ns

High-Speed Data Transmission in Bursts



Parameter	Symbol	Parameter	Specification			Unit
			MIN	TYP	MAX	
Switching the clock Lane between clock Transmission and Low Power Mode						
DSI-CLK+/-	T _{CLK-POST}	Time that the transmitter shall continue sending HS clock after the last associated Data Lane has transitioned to LP mode	60ns + 52UI	-	-	ns
DSI-CLK+/-	T _{CLK-PRE}	Time that the HS clock shall be driven prior to any associated Data Lane beginning the transition from LP to HS mode	8	-	-	UI
DSI-CLK+/-	T _{CLK-PREPARE}	Time to drive LP-00 to prepare for HS clock transmission	38	-	95	ns
DSI-CLK+/-	T _{CLK-TERM-EN}	Time to enable Clock Lane receiver line termination measured from when Dn crosses V _{IL(max)}	Time for Dn to reach V _{TERM-EN}	-	38	ns
DSI-CLK+/-	T _{CLK-PREPARE} + T _{CLK-ZERO}	T _{CLK-PREPARE} + time for lead HS-0 drive period before starting Clock	300	-	-	ns
DSI-CLK+/-	T _{CLK-TRAIL}	Time to drive HS differential state after last payload clock bit of a HS transmission burst	60	-	-	ns
DSI-CLK+/-	T _{EoT}	Time from start of T _{CLK-TRAIL} period to start of LP-11 state	-	-	105ns + 12UI	ns

Switching the Clock Lane between Clock Transmission and Low-Power Mode



5.2.1 LED characteristics


Parameter	Symbol	Min	Typ	Max	Units	Condition
Backlight Power Consumption (W/O Efficiency)	PLED			1.66	[Watt]	Note 1 (Ta= 25℃)
LED Forward Voltage	VF	2.8	3.0	3.1	[Volt]	(Ta= 25℃)
LED Forward Voltage of every LED string	Vf-string	16.8	18.0	18.6	[Volt]	
LED Forward Current	IF		22		[mA]	(Ta= 25℃)
LED Life time	N/A	>15000			Hour	Note 1 (Ta=25℃)

Note 1: calculator value for reference PLED based on 20 mA

6. Signal Interface Characteristic

6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.



6.2 Integration Interface Requirement

6.2.1 MIPI/TP Connector Description

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

Connector Name / Designation	For Signal Connector
Manufacturer	Panasonic
Type / Part Number	AYF333935
Mating Housing/Part Number	FPC or Compatible



Product Specification

AU OPTRONICS CORPORATION

6.2.2 MIPI Pin Assignment

MIPI is a differential signal technology for LCD interface and high speed data transfer device.

	Signal Name	Description
1	VLED	Anode for BLU
2	VLED	Anode for BLU
3	NC	No connection
4	NC	No connection
5	VLED_Isink1	Current sink for LED String 1
6	VLED_Isink2	Current sink for LED String 2
7	VLED_Isink3	Current sink for LED String 3
8	VLED_Isink4	Current sink for LED String 4
9	NC	No connection
10	GND	Ground
11	RST	Device reset signal (1.8V)
12	NC	No connection (AUO OTP Use)
13	SDA	For AUO internal use
14	SCL	For AUO internal use
15	GND	Ground
16	DSI_D2P	MIPI input data pair
17	DSI_D2N	MIPI input data pair
18	GND	Ground
19	DSI_D1P	MIPI input data pair
20	DSI_D1N	MIPI input data pair
21	GND	Ground
22	DSI_CLKP	MIPI input CLK pair
23	DSI_CLKN	MIPI input CLK pair
24	GND	Ground
25	DSI_D0P	MIPI input data pair
26	DSI_D0N	MIPI input data pair
27	GND	Ground
28	DSI_D3P	MIPI input data pair
29	DSI_D3N	MIPI input data pair
30	GND	Ground
31	ID0	1 (預留 0 ohm 對 GND 電阻，電阻預設不上件)
32	ID1	0 (預留 0 ohm 對 GND 電阻，電阻預設上件)
33	NC	No connection
34	ID2	1 (預留 0 ohm 對 GND 電阻，電阻預設不上件)
35	VDD	Power supply(3.3V)



Product Specification

AU OPTRONICS CORPORATION

36	VDD	Power supply(3.3V)
37	VDD	Power supply(3.3V)
38	Core_VDD	Power supply for T/CON Logic(1.8V)
39	Core_VDD	Power supply for T/CON Logic(1.8V)

6.3 MIPI Interface Timing

6.3.1 Timing Characteristics


Basically, interface timings should match the 800 x 1280 /60 Hz manufacturing guide line timing.

Vertical Total	VT (tv)	1300	line
Vertical Front-Porch	VFP (tvp)	8	line
Vertical Active	VA (tvd)	1280	line
Vertical Sync.	VS (twv)	4	line
Vertical Back-Porch	VBP (tvbp)	8	line
Horizontal Total	HT (th)	960	clk(pixel)
Horizontal Front-Porch	HFP (thfp)	24	clk(pixel)
Horizontal Active	HA (thd)	800	clk(pixel)
Horizontal Sync.	HS (thw)	4	clk(pixel)
Horizontal Back-Porch	HBP (thbp)	132	clk(pixel)
Pixel Frequency	CLK (fc)	75.00	MHz

Driving


(LVDS Receiver Output)

Vertical Timing



Item	T1 Vertical Blanking	T2 Active Field	T3 VSYNC Front Porch	T4 Frame Time	T5 VSYNC Width	T6 VSYNC Back Porch
Value	20	1280	8	1300	4	8

Horizontal Timing



Item	T7 Horizontal Blanking	T8 Active Field	T9 HSYNC Front Porch	T10 H line Time	T11 HSYNC Width	T12 HSYNC Back Porch
Value	160	800	24	960	4	132


Dot Timing

Item	Dot Clock Frequency	Data Clock Frequency
Value	75MHz	Dot Clock Frequency

6.4 Power ON(Wake Up)/OFF(Stand-by) sequence

6.4.1 Power

Power on/off sequence is as follows. Interface signals and LED on/off sequence are also shown in the chart.



Power Sequence Timing			
Parameter	Value		Units
	Min.	Max.	
T1	0.5	10	ms
T2	1	-	
T3	0.5	10	
T4	0	50	
T5	0	0.002	
T6	1	-	
T7	0	0.002	
T8	0.01	-	
T9	5	-	
T10	180	-	
T11	33.4	-	
T12	200	-	
T13	200	-	
T14	33.4	-	
T15	180	-	
T16	50	-	
T17	120	-	
T18	0	10	
T19	0	10	
T20	0	10	
T21	500	-	

6.4.2 MIPI Command

T10 : power on => initial code + sleep out(0x11) (by panel different)

T11 : display on (0x29)

T14 : display off (0x28)

T15 : power off => sleep in (0x10)

7. Panel Reliability Test

7.1 Vibration Test

Test Spec:

- Test method: Non-Operation
- Acceleration: 1.5 G
- Frequency: 10 - 500Hz Random
- Sweep: 30 Minutes each Axis (X, Y, Z)

7.2 Shock Test

Test Spec:

- Test method: Non-Operation
- Acceleration: 220 G , Half sine wave
- Active time: 2 ms
- Pulse: X,Y,Z .one time for each side

7.3 Reliability Test

Items	Required Condition	Note
Temperature Humidity Bias	Ta= 40℃ , 90%RH, 300h	
High Temperature Operation	Ta= 50℃ , Dry, 300h	
Low Temperature Operation	Ta= 0℃ , 300h	
High Temperature Storage	Ta= 60℃ , 300h	
Low Temperature Storage	Ta= -20℃ , 300h	
Thermal Shock Test	Ta=-20℃to 60℃ , Duration at 30 min, 100 cycles	
ESD	Contact : ±8 KV Air : ±15 KV	Note 1


Note1: According to EN 61000-4-2 , ESD class B: Some performance degradation allowed. No data lost
. Self-recoverable. No hardware failures.

Remark: MTBF (Excluding the LED): 30,000 hours with a confidence level 90%


8. Mechanical Characteristics

8.1 LCM Outline Dimension

8.1.1 Standard Front View













8.1.2 Standard Rear View







9. Shipping and Package

9.1 Shipping Label Format

	<p>Manufactured YY/WW Model No: B101EAN02.0 AU Optronics MADE IN CHINA (Z30) H/W: 0A F/W:0</p>	<p>c   E204356  </p>
 B101EAN02.0		

	<p>Manufactured YY/WW Model No: B101EAN02.0 AU Optronics MADE IN CHINA (Z31) H/W: 0A F/W:0</p>	<p>c   E204356  </p>
 B101EAN02.0		

9.2 Carton Label Format

AU Optronics	QTY : 56	
MODEL NO : B101EAN02.0		
PART NO : 97.10B56.000		
CUSTOMER NO :		
CARTON NO :		
		
xxxxxx-xxxxxxxxxxx		
MADE IN CHINA		



Product Specification

AU OPTRONICS CORPORATION

AU Optronics

QTY : 48



MODEL NO : B101EAN02.0



PART NO : 97.10B56.001



CUSTOMER NO :

CARTON NO :



XXXXXX-XXXXXXXXXXXX

MADE IN CHINA