



() Preliminary Specifications
(V) Final Specifications

Module	15 Inch Color TFT-LCD
Model Name	G150XAN01.0

Customer**Date****Checked &
Approved by****Approved by****Date**2019/3/26**Prepared by**2019/3/26

General Display Business Unit /
AU Optronics corporation

Contents

1. Operating Precautions	4
2. General Description	5
2.1 Display Characteristics	5
2.2 Optical Characteristics	6
3. Functional Block Diagram	9
4. Absolute Maximum Ratings.....	10
4.1 Absolute Ratings of TFT LCD Module.....	10
4.2 Absolute Ratings of Environment.....	10
5.1 TFT LCD Module	11
5.2 Backlight Unit.....	13
6. Signal Characteristic.....	14
6.1 Pixel Format Image.....	14
6.2 Scanning Direction.....	14
6.3 Signal Description	15
6.4 The Input Data Format.....	16
6.5 Interface Timing	17
6.6 Power ON/OFF Sequence	18
7. Connector & Pin Assignment	19
7.1 TFT LCD Module: LVDS Connector.....	19
7.2 LED Backlight Unit: LED Driver Connector	20
7.2 LED Backlight Unit: LED Driver Connector	21
7.3 LED Driver Connector Pin Assignment	21
8. Reliability Test Criteria.....	22
9. Mechanical Characteristics	23
9.1 LCM Outline Dimension (Front View).....	23
9.2 CM Outline Dimension (Rear View)	24
10. Label and Packaging.....	25
10.1 Shipping Label (on the rear side of TFT-LCD display)	25
10.2 Carton Package	25
10.3 Palletizing.....	26
11 Safety.....	27
11.1 Sharp Edge Requirements.....	27
11.2 Materials.....	27
11.3 Capacitors	27
11.4 National Test Lab Requirement.....	27

Record of Revision

Version and Date	Page	Old description	New Description																																																																																																																		
0.0 2017/12/15	All	First Edition																																																																																																																			
0.1 2018/06/20	17	<div>6.5.1 Timing Characteristics<table><thead><tr><th>Signal</th><th>Parameter</th><th>Symbol</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th></tr></thead><tbody><tr><td>Clock Timing</td><td>Clock frequency</td><td>1/T_{CLK}</td><td>50</td><td>65</td><td>81</td><td>MHz</td></tr><tr><td rowspan="3">Vsync Timing</td><td rowspan="3">Vertical Section</td><td>Period</td><td>T_V</td><td>783</td><td>806</td><td>968</td><td rowspan="3">T_{Line}</td></tr><tr><td>Active</td><td>T_{VD}</td><td>768</td><td>768</td><td>768</td></tr><tr><td>Blanking</td><td>T_{VB}</td><td>15</td><td>38</td><td>200</td></tr><tr><td rowspan="3">Hsync Timing</td><td rowspan="3">Horizontal Section</td><td>Period</td><td>T_H</td><td>1224</td><td>1344</td><td>2024</td><td rowspan="3">T_{Clock}</td></tr><tr><td>Active</td><td>T_{HD}</td><td>1024</td><td>1024</td><td>1024</td></tr><tr><td>Blanking</td><td>T_{HB}</td><td>200</td><td>320</td><td>1000</td></tr><tr><td colspan="2">Frame Rate</td><td>F</td><td></td><td>60</td><td></td><td>Hz</td></tr></tbody></table></div>	Signal	Parameter	Symbol	Min.	Typ.	Max.	Unit	Clock Timing	Clock frequency	1/T _{CLK}	50	65	81	MHz	Vsync Timing	Vertical Section	Period	T _V	783	806	968	T _{Line}	Active	T _{VD}	768	768	768	Blanking	T _{VB}	15	38	200	Hsync Timing	Horizontal Section	Period	T _H	1224	1344	2024	T _{Clock}	Active	T _{HD}	1024	1024	1024	Blanking	T _{HB}	200	320	1000	Frame Rate		F		60		Hz	<div>6.5.1 Timing Characteristics<table><thead><tr><th>Signal</th><th>Parameter</th><th>Symbol</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th></tr></thead><tbody><tr><td>Clock Timing</td><td>Clock frequency</td><td>1/T_{CLK}</td><td>63</td><td>65</td><td>67</td><td>MHz</td></tr><tr><td rowspan="3">Vsync Timing</td><td rowspan="3">Vertical Section</td><td>Period</td><td>T_V</td><td>804</td><td>806</td><td>808</td><td rowspan="3">T_{Line}</td></tr><tr><td>Active</td><td>T_{VD}</td><td>768</td><td>768</td><td>768</td></tr><tr><td>Blanking</td><td>T_{VB}</td><td>36</td><td>38</td><td>40</td></tr><tr><td rowspan="3">Hsync Timing</td><td rowspan="3">Horizontal Section</td><td>Period</td><td>T_H</td><td>1328</td><td>1344</td><td>1360</td><td rowspan="3">T_{Clock}</td></tr><tr><td>Active</td><td>T_{HD}</td><td>1024</td><td>1024</td><td>1024</td></tr><tr><td>Blanking</td><td>T_{HB}</td><td>304</td><td>320</td><td>336</td></tr><tr><td colspan="2">Frame Rate</td><td>F</td><td>59</td><td>60</td><td>61</td><td>Hz</td></tr></tbody></table></div>	Signal	Parameter	Symbol	Min.	Typ.	Max.	Unit	Clock Timing	Clock frequency	1/T _{CLK}	63	65	67	MHz	Vsync Timing	Vertical Section	Period	T _V	804	806	808	T _{Line}	Active	T _{VD}	768	768	768	Blanking	T _{VB}	36	38	40	Hsync Timing	Horizontal Section	Period	T _H	1328	1344	1360	T _{Clock}	Active	T _{HD}	1024	1024	1024	Blanking	T _{HB}	304	320	336	Frame Rate		F	59	60	61	Hz
Signal	Parameter	Symbol	Min.	Typ.	Max.	Unit																																																																																																															
Clock Timing	Clock frequency	1/T _{CLK}	50	65	81	MHz																																																																																																															
Vsync Timing	Vertical Section	Period	T _V	783	806	968	T _{Line}																																																																																																														
		Active	T _{VD}	768	768	768																																																																																																															
		Blanking	T _{VB}	15	38	200																																																																																																															
Hsync Timing	Horizontal Section	Period	T _H	1224	1344	2024	T _{Clock}																																																																																																														
		Active	T _{HD}	1024	1024	1024																																																																																																															
		Blanking	T _{HB}	200	320	1000																																																																																																															
Frame Rate		F		60		Hz																																																																																																															
Signal	Parameter	Symbol	Min.	Typ.	Max.	Unit																																																																																																															
Clock Timing	Clock frequency	1/T _{CLK}	63	65	67	MHz																																																																																																															
Vsync Timing	Vertical Section	Period	T _V	804	806	808	T _{Line}																																																																																																														
		Active	T _{VD}	768	768	768																																																																																																															
		Blanking	T _{VB}	36	38	40																																																																																																															
Hsync Timing	Horizontal Section	Period	T _H	1328	1344	1360	T _{Clock}																																																																																																														
		Active	T _{HD}	1024	1024	1024																																																																																																															
		Blanking	T _{HB}	304	320	336																																																																																																															
Frame Rate		F	59	60	61	Hz																																																																																																															
	25	10.2 Carton Package NA	10.2 Carton Package Update Packing Spec & drawing.																																																																																																																		
	26	10.3 Palletizing NA	10.3 Palletizing Update Palletizing Spec & drawing.																																																																																																																		
0.2 2018/09/04	5	2.2 Optical Characteristics White Luminance 280(Min), 350(Typ)	2.2 Optical Characteristics White Luminance 320(Min), 400(Typ)																																																																																																																		
0.3 2018/12/11	6	<div>2.2 Optical Characteristics<table><tr><td>White x</td><td>0.263</td><td>0.313</td><td>0.363</td></tr><tr><td>White y</td><td>0.279</td><td>0.329</td><td>0.379</td></tr></table></div>	White x	0.263	0.313	0.363	White y	0.279	0.329	0.379	<div>2.2 Optical Characteristics<table><tr><td>White x</td><td>0.253</td><td>0.303</td><td>0.353</td></tr><tr><td>White y</td><td>0.269</td><td>0.319</td><td>0.369</td></tr></table></div>	White x	0.253	0.303	0.353	White y	0.269	0.319	0.369																																																																																																		
White x	0.263	0.313	0.363																																																																																																																		
White y	0.279	0.329	0.379																																																																																																																		
White x	0.253	0.303	0.353																																																																																																																		
White y	0.269	0.319	0.369																																																																																																																		
	24	9.2 LCM Outline Dimension (Rear View) BLU CN : 45.9mm LVDS CN : 46.1mm	9.2 LCM Outline Dimension (Rear View) BLU CN : 41.4mm LVDS CN : 41.6mm																																																																																																																		

1. Operating Precautions

- 1) Since front polarizer is easily damaged, please be cautious and not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or soft cloth.
- 5) Since the panel is made of glass, it may be broken or cracked if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the module assembly.
- 8) Do not press the reflector sheet at the back of the module to any direction.
- 9) In case if a module has to be put back into the packing container slot after it was taken out from the container, do not press the center of the LED Reflector edge. Instead, press at the far ends of the LED Reflector edge softly. Otherwise the TFT Module may be damaged.
- 10) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) TFT-LCD Module is not allowed to be twisted & bent even force is added on module in a very short time. Please design your display product well to avoid external force applying to module by end-user directly.
- 12) Small amount of materials without flammability grade are used in the TFT-LCD module. The TFT-LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950-1 or UL60950-1), or be applied exemption.
- 13) Severe temperature condition may result in different luminance, response time.
- 14) Continuous operating TFT-LCD Module under high temperature environment may accelerate LED light bar exhaustion and reduce luminance dramatically.
- 15) The data on this specification sheet is applicable when TFT-LCD module is placed in landscape position.
- 16) Continuous displaying fixed pattern may induce image sticking. It's recommended to use screen saver or moving content periodically if fixed pattern is displayed on the screen.

2. General Description

G150XAN01.0 is a Color Active Matrix Liquid Crystal Display composed of a TFT-LCD display, a driver circuit, and a backlight system. The screen format is intended to support XGA (1024(H) x 768(V)) screen and 16.2M (RGB 6+2FRC) colors. All input signals are LVDS interface compatible.

G150XAN01.0 is designed for industrial display applications.

2.1 Display Characteristics

The following items are characteristics summary on the table under 25 °C condition:

Items	Unit	Specifications
Screen Diagonal	[inch]	15
Active Area	[mm]	304.128(H) x 228.096(V)
Pixels H x V		1024x3(RGB) x 768
Pixel Pitch	[mm]	0.297 x 0.297
Pixel Arrangement		R.G.B. Vertical Stripe
Display Mode		AHVA
Nominal Input Voltage VDD	[Volt]	3.3 typ.
Typical Power Consumption	[Watt]	7.5 W
Weight	[Grams]	920g (max.)
Physical Size	[mm]	326.5(H) x 253.5(V) x 9.0 (D)
Electrical Interface		LVDS
Surface Treatment		Anti-glare, Hardness 3H
Support Color		16.2M colors
Temperature Range Operating Storage (Non-Operating)	[°C] [°C]	-20 to +70 (+70 °C as panel surface temperature)
RoHS Compliance		RoHS Compliance
Light Bar Unit		LED, Non-Replaceable

2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25°C (Room Temperature):

Item	Unit	Conditions	Min.	Typ.	Max.	Note
White Luminance	[cd/m ²]		320	400	-	1
Uniformity	%	9 Points	75	80	-	1, 2, 3
Contrast Ratio			800	1000	-	4
Cross talk	%		-	--	1.5	5
Response Time	[msec]	Rising	-			6
	[msec]	Falling	-			
	[msec]	Raising + Falling	-	25	30	
Viewing Angle	[degree]	Horizontal (Right) CR = 10 (Left)	80	89	-	7
	[degree]		80	89	-	
	[degree]	Vertical (Upper) CR = 10 (Lower)	80	89	-	
	[degree]		80	89	-	
Color / Chromaticity Coordinates (CIE 1931)		Red x	0.569	0.619	0.669	
		Red y	0.302	0.352	0.402	
		Green x	0.279	0.329	0.379	
		Green y	0.559	0.609	0.659	
		Blue x	0.100	0.150	0.200	
		Blue y	0.068	0.118	0.168	
		White x	0.253	0.303	0.353	
		White y	0.269	0.319	0.369	
Color Gamut	%			60	-	


Note 1: Measurement method

Equipment Pattern Generator, Power Supply, Digital Voltmeter, Luminance meter (SR_3 or equivalent)


Aperture 1° with 50cm viewing distance

Test Point Center

Environment < 1 lux



Note 2: Definition of 9 points position (Display active area: 304.128(H) x 228.096(V))



Note 3: The luminance uniformity of 9 points is defined by dividing the minimum luminance values by the maximum test point luminance

$$\delta_{w9} = \frac{\text{Minimum Brightness of nine points}}{\text{Maximum Brightness of nine points}}$$

Note 4 : Definition of contrast ratio (CR):

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$


Note 5 : Definition of cross talk (CT)

$$CT = |YB - YA| / YA \times 100 (\%)$$

Where


YA = Luminance of measured location without gray level 0 pattern (cd/m²)

YB = Luminance of measured location with gray level 0 pattern (cd/m²)




Note 6: Definition of response time:

The output signals of photo detector are measured when the input signals are changed from “White” to “Black” (falling time) and from “Black” to “White” (rising time), respectively. The response time interval is between 10% and 90% of amplitudes. Please refer to the figure as below.




Note 7: Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as below: 90° (θ) horizontal left and right, and 90° (ϕ) vertical high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated to its center to develop the desired measurement viewing angle.



3. Functional Block Diagram

The following diagram shows the functional block of the 15 inch color TFT/LCD module:



4. Absolute Maximum Ratings

4.1 Absolute Ratings of TFT LCD Module


Item	Symbol	Min	Max	Unit
Logic/LCD Drive Voltage	V _{in}	-0.3	+3.6	[Volt]

4.2 Absolute Ratings of Environment

Item	Symbol	Min	Max	Unit
Operating Temperature	TOP	-20	+70*	[°C]
Operation Humidity	HOP	8	90	[%RH]
Storage Temperature	TST	-20	+70	[°C]
Storage Humidity	HST	8	90	[%RH]

Note: Maximum Wet-Bulb should be 39°C and no condensation.

* 70°C is panel surface temperature





5. Electrical Characteristics

5.1 TFT LCD Module

5.1.1 Power Specification

Symbol	Parameter	Min	Typ	Max	Units	Remark
VDD	Logic/LCD Drive Voltage	3.0	3.3	3.6	[Volt]	± 10%
IDD	VDD Current	-	0.43	0.52	[A]	All White Pattern (VDD=3.3V, at 60Hz)
Irush	LCD Inrush Current			3	[A]	Note 1
PDD	VDD Power	-	1.41	1.70	[Watt]	All White Pattern (VDD=3.3V, at 60Hz)

Note 1: Measurement condition:



VDD rising time



64 Gray pattern

5.1.2 Signal Electrical Characteristics


Input signals shall be low or Hi-Z state when VDD is off.

Symbol	Item	Min.	Typ.	Max.	Unit	Remark
V_{TH}	Differential Input High Threshold	-	-	100	[mV]	$V_{CM}=1.2V$
V_{TL}	Differential Input Low Threshold	-100	-	-	[mV]	$V_{CM}=1.2V$
$ VID $	Input Differential Voltage	100		600	[mV]	
V_{ICM}	Differential Input Common Mode Voltage	1.0	1.2	1.5	[V]	$V_{TH}/V_{TL}=\pm 100mV$


Note: LVDS Signal Waveform.

$V_P - V_N = |VID| > V_{TH} = \text{"High"}$
 $V_P - V_N = -|VID| < V_{TL} = \text{"Low"}$

Single-end Signal



Differential Signal



5.2 Backlight Unit

5.2.1 Parameter guideline for LED

Following characteristics are measured under stable condition using a LED driving board at 25°C (Room Temperature).

Symbol	Parameter	Min.	Typ.	Max.	Unit	Remark
V _{CC}	Input Voltage	10.8	12	13.2	Volt	
I _{VCC}	Input Current	-	0.49	0.54	A	100% Dimming
P _{LED}	Power Consumption	-	5.9	6.48	Watt	100% Dimming
I _{rush}	Inrush Current			2	A	
V _{LED on/off}	On Control Voltage	2.5	3.3	5.5	Volt	
	Off Control Voltage			0.5	Volt	
F _{PWM}	PWM Dimming Frequency	200		10k	Hz	
	High Voltage	2.5	3.3	5.5	Volt	
	Low Voltage			0.5	Volt	
	Dimming Duty Cycle	5	-	100	%	
I _F	LED Forward Current		60		mA	Ta = 25°C
Operating Life		50,000			Hrs	Ta = 25°C

Note 1: Ta means ambient temperature of TFT-LCD module.


Note 2: If G150XAN01.0 module is driven at high ambient temperature & humidity condition. The operating life will be reduced.

Note 3: Definition of life time: LED brightness becomes 50% of its original value. The minimum life time of LED unit is defined at the condition of I_{RLED} = 60 mA and 25±2°C (Room temperature).

6. Signal Characteristic


6.1 Pixel Format Image

Following figure shows the relationship between input signal and LCD pixel format.



6.2 Scanning Direction

The following figures show the image seen from the front view. The arrow indicates the direction of scan.




6.3 Signal Description

LVDS is a differential signal technology for LCD interface and high speed data transfer device.

MSB240420E(STM)		
Pin No.	Symbol	Description
1	VDD	Power Supply, 3.3V (typical)
2	VDD	Power Supply, 3.3V (typical)
3	NC	No Connect
4	NC	No Connect
5	Rin1-	- LVDS differential data input (R0-R5, G0)
6	Rin1+	+ LVDS differential data input (R0-R5, G0)
7	VSS	Ground
8	Rin2-	- LVDS differential data input (G1-G5, B0-B1)
9	Rin2+	+ LVDS differential data input (G1-G5, B0-B1)
10	VSS	Ground
11	Rin3-	- LVDS differential data input (B2-B5, HS, VS, DE)
12	Rin3+	+ LVDS differential data input (B2-B5, HS, VS, DE)
13	VSS	Ground
14	ClkIN-	- LVDS differential clock input
15	ClkIN+	+ LVDS differential clock input
16	GND	Ground
17	Rin4-	- LVDS differential data input (R6-R7, G6-G7, B6-B7)
18	Rin4+	+ LVDS differential data input (R6-R7, G6-G7, B6-B7)
19	VSS	Ground
20	VSS	Ground

Note 1: Input signals shall be in low status when VDD is off.

6.4 The Input Data Format



Note1: Please follow PSWG.

Note2: R/G/B data 7:MSB, R/G/B data 0:LSB

Signal Name	Description	Remark
R7 R6 R5 R4 R3 R2 R1 R0	Red Data 7 Red Data 6 Red Data 5 Red Data 4 Red Data 3 Red Data 2 Red Data 1 Red Data 0	Red-pixel Data For 8Bits LVDS input MSB: R7 ; LSB: R0
G7 G6 G5 G4 G3 G2 G1 G0	Green Data 7 Green Data 6 Green Data 5 Green Data 4 Green Data 3 Green Data 2 Green Data 1 Green Data 0	Green-pixel Data For 8Bits LVDS input MSB: G7 ; LSB: G0
B7 B6 B5 B4 B3 B2 B1 B0	Blue Data 7 Blue Data 6 Blue Data 5 Blue Data 4 Blue Data 3 Blue Data 2 Blue Data 1 Blue Data 0	Blue-pixel Data For 8Bits LVDS input MSB: B7 ; LSB: B0
RxCLKIN	LVDS Data Clock	
DE	Data Enable Signal	When the signal is high, the pixel data shall be valid to be displayed.

Note: Output signals from any system shall be low or Hi-Z state when VDD is off.

6.5 Interface Timing


6.5.1 Timing Characteristics

Signal	Parameter		Symbol	Min.	Typ.	Max.	Unit
Clock Timing	Clock frequency		1/ T _{Clock}	63	65	67	MHz
Vsync Timing	Vertical Section	Period	T _V	804	806	808	T _{Line}
		Active	T _{VD}	768	768	768	
		Blanking	T _{VB}	36	38	40	
Hsync Timing	Horizontal Section	Period	T _H	1328	1344	1360	T _{Clock}
		Active	T _{HD}	1024	1024	1024	
		Blanking	T _{HB}	304	320	336	
Frame Rate			F	59	60	61	Hz

Note: Support DE mode only.


Note : Typical value refer to VESA STANDARD

6.5.2 Input Timing Diagram



6.6 Power ON/OFF Sequence

VDD power and backlight on/off sequence is as below. Interface signals are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off.



Parameter	Value			Unit
	Min. ³	Typ.	Max. ¹⁰	
T1	0.5	-	10	[ms]
T2	30	40	50	[ms]
T3	200	-	-	[ms]
T4	0.5	-	10	[ms]
T5	10	-	-	[ms]
T6	10	-	-	[ms]
T7	0	-	-	[ms]
T8	10	-	-	[ms]
T9	-	-	200	[ms]
T10	110	-	-	[ms]
T11	0	16	50	[ms]
T12	-	-	200	[ms]
T13	1000	-	-	[ms]

The above on/off sequence should be applied to avoid abnormal function in the display. Please make sure to turn off the power when you plug the cable into the input connector or pull the cable out of the connector.

7. Connector & Pin Assignment


Physical interface is described as for the connector on module. These connectors are capable of accommodating the following signals and will be following components.

7.1 TFT LCD Module: LVDS Connector

Connector Name / Designation	Signal Connector
Manufacturer	STM or compatible
Connector Model Number	MSB240420HD or compatible
Adaptable Plug	P240420 or compatible

Pin#	Signal Name	Pin#	Signal Name
1	VDD	2	VDD
3	NC	4	NC
5	Rin1-	6	Rin1+
7	VSS	8	Rin2-
9	Rin2+	10	VSS
11	Rin3-	12	Rin3+
13	VSS	14	ClkIN-
15	ClkIN+	16	GND
17	Rin4-	18	Rin4+
19	VSS	20	VSS

7.1.1 Connector Illustration



7.2 LED Backlight Unit: LED Driver Connector

Connector Name / Designation	LED Connector
Manufacturer	Entery or compatible
Connector Model Number	3808K-F05N-12R or compatible
Mating Model Number	H208K-P05N-02B or compatible

7.3 LED Driver Connector Pin Assignment

Pin#	Symbol	Signal Name
1	Vcc	12V
2	GND	GND
3	Enable	VLED On/Off
4	Dimming	PWM Dimming
5	NC	NC

8. Reliability Test Criteria

Items	Required Condition	Note
Temperature Humidity Bias	50°C/80%,300 hours	
High Temperature Operation	70°C,300 hours	
Low Temperature Operation	-20°C,300 hours	
Hot Storage	70°C,300 hours	
Cold Storage	-20°C,300 hours	
Thermal Shock Test	-20°C/30 min ,60°C/30 min ,100cycles	
Shock Test (Non-Operating)	50G,20ms,Half-sine wave,(±X, ±Y, ±Z)	
Vibration Test (Non-Operating)	1.5G, (10~200Hz, P-P) 30 mins/axis (X, Y, Z)	
On/off test	On/10 sec, Off/10 sec, 30,000 cycles	
ESD	Contact Discharge: ± 8KV, 150pF(330Ω) 1sec, 8 points, 25 times/ point Air Discharge: ± 15KV, 150pF(330Ω) 1sec, 8 points, 25 times/ point	Note 1


Note1: According to EN61000-4-2, ESD class B: Some performance degradation allowed. No data lost
Self-recoverable. No hardware failures.

Note 2:

- Water condensation is not allowed for each test items.
- Each test is done by new TFT-LCD module. Don't use the same TFT-LCD module repeatedly for reliability test.
- The reliability test is performed only to examine the TFT-LCD module capability.
- To inspect TFT-LCD module after reliability test, please store it at room temperature and room humidity for 24 hours at least in advance.
- No function failure occurs. Mura shall be ignored after high temperature reliability test.

9. Mechanical Characteristics


9.1 LCM Outline Dimension (Front View)





G150XAN01.0

9.2 LCM Outline Dimension (Rear View)




G150XAN01.0 rev. 1.0

24/27

10. Label and Packaging

10.1 Shipping Label (on the rear side of TFT-LCD display)




10.2 Carton Package

Max capacity : 20 PCS TFT-LCD module per carton

Max weight: 20 kg per carton

Outside dimension of carton: 430mm(L)* 370mm(W)*350mm(H)

Pallet size : 1140 mm * 890 mm * 132mm



Protect film with 4 tape




Put panel into ESD BAG



2 pcs Panel face to face , put 2 panel into 1 groove



Put Top Cushion into carton




20pcs/Carton

10.3 Palletizing


Module by air_Max: $(2 * 3) * 4$ layers , one pallet put 24 boxes , total 480pcs module

Module by sea_Max: $(2 * 3) * 4$ layers + $(2 * 3) * 1$ layers , two pallet put 30 boxes , total 600pcs module

Module by sea_HQ_Max: $(2 * 3) * 4$ layers+ $(2 * 3) * 2$ layers, two pallet put 36 boxes, total 720pcs module



By air : one pallet



By sea : two pallet

11 Safety

11.1 Sharp Edge Requirements

There will be no sharp edges or comers on the display assembly that could cause injury.

11.2 Materials

11.2.1 Toxicity

There will be no carcinogenic materials used anywhere in the display module. If toxic materials are used, they will be reviewed and approved by the responsible AUO toxicologist.

11.2.2 Flammability

All components including electrical components that do not meet the flammability grade UL94-V1 in the module will complete the flammability rating exception approval process.

The printed circuit board will be made from material rated 94-V1 or better. The actual UL flammability rating will be printed on the printed circuit board.

11.3 Capacitors

If any polarized capacitors are used in the display assembly, provisions will be made to keep them from being inserted backwards.

11.4 National Test Lab Requirement

The display module will satisfy all requirements for compliance to:

UL 60950-1, Second Edition

U.S.A. Information Technology Equipment