



**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF BOE DT AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE DT AND MUST BE RETURNED TO BOE DT UPON ITS REQUEST

**TITLE : MV238QHM-N10**  
**Product Specification Rev. A**

**BEIJING BOE Display TECHNOLOGY**

**SPEC. NUMBER**  
S8-64-8A-116/A

**PRODUCT GROUP**  
TFT-LCD

**Rev. A**

**ISSUE DATE**  
2017.04.06

**PAGE**  
1 OF 30

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2016.12.29

REVISION HISTORY

- ( )Preliminary specification
- (●)Final specification

Revision No.	Page	Description of changes	Date	Prepared
P0		Initial Release	2016.04.25	Liu Xiaona
P1	7,9	1.更新电学Spec 2.更新颜色坐标规格	2016.07.11	Liu Xiaona
P2	15,16	Timing更改	2016.11.04	Yang Weifan
O			2016.12.29	Liu Xiaona
A	15	Timing更改	2017.04.11	Yang Weifan

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-64-8A-116/A	B4 MV238QHM-N10 Product Specification Rev. A	2 OF 30

## Contents


No.	Item	Page
1.0	General Description	4
2.0	Absolute Maximum Ratings	6
3.0	Electrical Specifications	7
4.0	Optical Specifications	8
5.0	Interface Connection	10
6.0	Signal Timing Specifications	13
7.0	Signal Timing Waveforms of Interface Signal	15
8.0	Input Signals, Display Colors & Gray Scale of Colors	17
9.0	Power Sequence	18
10.0	Mechanical Characteristics	19
11.0	Reliability Test	20
12.0	Handling& Cautions	21
13.0	Product Serial Number	22
14.0	Packing	23
15.0	Appendix	25

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2017.04.06

# 1.0 GENERAL DESCRIPTION

## 1.1 Introduction

MV238QHM-N10 is a color active matrix TFT LCD module using amorphous silicon TFT’s (Thin Film Transistors,ADS panel) as an active switching devices. This module has a 23.8 inch diagonally measured active area with FHD resolutions (2560 horizontal by 1440 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.7M colors. The TFT-LCD panel used for this module is adapted for a low reflection and higher color type.



## 1.2 Features

- LVDS Interface with 2 pixel / clock
- High-speed response
- 6-bit (Hi-FRC) color depth, display 16. 7M colors
- High luminance and contrast ratio, low reflection and wide viewing angle
- DE (Data Enable) only
- RoHS/Halogen Free
- TCO 7.0 , ES 7.0 compliant
- Gamma Correction
- Reverse type

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-64-8A-116/A	B4 MV238QHM-N10 Product Specification Rev. A	4 OF 30

### 1.3 Application

- Desktop Type of PC & Workstation Use
- Slim-Size Display for Stand-alone Monitor
- Display Terminals for Control System
- Monitors for Process Controller

### 1.4 General Specification

The followings are general specifications at the model MV238QHM-N10.

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	526.848(H) × 296.352(V)	mm	
Number of pixels	2560(H) × 1440(V)	pixels	
Pixel pitch	0.2058(H) × 0.2058(V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	16.7M	colors	
Display mode	Normally Black		
Dimensional outline	535.0 (H)×313.0(V)×12.2 (D)Typ.	mm	Detail refer to drawing
Weight	2220(Typ.)	g	
Bezel width (L/R/U/D)	None	mm	
Surface Treatment	Haze 25%, 3H		
Back-light	Horizontal arranged, 1-LED Lighting Bar type		

## 2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.


< Table 2. Absolute Maximum Ratings >

[VSS=GND=0V]

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	$V_{DD}$	-0.3	6.0	V	Ta = 25 °C
Logic Supply Voltage	$V_{IN}$	VSS-0.3	$V_{DD}+0.3$	V	
Operating Temperature	$T_{OP}$	0	+50	°C	1)
Storage Temperature	$T_{ST}$	-20	+60	°C	1)

Note : 1) Temperature and relative humidity range are shown in the figure below.

Wet bulb temperature should be 39 °C max. and no condensation of water.



## 2.0 ABSOLUTE MAXIMUM RATINGS

Note : 2) Panel Surface Temperature should be Min. 0°C and Max. +65°C under the VDD = 5.0V, Frame rate = 60Hz, 25°C ambient Temp. no humidity control and LED string current is typical value.

## 3.0 ELECTRICAL SPECIFICATIONS


### 3.1 Electrical Specifications

< Table 3. Electrical specifications >


[Ta = 25 ± 2 °C]

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V <sub>DD</sub>	4.5	5.0	5.5	V	Note 1
Power Supply Current	I <sub>DD</sub>	-	900	1600	mA	
In-Rush Current	I <sub>RUSH</sub>	-	2.0	3.0	A	Note 2
Permissible Input Ripple Voltage	V <sub>RF</sub>	-	-	300	mV	Note 1,3
High Level Differential Input Threshold Voltage	V <sub>IH</sub>	-	-	+100	mV	
Low Level Differential Input Threshold Voltage	V <sub>IL</sub>	-100	-	-	mV	
Differential input voltage	V <sub>ID</sub>	200	-	600	mV	
Differential input common mode voltage	V <sub>cm</sub>	1.0	1.2	1.5		V <sub>IH</sub> =100mV, V <sub>IL</sub> =-100mV
Power Consumption	P <sub>D</sub>	±	4.5	8.0	W	
	P <sub>BL</sub>	±	16.6	17.5	W	Note 4
	P <sub>total</sub>	±			W	

- Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.  
 The current draw and power consumption specified is for VDD=5.0V, Frame rate=75Hz  
 Clock frequency = 75.6 MHz. Test Pattern of power supply current  
 a) Typ : Color Test  
 b) Max : Vertical SubLine 255



a. Color Test



b. Vertical SubLine 255

2. Duration of rush current is about 2 ms and rising time of VDD is 520 μs ± 20 %  
 3. Ripple Voltage should be covered by Input voltage Spec.  
 4. Calculated value for reference (Input pins\*VPIN × IPIN) excluding inverter loss.

### 3.2 Backlight Unit

< Table 4. LED Backlight Unit >

Parameter		Min.	Typ.	Max.	Unit	Remarks
LED Light Bar Input Voltage Per Input Pin	VPIN	±	48.8	51.52	V	Duty 100%
LED Light Bar Input Current Per Input Pin	IPIN	82	85	88	mA	Note1,2,
LED Power Consumption	P <sub>BL</sub>	±	16.6	17.5	W	Note 3
LED Life-Time	-	30,000	-		Hrs	Note 4

**LED bar consists of 64LED packages,4strings(parallel)\*16packages(serial)**

Note1: There are one light bar ,and the specified current is input LED chip 100% duty current

Note2: The sense current of each input pin is 85mA

**Note3:  $P_{BL} = 4 \text{Input pins} * V_{PIN} \times I_{PIN}$**

Note4: The lifetime is determined as the time at which luminance of LED become 50% of the initial brightness or not normal lighting at IPIN=85mA on condition of continuous operating at  $25 \pm 2 \text{ }^{\circ}\text{C}$



## 4.0 OPTICAL SPECIFICATION

### 4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance  $\leq 1$  lux and temperature =  $25 \pm 2^\circ\text{C}$ ) with the equipment of Luminance meter system (Goniometer system and **TOPCONE PR730**) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of  $\theta$  and  $\Phi$  equal to  $0^\circ$ . We refer to  $\theta_{\Phi=0}$  ( $=\theta_3$ ) as the 3 o'clock direction (the "right"),  $\theta_{\Phi=90}$  ( $=\theta_{12}$ ) as the 12 o'clock direction ("upward"),  $\theta_{\Phi=180}$  ( $=\theta_9$ ) as the 9 o'clock direction ("left") and  $\theta_{\Phi=270}$  ( $=\theta_6$ ) as the 6 o'clock direction ("bottom"). While scanning  $\theta$  and/or  $\Phi$ , the center of the measuring spot on the Display surface shall stay fixed. The measurement shall be executed after 30 minutes warm-up period. VDD shall be 5.0V +/-10% at  $25^\circ\text{C}$ . Optimum viewing angle direction is 6 °clock.

### 4.2 Optical Specifications

[VDD = 5.0V, Frame rate = 60Hz, Clock = **60.4MHz**, **I<sub>BL</sub>** = **340mA**, Ta =  $25 \pm 2^\circ\text{C}$ ]

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	$\Theta_3$	CR > 10	80	89	-	Deg.	Note 1
		$\Theta_9$		80	89	-	Deg.	
	Vertical	$\Theta_{12}$		80	89	-	Deg.	
		$\Theta_6$		80	89	-	Deg.	
Luminance Contrast ratio		CR	$\Theta = 0^\circ$ (Center) Normal Viewing Angle	700	1000			Note 2
Luminance of White		$Y_w$		240	300		cd/m <sup>2</sup>	Note 3
White luminance uniformity		$\Delta Y$		75	-		%	Note 4
Reproduction of color	White	$W_x$		0.283	0.313	0.343	-	Note 5
		$W_y$		0.299	0.329	0.359	-	
	Red	$R_x$		0.611	0.641	0.671	-	
		$R_y$		0.298	0.328	0.358	-	
	Green	$G_x$		0.274	0.304	0.334	-	
		$G_y$		0.585	0.615	0.645	-	
	Blue	$B_x$		0.118	0.148	0.178	-	
		$B_y$		0.032	0.062	0.092	-	
Color Gamut				-	72	-	%	NTSC CIE1931
Response Time	GTG	$T_g$			14	20	ms	Note 6
Cross Talk		CT		-	-	2.0	%	Note 7

**Note :**

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface.
2. Contrast measurements shall be made at viewing angle of  $\theta = 0^\circ$  and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state. (See FIGURE 1 shown in Appendix) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.
4. The White luminance uniformity on LCD surface is then expressed as :  
 $\Delta Y = (\text{Minimum Luminance of 9points} / \text{Maximum Luminance of 9points}) * 100$   
 (See FIGURE 2 shown in Appendix).
5. The color chromaticity coordinates specified in Table 4. shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
6. Response time  $T_g$  is the average time required for display transition by switching the input signal as below table and is based on Frame rate  $f_V = 60\text{Hz}$  to optimize.  
 Each time in below table is defined as Figure 3 and shall be measured by switching the input signal for “any level of gray(bright)” and “any level of gray(dark)”.

Measured Response Time	Target															
	0	15	31	47	63	79	95	111	127	143	159	175	191	207	223	239
Start	0															
	15															
	31															
	47															
	63															
	79															
	95															
	111															
	127															
	143															
	159															
	175															
	191															
	207															
	223															
	239															
	255															

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance ( $Y_A$ ) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance ( $Y_B$ ) of that same area when any adjacent area is driven dark. (See FIGURE 4 shown in Appendix).

## 5.0 INTERFACE CONNECTION.

### 5.1 Electrical Interface Connection

#### 5.1.1 LED Light Bar

-LED connector : BM06B-SHJS-TB(JST) or 10035WS-H06B (YEONHO) or EQUIVALENT

< Table 1. LED Light Bar>

Pin No	Symbol	Description
1	IRLED1	LED current sense for string1
2	IRLED <sub>2</sub>	LED current sense for string2
3	VLED	LED power supply
4	VLED	LED power supply
5	IRLED <sub>3</sub>	LED current sense for string3
6	IRLED <sub>4</sub>	LED current sense for string4

**5.0 INTERFACE CONNECTION.****5.1 Electrical Interface Connection**

- CN101      Module Side Connector : PM.LVS.08115F4001 or Equivalent

Pin No	Symbol	Function	Pin No	Symbol	Function
1	CLV0-	Negative Transmission data of Pixel 0	21	DLV2+	Positive Transmission data of Pixel 2
2	CLV0+	Positive Transmission data of Pixel 0	22	GND	Power Ground
3	CLV1-	Negative Transmission data of Pixel 1	23	DLVC-	Negative Transmission Clock
4	CLV1+	Positive Transmission data of Pixel 1	24	DLVC+	Positive Transmission Clock
5	CLV2-	Negative Transmission data of Pixel 2	25	GND	Power Ground
6	CLV2+	Positive Transmission data of Pixel 2	26	DLV3-	Negative Transmission data of Pixel 3
7	GND	Power Ground	27	DLV3+	Positive Transmission data of Pixel 3
8	CLVC-	Negative Transmission Clock	28	NC	No Connection
9	CLVC+	Positive Transmission Clock	29	NC	No Connection
10	GND	Power Ground	30	NC	No Connection
11	CLV3-	Negative Transmission data of Pixel 3	31	NC	No Connection
12	CLV3+	Positive Transmission data of Pixel 3	32	NC	No Connection
13	NC	No Connection	33	NC	No Connection
14	NC	No Connection	34	GND	Power Ground
15	GND	Power Ground	35	GND	Power Ground
16	DLV0-	Negative Transmission data of Pixel 0	36	VDD	Power Supply
17	DLV0+	Positive Transmission data of Pixel 0	37	VDD	Power Supply
18	DLV1-	Negative Transmission data of Pixel 1	38	VDD	Power Supply
19	DLV1+	Positive Transmission data of Pixel 1	39	VDD	Power Supply
20	DLV2-	Negative Transmission data of Pixel 2	40	VDD	Power Supply

Note 1: H: White-Black-Red-Green-Blue Pattern Aging, L: Black Pattern, when no LVDS signal.

Note 2: This pin should be connected with GND.

**5.0 INTERFACE CONNECTION.****5.2 Electrical Interface Connection**

- CN102      Module Side Connector : UJU IS100-L300-C23or Equivalent  
User Side Connector : JAE FI-X30H or Equivalent

Pin No	Symbol	Function	Pin No	Symbol	Function
1	ALV0-	Negative Transmission data of Pixel 0	16	BLV0-	Negative Transmission data of Pixel 0
2	ALV0+	Positive Transmission data of Pixel 0	17	BLV0+	Positive Transmission data of Pixel 0
3	ALV1-	Negative Transmission data of Pixel 1	18	BLV1-	Negative Transmission data of Pixel 1
4	ALV1+	Positive Transmission data of Pixel 1	19	BLV1+	Positive Transmission data of Pixel 1
5	ALV2-	Negative Transmission data of Pixel 2	20	BLV2-	Negative Transmission data of Pixel 2
6	ALV2+	Positive Transmission data of Pixel 2	21	BLV2+	Positive Transmission data of Pixel 2
7	GND	Power Ground	22	GND	Power Ground
8	ALVC-	Negative Transmission Clock	23	BLVC-	Negative Transmission Clock
9	ALVC+	Positive Transmission Clock	24	BLVC+	Positive Transmission Clock
10	GND	Power Ground	25	GND	Power Ground
11	ALV3-	Negative Transmission data of Pixel 3	26	BLV3-	Negative Transmission data of Pixel 3
12	ALV3+	Positive Transmission data of Pixel 3	27	BLV3+	Positive Transmission data of Pixel 3
13	NC	No Connection	28	NC	No Connection
14	NC	No Connection	29	NC	No Connection (*Reserved for LCD manufacturer's use )
15	GND	Power Ground	30	NC	No Connection (*Reserved for LCD manufacturer's use )

**5.2 LVDS Interface (Tx; THC63LVDF83A or Equivalent)****5.2.1 LVDS Interface**

	Input Signal	Transmitter		Interface		MV238QHM-N10 (CN102)	Remark
		Pin No.	Pin No.	System (Tx)	TFT-LCD (Rx)	Pin No.	
L V D S	OR0	51	48 47	OUT0- OUT0+	RX00- RX00+	1 2	
	OR1	52					
	OR2	54					
	OR3	55					
	OR4	56					
	OR5	3					
	OG0	4					
	OG1	6	46 45	OUT1- OUT1+	RX01- RX01+	3 4	
	OG2	7					
	OG3	11					
	OG4	12					
	OG5	14					
	OB0	15					
	OB1	19					
	OB2	20	42 41	OUT2- OUT2+	RX02- RX02+	5 6	
	OB3	22					
	OB4	23					
	OB5	24					
	Hsync	27					
	Vsync	28					
	DE	30					
	MCLK	31	40 39	CLK OUT- CLK OUT+	RXO CLK- RXO CLK+	8 9	
	OR6	50	38 37	OUT3- OUT3+	RX03- RX03+	10 11	
	OR7	2					
	OG6	8					
	OG7	10					
	OB6	16					
	OB7	18					
	RSVD	25					

Note: The order of even data is same with odd data.

## 6.0 SIGNAL TIMING SPECIFICATION

6.1 The MV238QHM-N10 is operated by the DE only.

Item	Symbols		Min	Typ	Max	Unit
DCLK	Period	tCLK	12.12	16.56	20.71	ns
	Frequency	-	48.3	60.4	82.5	MHz
Horizontal Display Term	Period	tHP	679	680	709	tCLK
	Horizontal Valid	tHV	640	640	640	tCLK
	Horizontal Blank	tHB	39	40	69	tCLK
	Frequency	fH	74	88.9	112	KHz
Vertical Display Term	Period	tVP	1452	1481	1550	tHP
	Vertical Valid	tVV	1440	1440	1440	tHP
	Vertical Blank	tVB	12	41	110	tHP
	Frequency	fV	48	60	75	Hz
LVDS Receiver clock	Input spread spectrum ratio	SSr	-3	-	+3	%

Note:


- 1). The DCLK range at last line of V-blanking should be set in 0~987
- 2). V-total maximum can reach 1616 when the following timing is requirement  
@720x400, 640x480, PC98 640x400 and 800x600.

## 6.2 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 4.

<Table 4. LVDS Rx Interface Timing Specification>

Item	Symbol	Min	Typ	Max	Unit	Remark
CLKIN Period	tRCIP	12.12	16.56	20.71	nsec	
Input Data 0	tRIP1	-0.4	0.0	+0.4	nsec	
Input Data 1	tRIP0	tRCIP/7-0.4	tRCIP/7	tRCIP/7+0.4	nsec	
Input Data 2	tRIP6	$2 \times tRCIP/7-0.4$	$2 \times tRCIP/7$	$2 \times tRCIP/7+0.4$	nsec	
Input Data 3	tRIP5	$3 \times tRCIP/7-0.4$	$3 \times tRCIP/7$	$3 \times tRCIP/7+0.4$	nsec	
Input Data 4	tRIP4	$4 \times tRCIP/7-0.4$	$4 \times tRCIP/7$	$4 \times tRCIP/7+0.4$	nsec	
Input Data 5	tRIP3	$5 \times tRCIP/7-0.4$	$5 \times tRCIP/7$	$5 \times tRCIP/7+0.4$	nsec	
Input Data 6	tRIP2	$6 \times tRCIP/7-0.4$	$6 \times tRCIP/7$	$6 \times tRCIP/7+0.4$	nsec	




$$* V_{diff} = (RX_{Z+}) - (RX_{Z-}), \dots, (RX_{CLK+}) - (RX_{CLK-})$$




## 7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL

### 7.1 Sync Timing Waveforms





- 1) Need over 3 H-sync during V-Sync Low
- 2) Fix H-Sync width from V-Sync falling edge to first rising edge

### 7.2 Vertical Timing Waveforms



### 7.3 Horizontal Timing Waveforms




## 8.0 INPUT SIGNALS, BASIC DISPLAY COLORS &amp; GRAY SCALE OF COLORS

Color & Gray Scale		RED DATA								GREEN DATA								BLUE DATA							
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale of RED	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	▽	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale of GREEN	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0
	▽	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
Gray Scale of BLUE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
Gray Scale of WHITE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1
	▽	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	1	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2017.04.06

### 9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



- 0.5 ms ≤ T1 ≤ 10 ms
- 0 ≤ T2 ≤ 50 ms
- 0 ≤ T3 ≤ 50 ms
- 1 sec ≤ T4
- 200 ms ≤ T5
- 200 ms ≤ T6

Notes:

1. When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
2. Do not keep the interface signal high impedance when power is on.
3. Back Light must be turn on after power for logic and interface signal are valid.

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-64-8A-116/A	B4 MV238QHM-N10 Product Specification Rev. A	20 OF 30

## 10.0 MECHANICAL CHARACTERISTICS

### 10.1 Dimensional Requirements

FIGURE 6 (located in Appendix) shows mechanical outlines for the model MV238FHM-N30. Other parameters are shown in Table 5.

<Table 5. Dimensional Parameters>

Parameter	Specification	Unit
Dimensional outline	535.0 (H) × 313.0(V) × 12.2 (D)Typ.	mm
Weight	2220(Typ.)	gram
Active area	526.848(H) × 296.352(V)	mm
Pixel pitch	0.2058(H) × 0.2058(V)	mm
Number of pixels	2560 (H) × 1440 (V) (1 pixel = R + G + B dots)	pixels
Back-light	Horizontal arranged, 1-LED Lighting Bar type	

### 10.2 Mounting

See FIGURE 5. (shown in Appendix)

### 10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an anti-glare coating to minimize reflection and a coating to reduce scratching.

### 10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

## 11.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 6. Reliability Test Parameters >

No	Test Items	Conditions	
1	High temperature storage test	Ta = 60 °C , 240 hrs	
2	Low temperature storage test	Ta = -20 °C , 240 hrs	
3	High temperature & high humidity operation test	Ta = 50 °C , 80%RH, 240hrs	
4	High temperature operation test	Ta = 50 °C , 240hrs	
5	Low temperature operation test	Ta = 0°C , 240hrs	
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle	
7	Vibration test (non-operating)	Frequency	Random, 10 ~ 300 Hz, 30 min/Axis
		Gravity / AMP	1.5 Grms
		Period	X, Y, Z 30 min
8	Shock test (non-operating)	Gravity	50G
		Pulse width	11msec, sine wave
		Direction	± X, ± Y, ± Z Once for each
9	Electro-static discharge test	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV	

## 12.0 HANDLING & CAUTIONS


- (1) Cautions when taking out the module
  - Pick the pouch only, when taking out module from a shipping package.
- (2) Cautions for handling the module
  - As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
  - As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
  - As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
  - Do not pull the interface connector in or out while the LCD module is operating.
  - Put the module display side down on a flat horizontal plane.
  - Handle connectors and cables with care.
- (3) Cautions for the operation
  - When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
  - Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.
- (4) Cautions for the atmosphere
  - Dew drop atmosphere should be avoided.
  - Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.
- (5) Cautions for the module characteristics
  - Do not apply fixed pattern data signal to the LCD module at product aging.
  - Applying fixed pattern for a long time may cause image sticking.
- (6) Other cautions
  - Do not disassemble and/or re-assemble LCD module.
  - Do not re-adjust variable resistor or switch etc.
  - When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2017.04.06

13.0 PRODUCT SERIAL NUMBER

MV238QHM-N10B4


XXXX



XXXXXXXXXXXXXXXXXXXXX


P/N : XXXXXXXXXXXX

FRU : XXXXXXXXXXXX



XXXXXXXXXXXXXXXXXXXXX

BOE


MADE IN CHINA

目前按照Lenovo PPID更新标签

1

X

X

2

X

3

X

4

X

X

5

X

6

X

X

X

X

7

X

X

X

X

X

X

X

1. Control Number

2. Rank / Grade

3. Line Classification

4. Year (2001 : 01, 2002 : 02, ...)
5. Month (1,2,3, ... , 9, X, Y, Z)

6. Internal Use

7. Serial Number


SPEC. NUMBER	SPEC. TITLE	PAGE
S8-64-8A-116/A	B4 MV238QHM-N10 Product Specification Rev. A	24 OF 30





## 14.0 Packing

### 14.1 Packing Order


Put 1 EPO bottom into the inner box.



Put each module into a PE bag.  
Insert 10 Pcs MDL into each box



Place paper corners and wrap film a round the boxes.  
Pack with 4 packing belts.



Put 1 EPO cover in and seal the box.

## 14.2 Packing Note

- Box Dimension : 306.4mm(W) × 617mm(L) × 405mm(H)
- Package Quantity in one Box : 10pcs

## 14.3 Box label

- Label Size : 108 mm (L) × 56 mm (W)
- Contents

Model : MV238QHM-N10

Q`ty : Module 10 Q`ty in one box

Serial No. : Box Serial No. See next page for detail description.

Date : Packing Date



MODEL : MV238QHM-N10

Q'TY : 10

SERIAL NO. : 00000000000000

DATE : 20XX.X.XX



• QAA0330000268 •

5940



(QA)

00 0 00 0 0 000000  
Type Grade Year Month ITEM-CODE Serial\_no

Internal Use

RoHS Mark

## 15.0 APPENDIX

Figure 1. Measurement Set Up





Figure 2. White Luminance and Uniformity Measurement Locations (9 points)



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2017.04.06

Figure 3. Response Time Testing





Figure 4. Cross Modulation Test Description




$$\text{Cross-Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$$

Where:  $Y_A$  = Initial luminance of measured area (cd/m<sup>2</sup>)  
 $Y_B$  = Subsequent luminance of measured area (cd/m<sup>2</sup>)  
The location measured will be exactly the same in both patterns


SPEC. NUMBER	SPEC. TITLE	PAGE
S8-64-8A-116/A	B4 MV238QHM-N10 Product Specification Rev. A	28 OF 30

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	A	2017.04.06



SPEC. NUMBER S8-64-8A-116/A	SPEC. TITLE B4 MV238QHM-N10 Product Specification Rev. A	PAGE 29 OF 30
--------------------------------	---	------------------

Figure 6. TFT-LCD Module Outline Dimensions (Rear view)



## NOTE:

## 1. I/F CONNECTOR SPECIFICATION

CNT1(30 pin):MSBKT2407P30HB(STM) or EQUIVALENT


CNT2(40 pin):PM.LVS.08115F4001(GESEN) or EQUIVALENT

## 2. LED CONNECTOR SPECIFICATION

BM06B-SHJS-TB(JST) or EQUIVALENT


## 3. USER MOUNTING TORQUE SPEC : 3 ~ 4 kgf-cm

## 4. Tilt and portial disposition tolerance of display area as following

(1)Y-direction :  $-0.45 \leq A \leq 0.45$ ,  $-0.45 \leq B \leq 0.45$ (2)X-direction :  $-0.45 \leq C \leq 0.45$ ,  $-0.45 \leq D \leq 0.45$ 


Section A-A

Scale 2:1




Section B-B

Scale 2:1




Section C-C

Scale 2:1



Section D-D

Scale 2:1

5.Unspecified tolerances to be  $\pm 0.5$ 

6.The COF area is weak &amp; sensitive, so please don't press the COF Area