Product Specification

SPECIFICATION
FOR
APPROVAL

(   ) **Preliminary Specification**

(◆) **Final Specification**

Title	8.9" WSVGA TFT LCD

Customer	Lenovo
MODEL	LP089WS1-TLA2

SUPPLIER	LG Display Co., Ltd.
*MODEL	LP089WS1
Suffix	TLA2

*When you obtain standard approval,
 please use the above model name without suffix

APPROVED BY	SIGNATURE
/	
/	
/	

Please return 1 copy for your confirmation with your signature and comments.

APPROVED BY	SIGNATURE
G. J. Kwon/ Manager	
REVIEWED BY	
C. J. Jun / Manager	
PREPARED BY	
P. A. Choi / Engineer	

**Products Engineering Dept.
LG Display Co., Ltd**

Contents

RECORD OF REVISIONS

Revision No	Revision Date	Page	Description	EDID ver
0.0	May. 26. 2008	All	First Draft (Preliminary Specification)	-
0.1	July. 23. 2008	All	All page update	-
1.0	Sep. 16. 2008	-	Final CAS	-

## 1. General Description

The LP089WS1 is a Color Active Matrix Liquid Crystal Display with an integral LED backlight system. The matrix employs a-Si Thin Film Transistor as the active element. It is a transmissive type display operating in the normally white mode. This TFT-LCD has 8.9 inches diagonally measured active display area with WSVGA resolution(1024 horizontal by 600 vertical pixel array). Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 6-bit gray scale signal for each dot, thus, presenting a palette of more than 262,144 colors.

The LP089WS1 has been designed to apply the interface method that enables low power, high speed, low EMI.

The LP089WS1 is intended to support applications where thin thickness, low power are critical factors and graphic displays are important. In combination with the vertical arrangement of the sub-pixels, the LP089WS1 characteristics provide an excellent flat display for office automation products such as Notebook PC.

General Features

|	
Active Screen Size	8.9 inches diagonal
Outline Dimension	213.4(H) × 129.55(V) × .5.45(D,Max.) [mm]
Pixel Pitch	0.1905mm × 0.189 mm
Pixel Format	1024 horiz. By 600 vert. Pixels RGB strip arrangement
Color Depth	6-bit, 262,144 colors
Luminance, White	200 cd/m^2(Typ.5 point)
Power Consumption	Total 2.08 Watt(Typ.) @ LCM circuit 0.76 Watt(Typ.), B/L input 1.32 Watt(Typ.)
Weight	200g (Max.)
Display Operating Mode	Transmissive mode, normally white
Surface Treatment	Glare treatment of the front polarizer
RoHS Comply	Yes

2. Absolute Maximum Ratings

The following are maximum values which, if exceeded, may cause faulty operation or damage to the unit.

Table 1. ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Values		Units	Notes
		Min	Max		
Power Input Voltage	VCC	-0.3	4.0	Vdc	at 25 ± 5°C
Operating Temperature	TOP	0	50	°C	1
Storage Temperature	HST	-20	60	°C	1
Operating Ambient Humidity	HOP	10	90	%RH	1
Storage Humidity	HST	10	90	%RH	1

Note : 1. Temperature and relative humidity range are shown in the figure below.
　　　　Wet bulb temperature should be 39°C Max, and no condensation of water.

Wet Bulb Temperature [℃]

Humidity[(%)RH]

Storage

Operation

Dry Bulb Temperature [℃]

3. Electrical Specifications

3-1. Electrical Characteristics

The LP141WX5 requires two power inputs. One is employed to power the LCD electronics and to drive the TFT array and liquid crystal. The second input which powers the LED BL.

Table 2. ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Values			Unit	Notes
		Min	Typ	Max		
MODULE :						
Power Supply Input Voltage	VCC	3.0	3.3	3.6	V_{DC}	
Power Supply Input Current	I_{CC}	-	230	265	mA	1
Power Consumption	Pc	-	0.76	0.87	Watt	1
Differential Impedance	Zm	90	100	110	Ohm	2
LED Backlight (With LED Driver) :						
LED Driver (@5V)	P_{DRIVER}	-	0.18	0.21	Watt	
Operating Voltage	V_{LED}	-	25.6	29	V	
Operating Current per string	I_{LED}	-	17.2	18	mA	3
Power Consumption	P_{BL}	-	1.32	1.49	Watt	4
Life Time		10000	-	-	Hrs	5

Note)
1. The specified current and power consumption are under the Vcc = 3.3V , 25℃, fv = 60Hz condition whereas Mosaic pattern is displayed and fv is the frame frequency.


2. This impedance value is needed to proper display and measured form LVDS Tx to the mating connector.
3. The typical operating current is for the typical surface luminance (L_{WH}) in optical characteristics. I_{LED} is the current of each LED's string, LED backlight has 6 strings on it.
4. The LED power consumption shown above does not include power of external LED driver circuit for typical current condition.
5. The life time is determined as the time at which brightness of LED is 50% compare to that of initial value at the typical LED current.

3-2. Interface Connection

This LCD employs one interface connection, a 40 pin connector is used for the module electronics interface. The electronics interface connector is a model 20347-#40E-## manufactured by I-PEX.

Table 3. MODULE CONNECTOR PIN CONFIGURATION (CN1)

Pin	Symbol	Description	Notes
1	GND	Ground	
2	VDD	+3.3V Power Supply	
3	VDD	+3.3V Power Supply	
4	V_{EDID}	+3.3V EDID Power	1, Interface chips
5	NC	No Connection	1.1 LCD : SiW, 1port including
6	CLK_{EDID}	EDID Clock Input	LVDS Receiver
7	$DATA_{EDID}$	EDID Data Input	1.2 System :
8	RxIN0-	LVDS differential data input	* Pin to Pin compatible with LVDS
9	RxIN0+	LVDS differential data input	
10	GND	Ground	2. Connector
11	RxIN1-	LVDS differential data input	2.1 LCD :I-PEX 20347-340E-12
12	RxIN1+	LVDS differential data input	(Locking type)
13	GND	Ground	or equivalent
14	RxIN2-	LVDS differential data input	
15	RxIN2+	LVDS differential data input	2.2 Mating : 20345-#40T-##
16	GND	Ground	2.3 Connector pin arrangement
17	RxCLKIN-	LVDS differential clock input	
18	RxCLKIN+	LVDS differential clock input	
19	GND	Ground	[LCD Module Rear View]
20	NC	No Connection	
21	NC	No Connection	
22	GND	Ground	
23	NC	No Connection	
24	NC	No Connection	
25	GND	Ground	
26	NC	No Connection	
27	NC	No Connection	
28	GND	Ground	
29	VLED	+5V LED Power Supply	
30	VLED	+5V LED Power Supply	
31	VLED_GND	LED Ground	
32	VLED_GND	LED Ground	
33	VLED_GND	LED Ground	
34	NC	No Connection	
35	NC	No Connection	
36	NC	No Connection	
37	NC	No Connection	
38	S_PWMIN	System PWM signal input	[Note 1]
39	BL_ON or NC	LED Enable or No Connection[Note 1]	Let this pin NC if this pin is not used.
40	NC	No Connection	(On: 2.0V↑,Off:0~0.4V)

3-3. LVDS Signal Timing Specifications

3-3-1. DC Specification

$|V_{ID}| = |(LVDS+) - (LVDS-)|$
$V_{CM} = \{(LVDS+) + (LVDS-)\}/2$

Description	Symbol	Min	Max	Unit	Notes
LVDS Differential Voltage	$|V_{ID}|$	100	600	mV	-
LVDS Common mode Voltage	V_{CM}	0.6	1.8	V	-
LVDS Input Voltage Range	V_{IN}	0.3	2.1	V	-

3-3-2. AC Specification

$t_{SKEW}(F_{clk} = 1/T_{clk})$
1) 85MHz > Fclk ≥ 65MHz : –400 ~ +400
2) 65MHz > Fclk ≥ 25MHz : -600 ~ +600

Description	Symbol	Min	Max	Unit	Notes
LVDS Clock to Data Skew Margin	t_{SKEW}	- 400	+ 400	ps	85MHz > Fclk ≥ 65MHz
	t_{SKEW}	- 600	+ 600	ps	65MHz > Fclk ≥ 25MHz
LVDS Clock to Clock Skew Margin (Even to Odd)	t_{SKEW_EO}	- 1/7	+ 1/7	T_{clk}	-
Maximum deviation of input clock frequency during SSC	F_{DEV}	-	± 3	%	-
Maximum modulation frequency of input clock during SSC	F_{MOD}	-	200	KHz	-

< Clock skew margin between channel >

< Spread Spectrum >

3-3-3. Data Format

- LVDS 1 Port

< LVDS Data Format >

3-4. Signal Timing Specifications

This is the signal timing required at the input of the User connector. All of the interface signal timing should be satisfied with the following specifications and specifications of LVDS Tx/Rx for its proper operation.

Table 5. TIMING TABLE

ITEM	Symbol		Min	Typ	Max	Unit	Note
DCLK	Frequency	f_{CLK}	-	50.4	-	MHz	
Hsync	Period	Thp	1320	1344	1362	tCLK	
	Width	t_{WH}	132	136	150		
	Width-Active	t_{WHA}	1024	1024	1024		
Vsync	Period	t_{VP}	621	625	632	tHP	
	Width	t_{WV}	1	3	5		
	Width-Active	t_{WVA}	600	600	600		
Data Enable	Horizontal back porch	t_{HBP}	144	160	160	tCLK	
	Horizontal front porch	t_{HFP}	20	24	28		
	Vertical back porch	t_{VBP}	20	22	24	tHP	
	Vertical front porch	t_{VFP}	0	0	3		

3-5. Signal Timing Waveforms

Condition : VCC =3.3V

Data Enable, Hsync, Vsync

LG Display

3-6. Color Input Data Reference

The brightness of each primary color (red,green and blue) is based on the 6-bit gray scale data input for the color ; the higher the binary input, the brighter the color. The table below provides a reference for color versus data input.

Table 7. COLOR DATA REFERENCE

Color		Input Color Data																		
		RED (MSB ... LSB)						GREEN (MSB ... LSB)						BLUE (MSB ... LSB)						
		R 5	R 4	R 3	R 2	R 1	R 0	G 5	G 4	G 3	G 2	G 1	G 0	B 5	B 4	B 3	B 2	B 1	B 0
Basic Color	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
RED	RED (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (01)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	...			...						...						...			
	RED (62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
GREEN	GREEN (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	GREEN (01)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	...			...						...						...			
	GREEN (62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	GREEN (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
BLUE	BLUE (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	BLUE (01)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	...			...						...						...			
	BLUE (62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	BLUE (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

3-7. Power Sequence

Table 7. POWER SEQUENCE TABLE

Parameter	Value			Units
	Min.	Typ.	Max.	
T_1	0.5	-	10	(ms)
T_2	0	-	50	(ms)
T_3	200	-	-	(ms)
T_4	200	-	-	(ms)
T_5	0	-	50	(ms)
T_6	3	-	10	(ms)
T_7	400	-	-	(ms)

Note)
1. Valid Data is Data to meet "3-3. LVDS Signal Timing Specifications"
2. Please avoid floating state of interface signal at invalid period.
3. When the interface signal is invalid, be sure to pull down the power supply for LCD VCC to 0V.
4. LED power must be turn on after power supply for LCD and interface signal are valid.

4. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable for approximately 30 minutes in a dark environment at 25°C. The values specified are at an approximate distance 50cm from the LCD surface at a viewing angle of Φ and Θ equal to 0°.
FIG. 1 presents additional information concerning the measurement equipment and method.

**FIG. 1 Optical Characteristic Measurement Equipment and Method**

Optical Stage(x,y)   LCD Module   Pritchard 880 or equivalent

1°

50cm

Table 8. OPTICAL CHARACTERISTICS

Ta=25°C, VCC=3.3V, f$_V$=60Hz, f$_{CLK}$= 69.3MHz, I$_{BL}$= 17 mA

Parameter	Symbol	Values			Units	Notes
		Min	Typ	Max		
Contrast Ratio	CR	300	-	-		1
Surface Luminance, white	L$_{WH}$	170	200	-	cd/m^2	2
Luminance Variation	δ $_{WHITE}$	-	1.4	1.6		3
Response Time	Tr$_R$+ Tr$_D$	-	16	25	ms	4
Color Coordinates						
RED	RX	0.551	0.581	0.611		
	RY	0.315	0.345	0.375		
GREEN	GX	0.312	0.342	0.372		
	GY	0.537	0.567	0.597		
BLUE	BX	0.132	0.162	0.192		
	BY	0.096	0.126	0.156		
WHITE	WX	0.283	0.313	0.343		
	WY	0.299	0.329	0.359		
Viewing Angle						5
x axis, right(Φ=0°)	Θr	40	-	-	degree	
x axis, left (Φ=180°)	Θl	40	-	-	degree	
y axis, up (Φ=90°)	Θu	15	-	-	degree	
y axis, down (Φ=270°)	Θd	30	-	-	degree	
Gray Scale			2.2			6

G LG Display

Product Specification

Note)

1. Contrast Ratio(CR) is defined mathematically as

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

2. Surface luminance is the average of 5 point across the LCD surface 50cm from the surface with all pixels displaying white. For more information see FIG 1.

$$L_{WH} = \text{Average}(L_1, L_2, \ldots L_5)$$

3. The variation in surface luminance , The panel total variation (δ_{WHITE}) is determined by measuring L_N at each test position 1 through 13 and then defined as followed numerical formula. For more information see FIG 2.

$$\delta_{WHITE} = \frac{\text{Maximum}(L_1, L_2, \ldots L_{13})}{\text{Minimum}(L_1, L_2, \ldots L_{13})}$$

4. Response time is the time required for the display to transition from white to black (rise time, Tr_R) and from black to white(Decay Time, Tr_D). For additional information see FIG 3.

5. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are   determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 4.

6. Gray scale specification   * f_V = 60Hz

Gray Level	Luminance [%] (Typ)
L0	0.1
L7	2.4
L15	8.3
L23	16.4
L31	26.2
L39	40.8
L47	59.0
L55	79.6
L63	100.0

Product Specification

FIG. 2 Luminance

<measuring point for surface luminance & measuring point for luminance variation>

H,V : ACTIVE AREA
A : H/4 mm
B : V/4 mm
POINTS: 13 POINTS

Active Area

FIG. 3 Response Time

The response time is defined as the following figure and shall be measured by switching the input signal for "black" and "white".

Tr_R Tr_D

%

100
90

Optical

Response

10
0

white   black   white

FIG. 4 Viewing angle

Normal

Eye   Y

$\phi = 90°$, Up

$\phi = 180°$ Left

θ

ϕ

$\phi = 0°$ Right

$\phi = 270°$ Down

5. Mechanical Characteristics

The contents provide general mechanical characteristics for the model LP089WS1. In addition the figures in the next page are detailed mechanical drawing of the LCD.

Outline Dimension	Horizontal	213.40 ± 0.3 mm
	Vertical	129.55 ± 0.3 mm
	Thickness	5.45mm (max)
Bezel Area	Horizontal	198.37 mm
	Vertical	116.70 mm
Active Display Area	Horizontal	195.07 mm
	Vertical	113.40 mm
Weight	200g (Max.)	
Surface Treatment	Glare treatment of the front polarizer	

Product Specification

<FRONT VIEW>

Note) Unit:[mm], General tolerance: ± 0.3mm

LG Display

Product Specification

<REAR VIEW>

Note) Unit:[mm], General tolerance: ± 0.3mm

[DETAIL DESCRIPTION OF SIDE MOUNTING SCREW]

2.95±0.3

Screw Length(A)
Screw Depth(B)

Section A-A

* Mounting Screw Length (A)
  = 1.7(Min) /2.0(Max)
* Mounting Screw Hole Depth (B)
  = 2.0(Min)
* Mounting hole location : 2.95(typ.)
* Torque : 2.0 kgf.cm(Max)
  (Measurement gauge : torque meter)

Notes : 1. Screw plated through the method of non-electrolytic nickel plating is preferred
to reduce possibility that results in vertical and/or horizontal line defect due to
the conductive particles from screw surface.

6. Reliability

Environment test condition

No.	Test Item	Conditions
1	High temperature storage test	Ta= 60°C, 240h
2	Low temperature storage test	Ta= -20°C, 240h
3	High temperature operation test	Ta= 50°C, 50%RH, 240h
4	Low temperature operation test	Ta= 0°C, 240h
5	Vibration test (non-operating)	Sine wave, 10 ~ 500 ~ 10Hz, 1.5G, 0.37oct/min 3 axis, 1hour/axis
6	Shock test (non-operating)	Half sine wave, 180G, 2ms one shock of each six faces(I.e. run 180G 6ms for all six faces)
7	Altitude operating storage / shipment	0 ~ 10,000 feet (3,048m) 24Hr 0 ~ 40,000 feet (12,192m) 24Hr

{ Result Evaluation Criteria }
 There should be no change which might affect the practical display function when the display quality
test is conducted under normal operating condition.

7. International Standards

7-1. Safety

a) UL 60950-1:2003, First Edition, Underwriters Laboratories, Inc.,
Standard for Safety of Information Technology Equipment.
b) CAN/CSA C22.2, No. 60950-1-03 1st Ed. April 1, 2003, Canadian Standards Association,
Standard for Safety of Information Technology Equipment.
c) EN 60950-1:2001, First Edition,
European Committee for Electrotechnical Standardization(CENELEC)
European Standard for Safety of Information Technology Equipment.

7-2. EMC

a) ANSI C63.4 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electrical Equipment in the Range of 9kHZ to 40GHz. "American National Standards Institute(ANSI), 1992
b) C.I.S.P.R "Limits and Methods of Measurement of Radio Interface Characteristics of Information Technology Equipment." International Special Committee on Radio Interference.
c) EN 55022 "Limits and Methods of Measurement of Radio Interface Characteristics of Information Technology Equipment." European Committee for Electrotechnical Standardization.(CENELEC), 1998
(Including A1: 2000)

8. Packing

8-1. Designation of Lot Mark

a) Lot Mark

A	B	C	D	E	F	G	H	I	J	K	L	M

A,B,C : SIZE(INCH)　　　　　　　　　　　　D : YEAR
E : MONTH　　　　　　　　　　　　　　　　F ~ M : SERIAL NO.

Note
  1. YEAR

Year	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010
Mark	1	2	3	4	5	6	7	8	9	0

2. MONTH

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Mark	1	2	3	4	5	6	7	8	9	A	B	C

b) Location of Lot Mark

Serial No. is printed on the label. The label is attached to the backside of the LCD module.
This is subject to change without prior notice.

8-2. Packing Form

a) Package quantity in one box : 40 pcs

b) Box Size : 395mm × 390mm × 286mm

9. PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD module.

9-1. MOUNTING PRECAUTIONS

(1) You must mount a module using holes arranged in four corners or four sides.
(2) You should consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
(3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to the resist external force.
(4) You should adopt radiation structure to satisfy the temperature specification.
(5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
(6) Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment.
Do not touch the surface of polarizer for bare hand or greasy cloth.(Some cosmetics are detrimental to the polarizer.)
(7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
(8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
(9) Do not open the case because inside circuits do not have sufficient strength.

9-2. OPERATING PRECAUTIONS

(1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage :
V=± 200mV(Over and under shoot voltage)

(2) Response time depends on the temperature.(In lower temperature, it becomes longer.)
(3) Brightness depends on the temperature. (In lower temperature, it becomes lower.)
And in lower temperature, response time(required time that brightness is stable after turned on) becomes longer.
(4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
(5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
(6) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference.

9-3. ELECTROSTATIC DISCHARGE CONTROL

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

9-4. PRECAUTIONS FOR STRONG LIGHT EXPOSURE

Strong light exposure causes degradation of polarizer and color filter.

9-5. STORAGE

When storing modules as spares for a long time, the following precautions are necessary.

(1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
(2) The polarizer surface should not come in contact with any other object.
   It is recommended that they be stored in the container in which they were shipped.

9-6. HANDLING PRECAUTIONS FOR PROTECTION FILM

(1) When the protection film is peeled off, static electricity is generated between the film and polarizer. This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
(2) The protection film is attached to the polarizer with a small amount of glue. If some stress is applied to rub the protection film against the polarizer during the time you peel off the film, the glue is apt to remain on the polarizer.
   Please carefully peel off the protection film without rubbing it against the polarizer.
(3) When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the polarizer after the protection film is peeled off.
(4) You can remove the glue easily. When the glue remains on the polarizer surface or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.

Product Specification

APPENDIX A. Enhanced Extended Display Identification Data (EEDID™) 1/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
Header	0	00	Header		00	00000000
	1	01	Header		FF	11111111
	2	02	Header		FF	11111111
	3	03	Header		FF	11111111
	4	04	Header		FF	11111111
	5	05	Header		FF	11111111
	6	06	Header		FF	11111111
	7	07	Header		00	00000000
EDID Vendor / Product Version	8	08	EISA manufacture code (3 Character ID)	LGD	30	00110000
	9	09	EISA manufacture code (Compressed ASCII)		E4	11100100
	10	0A	Panel Supplier Reserved - Product Code	017Fh	7F	01111111
	11	0B	(Hex. LSB first)		01	00000001
	12	0C	LCD Module Serial No - Preferred but Optional ("0" If not used)		00	00000000
	13	0D	LCD Module Serial No - Preferred but Optional ("0" If not used)		00	00000000
	14	0E	LCD Module Serial No - Preferred but Optional ("0" If not used)		00	00000000
	15	0F	LCD Module Serial No - Preferred but Optional ("0" If not used)		00	00000000
	16	10	Week of Manufacture	0 weeks	00	00000000
	17	11	Year of Manufacture	2008years	12	00010010
	18	12	EDID structure version # = 1		01	00000001
	19	13	EDID revision # = 3		03	00000011
Display Parameters	20	14	Video input Definition = Digital signal		80	10000000
	21	15	Max H image size (Rounded cm) = 19 cm		13	00010011
	22	16	Max V image size (Rounded cm) = 11 cm		0B	00001011
	23	17	Display gamma = (gamma*100)-100 = Example:(2.2*100)-100=120 = 2.2 Gamma		78	01111000
	24	18	Feature Support (no_DPMS, no_Active Off/Very Low Power, RGB color display, Timing BLK 1,no_ GTF)		0A	00001010
Panel Color Coordinates	25	19	Red/Green Low Bits (RxRy/GxGy)		D9	11011001
	26	1A	Blue/White Low Bits (BxBy/WxWy)		95	10010101
	27	1B	Red X Rx = 0.581		94	10010100
	28	1C	Red Y Ry =0.345		58	01011000
	29	1D	Green X Gx = 0.342		57	01010111
	30	1E	Green Y Gy =0.567		91	10010001
	31	1F	Blue X Bx = 0.162		29	00101001
	32	20	Blue Y By = 0.126		20	00100000
	33	21	White X Wx =0.313		50	01010000
	34	22	White Y Wy =0.329		54	01010100
Establ ished	35	23	Established timing 1 (00h if not used)		00	00000000
	36	24	Established timing 2 (00h if not used)		00	00000000
	37	25	Manufacturer's timings (00h if not used)		00	00000000
Standard Timing ID	38	26	Standard timing ID1 (01h if not used)		01	00000001
	39	27	Standard timing ID1 (01h if not used)		01	00000001
	40	28	Standard timing ID2 (01h if not used)		01	00000001
	41	29	Standard timing ID2 (01h if not used)		01	00000001
	42	2A	Standard timing ID3 (01h if not used)		01	00000001
	43	2B	Standard timing ID3 (01h if not used)		01	00000001
	44	2C	Standard timing ID4 (01h if not used)		01	00000001
	45	2D	Standard timing ID4 (01h if not used)		01	00000001
	46	2E	Standard timing ID5 (01h if not used)		01	00000001
	47	2F	Standard timing ID5 (01h if not used)		01	00000001
	48	30	Standard timing ID6 (01h if not used)		01	00000001
	49	31	Standard timing ID6 (01h if not used)		01	00000001
	50	32	Standard timing ID7 (01h if not used)		01	00000001
	51	33	Standard timing ID7 (01h if not used)		01	00000001
	52	34	Standard timing ID8 (01h if not used)		01	00000001
	53	35	Standard timing ID8 (01h if not used)		01	00000001

Product Specification

APPENDIX A. Enhanced Extended Display Identification Data (EEDID™)   2/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
Timing Descriptor #1	54	36	Pixel Clock/10,000 (LSB) 50.4 MHz @ 60Hz		B0	10110000
	55	37	Pixel Clock/10,000 (MSB)		13	00010011
	56	38	Horizontal Active (lower 8 bits)	1024 Pixels	00	00000000
	57	39	Horizontal Blanking(Thp-HA) (lower 8 bits)	320 Pixels	40	01000000
	58	3A	Horizontal Active / Horizontal Blanking(Thp-HA) (upper 4:4bits)		41	01000001
	59	3B	Vertical Avtive	600 Lines	58	01011000
	60	3C	Vertical Blanking (Tvp-HA) (DE Blanking typ.for DE only panels)	25 Lines	19	00011001
	61	3D	Vertical Active : Vertical Blanking (Tvp-HA) (upper 4:4bits)		20	00100000
	62	3E	Horizontal Sync. Offset (Thfp)	24 Pixels	18	00011000
	63	3F	Horizontal Sync Pulse Width (HSPW)	136 Pixels	88	10001000
	64	40	Vertical Sync Offset(Tvfp) : Sync Width (VSPW) 0 Lines : 22 Lines		03	00000011
	65	41	Horizontal Vertical Sync Offset/Width (upper 2bits)		01	00000001
	66	42	Horizontal Image Size (mm)	195 mm	C3	11000011
	67	43	Vertical Image Size (mm)	113 mm	71	01110001
	68	44	Horizontal Image Size / Vertical Image Size		00	00000000
	69	45	Horizontal Border = 0 (Zero for Notebook LCD)		00	00000000
	70	46	Vertical Border = 0 (Zero for Notebook LCD)		00	00000000
	71	47	Non-Interlace, Normal display, no stereo, Digital Separate (Vsync_NEG, Hsync_NEG), DE only note : LSB is set to '1' if panel is DE-timing only. H/V can be ignored.		18	00011000
Timing Descriptor #2	72	48	Flag		00	00000000
	73	49	Flag		00	00000000
	74	4A	Flag		00	00000000
	75	4B	Data Type Tag (Descriptor Defined by manufacturer)		00	00000000
	76	4C	Flag		00	00000000
	77	4D	Descriptor Defined by manufacturer		00	00000000
	78	4E	Descriptor Defined by manufacturer		00	00000000
	79	4F	Descriptor Defined by manufacturer		00	00000000
	80	50	Descriptor Defined by manufacturer		00	00000000
	81	51	Descriptor Defined by manufacturer		00	00000000
	82	52	Descriptor Defined by manufacturer		00	00000000
	83	53	Descriptor Defined by manufacturer		00	00000000
	84	54	Descriptor Defined by manufacturer		00	00000000
	85	55	Descriptor Defined by manufacturer		00	00000000
	86	56	Descriptor Defined by manufacturer		00	00000000
	87	57	Descriptor Defined by manufacturer		00	00000000
	88	58	Descriptor Defined by manufacturer		00	00000000
	89	59	Descriptor Defined by manufacturer		00	00000000
Timing Descriptor #3	90	5A	Flag		00	00000000
	91	5B	Flag		00	00000000
	92	5C	Flag		00	00000000
	93	5D	Data Type Tag (ASCII String)		FE	11111110
	94	5E	Flag		00	00000000
	95	5F	ASCII String	L	4C	01001100
	96	60	ASCII String	G	47	01000111
	97	61	ASCII String		20	00100000
	98	62	ASCII String	D	44	01000100
	99	63	ASCII String	i	69	01101001
	100	64	ASCII String	s	73	01110011
	101	65	ASCII String	p	70	01110000
	102	66	ASCII String	l	6C	01101100
	103	67	ASCII String	a	61	01100001
	104	68	ASCII String	y	79	01111001
	105	69	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		0A	00001010
	106	6A	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		20	00100000
	107	6B	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASCⅡ code 0Ah,set remaining char = 20h)		20	00100000

Product Specification

APPENDIX A. Enhanced Extended Display Identification Data (EEDID™)   3/3

	Byte (Dec)	Byte (Hex)	Field Name and Comments		Value (Hex)	Value (Bin)
Timing Descriptor #4	108	6C	Flag		00	00000000
	109	6D	Flag		00	00000000
	110	6E	Flag		00	00000000
	111	6F	Data Type Tag (Monitor Name, stored as ASCII)		FE	11111110
	112	70	Flag		00	00000000
	113	71	Monitor Name, stored as ASCII	L	4C	01001100
	114	72	Monitor Name, stored as ASCII	P	50	01010000
	115	73	Monitor Name, stored as ASCII	0	30	00110000
	116	74	Monitor Name, stored as ASCII	8	38	00111000
	117	75	Monitor Name, stored as ASCII	9	39	00111001
	118	76	Monitor Name, stored as ASCII	W	57	01010111
	119	77	Monitor Name, stored as ASCII	S	53	01010011
	120	78	Monitor Name, stored as ASCII	1	31	00110001
	121	79	Monitor Name, stored as ASCII	-	2D	00101101
	122	7A	Monitor Name, stored as ASCII	T	54	01010100
	123	7B	Monitor Name, stored as ASCII	L	4C	01001100
	124	7C	Monitor Name, stored as ASCII	A	41	01000001
	125	7D	Monitor Name, stored as ASCII	2	32	00110010
Chec	126	7E	Extension flag (# of optional 128 panel ID extension block to follow, Typ = 0)		00	00000000
	127	7F	Check Sum (The 1-byte sum of all 128 bytes in this panel ID block shall = 0)		01	00000001