

# SPECIFICATION FOR APPROVAL

( ) Preliminary Specification

( ◆ ) Final Specification

Title	15.6" FHD TFT LCD
-------	-------------------

Customer	
MODEL	

SUPPLIER	LG Display Co., Ltd.
*MODEL	LP156WF6
Suffix	SPK6

\*When you obtain standard approval,  
please use the above model name without suffix

APPROVED BY	SIGNATURE
/	
/	
/	

Please return 1 copy for your confirmation with your signature and comments.

APPROVED BY	SIGNATURE
J. S. Park / Manager	
<b>REVIEWED BY</b>	
I. Y. Jung / Manager	
<b>PREPARED BY</b>	
S.U. Kim / Engineer	
C. K. Uh / Engineer	
<b>Products Engineering Dept.</b> <b>LG Display Co., Ltd</b>	

## Contents

<b>RECORD OF REVISIONS.....</b>	<b>3</b>
<b>1. GENERAL DESCRIPTION.....</b>	<b>4</b>
<b>2. ABSOLUTE MAXIMUM RATINGS.....</b>	<b>5</b>
<b>3. ELECTRICAL SPECIFICATIONS.....</b>	<b>6</b>
3-1. LCD ELECTRICAL CHARACTERISTICS.....	6
3-2. LED BACKLIGHT ELECTRICAL CHARACTERISTICS.....	7
3-3. INTERFACE CONNECTIONS.....	8
3-4. eDP SIGNAL TIMING SPECIFICATION.....	9
3-5. SIGNAL TIMING SPECIFICATIONS.....	13
3-6. SIGNAL TIMING WAVEFORMS.....	13
3-7. COLOR INPUT DATA REFERENCE.....	14
3-8. POWER SEQUENCE.....	15
<b>4. OPTICAL SPECIFICATIONS.....</b>	<b>16</b>
<b>5. MECHANICAL CHARACTERISTICS.....</b>	<b>19</b>
<b>6. RELIABILITY.....</b>	<b>22</b>
<b>7. INTERNATIONAL STANDARDS.....</b>	<b>23</b>
7-1. SAFETY.....	23
7-2. ENVIRONMENT.....	23
<b>8. PACKING.....</b>	<b>24</b>
8-1. DESIGNATION OF LOT MARK.....	24
8-2. PACKING FORM.....	24
<b>9. PRECAUTIONS.....</b>	<b>27</b>
 APPENDIX A. LGD PROPOSAL FOR SYSTEM COVER DESIGN.....	 29
APPENDIX B. LGD PROPOSAL FOR eDP INTERFACE DESIGN GUIDE.....	35
APPENDIX C. ENHANCED EXTENDED DISPLAY IDENTIFICATION DATA.....	43

## Product Specification


**Record of Revisions**

Revision No	Revision Date	Page	Description	EDID version
0.0	Feb. 01. 2017	All	Preliminary Specification	0.0
1.0	Apr. 07. 2017	-	Final	

## Product Specification

### 1. General Description

The LP156WF6 is a Color Active Matrix Liquid Crystal Display with an integral LED backlight system. The matrix employs a-Si Thin Film Transistor as the active element. It is a transmissive type display operating in the normally black mode. This TFT-LCD has 15.6 inches diagonally measured active display area with FHD resolution (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 6-bit gray scale signal for each dot, thus, presenting a palette of more than 262,144 colors. The LP156WF6 has been designed to apply the interface method that enables low power, high speed, low EMI. The LP156WF6 is intended to support applications where thin thickness, low power are critical factors and graphic displays are important. In combination with the vertical arrangement of the sub-pixels, the LP156WF6 characteristics provide an excellent flat display for office automation products such as Notebook PC.



### General Features

Active Screen Size	15.6 inches diagonal
Outline Dimension	359.5(H, Typ.) × 223.80(V, Typ.) × 3.2(D, Max.) [mm](with Bracket & PCB Board)
Pixel Pitch	0.17925 mm X 0.17925 mm
Pixel Format	1920 horiz. By 1080 vert. Pixels RGB strip arrangement
Color Depth	6-bit, 262,144 colors
Luminance, White	250 cd/m <sup>2</sup> (Typ.)
Power Consumption	Total 3.85W (Typ.) Logic : 0.85W (Typ. @ Mosaic), B/L : 3.0W (Typ.)
Weight	350g (Max.) / 340g(Typ.)
Display Operating Mode	Normally Black
Surface Treatment	Anti-glare treatment of the front Polarizer
RoHS Compliance	Yes
BFR / PVC / As Free	Yes for all

## 2. Absolute Maximum Ratings

The following are maximum values which, if exceeded, may cause faulty operation or damage to the unit.

**Table 1. ABSOLUTE MAXIMUM RATINGS**


Parameter	Symbol	Values		Units	Notes
		Min	Max		
Power Input Voltage	VCC	-0.3	4.0	V <sub>DC</sub>	at 25 ± 2°C
Operating Temperature	T <sub>OP</sub>	0	50	°C	1
Storage Temperature	HST	-20	60	°C	1,2
Operating Ambient Humidity	H <sub>OP</sub>	10	90	%RH	1
Storage Humidity	HST	10	90	%RH	1,2

Note : 1. Temperature and relative humidity range are shown in the figure below.

Wet bulb temperature should be 39°C Max, and no condensation of water.

Note : 2. Storage Condition is guaranteed under packing condition.

Note : 3. System Storage Temp/Humidity Test Condition is guaranteed as described at appendix file.  
 (Appendix.System Storage Temp/Humidity Test Condition\_LGD\_160420.ppt)



### 3. Electrical Specifications


#### 3-1. LCD Electrical Characteristics

**Table 2. LCD ELECTRICAL CHARACTERISTICS**


Parameter	Symbol	Values			Unit	Notes
		Min	Typ	Max		
Power Supply Input Voltage	$V_{CC}$	3.0	3.3	3.6	V	1
Permissive Power Supply Input Ripple	$V_{CCrp}$	-	-	100	mV <sub>p-p</sub>	
Power Supply Input Current	Mosaic $I_{CC}$	-	255	305	mA	2
Power Consumption	$P_{CC}$	-	0.85	1.0	W	
Power Supply Inrush Current	$I_{CC\_P}$	-	-	1.5	A	3
Differential Impedance	$Z_{eDP}$	90	100	110	$\Omega$	

Note)

1. The measuring position is the connector of LCM and the test conditions are under 25°C,  $f_v = 60\text{Hz}$
2. The specified  $I_{CC}$  current and power consumption are under the  $V_{CC} = 3.3\text{V}$ , 25°C,  $f_v = 60\text{Hz}$  condition and Mosaic pattern.



3. The  $V_{CC}$  rising time is same as the minimum of T1 at Power on sequence.




### 3-2. LED Backlight Electrical Characteristics

**Table 3. LED B/L ELECTRICAL CHARACTERISTICS**

Parameter		Symbol	Values			Unit	Notes
			Min	Typ	Max		
LED Power Input Voltage		$V_{LED}$	5.5	12.0	21.0	V	1
LED Power Input Current		$I_{LED}$	-	250	260	mA	2
LED Power Consumption		$P_{LED}$	-	3.0	3.1	W	
LED Power Inrush Current		$I_{LED\_P}$	-	-	1.5	A	3
PWM Duty Ratio			1	-	100	%	4
PWM Jitter			0	-	0.2	%	5
PWM Frequency		$F_{PWM}$	200	-	1000	Hz	6
PWM	High Level Voltage	$V_{PWM\_H}$	2.2	-	3.6	V	
	Low Level Voltage	$V_{PWM\_L}$	0	-	0.6	V	
LED_EN	High Voltage	$V_{LED\_EN\_H}$	2.2	-	3.6	V	
	Low Voltage	$V_{LED\_EN\_L}$	0	-	0.6	V	
Life Time			12,000	-	-	Hrs	7

Note)

1. The measuring position is the connector of LCM and the test conditions are under 25°C.
2. The current and power consumption with LED Driver are under the  $V_{LED} = 12.0V$ , 25°C, PWM Duty 100% and White pattern with the normal frame frequency operated(60Hz).
3. The  $V_{LED}$  rising time is same as the minimum of T13 at Power on sequence.




4. The operation of LED Driver below minimum dimming ratio may cause flickering or reliability issue.
5. If Jitter of PWM is bigger than maximum, it may induce flickering.
6. This Spec. is not effective at 100% dimming ratio as an exception because it has DC level equivalent to 0Hz. In spite of acceptable range as defined, the PWM Frequency should be fixed and stable for more consistent brightness control at any specific level desired.
7. The life time is determined as the time at which brightness of LCD is 50% compare to that of minimum value specified in table 7. under general user condition.

## Product Specification

### 3-3. Interface Connections

**Table 4. MODULE CONNECTOR PIN CONFIGURATION (CN1)**


Pin	Symbol	Description	Notes
1	NC Reserved	Reserved for LCD manufacturer's use	[Connector] KN38B-30-0.5H, HRS, 30, 0.5
2	GND	High Speed Ground	
3	Lane1_N	Complement Signal Link Lane 1	
4	Lane1_P	True Signal Link Lane 1	
5	GND	High Speed Ground	
6	Lane0_N	Complement Signal Link Lane 0	
7	Lane0_P	True Signal Link Lane 0	
8	GND	High Speed Ground	
9	AUX_CH_P	True Signal Auxiliary Channel	
10	AUX_CH_N	Complement Signal Auxiliary Channel	
11	GND	High Speed Ground	[Connector pin arrangement] 
12	VCC	LCD logic and driver power	
13	VCC	LCD logic and driver power	
14	LCD Self Test or NC	LCD Panel Self Test Enable (Optional)	
15	GND	LCD logic and driver ground	
16	GND	LCD logic and driver ground	
17	HPD	HPD signal pin	
18	BL_GND	LED Backlight ground	
19	BL_GND	LED Backlight ground	
20	BL_GND	LED Backlight ground	
21	BL_GND	LED Backlight ground	[LGD P-Vcom using information] 1. Pin for P-Vcom : #25, #30 2. P-Vcom Address : 0101000x
22	BL ENABLE	LED Backlight control on/off control	
23	BL PWM	System PWM signal input for dimming	
24	Hsync	Hsync for Active Pen	
25	NC Reserved	Reserved for LCD manufacture's use	
26	VLED	LED Backlight power (12V Typical)	
27	VLED	LED Backlight power (12V Typical)	
28	VLED	LED Backlight power (12V Typical)	
29	VLED	LED Backlight power (12V Typical)	
30	NC Reserved	Reserved for LCD manufacture's use	




Product Specification

### 3-4. eDP Signal Timing Specifications


#### 3-4-1. Definition of Differential Voltage



#### 3-4-2. Main Link EYE Diagram



[ EYE Mask at Source Connector Pins ]



[ EYE Mask at Sink Connector Pins ]

Point	Reduced Bit Rate		High Bit Rate	
	Time(UI)	Voltage(V)	Time(UI)	Voltage(V)
1	0.127	0.000	0.210	0.000
2	0.291	0.160	0.355	0.140
3	0.500	0.200	0.500	0.175
4	0.709	0.200	0.645	0.175
5	0.873	0.000	0.790	0.000
6	0.709	-0.200	0.645	-0.175
7	0.500	-0.200	0.500	-0.175
8	0.291	-0.160	0.355	-0.140

[ EYE Mask Vertices at Source Connector Pins ]

Point	Reduced Bit Rate		High Bit Rate	
	Time(UI)	Voltage(V)	Time(UI)	Voltage(V)
1	0.375	0.000	0.246	0.000
2	0.500	0.023	0.500	0.075
3	0.625	0.000	0.755	0.000
4	0.500	-0.023	0.500	-0.075


[ EYE Mask Vertices at Sink Connector Pins ]

Point	Reduced Bit Rate		High Bit Rate	
	Time(UI)	Voltage(V)	Time(UI)	Voltage(V)
1	0.270	0.000	0.246	0.000
2	0.500	0.068	0.500	0.075
3	0.731	0.000	0.755	0.000
4	0.500	-0.068	0.500	-0.075

[ EYE Mask Vertices at embedded DP Sink Connector Pins ]

## Product Specification

### 3-4-3. eDP Main Link Signal




Parameter	Symbol	Min	Typ	Max	Unit	Notes
Unit Interval for high bit rate (2.7Gbps / lane)	UI_HBR	-	370	-	ps	
Unit Interval for reduced bit rate (1.62Gbps / lane)	UI_RBR	-	617	-	ps	
Link Clock Down Spreading	Amplitude	0	-	0.5	%	
	Frequency	30		33	kHz	
Differential peak-to-peak voltage at Source side connector	$V_{TX-DIFFp-p}$	350	-	-	mV	For HBR(2.7Gbps)
		400	-	-		For RBR(1.62Gbps)
EYE width at Source side connector	$T_{TX-EYE-CONN}$	0.58	-	-	UI	For HBR(2.7Gbps)
		0.75	-	-	UI	For RBR(1.62Gbps)
Differential peak-to-peak voltage at Sink side connector	$V_{RX-DIFFp-p}$	150	-	-	mV	For HBR(2.7Gbps)
		136	-	-		For RBR(1.62Gbps)
EYE width at Sink side connector	$T_{RX-EYE-CONN}$	0.51	-	-	UI	For HBR(2.7Gbps)
		0.46	-	-	UI	For RBR(1.62Gbps)
Rx DC common mode voltage	$V_{RX CM}$	0	-	1.0	V	
AC Coupling Capacitor	$C_{SOURCE-ML}$	75		200	nF	Source side

#### Note)

1. Termination resistor is typically integrated into the transmitter and receiver implementations.
2. AC Coupling Capacitor is not placed at the sink side.
3. In cabled embedded system, it is recommended the system designer ensure that EYE width and voltage are met at the sink side connector pins.

## Product Specification

**3-4-4. eDP AUX Channel Signal**



Parameter	Symbol	Min	Typ	Max	Unit	Notes
AUX Unit Interval	UI	0.4	-	0.6	us	
AUX Jitter at Tx IC Package Pins	$T_{\text{jitter}}$	-	-	0.04	UI	Equal to 24ns
AUX Jitter at Rx IC Package Pins		-	-	0.05	UI	Equal to 30ns
AUX Peak-to-peak voltage at Connector Pins of Receiving	$V_{\text{AUX-DIFFp-p}}$	0.39	-	1.38	V	
AUX Peak-to-peak voltage at Connector Pins of Transmitting		0.36	-	1.36	V	
AUX EYE width at Connector Pins of Tx and Rx		0.98	-	-	UI	
AUX DC common mode voltage	$V_{\text{AUX-CM}}$	0	-	1.0	V	
AUX AC Coupling Capacitor	$C_{\text{SOURCE-AUX}}$	75		200	nF	Source side

Note)

1. Termination resistor is typically integrated into the transmitter and receiver implementations.
2. AC Coupling Capacitor is not placed at the sink side.
3.  $V_{\text{AUX-DIFFp-p}} = 2 * |V_{\text{AUXP}} - V_{\text{AUXN}}|$

## Product Specification

### 3-4-5. eDP HPD Signal



Parameter	Symbol	Min	Typ	Max	Unit	Notes
HPD Voltage	HPD	2.25	-	3.6	V	Sink side Driving
Hot Plug Detection Threshold		2.0	-	-	V	Source side Detecting
Hot Unplug Detection Threshold		-	-	0.8	V	
HPD_IRQ Pulse Width	HPD_IRQ	0.5	-	1.0	ms	
HPD_TimeOut		2.0	-	-	ms	HPD Unplug Event

#### Note)

1. HPD IRQ : Sink device wants to notify the Source device that Sink's status has changed so it toggles HPD line, forcing the Source device to read its Link / Sink Receiver DPCD field via the AUX-CH
2. HPD Unplug : The Sink device is no longer attached to the Source device and the Source device may then disable its Main Link as a power saving mode
3. Plug / Re-plug : The Sink device is now attached to the Source device, forcing the Source device to read its Receiver capabilities and Link / Sink status Receiver DPCD fields via the AUX-CH

**Product Specification**

### 3-5. Signal Timing Specifications


This is the signal timing required at the input of the User connector. All of the interface signal timing should be satisfied with the following specifications and specifications of eDP Tx/Rx for its proper operation.

**Table 4. TIMING TABLE**

ITEM	Symbol		Min	Typ	Max	Unit	Note
DCLK	Frequency	f <sub>CLK</sub>	-	138.7	-	MHz	
Hsync	Period	t <sub>HP</sub>	2072	2080	2088	t <sub>CLK</sub>	
	Width	t <sub>WH</sub>	32	32	32		
	Width-Active	t <sub>WHA</sub>	1920				
Vsync	Period	t <sub>VP</sub>	1108	1111	1114	t <sub>HP</sub>	
	Width	t <sub>WV</sub>	5	5	5		
	Width-Active	t <sub>WVA</sub>	1080				
Data Enable	Horizontal back porch	t <sub>HBP</sub>	72	80	88	t <sub>CLK</sub>	
	Horizontal front porch	t <sub>HFP</sub>	48	48	48		
	Vertical back porch	t <sub>VBP</sub>	20	23	24	t <sub>HP</sub>	
	Vertical front porch	t <sub>VFP</sub>	3	3	5		

**Notice.** all reliabilities are specified for timing specification based on refresh rate of 60Hz. However, LP156WF6 has a good actual performance even at lower refresh rate (e.g. 40Hz or 50Hz) for power saving Mode, whereas LP156WF6 is secured only for function under lower refresh rate. 60Hz at Normal mode, 50Hz, 40Hz at Power save mode. Don't care Flicker level (Power save mode).

### 3-6. Signal Timing Waveforms



**Product Specification**
**3-7. Color Input Data Reference**

The brightness of each primary color (red, green and blue) is based on the 6-bit gray scale data input for the color ; the higher the binary input, the brighter the color. The table below provides a reference for color versus data input.

**Table 5. COLOR DATA REFERENCE**

Color		Input Color Data																	
		RED						GREEN						BLUE					
		MSB			LSB			MSB			LSB			MSB			LSB		
		R 5	R 4	R 3	R 2	R 1	R 0	G 5	G 4	G 3	G 2	G 1	G 0	B 5	B 4	B 3	B 2	B 1	B 0
Basic Color	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
RED	RED (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (01)	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0
	...	...						...						...					
	RED (62)	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0
	RED (63)	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
GREEN	GREEN (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	GREEN (01)	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0
	...	...						...						...					
	GREEN (62)	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	0
	GREEN (63)	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
BLUE	BLUE (00)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	BLUE (01)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	...	...						...						...					
	BLUE (62)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	0
	BLUE (63)	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1

Product Specification

### 3-8. Power Sequence




Table 6. POWER SEQUENCE TABLE

Symbol	Required By	Limits		Units	Notes
		Min	Max		
T <sub>1</sub>	Source	0.5	10	ms	-
T <sub>2</sub>	Sink	0	200	ms	-
T <sub>3</sub>	Sink	0	200	ms	-
T <sub>4</sub>	Source	-	-	ms	-
T <sub>5</sub>	Source	-	-	ms	-
T <sub>6</sub>	Source	-	-	ms	-
T <sub>7</sub>	Sink	0	50	ms	-
T <sub>8</sub>	Source	-	-	ms	LGD recommend Min 200ms
T <sub>9</sub>	Source	-	-	ms	
T <sub>10</sub>	Source	0	500	ms	-
T <sub>11</sub>	Source	-	10	ms	-
T <sub>12</sub>	Source	150	-	ms	VESA recommend Min 500ms
T <sub>13</sub>	Source	0.5	10	ms	-
T <sub>14</sub>	Source	0.5	10	ms	-
T <sub>15</sub>	Source	10	-	ms	-
T <sub>16</sub>	Source	10	-	ms	-
T <sub>17</sub>	Source	0	-	ms	-
T <sub>18</sub>	Source	0	-	ms	-

- Note) 1. Do not insert the mating cable when system turn on.  
 2. Valid Data have to meet "3-3. eDP Signal Timing Specifications"  
 3. Video Signal, LED\_EN and PWM need to be on pull-down condition on invalid status.  
 4. LGD recommend the rising sequence of VLED after the Vcc and valid status of Video Signal turn on.


## Product Specification

### 4. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable for approximately 20 minutes in a dark environment at 25°C. The values specified are at an approximate distance 50cm from the LCD surface at a viewing angle of  $\Phi$  and  $\Theta$  equal to 0°.

FIG. 1 presents additional information concerning the measurement equipment and method.

**FIG. 1 Optical Characteristic Measurement Equipment and Method**



**Table 7. OPTICAL CHARACTERISTICS**

Ta=25°C, VCC=3.3V, fv=60Hz

Parameter		Symbol	Values			Units	Notes
			Min	Typ	Max		
Contrast Ratio		CR	600	700	-		1
Surface Luminance, white		L <sub>WH</sub>	213	250	288	cd/m <sup>2</sup>	2
Luminance Variation		$\delta_{\text{WHITE (5P)}}$	80%		-	-	3
		$\delta_{\text{WHITE (13P)}}$	60%	70%	-		
Response Time		Tr + Tf	-	25	35	ms	4
Color Coordinates	RED	Rx	Typical - 0.03	0.580	Typical + 0.03		5
		Ry		0.350			
	GREEN	Gx		0.340			
		Gy		0.560			
	BLUE	Bx		0.155			
		By		0.125			
	WHITE	Wx		0.313			
		Wy		0.329			
Viewing Angle	x axis, right( $\Phi=0^\circ$ )	$\Theta_r$	80	-	-	Degree	6
	x axis, left ( $\Phi=180^\circ$ )	$\Theta_l$	80	-	-		
	y axis, up ( $\Phi=90^\circ$ )	$\Theta_u$	80	-	-		
	y axis, down ( $\Phi=270^\circ$ )	$\Theta_d$	80	-	-		
Gray Scale							7



## Product Specification

Note)

1. It should be measured in the center of screen(1 Point). Contrast Ratio(CR) is defined mathematically as

$$\text{Contrast Ratio(1 Point)} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

2. Surface luminance is the average of 5 point across the LCD surface 50cm from the surface with all pixels displaying white. For more information see FIG 2.

$$L_{WH} = \text{Average}(1,2, \dots 5 \text{ Point})$$

3. The variation in surface luminance , The panel total variation ( $\delta$  WHITE) is determined by measuring N at each test position 1 through 13 and then defined as following numerical formula.  
For more information see FIG 2.

$$\delta \text{ WHITE (5P)} = \frac{\text{Maximum (1,2, ... 5 Point)}}{\text{Minimum (1,2, ... 5 Point)}} \quad \delta \text{ WHITE (13P)} = \frac{\text{Maximum (1,2, ... 13 Point)}}{\text{Minimum (1,2, ... 13 Point)}}$$

4. Response time is the time required for the display to transition from black to white (rise time, Tr) and from white to black (falling time, Tf). For additional information see FIG 3.

5. It should be measured in the center of screen (1Point).

6. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 4.


7. Gray scale specification

Gray Level	Luminance [%] (Typ)
L0	0.1
L7	0.8
L15	5.6
L23	13.3
L31	23.0
L39	37.7
L47	55.2
L55	75.5
L63	100.0

Product Specification

**FIG. 2 Luminance**


<Measuring point for Average Luminance & measuring point for Luminance variation>




**FIG. 3 Response Time**

Active Area

The response time is defined as the following figure and shall be measured by switching the input signal for "black" and "white".



**FIG. 4 Viewing angle**



## Product Specification

## 5. Mechanical Characteristics

The contents provide general mechanical characteristics for the model LP156WF6. In addition the figures in the next page are detailed mechanical drawing of the LCD.


<b>Outline Dimension</b>	Horizontal	359.5 ± 0.5 mm
	Vertical	223.80 ± 0.5 mm(with Bracket & PCB Board)
	Thickness	3.2 mm(max.)
<b>Upper Polarizer Dimension</b>	Horizontal	347.45 ± 0.5 mm
	Vertical	196.8 ± 0.5 mm
<b>Active Display Area</b>	Horizontal	344.16 mm
	Vertical	193.59 mm
<b>Weight</b>	350g (Max.) / 340g(Typ.)	
<b>Surface Treatment</b>	Anti-Glare treatment of the front polarizer	

## Product Specification

### <FRONT VIEW>

Notes (Measurement method refer to the Appendix D)


- 1) Unit[mm], General tolerance :  $\pm 0.5\text{mm}$
- 2) System Bracket Angle Spec :  $87 \pm 2^\circ$
- 3) All components except cover shield of LCM is under upper POL.



UPPER POLARIZER IS HIGHER THAN SOURCE C/SHEILD PRESSED DOWN 50gf

<REAR VIEW>

1) Unit[mm], General tolerance :  $\pm 0.5\text{mm}$   
2) LCM Label Information refer to the page 24.



## Product Specification

### 6. Reliability

Environment test condition

No.	Test Item	Conditions
1	High temperature storage test	Ta= 60°C, 240h
2	Low temperature storage test	Ta= -20°C, 240h
3	High temperature operation test	Ta= 50°C, 50%RH, 240h
4	Low temperature operation test	Ta= 0°C, 240h
5	Vibration test (non-operating)	Random, 1.0Grms, 10 ~ 300Hz(PSD 0.0035) 3 axis, 30min/axis
6	Shock test (non-operating)	- No functional or cosmetic defects following a shock to all 6 sides delivering at least 180 G in a half sine pulse no longer than 2 ms to the display module - No functional defects following a shock delivering at least 200 g in a half sine pulse no longer than 2 ms to each of 6 sides. Each of the 6 sides will be shock tested with one each display, for a total of 6 displays
7	Altitude operating storage / shipment	0 ~ 10,000 feet (3,048m) 24Hr 0 ~ 40,000 feet (12,192m) 24Hr

[ Result Evaluation Criteria ]

1. Comparing the initial functional FOS status, there should be no major change which might affect the practical display function when the display reliability test is conducted.
2. After conduct reliability tests, LGD guarantees only functional FOS quality.
3. In the Reliability Test, Confirm performance after leaving in room temp.
4. In the standard condition, there shall be no practical problems that may affect the display function 24 hours later after reliability test. After the reliability test, we can guarantee the product only when the corrosion is causing its malfunction. The corrosion causing no functional defect can not be guaranteed.

## 7. International Standards

### 7-1. Safety

- a) UL 60950-1, Underwriters Laboratories Inc.  
Information Technology Equipment - Safety - Part 1 : General Requirements.
- b) CAN/CSA-C22.2 No. 60950-1-07, Canadian Standards Association.  
Information Technology Equipment - Safety - Part 1 : General Requirements.
- c) EN 60950-1, European Committee for Electro technical Standardization (CENELEC).  
Information Technology Equipment - Safety - Part 1 : General Requirements.
- d) IEC 60950-1, The International Electro technical Commission (IEC).  
Information Technology Equipment - Safety - Part 1 : General Requirements

### 7-2. Environment

- a) RoHS, Directive 2011/65/EU of the European Parliament and of the council of 8 June 2011

## Product Specification

### 8. Packing

#### 8-1. Designation of Lot Mark



##### a) Lot Mark

A	B	C	D	E	F	G	H	I	J	K	L	M
---	---	---	---	---	---	---	---	---	---	---	---	---

A,B,C : SIZE(INCH)

E : MONTH

D : YEAR

F ~ M : SERIAL NO.

##### Note

##### 1. YEAR

Year	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020
Mark	A	B	C	D	E	F	G	H	J	K

##### 2. MONTH

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Mark	1	2	3	4	5	6	7	8	9	A	B	C

##### b) Location of Lot Mark

Serial No. is printed on the label. The label is attached to the backside of the LCD module.  
 This is subject to change without prior notice.

#### 8-2. Packing Form


a) Package quantity in one box : 20 pcs

b) Box Size : 365 x 478 x 328



## # APPENDIX-1


### ■ Packing Assembly




## # APPENDIX-2

### ■ Pallet Assembly


1. Pallet Ready




2. 3 x 2 x 3 Box Pattern



3. Angle Packing & Taping



4. Banding



## 9. PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD module.

### 9-1. MOUNTING PRECAUTIONS

- (1) You must mount a module using holes arranged in four corners or four sides.
- (2) You should consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
- (3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to resist external force.
- (4) You should adopt radiation structure to satisfy the temperature specification.
- (5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
- (6) Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment. Do not touch the surface of polarizer for bare hand or greasy cloth. (Some cosmetics are detrimental to the polarizer.)
- (7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
- (8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
- (9) Do not open the case because inside circuits do not have sufficient strength.
- (10) When handling the LCD module, it needs to handle with care not to give mechanical stress to the PCB and Mounting Hole area."

### 9-2. OPERATING PRECAUTIONS

- (1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage :  
 $V = \pm 200\text{mV}$  (Over and under shoot voltage)
- (2) Response time depends on the temperature. (In lower temperature, it becomes longer.)
- (3) Brightness depends on the temperature. (In lower temperature, it becomes lower.)  
And in lower temperature, response time (required time that brightness is stable after turned on) becomes longer.
- (4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
- (5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
- (6) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.

### 9-3. ELECTROSTATIC DISCHARGE CONTROL

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

### 9-4. PRECAUTIONS FOR STRONG LIGHT EXPOSURE

Strong light exposure causes degradation of polarizer and color filter.

### 9-5. STORAGE

When storing modules as spares for a long time, the following precautions are necessary.

- (1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
- (2) The polarizer surface should not come in contact with any other object.  
It is recommended that they be stored in the container in which they were shipped.

### 9-6. HANDLING PRECAUTIONS FOR PROTECTION FILM





- (1) When the protection film is peeled off, static electricity is generated between the film and polarizer.  
This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
- (2) The protection film is attached to the polarizer with a small amount of glue. If some stress is applied to rub the protection film against the polarizer during the time you peel off the film, the glue is apt to remain on the polarizer.  
Please carefully peel off the protection film without rubbing it against the polarizer.
- (3) When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the polarizer after the protection film is peeled off.
- (4) You can remove the glue easily. When the glue remains on the polarizer surface or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.

### 9-7. THE LGD QA RESPONSIBILITY WILL BE AVOIDED IN CASE OF BELOW

- (1) When the customer attaches TSM(Touch Sensor Module) on LCM without Supplier's approval.
- (2) When the customer attaches cover glass on LCM without Supplier's approval.
- (3) When the LCMs were repaired by 3rd party without Supplier's approval.
- (4) When the LCMs were treated like Disassemble and Rework by the Customer and/or Customer's representatives without supplier's approval.

Product Specification

APPENDIX A. LGD Proposal for system cover design

1	Gap check for securing the enough gap between LCM and System back cover.
<div>   <div> <p>Boss</p> <p>Back cover</p> <p>LCM</p> <p>PAD</p> <p>a</p> <p>b</p> </div> <div> <p>Boss</p> <p>PAD</p> <p>Back cover</p> </div> <div> <p>◆ a : min 0mm</p> <p>◆ b : min 0.3mm, Max 1.0mm</p> </div> </div>	
Define	<p>1. Rear side of LCM is sensitive against external stress, and previous check about interference is highly needed.</p> <p>2. In case there is something from system cover comes into the boundary above, mechanical interference may cause the FOS defects. (e.g.. Ripple, White spot..)</p>
2	Check if antenna cable is sufficiently apart from T-CON of LCD Module.
<div>   <div> <p>Antenna</p> <p>Antenna</p> <p>Antenna Cable</p> <p>T-CON</p> <p>OK</p> <p>NG</p> </div> </div>	
Define	If system antenna is overlapped with T-CON, It might be cause the noise






Product Specification

APPENDIX A. LGD Proposal for system cover design

3	Checking the path of the System wire
Define	<p>1. If Wire path overlapped with LCM, it is happened white spot. COF problem, etc.</p> <p>2. OK → Wire path design to system side. NG → Wire path overlapped with LCM.</p>
4	Add pad to Prevent panel crack against external load (push)
Define	<p>1. At flat type LCM, panel is easily cracked at flange area during push, assemble.</p> <p>2. Add pad, it prevent panel crack</p>





Product Specification

APPENDIX A. LGD Proposal for system cover design

5	Check the rib or Bracket on back cover
<div>  <div>OK</div> <div>Rib</div> </div> <div>  <div>OK</div> <div>Bracket</div> </div> <div>  <div>NG</div> </div> <div>  <div>CO</div> </div>	
Define	1.It is necessary that the height of back cover rib or bracket is higher than LCM height. It can prevent direct compression of panel at LCM edge.
	2.“┐” shape bracket is stronger than “I” shape one.
6	Check the gap between front cover and LCM (glass)
<div>  <div> <div>[OK] <math>a \geq 0.3\text{mm}</math></div> <div>[CO] <math>0.3\text{mm} \geq a \geq 0.1\text{mm}</math></div> <div>[NG] <math>a \leq 0.1\text{mm}</math></div> </div> </div>	
Define	Ripple can be happened by little gap between glass and front cover.

## Product Specification




**APPENDIX A. LGD Proposal for system cover design**

7	<b>Check the rib or Bracket on back cover</b>
	<div data-bbox="125 415 684 687">  <p>OK</p> </div> <div data-bbox="741 415 1299 687">  <p>NG</p> </div>
Define	1.If it is possible, shrink to apply front cover of white color. 2. White color can caused light leakage
8	<b>Check the wire position(path)</b>
	<div data-bbox="132 1014 778 1269">  <p>OK</p> </div> <div data-bbox="132 1323 778 1593">  <p>NG</p> </div>
Define	1. It is necessary that wire is posited out of hook, not posited near hook,. 2. If wire is posited near hook, it can be happened assemble error and panel crack during assemble front cover








Product Specification




APPENDIX A. LGD Proposal for system cover design

9	Check mouse pad (touch pad) depth and shape of edge
<div>   <div> <p>[OK] <math>a \leq 0.3\text{mm}</math>  [CO] <math>0.5\text{mm} \geq a \geq 0.3\text{mm}</math>  [NG] <math>a \geq 0.5\text{mm}</math></p> </div> <p>Mouse pad</p> <p>OK NG</p> </div>	
Define	<p>1. Mouse pad step is deep, it is caused panel crack by external load.</p> <p>2. The edge shape must be smooth.</p>
10	Check the step of keyboard area
<div>  <p>Keyboard</p> <p>push</p> <p>OK NG</p> </div>	
Define	The step of keyboard at the side edge of main body, it is caused panel crack

## APPENDIX A. LGD Proposal for system cover design

11	Check the gap [PCB ~ system]
<div style="display: flex; justify-content: space-around; align-items: flex-start;">   </div> <div style="background-color: #c8e6c9; padding: 5px; margin-top: 10px;"> <math>a \geq 0.5\text{mm}</math> [at max dimension of design]  <math>a \geq 1.0\text{mm}</math> [at typical dimension of design]         </div>	
Define	<ol style="list-style-type: none"> <li>Gap is too small, FPC is easily cracked by interference and repetitive bending. (circuit is opened) .</li> <li>Gap is must be kept more than 0.5mm(max dim.) and 1.0mm(typ dim.) .</li> </ol>
12	System rib (on A cover)
<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;">  <div style="background-color: #bbdefb; padding: 5px; margin-top: 10px;">OK</div> </div> <div style="text-align: center;">  <div style="background-color: #bbdefb; padding: 5px; margin-top: 10px;">NG</div> </div> </div> <div style="display: flex; justify-content: space-around; align-items: flex-start; margin-top: 20px;">  <div style="background-color: #c8e6c9; padding: 5px;"> <math>a \geq 0.5\text{mm}</math> [at max dimension of design]  <math>a \geq 1.0\text{mm}</math> [at typical dimension of design]         </div> </div>	
Define	<ol style="list-style-type: none"> <li>Gap is too small and rib is too short, panel is easily cracked by external stress.</li> <li>Gap is must be kept more than 0.5mm(max dim.) and 1.0mm(typ dim.) .</li> <li>The figure of rib is continuous or fully long.</li> </ol>



**APPENDIX B. LGD Proposal for eDP Interface Design Guide**

1	<b>HPD Signal recognition</b>
	<div style="display: flex; justify-content: space-around;"> <div data-bbox="107 382 721 782">  <p><b>[ Abnormal Communication By HPD Glitch ]</b></p> </div> <div data-bbox="742 382 1349 782">  <p><b>[ Normal Communication By HPD Signal ]</b></p> </div> </div>
Define	<ol style="list-style-type: none"> <li>1. Hot Plug Detection (HPD) Threshold level of Source Device is minimum 2.0V</li> <li>2. HPD Unplug : HPD pulse stays low longer than 2ms. DP Tx shall wait for HPD signal to go high again.</li> <li>3. "HPD High" is confirmed only after HPD has been asserted continuously for 100msec.</li> </ol>
2	<b>IRQ (Interrupt Request) HPD Pulse Definition</b>
Ex) HPD Pulse	
Define	Upon detection this "HPD IRQ Event"(0.5ms ~ 1ms) ,the source device must read the link / sink status field of the DPCD and take corrective action.


Product Specification

APPENDIX B. LGD Proposal for eDP Interface Design Guide

3 Main Link EYE Diagram




[EYE Diagram]



Point	UI	Voltage (Volts)
1	0.210	0.000
2	0.355	0.140
3	0.500	0.175
4	0.645	0.175
5	0.790	0.000
6	0.645	-0.175
7	0.500	-0.175
8	0.355	-0.140

[EYE Vertices for TP2 at HBR]




Point	UI	Voltage (Volts)
1	0.246	0.000
2	0.500	0.075
3	0.755	0.000
4	0.500	-0.075

[EYE Vertices for TP3 at HBR]

Define Main Link EYE Diagram should meet TP2 and TP3 point

4 Cable Impedance management




Segment	Differential Impedance	Maximum Tolerance
Fixture	100 $\Omega$	+/- 10%
Connector	100 $\Omega$	
Wire management	100 $\Omega$	
Cable	100 $\Omega$	+/- 5%

Define Cable Impedance 100  $\Omega$  +/- 5% ( 95 $\Omega$  ~ 105 $\Omega$  )

## APPENDIX B. LGD Proposal for eDP Interface Design Guide

### 5

### Main Link Off vs. LCD Power Off at Non-PSR




Timing Parameter	Description	Required By	Min	Max
T10	Delay from end of valid video from Source to Power Off	Source	0ms	500ms

\* LGD recommend that Source must power off the LCDVCC if Main Link off like below.



[Case1. Resolution Change]




[Case2. Close the Lid]

Define

If Main Link off signal from Source, then LCDVCC must be Power Off within T10 period at Non-PSR mode

## Product Specification

**APPENDIX B. LGD Proposal for eDP Interface Design Guide**
**6 Main Link M & N value of MSA data**


Define


It need to fix M&amp; N value of MSA data output to prevent the initial abnormal M&amp; N Value from incoming after power on.

Product Specification


APPENDIX B. LGD Proposal for eDP Interface Design Guide

7	PSR Exit
---	----------

If link training is not required, the Source must begin transmitting data on the Main Link prior to the wake AUX command which occurs through writing 01h to the SET\_POWER & SET\_DP\_PWR\_VOLTAGE register (DPCD Address 00600h; see DP v1.2a), as illustrated in the upper portion of Figure 6-9. This transmitted data must be a repetition of D10.2 symbols (which is the same as Link Training Pattern 1). Note the requirement above to transmit five repeats of the Idle Pattern after receiving ACK from the Sink.




- The below waveform is the issued case.




Define	If link training is not required, the source must begin transmitting data on the ML prior to the wake AUX wake-up command.
--------	--

## APPENDIX B. LGD Proposal for eDP Interface Design Guide

### 8 1<sup>st</sup> time PSR Entry after Power on



< Issue waveform >



< solution waveform >

1. It is found that with solution , the TCON enter the PSR timing is 1.2s delay from VCC on which avoid TCON capture the wrong data from DP link(poor link quality) and enter the BIST mode + PSR mode(black screen).
2. According to test, link is stable 800ms after VCC on.



Define

After power(Vcc) on, the DP link is not stable, so the source try to PSR entry at 800ms after Power(Vcc) on..



## APPENDIX B. LGD Proposal for eDP Interface Design Guide

### 9 PSR Period Issue





1. When issue is happened, system go to PSR mode for very short time.
2. If PSR active period is shorter than 1frame(16.67ms), T-Con can not go to the standby mode for PSR exit.

Define

When GPU go to the PSR mode, the source must hold the main link off over than 1frame.

## APPENDIX B. LGD Proposal for eDP Interface Design Guide

10	Main Link Noise at PSR Exit
	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p><b>[ Abnormal Main Link Noise ]</b></p> </div> <div style="text-align: center;">  <p><b>[ Normal Main Link Signal ]</b></p> </div> </div>
Define	Main Link Noise at PSR Exit mode can be a cause abnormal display.

**Product Specification**
**APPENDIX C. Enhanced Extended Display Identification Data (EEDID™) 1/3**

	Byte (Dec)	Byte (Hex)	Field Name and Comments	Value (Hex)	Value (Bin)
<b>Header</b>	0	00	Header	00	00000000
	1	01	Header	FF	11111111
	2	02	Header	FF	11111111
	3	03	Header	FF	11111111
	4	04	Header	FF	11111111
	5	05	Header	FF	11111111
	6	06	Header	FF	11111111
<b>Vendor / Product EDID Version</b>	7	07	Header	00	00000000
	8	08	ID Manufacture Name LGD	30	00110000
	9	09	ID Manufacture Name	E4	11100100
	10	0A	ID Product Code 0590h	90	10010000
	11	0B	( Hex. LSB first )	05	00000101
	12	0C	ID Serial No. - Optional ("00h" If not used, Number Only and LSB First)	00	00000000
	13	0D	ID Serial No. - Optional ("00h" If not used, Number Only and LSB First)	00	00000000
	14	0E	ID Serial No. - Optional ("00h" If not used, Number Only and LSB First)	00	00000000
	15	0F	ID Serial No. - Optional ("00h" If not used, Number Only and LSB First)	00	00000000
	16	10	Week of Manufacture - Optional 00 weeks	00	00000000
<b>Display Parameters</b>	17	11	Year of Manufacture 2017 years	1B	00011011
	18	12	EDID structure version # = 1	01	00000001
	19	13	EDID revision # = 4	04	00000100
	20	14	Video input Definition = Input is a Digital Video signal Interface , Colo Bit Depth : 6 Bits per Primary Color , Digital Video Interface Standard Supported: DisplayPort is supported	95	10010101
	21	15	Horizontal Screen Size (Rounded cm) = 34 cm	22	00100010
<b>Panel Color Coordinates</b>	22	16	Vertical Screen Size (Rounded cm) = 19 cm	13	00010011
	23	17	Display Transfer Characteristic (Gamma) = (gamma*100)-100 = Example:(2.2*100)-100=120	78	01111000
	24	18	Feature Support [ Display Power Management(DPM) : Standby Mode is supported, Suspend Mode is not supported, Active Off = Very Low Power is supported ,Supported Color Encoding Formats : RGB 4:4:4 & YCrCb 4:4:4 ,Other Feature Support Flags : No_sRGB, Preferred Timing Mode, No_Display is continuous frequency (Multi-mode_Base EDID and Extension Block).]	EA	11101010
	25	19	Red/Green Low Bits (RxRy/GxCy)	A1	10100001
	26	1A	Blue/White Low Bits (BxBY/WxWy)	C5	11000101
	27	1B	Red X Rx = 0.580	94	10010100
	28	1C	Red Y Ry = 0.350	59	01011001
	29	1D	Green X Gx = 0.340	57	01010111
<b>Established Timing</b>	30	1E	Green Y Gy = 0.560	8F	10001111
	31	1F	Blue X Bx = 0.155	27	00100111
	32	20	Blue Y By = 0.125	20	00100000
	33	21	White X Wx = 0.313	50	01010000
	34	22	White Y Wy = 0.329	54	01010100
	35	23	Established timing 1 ( Optional_00h if not used)	00	00000000
	36	24	Established timing 2 ( Optional_00h if not used)	00	00000000
	37	25	Manufacturer's timings ( Optional_00h if not used)	00	00000000
	38	26	Standard timing ID1 ( Optional_01h if not used)	01	00000001
	39	27	Standard timing ID1 ( Optional_01h if not used)	01	00000001
	40	28	Standard timing ID2 ( Optional_01h if not used)	01	00000001
	41	29	Standard timing ID2 ( Optional_01h if not used)	01	00000001
	42	2A	Standard timing ID3 ( Optional_01h if not used)	01	00000001
	43	2B	Standard timing ID3 ( Optional_01h if not used)	01	00000001
	44	2C	Standard timing ID4 ( Optional_01h if not used)	01	00000001
<b>Standard Timing ID</b>	45	2D	Standard timing ID4 ( Optional_01h if not used)	01	00000001
	46	2E	Standard timing ID5 ( Optional_01h if not used)	01	00000001
	47	2F	Standard timing ID5 ( Optional_01h if not used)	01	00000001
	48	30	Standard timing ID6 ( Optional_01h if not used)	01	00000001
	49	31	Standard timing ID6 ( Optional_01h if not used)	01	00000001
	50	32	Standard timing ID7 ( Optional_01h if not used)	01	00000001
	51	33	Standard timing ID7 ( Optional_01h if not used)	01	00000001
	52	34	Standard timing ID8 ( Optional_01h if not used)	01	00000001
	53	35	Standard timing ID8 ( Optional_01h if not used)	01	00000001

**Product Specification**
**APPENDIX C. Enhanced Extended Display Identification Data (EEDID™) 2/3**

	Byte (Dec)	Byte (Hex)	Field Name and Comments	Value (Hex)	Value (Bin)
<b>Timing Descriptor #1</b>	54	36	Pixel Clock/10,000 (LSB) 138.7 MHz @ 60 Hz	2E	00101110
	55	37	Pixel Clock/10,000 (MSB)	36	00110110
	56	38	Horizontal Active (HA) (lower 8 bits) 1920 pixels	80	10000000
	57	39	Horizontal Blanking (HB) (lower 8 bits) 160 pixels	A0	10100000
	58	3A	Horizontal Active (HA) / Horizontal Blanking (HB) (upper 4:4bits)	70	01110000
	59	3B	Vertical Active (VA) 1080 lines	38	00111000
	60	3C	Vertical Blanking (VB) (DE Blanking typ.for DE only panels) 31 lines	1F	00011111
	61	3D	Vertical Active (VA) / Vertical Blanking (VB) (upper 4:4bits)	40	01000000
	62	3E	Horizontal Front Porch in pixels (HF) (lower 8 bits) 48 pixels	30	00110000
	63	3F	Horizontal Sync Pulse Width in pixels (HS) (lower 8 bits) 32 pixels	20	00100000
	64	40	Vertical Front Porch in lines (VF) : Vertical Sync Pulse Width in lines (VS) (lower 4 bits) 3 lines : 5 lines	35	00110101
	65	41	Horizontal Front Porch/ Sync Pulse Width/ Vertical Front Porch/ Sync Pulse Width (upper 2bits)	00	00000000
	66	42	Horizontal Video Image Size (mm) (lower 8 bits) 344 mm	58	01011000
	67	43	Vertical Video Image Size (mm) (lower 8 bits) 194 mm	C2	11000010
	68	44	Horizontal Image Size / Vertical Image Size (upper 4 bits)	10	00010000
	69	45	Horizontal Border = 0 (Zero for Notebook LCD)	00	00000000
	70	46	Vertical Border = 0 (Zero for Notebook LCD)	00	00000000
<b>Timing Descriptor #2</b>	71	47	Non-Interlace, Normal display, no stereo, Digital Separate [ Vsync_NEG, Hsync_POS (outside of V-sync) ]	1A	00011010
	72	48	Flag	00	00000000
	73	49	Flag	00	00000000
	74	4A	Flag	00	00000000
	75	4B	Data Type Tag (Descriptor Defined by manufacturer )	00	00000000
	76	4C	Flag	00	00000000
	77	4D	Descriptor Defined by manufacturer	00	00000000
	78	4E	Descriptor Defined by manufacturer	00	00000000
	79	4F	Descriptor Defined by manufacturer	00	00000000
	80	50	Descriptor Defined by manufacturer	00	00000000
	81	51	Descriptor Defined by manufacturer	00	00000000
	82	52	Descriptor Defined by manufacturer	00	00000000
	83	53	Descriptor Defined by manufacturer	00	00000000
	84	54	Descriptor Defined by manufacturer	00	00000000
	85	55	Descriptor Defined by manufacturer	00	00000000
	86	56	Descriptor Defined by manufacturer	00	00000000
	87	57	Descriptor Defined by manufacturer	00	00000000
	88	58	Descriptor Defined by manufacturer	00	00000000
<b>Timing Descriptor #3</b>	89	59	Descriptor Defined by manufacturer	00	00000000
	90	5A	Flag	00	00000000
	91	5B	Flag	00	00000000
	92	5C	Flag	00	00000000
	93	5D	Data Type Tag ( Alphanumeric Data String (ASCII String) )	FE	11111110
	94	5E	Flag	00	00000000
	95	5F	Alphanumeric Data String (ASCII String) L	4C	01001100
	96	60	Alphanumeric Data String (ASCII String) G	47	01000111
	97	61	Alphanumeric Data String (ASCII String)	20	00100000
	98	62	Alphanumeric Data String (ASCII String) D	44	01000100
	99	63	Alphanumeric Data String (ASCII String) i	69	01101001
	100	64	Alphanumeric Data String (ASCII String) s	73	01110011
	101	65	Alphanumeric Data String (ASCII String) p	70	01110000
	102	66	Alphanumeric Data String (ASCII String) l	6C	01101100
	103	67	Alphanumeric Data String (ASCII String) a	61	01100001
	104	68	Alphanumeric Data String (ASCII String) y	79	01111001
	105	69	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASC II code 0Ah,set remaining char = 20h)	0A	00001010
	106	6A	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASC II code 0Ah,set remaining char = 20h)	20	00100000
	107	6B	Manufacturer P/N(If<13 char--> 0Ah, then terminate with ASC II code 0Ah,set remaining char = 20h)	20	00100000

## Product Specification

**APPENDIX C. Enhanced Extended Display Identification Data (EEDID™) 3/3**

	Byte (Dec)	Byte (Hex)	Field Name and Comments	Value (Hex)	Value (Bin)
<b>Timing Descriptor #4</b>	108	<b>6C</b>	Flag	<b>00</b>	00000000
	109	<b>6D</b>	Flag	<b>00</b>	00000000
	110	<b>6E</b>	Flag	<b>00</b>	00000000
	111	<b>6F</b>	Data Type Tag ( Alphanumeric Data String (ASCII String) )	<b>FE</b>	11111110
	112	<b>70</b>	Flag	<b>00</b>	00000000
	113	<b>71</b>	Alphanumeric Data String (ASCII String) L	<b>4C</b>	01001100
	114	<b>72</b>	Alphanumeric Data String (ASCII String) P	<b>50</b>	01010000
	115	<b>73</b>	Alphanumeric Data String (ASCII String) 1	<b>31</b>	00110001
	116	<b>74</b>	Alphanumeric Data String (ASCII String) 5	<b>35</b>	00110101
	117	<b>75</b>	Alphanumeric Data String (ASCII String) 6	<b>36</b>	00110110
	118	<b>76</b>	Alphanumeric Data String (ASCII String) W	<b>57</b>	01010111
	119	<b>77</b>	Alphanumeric Data String (ASCII String) F	<b>46</b>	01000110
	120	<b>78</b>	Alphanumeric Data String (ASCII String) 6	<b>36</b>	00110110
	121	<b>79</b>	Alphanumeric Data String (ASCII String) -	<b>2D</b>	00101101
	122	<b>7A</b>	Alphanumeric Data String (ASCII String) S	<b>53</b>	01010011
	123	<b>7B</b>	Alphanumeric Data String (ASCII String) P	<b>50</b>	01010000
	124	<b>7C</b>	Alphanumeric Data String (ASCII String) K	<b>4B</b>	01001011
	125	<b>7D</b>	Alphanumeric Data String (ASCII String) 6	<b>36</b>	00110110
<b>Check</b>	126	<b>7E</b>	Extension flag (# of optional 128 panel ID extension block to follow, Typ = 0)	<b>00</b>	00000000
	127	<b>7F</b>	Check Sum (The 1-byte sum of all 128 bytes in this panel ID block shall = 0)	<b>5E</b>	01011110



Product Specification

APPENDIX D. LGD Proposal for Measurement Method

1	LCM Thickness	
Point		
Measure Tool	Micro Meter	
Guide	<ul style="list-style-type: none"> <li>✓ Measure the thickness between Polarizer surface and M-Chassis on the rear of LCM</li> <li>✓ Subtract Pol. protect film thickness from LCM thickness</li> </ul>	
2	Dimension Between Upper Polarizer to Bottom surface of Bracket	
Point	<p>[ Height gauge with load cell]</p>	<p>[ Height gauge with weight 400g]</p>
Measure Tool	Height Gauge ( With Force 400gf)	
Guide	<ul style="list-style-type: none"> <li>✓ Measure the thickness between Polarizer surface and Bracket top surface.</li> <li>✓ Measure the thickness include force(400gf) on the Panel surface.</li> <li>✓ The CAS Spec. : Height from Pol. to Bracket top surface + Material Thickness</li> </ul>	





## Product Specification

**APPENDIX D. LGD Proposal for Measurement Method**

3	System Bracket Angle Management
Point	
Measure Tool	Height Gauge 
Guide	<ul style="list-style-type: none"> <li>✓ Measure the Height point “A” and “B” at all system bracket in LCM</li> <li>✓ The CAS Spec. : <math>87^{\circ} \pm 2^{\circ} \rightarrow 0.09 &lt; A-B &lt; 0.43</math></li> <li>✓ “A-B” spec. could be changed, if bracket dimension is not over than 5mm .</li> </ul>

Product Specification

APPENDIX D. LGD Proposal for Measurement Method

4	Height of PCB Area	
Measure Tool & Point	 	
Measure Tool & Point	 	
Guide	<ul style="list-style-type: none"> <li>✓ Measure the height between upper Polarizer surface and C/Shield top surface.</li> <li>✓ Measure the height include force(50gf) on the C/Shield surface at FPC/COF Center.</li> <li>✓ The CAS Spec. : All components except cover shield of LCM is under upper POL. Upper polarizer higher than source cover shield pressed down 50g.</li> </ul>	
Measure condition	Put the LCM on flat ground w/o interference on PCB rear side	

