



Version	5
Total pages	21
Date	2006.11.21

Product Specification

7" color TFT-LCD module

MODEL NAME: C070FW03 V0

(◆) Preliminary Specification

(.....) Final Specification

Note: The content of this specification is subject to change.

© 2004 AU Optronics
All Rights Reserved,
Do Not Copy.

[illegible]

Contents:

A. Physical specification.....	P3
B. Electrical specifications.....	P4
1. Pin assignment.....	P4
a. TFT-LCD panel driving section.....	P4
b. Backlight driving section.....	P5
2. Absolute maximum ratings.....	P5
3. Electrical characteristics.....	P6
a. Typical operating conditions.....	P6
b. Current consumption.....	P6
c. Backlight driving conditions.....	P6
4. AC Timing.....	P8
a. Timing conditions.....	P8
b. Timing diagram.....	P8
5. Power sequence.....	P9
C. Optical specifications.....	P10
D. Reliability test items.....	P12
E. Packing form.....	P13

Appendix:

Fig.1 Outline dimension of TFT-LCD module.	P14
Fig.2 Sampling clock timing.	P15
Fig.3 Horizontal display timing range.	P16
Fig.4-(a) Horizontal timing.	P17
Fig.4- (b) Detail horizontal timing.	P18
Fig.5 Vertical shift clock timing.	P19
Fig.6- (a) Vertical timing (From up to down).....	P20
Fig.6-(b) Vertical timing (From down to up)	P21

A. Physical specifications

NO.	Item	Specification	Remark
1	Display resolution(dot)	480RGB(W)x234(H)	
2	Active area(mm)	156.24(W)x82.37(H)	
3	Screen size(inch)	6.95(Diagonal)	
4	Dot pitch(mm)	0.1085(W)x0.352(H)	
5	Color configuration	R. G. B. stripe	
6	NTSC ratio	72%	
7	Overall dimension(mm)	167(W)x93.0(H)x6.25(D)	Note 1
8	Weight(g)	TBD	
9	Surface treatment	AG(25%) with SWV film	
10	Backlight unit	L type CCFL	
11	Gray scale inversion direction	6 o'clock	

Note 1: Refer to Fig. 1

B. Electrical specifications

1.Pin assignment

a. TFT-LCD panel driving section

Pin no	Symbol	I/O	Description	Remark
1	GND	-	Ground for logic circuit	
2	NC	-		
3	V _{GL}	I	Negative power for scan driver	
4	STVD	I/O	Vertical start pulse	Note 1
5	UDC	I	UP/DOWN scan control input	Note 1,2
6	CKV	I	Shift clock input for scan driver	
7	OEV	I	Output enable input for scan driver	
8	NC	-		
9	NC	-		
10	STVU	I/O	Vertical start pulse	Note 1
11	V _{CC}	I	Supply voltage of logic control circuit for scan driver	Note 4
12	DV _{CC}	I	Supply voltage of logic control circuit for data driver	Note 4
13	V _{GH}	I	Positive power for scan driver	
14	NC	-		
15	VCOM	I	Common electrode driving signal	
16	STHR	I/O	Start pulse for horizontal scan line	Note 1
17	AV _{DD}	I	Supply voltage for analog circuit	
18	VR	I	Alternated video signal input(Red)	
19	VG	I	Alternated video signal input(Green)	
20	VB	I	Alternated video signal input(Blue)	
21	AGND	-	Ground for analog circuit	
22	CPH1	I	Sampling and shifting clock pulse for data driver	
23	CPH2	I	Sampling and shifting clock pulse for data driver	
24	CPH3	I	Sampling and shifting clock pulse for data driver	
25	GND	-	Ground for logic circuit	
26	MOD	I	Sequential sampling and simultaneous sampling setting	Note 3
27	LRC	I	LEFT/RIGHT scan control input	Note 1,2
28	OEH	I	Output enable input for data driver	
29	STHL	I/O	Start pulse for horizontal scan line	
30	GND	-	Ground for logic circuit	


Note 1: Selection of scanning mode (please refer to the following table)

Setting of scan control input		IN/OUT state for start pulse				Scanning direction
UDC	LRC	STVD	STVU	STHR	STHL	
GND	V _{CC}	OUT	IN	OUT	IN	From up to down, and from left to right.
V _{CC}	GND	IN	OUT	IN	OUT	From down to up, and from right to left.
GND	GND	OUT	IN	IN	OUT	From up to down, and from right to left.
V _{CC}	V _{CC}	IN	OUT	OUT	IN	From down to up, and from left to right.

IN: Input; OUT: Output.

Note 2: Definition of scanning direction.

Refer to figure as below:



Note 3: MOD = H: Simultaneous sampling.

MOD = L: Sequential sampling.

Please set CPH2 and CPH3 to GND when MOD = H.

Note 4: Electrical characteristics of V_{CC} and DV_{CC} are the same.

b. Backlight driving section (Refer to Figure 1)

No.	Symbol	I/O	Description	Remark
1	HI	I	Power supply for backlight unit (High voltage)	--
2	GND	-	Ground for backlight unit	--

2. Absolute maximum ratings

Item	Symbol	Condition	Min.	Max.	Unit	Remark
Power voltage	V _{CC}	GND=0	-0.3	7	V	
	AV _{DD}	AGND=0	-0.3	7	V	
	V _{GH}	GND=0	-0.3	18	V	
	V _{GL}		-15	0.3	V	
	V _{GH} - V _{GL}		-	33	V	
Input signal voltage	V _i		-0.3	AV _{DD} +0.3	V	Note 1
	V _i		-0.3	V _{CC} +0.3	V	Note 2
	VCOM		-2.9	7.5	V	
CCFL	V _L			3000	Vrms	
	I _L			10	mA	

Note 1: VR, VG, VB.

Note 2: STHL, STHR, OEH, LRC, CPH1~CPH3, STVD, STVU, OEV, CKV, UDC.

3. Electrical characteristics

a. Typical operating conditions (GND=AGND=0V, Note 3)

Item	Symbol	Min.	Typ.	Max.	Unit	Remark
Power supply	V_{CC}	3	5	5.5	V	
	AV_{DD}	4.5	5	5.5	V	
	V_{GH}	14.3	15	15.7	V	
	V_{GL}	-10.5	-10	-9.5	V	
Video signal amplitude (VR,VG,VB)	V_{iA}	0.4	-	$AV_{DD}-0.4$	V	Note 1
	V_{iAC}	-	3	-	V	AC component
	V_{iDC}	-	$AV_{DD}/2$	-	V	DC component
VCOM	V_{CAC}	3.5	5.6	6.5	Vp-p	AC component
	V_{CDC}	1.4	1.7	2.0	V	DC component
Input signal voltage	H Level	V_{IH}	0.8 V_{CC}	-	V_{CC}	Note 2
	L Level	V_{IL}	0	-	0.2 V_{CC}	

Note 1: Refer to Fig.4- (a).

Note 2: STHL, STHR, OEH, LRC, CPH1~CPH3, STVD, STVU, OEV, CKV, UDC.

Note 3: Be sure to apply GND, V_{CC} and V_{GL} to the LCD first, and then apply V_{GH} .

b. Current consumption (GND=AGND=0V)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Current for driver	I_{GH}	$V_{GH}=15V$	-	0.20	0.5	mA	
	I_{GL}	$V_{GL}=-10V$	-	0.80	1.5	mA	
	I_{CC}	$DV_{CC}=5V$	-	3.0	6.0	mA	Note 1
	I_{DD}	$AV_{DD}=5V$	-	17.0	30	mA	

Note 1: I_{CC} is current consumption of DV_{CC} plus V_{CC} .


c. Backlight driving conditions (Self-heating type)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Remark
Lamp voltage	V_L	-	560	660	Vrms	
Lamp current	I_L	-	6	7	mAmps	
Frequency	F_L	40	-	80	kHz	Note 2
Lamp starting voltage	V_S	-	850	1060	Vrms	$T_a = 25^{\circ}C$, Note 4
		-	1100	1380	Vrms	$T_a = 0^{\circ}C$, Note 4
		-	1350	1750	Vrms	$T_a = -30^{\circ}C$, Note 4
Discharge Stabilization Time	T_s			3	min	
Discharge Time lag	T_d			1	sec	Note 5
Lamp life time		10,000	-	-	Hr	Note 6

Note 1: Panel surface temperature should be kept less than content of "2. Absolute maximum ratings"

Note 2: The lamp frequency should be selected as different as possible from display horizontal synchronous signal to avoid interference. (Reference value)

Note 3: Values of “Lamp Voltage”, “Lamp power consumption” and “Starting voltage” are defined on condition of the LCD module derived by NF[AS-114B] circuit which measured from connectors of product(as below figure). However this isn't the values that we can assure stability of starting lamp on condition that the module is installed in your set.



Note 4: The “MAX” of “Starting voltage” means the minimum voltage to light normally in the LCD module.

Note 5: The time needed to start discharge when the over 1500Vrms voltage is continuously applied to both end of the lamp. Before testing, the lamp is left in the dark room(ambient temperature: 25+/- 2°C, ambient luminance: less than 0.1lux) for 24Hrs after lighted for 1minute at lated lamp current.

Note 6:The” Lamp life time” is defined as the module brightness decrease to 50% original brightness at Ta=25°C , IL=6.5mA.

5. AC Timing

a. Timing conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit.	Remark
Rising time	t_r	-	-	10	ns	Note 1
Falling time	t_f	-	-	10	ns	Note 1
High and low level pulse width	t_{CPH}	99	103	107	ns	CPH1~CPH3
		83.3			ns	Note3
CPH pulse duty	t_{CWH}	40	50	60	%	CPH1~CPH3
CPH pulse delay	t_{C12} t_{C23} t_{C31}	30	$t_{CPH}/3$	$t_{CPH}/2$	ns	CPH1~CPH3
STH setup time	t_{SUH}	20	-	-	ns	STHR,STHL
STH hold time	t_{HDH}	20	-	-	Ns	STHR,STHL
STH pulse width	t_{STH}	-	1	-	t_{CPH}	STHR,STHL
STH period	t_H	61.5	63.5	65.5	μs	STHR,STHL
OEH pulse width	t_{OEH}	-	1.22	-	μs	OEH
Sample and hold disable time	t_{DIS1}	-	8.28	-	μs	
OEV pulse width	t_{OEV}	-	5.40	-	μs	OEV
CKV pulse width	t_{CKV}	-	4.18	-	μs	CKV
Clean enable time	t_{DIS2}	-	3.74	-	μs	
Horizontal display start	t_{SH}	-	0	-	$T_{CPH}/3$	
Horizontal display timing range	t_{DH}	-	1440	-	$T_{CPH}/3$	
STV setup time	t_{SUV}	400	-	-	ns	STVU, STVD
STV hold time	t_{HDV}	400	-	-	ns	STVU, STVD
STV pulse width	t_{STV}	-	-	1	t_H	STVU, STVD
Horizontal lines per field	t_V	256	262	268	t_H	Note 2
Vertical display start	t_{SV}		3	-	t_H	
Vertical display timing range	t_{DV}		234	-	t_H	
VCOM rising time	t_{rCOM}		-	5	μs	
VCOM falling time	t_{fCOM}		-	5	μs	
VCOM delay time	t_{DCOM}		-	3	μs	
RGB delay time	t_{DRGB}		-	1	μs	

Note 1: For all of the logic signals.

Note 2: Please don't use odd horizontal lines to drive LCD panel for both odd and even field simultaneously.


Note 3: For Partial mode (4:3, side-black)

b. Timing diagram

Please refer to the attached drawing, from Fig.2 to Fig.6.

5. Power Sequence (Suggestion)

Sequence for power on/off and Signal on/off



$T1 \leq 15\text{ms}$ (From 10%*VCC to 90%*VCC , when VCC is Low to High) ;

$T2 \leq 10\text{ms}$ (From 90%*VCC to 10%*VGH , when VCC is Low to High) ;

$T3 \leq 10\text{ms}$ (From 90%*VGH to Video signal , when VGH is Low to High) ;

$T4 \leq 10\text{ms}$ (From Video signal to 90%*VGH , when VGH is High to Low) ;

$T5 \leq 20\text{ms}$ (From 90%*VCC to 10%*VCC , when VCC is High to Low) ;

$T6 \leq 10\text{ms}$ (From 10%*VGH to 90%*VCC , when VCC is Low to High) ;

$T7 \geq 0.4\text{s}$ (From 10%*VCC is H→L to 10%*VCC is L→H) °

C. Optical specification (Note1, Note2)


Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Response time	Rise	Tr	$\theta = 0^\circ$	-	6	10	ms	Note 3,5
	Fall	Tf		-	10	20	ms	
Contrast ratio		CR	At optimized Viewing angle	200	300	-		Note 4, 5
Viewing angle	Top	$CR \geq 10$		30	45	-	deg.	Note 5, 6
	Bottom			50	60	-		
	Left			50	60	-		
	Right			50	60	-		
Viewing angle	Top	$CR \geq 5$		40	50	-	deg.	Note 5, 6
	Bottom			60	70	-		
	Left			60	70	-		
	Right			60	70	-		
Brightness			$I_L = 6.5 \text{ mA}, 25^\circ \text{C}$	400	475		cd/m^2	
White chromaticity		X	$\theta = 0^\circ$	0.26	0.31	0.36		Note 7
		Y	$\theta = 0^\circ$	0.28	0.33	0.38		

Note 1 : Ambient temperature =25℃, and lamp current $I_L = 6.5 \text{ mA}$. To be measured in the dark room. DC/AC inverter driving frequency: 70 kHz.

Note 2 :To be measured on the center area of panel with a viewing cone of 1°by Topcon luminance meter BM-5, after 15 minutes operation.

Note 3. Definition of response time:

The output signals of photo detector are measured when the input signals are changed from “black” to “white”(falling time) and from “white” to “black”(rising time), respectively. The response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to figure as below.



Note 4. Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Photo detector output when LCD is at "White" state}}{\text{Photo detector output when LCD is at "Black" state}}$$

Note 5. White $V_i = V_{i50} + 1.5V$

Black $V_i = V_{i50} \pm 2.0V$


“ \pm ” means that the analog input signal swings in phase with V_{COM} signal.

“ \mp ” means that the analog input signal swings out of phase with V_{COM} signal.

V_{i50} : The analog input voltage when transmission is 50%

The 100% transmission is defined as the transmission of LCD panel when all the input terminals of module are electrically opened.

Note 6. Definition of viewing angle, Refer to figure as below.



Note 7. Measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.

D. Reliability test items(Note 2):

No.	Test items	Conditions	Remark
1	High temperature storage	Ta= 95℃ 240Hrs	
2	Low temperature storage	Ta= -40℃ 240Hrs	
3	High temperature operation	Tp= 85℃ 240Hrs	
4	Low temperature operation	Ta= -30℃ 240Hrs	
5	High temperature and high humidity	Tp= 60℃, 90% RH 240Hrs	Operation
6	Heat shock	-30℃~85℃/200 cycles 1Hrs/cycle	Non-operation
7	Electrostatic discharge	±200V,200pF(0Ω), once for each terminal	Non-operation
8	Vibration	Frequency range : 8~33.3Hz Stoke : 1.3mm Sweep : 2.9G, 33.3 ~ 400Hz Cycle : 15 minutes 2 hours for each direction of X,Z 4 hours for Y direction	JIS D1601, A-10 condition A Note4
9	Mechanical shock	100G, 6ms, ±X,±Y,±Z 3 times for each direction	JIS C7021, A-7 Condition C
10	Vibration (with carton)	Random vibration: 0.015G ² /Hz from 5~200Hz -6dB/octave from 200~500Hz	IEC 68-34
11	Drop (with carton)	Height: 60cm 1 corner, 3 edges, 6 surfaces	JIS Z0202


Note1: Ta: Ambient temperature.

Note2: Tp: Panel Surface Temperature

Note3: In the standard conditions, there is not display function NG issue occurred. All the cosmetic specification is judged before the reliability stress.

Note 4: Cycle time for vibration is 15 minutes.

E. Packing form






Fig.1- Outline dimension of TFT-LCD module




Fig.2 Sampling clock timing




Fig.3 Horizontal display timing range





Fig.4-(a) Horizontal timing



Note: The falling edge of OEV should be synchronized with the falling edge of OEH

Fig.4-(b) Detail horizontal timing




Fig.5 Vertical shift clock timing




Fig.6-(a) Vertical timing (From up to down)




Fig.6-(b) Horizontal timing (From down to up)