Product Specification

CUSTOMER	Fujitsu
DATE OF ISSUE	2013.05.21

MODEL NO.	LTN156AT32
EXTENSION CODE	-701

Approved by	Y.E.PARK 13/05/21
Prepared by	W.W.LEE 13/05/21
IT Development Team **Samsung Display Co., Ltd**	

Table of Contents

SAMSUNG DISPLAY

REVISION HISTORY

Date.	Rev. No.	Page	Revision Description
13/05/21	V0.0		Initial Release

SAMSUNG DISPLAY

1. GENERAL DESCRIPTION

DESCRIPTION

The LTN156AT32-701 uses a color active matrix TFT (Thin Film Transistor) liquid crystal display (LCD) that uses amorphous silicon TFTs as switching components. This model is composed of a TFT LCD panel, a driver circuit, and a backlight unit. This 15.6" model has a resolution of 1366 x 768 pixels and can display up to 262,144 colors.

FEATURES

High contrast ratio
HD (1366 x 768 pixels) resolution
Low power consumption
Fast Response
LED back light with an embedded LED driver
DE (Data enable) only mode
3.3V LVDS Interface
Onboard EDID chip

APPLICATIONS

Notebook PC
If the intent to use this product is for other purpose, please contact Samsung Display.

GENERAL INFORMATION

Item	Specification	Unit	Note
Display area	344.232 (H) x 193.536 (V) (15.6"diagonal)	mm	
Driver Element	a-Si TFT active matrix		
Display colors	262,144 (6bit)		
Number of pixel	1366 *768(HD)	Pixel	16:9
Pixel Arrangement	RGB vertical stripe		
Pixel pitch	0.252 (H) x 0.252 (V) (TYP.)	mm	
Display Mode	Normally white, TN mode		
Thickness of glass	0.5	mm	
Surface treatment	Haze 25%, Hardness 3H		Anti-Glare
Environmental safe regulation	Pb Free, Halogen Free		
Power Consumption	Total 4.26W(Typ) @Logic 0.8W(Typ) BLU 3.46W (Typ) Total 5.0W(Max)		Mosaic PTN

MECHANICAL INFORMATION

Item		Min.	Typ.	Max.	Unit	Note
Module Size	Horizontal (H)	358.8	359.3	359.8	mm	
	Vertical (V)	209.0	209.5	210.0	mm	
	Depth (D)	-	5.0	5.5	mm	(1)
Weight		-	440	450	g	

NOTE (1) Measuring method for thickness
　　　　　Force to be applied for measurement: The 200gf when using the height gauge.

2. ABSOLUTE MAXIMUM RATINGS

2.1 ENVIRONMENTAL ABSOLUTE RATINGS

Item	Symbol	Min.	Max.	Unit	Note
Storage temperate	TSTG	-20	60	°C	(1)
Operating temperature (Temperature of glass surface)	TOPR	0	50	°C	(1)
Shock (non-operating)	Snop	-	240	G	(2), (4)
Vibration (non-operating)	Vnop	-	2.41	G	(3), (4)

Note (1) The range of temperature and relative humidity is shown in the graph below 90% RH Max. .

   (39℃ ≥ Ta) If the temperature is higher than 40 ℃, the maximum temperature of wet–bulb shall be less than 39℃. No condensation

(2) Vibrate ±X, ±Y, and ± Z axis in the shape of the half sine wave one time for 2ms.

(3) Vibrate the X, Y, and Z randomly within a 5 - 500 Hz range for 30min.

(4) When testing a vibration and a shock, the fixture, which holds the module to be tested, shall be hard and rigid in order for the module not to be twisted or bent by the fixture.

2.2 ELECTRICAL ABSOLUTE RATINGS

(1) TFT LCD MODULE

$V_{LCD\_VCC} = 3.3V$, $V_{SS} = GND = 0V$

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	V_{LCD_VCC}	$V_{SS} - 0.3$	4.0	V	(1), (2)
LVDS Input Voltage	V_{LVDS}	$V_{SS} - 0.3$	2.0		

Note (1) Within Ta (25 ± 2 °C)

    (2) Permanent damage to the device may occur if exceed maximum values.

(2) BACKLIGHT UNIT

$VSS = GND = 0V$

Item	Symbol	Min.	Max.	Unit	Note
BLU Supply Voltage	V_{BL_PWR}	$V_{SS} - 0.3$	26.5	V	(1), (2)
BLU Supply Current	I_{BL_PWR}	-	0.96	A	(1), (2) Vin=12V Duty 100%

Note (1) Within Ta (25 ± 2 °C)

    (2) Permanent damage to the device may occur if exceed maximum values

2.3 THE OTHERS

(1) STATIC ELECTRICITY PRESSURE RESISTANCE

Item	Test Conditions	Remark
CONTACT DISCHARGE	150pF, 330Ω, $\pm$ 8kV, 200points, 1 time/point	Operating
AIR DISCHARGE	150pF, 330Ω, $\pm$ 15kV, 200points, 1 time/point	Operating

3. OPTICAL CHARACTERISTICS

The following items are measured under the stable conditions.* The optical characteristics should be measured in the dark room or the equivalent environment by the methods shown in the Note (5).
Measuring equipment: TOPCON SR-3

Ta = 25 ± 2 °C, V_{LCD_VCC}=3.3V, f_V = 60Hz, f_{DCLK} = 72.33MHz, I_F = 100% duty

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast Ratio		CR	Normal Viewing Angle $\phi = 0$ $\theta = 0$	300	500	-	-	(1),(2),(5)
Response time (Rising + Falling)		T_{RT}		-	16	25	msec	(1),(3)
Average Luminance of White (5 Points)		$Y_{L,AVE}$		190	220	-	cd/m^2	IF=100% Duty (1),(4)
Cross Modulation		DSHA		-	1.0	2.0	%	(7)
Color Chromaticity (CIE)	Red	R_X		-0.03	0.619	+0.03		(1),(5)
		R_Y		0.302	0.350	0.362		
	Green	G_X		-0.03	0.340	+0.03		
		G_Y			0.600			
	Blue	B_X			0.154			
		B_Y			0.095			
	White	W_X			0.313			
		W_Y			0.329			
Viewing Angle	Hor.	θ_L	CR $\geq$ 10 At center	40	45	-	Degrees	(1),(5)
		θ_H		40	45	-		
	Ver.	ϕ_H		10	15	-		
		ϕ_L		30	35	-		
Color Gamut		CG		55	60	-	%	
White variation (13P)		δ_L		-	1.44	1.6		(6)

Note (1) The definition of viewing angle: The range of viewing angle (10 ≤ C/R)


Note (2) The definition of contrast ratio (CR): The ratio of max. gray and min gray at 5 points
(4, 5, 7, 9, and 10)

$$CR = \frac{CR(4) + CR(5) + CR(7) + CR(9) + CR(10)}{5}$$

Points = ④ , ⑤ , ⑦ , ⑨ , ⑩ at the figure of Note(6).

Note (3) The definition of Response time: Subtotal of the time, during which the transmission changes from
10% to 90% when the TFT turns on and off.

Note (4) The definition of average luminance of white: Measure the luminance of white at 5 points.

$$Y_{L.AVE} = \frac{Y_{L4} + Y_{L5} + Y_{L7} + Y_{L9} + Y_{L10}}{5}$$


○ : test point

Note (5) Measure the panel, which is left for 30 min. at the normal temp. after leaving it for 30 min with turning the back light on at the rating. The measurement should be executed under the condition including the ambient temp., 25℃±2℃, the dark room, windless (removed the direct wind), and no vibration.

Photo-detector
(TOPCON SR-3)

Field = 2°

50 cm

TFT-LCD module

LCD panel

Center of the screen

[Optical characteristics measurement setup]

Note (6) The definition of white variation at 13 points (δ L)

$$\delta L = \frac{\text{Maximum luminance of 13 points}}{\text{Minimum luminance of 13 points}}$$

10mm   (25%)   (50%)   (75%)   10mm

10mm

⑬   ⑫   ⑪

⑩   ⑨   (25%)

⑧   ⑦   ⑥   (50%)   ◯ : test point

⑤   ④   (75%)

③   ②   ①
10mm

Note (7) The definition of crosstalk (Cross modulation)

: The phenomenon, which the contrast ratio is decreased by the interference of signal between pixels

Crosstalk Calculation Method

$$\text{Crosstalk Modulation Ratio}(D_{SHA}) = \frac{|\ Y_A\ -\ Y_B\ |}{Y_A} \times 100\ (\%)$$

Where

$Y_A,\ Y_B$ = Measured under the 2° viewing angle (Measured area: ψ12 ㎜)

The rectangle area, which excludes the black-colored rectangle includes the range, which is from 1 gray to 63 gray.

1) The method of measurement for horizontal-crosstalk

2) The method of measurement for vertical-crosstalk

4. BLOCK DIAGRAM

4.1 TFT LCD MODULE

LTN156AT32-701 Circuit Block Diagram

4.2 THE STRUCTURE OF LED PLACEMENT

(1 channels x 4ea = 4ea)

SAMSUNG DISPLAY

5. ELECTRICAL CHARACTERISTICS

5.1 TFT LCD MODULE

Ta = 25 ± 2 °C

Item		Symbol	Min.	Typ.	Max.	Unit	Note
Power Supply Voltage		V_{LCD_VCC}	3.0	3.3	3.6	V	
T-CON TTL Input Voltage	High	V_{IH}	0.7 V_{LCD_VCC}	-	-	V	(1)
	Low	V_{IL}	-	-	0.3 V_{LCD_VCC}	V	
Vsync	60Hz	f_V	-	60	-	Hz	
	50Hz	f_V	-	50	-	Hz	(3)
	40Hz	f_V	-	40	-	Hz	
Hsync	60Hz	f_H	46.50	47.40	48.60	kHz	
Main Frequency	60Hz	f_{DCLK}	67.24	72.33	83.88	MHz	
	50Hz	f_{DCLK}	-	60.28	-	MHz	(3)
	40Hz	f_{DCLK}	-	48.22	-	MHz	
Rush Current		I_{RUSH}	-	-	1.5	A	(5)
Input Current	White	I_{LCD_VCC}	-	242	303	mA	(2), (4)
	Mosaic	I_{LCD_VCC}	-	242	303	mA	
	Black	I_{LCD_VCC}	-	242	303	mA	
	V.Stripe	I_{LCD_VCC}	-	400	450	mA	
	Red	I_{LCD_VCC}	-	400	450	mA	(2), (4)
	Green	I_{LCD_VCC}	-	400	450	mA	
	Blue	I_{LCD_VCC}	-	400	450	mA	
	1Dot	I_{LCD_VCC}	-	400	450	mA	(2), (4)
Logic Input Power Consumption		P_{LCD_VCC}	-	0.8	1.0	W	(4)*(b)
EDID Input Voltage		V_{EDID}	3.0	3.3	3.6	V	
EDID Input Current		I_{EDID}	-	-	5	mA	
Skew		PS	-400	-	400	ps	(2)

Note (1) The data pins for display and signal pins for timing should be connected. (GND= 0V)

(2) f_V = 60Hz, f_{DCLK} = 72.33MHZ, V_{LCD_VCC} = 3.3V, DC Current.

(3) In the case of 40Hz & 50Hz for sDRRS, FOS,

Flicker & Brightness are not guaranteed, because their level might be different from 60Hz operation.

Note (4) The dissipation pattern for power

a) White Pattern

VIEW AREA

b) Mosaic Pattern

c) Black Pattern

d) Sub Vertical stripe pattern

e) Sub 1dot pattern

f) Red Pattern

g) Green Pattern

h) Blue Pattern

Note (5) The condition for measurement for rush current

3.3V

M1
2SK1059

V_{LCD_VCC}
(LCD INPUT)

FUSE

R1
47K

C1
1uF

CONTROL SIGNAL
(HIGH to LOW)

R2
1K

M2
2SK1399

12V

R3
47K

C2
10000pF

C3
1uF

V_{DD} rising time is 470us

3.3V

$0.9V_{DD}$

$0.1V_{DD}$

GND

470us

5.2 BACK LIGHT UNIT

Ta = 25 ± 2 °C

Item	Symbol	Min.	Typ.	Max.	Unit	Note
LED Forward Current	IF	-	115	-	mA	
LED Forward Voltage	VF	6.1	6.4	6.7	V	IF = 120mA
LED Array Voltage	VP	-	25.6	-	V	
LED Power Consumption	P	-	3.46	4.0	W	
LED Life time	Hr	15,000	-	-	Hours	(1)
LED Counts	Q	-	4	-	EA	

Note (1) The life time (Hr) of LEDs can be defined as the time during which it continues to operate under the condition, which the Ta is 25 ± 2 °C and IF= 115.0 mArms until the one of the following events occurs when the brightness becomes 50% or lower than the original.

5.3 LED DRIVER

The manufacturer of LED driver: Richtek RT8510   Ta= 25 ± 2 °C

Item		Symbol	Min.	Typ.	Max.	Unit	Note
Input Voltage		V_{BL_PWR}	7	12	21	V	
Input Current		I_{BL_PWR}	-	289	333	mA	Vin=12V Duty 100%
PWM duty Ratio		$D_{BL\_PWM\_DIM}$	1	-	100	%	(1)
External PWM Frequency		$F_{BL\_PWM\_DIM}$	0.2	1	2	kHz	APS ON
			0.12	1	2	kHz	APS OFF
PWM Resolution		$R_{BL\_PWM\_DIM}$	0.8	-	-	%	APS ON
			0.3			%	APS OFF
In-Rush Current		$I_{RUSH\_BL\_PWR}$	-	-	1.5	A	(2)
EN Control Level	High	V_{BL_ENABLE}	2.0	-	5.0	V	
	Low		0.0	-	0.8	V	
PWM Control Level	High	$V_{BL\_PWM\_DIM}$	2.0	-	5.0	V	
	Low		0.0	-	0.8	V	
VBL_PWR @ LED Driver On		V_{BL_PWR}	7	-	21	V	
VBL_PWR @ LED Driver Off		V_{BL_PWR}	0	-	2	V	
Operating frequency		FO	0.8	1.0	1.2	kHz	
Efficiency		η	-	85	-	%	

Note (1) Rush current measurement condition

The V_{BL_PWR} rising time is 470us.

5.4 LVDS INTERFACE

5.4.1 LVDS DC Specifications

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Conditions
Differential input high threshold voltage	V_{TH}	-	-	+200	mV	V_{CM} = 1.2V
Differential input low threshold voltage	V_{TL}	-200	-	-	mV	
Differential input voltage	$|V_{ID}|$	200	400	600	mV	
Common mode voltage	V_{CM}	0.4	1.2	1.8	V	$|V_{ID}|$= 200mV

5.4.2 LVDS AC Specifications

Characteristics		Symbol	Min.	Typ.	Max.	Unit	Remarks
ROUTCLK frequency		f_{RCP}	67.24	72.33	83.88	MHz	
LVDS RX Skew (Strobe) Right Margin	85MHz	T_{RSRM}	-	-	400	ps	
	50MHz		-	-	700	ps	
LVDS RX Skew (Strobe) Left Margin	85MHz	T_{RSLM}	-400	-	-	ps	
	50MHz		-700	-	-	ps	

< The definition of LVDS DC characteristics >

< The definition of LVDS Receiver Skew (Strobe) Margin >

SAMSUNG DISPLAY

5.4.3 LVDS SSC Specification

Characteristics	Symbol	Min.	Typ.	Max.	Unit	Remarks
Modulation Rate	F_{mr}	-3	0	+3	%	
Modulation Frequency	F_{mf}	30	-	300	kHz	@ MAINCLK = 72.33MHz

< Definition of SSC (Spread Spectrum Clock) >

5.4.4 Timing diagrams of LVDS transmission

5.5 INTERFACE TIMING

5.5.1 TIMING PARAMETERS

Signal	Item	Symbol	Min.	Typ.	Max.	Unit	Note
Frame Frequency	Cycle	T_V	775	790	810	Lines	
Vertical active in the display term	Display Period	T_{VD}	-	768	-	Lines	
Scanning time in one line	Cycle	T_H	1446	1526	1726	Clocks	
Horizontal active in the display term	Display Period	T_{HD}	-	1366	-	Clocks	

5.5.2 TIMING DIAGRAMS OF INTERFACE SIGNAL

5.6 INPUT COLOR DATA MAPPING

| Color	Display	Red						Green						Blue						Gray Scale Level
		R0	R1	R2	R3	R4	R5	G0	G1	G2	G3	G4	G5	B0	B1	B2	B3	45	B5	
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	-
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	-
	Cyan	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	-
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	-
	Magenta	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1	-
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	-
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
Gray Scale Of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0
	Dark	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1
	↑	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	R3~R60
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	↓	1	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	R61
	Light	0	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	R62
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	R63
Gray Scale Of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0
	Dark	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	G1
	↑	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	G2
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	G3~G60
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	↓	0	0	0	0	0	0	1	0	1	1	1	1	0	0	0	0	0	0	G61
	Light	0	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0	G62
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	G63
Gray Scale Of Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0
	Dark	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	B1
	↑	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	B2
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	B3~B60
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	↓	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	B61
	Light	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	B62
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	B63

Note (1) Definition of gray: Rn: Red gray, Gn: Green gray, Bn: Blue gray (n=gray level)
Note (2) Input signal: 0 =Low level voltage, 1=High level voltage

5.7 POWER ON/OFF SEQUENCE

To prevent the product from being latched up or the DC in the LCD module from starting an operation, the order to turn the power on and off should be changed to the order as shown in the diagram below.

Timing (ms)	Remarks
$0.5 < T_1 \leq 10$	V_{LCD_VCC} rising time from 10% to 90%
$0 < T_2 \leq 50$	Interval from V_{LCD_VCC} to valid data at power ON
$0 < T_3 \leq 50$	Interval from valid data OFF to V_{LCD_VCC} OFF at power Off
$150 \leq T_4$	V_{LCD_VCC} OFF time for Windows restart
$200 \leq T_5$	Interval from valid data to B/L enable at power ON
$0 < T_6$	Interval from valid data off to B/L disable at power Off
$0 < T_7 \leq 10$	V_{LCD_VCC} falling time from 90% to 10%
$10 < T_8$	Interval from valid data on to LED driver Vin rising time 10%
$10 < T_9$	Interval from LED driver Vin falling time 10% to valid data Off
$0.5 < T_{10} \leq 10$	LED V_{in} rising time from 10% to 90%
$0.5 < T_{11} \leq 10$	LED V_{in} falling time from 90% to 10%
$0 < T_{12}$	Interval from LED driver Vin rising time 90% to PWM ON
$0 < T_{13}$	Interval from PWM Off to LED driver Vin falling time 90%
$0 \leq T_{14}$	Interval from PWM ON to B/L Enable ON
$0 \leq T_{15}$	Interval from B/L Enable Off to PWM Off

The backlight may be flashed if the interface signal remains floated when the above-mentioned signal becomes invalid.

Note (1) The power voltage from system shall be supplied to the input pin of LCD constantly.

(2) Enable the voltage to the LED within the range, which the LCD is operated. The screen becomes white when turning the back-light on before the LCD is operated or turning the LCD off before turning the back-light off. Operation or the LCD turns off before the back-light turns off; the display may momentarily become white.

(3) Don't leave the system at a high impedance state, which the interface signal is out for a long time after the V_{LCD_VCC} is enabled.

(4) The T4 should be measured the module is fully discharged.

(5) The interface signal shall not maintain the high impedance when the power is on.

5.8 INPUT TERMINAL PIN ASSIGNMENT

5.8.1 INPUT SIGNAL & POWER

(LVDS, Connector: 20455-040E-0, I-PEX or the equipment with the equivalent capability)

Pin	Symbol	Function
1	NC	Hot Plug Detect or No connection (optional)
2	LCD_VCC	LCD logic and driver IC Power (3.3V typ.)
3	LCD_VCC	LCD logic and driver IC Power (3.3V typ.)
4	VCC_EDID	DDC power
5	NC (WPN)	Reserved for the use by LCD manufacturer (WPN)
6	CLK_EDID	DDC clock
7	DAT_EDID	DDC data
8	RX0-	Negative LVDS differential data input for pixel
9	RX0+	Positive LVDS differential data input for pixel
10	H_GND	High speed ground
11	RX1-	Negative LVDS differential data input for pixel
12	RX1+	Positive LVDS differential data input for pixel
13	H_GND	High speed ground
14	RX2-	Negative LVDS differential data input for pixel
15	RX2+	Positive LVDS differential data input for pixel
16	H_GND	High speed ground
17	RXC-	Negative LVDS differential clock input for pixel
18	RXC+	Positive LVDS differential clock input for pixel
19	H_GND	High speed ground
20	NC	No connection
21	NC	No connection
22	LCD_GND	LCD logic and driver IC Ground
23	NC	No connection
24	NC	No connection
25	LCD_GND	LCD logic and driver IC Ground
26	NC	No connection
27	NC	No connection
28	LCD_GND	LCD logic and driver IC Ground
29	NC	No connection
30	NC	No connection
31	BL_GND	Backlight ground
32	BL_GND	Backlight ground
33	BL_GND	Backlight ground
34	NC	Hot Plug Detect or No connection (optional)
35	BL_PWM_DIM	Signal input for the system PWM for dimming
36	BL_ENABLE	Backlight on/off
37	NC	APS on/off or No connection (optional)
38	BL_PWR	Backlight power
39	BL_PWR	Backlight power
40	BL_PWR	Backlight power

## 6. PIXEL FORMAT

SAMSUNG DISPLAY

7. OUTLINE DIMENSION

8. MARKING

A nameplate is affixed to the specified location on each product.

(1)Parts number   : LTN156AT32
(2)Revision code   : 3 letters
(3)Lot number   : X X X X XXX XX X 701

                                          Samsung Revision Code

                                          Panel number
                                          Cell ID
                                          Lot ID
                                          Month
                                          Year
                                          Product Code

9. GENERAL PRECAUTIONS

9.1 STORAGE

We highly recommend to comply with the criteria in the table below.

ITEM	Unit	Min.	Max.
Storage Temperature	(℃)	5	40
Storage Humidity	(%rH)	35	75
Storage Life	12 months		
Storage Condition	- The storage room should be equipped with a good ventilation facility, which has a temperature controlling system. - Products should be placed on the pallet, which is away from the wall not on the floor. - Prevent products from being exposed to the direct sunlight, moisture, and water; Be cautious not to pile the products up. - Avoid storing products in the environment, which other hazardous material is placed. - If products are delivered or kept in the storage facility more than 3 months, we recommend you to leave products under the condition including a 20℃ temperature and a humidity of 50% for 24 hours. - If you store semi-manufactured products for more than 3 months, bake the products under the condition including the 50℃ temp. and the 10% humidity for 24hrs after being used.		

10. APPENDIX

Only Internal

[OPTICAL CHARACTERISTICS]

The following items are measured under the stable conditions.* The optical characteristics should be measured in the dark room or the equivalent environment by the methods shown in the Note (5).
Measuring equipment: TOPCON SR-3

Ta = 25 ± 2 °C, V_{LCD_VCC} =3.3V,   fv= 60Hz, f_{DCLK} = 72.33MHz, IF = 100% duty

| Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Flicker	F		-	3.2	5.2		(8)

Note (8) The definition of flicker: The phenomenon, which the pixel on the screen of LCD panel blinks.

1) Calculate the figure with observing the standard for the measurement for the flicker.

2) Measurement point

3) Pattern to measure the flicker: Inverting driving of DOT

[LED DRIVER]

The manufacturer of LED driver: Richtek RT8510   Ta= 25 ± 2 °C

Item	Symbol	Min.	Typ.	Max.	Unit	Note
OVP driving Voltage	V_{OVP}	-	-	42	V	

[ELECTRICAL CHARACTERISTICS]

TFT LCD MODULE

Ta = 25 ± 2 °C

Item		Symbol	Min.	Typ.	Max.	Unit	Note
Power Supply Voltage Ripple	Active Period	$V_{LCD\_VCC\_RIPPLE}$	-	-	0.05 * V_{LCD_VCC}	V	(1)

Note (1) f_V = 60Hz, f_{DCLK} = 72.33MHz, V_{LCD_VCC} = 3.3V, Sub Dot Pattern