



# Product Specification

M270HTN01.0

AU OPTRONICS CORPORATION

( ) Preliminary Specification

( V ) Final Specification

Module	27" Color TFT-LCD
Model Name	M270HTN01.0

Customer

Date

\_\_\_\_\_

Approved by

\_\_\_\_\_

Note: This Specification is subject to  
change without notice.

Approved by

Date

**Howard Lee**

Oct. 18, 2013

Prepared by

Date

**Evelyn Sung**





Oct. 18, 2013

AU Optronics corporation

## Contents

<b>1 Handling Precautions</b>	<b>5</b>
<b>2 General Description</b>	<b>6</b>
2.1 Display Characteristics	6
2.2 Absolute Maximum Rating of Environment	7
2.3 Optical Characteristics	8
2.4 Mechanical Characteristics	12
<b>3 TFT-LCD Module</b>	<b>13</b>
3.1 Block Diagram	13
3.2.1 Connector Type	14
3.2.2 Connector Pin Assignment	14
3.3 Electrical Characteristics	17
3.3.1 Absolute Maximum Rating	17
3.3.2 Recommended Operating Condition	17
3.4 Signal Characteristics	18
3.4.1 LCD Pixel Format	18
3.4.2 LVDS Data Format	18
3.4.3 Color versus Input Data	19
3.4.4 LVDS Specification	20
3.4.5 Input Timing Specification	22
3.4.6 Input Timing Diagram	23
3.5 Power ON/OFF Sequence	24
<b>4 Backlight Unit</b>	<b>25</b>
4.1 Block Diagram	25
4.2 Interface Connection	26
4.2.1 Connector Type	26
4.2.2 Connector Pin Assignment	28
4.3 Electrical Characteristics	29
4.3.1 Absolute Maximum Rating	29
4.3.2 Recommended Operating Condition	29
<b>5 Reliability Test</b>	<b>31</b>
<b>6 Shipping Label</b>	<b>32</b>
<b>7 Mechanical Characteristics</b>	<b>33</b>
<b>8 Packing Specification</b>	<b>35</b>

## Record of Revision

Version	Date	Page	Old description	New Description	Remark																																																																																																																																																																		
0.1	2013/3/22	All	First version release	-																																																																																																																																																																			
1.1	2013/5/2	13	3.2.1 Connector Type (30 pin)	3.2.1 Connector Type (30 pin & 40 pin)																																																																																																																																																																			
	2013/5/2	13-15	3.2.2 Connector Pin Assignment	Modify 3.2.2 Connector Pin Assignment																																																																																																																																																																			
	2013/5/2	17	3.4.1 LCD Pixel Format 	3.4.1 LCD Pixel Format 																																																																																																																																																																			
	2013/5/2	32	7 Mechanical Characteristics 	7 Mechanical Characteristics 																																																																																																																																																																			
2.1	2013/5/24	21	3.4.5 Input Timing Specification <table><tr><th>Symbol</th><th>Description</th><th>Peak</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th><th>Remark</th></tr><tr><td>Tv</td><td rowspan="4">Vertical Section</td><td>Peak</td><td>150</td><td>110</td><td>150</td><td>Th</td><td></td></tr><tr><td>Tdelay (v)</td><td>Active</td><td>150</td><td>100</td><td>150</td><td>Th</td><td></td></tr><tr><td>Tsk (v)</td><td>Blanking</td><td>150</td><td>50</td><td>150</td><td>Th</td><td></td></tr><tr><td>Fv</td><td>Frequency</td><td>30</td><td>60</td><td>76</td><td>Hz</td><td></td></tr><tr><td>Th</td><td rowspan="4">Horizontal Section</td><td>Peak</td><td>150</td><td>80</td><td>150</td><td>Tsk</td><td></td></tr><tr><td>Tdelay (h)</td><td>Active</td><td>150</td><td>40</td><td>150</td><td>Tsk</td><td></td></tr><tr><td>Tsk (h)</td><td>Blanking</td><td>150</td><td>60</td><td>150</td><td>Tsk</td><td></td></tr><tr><td>Fh</td><td>Frequency</td><td>150</td><td>750</td><td>150</td><td>MHz</td><td>Note 3.3</td></tr><tr><td>Tclk</td><td rowspan="2">LVDS Clock</td><td>Peak</td><td>100</td><td>130</td><td>100</td><td>mV</td><td>MPdc</td></tr><tr><td>Fclk</td><td>Frequency</td><td>50</td><td>120</td><td>100</td><td>MHz</td><td>Note 3.4</td></tr></table>	Symbol	Description	Peak	Min.	Typ.	Max.	Unit	Remark	Tv	Vertical Section	Peak	150	110	150	Th		Tdelay (v)	Active	150	100	150	Th		Tsk (v)	Blanking	150	50	150	Th		Fv	Frequency	30	60	76	Hz		Th	Horizontal Section	Peak	150	80	150	Tsk		Tdelay (h)	Active	150	40	150	Tsk		Tsk (h)	Blanking	150	60	150	Tsk		Fh	Frequency	150	750	150	MHz	Note 3.3	Tclk	LVDS Clock	Peak	100	130	100	mV	MPdc	Fclk	Frequency	50	120	100	MHz	Note 3.4	3.4.5 Input Timing Specification <table><tr><th>Symbol</th><th>Description</th><th>Peak</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th><th>Remark</th></tr><tr><td>Tv</td><td rowspan="4">Vertical Section</td><td>Peak</td><td>1000</td><td>1100</td><td>500</td><td>Th</td><td></td></tr><tr><td>Tdelay (v)</td><td>Active</td><td>1000</td><td>1000</td><td>1000</td><td>Th</td><td></td></tr><tr><td>Tsk (v)</td><td>Blanking</td><td>10</td><td>50</td><td>200</td><td>Th</td><td></td></tr><tr><td>Fv</td><td>Frequency</td><td>30</td><td>60</td><td>76</td><td>Hz</td><td></td></tr><tr><td>Th</td><td rowspan="4">Horizontal Section</td><td>Peak</td><td>500</td><td>500</td><td>170</td><td>Tsk</td><td></td></tr><tr><td>Tdelay (h)</td><td>Active</td><td>400</td><td>400</td><td>400</td><td>Tsk</td><td></td></tr><tr><td>Tsk (h)</td><td>Blanking</td><td>30</td><td>60</td><td>120</td><td>Tsk</td><td></td></tr><tr><td>Fh</td><td>Frequency</td><td>60</td><td>120</td><td>150</td><td>MHz</td><td>Note 3.3</td></tr><tr><td>Tclk</td><td rowspan="2">LVDS Clock</td><td>Peak</td><td>100</td><td>130</td><td>100</td><td>mV</td><td>MPdc</td></tr><tr><td>Fclk</td><td>Frequency</td><td>30</td><td>750</td><td>100</td><td>MHz</td><td>Note 3.4</td></tr></table>	Symbol	Description	Peak	Min.	Typ.	Max.	Unit	Remark	Tv	Vertical Section	Peak	1000	1100	500	Th		Tdelay (v)	Active	1000	1000	1000	Th		Tsk (v)	Blanking	10	50	200	Th		Fv	Frequency	30	60	76	Hz		Th	Horizontal Section	Peak	500	500	170	Tsk		Tdelay (h)	Active	400	400	400	Tsk		Tsk (h)	Blanking	30	60	120	Tsk		Fh	Frequency	60	120	150	MHz	Note 3.3	Tclk	LVDS Clock	Peak	100	130	100	mV	MPdc	Fclk	Frequency	30	750	100	MHz	Note 3.4	
Symbol	Description	Peak	Min.	Typ.	Max.	Unit	Remark																																																																																																																																																																
Tv	Vertical Section	Peak	150	110	150	Th																																																																																																																																																																	
Tdelay (v)		Active	150	100	150	Th																																																																																																																																																																	
Tsk (v)		Blanking	150	50	150	Th																																																																																																																																																																	
Fv		Frequency	30	60	76	Hz																																																																																																																																																																	
Th	Horizontal Section	Peak	150	80	150	Tsk																																																																																																																																																																	
Tdelay (h)		Active	150	40	150	Tsk																																																																																																																																																																	
Tsk (h)		Blanking	150	60	150	Tsk																																																																																																																																																																	
Fh		Frequency	150	750	150	MHz	Note 3.3																																																																																																																																																																
Tclk	LVDS Clock	Peak	100	130	100	mV	MPdc																																																																																																																																																																
Fclk		Frequency	50	120	100	MHz	Note 3.4																																																																																																																																																																
Symbol	Description	Peak	Min.	Typ.	Max.	Unit	Remark																																																																																																																																																																
Tv	Vertical Section	Peak	1000	1100	500	Th																																																																																																																																																																	
Tdelay (v)		Active	1000	1000	1000	Th																																																																																																																																																																	
Tsk (v)		Blanking	10	50	200	Th																																																																																																																																																																	
Fv		Frequency	30	60	76	Hz																																																																																																																																																																	
Th	Horizontal Section	Peak	500	500	170	Tsk																																																																																																																																																																	
Tdelay (h)		Active	400	400	400	Tsk																																																																																																																																																																	
Tsk (h)		Blanking	30	60	120	Tsk																																																																																																																																																																	
Fh		Frequency	60	120	150	MHz	Note 3.3																																																																																																																																																																
Tclk	LVDS Clock	Peak	100	130	100	mV	MPdc																																																																																																																																																																
Fclk		Frequency	30	750	100	MHz	Note 3.4																																																																																																																																																																
2.2	2013/5/30	27	4.3.2 Recommended Operating Condition LED Light Bar Power Consumption Max 24.7 Watt	4.3.2 Recommended Operating Condition LED Light Bar Power Consumption Max 22.5 Watt																																																																																																																																																																			
2.3	2013/6/27	28	4.3.1 Absolute Maximum Rating <table><tr><th>Symbol</th><th>Description</th><th>Min</th><th>Max</th><th>Unit</th><th>Remark</th></tr><tr><td>Is</td><td rowspan="2">LED String Current</td><td></td><td>150</td><td>[mA]</td><td>100% duty ratio</td></tr><tr><td></td><td></td><td>300</td><td>[mA]</td><td>Duty ratio ≤ 10% Pulse time=10 ms</td></tr></table>	Symbol	Description	Min	Max	Unit	Remark	Is	LED String Current		150	[mA]	100% duty ratio			300	[mA]	Duty ratio ≤ 10% Pulse time=10 ms	4.3.1 Absolute Maximum Rating <table><tr><th>Symbol</th><th>Description</th><th>Min</th><th>Max</th><th>Unit</th><th>Remark</th></tr><tr><td>Is</td><td rowspan="2">LED String Current</td><td></td><td>120</td><td>[mA]</td><td>100% duty ratio</td></tr><tr><td></td><td></td><td>300</td><td>[mA]</td><td>Duty ratio ≤ 10% Pulse time=10 ms</td></tr><tr><td>I<sub>fp</sub></td><td rowspan="2">LED Pulse Forward Current</td><td></td><td>200</td><td>[mA]</td><td>Note 5</td></tr><tr><td></td><td></td><td>250</td><td>[mA]</td><td>Pulse Width=10ms Duty=25% Note 2</td></tr></table>	Symbol	Description	Min	Max	Unit	Remark	Is	LED String Current		120	[mA]	100% duty ratio			300	[mA]	Duty ratio ≤ 10% Pulse time=10 ms	I <sub>fp</sub>	LED Pulse Forward Current		200	[mA]	Note 5			250	[mA]	Pulse Width=10ms Duty=25% Note 2																																																																																																																						
Symbol	Description	Min	Max	Unit	Remark																																																																																																																																																																		
Is	LED String Current		150	[mA]	100% duty ratio																																																																																																																																																																		
			300	[mA]	Duty ratio ≤ 10% Pulse time=10 ms																																																																																																																																																																		
Symbol	Description	Min	Max	Unit	Remark																																																																																																																																																																		
Is	LED String Current		120	[mA]	100% duty ratio																																																																																																																																																																		
			300	[mA]	Duty ratio ≤ 10% Pulse time=10 ms																																																																																																																																																																		
I <sub>fp</sub>	LED Pulse Forward Current		200	[mA]	Note 5																																																																																																																																																																		
			250	[mA]	Pulse Width=10ms Duty=25% Note 2																																																																																																																																																																		
3.3	2013/6/30	6	Power Consumption 29.52 (Typ.) LCD module : PDD (Typ.)=8.92 @ Black pattern,Fv=144Hz	Power Consumption 27.85 (Typ.) LCD module : PDD (Typ.) =7.25 @ Black pattern,Fv=144Hz																																																																																																																																																																			

		13	3.1 Block Diagram	3.1 Block Diagram																																																																																																																																															
		17	<div>3.3.2 Recommended Operating Condition</div> <table><thead><tr><th>Symbol</th><th>Description</th><th>Min</th><th>Typ</th><th>Max</th><th>Unit</th><th>Remark</th></tr></thead><tbody><tr><td>VDD</td><td>Power supply input voltage</td><td>4.5</td><td>5.0</td><td>5.5</td><td>[V<sub>olt</sub>]</td><td></td></tr><tr><td>IDD</td><td>Power supply input current (RMS)</td><td>-</td><td>1.2</td><td>1.4</td><td>[A]</td><td>VDD= 5.0V, Black Pattern, Fv=60Hz</td></tr><tr><td></td><td></td><td>-</td><td>1.4</td><td>1.7</td><td>[A]</td><td>VDD= 5.0V, Black Pattern, Fv=75Hz</td></tr><tr><td>PDD</td><td></td><td>-</td><td>7</td><td>9.5</td><td>[Watt]</td><td>VDD= 5.0V, Black Pattern, Fv=60Hz</td></tr><tr><td></td><td></td><td>-</td><td>9.5</td><td>8.0</td><td>[Watt]</td><td>VDD= 5.0V, Black Pattern, Fv=75Hz</td></tr><tr><td>IRush</td><td>Inrush Current</td><td>-</td><td>-</td><td>3.0</td><td>[A]</td><td>Note 3-1</td></tr><tr><td>VDDip</td><td>Allowable VDD Ripple Voltage</td><td>-</td><td>-</td><td>500</td><td>[mV]</td><td>VDD= 5.0V, Black Pattern, Fv=75Hz</td></tr></tbody></table>	Symbol	Description	Min	Typ	Max	Unit	Remark	VDD	Power supply input voltage	4.5	5.0	5.5	[V <sub>olt</sub> ]		IDD	Power supply input current (RMS)	-	1.2	1.4	[A]	VDD= 5.0V, Black Pattern, Fv=60Hz			-	1.4	1.7	[A]	VDD= 5.0V, Black Pattern, Fv=75Hz	PDD		-	7	9.5	[Watt]	VDD= 5.0V, Black Pattern, Fv=60Hz			-	9.5	8.0	[Watt]	VDD= 5.0V, Black Pattern, Fv=75Hz	IRush	Inrush Current	-	-	3.0	[A]	Note 3-1	VDDip	Allowable VDD Ripple Voltage	-	-	500	[mV]	VDD= 5.0V, Black Pattern, Fv=75Hz	<div>3.3.2 Recommended Operating Condition</div> <table><thead><tr><th>Symbol</th><th>Description</th><th>Min</th><th>Typ</th><th>Max</th><th>Unit</th><th>Remark</th></tr></thead><tbody><tr><td>VDD</td><td>Power supply input voltage</td><td>4.5</td><td>5.0</td><td>5.5</td><td>[V<sub>olt</sub>]</td><td></td></tr><tr><td>IDD</td><td>Power supply input current (RMS)</td><td>-</td><td>0.8</td><td>0.98</td><td>[A]</td><td>VDD= 5.0V, Black Pattern, Fv=60Hz</td></tr><tr><td></td><td></td><td>-</td><td>1.45</td><td>1.74</td><td>[A]</td><td>VDD= 5.0V, Black Pattern, Fv=144Hz</td></tr><tr><td>PDD</td><td></td><td>-</td><td>4</td><td>4.8</td><td>[Watt]</td><td>VDD= 5.0V, Black Pattern, Fv=60Hz</td></tr><tr><td></td><td></td><td>-</td><td>7.25</td><td>9.7</td><td>[Watt]</td><td>VDD= 5.0V, Black Pattern, Fv=144Hz</td></tr><tr><td>IRush</td><td>Inrush Current</td><td>-</td><td>-</td><td>3.0</td><td>[A]</td><td>Note 3-1</td></tr><tr><td>VDDip</td><td>Allowable VDD Ripple Voltage</td><td>-</td><td>-</td><td>500</td><td>[mV]</td><td>VDD= 5.0V, Black Pattern, Fv=75Hz</td></tr></tbody></table>	Symbol	Description	Min	Typ	Max	Unit	Remark	VDD	Power supply input voltage	4.5	5.0	5.5	[V <sub>olt</sub> ]		IDD	Power supply input current (RMS)	-	0.8	0.98	[A]	VDD= 5.0V, Black Pattern, Fv=60Hz			-	1.45	1.74	[A]	VDD= 5.0V, Black Pattern, Fv=144Hz	PDD		-	4	4.8	[Watt]	VDD= 5.0V, Black Pattern, Fv=60Hz			-	7.25	9.7	[Watt]	VDD= 5.0V, Black Pattern, Fv=144Hz	IRush	Inrush Current	-	-	3.0	[A]	Note 3-1	VDDip	Allowable VDD Ripple Voltage	-	-	500	[mV]	VDD= 5.0V, Black Pattern, Fv=75Hz																															
Symbol	Description	Min	Typ	Max	Unit	Remark																																																																																																																																													
VDD	Power supply input voltage	4.5	5.0	5.5	[V <sub>olt</sub> ]																																																																																																																																														
IDD	Power supply input current (RMS)	-	1.2	1.4	[A]	VDD= 5.0V, Black Pattern, Fv=60Hz																																																																																																																																													
		-	1.4	1.7	[A]	VDD= 5.0V, Black Pattern, Fv=75Hz																																																																																																																																													
PDD		-	7	9.5	[Watt]	VDD= 5.0V, Black Pattern, Fv=60Hz																																																																																																																																													
		-	9.5	8.0	[Watt]	VDD= 5.0V, Black Pattern, Fv=75Hz																																																																																																																																													
IRush	Inrush Current	-	-	3.0	[A]	Note 3-1																																																																																																																																													
VDDip	Allowable VDD Ripple Voltage	-	-	500	[mV]	VDD= 5.0V, Black Pattern, Fv=75Hz																																																																																																																																													
Symbol	Description	Min	Typ	Max	Unit	Remark																																																																																																																																													
VDD	Power supply input voltage	4.5	5.0	5.5	[V <sub>olt</sub> ]																																																																																																																																														
IDD	Power supply input current (RMS)	-	0.8	0.98	[A]	VDD= 5.0V, Black Pattern, Fv=60Hz																																																																																																																																													
		-	1.45	1.74	[A]	VDD= 5.0V, Black Pattern, Fv=144Hz																																																																																																																																													
PDD		-	4	4.8	[Watt]	VDD= 5.0V, Black Pattern, Fv=60Hz																																																																																																																																													
		-	7.25	9.7	[Watt]	VDD= 5.0V, Black Pattern, Fv=144Hz																																																																																																																																													
IRush	Inrush Current	-	-	3.0	[A]	Note 3-1																																																																																																																																													
VDDip	Allowable VDD Ripple Voltage	-	-	500	[mV]	VDD= 5.0V, Black Pattern, Fv=75Hz																																																																																																																																													
		20	<div>3.4.4 LVDS Specification</div> <div>a. DC Characteristics:</div> <table><thead><tr><th>Symbol</th><th>Description</th><th>Min</th><th>Typ</th><th>Max</th><th>Units</th><th>Condition</th></tr></thead><tbody><tr><td>V<sub>TH</sub></td><td>LVDS Differential Input High Threshold</td><td>-</td><td>-</td><td>+100</td><td>[mV]</td><td>V<sub>CM</sub> = 1.2V</td></tr><tr><td>V<sub>TL</sub></td><td>LVDS Differential Input Low Threshold</td><td>-100</td><td>-</td><td>-</td><td>[mV]</td><td>V<sub>CM</sub> = 1.2V</td></tr><tr><td> V<sub>CL</sub> </td><td>LVDS Differential Input Voltage</td><td>100</td><td>-</td><td>600</td><td>[mV]</td><td></td></tr><tr><td>V<sub>CM</sub></td><td>LVDS Common Mode Voltage</td><td>+1.0</td><td>+1.2</td><td>+1.5</td><td>[V]</td><td>V<sub>TH</sub>-V<sub>TL</sub> = 200mV</td></tr></tbody></table>	Symbol	Description	Min	Typ	Max	Units	Condition	V <sub>TH</sub>	LVDS Differential Input High Threshold	-	-	+100	[mV]	V <sub>CM</sub> = 1.2V	V <sub>TL</sub>	LVDS Differential Input Low Threshold	-100	-	-	[mV]	V <sub>CM</sub> = 1.2V	V <sub>CL</sub>	LVDS Differential Input Voltage	100	-	600	[mV]		V <sub>CM</sub>	LVDS Common Mode Voltage	+1.0	+1.2	+1.5	[V]	V <sub>TH</sub> -V <sub>TL</sub> = 200mV	<div>3.4.4 LVDS Specification</div> <div>a. DC Characteristics:</div> <table><thead><tr><th>Symbol</th><th>Description</th><th>Min</th><th>Typ</th><th>Max</th><th>Units</th><th>Condition</th></tr></thead><tbody><tr><td>V<sub>TH</sub></td><td>LVDS Differential Input High Threshold</td><td>-</td><td>-</td><td>+100</td><td>[mV]</td><td>V<sub>CM</sub> = 1.2V</td></tr><tr><td>V<sub>TL</sub></td><td>LVDS Differential Input Low Threshold</td><td>-100</td><td>-</td><td>-</td><td>[mV]</td><td>V<sub>CM</sub> = 1.2V</td></tr><tr><td> V<sub>CL</sub> </td><td>LVDS Differential Input Voltage</td><td>100</td><td>-</td><td>600</td><td>[mV]</td><td></td></tr><tr><td>V<sub>CM</sub></td><td>LVDS Common Mode Voltage</td><td>+1.0</td><td>+1.2</td><td>+1.5</td><td>[V]</td><td>V<sub>TH</sub>-V<sub>TL</sub> = 200mV</td></tr></tbody></table>	Symbol	Description	Min	Typ	Max	Units	Condition	V <sub>TH</sub>	LVDS Differential Input High Threshold	-	-	+100	[mV]	V <sub>CM</sub> = 1.2V	V <sub>TL</sub>	LVDS Differential Input Low Threshold	-100	-	-	[mV]	V <sub>CM</sub> = 1.2V	V <sub>CL</sub>	LVDS Differential Input Voltage	100	-	600	[mV]		V <sub>CM</sub>	LVDS Common Mode Voltage	+1.0	+1.2	+1.5	[V]	V <sub>TH</sub> -V <sub>TL</sub> = 200mV																																																																									
Symbol	Description	Min	Typ	Max	Units	Condition																																																																																																																																													
V <sub>TH</sub>	LVDS Differential Input High Threshold	-	-	+100	[mV]	V <sub>CM</sub> = 1.2V																																																																																																																																													
V <sub>TL</sub>	LVDS Differential Input Low Threshold	-100	-	-	[mV]	V <sub>CM</sub> = 1.2V																																																																																																																																													
V <sub>CL</sub>	LVDS Differential Input Voltage	100	-	600	[mV]																																																																																																																																														
V <sub>CM</sub>	LVDS Common Mode Voltage	+1.0	+1.2	+1.5	[V]	V <sub>TH</sub> -V <sub>TL</sub> = 200mV																																																																																																																																													
Symbol	Description	Min	Typ	Max	Units	Condition																																																																																																																																													
V <sub>TH</sub>	LVDS Differential Input High Threshold	-	-	+100	[mV]	V <sub>CM</sub> = 1.2V																																																																																																																																													
V <sub>TL</sub>	LVDS Differential Input Low Threshold	-100	-	-	[mV]	V <sub>CM</sub> = 1.2V																																																																																																																																													
V <sub>CL</sub>	LVDS Differential Input Voltage	100	-	600	[mV]																																																																																																																																														
V <sub>CM</sub>	LVDS Common Mode Voltage	+1.0	+1.2	+1.5	[V]	V <sub>TH</sub> -V <sub>TL</sub> = 200mV																																																																																																																																													
		22	<div>3.4.5 Input Timing Specification</div> <table><thead><tr><th>Symbol</th><th>Description</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th><th>Remark</th></tr></thead><tbody><tr><td>Tv</td><td rowspan="3">Vertical Section</td><td>Period</td><td>1088</td><td>1130</td><td>3811</td><td>Th</td></tr><tr><td>Tdisp (v)</td><td>Active</td><td>1080</td><td>1080</td><td>1090</td><td>Th</td></tr><tr><td>Tblk (v)</td><td>Blanking</td><td>18</td><td>50</td><td>2731</td><td>Th</td></tr><tr><td>Fv</td><td rowspan="3">Horizontal Section</td><td>Frequency</td><td>50</td><td>120</td><td>144</td><td>Hz</td></tr><tr><td>Th</td><td>Period</td><td>510</td><td>560</td><td>1770</td><td>Tclk</td></tr><tr><td>Tdisp (h)</td><td>Active</td><td>480</td><td>480</td><td>480</td><td>Tclk</td></tr><tr><td>Tblk (h)</td><td rowspan="3">LVDS Clock</td><td>Blanking</td><td>30</td><td>80</td><td>1290</td><td>Tclk</td></tr><tr><td>Fh</td><td>Frequency</td><td>50</td><td>136</td><td>191</td><td>KHz</td></tr><tr><td>Tclk</td><td>Period</td><td>10.3</td><td>13.2</td><td>35.7</td><td>ns</td></tr><tr><td>Fclk</td><td></td><td>Frequency</td><td>28</td><td>75.9</td><td>97.2</td><td>MHz</td></tr></tbody></table>	Symbol	Description	Min.	Typ.	Max.	Unit	Remark	Tv	Vertical Section	Period	1088	1130	3811	Th	Tdisp (v)	Active	1080	1080	1090	Th	Tblk (v)	Blanking	18	50	2731	Th	Fv	Horizontal Section	Frequency	50	120	144	Hz	Th	Period	510	560	1770	Tclk	Tdisp (h)	Active	480	480	480	Tclk	Tblk (h)	LVDS Clock	Blanking	30	80	1290	Tclk	Fh	Frequency	50	136	191	KHz	Tclk	Period	10.3	13.2	35.7	ns	Fclk		Frequency	28	75.9	97.2	MHz	<div>3.4.5 Input Timing Specification</div> <table><thead><tr><th>Symbol</th><th>Description</th><th>Min.</th><th>Typ.</th><th>Max.</th><th>Unit</th><th>Remark</th></tr></thead><tbody><tr><td>Tv</td><td rowspan="3">Vertical Section</td><td>Period</td><td>1088</td><td>1130</td><td>3000</td><td>Th</td></tr><tr><td>Tdisp (v)</td><td>Active</td><td>1080</td><td>1080</td><td>1080</td><td>Th</td></tr><tr><td>Tblk (v)</td><td>Blanking</td><td>18</td><td>50</td><td>1930</td><td>Th</td></tr><tr><td>Fv</td><td rowspan="3">Horizontal Section</td><td>Frequency</td><td>50</td><td>120</td><td>144</td><td>Hz</td></tr><tr><td>Th</td><td>Period</td><td>510</td><td>560</td><td>715</td><td>Tclk</td></tr><tr><td>Tdisp (h)</td><td>Active</td><td>480</td><td>480</td><td>480</td><td>Tclk</td></tr><tr><td>Tblk (h)</td><td rowspan="3">LVDS Clock</td><td>Blanking</td><td>30</td><td>80</td><td>235</td><td>Tclk</td></tr><tr><td>Fh</td><td>Frequency</td><td>50</td><td>136</td><td>191</td><td>KHz</td></tr><tr><td>Tclk</td><td>Period</td><td>10.3</td><td>13.2</td><td>35.7</td><td>ns</td></tr><tr><td>Fclk</td><td></td><td>Frequency</td><td>28</td><td>75.9</td><td>97.2</td><td>MHz</td></tr></tbody></table>	Symbol	Description	Min.	Typ.	Max.	Unit	Remark	Tv	Vertical Section	Period	1088	1130	3000	Th	Tdisp (v)	Active	1080	1080	1080	Th	Tblk (v)	Blanking	18	50	1930	Th	Fv	Horizontal Section	Frequency	50	120	144	Hz	Th	Period	510	560	715	Tclk	Tdisp (h)	Active	480	480	480	Tclk	Tblk (h)	LVDS Clock	Blanking	30	80	235	Tclk	Fh	Frequency	50	136	191	KHz	Tclk	Period	10.3	13.2	35.7	ns	Fclk		Frequency	28	75.9	97.2	MHz	
Symbol	Description	Min.	Typ.	Max.	Unit	Remark																																																																																																																																													
Tv	Vertical Section	Period	1088	1130	3811	Th																																																																																																																																													
Tdisp (v)		Active	1080	1080	1090	Th																																																																																																																																													
Tblk (v)		Blanking	18	50	2731	Th																																																																																																																																													
Fv	Horizontal Section	Frequency	50	120	144	Hz																																																																																																																																													
Th		Period	510	560	1770	Tclk																																																																																																																																													
Tdisp (h)		Active	480	480	480	Tclk																																																																																																																																													
Tblk (h)	LVDS Clock	Blanking	30	80	1290	Tclk																																																																																																																																													
Fh		Frequency	50	136	191	KHz																																																																																																																																													
Tclk		Period	10.3	13.2	35.7	ns																																																																																																																																													
Fclk		Frequency	28	75.9	97.2	MHz																																																																																																																																													
Symbol	Description	Min.	Typ.	Max.	Unit	Remark																																																																																																																																													
Tv	Vertical Section	Period	1088	1130	3000	Th																																																																																																																																													
Tdisp (v)		Active	1080	1080	1080	Th																																																																																																																																													
Tblk (v)		Blanking	18	50	1930	Th																																																																																																																																													
Fv	Horizontal Section	Frequency	50	120	144	Hz																																																																																																																																													
Th		Period	510	560	715	Tclk																																																																																																																																													
Tdisp (h)		Active	480	480	480	Tclk																																																																																																																																													
Tblk (h)	LVDS Clock	Blanking	30	80	235	Tclk																																																																																																																																													
Fh		Frequency	50	136	191	KHz																																																																																																																																													
Tclk		Period	10.3	13.2	35.7	ns																																																																																																																																													
Fclk		Frequency	28	75.9	97.2	MHz																																																																																																																																													
		24	<div>Power Sequence Timing</div> <table><thead><tr><th rowspan="2">Symbol</th><th colspan="3">Value</th><th rowspan="2">Unit</th><th rowspan="2">Remark</th></tr><tr><th>Min.</th><th>Typ.</th><th>Max.</th></tr></thead><tbody><tr><td>T1</td><td>0.5</td><td>-</td><td>10</td><td>[ms]</td><td></td></tr><tr><td>T2</td><td>0</td><td>-</td><td>50</td><td>[ms]</td><td></td></tr><tr><td>T3</td><td>500</td><td>-</td><td>-</td><td>[ms]</td><td></td></tr><tr><td>T4</td><td>100</td><td>-</td><td>-</td><td>[ms]</td><td></td></tr><tr><td>T5</td><td>0</td><td>-</td><td>50</td><td>[ms]</td><td>Note 3-5 Note 3-6</td></tr><tr><td>T6</td><td>0</td><td>-</td><td>100</td><td>[ms]</td><td>Note 3-6</td></tr><tr><td>T7</td><td>1000</td><td>-</td><td>-</td><td>[ms]</td><td></td></tr></tbody></table>	Symbol	Value			Unit	Remark	Min.	Typ.	Max.	T1	0.5	-	10	[ms]		T2	0	-	50	[ms]		T3	500	-	-	[ms]		T4	100	-	-	[ms]		T5	0	-	50	[ms]	Note 3-5 Note 3-6	T6	0	-	100	[ms]	Note 3-6	T7	1000	-	-	[ms]		<div>Power Sequence Timing</div> <table><thead><tr><th rowspan="2">Symbol</th><th colspan="3">Value</th><th rowspan="2">Unit</th><th rowspan="2">Remark</th></tr><tr><th>Min.</th><th>Typ.</th><th>Max.</th></tr></thead><tbody><tr><td>T1</td><td>0.5</td><td>-</td><td>10</td><td>[ms]</td><td></td></tr><tr><td>T2</td><td>250</td><td>-</td><td>300</td><td>[ms]</td><td></td></tr><tr><td>T3</td><td>500</td><td>-</td><td>-</td><td>[ms]</td><td></td></tr><tr><td>T4</td><td>100</td><td>-</td><td>-</td><td>[ms]</td><td></td></tr><tr><td>T5</td><td>0</td><td>-</td><td>50</td><td>[ms]</td><td>Note 3-5 Note 3-6</td></tr><tr><td>T6</td><td>0</td><td>-</td><td>150</td><td>[ms]</td><td>Note 3-6</td></tr><tr><td>T7</td><td>1000</td><td>-</td><td>-</td><td>[ms]</td><td></td></tr></tbody></table>	Symbol	Value			Unit	Remark	Min.	Typ.	Max.	T1	0.5	-	10	[ms]		T2	250	-	300	[ms]		T3	500	-	-	[ms]		T4	100	-	-	[ms]		T5	0	-	50	[ms]	Note 3-5 Note 3-6	T6	0	-	150	[ms]	Note 3-6	T7	1000	-	-	[ms]																																										
Symbol	Value				Unit	Remark																																																																																																																																													
	Min.	Typ.	Max.																																																																																																																																																
T1	0.5	-	10	[ms]																																																																																																																																															
T2	0	-	50	[ms]																																																																																																																																															
T3	500	-	-	[ms]																																																																																																																																															
T4	100	-	-	[ms]																																																																																																																																															
T5	0	-	50	[ms]	Note 3-5 Note 3-6																																																																																																																																														
T6	0	-	100	[ms]	Note 3-6																																																																																																																																														
T7	1000	-	-	[ms]																																																																																																																																															
Symbol	Value			Unit	Remark																																																																																																																																														
	Min.	Typ.	Max.																																																																																																																																																
T1	0.5	-	10	[ms]																																																																																																																																															
T2	250	-	300	[ms]																																																																																																																																															
T3	500	-	-	[ms]																																																																																																																																															
T4	100	-	-	[ms]																																																																																																																																															
T5	0	-	50	[ms]	Note 3-5 Note 3-6																																																																																																																																														
T6	0	-	150	[ms]	Note 3-6																																																																																																																																														
T7	1000	-	-	[ms]																																																																																																																																															
		18	<div>3.4.2 LVDS Data Format</div>	<div>3.4.2 LVDS Data Format</div>																																																																																																																																															

## 1 Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open or modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) In case a TFT-LCD Module has to be put back into the packing container slot after once it was taken out from the container, do not press the center of the LED lightbar edge. Otherwise the TFT-LCD Module may be damaged.
- 10) Insert or pull out the interface connector, be sure not to rotate nor tilt it of the TFT-LCD Module.
- 11) Do not twist nor bend the TFT -LCD Module even momentarily. It should be taken into consideration that no bending/twisting forces are applied to the TFT-LCD Module from outside. Otherwise the TFT-LCD Module may be damaged.
- 12) Please avoid touching COF position while you are doing mechanical design.
- 13) When storing modules as spares for a long time, the following precaution is necessary:  
Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.



## 2 General Description

This specification applies to the 27 inch wide Color a-Si TFT-LCD Module M270HTN01.0. The display supports the Full HD - 1920(H) x 1080(V) screen format and 16.7M colors (RGB 6-bits + Hi-FRC data). The input interface is Four channel LVDS and this module doesn't contain an driver board for backlight.

### 2.1 Display Characteristics

The following items are characteristics summary on the table under 25°C condition:

ITEMS	Unit	SPECIFICATIONS
Screen Diagonal	[mm]	685.65(27")
Active Area	[mm]	597.6 (H) x 336.15 (V)
Pixels H x V	-	1920(x3) x 1080
Pixel Pitch	[um]	311.25 (per one triad) x311.25
Pixel Arrangement	-	R.G.B. Vertical Stripe
Display Mode	-	TN Mode, Normally White
White Luminance ( Center )	[cd/m <sup>2</sup> ]	300 (Typ.)
Contrast Ratio	-	1000:1 (Typ.)
Response Time	[msec]	5ms (Typ., on/off)
Power Consumption (LCD Module + Backligh unit)	[Watt]	27.85 (Typ.) LCD module : PDD (Typ.) =7.25 @ Black pattern,Fv=144Hz Backlight unit : P <sub>BLU</sub> (Typ.) =20.6 @Is=120mA
Weight	[Grams]	2860
Outline Dimension	[mm]	630 (W) x 368.2 (H) x 14.1(D)
Electrical Interface	-	Four channel LVDS
Support Color	-	16.7M colors (RGB 6-bit + Hi_FRC )
Surface Treatment	-	Anti-Glare, 3H
Temperature Range Operating	[°C]	0 to +50
Storage (Shipping)	[°C]	-20 to +60
RoHS Compliance	-	RoHS Compliance
TCO Compliance	-	TCO 6.0 Compliance




## 2.2 Absolute Maximum Rating of Environment

Permanent damage may occur if exceeding the following maximum rating.

Symbol	Description	Min.	Max.	Unit	Remark
TOP	Operating Temperature	0	+50	[°C]	<b>Note 2-1</b>
TGS	Glass surface temperature (operation)	0	+65	[°C]	<b>Note 2-1</b> Function judged only
HOP	Operation Humidity	5	90	[%RH]	<b>Note 2-1</b>
TST	Storage Temperature	-20	+60	[°C]	
HST	Storage Humidity	5	90	[%RH]	

**Note 2-1:** Temperature and relative humidity range are shown as the below figure.


1. 90% RH Max (  $T_a \leq 39^{\circ}\text{C}$  )
2. Max wet-bulb temperature at  $39^{\circ}\text{C}$  or less. (  $T_a \leq 39^{\circ}\text{C}$  )
3. No condensation



Operating Range



Storage Range



## 2.3 Optical Characteristics

The optical characteristics are measured on the following test condition.


### Test Condition:

1. Equipment setup: Please refer to **Note 2-2**.
2. Panel Lighting time: 30 minutes
3. VDD=5.0V, Fv=144Hz, Is=120mA, Ta=25°C

Symbol	Description		Min.	Typ.	Max.	Unit	Remark
L <sub>w</sub>	White Luminance (Center of screen)		240	300	-	[cd/m <sup>2</sup> ]	<b>Note 2-2</b> By SR-3
L <sub>uni</sub>	Luminance Uniformity (9 points)		75	80	-	[%]	<b>Note 2-3</b> By SR-3
CR	Contrast Ratio (Center of screen)		600	1000	-	-	<b>Note 2-4</b> By SR-3
θ <sub>R</sub>	Horizontal Viewing Angle (CR=10)	Right	75	85	-	[degree]	<b>Note 2-5</b> By SR-3
θ <sub>L</sub>		Left	75	85	-		
Φ <sub>H</sub>	Vertical Viewing Angle (CR=10)	Up	70	80	-		
Φ <sub>L</sub>		Down	70	80	-		
θ <sub>R</sub>	Horizontal Viewing Angle (CR=5)	Right	75	88	-		
θ <sub>L</sub>		Left	75	88	-		
Φ <sub>H</sub>	Vertical Viewing Angle (CR=5)	Up	70	85	-		
Φ <sub>L</sub>		Down	70	85	-		
T <sub>R</sub>	Response Time	Rising Time	-	3.8	5.5	[msec]	<b>Note 2-6</b> By TRD-100
T <sub>F</sub>		Falling Time	-	1.2	2.5		
-		Rising + Falling	-	5	8		
R <sub>x</sub>	Color Coordinates (CIE 1931)	Red x	0.615	0.645	0.675	-	By SR-3
R <sub>y</sub>		Red y	0.315	0.345	0.375		
G <sub>x</sub>		Green x	0.291	0.321	0.351		
G <sub>y</sub>		Green y	0.603	0.633	0.663		
B <sub>x</sub>		Blue x	0.121	0.151	0.181		
B <sub>y</sub>		Blue y	0.018	0.048	0.078		
W <sub>x</sub>		White x	0.283	0.313	0.343		
W <sub>y</sub>		White y	0.299	0.329	0.359		
CT	Crosstalk		-	-	1.5	[%]	<b>Note 2-7</b> By SR-3
F <sub>dB</sub>	Flicker (Center of screen)		-	-	-20	[dB]	<b>Note 2-8</b> By SR-3



**Note 2-2:** Equipment setup :




**Note 2-3:** Luminance Uniformity Measurement

## Definition:

$$\text{Luminance Uniformity} = \frac{\text{Minimum Luminance of 9 Points (P1 ~ P9)}}{\text{Maximum Luminance of 9 Points (P1 ~ P9)}}$$

*a. Test pattern: White Pattern*



## Note 2-4: Contrast Ratio Measurement

### Definition:


$$\text{Contrast Ratio} = \frac{\text{Luminance of White pattern}}{\text{Luminance of Black pattern}}$$

- a. Measured position: Center of screen (P5) & perpendicular to the screen ( $\theta = \Phi = 0^\circ$ )

## Note 2-5: Viewing angle measurement


**Definition:** The angle at which the contrast ratio is greater than 10 & 5 .

- a. Horizontal view angle: Divide to left & right ( $\theta_L$  &  $\theta_R$ )  
Vertical view angle: Divide to up & down ( $\Phi_H$  &  $\Phi_L$ )



## Note 2-6: Response time measurement

The output signals of photo detector are measured when the input signals are changed from “Black” to “White” (rising time,  $T_R$ ), and from “White” to “Black” (falling time,  $T_F$ ), respectively. The response time is interval between the 10% and 90% of optical response. (*Black & White color definition: Please refer section 3.4.3*)



## Note 2-7: Crosstalk measurement

### Definition:

$$CT = \text{Max. } (CT_H, CT_V);$$

Where

a. Maximum Horizontal Crosstalk :


$$CT_H = \text{Max. } (|Y_{BL} - Y_{AL}| / Y_{AL} \times 100 \%, |Y_{BR} - Y_{AR}| / Y_{AR} \times 100 \%);$$

Maximum Vertical Crosstalk:

$$CT_V = \text{Max. } (|Y_{BU} - Y_{AU}| / Y_{AU} \times 100 \%, |Y_{BD} - Y_{AD}| / Y_{AD} \times 100 \%);$$


b.  $Y_{AU}$ ,  $Y_{AD}$ ,  $Y_{AL}$ ,  $Y_{AR}$  = Luminance of measured location without Black pattern

$Y_{BU}$ ,  $Y_{BD}$ ,  $Y_{BL}$ ,  $Y_{BR}$  = Luminance of measured location with Black pattern



## Note 2-8: Flicker measurement

a. Test pattern: It is listed as following.



R: Red, G: Green, B:Blue

b. Measured position: Center of screen (P5) & perpendicular to the screen ( $\theta=\Phi=0^\circ$ )

## 2.4 Mechanical Characteristics


Symbol	Description	Min.	Max.	Unit	Remark
P <sub>bc</sub>	Backside Compression	2.5	-	[Kgf]	<b>Note 2-9</b>

### Note 2-9: Test Method:

The point is at a distance from right-downside 25mm x 25mm defined as the Start Point of Measure Points, and the point is at a distance 25mm from left-side & around 10mm from PCB defined as the End Point.

Align 50mm x 50mm block from Start Point on the Bezel Back, and the corners of each block are Measure Points.


If the distance from the last block to each side of the End Point  $\geq 25\text{mm}$ , add other blocks to make sure that most area of Bezel Back can be measured.



## 3 TFT-LCD Module

### 3.1 Block Diagram

The following shows the block diagram of the 27 inch Color TFT-LCD Module.



## 3.2 Interface Connection

### 3.2.1 Connector Type

#### 30 Pin

TFT-LCD Connector	Manufacturer	STARCONN	STM
	Part Number	093G30-02001AM4	MSCKT2407P30HB
Mating Connector	Manufacturer	JAE	
	Part Number	FI-X30HL (Locked Type)	

#### 40 Pin


TFT-LCD Connector	Manufacturer	STARCONN	
	Part Number	115F40-R000RA-M3	
Mating Connector	Manufacturer	JAE	
	Part Number	FI-NX40HL (Locked Type)	

### 3.2.2 Connector Pin Assignment

Pin number	Signal name	Description
1	RxO1CN0	F path_ Negative LVDS differential data input (Odd data)
2	RxO1CP0	F path_ Positive LVDS differential data input (Odd data)
3	RxO1CN1	F path_ Negative LVDS differential data input (Odd data)
4	RxO1CP1	F path_ Positive LVDS differential data input (Odd data)
5	RxO1CN2	F path_ Negative LVDS differential data input (Odd data)
6	RxO1CP2	F path_ Positive LVDS differential data input (Odd data)
7	GND	Power Ground
8	RxO1CCLKN	F path_ Negative LVDS differential clock input (Odd clock)
9	RxO1CCLKP	F path_ Positive LVDS differential clock input (Odd clock)
10	GND	Power Ground
11	RxO1CN3	F path_ Negative LVDS differential data input (Odd data)
12	RxO1CP3	F path_ Positive LVDS differential data input (Odd data)
13	NC	Do not connect (for AUO test only.)
14	NC	Do not connect (for AUO test only.)
15	GND	Power Ground
16	RxE2CN0	F path_ Negative LVDS differential data input (Even data)
17	RxE2CP0	F path_ Positive LVDS differential data input (Even data)
18	RxE2CN1	F path_ Negative LVDS differential data input (Even data)
19	RxE2CP1	F path_ Positive LVDS differential data input (Even data)
20	RxE2CN2	F path_ Negative LVDS differential data input (Even data)
21	RxE2CP2	F path_ Positive LVDS differential data input (Even data)
22	GND	Power Ground
23	RxE2CCLKN	F path_ Negative LVDS differential clock input (Even clock)
24	RxE2CCLKP	F path_ Positive LVDS differential clock input (Even clock)



25	GND	Power Ground
26	RxE2CN3	F path_ Negative LVDS differential data input (Even data)
27	RxE2CP3	F path_ Positive LVDS differential data input (Even data)
28	NC	Do not connect (for AUO test only.)
29	NC	Do not connect (for AUO test only.)
30	GND	Power Ground





# Product Specification

M270HTN01.0

AU OPTRONICS CORPORATION

Pin number	Signal name	Description
1	RxO3CN0	B path_ Negative LVDS differential data input (Odd data)
2	RxO3CP0	B path_ Positive LVDS differential data input (Odd data)
3	RxO3CN1	B path_ Negative LVDS differential data input (Odd data)
4	RxO3CP1	B path_ Positive LVDS differential data input (Odd data)
5	RxO3CN2	B path_ Negative LVDS differential data input (Odd data)
6	RxO3CP2	B path_ Positive LVDS differential data input (Odd data)
7	GND	Power Ground
8	RxO3CCLKN	B path_ Negative LVDS differential clock input (Odd clock)
9	RxO3CCLKP	B path_ Positive LVDS differential clock input (Odd clock)
10	GND	Power Ground
11	RxO3CN3	B path_ Negative LVDS differential data input (Odd data)
12	RxO3CP3	B path_ Positive LVDS differential data input (Odd data)
13	NC	Do not connect (for AUO test only.)
14	NC	Do not connect (for AUO test only.)
15	GND	Power Ground
16	RxE4CN0	B path_ Negative LVDS differential data input (Even data)
17	RxE4CP0	B path_ Positive LVDS differential data input (Even data)
18	RxE4CN1	B path_ Negative LVDS differential data input (Even data)
19	RxE4CP1	B path_ Positive LVDS differential data input (Even data)
20	RxE4CN2	B path_ Negative LVDS differential data input (Even data)
21	RxE4CP2	B path_ Positive LVDS differential data input (Even data)
22	GND	Power Ground
23	RxE4CCLKN	B path_ Negative LVDS differential clock input (Even clock)
24	RxE4CCLKP	B path_ Positive LVDS differential clock input (Even clock)
25	GND	Power Ground
26	RxE4CN3	B path_ Negative LVDS differential data input (Even data)
27	RxE4CP3	B path_ Positive LVDS differential data input (Even data)
28	NC	Do not connect (for AUO test only.)
29	NC	Do not connect (for AUO test only.)
30	GND	Power Ground
31	NC	Do not connect (for AUO test only.)
32	NC	Do not connect (for AUO test only.)
33	GND	Power Ground
34	GND	Power Ground
35	GND	Power Ground
36	VDD	Power +5V
37	VDD	Power +5V
38	VDD	Power +5V
39	VDD	Power +5V
40	VDD	Power +5V

## 3.3 Electrical Characteristics

### 3.3.1 Absolute Maximum Rating

Permanent damage may occur if exceeding the following maximum rating.



Symbol	Description	Min	Max	Unit	Remark
VDD	Power Supply Input Voltage	GND-0.3	6.0	[Volt]	Ta=25°C

### 3.3.2 Recommended Operating Condition

Symbol	Description	Min	Typ	Max	Unit	Remark
VDD	Power supply Input voltage	4.5	5.0	5.5	[Volt]	
IDD	Power supply Input Current (RMS)	-	0.8	0.96	[A]	VDD= 5.0V, Black Pattern, Fv=60Hz
			1.45	1.74	[A]	VDD= 5.0V, Black Pattern, Fv=144Hz
PDD	VDD Power Consumption	-	4	4.8	[Watt]	VDD= 5.0V, Black Pattern, Fv=60Hz
			7.25	8.7	[Watt]	VDD= 5.0V, Black Pattern, Fv=144Hz
IRush	Inrush Current	-	-	3.0	[A]	<b>Note 3-1</b>
VDDrp	Allowable VDD Ripple Voltage	-	-	500	[mV]	VDD= 5.0V, Black Pattern, Fv=75Hz

**Note 3-1:** Inrush Current measurement:


Test circuit:




The duration of VDD rising time: 470us.

## 3.4 Signal Characteristics

### 3.4.1 LCD Pixel Format



### 3.4.2 LVDS Data Format



**Note 3-2:**

- O1 and O3 = "Odd Pixel Data" E2 and E4 = "Even Pixel Data"
- Refer to 3.4.1 LCD pixel format, the 1st data is O1 (Odd Pixel Data), the 2nd data is E2 (Even Pixel Data), the 3rd data is O3 (Even Pixel Data), the 4th data is E4 (Even Pixel Data), and the last data is 1920 (Even Pixel Data).

## 3.4.3 Color versus Input Data

The following table is for color versus input data (8bit). The higher the gray level, the brighter the color.

Color	Gray Level	Color Input Data																								Remark
		RED data ( <b>MSB</b> :R7, <b>LSB</b> :R0)								GREEN data ( <b>MSB</b> :G7, <b>LSB</b> :G0)								BLUE data ( <b>MSB</b> :B7, <b>LSB</b> :B0)								
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0	
Black	-	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
White	-	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
Gray 127	-	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	
Red	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	L255	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Green	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	L255	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	
Blue	L0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	Black
	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	:	
	L255	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	


## 3.4.4 LVDS Specification

### a. DC Characteristics:

LVDS Receiver Differential Input					
Symbol	Parameter	Min.	Max.	Unit	Condition
$R_{xVTH}$	Differential input high threshold voltage		+0.1	V	$R_{xVCM} = 1.2V$
$R_{xVTL}$	Differential input low threshold voltage	-0.1		V	
$R_{xVIN}$	Input voltage range (singled-end)	0	2.4	V	
$R_{xVCM}$	Differential input common mode voltage	$ V_{ID} /2$	$2.4 -  V_{ID} /2$	V	
$ V_{ID} $	Differential input voltage	0.1	0.6	V	
$R_{V_{xIIZ}}$	Differential input leakage current	-10	+10	$\mu A$	

### LVDS Signal Waveform:


Use RxOCLK- & RxOCLK+ as example.





## b. AC Characteristics:

Symbol	Description	Min	Max	Unit	Remark
$F_{DEV}$	Maximum deviation of input clock frequency during Spread Spectrum	-	$\pm 3$	%	
$F_{MOD}$	Maximum modulation frequency of input clock during Spread Spectrum	-	200	KHz	



$F_{clk}$ : LVDS Clock Frequency

## 3.4.5 Input Timing Specification

It only support DE mode, and the input timing are shown as the following table.

Symbol	Description		Min.	Typ.	Max.	Unit	Remark
Tv	Vertical Section	Period	1098	1130	3000	Th	
Tdisp (v)		Active	1080	1080	1080	Th	
Tblk (v)		Blanking	18	50	1920	Th	
Fv		Frequency	50	120	144	Hz	
Th	Horizontal Section	Period	510	560	715	Tclk	
Tdisp (h)		Active	480	480	480	Tclk	
Tblk (h)		Blanking	30	80	235	Tclk	
Fh		Frequency	50	136	191	KHz	<b>Note 3-3</b>
Tclk	LVDS Clock	Period	10.3	13.2	35.7	ns	1/Fclk
Fclk		Frequency	28	75.9	97.2	MHz	<b>Note 3-4</b>

※ For 2D mode(FHD), the suggestion in 144Hz frame rate: Tv=1098 Th , and Th=520 Tclk

※ For 3D mode(FHD), the suggestion in 120Hz frame rate: Tv=1588 Th , and Th=510 Tclk

**Note 3-3:** The equation is listed as following. Please don't exceed the above recommended value.

$$Fh (\text{Min.}) = Fclk (\text{Min.}) / Th (\text{Min.});$$

$$Fh (\text{Typ.}) = Fclk (\text{Typ.}) / Th (\text{Typ.});$$

$$Fh (\text{Max.}) = Fclk (\text{Max.}) / Th (\text{Min.});$$


**Note 3-4:** The equation is listed as following. Please don't exceed the above recommended value.

$$Fclk (\text{Min.}) = Fv (\text{Min.}) \times Th (\text{Min.}) \times Tv (\text{Min.});$$

$$Fclk (\text{Typ.}) = Fv (\text{Typ.}) \times Th (\text{Typ.}) \times Tv (\text{Typ.});$$


$$Fclk (\text{Max.}) = Fv (\text{Max.}) \times Th (\text{Typ.}) \times Tv (\text{Typ.});$$

## 3.4.6 Input Timing Diagram



## 3.5 Power ON/OFF Sequence

VDD power, LVDS signal and backlight on/off sequence are as following. LVDS signals from any system shall be Hi-Z state when VDD is off.



Power Sequence Timing

Symbol	Value			Unit	Remark
	Min.	Typ.	Max.		
T1	0.5	-	10	[ms]	
T2	0	-	50	[ms]	
T3	500	-	-	[ms]	
T4	100	-	-	[ms]	
T5	0		50	[ms]	<b>Note 3-5</b> <b>Note 3-6</b>
T6	0	-	150	[ms]	<b>Note 3-6</b>
T7	1000	-	-	[ms]	


**Note 3-5 :** Recommend setting T5 = 0ms to avoid electronic noise when VDD is off.

**Note 3-6 :** During T5 and T6 period , please keep the level of input LVDS signals with Hi-Z state.

## 4 Backlight Unit

### 4.1 Block Diagram

The following shows the block diagram of the 27 inch Backlight Unit. And it includes 52 pcs LED in the LED light bar. (4 strings and 13 pcs LED of one string).





## 4.2 Interface Connection

### 4.2.1 Connector Type

Backlight Connector	Manufacturer	ENTERY
	Part Number	3707K-S06N-21R
Mating Connector	Manufacturer	ENTERY
	Part Number	H112K-P06N-00B (Non-Locking type) H112K-P06N-03B (Locking type)


### Backlight Connector dimension:

$H \times V \times D = 13.9 \times 3.00 \times 4.25$ ,  $Pitch = 1.0$ (unit = mm)






## Mating Connector dimension:



## 4.2.2 Connector Pin Assignment

Pin#	Symbol	Description	Remark
1	Ch1	LED Current Feedback Terminal (Channel 1)	
2	Ch2	LED Current Feedback Terminal (Channel 2)	
3	V <sub>SLED</sub>	LED Power Supply Voltage Input Terminal	
4	V <sub>SLED</sub>	LED Power Supply Voltage Input Terminal	
5	Ch3	LED Current Feedback Terminal (Channel 3)	
6	Ch4	LED Current Feedback Terminal (Channel 4)	




## 4.3 Electrical Characteristics

### 4.3.1 Absolute Maximum Rating

Permanent damage may occur if exceeding the following maximum rating.

(Ta=25°C)

Symbol	Description	Min	Max	Unit	Remark
Is	LED String Current	0	150	[mA]	100% duty ratio
			300	[mA]	<i>Duty ratio ≤ 10%</i> <i>Pulse time=10 ms</i>
IFp	LED Pulse Forward Current		200	[mA] <b>Note 5</b>	Pulse Width=8~10ms Duty=33% <b>Note 1</b>
			214	[mA] Note 5	Pulse Width=8~10ms Duty=24% <b>Note 2</b>



Duty ratio= (A / B) X 100% ; (A: Pulse time, B: Period)

**Note 1:** Current @33% duty~I=200mA lifetime=30khrs (base on Lextar's measurement,it's vender's limit)

**Note 2:** Current @24% duty~I=214mA lifetime=30khrs (base on Lextar 's measurement,it's vender's limit)

### 4.3.2 Recommended Operating Condition


(Ta=25°C)

Symbol	Description	Min.	Typ.	Max.	Unit	Remark
Is	LED String Current	-	120	132	[mA]	100% duty ratio of LED chip
Vs	LED String Voltage	39	42.9	46.8	[Volt]	Is=120mA @ 100% duty ratio; <b>Note 4-1, Note 4-5</b>
ΔVs	Maximum Vs Voltage Deviation of light bar	-	-	2.6	[Volt]	Is=120mA @ 100% duty ratio; <b>Note 4-2</b>
P <sub>BLU</sub>	LED Light Bar Power Consumption	-	20.6	22.5	[Watt]	<b>Note 4-3</b>
LT <sub>LED</sub>	LED Life Time	30,000	-	-	[Hour]	<b>Note 4-4</b>

**Note 4-1:**  $V_s (\text{Typ.}) = V_F (\text{Typ.}) \times \text{LED No. (one string)}$ ;

a.  $V_F$ : LED chip forward voltage,  $V_F (\text{Min.})=3.0\text{V}$ ,  $V_F (\text{Typ.})=3.3\text{V}$ ,  $V_F (\text{Max.})=3.6\text{V}$

b. The same equation to calculate  $V_s (\text{Min.})$  &  $V_s (\text{Max.})$  for respective  $V_F (\text{Min.})$  &  $V_F (\text{Max.})$ ;



**Note 4-2:**  $\Delta V_s (\text{Max.}) = \Delta V_F \times \text{LED No. (one string)}$ ;

a.  $\Delta V_F$ : LED chip forward voltage deviation; (0.2 V , each Bin of LED  $V_F$ )

**Note 4-3:**  $P_{BLU} (\text{Typ.}) = V_s (\text{Typ.}) \times I_s (\text{Typ.}) \times 4$  ; ( 4 is total String No. of LED Light bar)

$P_{BLU} (\text{Max.}) = V_s (\text{Max.}) \times I_s (\text{Typ.}) \times 4$  ;

**Note 4-4:** Definition of life time:

a. Brightness of LED becomes to 50% of its original value

b. Test condition:  $I_s = 120\text{mA}$  and  $25 \pm 2^\circ\text{C}$  (Room Temperature)

**Note 4-5:** Recommendation for LED driver power design:

Due to there are electrical property deviation in LED & monitor set system component after long time operation. AUO strongly recommend the design value of LED driver board OVP (over voltage protection) should be 10% higher than max. value of LED string voltage ( $V_s$ ) at least.

**Note 4-6:** AUO strongly recommend “Analog Dimming” method for backlight brightness control for Wavy Noise Free. Otherwise, recommend that Dimming Control Signal (PWM Signal) should be synchronized with Frame Frequency.



## 5 Reliability Test

AUO reliability test items are listed as following table. (*Bare Panel only*)

Items	Condition	Remark
Temperature Humidity Bias (THB)	Ta= 50°C , 80%RH, 300hours	
High Temperature Operation (HTO)	Ta= 60°C , 300hours	
Low Temperature Operation (LTO)	Ta= 0°C , 300hours	
High Temperature Storage (HTS)	Ta= 60°C , 300hours	
Low Temperature Storage (LTS)	Ta= -20°C , 300hours	
Vibration Test (Non-operation)	Acceleration: 1.5 Grms Wave: Random Frequency: 10 - 200 Hz Sweep: 30 Minutes each Axis (X, Y, Z)	
Shock Test (Non-operation)	Acceleration: 50 G Wave: Half-sine Active Time: 20 ms Direction: ±X, ±Y, ±Z (one time for each Axis)	
Drop Test	Height: 60 cm, package test	
Thermal Shock Test (TST)	-20°C/30min, 60°C /30min, 100 cycles	<b>Note 5-1</b>
On/Off Test	On/10sec, Off/10sec, 30,000 cycles	
ESD (Electro Static Discharge)	Contact Discharge: ± 15KV, 150pF(330Ω ) 1sec, 8 points, 25 times/ point.	<b>Note 5-2</b>
	Air Discharge: ± 15KV, 150pF(330Ω ) 1sec 8 points, 25 times/ point.	
Altitude Test	Operation:18,000 ft Non-Operation:40,000 ft	

**Note 5-1:** a. A cycle of rapid temperature change consists of varying the temperature from -20°C to 60°C, and back again. Power is not applied during the test.

b. After finish temperature cycling, the unit is placed in normal room ambient for at least 4 hours before power on.

**Note 5-2:** EN61000-4-2, ESD class B: Certain performance degradation allowed

No data lost


Self-recoverable

No hardware failures.



## 6 Shipping Label

The label is on the panel as shown below:



**Note 6-1:** For Pb Free products, AUO will add  for identification.


**Note 6-2:** For RoHS compatible products, AUO will add  for identification.

**Note 6-3:** For China RoHS compatible products, AUO will add  for identification.


**Note 6-4:** The Green Mark will be presented only when the green documents have been ready by AUO Internal Green Team.




## 7 Mechanical Characteristics




## Avoid touching COF position when doing mechanical design



Avoid Touching CDF Position When Doing Mechanical Design



## 8 Packing Specification



### Pallet and shipment information

	Item	Specification			Remark
		Q'ty	Dimension	Weight(kg)	
1	Panel	1	630(H)mm x 368.2(V)mm x 14.1(D)mm	2.86	
2	Cushion	1	-	2.97	
3	Box	1	715(L)mm x 261(W)mm x 455(H)mm	1.43	without Panel & cushion
4	Packing Box	7 pcs/Box	715(L)mm x 261(W)mm x 455(H)mm	24.42	with panel & cushion
5	Pallet	1	1070(L)mm x 740(W)mm x 138(H)mm	12	
6	Pallet after Packing	8 boxes/pallet	1070(L)mm x 740(W)mm x 138(H)mm	262.48	