

**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF BOE HF AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE HF AND MUST BE RETURNED TO BOE HF UPON ITS REQUEST

SPEC. NUMBER

PRODUCT GROUP

Rev.

ISSUE DATE

PAGE

TFT-LCD

P0

2016.4.8

1

OF 34

PRODUCT SPECIFICATION FOR APPROVAL

Model Name	NV156QUM-N43
Description	15.6UHD color TFT-LCD with LED backlight / LR surface
Prepared by	
Checked by	
Approved by	

Customer

Lenovo

_____	_____
_____	_____
_____	_____

Please return one copy for confirmation with your signature and comments



PROPRIETARY NOTE

THIS SPECIFICATION IS THE PROPERTY OF BOE HF AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE HF AND MUST BE RETURNED TO BOE HF UPON ITS REQUEST

SPEC. NUMBER

PRODUCT GROUP

Rev.

ISSUE DATE

PAGE

TFT-LCD

P0

2016.4.8

2 OF 34

NV156QUM-N43

Preliminary Product Specification

Rev. P1

HEFEI BOE OPTOELECTRONICS TECHNOLOGY

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 4 OF 34

Contents


No.	Items	Page
1.0	General Description	5
2.0	Absolute Maximum ratings	7
3.0	Electrical specifications.	8
4.0	Optical specifications.	11
5.0	Interface Connection	16
6.0	Signal Timing Specification	19
7.0	Input Signals, Display Colors & Gray Scale of Colors	21
8.0	Power Sequence	22
9.0	Connector description	23
10.0	Mechanical Characteristics	24
11.0	Reliability Test	25
12.0	Handling & Cautions.	25
13.0	Label	26
14.0	Packing information	28
15.0	Mechanical Outline Dimension	29
16.0	EDID Table	31

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 5 OF 34	

1.0 GENERAL DESCRIPTION

1.1 Introduction

NV156QUM-N43 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 15.6 inch diagonally measured active area with Ultra-HD resolutions (3840 horizontal by 2160 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical Stripe and this module can display 16.7M colors. The TFT-LCD panel used for this module is a low reflection and higher color type. Therefore, this module is suitable for Notebook PC. The LED Driver for back-light driving is built in this model. All input signals are eDP interface compatible.



1.2 Features

- 4 lane eDP Interface with 5.4Gbps Link Rates
- Thin and light weight
- 8-bit color depth, display 16.7M colors
- Single LED Lighting Bar. (Bottom side/Horizontal Direction)
- Data enable signal mode
- Green Product (RoHS & Halogen free product)
- On board LED Driving circuit
- Low driving voltage and low power consumption
- On board EDID chip

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 6 OF 34	

1.3 Application

- Notebook PC (Wide type)

1.4 General Specification

The followings are general specifications at the model NV156QUM-N43. (listed in Table 1.)

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	345.6(H) × 194.4(V)	mm	
Number of pixels	3840 (H) ×	pixels	
Pixel pitch	0.09(H) × 0.09 (V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	16.7M	colors	
Display mode	Normally Black		
Dimensional outline	358.62 (H) 208.06(V) × 3.2 (D:max)	mm	
Weight	370 (max)	g	
Surface treatment	LR		
Back-light	Bottom edge side, 1-LED Lighting Bar type		Note 1
Power consumption	P _D : 2.0 max	W	Note 2
	P _{BL} : 5.0 max	W	
	P _{total} : 7.0 max	W	

Notes : 1. LED Lighting Bar (72*LED Array)

Notes: 2. Typical Measurement Condition : Mosaic pattern

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 7 OF 34

2.0 ABSOLUTE MAXIMUM RATINGS


The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings >

Ta=25+/-2°C

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	-0.3	4.0		Note 1
Logic Supply Voltage	V _{IN}	V _{SS} -0.3	V _{DD} +0.3	V	
Operating Temperature	T _{OP}	0	+50	°C	Note 2
Storage Temperature	T _{ST}	-20	+60	°C	

- Notes : 1. Permanent damage to the device may occur if maximum values are exceeded functional operation should be restricted to the condition described under normal operating conditions.
2. Temperature and relative humidity range are shown in the figure below.
95 % RH Max. (40 °C ≥ Ta)
Maximum wet - bulb temperature at 39 °C or less. (Ta > 40 °C) No condensation.



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 8 OF 34	

3.0 ELECTRICAL SPECIFICATIONS


3.1 Electrical Specifications

< Table 3. Electrical specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	3.0	3.3	3.6	V	Note 1
Permissible Input Ripple Voltage	V _{RF}	-	100	-	mV	At V _{DD} = 3.3V
Power Supply Current	I _{DD}	-	600	1200	mA	Note 1
Positive-going Input Threshold Voltage	V _{IT+}	-	-	100	mV	V _{cm} = 1.2V typ.
Negative-going Input Threshold Voltage	V _{IT-}	-100	-	-	mV	
Differential Input Voltage	V _{ID}	200	-	600	mV	
Power Consumption	P _D	-	1.8	2.0	W	Note 1
	P _{BL}	-	4.84	5.0	W	Note 2
	P _{total}	-	6.64	7.0	W	

Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.
The current draw and power consumption specified is for 3.3V at 25°C.
Pattern type : Mosaic 32x32



2. Calculated value for reference (V_{LED} × I_{LED})

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 9 OF 34	

3.2 Backlight Unit

< Table 4. LED Driving guideline specifications >


Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks	
LED Forward Voltage		V _F	-	-	3.0	V	-
LED Forward Current		I _F	-	20.4	-	mA	-
LED Power Consumption		P _{LED}		-	5.0	W	Note 1
LED Life-Time		N/A	15,000	-	-	Hour	I _F = 20.4mA
Power supply voltage for LED Driver		V _{LED}	5	12	21	V	
EN Control Level	Backlight on		2.1		5.0	V	
	Backlight off		0		0.8	V	
PWM Control Level	PWM High Level		2.1		5.0	V	
	PWM Low Level		0		0.8	V	
PWM Control Frequency		F _{PWM}	200	-	10,000	Hz	
Duty Ratio		-	1	-	100	%	

Notes : 1. Power supply voltage 12V for LED Driver, Driver efficiency 87%,
Calculator Value for reference $I_F \times V_F \times 72 / 0.87 = P_{LED}$
2. The LED Life-time define as the estimated time to 50% degradation of initial luminous.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 10 OF 34

3.3 LED structure



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 11 OF 34	

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25 \pm 2^\circ\text{C}$) with the equipment of Luminance meter system (Goniometer system and TOPCON BM-5) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and ϕ equal to 0° . We refer to $\theta\phi=0$ ($=\theta_3$) as the 3 o'clock direction (the "right"), $\theta\phi=90$ ($=\theta_{12}$) as the 12 o'clock direction ("upward"), $\theta\phi=180$ ($=\theta_9$) as the 9 o'clock direction ("left") and $\theta\phi=270$ ($=\theta_6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or ϕ , the center of the measuring spot on the Display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be $3.3 \pm 0.3\text{V}$ at 25°C . Optimum viewing angle direction is 6 'clock.

4.2 Optical Specifications

<Table 5. Optical Specifications>

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	Θ_3	CR > 10		85	-	Deg.	Note 1
		Θ_9			85	-	Deg.	
	Vertical	Θ_{12}			85	-	Deg.	
		Θ_6			85	-	Deg.	
Luminance Contrast ratio		CR	$\Theta = 0^\circ$	-	1000			Note 2
Luminance of White	5 Points	Y_w	$\Theta = 0^\circ$ ILED = 20.4mA	255	300	345	cd/m ²	Note 3
White Luminance uniformity	5 Points	$\Delta Y5$		80	-	-		Note 4
	13 Points	$\Delta Y13$		60	-	-		
White Chromaticity		x_w	$\Theta = 0^\circ$	0.283	0.313	0.343		Note 5
		y_w		0.299	0.329	0.359		
Reproduction of color	Red	x_R	$\Theta = 0^\circ$	-0.03	0.64	+0.03		
		y_R			0.33			
	Green	x_G			0.21			
		y_G			0.71			
	Blue	x_B			0.15			
		y_B			0.06			
Gamut				94	100	-	%	Adobe
Response Time (Rising + Falling)		T _{RT}	Ta= 25° C $\Theta = 0^\circ$	-	35	40	ms	Note 6
Cross Talk		CT	$\Theta = 0^\circ$	-	-	2.0	%	Note 7

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 12 OF 34	

Notes :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).

2. Contrast measurements shall be made at viewing angle of $\Theta = 0$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state .

(see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

4. The White luminance uniformity on LCD surface is then expressed as : $\Delta Y = \text{Minimum Luminance of 5(or 13) points} / \text{Maximum Luminance of 5(or 13) points}$.
(see FIGURE 2 and FIGURE 3).

5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.


6. The electro-optical response time measurements shall be made as FIGURE 4 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_r , and 90% to 10% is T_d .

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark.
(See FIGURE 5).

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 13 OF 34	


4.3 Optical measurements

Figure 1. Measurement Set Up



Optical characteristics measurement setup


Figure 2. White Luminance and Uniformity Measurement Locations (5 points)



Center Luminance of white is defined as luminance values of center 5 points across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.


BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 14 OF 34	

Figure 3. Uniformity Measurement Locations (13 points)



The White luminance uniformity on LCD surface is then expressed as : $\Delta Y5$ = Minimum Luminance of five points / Maximum Luminance of five points (see FIGURE 2) , $\Delta Y13$ = Minimum Luminance of 13 points /Maximum Luminance of 13 points (see FIGURE 3).


Figure 4. Response Time Testing



The electro-optical response time measurements shall be made as shown in FIGURE 4 by switching the “data” input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_d and 90% to 10% is T_r .

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 15 OF 34	

Figure 5. Cross Modulation Test Description



Where:

Y_A = Initial luminance of measured area (cd/m²)

Y_B = Subsequent luminance of measured area (cd/m²)

The location measured will be exactly the same in both patterns

Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark (Refer to FIGURE 5).

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 16 OF 34	

5.0 INTERFACE CONNECTION.

5.1 Electrical Interface Connection


The electronics interface connector is STM. The mating connector part number is STM MSAK24025P40. The connector interface pin assignments are listed in Table 6.

<Table 6. Pin Assignments for the Interface Connector>

Terminal PIN No.	Symbol	Functions Description
1	G_Sync	G_Sync
2	H_GND	eDP lane Up to 5.4G
3	Lane3_N	
4	Lane3_P	
5	H_GND	
6	Lane2_N	
7	Lane2_P	
8	H_GND	
9	Lane1_1N	
10	Lane1_1P	
11	H_GND	
12	Lane1_0N	
13	Lane1_0P	
14	H_GND	
15	AUX_CH_P	
16	AUX_CH_N	
17	H_GND	LCD Logic Power (3.3±0.3V)
18	LCD_VCC	
19	LCD_VCC	
20	LCD_VCC	
21	LCD_VCC	BIST (IN Port)
22	LCD_Self_Test(BIST)	
23	LCD_GND	
24	LCD_GND	
25	LCD_GND	Logic GND (Connect to GND in Module)
26	LCD_GND	
27	HPD	
28	BL_GND	
29	BL_GND	BLU GND (Connect to GND in Module)
30	BL_GND	
31	BL_GND	
32	BL_ENABLE	
33	BL_PWM	IN Port
34	H_sync	IN Port
35	NC	H_sync (OUT Port)
36	BL_PWR	NC
37	BL_PWR	BLU Power (5~21V)
38	BL_PWR	
39	BL_PWR	
40	Color Engine	
		NC

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 17 OF 34	


5-2. eDP Interface



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 18 OF 34	

5.3 Data Input Format

<Table 6. Pin Assignments for the Interface Connector>



5.4 Back-light & LCM Interface Connection

Interface Connector: STM MSK24022P12

<Table 7. Pin Assignments for the BLU & LCM Connector>

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	Vout	LED anode connection	7	LED3	LED cathode connection
2	Vout	LED anode connection	8	LED4	LED cathode connection
3	Vout	LED anode connection	9	LED5	LED cathode connection
4	NC	No Connection	10	LED6	LED cathode connection
5	LED1	LED cathode connection	11	LED7	LED cathode connection
6	LED2	LED cathode connection	12	LED8	LED cathode connection

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 19 OF 34	

6.0 SIGNAL TIMING SPECIFICATION

6.1 The NV156QUM-N81 is operated by the DE only.

Item		Symbols	Min	Typ	Max	Unit
Clock	Frequency	1/Tc	355.52	533.25	586.6	MHz
	High Time	Tch	-	4/7Tc	-	Tc
	Low Time	Tcl	-	3/7Tc	-	Tc
Frame Period		Tv	3900	4000	4050	lines
			-	60	-	Hz
			25	16.67	15.15	ms
Vertical Display Period		Tvd	-	2160	-	lines
One line Scanning Period		Th	2180	2222	2240	clocks
Horizontal Display Period		Thd	-	3840	-	clocks

Note : This module can support low frame refresh rate 50Hz&40Hz.


BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 20 OF 34	

6.2 eDP Rx Interface Timing Parameter

The specification of the eDP Rx interface timing parameter is shown in Table 8.

<Table 8. eDP Rx Interface Timing Specification>

Item	Symbol	Min	Typ	Max	Unit	Remark
Spread spectrum clock	SSC		0.5		%	
Differential peak-to-peak input voltage at package pins	VRX-DIFFp-p	100	0	1320	mV	
Rx input DC common mode voltage	VRX_DC_CM	-	GND	-	V	
Differential termination resistance	RRX-DIFF	80	-	100	Ω	
Single-ended termination resistance	RRX-SE	40	-	60	Ω	
Rx short circuit current limit	IRX_SHORT	-	-	50	mA	
Intra-pair skew at Rx package pins (HBR) RX intra-pair skew tolerance at HBR	LRX_SKEW_INTRA_PAIR HBR2	-	-	50	ps	



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 21 OF 34	


7.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

	Colors & Gray scale	Data signal																	
		R0	R1	R2	R3	R4	R5	G0	G1	G2	G3	G4	G5	B0	B1	B2	B3	B4	B5
Basic colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Light Blue	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Purple	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray scale of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△ ▽	↑ ↓						↑ ↓						↑ ↓					
	Brighter	1	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	▽	0	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Gray scale of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0
	△ ▽	↑ ↓						↑ ↓						↑ ↓					
	Brighter	0	0	0	0	0	0	1	0	1	1	1	1	0	0	0	0	0	0
	▽	0	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Gray scale of Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0
	△ ▽	↑ ↓						↓ ↑						↑ ↓					
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
Gray scale of White & Black	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0
	Darker	0	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0
	▽	↑ ↓						↑ ↓						↑ ↓					
	Brighter	1	0	1	1	1	1	1	0	1	1	1	1	1	0	1	1	1	1
	▽	0	1	1	1	1	1	0	1	1	1	1	1	0	1	1	1	1	1
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 22 OF 34

8.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



- 0.5ms ≤ T1 ≤ 10 ms
 - 0ms ≤ T2 ≤ 200 ms
 - 0ms ≤ T3 ≤ 200 ms
 - 0ms ≤ T13
 - 0ms ≤ T14
 - 0ms ≤ T17
- 0ms ≤ T7 ≤ 50ms
 - 0ms ≤ T10 ≤ 500 ms
 - 0 ms ≤ T11 ≤ 20 ms
 - 150ms ≤ T12
 - 0ms ≤ T15
 - 0ms ≤ T16
 - 0ms ≤ T18

Notes:

- When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
- Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 23 OF 34

9.0 Connector Description

Physical interface is described as for the connector on LCM.

These connectors are capable of accommodating the following signals and will be following components.

9.1 TFT LCD Module

Connector Name /Description	For Signal Connector
Manufacturer	STM
Type/ Part Number	MSAK24025P40
Mating housing/ Part Number	I-PEX 20455-040E

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 24 OF 34

10.0 MECHANICAL CHARACTERISTICS

10.1 Dimensional Requirements

FIGURE 6 shows mechanical outlines for the model NV156QUM-N81
Other parameters are shown in Table 9.

<Table 9. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	345.6 (H) × 194.4 (V)	Mm
Number of pixels	3840 (H) X 2160 (V) (1 pixel = R + G + B dots)	-
Pixel pitch	0.09(H) × 0.09 (V)	mm
Pixel arrangement	RGB Vertical stripe	
Display colors	16.7M	
Display mode	Normally Black	
Dimensional outline	358.62 (H)×208.06(V)×3.2 (D:max)	mm
Weight	370 (max)	g

10.2 Mounting

See FIGURE 6.

10.3 LR and Polarizer Hardness.

The surface of the LCD has an LR coating to reduce reflection.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 25 OF 34	

11.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 10. Reliability test>

No	Test Items	Conditions
1	High temperature storage test	Ta = 60 °C, 240 hrs
2	Low temperature storage test	Ta = -20 °C, 240 hrs
3	High temperature & high humidity operation test	Ta = 50 °C, 80%RH, 240 hrs
4	High temperature operation test	Ta = 50 °C, 240 hrs
5	Low temperature operation test	Ta = 0 °C, 240 hrs
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle
7	Vibration test (non-operating)	1.5G, 10~500Hz, Half Sine X,Y,Z / Sweep rate : 1 hour
8	Shock test (non-operating)	220G, Half Sine Wave 2msec ± X, ± Y, ± Z Once for each direction
9	Electro-static discharge test (non-operating)	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV

12.0 HANDLING & CAUTIONS

(1) Cautions when taking out the module

- Pick the pouch only, when taking out module from a shipping package.

(2) Cautions for handling the module

- As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
- As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
- As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
- Do not pull the interface connector in or out while the LCD module is operating.
- Put the module display side down on a flat horizontal plane.
- Handle connectors and cables with care.

(3) Cautions for the operation

- When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
- Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 26 OF 34	

(4) Cautions for the atmosphere

- Dew drop atmosphere should be avoided.
- Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.

(5) Cautions for the module characteristics


- Do not apply fixed pattern data signal to the LCD module at product aging.
- Applying fixed pattern for a long time may cause image sticking.

(6) Other cautions

- Do not disassemble and/or re-assemble LCD module.
- Do not re-adjust variable resistor or switch etc.
- When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

13.0 LABEL

(1) Product label



Remark:

标签尺寸: 80mm × 25mm, 厚度0.08mm

贴覆PCB 左下角

1. FG-CODE: NV156QUM-N43
2. MDL ID 条纹码
3. MDL ID
4. 8S 码对应条纹码
5. 8S码
6. P/N 码: SD10K93475
7. FRU 码: 00NY431

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 27 OF 34

(2) Box label

Label Size: 109.5 mm (L) × 55 mm (W)

Contents

Model: NV156QUM-N43

Q'ty: Module Q'ty in one box

Serial No.: Box Serial No. See next figure for detail description.

Date: Packing Date

Internal use of Product


BOE BOE Technology Group Co., Ltd.

MODEL: NV156QUM-N43 ①


QTY: XX ②

SERIAL NO: XXXXXXXXXXXX ③

DATE: 20XX / XX / XX ④



3940 ⑥



1. FG-CODE
2. Box 产品数量
3. Box ID, 编码规则如下
4. Box Packing 日期
5. FG-CODE 后四位


SERIA NO	1	2	3	4	5	6	7	8	9	10	11	12	13
code	X	X	X	X	X	X	X	X	X	X	X	X	X
Description	GBN		Grade	Line	Year		Month	Rev	Serial No.				

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 28 OF 34	

14.0 PACKING INFORMATION

14.1 Packing order


- 将1pcs MDL 水平放入Tray



- 将26pcs PET Tray 平放入PE Bag

顶部1pcs 空Tray


- Tray 不旋转码放



- 每个Pallet上放3层Box1层4箱,共计12ea Box

- Pallet外进行缠膜包装


- 容量: 300pcs/Pallet



- 将PET Tray堆码后平放入Inner Box

上下放置EPE Cover

- 容量 : 25pcs/Inner Box




14.2 Notes

- Box Dimension: 500mm(W) x 400mm(D) x 300mm(H)
- Package Quantity in one Box: 25pcs
- Total Weight: TBD kg

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification	PAGE 30 OF 34	

Figure 7. TFT-LCD Module Outline Dimensions (Rear view)




BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 31 OF 34

16.0 EDID Table

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
00	Header	00	0		0	EDID Header
01		FF	255		255	
02		FF	255		255	
03		FF	255		255	
04		FF	255		255	
05		FF	255		255	
06		FF	255		255	
07		00	0		0	
08	ID Manufacturer Name	09	9		BOE	ID = BOE
09		E5	229			
0A	ID Product Code	CD	205		1741	ID = 1741
0B		06	6			
0C	32-bit serial No.	00	0		0	
0D		00	0		0	
0E		00	0		0	
0F		00	0		0	
10	Week of manufacture	01	1		1	
11	Year of Manufacture	1A	26		2016	Manufactured in 2016
12	EDID Structure Ver.	01	1		1	EDID Ver 1.0
13	EDID revision #	04	4		4	EDID Rev. 0.4
14	Video input definition	A5	165		-	Refer to right table
15	Max H image size	22	34		35	34.56 cm (Approx)
16	Max V image size	13	19		19	19.44 cm (Approx)
17	Display Gamma	78	120		2.2	Gamma curve = 2.2
18	Feature support	02	2		-	Refer to right table
19	Red/Green low bits	CF	207		-	Red / Green Low Bits
1A	Blue/White low bits	50	80		-	Blue / White Low Bits
1B	Red x high bits	A3	163	655	0.640	Red (x) = 10100011 (0.64)
1C	Red y high bits	54	84	336	0.329	Red (y) = 01010100 (0.329)
1D	Green x high bits	35	53	215	0.210	Green (x) = 00110101 (0.21)
1E	Green y high bits	B5	181	727	0.710	Green (y) = 10110101 (0.71)
1F	Blue x high bits	26	38	153	0.150	Blue (x) = 00100110 (0.15)
20	Blue y high bits	0F	15	61	0.060	Blue (y) = 00001111 (0.06)
21	White x high bits	50	80	320	0.313	White (x) = 01010000 (0.313)
22	White y high bits	54	84	336	0.329	White (y) = 01010100 (0.329)
23	Established timing 1	00	0		-	Refer to right table
24	Established timing 2	00	0		-	

BOE	PRODUCT GROUP				REV	ISSUE DATE
	TFT- LCD PRODUCT				P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification					PAGE 32 OF 34
Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
25	Established timing 3	00	0		-	
26	Standard timing #1	01	1			Not Used
27		01	1			
28	Standard timing #2	01	1			Not Used
29		01	1			
2A	Standard timing #3	01	1			Not Used
2B		01	1			
2C	Standard timing #4	01	1			Not Used
2D		01	1			
2E	Standard timing #5	01	1			Not Used
2F		01	1			
30	Standard timing #6	01	1			Not Used
31		01	1			
32	Standard timing #7	01	1			Not Used
33		01	1			
34	Standard timing #8	01	1			Not Used
35		01	1			
36	Detailed timing/monitor descriptor #1	4D	77		533.3	533.25MHz Main clock
37		D0	208			
38		00	0		3840	Hor Active = 3840
39		A0	160		160	Hor Blanking = 160
3A		F0	240		-	4 bits of Hor. Active + 4 bits of Hor. Blanking
3B		70	112		2160	Ver Active = 2160
3C		3E	62		62	Ver Blanking = 62
3D		80	128		-	4 bits of Ver. Active + 4 bits of Ver. Blanking
3E		30	48		48	Hor Sync Offset = 48
3F		20	32		32	H Sync Pulse Width = 32
40		35	53		3	V sync Offset = 3 line
41		00	0		5	V Sync Pulse width : 5 line
42		59	89		346	Horizontal Image Size = 345.6 mm (Low 8 bits)
43		C2	194		194	Vertical Image Size = 194.4 mm (Low 8 bits)
44		10	16		-	4 bits of Hor Image Size + 4 bits of Ver Image Size
45		00	0		0	Hor Border (pixels)
46		00	0		0	Vertical Border (Lines)
47		1A	26		-	Refer to right table

	PRODUCT GROUP				REV	ISSUE DATE
	TFT- LCD PRODUCT				P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification					PAGE 33 OF 34
Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
48	Detailed timing/monitor descriptor #2	00	0		0	0MHz Main clock
49		00	0			
4A		00	0		0	Hor Active = 0
4B		00	0		0	Hor Blanking = 0
4C		00	0		-	4 bits of Hor. Active + 4 bits of Hor. Blanking
4D		00	0		0	Ver Active = 0
4E		00	0		0	Ver Blanking = 0
4F		00	0		-	4 bits of Ver. Active + 4 bits of Ver. Blanking
50		00	0		0	Hor Sync Offset = 0
51		00	0		0	H Sync Pulse Width = 0
52		00	0		0	V sync Offset = 0 line
53		00	0		0	V Sync Pulse width : 0 line
54		00	0		0	Horizontal Image Size = 0 mm (Low 8 bits)
55		00	0		0	Vertical Image Size = 0 mm (Low 8 bits)
56		00	0		-	4 bits of Hor Image Size + 4 bits of Ver Image Size
57		00	0		0	Hor Border (pixels)
58		00	0		0	Vertical Border (Lines)
59		00	0		-	Refer to right above table
5A	Detailed timing/monitor descriptor #3	00	0			Indicates descriptor #3 is a display Descriptor
5B		00	0			
5C		00	0			Reserved
5D		FE	254			Tag : ASCII String
5E		00	0			Reserved
5F		42	66		B	Manufacture name : BOEHF
60		4F	79		O	
61		45	69		E	
62		20	32			
63		48	72		H	
64		46	70		F	
65		0A	10			
66		20	32			
67		20	32			
68		20	32			
69		20	32			
6A		20	32			
6B		20	32			

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	P0	2016.04.08
SPEC. NUMBER	SPEC. TITLE NV156QUM-N43 Preliminary Product Specification		PAGE 34 OF 34

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
6C	Detailed timing/monitor descriptor #4	00	0			Indicates descriptor #4 is a display Descriptor
6D		00	0			
6E		00	0			Reserved
6F		FE	254			Tag : ASCII String
70		00	0			Reserved
71		4E	78		N	Model name : NV156QUM-N43
72		56	86		V	
73		31	49		1	
74		35	53		5	
75		36	54		6	
76		51	81		Q	
77		55	85		U	
78		4D	77		M	
79		2D	45		-	
7A		4E	78		N	
7B		34	52		4	
7C		33	51		3	
7D		0A	10			
7E	Extension flag	00	0		1	0 : 1個EDID ; N-1 : N個EDID
7F	Checksum	DA	218	218	-	