SAMSUNG ELECTRONICS

Customer :   **DATE : Dec. 20, 2007**

SAMSUNG TFT-LCD

MODEL **: LTA320AB02**

The Information Described in this Specification is Preliminary and can be changed without prior notice

NOTE :

Customer's *Approval*		APPROVAED BY *Kyunghwan Ko*	DATE Dec. 20, 2007
SIGNATURE	DATE	PREPARED BY *Byungsun Park*	DATE Dec. 20, 2007

LCD Business

Samsung Electronics Co . , LTD.

Contents

Revision History

Date	Rev. No	Page	Summary
Dec. 20, 2007	000	all	First issued

MODEL	LTA320AB02	Doc. No	06-000-G-071220	Page	3/26

General Description

Description

LTA320AB02 is a color active matrix liquid crystal display (LCD) that uses amorphous silicon TFT(Thin Film Transistor) as switching components. This model is composed of a TFT LCD panel, a driver circuit and a back light unit. The resolution of a 32.0" is 1366 x 768 and this model can display up to 16.7 million colors with wide viewing angle of 89° or higher in all directions. This panel is intended to support applications to provide a excellent performance for Flat Panel Display such as Home-alone Multimedia TFT-LCD TV and High Definition TV.

Features

- RoHS compliance (Pb-free)
- High contrast & aperture ratio with wide color gamut
- PVA(Patterned Vertical Align) mode
- Wide viewing angle (±178°)
- High speed response
- HD resolution (16:9)
- Low Power consumption
- Direct Type 12 CCFLs (Cold Cathode Fluorescent Lamp)
- DE(Data Enable) mode
- LVDS (Low Voltage Differential Signaling) interface (1pixel/clock)

General Information

Items	Specification	Unit	Note
Module Size	$760.0(H_{TYP})$ x $450.0(V_{TYP})$	mm	±1.0mm
	$50.5(D_{MAX})$		
Weight	7,500 (max)	g	
Pixel Pitch	0.51075(H) x 0.51075(W)	mm	
Active Display Area	697.6845(H) x 392.256(V)	mm	
Surface Treatment	Haze 14% , Hard-coating (3H)	-	
Display Colors	8 bit - 16.7M	colors	
Number of Pixels	1366 x 768	pixel	
Pixel Arrangement	RGB Horizontal stripe	-	
Display Mode	Normally Black	-	
Luminance of White	450 (Typ.)	cd/m^2	

1. Absolute Maximum Ratings

If the condition exceeds maximum ratings, it can cause malfunction or unrecoverable damage to the device.

Item		Symbol	Min.	Max.	Unit	Note
Power Supply Voltage		V_{DD}	10.8	13.2	V	(1)
Storage temperature		T_{STG}	-20	60	℃	(2)
Glass surface temperature (Operation)	Center	T_{OPR}	0	50	℃	(2)
Shock (non - operating)		S_{nop}	-	50	G	(3)
Vibration (non - operating)		V_{nop}	-	1.5	G	(4)

Note (1) Ta= 25 $\pm$ 2 °C
    (2) Temperature and relative humidity range are shown in the figure below.
       a. 90 % RH Max. (Ta ≤ 39 °C)
       b. Relative Humidity is 90% or less. (Ta > 39 °C)
       c. No condensation
    (3) 11ms, sine wave, one time for $\pm$X, $\pm$Y, $\pm$Z axis
    (4) 10-300 Hz, Sweep rate 10min, 30min for X,Y,Z axis

Relative Humidity(%RH)

(39, 90)

Operating Range

(50, 50.4)

(60, 27.7)

Storage Range

Temperature(℃)

Fig. Temperature and Relative humidity range

2. Optical Characteristics

The optical characteristics should be measured in a dark room or equivalent.
Measuring equipment : TOPCON RD-80S,TOPCON SR-3, ELDIM EZ-Contrast

(Ta = 25 ± 2°C, VDD=12V, fv= 60Hz, f_{DCLK}=78MHz)

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Contrast Ratio (Center of screen)		C/R		2,000	3,000	-		(1) SR-3
Response Time	G-to-G (Avg)	Tg		-	8	16		(3) RD-80S
Luminance of White (Center of screen)		Y_L		400	500		cd/m²	(4) SR-3
Color Chromaticity (CIE 1931)	Red	Rx	Normal θL,R=0 θU,D=0 Viewing Angle	TYP. -0.03	0.644	TYP. +0.03		(5),(6) SR-3
		Ry			0.337			
	Green	Gx			0.290			
		Gy			0.610			
	Blue	Bx			0.149			
		By			0.066			
	White	Wx			0.280			
		Wy			0.290			
Color Gamut		-		-	72	-	%	(5) SR-3
Color Temperature		-		8,000	10,000	12,000	K	(5) SR-3
Viewing Angle	Hor.	θ_L	C/R≥10	75	89	-	Degree	(6) EZ-Contrast
		θ_R		75	89	-		
	Ver.	θ_U		75	89	-		
		θ_D		75	89	-		
Brightness Uniformity (9 Points)		B_{uni}		-	-	25	%	(2) SR-3

- Test Equipment Setup

   The measurement should be executed in a stable, windless and dark room between
   40min and 60min after lighting the back light at the given temperature for stabilization
   of the back light. This should be measured in the center of screen.

   Environment condition : Ta = 25 ± 2 °C

Photo detector	Field
SR-3	1°
RD-80S	2°

Photo detector

Field

SR-3 : 50㎝
RD-80S : 50㎝
EZ-Contrast :0㎝

TFT - LCD Module

LCD Panel

The center of the screen

- Definition of test point

	228	683	1138
128	⑨	⑧	⑦
384	⑥	⑤	④
640	③	②	①

Active Area

◯ Test Point

Note (1) Definition of Contrast Ratio (C/R)
: Ratio of gray max (Gmax) & gray min (Gmin) at the center point ⑤ of the panel

$$C/R = \frac{G\max}{G\min}$$

Gmax : Luminance with all pixels white
Gmin : Luminance with all pixels black

Note (2) Definition of 9 points brightness uniformity (Test pattern : Full White)

$$Buni = 100 * \frac{(B\max - B\min)}{B\max}$$

        Bmax : Maximum brightness
        Bmin : Minimum brightness

Note (3) Definition of Response time : Sum of Tr, Tf

Display data	Black (data off)	White (data on)	Black (data off)

Optical Instruments Response

100%
90%

10%
0%

T_R T_F

TIME

※ G-to-G : Average response time between Gray to gray (scale)

Note (4) Definition of Luminance of White : Luminance of white at center point ⑤

Note (5) Definition of Color Chromaticity (CIE 1931)
      Color coordinate of Red, Green, Blue & White at center point ⑤

Note (6) Definition of Viewing Angle
      : Viewing angle range (C/R ≥10)

Θ_U
Θ_R
Θ_L
Θ_D

MODEL	LTA320AB02	Doc. No	06-000-G-071220	Page	8/26

3. Electrical Characteristics

3.1 TFT LCD Module
The connector for display data & timing signal should be connected.

Ta = 25°C ± 2 °C

| Item		Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply		V_{DD}	10.8	12.0	13.2	V	(1)
Current of Power Supply	(a) Black	I_{DD}	-	600	800	mA	(2),(3)
	(b) White		-	750	950	mA	
	(c) V-Stripe		-	720	920	mA	
Vsync Frequency		f_V	48	60	66	Hz	
Hsync Frequency		f_H	46	48	52	kHz	
Main Frequency		f_{DCLK}	67	75	82	MHz	
Rush Current		I_{RUSH}	-	-	4	A	(4)

Note (1) The ripple voltage should be controlled under 10% of V_{DD}.
   (2) fv=60Hz, fDCLK = 78MHz, V_{DD} = 12.0V, DC Current.
   (3) Power dissipation check pattern (LCD Module only)

a) Black Pattern   b) White Pattern   c) V-Stripe

   (4) Measurement Conditions

T_{RUSH}=470μs

Rush Current I_{RUSH} can be measured when T_{RUSH}. is 470μs.

MODEL	LTA320AB02	Doc. No	06-000-G-071220	Page	9/26

3.2 Back Light Unit

The back light unit contains 12 direct-lighting type CCFLs (Cold Cathode Fluorescent Lamp). The characteristics of lamps are shown in the following tables.

Ta=25 $\pm$ 2°C

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Operating Life Time	Hr	50,000	-	-	Hour	(1)

Note (1) It is defined as the time to take until the brightness reduces to 50% of its original value.

[Operating condition : Ta = 25$\pm$2 ℃, I_L = 8.0 A , For single lamp only.]

3.3 Inverter Input Condition & Specification

Items	Symbol	Conditions	Specifications			Unit	Note
			Min.	Typ.	Max.		
Input Voltage	Vin	-	22	24	26	V	Ta=25±2 ℃
Input Current	Iin	Vin=24.0V Vdim=3.3V	-	4.1	-	Adc	(1)
Frequency	F_{LAMP}	Vin=24.0 V	62	63.5	65	kHz	After 2 Hours Warm-Up @Vin=24V
Lamp current	I_O	Vin=24.0V Vdim=3.3V	7.5	8.0	8.5	mArms	
Backlight On/Off	ON	Vin=24.0 V	2.4	-	5.25	V	-
	OFF	Vin=24.0 V	0	-	0.8		
Dimming Control	V_{DIM}	Max Lum	3.3	-	-	V	-
		Min. Lum	-	-	0		

Note) Power Consumption is measured when 500[cd/m²] of luminance which is the typical luminance.
    Lamp Current is measured at the point before Lamp.
  (1) Max Value of the Power Consumption is measured after 60 min warm-up.
.
  * Initial turn-on time : From 0sec to 60min after turn-on

4. Input Terminal Pin Assignment

4.1. Input Signal & Power   Connector : FI-E30S (JAE)

PIN No.	Description	PIN No.	Description
1	No Connection (Note1)	16	GND
2	No Connection (Note1)	17	RxIN3-
3	No Connection (Note1)	18	RxIN3+
4	GND	19	GND
5	RxIN0-	20	GND
6	RxIN0+	21	LVDS OPTION (Note 2)
7	GND	22	No Connection (Note1)
8	RxIN1-	23	GND
9	RxIN1+	24	GND
10	GND	25	GND
11	RxIN2-	26	Vin
12	RxIN2+	27	Vin
13	GND	28	Vin
14	RxCLK-	29	Vin
15	RxCLK+	30	Vin

Note1) No Connection: **This PINS are only used for SAMSUNG internal using.
DO NOT CONNECT**
Note2) LVDS OPTION : If this PIN is HIGH (3.3 V) → Normal LVDS format
LOW (GND) → JEIDA LVDS format

**SEQUENCE   : On = V$_{DD}$(T1) ≥ LVDS Option ≥ Interface Signal(T2)
OFF = Interface Signal(T3) ≥ LVDS Option ≥ V$_{DD}$**

Note(1) Pin number starts from Left side

PCB

▼

Pin No. 1   Pin No. 30

#1   #30

#1   #30

Fig. Connector diagram

a. Power GND pins should be connected to the LCD's metal chassis.
b. All power input pins should be connected together.
c. All NC pin should be separated from other signal or power.

4.2. Inverter Input Pin Configuration

Connector : S14B-PHA-SM-TB(LF) (JST)

Pin No.	Pin Configuration(FUNCTION)
1	24 V
2	24 V
3	24 V
4	24 V
5	24 V
6	GND
7	GND
8	GND
9	GND
10	GND
11	No Connection (DO NOT CONNECT)
12	Backlight On /Off [ON:2.4 – 5.25 V, OFF: 0 - 0.8 V]
13	Dimming Control [0V:Min, 3.3V:Max]
14	No Connection (DO NOT CONNECT)

4.3. Inverter Input Power Sequence

Vin (24V)
0.9 Vin
20msec [Min]
0.1 Vin
0.9 Vin

Dimming Control (0 ~ 3.3 V)

0.5sec [Min]
0.5sec [Min]

Backlight On/Off
2.4V(On level)
0.8V(Off level)

0.5sec [Min]
0.1sec [Min]

4.4 LVDS Interface
- LVDS Receiver : Tcon (merged)
- Data Format (JEIDA & VESA)

	LVDS pin	JEIDA -DATA	VESA -DATA
TxOUT/RxIN0	TxIN/RxOUT0	R2	R0
	TxIN/RxOUT1	R3	R1
	TxIN/RxOUT2	R4	R2
	TxIN/RxOUT3	R5	R3
	TxIN/RxOUT4	R6	R4
	TxIN/RxOUT6	R7	R5
	TxIN/RxOUT7	G2	G0
TxOUT/RxIN1	TxIN/RxOUT8	G3	G1
	TxIN/RxOUT9	G4	G2
	TxIN/RxOUT12	G5	G3
	TxIN/RxOUT13	G6	G4
	TxIN/RxOUT14	G7	G5
	TxIN/RxOUT15	B2	B0
	TxIN/RxOUT18	B3	B1
TxOUT/RxIN2	TxIN/RxOUT19	B4	B2
	TxIN/RxOUT20	B5	B3
	TxIN/RxOUT21	B6	B4
	TxIN/RxOUT22	B7	B5
	TxIN/RxOUT24	HSYNC	HSYNC
	TxIN/RxOUT25	VSYNC	VSYNC
	TxIN/RxOUT26	DEN	DEN
TxOUT/RxIN3	TxIN/RxOUT27	R0	R6
	TxIN/RxOUT5	R1	R7
	TxIN/RxOUT10	G0	G6
	TxIN/RxOUT11	G1	G7
	TxIN/RxOUT16	B0	B6
	TxIN/RxOUT17	B1	B7
	TxIN/RxOUT23	RESERVED	RESERVED

4.5 Input Signals, Basic Display Colors and Gray Scale of Each Color

COLOR	DISPLAY (8bit)	DATA SIGNAL																								GRAY SCALE LEVEL
		RED								GREEN								BLUE								
		R0	R1	R2	R3	R4	R5	R6	R7	G0	G1	G2	G3	G4	G5	G6	G7	B0	B1	B2	B3	B4	B5	B6	B7	
BASIC COLOR	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	-
	GREEN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	-
	CYAN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
	RED	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	-
	MAGENTA	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	-
	YELLOW	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	-
	WHITE	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-
GRAY SCALE OF RED	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R0
	DARK ↑	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R1
		0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R2
		:	:	:	:	:	:			:	:	:	:	:	:			:	:	:	:	:	:			R3~ R252
		:	:	:	:	:	:			:	:	:	:	:	:			:	:	:	:	:	:			
	↓ LIGHT	1	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R253
		0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R254
	RED	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	R255
GRAY SCALE OF GREEN	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G0
	DARK ↑	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G1
		0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	G2
		:	:	:	:	:	:			:	:	:	:	:	:			:	:	:	:	:	:			G3~ G252
		:	:	:	:	:	:			:	:	:	:	:	:			:	:	:	:	:	:			
	↓ LIGHT	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	G253
		0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	G254
	GREEN	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	G255
GRAY SCALE OF BLUE	BLACK	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	B0
	DARK ↑	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	B1
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	B2
		:	:	:	:	:	:			:	:	:	:	:	:			:	:	:	:	:	:			B3~ B252
		:	:	:	:	:	:			:	:	:	:	:	:			:	:	:	:	:	:			
	↓ LIGHT	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	1	1	B253
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	B254
	BLUE	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	B255

Note) Definition of Gray :
Rn : Red Gray, Gn : Green Gray, Bn : Blue Gray (n = Gray level)
Input Signal : 0 = Low level voltage, 1 = High level voltage

5. Interface Timing

5.1 Timing Parameters (DE only mode)

SIGNAL	ITEM	SYMBOL	MIN.	TYP.	MAX.	Unit	NOTE
Clock	Frequency	$1/T_C$	67	75	82	MHz	-
Hsync		F_H	46	48	52	KHz	-
Vsync		F_V	48	60	66	Hz	-
Vertical Display Term	Active Display Period	T_{VD}	-	768	-	lines	-
	Vertical Total	T_V	773	810	1200	lines	-
Horizontal Display Term	Active Display Period	T_{HD}	-	1366	-	clocks	-
	Horizontal Total	T_H	1460	1648	2000	clocks	-

Note) This product is DE only mode. The input of Hsync & Vsync signal does
   not have an effect on normal operation.
   (1) Test Point : TTL control signal and CLK at LVDS Tx input terminal in system
   (2) Internal V_{DD} = 3.3V

5.2 Timing diagrams of interface signal (DE only mode)

5.3 Power ON/OFF Sequence

   To prevent a latch-up or DC operation of the LCD Module, the power on/off sequence should be as the diagram below.

T1 : V_{DD} rising time from 10% to 90%
T2 : The time from V_{DD} to valid data at power ON.
T3 : The time from valid data off to V_{DD} off at power Off.
T4 : V_{DD} off time for Windows restart
T5 : The time from valid data to B/L enable at power ON.
T6 : The time from valid data off to B/L disable at power Off.

▪ The supply voltage of the external system for the Module input should be the same
    as the definition of V_{DD}.
▪ Apply the lamp voltage within the LCD operation range. When the back light turns on
    before the LCD operation or the LCD turns off before the back light turns off,
    the display may momentarily show abnormal screen.
▪ In case of V_{DD} = off level,
    please keep the level of input signals low or keep a high impedance.
▪ T4 should be measured after the Module has been fully discharged between power off
    and on period.
▪ Interface signal should not be kept at high impedance when the power is on.

| MODEL | LTA320AB02 | Doc. No | 06-000-G-071220 | Page | 19/26 |

SECTION B-B'

SECTION A-A'

SECTION C-C'

* NOTES
1. BACKLIGHT : 12 COLD CATHODE FLUORESCENT LAMPS.
2. I/F CONNECTOR SPECIFICATION.
   - MAKER : JAE
   - PART NO. : FI-E30S
3. INVERTER CONNECTOR SPECIFICATION
   - MAKER : JST
   - PART NO : S14B-PHA-SM
4. UNSPECIFIED TORLERANCE TO BE ±0.5.
5. ALLOWED DEPTH OF USERHOLE SCREW INSERTION IS 8.0 MAX
6. CALLIFERS MEASURING FORCE : 750 ±250 gf
7. GAP BETWEEN TOP CHASSIS AND GLASS IS 1.2 mm MAX
8. WEIGHT : 7.0 Kg (Max 7.5Kg)
9. BLACK MATRIX SPEC
   -|A - B| ≤ 2.0 mm
   -|C - D| ≤ 2.0 mm

PRELIMINARY

BLACK MATRIX

ACTIVE CENTER

2-M4, DP 8mm MAX (USERHOLE)
2-DP 3mm MAX (USER HOLE GUIDE)
2-M4, USERHOLE(DP 8mm MAX)
4-Ø9.0
2-Ø5
2-Ø5
R2.5
R2

450±1 (OUTLINE)
398.4±1 (BEZEL OPENING)
392.256 (ACTIVE AREA)
213±0.5
213±0.5
(28.2)
(41)
(32)
(32.5)
25.8
3
0.7
MAX 1.2 GAP
2±0.5
16
12.7.3.8
Ø5
11.3
27.5
(32.5)
Ø5

760±1 (OUTLINE)
703.6±1 (BEZEL OPENING)
697.6845 (ACTIVE AREA)
368±0.5
368±0.5
(380)
210±0.5
210±0.5
210.4±1
144±0.5
144±0.5
210±0.5
210±0.5
102±0.5
102±0.5
365
MAX 50.5
MAX 44
MAX 36
32.5±1
32.5±1
2-32±0.5
2-32±0.5
2-25.5±0.5
15
15
15
15
Ø4
41±1
41±1
(25.8)
171.5±0.5
171.5±0.5
171.5±0.5
171.5±0.5
3-18±0.5
3-18±0.5
11.3
6.1
30
6.3
12
2.5

NO	PART NAME	CODE NO	SPECIFICATION	Q'TY	SPEC NO	REMARK
1	OUTLINE DIMENSION	-	LTA320AB02-001	1		

GENERAL TOLERANCE

STEP	LEVEL 1	LEVEL 2	LEVEL 3
0 < X < 4	±0.05	±0.1	±0.2
4 < X <= 16	±0.08	±0.15	±0.3
16 < X <= 64	±0.12	±0.25	±0.5
64 < X <= 256	±0.25	±0.4	±0.8

DETAIL"A" (4PARTS)

22
(28.6)
(42)
4

REAR MOUNT 4x2-M4 (DP=4mm)
4-LOCATION PIN BOSS ø5(HT=1.5)
4-EMBOSS(HT=4mm)

"A"

LAMP SUPPORT AREA
HT MAX 3.5mm

333
(166.5)

306.7
176
88
122.85±1

190
190

272.6±1

130±1

3-BEAD(HT=0.5mm)

PRELIMINARY

GENERAL TOLERANCE

STEP	LEVEL 1	LEVEL 2	LEVEL 3
0 < X ≤ 4	±0.05	±0.1	±0.2
4 < X ≤ 16	±0.08	±0.15	±0.3
16 < X ≤ 64	±0.12	±0.25	±0.5
64 < X ≤ 256	±0.25	±0.4	±0.8

REV	DATE	DESCRIPTION OF REVISION			CHC'D BY
UNIT	mm	DRA'N BY	DES'D BY	CHK'D BY	APP'D BY
SCALE	1/2	K.R.KO			J.H.CHUN
TOLERANCE		07.12.06			07.12.07
		SPEC. NO			SPEC. NO

SAMSUNG ELECTRONICS

REASON		MODEL NAME	LTA320AB02-001	CHC'D BY
		PART/SHEET NAME	OUTLINE DIM. (REAR)	SHEET 2/2
		CODE NO.	-	VER. 000

7. PACKING

7.1 CARTON (Internal Package)
  (1) Packing Form
      Corrugated fiberboard box and corrugated cardboard as shock absorber
  (2) Packing Method

**Packing
-Pallet Box**

→ Direction to open

Cushion-Foam

LCD Module

Cushion-Foam

Cushion-Foam

LCD Module

Cushion-Foam

Pallet-Plastic

7.2 Packing Specification

Item	Specification	Remark
LCD Packing	24ea / (Packing-Pallet Box)	1. 168 Kg / LCD (24ea) 2. 14 Kg / Cushion-pallet (4ea) 3. 8.8 Kg / Packing-Pallet Box (1ea) 4. Cushion-pallet Material : EPS 5. Packing-Pallet Box Material : DW4
Pallet	1Box / Pallet	1. Pallet weight = 8kg 2. 8Kg/Pallet
Packing Direction	Vertical	
Total Pallet Size	H x V x height	1150mm(H) x 985mm(V) x 1161mm(height)
Total Pallet Weight	198.8 kg	Pallet(8kg) + Module(7*24=168) + Cushion(4ea=14kg) + Pallet-BOX(8.8kg)

8. MARKING & OTHERS

A nameplate bearing followed by is affixed to a shipped product at the specified location on each product.

(1) Parts number : LTA320AB02
(2) Revision: Three letters
(3) Lot number : X X X X XXX XX X

- Cell Position No. (In the Glass)
- Glass No. (In the one Lot)
- Lot No. (Glass)
- Month
- Year (Note1)
- Product code
- Line

(4) Nameplate Indication

Week code : 05 29
- week
- year

LTA320AB02

0730

XXXXXXXXX   XXX

Revision code

Lot number

MADE IN KOREA

40mm

80mm

(5) Packing box attach

DVC : LTA320AB02
TYPE: XXXX
QTY : 24

ZAT53K0003   G1

100mm

Part number

Box serial number

165mm

(6) Others
1. After service part
   Lamps cannot be replaced because of the narrow bezel structure.

| MODEL | LTA320AB02 | Doc. No | 06-000-G-071220 | Page | 23/26 |

9. General Precautions
9.1 Handling

(a) When the Module is assembled, it should be attached to the system firmly using all mounting holes. Be careful not to twist and bend the Module.

(b) Because the inverter use high voltage, it should be disconnected from power before it is assembled or disassembled.

(c) Refrain from strong mechanical shock and / or any force to the Module. In addition to damage, this may cause improper operation or damage to the Module and CCFL back light.

(d) Note that polarizers are very fragile and could be damage easily. Do not press or scratch the surface harder than a HB pencil lead.

(e) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, staining or discoloration may occur.

(f) If the surface of the polarizer is dirty, clean it using absorbent cotton or soft cloth.

(g) Desirable cleaners are water, IPA(Isopropyl Alcohol) or Hexane. Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanent damage to the polarizer due to chemical reaction.

(h) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth . In case of contact with hands, legs or clothes, it must be washed away with soap thoroughly.

(i) Protect the module from Electrostatic discharge. Otherwise the ASIC IC or Semiconductor would be damaged.

(j) Use finger-stalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.

(k) Do not disassemble the Module.

(l) Do not disassemble shield case of inverter & LVDS board.

(m) Do not connect N.C pins. (Samsung internal use only)

(n) Protection film for polarizer on the Module should be slowly peeled off just before use so that the electrostatic charge can be minimized. Must put on antistatic glove while handle a module

(o) Pins of I/F connector should not be touched directly with bare hands.

| MODEL | LTA320AB02 | Doc. No | 06-000-G-071220 | Page | 24/26 |

9.2 Storage

(a) Do not leave the Module in high temperature, and high humidity for a long time. It is highly recommended to store the Module with temperature from 0 to 35℃ and relative humidity of less than 70%.

(b) Do not store the TFT-LCD Module in direct sunlight.

(c) The Module should be stored in a dark place. It is prohibited to apply sunlight or fluorescent light in storing.

9.3 Operation

(a) Do not connect or disconnect the Module in the "Power On" condition.

(b) Power supply should always be turned on/off by the "Power on/off sequence"

(c) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.

(d) The cable between the back light connector and its inverter power supply should be connected directly with a minimized length. A longer cable between the back light and the inverter may cause lower luminance of lamp(CCFL) and may require higher startup voltage(Vs).

9.4 Operation Condition Guide

(a) The LCD product should be operated under normal conditions.
    Normal condition is defined as below;
    - Temperature : 20 ± 15℃
    - Humidity : 55 ± 20%
    - Display pattern : continually changing pattern (Not stationary)

(b) If the product will be used in extreme conditions such as high temperature, humidity, display patterns or operation time etc.., It is strongly recommended to contact SEC for Application engineering advice. Otherwise, its reliability and function may not be guaranteed. Extreme conditions are commonly found at Airports, Transit Stations, Banks, Stock market, and Controlling systems.

9.5 Others

(a) Ultra-violet ray filter is necessary for outdoor operation.

(b) Avoid condensation of water. It may result in improper operation or disconnection
   of electrode.

(c) Do not exceed the absolute maximum rating value. (supply voltage variation,
   input voltage variation, variation in part contents and environmental temperature,
   and so on)
   Otherwise the Module may be damaged.

(d) If the Module keeps displaying the same pattern for a long period of time,
   the image may be "sticked" to the screen.
   To avoid image sticking, it is recommended to use a screen saver.

(e) This Module has its circuitry PCB's on the rear side and should be handled
   carefully in order not to be stressed.

(f) Please contact SEC in advance when you display the same pattern for a long time.