

☒ Preliminary Specifications

☐ Final Specifications

Title	Backlight Driving Board
Model Name	DB-LD01-XX
Version	Rev.0

Customer	
<hr/>	
Approved by	Date
<hr/>	<hr/>
Notice : This Specification is subject to change without notice.	

Approved By	Prepared By
Tony Chiu 2021/03/22	Frank Kuo 2021/03/22

Contents

1.GENERAL FUNCTION.....	4
2.INTERFACE	4
3.ELECTRICAL CHARACTERISTICS.....	5
4.INTERFACE CHARACTERISTICS.....	6
5.MECHANICAL CHARACTERISTICS	7

TWScreen

Revised Record


Version	Date	Revised Content/Summary	Page	Remark
0	2021/03/22	Final Specification was first issued	All	

1.General Function

This is a high efficiency LED backlight driver board which is capable to driving up to 4 channels of LED string. This board provides the user with OVP and OCP features.

This Product Specification is made to be the standard of TWScreen manufactured LED Driving Board such a standard will be followed in TWScreen production, shipment, and quality inspection.

2.Interface



2-1. CN1 : Input Connector

2-2. CN2 : Output Connector

3.Electrical Characteristics

<u>Parameter</u>		<u>Min.</u>	<u>Typ.</u>	<u>Max.</u>	<u>Unit</u>
Input Voltage	Vin	10.8	12.0	26	V
Input Current	Iin	---	2.5	---	A
Output Voltage	Vout	---	---	51	V
Efficiency	Eff.	---	80	---	%
Sub Current	Iout	---	---	200	mA
Total Current	Iout	---	---	800	mA
LED ON/OFF	Von	2.5	---	5.0	V
	Voff	---	---	0.5	
Dimming	PWM High Level	2.5	---	5.0	V
	PWM Low Level	---	---	0.5	V
	PWM Duty Cycle	5	---	100	%
	PWM Frequency	0.1	---	20	KHz

*** Depend on panel type

4.Interface Characteristics

4.1. Input Connector

Location – CN1 : 7pin wafer , pitch 2.0mm R/A , STM M24267R or equiv

Pin Assign and Definition

Pin No.	Symbol	Pin No.	Symbol	Pin No.	Symbol
1	GND	4	NC	7	+12 V
2	GND	5	ON/OFF	---	-----
3	ADJ	6	+12 V	---	-----

4.2. Output Connector

Location – CN4 : 6pin wafer , pitch 2.0mm R/A , STM M24266R or equiv

Pin Assign and Definition

Pin No.	Symbol	Pin No.	Symbol
1	IRLED_1	4	VLED+
2	IRLED_2	5	IRLED_3
3	VLED+	6	IRLED_4

Dimension: 115(L) *40(W) *12(H) mm

