BOE 京东方

TITLE : HT150X02-100

Product Specification

Rev.B

BEIJING BOE OPTOELECTRONICS TECHNOLOGY

SPEC. NUMBER	PRODUCT GROUP	REV.	ISSUE DATE	PAGE
S864-5003	TFT-LCD	B	2007. 05. 31	1 OF 28

B2006-5006-O(1/3)　　　　　　　　　　　　　　　　　　　A4(210 X 297)

	PRODUCT GROUP		REV	ISSUE DATE
京东方 BOE	TFT- LCD PRODUCT		B	2007.05.31

REVISION HISTORY

REV.	ECN No.	DESCRIPTION OF CHANGES	DATE	PREPARED
O	-	Initial Release	06.06.12.	B.C.Lim
A	-	Ⅰ. Shock test condition change - Gravity : 150G → 70G - Pulse width : 6msec, sine wave → 11msec, half sine wave Ⅱ. B/L Lamp current change - Max. : 8mA → 9mA Ⅲ. B/L Interface connection change - Hot : Blue → Pink - Cold : Black → Black/White	06.10.12	J.K.KIM
B	-	Ⅰ. Start Voltage (Typ): 850V (0°C), 1100V (25°C)---> 1100V (0°C), 850V (25°C) Ⅱ. Start Voltage (Max): none--->1300V (0°C), 1100V (25°C) Ⅲ. Life Time(Min): 30,000h (IBL=9.0mA)---> 40,000h (IBL=9.0mA)	07.05.31	C.Y

SPEC. NUMBER	SPEC. TITLE		PAGE
S864-5003	HT150X02-100 Product Specification		2 OF 28

A4(210 X 297)

Contents

1.0 GENERAL DESCRIPTION

1.1 Introduction

HT150X02-100 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 15.0 inch diagonally measured active area with XGA resolutions (1024 horizontal by 768 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16,194,227 colors. The TFT-LCD panel used for this module is adapted for a low reflection and higher color type.

1.2 Features

- ● LVDS Interface with 1 pixel / clock
- ● High-speed response
- ● Low power consumption
- ● 6-bit (FRC) color depth, display 16,194,227 colors
- ● Incorporated edge type back-light (Two lamps)
- ● High luminance and contrast ratio, low reflection and wide viewing angle
- ● DE (Data Enable) & H-Sync & V-Sync mode
- ● RoHS Compliant

1.3 Application

- Desktop Type of PC & Workstation Use
- Slim-Size Display for Stand-alone Monitor
- Display Terminals for Control System
- Monitors for Process Controller

1.4 General Specification

The followings are general specifications at the model HT150X02-100.

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	304.128(H) $\times$ 228.096(V)	mm	
Number of pixels	1024(H) $\times$ 768(V)	pixels	
Pixel pitch	0.297(H) $\times$ 0.297(V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	16,194,227	colors	
Display mode	Normally White		
Dimensional outline	326.5(H) $\times$ 253.5(V) $\times$ 11.4(D) typ.	mm	11.9max
Weight	1200 (max.)	g	
Surface Treatment	Haze 25%, 3H		
Back-light	Top/Bottom side, 2-CCFL type		

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings>   [VSS=GND=0V]

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V_{DD}	VSS-0.3	4.0	V	Ta = 25 ℃
Logic Supply Voltage	V_{IN}	VSS-0.3	V_{DD}+0.3	V	
Back-light Lamp Current	I_{BL}	3	9	mA	
Back-light Lamp frequency	F_L	30	80	kHz	
Operating Temperature	T_{OP}	0	+50	℃	1)
Storage Temperature	T_{ST}	-20	+60	℃	1)

Note : 1) Temperature and relative humidity range are shown in the figure below.
Wet bulb temperature should be 39 ℃ max. and no condensation of water.

3.0 ELECTRICAL SPECIFICATIONS
3.1 Electrical Specifications

< Table 3. Electrical specifications >   [Ta =25±2 ℃]

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V_{DD}	3.0	3.3	3.6	V	Note1
Power Supply Current	I_{DD}	-	700	1000	mA	
In Rush Current	I_{rush}	-	2.0	3.0	A	Note 2
Permissible Input Ripple Voltage	V_{RF}			100	mV	$V_{DD} = 3.3V$
High Level Differential Input Threshold Voltage	V_{IH}		-	+100	mV	Vcm = 1.2V typ.
Low Level Differential Input Threshold Voltage	V_{IL}	-100	-		mV	
Back-light Lamp Voltage	V_{BL}	504	560	616	V_{rms}	
Back-light Lamp Current	I_{BL}	3.0	8.0	9.0	mA_{rms}	
Back-light Lamp operating Frequency	F_L	35	-	80	KHz	Note 3
Lamp Start Voltage			850	1100	V_{rms}	25℃, Note 4
			1100	1300	V_{rms}	0℃, Note 4
Lamp Life		40000	50000		Hrs	I_{BL}= 9.0mA, Note 5
Power Consumption	P_D	-	2.3	3.3	W	
	P_{BL}		8.6	←	W	I_{BL}=8.0mA, Note 6
	P_{total}		10.9		W	

Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.
The current draw and power consumption specified is for VDD=3.3V, Frame rate=75Hz and
Clock frequency = 81.2MHz. Test Pattern of power supply current
    a) Typ : Windows XP pattern
    b) Max : Skip sub pixel pattern
2. Duration of rush current is about 2 ms and rising time of VDD is 520 μs ± 20 %
3. The lamp frequency should be selected as different as possible from the horizontal
  synchronous frequency and its harmonics to avoid interference, which may cause line flow on the display
4. The voltage above this value should be applied to the lamps for more than 1 second to start-up. Otherwise the
  lamps may not be turned on. This is inverter output voltage
5. The lamp life time is min 40,000 at I_{BL} = 9.0mA
6. Calculated value for reference (V_{BL} × I_{BL}) ×2 excluding inverter loss.

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = 25 ± 2℃) with the equipment of Luminance meter system (Goniometer system and TOPCONE BM-5) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of Θ and Φ equal to 0°. We refer to $\Theta_{\emptyset=0}$ (=Θ_3) as the 3 o'clock direction (the "right"), $\Theta_{\emptyset=90}$ (= Θ_{12}) as the 12 o'clock direction ("upward"), $\Theta_{\emptyset=180}$ (= Θ_9) as the 9 o'clock direction ("left") and $\Theta_{\emptyset=270}$(= Θ_6) as the 6 o'clock direction ("bottom"). While scanning Θ and/or Ø, the center of the measuring spot on the Display surface shall stay fixed. The measurement shall be executed after 30 minutes warm-up period. VDD shall be 3.3V +/-10% at 25°C. Optimum viewing angle direction is 6 'clock.

4.2 Optical Specifications

[VDD = 3.3V, Frame rate = 60Hz, Clock = 54MHz, I_{BL} = 8.0mA, Ta =25 ± 2 ℃]

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	Θ_3	CR > 10	65	75	-	Deg.	Note 1
		Θ_9		65	75	-	Deg.	
	Vertical	Θ_{12}		60	70	-	Deg.	
		Θ_6		50	60	-	Deg.	
Viewing Angle range	Horizontal	Θ_3	CR > 5	70	80	-	Deg.	
		Θ_9		70	80	-	Deg.	
	Vertical	Θ_{12}		70	80	-	Deg.	
		Θ_6		70	80	-	Deg.	
Luminance Contrast ratio		CR	Θ = 0° (Center) Normal Viewing Angle	400	500	-		Note 2
Luminance of White		Y_w		200	250	-	cd/m²	Note 3
White luminance uniformity		ΔY		75	80	-	%	Note 4
Reproduction of color	White	W_x		0.283	0.313	0.343	±0.03	Note 5
		W_y		0.299	0.329	0.359	±0.03	
	Red	R_x		0.616	0.646	0.676		
		R_y		0.313	0.343	0.373		
	Green	G_x		0.281	0.311	0.343		
		G_y		0.547	0.577	0.607		
	Blue	B_x		0.118	0.148	0.178		
		B_y		0.090	0.120	0.150		
Response Time	Rising	T_r			2	4	ms	Note 6
	Falling	T_f			6	8	ms	
Cross Talk		CT		-	-	2.0	%	Note 7

Note :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface.

2. Contrast measurements shall be made at viewing angle of θ= 0° and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state. (See FIGURE 1 shown in Appendix) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

4. The White luminance uniformity on LCD surface is then expressed as :
$\Delta Y = (\text{Minimum Luminance of 9points} / \text{Maximum Luminance of 9points}) * 100$
(See FIGURE 2 shown in Appendix).

5. The color chromaticity coordinates specified in Table 4. shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.

6. The electro-optical response time measurements shall be made as FIGURE 3 shown in Appendix by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is Td, and 90% to 10% is Tr.

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark. (See FIGURE 4 shown in Appendix).

5.0 INTERFACE CONNECTION.
5.1 Electrical Interface Connection

- CN11 : Module Side Connector : DF14H-20P-1.25H (Hirose) or Equivalent

  User Side Connector : DF14-20S-1.25C (Hirose) or equivalent

Pin No	Symbol	Function	Remark
1	VDD	Power Supply, 3.3V (typical)	
2	VDD	Power Supply, 3.3V (typical)	
3	VSS	Ground	
4	VSS	Ground	
5	RIN0-	- LVDS differential data input (R0-R5, G0)	
6	RIN0+	+ LVDS differential data input (R0-R5, G0)	
7	VSS	Ground	
8	RIN1-	- LVDS differential data input (G1-G5, B0-B1)	
9	RIN1+	+ LVDS differential data input (G1-G5, B0-B1)	
10	VSS	Ground	
11	RIN2-	- LVDS differential data input (B2-B5, HS, VS, DE)	
12	RIN2+	+ LVDS differential data input (B2-B5, HS, VS, DE)	
13	VSS	Ground	
14	CLKIN-	- LVDS differential clock input	
15	CLKIN+	+ LVDS differential clock input	
16	VSS	Ground	
17	RIN3-	- LVDS differential data input (R6-R7, G6-G7, B6-B7)	
18	RIN3+	+ LVDS differential data input (R6-R7, G6-G7, B6-B7)	
19	VSS	Ground	
20	NC	No Connection	

5.2 LVDS Interface (Tx; THC63LVDF83A or Equivalent)

Input Signal	Transmitter Pin No.	Pin No.	Interface System (Tx)	Interface TFT-LCD (Rx)	DF14H-20P-1.25H Pin No.	Remark
OR0	51					
OR1	52					
OR2	54					
OR3	55	48	OUT0-	IN0-	5	
OR4	56	47	OUT0+	IN0+	6	
OR5	3					
OG0	4					
OG1	6					
OG2	7					
OG3	11					
OG4	12	46	OUT1-	IN1-	8	
OG5	14	45	OUT1+	IN1+	9	
OB0	15					
OB1	19					
OB2	20					
OB3	22					
OB4	23					
OB5	24	42	OUT2-	IN2-	11	
Hsync	27	41	OUT2+	IN2+	12	
Vsync	28					
DE	30					
MCLK	31	40	CLK OUT-	CLKIN-	14	
		39	CLK OUT+	CLKIN+	15	
OR6	50					
OR7	2					
OG6	8					
OG7	10	38	OUT3-	IN3-	17	
OB6	16	37	OUT3+	IN3+	18	
OB7	18					
RSVD	25					

5.3 Data Input Format

Display Position of Input Data (V-H)

5.4 Back-light Interface Connection

●CN 21,22   Module Side Connector   :BHSR−03VS−1 or Equivalent

User Side Connector   :

PIN NO.	INPUT	COLOR	FUNCTION
1	HOT	Pink	High Voltage
2	COLD	White, Black	Ground

6.0 SIGNAL TIMING SPECIFICATION

6.1 The HT150X02-100 is operated by the DE & H-Sync & V-Sync mode (LVDS Transmitter Input)

| Item		Symbols	Min	Typ	Max	Unit
Clock	Frequency	1/Tc	54	65	84	MHz
	High Time	Tch	4.5	-	-	ns
	Low Time	Tcl	4.5	-	-	ns
Data	Setup Time	Tds	2.7	-	-	ns
	Hold Time	Tdh	0	-	-	ns
Data Enable Setup Time		Tes	2.7	-	-	ns
Frame Rate		Fv	50	60	77	Hz
Frame Period		Tv	772	806	1022	lines
Vertical Display Period		Tvd	768	768	768	lines
One Line Scanning Period		Th	1100	1344	2046	clocks
Horizontal Display Period		Thd	1024	1024	1024	clocks

6.2 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 4.

<Table 4. LVDS Rx Interface Timing Specification>

Item	Symbol	Min	Typ	Max	Unit	Remark
CLKIN Period	tRCIP	12.5	15.38	-	msec	
CLK Difference	tCdiff	-tRCIP*(3/7)	0	+tRCIP*(3/7)	nsec	
Input Data 0	tRIP1	-0.4	0.0	+0.4	nsec	
Input Data 1	tRIP0	tRICP/7-0.4	tRICP/7	tRICP/7+0.4	nsec	
Input Data 2	tRIP6	$2 \times$tRICP/7-0.4	$2 \times$tRICP/7	$2 \times$tRICP/7+0.4	nsec	
Input Data 3	tRIP5	$3 \times$tRICP/7-0.4	$3 \times$tRICP/7	$3 \times$tRICP/7+0.4	nsec	
Input Data 4	tRIP4	$4 \times$tRICP/7-0.4	$4 \times$tRICP/7	$4 \times$tRICP/7+0.4	nsec	
Input Data 5	tRIP3	$5 \times$tRICP/7-0.4	$5 \times$tRICP/7	$5 \times$tRICP/7+0.4	nsec	
Input Data 6	tRIP2	$6 \times$tRICP/7-0.4	$6 \times$tRICP/7	$6 \times$tRICP/7+0.4	nsec	

tRIP2

tRIP3

tRIP4

tRIP5

tRIP6

tRIP0

tRIP1

RXO/Ez +/-
* Z = 0, 1, 2,3   Rx3 | Rx2 | Rx1 | Rx0 | Rx6 | Rx5 | Rx4 | Rx3 | Rx2 | Rx1 | Rx0

RxOCLKIN+   Vdiff=0[v]   tRCIP   Vdiff=0[v]

RxECLKIN+   tCdiff

* Vdiff = (RINz+)-(RINz-),…. ,(CLKIN+)-(CLKIN-)

7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL

7.1 Sync Timing Waveforms

1) Need over 3 H-sync during V-Sync Low
2) Fix H-Sync width from V-Sync falling edge to first rising edge

7.2 Horizontal Timing Waveforms

7.3 Horizontal Timing Waveforms

MCLK

Th

Thd

Tc

DE

RA7 ~RA0
GA7 ~GA0
BA7 ~BA0

| D1 | D2 | Dn | D1022 | D1023 | D1024 | Invalid | Data | D1 | D2 | D3 |

Tch   Tcl

MCLK

2.0V
1.5V
0.8V

Tds   Tdh

Data

Valid   Data

2.0V
0.8V

Tes

DE

2.0V

8.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

| Color & Gray Scale		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
		\multicolumn RED DATA								GREEN DATA								BLUE DATA							
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale of RED	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△					↑								↑								↑			
	▽					↓								↓								↓			
	Brighter	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	▽	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale of GREEN	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0
	△					↑								↑								↑			
	▽					↓								↓								↓			
	Brighter	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0
	▽	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
Gray Scale of BLUE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	△					↑								↑								↑			
	▽					↓								↓								↓			
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
Gray Scale of WHITE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0
	△					↑								↑								↑			
	▽					↓								↓								↓			
	Brighter	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1
	▽	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below

- 0 ≤ T1 ≤ 10 ms
- 0 ≤ T2 ≤ 50 ms
- 200ms ≤ T3
- 500ms ≤ T4
- 0 ≤ T5 ≤ 50ms
- 500ms ≤ T6

Notes:

1. When the power supply VDD is 0V, Keep the level of input signals on the low or keep high impedance.
2. Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

10.0 MECHANICAL CHARACTERISTICS

10.1 Dimensional Requirements

FIGURE 6 (located in Appendix) shows mechanical outlines for the model HT150X02-100. Other parameters are shown in Table 5.

<Table 5. Dimensional Parameters>

Parameter	Specification	Unit
Dimensional outline	326.5 ×253.5×11.4 (11.9 Max.)	mm
Weight	1200 (max.)	gram
Active area	304.128(H) × 228.096(V)	mm
Pixel pitch	0.297(H) × 0.297(V)	mm
Number of pixels	1024(H) × 768(V) (1 pixel = R + G + B dots)	pixels
Back-light	Top / Bottom side 2-CCFL type	

10.2 Mounting

See FIGURE 5. (shown in Appendix)

10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an anti-glare coating to minimize reflection and a coating to reduce scratching.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

11.0 RELIABLITY TEST

The Reliability test items and its conditions are shown in below.

<Table 6. Reliability Test Parameters >

No	Test Items	Conditions	
1	High temperature storage test	Ta = 60 ℃, 240 hrs	
2	Low temperature storage test	Ta = -20 ℃, 240 hrs	
3	High temperature & high humidity operation test	Ta = 50 ℃, 80%RH, 240hrs	
4	High temperature operation test	Ta = 50 ℃, 240hrs	
5	Low temperature operation test	Ta = 0 ℃, 240hrs	
6	Thermal shock	Ta = -20 ℃ ↔ 60 ℃ (0.5 hr), 100 cycle	
7	Vibration test (non-operating)	Frequency Gravity / AMP Period	10 ~ 300 Hz, Sweep rate 30 min 1.5 G ±X, ±Y, ±Z 30 min
8	**Shock test (non-operating)**	Gravity	70G
		Pulse width	11msec, half sine wave
		Direction	±X, ±Y, ±Z Once for each
9	Electro-static discharge test (non-operating)	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV	

12.0 HANDLING & CAUTIONS

(1) Cautions when taking out the module
  - Pick the pouch only, when taking out module from a shipping package.

(2) Cautions for handling the module
  - As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
  - As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
  - As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
  - Do not pull the interface connector in or out while the LCD module is operating.
  - Put the module display side down on a flat horizontal plane.
  - Handle connectors and cables with care.

(3) Cautions for the operation
  - When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
  - Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

(4) Cautions for the atmosphere
  - Dew drop atmosphere should be avoided.
  - Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.

(5) Cautions for the module characteristics
  - Do not apply fixed pattern data signal to the LCD module at product aging.
  - Applying fixed pattern for a long time may cause image sticking.

(6) Other cautions
  - Do not disassemble and/or re-assemble LCD module.
  - Do not re-adjust variable resistor or switch etc.
  - When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

13.0 PRODUCT SERIAL NUMBER

京东方 BOE eco RoHS Compliant

HT150X02-100

c $\boldsymbol{\mathcal{H}}$ us

MADE IN CHINA   XXXXXXXXXXXXXXXX

| 1	2	3	4	5	6	7
X X	X	X	X X	X	X X X X	X X X X X X

Type

No 1. Control

No 2. Rank

No 3. Line Classification(BOE HYDIS : H, LCM : L, BOE OT : A/B/C)

No 4. Year(2001 : 01, 2002 : 02, ⋯)

No 5. Month(1, 2, 3, ⋯,9 X, Y, Z)

No 6. FG Code

No 7. Serial No.

14.0 Packing

14.1 Packing Order

Put pads into the box.

As shown in the figure, place the Modules bundled by shielding bag in the box.

After sealing the box, attach Packing Label on the attach position sign area of the box.

Place a cover on the top of the box.

14.2 Packing Note
- Box Dimension : 333mm(W) × 333mm(D) × 435mm(H)
- Package Quantity in one Box : 10pcs

14.3 Box label
- Label Size : 110 mm (L) × 56 mm (W)
- Contents
  Model : HT150X02
  Q`ty : Module Q`ty in one box
  Serial No. : Box Serial No. See next page for detail description.
  Date : Packing Date
  FG Code : FG Code of Product

BOE   BOE HYDIS TECHNOLOGY CO.,LTD.

MODEL : **HT150X02- 100**   Q'TY : 10

SERIAL NO. : 0000000000000   DATE : 2006.06.01.

QAA0330000268   110   (QA)

00	0	0	00	0	0	00000
Type	Grade	Line	Year	Month	ITEM-CODE	Serial_no

FG CODE

## 15.0 APPENDIX

Figure 1. Measurement Set Up

### Figure 2. White Luminance and Uniformity Measurement Locations (5 points)

Figure 3. Response Time Testing

Display data: White(TFT OFF) | Black(TFT ON) | White(TFT OFF)

Optical Response

100%
90%

T_R

T_F

10%
0%

Time

Figure 4. Cross Modulation Test Description

VIEW AREA

VIEW AREA

256,192   768,192

L31

Y_B(896, 384)

256,576   768,576

Y_A (896,384)

L0

$$\text{Cross-Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$$

Where:

Y_A = Initial luminance of measured area (cd/m²)
Y_B = Subsequent luminance of measured area (cd/m²)
The location measured will be exactly the same in both patterns

Figure 5. TFT-LCD Module Outline Dimensions (Front view)

Figure 6. TFT-LCD Module Outline Dimensions (Rear view)