



PROPRIETARY NOTE

THIS SPECIFICATION IS THE PROPERTY OF BOE AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE AND MUST BE RETURNED TO BOE UPON ITS REQUEST

NV133FHM-N62 V8.1

Initial Product Specification

Rev. 0

BOE Optoelectronics Technology Co., Ltd

SPEC. NUMBER

PRODUCT GROUP

Rev.

ISSUE DATE

PAGE

TFT-LCD

0

2018.07.19

1 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

REVISION HISTORY

Revision No.	Page	Description of Changes	Date	Prepared
0	-	Initial Release	2018.07.19	Guo Yongchao

REVIEWED	
Designer	Manager
Mei Wenlin (Array)	Wang Rui
Li Yang (Cell)	Hu Jingyong
Liu Chao (CF)	Li Min
Chen Shanbin (EE)	Lu Xu
Geng Yuxu (MO)	Gao Liang
Mou Bingkai (QE)	Huang Yuan
Chen Gang (PI)	Wang Zhihui
APPROVED	
Guo Yongchao(PM)	

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	2 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

Contents

No.	Items	Page
1.0	General Description	4
2.0	Absolute Maximum Ratings	6
3.0	Electrical Specifications	7
4.0	Optical Specifications	10
5.0	Interface Connection	15
6.0	Signal Timing Specification	19
7.0	Input Signals, Display Colors & Gray Scale of Colors	21
8.0	Power Sequence	22
9.0	Connector Description	23
10.0	Mechanical Characteristics	24
11.0	Reliability Test	25
12.0	Handling & Cautions	25
13.0	Label	26
14.0	Packing Information	28
15.0	Mechanical Outline Dimension	29
16.0	EDID Table	31

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	3 OF 34

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

1.0 GENERAL DESCRIPTION

1.1 Introduction

NV133FHM-N62 V8.1 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 13.3inch diagonally measured active area with Full-HD resolutions (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 262k(6bit) colors and color gamut 72%. The TFT-LCD panel used for this module is a low reflection and higher color type. Therefore, this module is suitable for Notebook PC. The LED driver for back-light driving is built in this model. All input signals are eDP1.3 interface compatible.




Figure 1. Drive Architecture

1.2 Features

- 2 lane eDP interface with 2.7Gbps link rates
- Thin and light weight
- 262k(6bit) color depth, color gamut 72%
- Single LED lighting bar (Bottom side/Horizontal Direction)
- Data enable signal mode
- Side mounting frame
- Green product (RoHS & Halogen free product)
- On board LED driving circuit
- Low driving voltage and low power consumption
- On board EDID chip

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	4 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

1.3 Application

- Notebook PC (Wide type)

1.4 General Specification

The followings are general specifications at the model NV133FHM-N62 V8.1. (listed in Table 1)

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	293.76 (H) x 165.24 (V)	mm	
Number of pixels	1920 (H) × 1080 (V)	pixels	
Pixel pitch	153(H) × 153(V)	um	
Pixel arrangement	RGB Vertical stripe		
Display colors	262k(6bit)		
Color gamut	72%		
Display mode	Normally Black		
Dimensional outline	300.56(H)*188.25(V) (w/PCB)*2.4 (max) 300.56(H)*177.69(V)*2.4 (max)	mm	
Weight	215(max)	g	
Surface treatment	AG		
Surface hardness	3H		
Back-light	Bottom edge side, 1-LED lighting bar type		Note 1
Power consumption	P _D : 0.92(max)	W	@Mosaic
	P _{BL} : 2.9(max)	W	
	P _{Total} : 3.82(typ.)	W	@Mosaic

Notes : 1. LED Lighting Bar (36*LED Array)

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	5 OF 34

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings>

Ta=25+/-2°C

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	-0.3	4.0	V	Note 1
Logic Supply Voltage	V _{IN}	V _{SS} -0.3	V _{DD} +0.3	V	
Operating Temperature	T _{OP}	0	+50	°C	Note 2
Storage Temperature	T _{ST}	-20	+60	°C	

Notes :

1. Permanent damage to the device may occur if maximum values are exceeded functional operation should be restricted to the condition described under normal operating conditions.

2. Temperature and relative humidity range are shown in the figure below.

95 % RH Max. (40 °C ≥ Ta) Maximum wet - bulb temperature at 39 °C or less. (Ta > 40 °C) No condensation.




Figure 2. Temperature and Relative Humidity Range

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

3.0 ELECTRICAL SPECIFICATIONS

3.1 Electrical Specifications

< Table 3. Electrical Specifications >

Ta=25+/-2℃

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	3.0	3.3	3.6	V	Note 1
Permissible Input Ripple Voltage	V _{RF}	-	-	100	mV	@ V _{DD} = 3.3V
BIST Control Level	High Level	2	-	3.6	V	-
	Low Level	0	-	0.8	V	-
Power Supply Current	I _{DD}	-	279	485	mA	Note 1
Power Supply Inrush Current	I _{nrush}	-	-	2	A	Note3
Power Consumption	P _D	-	0.92	1.6	W	Note 1
	P _{BL}	-	-	2.9	W	Note 2
	P _{total}	-	3.82	4.5	W	Note 1

- Notes :
1. The supply voltage is measured and specified at the interface connector of LCM.

The current draw and power consumption specified is for 3.3V at 25 °C.

a) Typ : Mosaic pattern 8*8

b) Max : R/G/B patterns




Figure 3. Power Measure Patterns

2. Calculated value for reference (V_{LED} × I_{LED})
3. Measure condition (Figure 4)




Figure 4. Inrush Measure Condition

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	7 OF 34

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

3.2 Backlight Unit

< Table 4. LED Driving Guideline Specifications > Ta=25+/-2°C

Parameter			Min.	Typ.	Max.	Unit	Remarks
LED Forward Voltage		V _F	-	-	2.9	V	-
LED Forward Current		I _F	-	23.5	-	mA	-
LED Power Consumption		P _{LED}	-	-	2.9	W	Note 1
LED Life-Time		N/A	15,000	-	-	Hour	I _F = 23.5mA
Power Supply Voltage for LED Driver		V _{LED}	5	12	21	V	-
Power Supply Voltage for LED Driver Inrush		I _{led inrush}	-	-	2	A	Note 4
EN Control Level	Backlight On		2.5	-	5.0	V	-
	Backlight Off		0	-	0.6	V	-
PWM Control Level	High Level		2.5	-	5.0	V	-
	Low Level		0	-	0.6	V	-
PWM Control Frequency		F _{PWM}	200	-	10,000	Hz	-
Duty Ratio			1	-	100	%	Note 3

Notes :

- Power supply voltage12V for LED driver.

Calculator value for reference $I_F \times V_F \times 36$ /driver efficiency = PLED
- The LED life-time define as the estimated time to 50% degradation of initial luminous.
- 1% duty cycle is achievable with a dimming frequency less than 1KHz.
- Measure condition (Figure 5)




Figure 5. Inrush Measure Condition

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	8 OF 34

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

3.3 LED Structure




Figure 6. LED Structure

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	9 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = 25±2°C) with the equipment of luminance meter system (PR730&PR810) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0°. We refer to θØ=0 (=θ3) as the 3 o’clock direction (the “right”), θØ=90 (= θ12) as the 12 o’clock direction (“upward”), θØ=180 (= θ9) as the 9 o’clock direction (“left”) and θØ=270(= θ6) as the 6 o’clock direction (“bottom”). While scanning θand/or Ø, the center of the measuring spot on the display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be 3.3+/- 0.3V at 25°C. Optimum viewing angle direction is 6 ’clock.

4.2 Optical Specifications

<Table 5. Optical Specifications>


Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle Range	Horizontal	Θ_3	CR > 10	-	85	-	Deg.	Note 1
		Θ_9		-	85	-	Deg.	
	Vertical	Θ_{12}		-	85	-	Deg.	
		Θ_6		-	85	-	Deg.	
Luminance Contrast Ratio		CR	$\Theta = 0^\circ$	-	800	-		Note 2
Luminance of White	5 Points	Y_w	$\Theta = 0^\circ$ $I_{LED} = 23.5mA$	255	300	-	cd/m ²	Note 3
White Luminance Uniformity	5 Points	$\Delta Y5$		80	-	-	%	Note 4
	13 Points	$\Delta Y13$		62.5	-	-	%	
White Chromaticity		W_x	$\Theta = 0^\circ$	0.283	0.309	0.343	-	Note 5
		W_y		0.299	0.340	0.359	-	
Reproduction of Color	Red	R_x	$\Theta = 0^\circ$	-0.03	0.648	+0.03	-	-
		R_y			0.345		-	-
	Green	G_x			0.330		-	-
		G_y			0.623		-	-
	Blue	B_x			0.153		-	-
		B_y			0.059		-	-
Color Gamut		-	-	-	72	-	%	-
Response Time (Rising + Falling)		T_{RT}	$T_a = 25^\circ C$ $\Theta = 0^\circ$	-	30	35	ms	Note 6
Cross Talk		CT	$\Theta = 0^\circ$	-	-	4.7	%	Note 7

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	10 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19
<p>Notes :</p> <ol style="list-style-type: none"> Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see Figure 7). Contrast measurements shall be made at viewing angle of $\Theta = 0$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state . (see Figure 7) Luminance Contrast Ratio (CR) is defined mathematically. <div style="text-align: center;"> $CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$ </div> Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in Figure 8 for a total of the measurements per display. The White luminance uniformity on LCD surface is then expressed as : $\Delta Y = \text{Minimum Luminance of 5(or 13) points} / \text{Maximum Luminance of 5(or 13) points.}$(see Figure 8 and Figure 9). The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel. The electro-optical response time measurements shall be made as Figure 10 by switching the “data” input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_r, and 90% to 10% is T_r. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a $10 \pm 1\text{mm}$ diameter area, with all display pixels set to gray 127(of 0 to 255), to the luminance (YB) of that same area when any adjacent area is driven dark.The luminance ratio shall not exceed 1:1.05 (See Figure 11). 			
SPEC. NUMBER	SPEC. TITLE	PAGE	
	NV133FHM-N62 V8.1 Product Specification Rev. 0	11 OF 34	

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

4.3 Optical Measurements



Optical characteristics measurement setup

Figure 7. Measurement Set Up




Figure 8. White Luminance and Uniformity Measurement Locations (5 points)

Center Luminance of white is defined as luminance values of center 5 points across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in Figure 7 for a total of the measurements per display.

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	12 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19




Figure 9. Uniformity Measurement Locations (13 points)

The White luminance uniformity on LCD surface is then expressed as : $\Delta Y5$ = Minimum Luminance of five points / Maximum Luminance of five points (see Figure 8) , $\Delta Y13$ = Minimum Luminance of 13 points /Maximum Luminance of 13 points (see Figure 9).





Figure 10. Response Time Testing

The electro-optical response time measurements shall be made as shown in Figure 10 by switching the “data” input signal ON and OFF. Tr: The luminance to change from 90% to 10% ,Tf: The luminance to change from 10% to 90% .

The test system : PR810

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	13 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19



Cross Talk (%) =

$$\left| \frac{Y_B - Y_A}{Y_B} \right| \times 100$$

Figure 11. Cross Talk Modulation Test Description

Where:

Y_A = Initial luminance of measured area (cd/m²)

Y_B = Subsequent luminance of measured area (cd/m²)

The location measured will be exactly the same in both patterns. The test background gray is L127.

Cross Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 10±1mm diameter area, with all display pixels set to a gray level 127, to the luminance (YB) of that same area when any adjacent area is driven dark.(Refer to Figure 11)

The test system: PR730

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	14 OF 34

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

5.0 INTERFACE CONNECTION

5.1 Electrical Interface Connection

The electronics interface connector is UJU IS050-L30B-C10.
The connector interface pin assignments are listed in Table 6.

<Table 6. Pin Assignments for the Interface Connector>

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	NC	No Connection
2	H_GND	Ground
3	LANE1_N	eDP RX Channel 1 Negative
4	LANE1_P	eDP RX Channel 1 Positive
5	H_GND	Ground
6	LANE0_N	eDP RX Channel 0 Negative
7	LANE0_P	eDP RX Channel 0 Positive
8	H_GND	Ground
9	AUX_CH_P	eDP AUX CH Positive
10	AUX_CH_N	eDP AUX CH Negative
11	H_GND	Ground
12	LCD_VCC	Power Supply, 3.3V (typ.)
13	LCD_VCC	Power Supply, 3.3V (typ.)
14	BIST	Panel Self Test Enable
15	H_GND	Ground
16	H_GND	Ground
17	HPD	Hot Plug Detect Output
18	BL_GND	LED Ground
19	BL_GND	LED Ground
20	BL_GND	LED Ground
21	BL_GND	LED Ground
22	BL_ENABLE	LED Enable Pin(+3.3V Input)
23	BL_PWM	System PWM Signal Input
24	NC	No Connection
25	NC	No Connection
26	BL_POWER	LED Power Supply 5V-21V
27	BL_POWER	LED Power Supply 5V-21V
28	BL_POWER	LED Power Supply 5V-21V
29	BL_POWER	LED Power Supply 5V-21V
30	NC	No Connection

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	15 OF 34

5.2 eDP Interface




Figure 12. eDP Interface Architecture

Note:
 Transmitter : Parade DP501 or equivalent.
 Transmitter is not contained in module.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

5.3 Data Input Format




Figure 13. Display Position of Input Data (V-H)

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	17 OF 34

	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

5.4 Back-light & LCM Interface Connection

BLU Interface Connector: UJU PF040-B09B-C09.

<Table 7. Pin Assignments for the BLU Connector>

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	LED	LED cathode connection	6	NC	No Connection
2	LED	LED cathode connection	7	Vout	LED anode connection
3	LED	LED cathode connection	8	Vout	LED anode connection
4	LED	LED cathode connection	9	Vout	LED anode connection
5	NC	No Connection			

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

6.0 SIGNAL TIMING SPECIFICATION

6.1 The NV133FHM-N62 V8.1 Is Operated By The DE Only

< Table 8. Signal Timing Specification >

Item		Symbols	Min	Typ	Max	Unit
Clock	Frequency	1/Tc	146.6	147.8	149	MHz
Frame Period		Tv	1115	1120	1125	lines
			-	60	-	Hz
			-	16.67	-	ms
Vertical Display Period		Tvd	-	1080	-	lines
One line Scanning Period		Th	2192	2200	2208	clocks
Horizontal Display Period		Thd	-	1920	-	clocks

Note : The above is as optimized setting.

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	19 OF 34

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

6.2 eDP Rx Interface Timing Parameter

The specification of the eDP Rx interface timing parameter is shown in Table 9.

<Table 9. eDP Main-Link RX TP4 Package Pin Parameters>

Item	Symbol	Min	Typ	Max	Unit	Remark
Spread spectrum clock (Link clock down-spreading)	ssc	-	-	0.5	%	
Differential peak-to-peak input voltage at package pins	VRX-DIFFp-p	100	-	1320	mV	
Rx input DC common mode voltage	VRX_DC_CM	0	-	2	V	
Differential termination resistance	RRX-DIFF	80	-	120	Ω	
Single-ended termination resistance	RRX-SE	40	-	60	Ω	
Rx short circuit current limit	IRX_SHORT	-	-	50	mA	
Intra-pair skew at Rx package pins (HBR) RX intra-pair skew tolerance at HBR	LRX_SKEW_INTRA_PAIR	-	-	60	ps	




Figure 14. VRX-DIFFp-p & LRX_SKEW_INTRA_PAIR

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	20 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

7.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

<Table 10. Input Signal & Basic Display Colors & Gray Scale of Colors >

	Colors & Gray scale	Data signal																	
		R0	R1	R2	R3	R4	R5	G0	G1	G2	G3	G4	G5	B0	B1	B2	B3	B4	B5
Basic colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Light Blue	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Purple	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray scale of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△ ▽	↕						↕						↕					
	Brighter ▽	1	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	▽	0	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Gray scale of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
△		0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0
Darker		0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0
△ ▽		↕						↕						↕					
Brighter ▽		0	0	0	0	0	0	1	0	1	1	1	1	0	0	0	0	0	0
▽		0	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0
Green		0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Gray scale of Blue		Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0
	△ ▽	↕						↓						↕					
	Brighter ▽	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Gray scale of White & Black	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
△		1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0
Darker		0	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0
△ ▽		↕						↕						↕					
Brighter ▽		1	0	1	1	1	1	1	0	1	1	1	1	1	0	1	1	1	1
▽		0	1	1	1	1	1	0	1	1	1	1	1	0	1	1	1	1	1
White		1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	21 OF 34

8.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below.




Figure 15. Power Sequence

- | | | |
|------------------------|-----------------------|---------------|
| ● 0.5ms ≤ T1 ≤ 10 ms | ● 0ms < T10 < 500 ms | ● 0ms < T16 |
| ● 0ms < T2 ≤ 200 ms | ● 0.5ms ≤ T11 ≤ 10 ms | ● 0.5ms ≤ T17 |
| ● 0ms < T3 ≤ 200 ms | ● 500ms ≤ T12 | ● 0.5ms ≤ T18 |
| ● T3+T4+T5+T6+T8>200ms | ● 0ms < T13 | |
| ● 0ms < T7 ≤ 50ms | ● 0ms < T14 | |
| ● T7 < T8 | ● 0ms < T15 | |
| ● 0ms < T9 | | |

Notes:

- When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
- Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

9.0 Connector Description

Physical interface is described as for the connector on LCM.
 These connectors are capable of accommodating the following signals and will be following components.

9.1 TFT LCD Module

< Table 11. Signal Connector >

Connector Name /Description	For Signal Connector
Manufacturer	UJU
Type/ Part Number	UJU IS050-L30B-C10
Mating Housing/ Part Number	I-PEX 20454-030T

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	23 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

10.0 MECHANICAL CHARACTERISTICS

10.1 Dimensional Requirements

Figure 23 shows mechanical outlines for the model NV133FHM-N62 V8.1
 Other parameters are shown in Table 12.

<Table 12. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	293.76 (H) x 165.24 (V)	mm
Number of pixels	1920 (H) X 1080 (V) (1 pixel = R + G + B dots)	pixels
Pixel pitch	153(H) × 153(V)	um
Pixel arrangement	RGB Vertical stripe	
Display colors	262K(6bit)	
Display mode	Normally Black	
Dimensional outline	300.56(H)*188.25(V) (w/PCB)*2.4 (max) 300.56(H)*177.69(V)*2.4 (max)	mm
Weight	215 (max)	g

10.2 Mounting

See Figure 20.

10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an AG coating to minimize reflection and a coating to reduce scratching.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	24 OF 34

11.0 RELIABILITY TEST

The reliability test items and its conditions are shown in below.

<Table 13. Reliability Test>

No	Test Items	Conditions
1	High temperature storage test	Ta = 60°C , 60%RH, 240 hrs
2	Low temperature storage test	Ta = -20°C , 240 hrs
3	High temperature & high humidity operation test	Ta = 50°C , 80%RH, 240 hrs
4	High temperature operation test	Ta = 50°C , 60%RH, 240 hrs
5	Low temperature operation test	Ta = 0°C , 240 hrs
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 60% ± 3%RH, 100 cycle
7	Vibration test (non-operating)	Ta = 25°C , 60%RH, 1.5G, 10~500Hz, Half Sine X,Y,Z / Sweep rate : 1 hour
8	Shock test (non-operating)	Ta = 25°C , 60%RH, 220G, Half Sine Wave 2msec ± X, ± Y, ± Z Once for each direction
9	Electro-static discharge test (non-operating)	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV Ta = 25°C , 60%RH,

12.0 HANDLING & CAUTIONS

(1) Cautions when taking out the module

- Pick the pouch only, when taking out module from a shipping package.

(2) Cautions for handling the module

- As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
- As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
- As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
- Do not pull the interface connector in or out while the LCD module is operating.
- Put the module display side down on a flat horizontal plane.
- Handle connectors and cables with care.

(3) Cautions for the operation

- When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
- Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

- (4) Cautions for the atmosphere
- Dew drop atmosphere should be avoided.
 - Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.
- (5) Cautions for the module characteristics
- Do not apply fixed pattern data signal to the LCD module at product aging.
 - Applying fixed pattern for a long time may cause image sticking.
- (6) Other cautions
- Do not disassemble and/or re-assemble LCD module.
 - Do not re-adjust variable resistor or switch etc.
 - When returning the module for repair or etc. Please pack the module not to be broken. We recommend to use the original shipping packages.

13.0 LABEL

(1) Product Label




Figure 16. Product Label

Module ID Naming Rule:

<Table 14. Module ID Naming Rule>

Digit	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
Code	S	L	S	5	1	2	3	5	9	4	2	0	0	0	1	D	B
Description	Model Code /GBN		Grade	Line	Year		Month	Model Extension Code (Last 4 Digits Of FGCD)				Serial No 00001-ZZZZZZ					

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	26 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

(2) High voltage caution label




Figure 17. High Voltage Caution Label

(3) Box Label




Figure 18. Box Label

Serial number marked part needs to print, show as follows:

1. FG-CODE(Before 12 bit)
2. Product quantity
3. Box ID
4. Date
5. The client section material number(The client)---919668-L32
6. FG-Code After four ---
7. The supplier code
8. Total Size:100×50mm

<Table 15. Box Label Naming Rule >

Digit	1	2	3	4	5	6	7	8	9	10	11	12	13
Code	S	L	S	F	1	2	3	D	0	0	0	6	8
Description	Products GBN		Grade	Line	Year		Month	Revision Code	Serial No				

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	27 OF 34

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

14.0 PACKING INFORMATION

14.1 Packing Order




Figure 19. Packing Order

14.2 Note

- Box dimension: 480mm*350mm*285mm
- Package quantity in one box: 42pcs
- Total weight: 10.7kg/Box

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	28 OF 34

<div>BOE</div>	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

15.0 MECHANICAL OUTLINE DIMENSION




Figure 20. TFT-LCD Module Outline Dimension (Front View)

Note:

1. Top Polarizer is the highest part. (exclude cover tape *Remark#1)
2. Curve Spec: 0<=d<=0.5mm.
3. No light leakage from all 4 corners of LCM.
4. Size Unit: mm.
5. General Tolerance:±0.3mm.




Figure 21. Highest Point Position

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	29 OF 34

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19




Figure 22. TFT-LCD Module Outline Dimensions (Rear view)

- Note:
1. Top Polarizer is the highest part. (exclude cover tape *Remark#1)
 2. Curve Spec: 0<=d<=0.5mm.
 3. No light leakage from all 4 corners of LCM.
 4. Size Unit: mm.
 5. General Tolerance: ±0.3mm.

- Remark:
1. PCBA cover tape will bulge without external force due to the material character of the tape. The tolerance of PCB A cover tape thickness will not exceed 2 mm from surface of polarizer and thickness of PCBA side can be reformed to normal thickness by external force.
 2. If system interfere with panel or twist panel while system operation, it may cause ripple or acoustic noise or other side effect. Please prevent such twist or interfere by system operation.
 - 3.The system materials should contain no or less NH4+ ions.

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	30 OF 34

16.0 EDID Table

Address s (HEX)	Function	Hex	Dec	Input values.	Notes
00	Header	00	0	0	EDID Header
01		FF	255	255	
02		FF	255	255	
03		FF	255	255	
04		FF	255	255	
05		FF	255	255	
06		FF	255	255	
07		00	0	0	
08	ID Manufacturer Name	09	9	BOE	ID = BOE
09		E5	229		
0A	ID Product Code	2D	45	2093	ID = 2093
0B		08	8		
0C	32-bit serial No.	00	0		
0D		00	0		
0E		00	0		
0F		00	0		
10	Week of manufacture	23	35	35	
11	Year of Manufacture	1C	28	2018	Manufactured in 2018
12	EDID Structure Ver.	01	1	1	EDID Ver 1.0
13	EDID revision #	04	4	4	EDID Rev. 0.4
14	Video input definition	95	149	-	
15	Max H image size	1D	29	29	29 .367cm (Approx)
16	Max V image size	11	17	17	16.524 cm (Approx)
17	Display Gamma	78	120	2.2	Gamma curve = 2.2
18	Feature support	02	2		RGB display, Preferred Timming mode
19	Red/Green low bits	D5	213	-	Red / Green Low Bits
1A	Blue/White low bits	00	00	-	Blue / White Low Bits
1B	Red x high bits	A6	166	0.648	Red (x) = 10100110 (0.648)
1C	Red y high bits	58	88	0.345	Red (y) = 01011000 (0.345)
1D	Green x high bits	54	84	0.330	Green (x) = 01010100 (0.33)
1E	Green y high bits	9F	159	0.623	Green (y) = 10011111 (0.623)
1F	Blue x high bits	27	39	0.153	Blue (x) = 00100111 (0.153)
20	BLue y high bits	0F	15	0.059	Blue (y) = 00001111 (0.059)
21	White x high bits	4F	79	0.309	White (x) = 01001111 (0.309)
22	White y high bits	57	87	0.340	White (y) = 01010111 (0.34)
23	Established timing 1	00	0	-	
24	Established timing 2	00	0	-	

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev. 0	2018.07.19

25	Established timing 3	00	0	-	
26	Standard timing #1	01	1		Not Used
27		01	1		
28	Standard timing #2	01	1		Not Used
29		01	1		
2A	Standard timing #3	01	1		Not Used
2B		01	1		
2C	Standard timing #4	01	1		Not Used
2D		01	1		
2E	Standard timing #5	01	1		Not Used
2F		01	1		
30	Standard timing #6	01	1		Not Used
31		01	1		
32	Standard timing #7	01	1		Not Used
33		01	1		
34	Standard timing #8	01	1		Not Used
35		01	1		
36	Detailed timing/monitor descriptor #1	C0	192	147.8	147.84MHz Main clock
37		39	57		
38		80	128	1920	Hor Active = 1920
39		18	24	280	Hor Blanking = 280
3A		71	113	-	4 bits of Hor. Active + 4 bits of Hor. Blanking
3B		38	56	1080	Ver Active = 1080
3C		28	40	40	Ver Blanking = 40
3D		40	64	-	4 bits of Ver. Active + 4 bits of Ver. Blanking
3E		30	48	48	Hor Sync Offset = 48
3F		20	32	32	H Sync Pulse Width = 32
40		36	54	3	V sync Offset = 3 line
41		00	0	6	V Sync Pulse width : 6 line
42		26	38	294	Horizontal Image Size = 293.76 mm (Low 8 bits)
43		A5	165	165	Vertical Image Size = 165.24 mm (Low 8 bits)
44		10	16	-	4 bits of Hor Image Size + 4 bits of Ver Image Size
45		00	0	0	Hor Border (pixels)
46		00	0	0	Vertical Border (Lines)
47		1A	26	-	Refer to right table

SPEC. NUMBER	SPEC. TITLE	PAGE
	NV133FHM-N62 V8.1 Product Specification Rev. 0	32 OF 34

BOE		PRODUCT GROUP			REV	ISSUE DATE
		Customer Spec			Rev. 0	2018.07.19
48	Detailed timing/monitor descriptor #2	00	0	0	0MHz Main clock	
49		00	0			
4A		00	0	0	Hor Active = 0	
4B		00	0	0	Hor Blanking = 0	
4C		00	0	-	4 bits of Hor. Active + 4 bits of Hor. Blanking	
4D		00	0	0	Ver Active = 0	
4E		00	0	0	Ver Blanking = 0	
4F		00	0	-	4 bits of Ver. Active + 4 bits of Ver. Blanking	
50		00	0	0	Hor Sync Offset = 0	
51		00	0	0	H Sync Pulse Width = 0	
52		00	0	0	V sync Offset = 0 line	
53		00	0	0	V Sync Pulse width : 0 line	
54		00	0	0	Horizontal Image Size = 0 mm (Low 8 bits)	
55		00	0	0	Vertical Image Size = 0 mm (Low 8 bits)	
56		00	0	-	4 bits of Hor Image Size + 4 bits of Ver Image Size	
57		00	0	0	Hor Border (pixels)	
58		00	0	0	Vertical Border (Lines)	
59		00	0	-		
5A	Detailed timing/monitor descriptor #3	00	0		Indicates descriptor #3 is a display Descriptor	
5B		00	0			
5C		00	0		Reserved	
5D		FE	254		Tag : ASCII String	
5E		00	0		Reserved	
5F		42	66	B	Manufacture name : BOECQ	
60		4F	79	O		
61		45	69	E		
62		20	32			
63		43	67	C		
64		51	81	Q		
65		0A	10			
66		20	32			
67		20	32			
68		20	32			
69	20	32				
6A	20	32				
6B	20	32				

6C	Detailed timing/monitor descriptor #4	00	0		Indicates descriptor #4 is a display Descriptor
6D		00	0		
6E		00	0		
6F		FE	254		Reserved
70		00	0		Tag : ASCII String
71		00	0		Reserved
72		4E	78	N	Model name:NV133FHM-N62
73		56	86	V	
74		31	49	1	
75		33	51	3	
76		33	51	3	
77		46	70	F	
78		48	72	H	
79		4D	77	M	
7A		2D	45	-	
7B		4E	78	N	
7C		36	54	6	
7D		32	50	2	
7E	Extension flag	0A	10	0	
7F	Checksum	00	0	1	0 : 1個EDID ; N-1 : N个EDID
		40	64	-	