




## Product Specification

AU OPTRONICS CORPORATION

( V ) Preliminary Specifications

( ) Final Specifications

Module	13.3"(13.26") FHD 16:9 Color TFT-LCD with LED Backlight design
Model Name	B133HAK01.1 (HW:0A)
Note (  )	<i>oTP Display</i>

Customer

Date

Checked &  
Approved by

Date

Note: This Specification is subject to change without notice.

Approved by

Date

Wen Hwa

08/02/2016

Prepared by

Date

Coppy Tung

08/02/2016

**AU Optronics corporation**



## Contents

<b>1. Handling Precautions .....</b>	<b>4</b>
<b>2. General Description .....</b>	<b>5</b>
2.1 General Specification.....	5
2.2 General Touch Specification .....	7
2.3 Optical Characteristics .....	8
2.3 Optical Characteristics .....	8
<b>3. Functional Block Diagram .....</b>	<b>13</b>
<b>4. Absolute Maximum Ratings .....</b>	<b>13</b>
4.1 Absolute Ratings of TFT LCD Module .....	13
4.2 Absolute Ratings of Touch Sensor Module .....	13
4.3 Absolute Ratings of Environment.....	14
<b>5. Electrical Characteristics.....</b>	<b>15</b>
5.1 TFT LCD Module .....	15
5.2 Backlight Unit.....	18
5.3 Touch Sensor Module .....	19
<b>6. Signal Interface Characteristic.....</b>	<b>20</b>
6.1 Pixel Format Image.....	20
6.2 Integration Interface Requirement .....	21
6.3 Interface Timing .....	24
6.4 Power ON/OFF Sequence .....	25
<b>7. Panel Reliability Test .....</b>	<b>28</b>
7.1 Vibration Test .....	28
7.2 Shock Test .....	28
7.3 Reliability Test.....	28
<b>8. Mechanical Characteristics.....</b>	<b>29</b>
8.1 Total Solution Outline Dimension .....	29
<b>9. Shipping and Package .....</b>	<b>31</b>
9.1 Shipping Label Format.....	31
9.2 Carton Package .....	32
9.3 Shipping Package of Palletizing Sequence .....	32
<b>10. Appendix: EDID Description .....</b>	<b>33</b>



# Product Specification

AU OPTRONICS CORPORATION

## Record of Revision

Version and Date	Page	Old description	New Description	Remark
0.1 2016/03/11	All	First Edition for Customer		
0.2 2016/03/16	P32		EDID update	
0.3 2016/03/23	P7	Interface: USB	Interface: I2C	
	P13		Functional Block Diagram update	
	P21		Pin Assignment update	
0.4 2016/04/26	P32		EDID update	
0.5 2016/06/02	P29		2D drawing update	
0.6 2016/08/02	P8		Update R/G/B coordinate	
	P32		Update Carton Package	

## 1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 10) After installation of the TFT Module into an enclosure (Notebook PC Bezel, for example), do not twist nor bend the TFT Module even momentarily. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 11) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 12) Disconnecting power supply before handling LCD modules, it can prevent electric shock, DO NOT TOUCH the electrode parts, cables, connectors and LED circuit part of TFT module that a LED light bar build in as a light source of back light unit. It can prevent electrostatic breakdown.

## 2. General Description

B133HAK01.1 is a Color Active Matrix Liquid Crystal Display composed of a TFT LCD panel, a driver circuit, and LED backlight system. The screen format is intended to support the 16:9 FHD, 1920(H) x1080(V) screen and 262K colors (RGB –6bits with FRC)with LED backlight driving circuit. All input signals are eDP (Embedded DisplayPort) interface compatible.

B133HAK01.1 is designed for a display unit of notebook style personal computer and industrial machine.

### 2.1 General Specification

The following items are characteristics summary on the table at 25 °C condition:

Items	Unit	Specifications			
Screen Diagonal	[mm]	336.71			
Active Area	[mm]	293.472x165.078			
Pixels H x V		1920x3(RGB) x 1080			
Pixel Pitch	[mm]	0.1529 x 0.1529			
Pixel Format		R.G.B. Vertical Stripe			
Display Mode		Normally Black			
White Luminance (I <sub>LED</sub> =24mA) (Note: I <sub>LED</sub> is LED current)	[cd/m <sup>2</sup> ]	310 max. (5 points average) 250 typ. (5 points average) 215 min. (5 points average)			
Luminance Uniformity		1.25 max. (5 points)			
Contrast Ratio		800 typ			
Response Time	[ms]	27 typ / 35 Max			
Nominal Input Voltage VDD	[Volt]	+3.3 typ.			
Power Consumption	[Watt]	3.2 max (Include Logic and Blu power)			
Weight	[Grams]	260 max (Total Solution) <sup>1</sup>			
Physical Size Include bracket	[mm]		Min.	Typ.	Max.
		Length	190.2	190.7	191.2
		Width	305.8	306.3	306.8

<sup>1</sup> Total solution max weight includes touch sensor FPCA and OGS.



## Product Specification

AU OPTRONICS CORPORATION

		Thickness	-	-	3.0 (Panel Side) 3.2 (PCBA Side)
Electrical Interface		2 Lane eDP 1.2			
Glass Thickness	[mm]	0.4			
Surface Treatment		Anti Glare			
Support Color		262K colors ( RGB 6-bit )			
Temperature Range					
Operating	[°C]	0 to +50			
Storage (Non-Operating)	[°C]	-20 to +60			
RoHS Compliance		RoHS Compliance			

## 2.2 General Touch Specification

Item	Spec	Unit
Type of Touch Sensor	Projective Capacitive (On cell)	
Panel Size	13.3"	
Outline Dimension	NA	mm
Total Thickness	NA	mm
Total Weight	NA	g
TP View Area	293.472 X 165.078 typ	mm
TP Active Area	295.82 X 167.44 typ	mm
Interface	I2C	
Report Rate	Follow win10 – $\geq 100\text{Hz}$	Hz
Multi-Touch Point	10 points	
Input method	Finger	
Touch panel sensor IC	Raydium (RM32380)	
Channel	70 x 40	
Distance between 2 point	Follow win10	mm
Surface hardness	3 (Note 1)	H
Surface treatment	NA	
TP F/W version	TBD (Version : 00)	
Support OS	Window 10	
BM ink	TBD	
TP Power Consumption	Active Mode: TBD	mW



# Product Specification

AU OPTRONICS CORPORATION


## 2.3 Optical Characteristics

The optical characteristics are measured under stable conditions at 25°C (Room Temperature) :


Item		Symbol	Conditions	Min.	Typ.	Max.	Unit	Note
White Luminance ILED=24mA (Base Panel Only)			5 points average	215	250	310	cd/m2	1, 4, 5.
Viewing Angle		θR θL	Horizontal (Right) CR = 10 (Left)	80 80	85 85	- -	degree	4, 9
		ψH ψL	Vertical (Upper) CR = 10 (Lower)	80 80	85 85	- -		
Luminance Uniformity		δ5P	5 Points	-	-	1.25		1, 3, 4
Luminance Uniformity		δ13P	13 Points	-	-	1.6		2, 3, 4
Contrast Ratio		CR		700	800	-		4, 6
Cross talk		%				4		4, 7
Response Time		TRT	Rising + Falling	-	27	35		
Color / Chromaticity Coodinates	Red	Rx	CIE 1931	0.541	0.571	0.601	- - - -	4
		Ry		0.315	0.345	0.375		
	Green	Gx		0.316	0.346	0.376		
		Gy		0.541	0.571	0.601		
	Blue	Bx		0.128	0.158	0.188		
		By		0.086	0.116	0.146		
	White	Wx		0.283	0.313	0.343		
		Wy		0.299	0.329	0.359		
NTSC		%		-	45	-		



**Note 1:** 5 points position (Ref: Active area)



**Note 2:** 13 points position (Ref: Active area)



**Note 3:** The luminance uniformity of 5 or 13 points is defined by dividing the maximum luminance values by the minimum test point luminance


$$\delta_{W5} = \frac{\text{Maximum Brightness of five points}}{\text{Minimum Brightness of five points}}$$

$$\delta_{W13} = \frac{\text{Maximum Brightness of thirteen points}}{\text{Minimum Brightness of thirteen points}}$$

**Note 4:** Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting

Backlight for 30 minutes in a stable, windless and dark room, and it should be measured in the center of screen.



**Note 5 :** Definition of Average Luminance of White ( $Y_L$ ):

Measure the luminance of gray level 63 at 5 points ,  $Y_L = [L(1) + L(2) + L(3) + L(4) + L(5)] / 5$

$L(x)$  is corresponding to the luminance of the point X at Figure in Note (1).

**Note 6 :** Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$


**Note 7 :** Definition of Cross Talk (CT)

$$CT = |Y_B - Y_A| / Y_A \times 100 (\%)$$

Where


$Y_A$  = Luminance of measured location without gray level 0 pattern (cd/m<sup>2</sup>)

$Y_B$  = Luminance of measured location with gray level 0 pattern (cd/m<sup>2</sup>)




**Note 8:** Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are changed from “Black” to “White” (falling time) and from “White” to “Black” (rising time), respectively. The response time interval between the 10% and 90% of amplitudes. Refer to figure as below.




## Note 9. Definition of viewing angle

Viewing angle is the measurement of contrast ratio  $\geq 10$ , at the screen center, over a  $180^\circ$  horizontal and  $180^\circ$  vertical range (off-normal viewing angles). The  $180^\circ$  viewing angle range is broken down as follows;  $90^\circ$  ( $\theta$ ) horizontal left and right and  $90^\circ$  ( $\phi$ ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



## 3. Functional Block Diagram



## 4. Absolute Maximum Ratings

An absolute maximum rating of the module is as following:

### 4.1 Absolute Ratings of TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	Vin	-0.3	4	[Volt]	Note 1,2

### 4.2 Absolute Ratings of Touch Sensor Module

Item	Symbol	Min	Max	Unit	Conditions
Touch Sensor Module Power Voltage	VTSP	-0.3	3.6	[Volt]	

Touch Sensor Module Reset Signal	RST	-0.3	3.6	[Volt]	
Touch Sensor Module enable Signal	TP_EN	-0.3	3.6	[Volt]	

## 4.3 Absolute Ratings of Environment

Item	Symbol	Min	Max	Unit	Conditions
Operating Temperature	TOP	0	+50	[°C]	Note 4
Operation Humidity	HOP	5	95	[%RH]	Note 4
Storage Temperature	TST	-20	+60	[°C]	Note 4
Storage Humidity	HST	5	95	[%RH]	Note 4

Note 1: At Ta (25°C )

Note 2: Permanent damage to the device may occur if exceed maximum values


Note 3: LED specification refer to section 5.2

Note 4: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).

Note 5: The packing material of system forbid to involve ammonium component

Note 6: The reliability test conditions of system do not exceed the verified conditions of TFT module

Note 7: Be sure the panel test condition do not exceed the component limitation of TFT module(TN Liquid crystal , for example)



## 5. Electrical Characteristics

### 5.1 TFT LCD Module

#### 5.1.1 Power Specification


Input power specifications are as follows;

The power specification are measured under 25°C and frame frequency under 60Hz

Symble	Parameter	Min	Typ	Max	Units	Note
VDD	Logic/LCD Drive Voltage	3.0	3.3	3.6	[Volt]	
PDD	VDD Power	-	-	0.8	[Watt]	Note 1
IDD	IDD Current	-	-	267	[mA]	Note 1
IRush	Inrush Current	-	-	2000	[mA]	Note 2
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	100	[mV] p-p	

Note 1 : Maximum Measurement Condition : Mosaic pattern at 3.3V driving voltage. ( $P_{max}=V_{3.3} \times I_{white}$ )

Note 2 : Measure Condition



## 5.1.2 Signal Electrical Characteristics


Signal electrical characteristics are as follows;

### Display Port main link signal:

Differential pair VD+ , VD-  
Which is one Display port  
Main link

VCM of Display port  
Main link

$$V_{diffP-P} = [(VD+) - (VD-)] \times 2$$




Display port main link					
		Min	Typ	Max	unit
VCM	RX input DC Common Mode Voltage		0		V
VDiff <sub>P-P</sub>	Peak-to-peak Voltage at a receiving Device	150		1320	mV

Follow as VESA display port standard V1.3

### Display Port AUX\_CH signal:

Differential AUX+ , AUX-  
Which is Display port AUX\_CH







## Product Specification

AU OPTRONICS CORPORATION

Display port AUX_CH					
		Min	Typ	Max	unit
VCM	AUX DC Common Mode Voltage		0		V
VDiff <sub>P-P</sub>	AUX Peak-to-peak Voltage at a receiving Device	270		800	mV

Follow as VESA display port standard V1.3

### Display Port VHPD signal:

Display port VHPD					
		Min	Typ	Max	unit
VHPD	HPD Voltage	2.25	-	3.6	V

Follow as VESA display port standard V1.3



## Product Specification

AU OPTRONICS CORPORATION

### 5.2 Backlight Unit

#### 5.2.1 LED characteristics

Parameter	Symbol	Min	Typ	Max	Units	Condition
Backlight Power Consumption	PLED	-	-	2.4	[Watt]	(Ta=25°C), Note 1
LED Life-Time	N/A	15,000	-	-	Hour	(Ta=25°C), Note 2 I <sub>F</sub> =24 mA

**Note 1:** Calculator value for reference  $P_{LED} = V_F$  (Normal Distribution) \*  $I_F$  (Normal Distribution) / Efficiency

**Note 2:** The LED life-time define as the estimated time to 50% degradation of initial luminous.

#### 5.2.2 Backlight input signal characteristics

Parameter	Symbol	Min	Typ	Max	Units	Remark
LED Power Supply	VLED (Note 1)	5.0 (Note 2)	12.0	21.0	[Volt]	Define as Connector Interface (Ta=25°C)
LED Enable Input High Level	VLED_EN	2.2	-	5.5	[Volt]	
LED Enable Input Low Level		-	-	0.6	[Volt]	
PWM Logic Input High Level	VPWM_EN	2.2	-	5.5	[Volt]	
PWM Logic Input Low Level		-	-	0.6	[Volt]	
PWM Input Frequency	FPWM	200	1K	10K	Hz	
PWM Duty Ratio	Duty	1 (Note 3)	--	100	%	

**Note 1 :** Recommend system pull up/down resistor no bigger than 10kohm

**Note 2 :** measured in panel VIN



## Product Specification

AU OPTRONICS CORPORATION

**Note 3 :** If the PWM duty ratio(min) is set between 5% to 1% , the PWM input frequency should be set below 1KHz .

The brightness-duty characteristic might not be able to keep in it's linearity if the dimming control is operated in 1% to 5% range.

### 5.3 Touch Sensor Module


#### 5.3.1 Power Specification

Items	Symbol		Specifications			Unit	Notes
			Min.	Typ.	Max.		
Touch sensor module Power Supply	VTSP		4.5	5	5.5	V	
	VDDIO			3.3		V	
Touch Sensor Module Power ripple	VTSPrp		-	-	100	mV	
Input Voltage	RST, TP_EN	VIH	2.64		3.3	V	
		VIL	0		0.66	V	
Touch sensor module Power Consumption	P <sub>VTSP</sub>				0.3	W	Active mode

## 6. Signal Interface Characteristic

### 6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.



## 6.2 Integration Interface Requirement

### 6.2.1 Connector Description

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

Connector Name / Designation	For Signal Connector
Manufacturer	IPEX or compatible
Type / Part Number	IPEX 20525-040E-02 or compatible (0.4mm pitch or compatible)
Mating Housing/Part Number	IPX or compatible

### 6.2.2 Pin Assignment (with Touch Sensor Pin Assignment)


Pin	Symbol	Description
1	NC Reserved	Reserved for LCD supplier
2	GND	High Speed Ground
3	Lane1_N	Complement Signal Link Lane 1
4	Lane1_P	True Signal Link Lane 1
5	GND	High Speed Ground
6	Lane0_N	Complement Signal Link Lane 0
7	Lane0_P	True Signal Link Lane 0
8	GND	High Speed Ground
9	AUX_CH_P	True Signal Auxiliary Channel
10	AUX_CH_N	Complement Signal Auxiliary Channel
11	GND	High Speed Ground
12	VCC	LCD logic
13	VCC	LCD logic
14	LCD Self Test or NC	LCD Panel Self Test Enable (Optional)
15	GND	LCD logic and driver ground
16	GND	LCD logic and driver ground
17	HPD	HPD signal pin
18	BL_GND	LED Backlight ground
19	BL_GND	LED Backlight ground
20	BL_GND	LED Backlight ground
21	BL_GND	LED Backlight ground
22	BL_ENABLE	LED Backlight control on/off control
23	BL PWM	System PWM signal input for dimming
24	H_SYNC or NC	H_SYNC function(Optional) or NC
25	NC Reserved	Reserved for LCD supplier
26	VLED	LED Backlight Power (5-21V)
27	VLED	LED Backlight Power (5-21V)
28	VLED	LED Backlight Power (5-21V)
29	VLED	LED Backlight Power (5-21V)
30	NC	NC
31	Reset	Reset for Touch



## Product Specification


AU OPTRONICS CORPORATION

32	SCK	I2C Clock for Touch
33	SDA	I2C Data for Touch
34	INT	Interrupt for Touch
35	GND	GND
36	NC Reserved	Reserved for USB Device port data (+)
37	NC Reserved	Reserved for USB Device port data (-)
38	GND	GND
39	Touch_EN	Touch Enable (Active High)
40	VTSP 3.3V	3.3V power for touch



**Note1:** Start from right side.

**Note2:** Input signals shall be low or High-impedance state when VDD is off.  
Internal circuit of **eDP inputs** are as following.



## 6.3 Interface Timing

### 6.3.1 Timing Characteristics


Basically, interface timings should match the 1920x1080 /60Hz manufacturing guide line timing.

Parameter		Symbol	Min.	Typ.	Max.	Unit
Frame Rate		-		60	-	Hz
Clock frequency		1/ T <sub>Clock</sub>	66.6	72	80	MHz
Vertical Section	Period	T <sub>V</sub>	1090	1116	1080+A	T <sub>Line</sub>
	Active	T <sub>VD</sub>	1080			
	Blanking	T <sub>VB</sub>	10	36	A	
Horizontal Section	Period	T <sub>H</sub>	1000	1052	960+B	T <sub>Clock</sub>
	Active	T <sub>HD</sub>	960			
	Blanking	T <sub>HB</sub>	40	92	B	

**Note 1 :** The above is as optimized setting

**Note 2 :** The maximum clock frequency =  $(1920+B) \times (1080+A) \times 60 < 149.1 \text{ MHz}$

### 6.3.2 Timing diagram






## 6.4 Power ON/OFF Sequence


Power on/off sequence is as follows. Interface signals and LED on/off sequence are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off

### Display Port panel power sequence:



### Display port interface power up/down sequence, normal system operation

### Display Port AUX\_CH transaction only:



### Display port interface power up/down sequence, AUX\_CH transaction only



# Product Specification

AU OPTRONICS CORPORATION

## Display Port panel power sequence timing parameter:

Timing parameter	Description	Reqd. by	Limits			Notes
			Min.	Typ.	Max.	
T1	power rail rise time, 10% to 90%	source	0.5ms		10ms	
T2	delay from LCDVDD to black video generation	sink	0ms		200ms	prevents display noise until valid video data is received from the source
T3	delay from LCDVDD to HPD high	sink	0ms		200ms	sink AUX_CH must be operational upon HPD high.
T4	delay from HPD high to link training initialization	source				allows for source to read link capability and initialize.
T5	link training duration	source				dependant on source link to read training protocol.
T6	link idle	source				Min accounts for required BS-Idle pattern. Max allows for source frame synchronization.
T7	delay from valid video data from source to video on display	sink	0ms		50ms	max allows sink validate video data and timing.
T8	delay from valid video data from source to backlight enable	source				source must assure display video is stable.
T9	delay from backlight disable to end of valid video data	source				source must assure backlight is no longer illuminated.
T10	delay from end of valid video data from source to power off	source	0ms		500ms	
T11	power rail fall time, 90% to 10%	source			10ms	
T12	power off time	source	500ms			


**Note1:** The sink must include the ability to generate black video autonomously. The sink must automatically enable black video under the following conditions:

- upon LCDVDD power on (within T2 max)-when the "Novideostream\_Flag" (VB-ID Bit 3) is received from the source (at the end of T9).
- when no main link data, or invalid video data, is received from the source. Black video must be displayed within 64ms (typ) from the start of either condition. Video data can be deemed invalid based on MSA and timing information, for example.


**Note 2:** The sink may implement the ability to disable the black video function, as described in Note 1, above, for system development and debugging purpose.

**Note 3:** The sink must support AUX\_CH polling by the source immediately following LCDVDD power on without causing damage to the sink device (the source can re-try if the sink is not ready). The sink must be able to respond to an AUX\_CH transaction with the time specified within T3 max.

## Display Port panel B/L power sequence timing parameter:



Note : When the adapter is hot plugged, the backlight power supply sequence is shown as below.



	Min (ms)	Max (ms)
T13	0.2	10
T14	0	-
T15	0	-
T16	0	-
T17	0	-
T18	0.2	10
T19	1*	-
T20	1*	-


Seamless change:  $T19/T20 = 5 \times T_{PWM}^*$

\* $T_{PWM} = 1/PWM \text{ Frequency}$

Note 1 : If T14,T15,T16,T17<10ms , The display garbage may occur. We suggest T14,T15,T16,T17>10ms to avoid the display garbage.

Note 2 : If T13 or T18<0.5ms , the inrush current may cause the damage of fuse. If T13 or T18<0.5ms , the inrush current  $I^2t$  is under typical melt of fuse Spec. , there is no mentioned problem.

## Touch Panel Power on Sequence



	Min	Max
T21	10ms	-
T22	1ms	-
T23	20ms	-
T24	2ms	-
T25	2ms	-
T26	100ms	-

## 7. Panel Reliability Test

### 7.1 Vibration Test

**Test Spec:**

- Test method: Non-Operation
- Acceleration: 1.5 G
- Frequency: 10 - 500Hz Random
- Sweep: 30 Minutes each Axis (X, Y, Z)

### 7.2 Shock Test

**Test Spec:**

- Test method: Non-Operation
- Acceleration: 220 G , Half sine wave
- Active time: 2 ms
- Pulse: X,Y,Z .one time for each side

### 7.3 Reliability Test


Items	Required Condition	Note
Temperature Humidity Bias	Ta= 40°C, 90%RH, 300h	
High Temperature Operation	Ta= 50°C, Dry, 300h	
Low Temperature Operation	Ta=0°C, 300h	
High Temperature Storage	Ta= 60°C, 300h	
Low Temperature Storage	Ta= -20°C, 250h	
Thermal Shock Test	Ta=-20°C(30min) ~60°C(30min), 100cycles condition.	
ESD	Contact : ±8 KV Air : ±15 KV	Note 1

**Note1:** According to EN 61000-4-2 , ESD class B: Some performance degradation allowed. No data lost  
 . Self-recoverable. No hardware failures.

**Remark:** MTBF (Excluding the LED): 30,000 hours with a confidence level 90%


## 8.1 Total Solution Outline Dimension






## 9. Shipping and Package

### 9.1 Shipping Label Format






## 9.2 Carton Package



## 9.3 Shipping Package of Palletizing Sequence





## 10. Appendix: EDID Description

Address	FUNCTION	Value	Value	Value
HEX		HEX	BIN	DEC
00	Header	00	00000000	0
01		FF	11111111	255
02		FF	11111111	255
03		FF	11111111	255
04		FF	11111111	255
05		FF	11111111	255
06		FF	11111111	255
07		00	00000000	0
08	EISA Manuf. Code LSB	06	00000110	6
09	Compressed ASCII	AF	10101111	175
0A	Product Code	2D	00101101	45
0B	hex, LSB first	11	00010001	17
0C	32-bit ser #	00	00000000	0
0D		00	00000000	0
0E		00	00000000	0
0F		00	00000000	0
10	Week of manufacture	14	00010100	20
11	Year of manufacture	1A	00011010	26
12	EDID Structure Ver.	01	00000001	1
13	EDID revision #	04	00000100	4
14	<b>Video input def.</b> <i>(digital I/P, non-TMDS, CRGB)</i>	95	10010101	149
15	<b>Max H image size</b> <i>(rounded to cm)</i>	1D	00011101	29
16	<b>Max V image size</b> <i>(rounded to cm)</i>	11	00010001	17
17	<b>Display Gamma</b> <i>(=(gamma*100)-100)</i>	78	01111000	120
18	<b>Feature support</b> <i>(no DPMS, Active OFF, RGB, tmg Blk#1)</i>	02	00000010	2
19	Red/green low bits <b>(Lower 2:2:2:2 bits)</b>	C3	11000011	195
1A	Blue/white low bits <b>(Lower 2:2:2:2 bits)</b>	15	00010101	21
1B	Red x <b>(Upper 8 bits)</b>	93	10010011	147
1C	Red y/ highER 8 bits	58	01011000	88
1D	Green x	59	01011001	89
1E	Green y	92	10010010	146
1F	Blue x	29	00101001	41
20	Blue y	22	00100010	34
21	White x	50	01010000	80
22	White y	54	01010100	84
23	Established timing 1	00	00000000	0
24	Established timing 2	00	00000000	0
25	Established timing 3	00	00000000	0
26	Standard timing #1	01	00000001	1
27		01	00000001	1
28	Standard timing #2	01	00000001	1
29		01	00000001	1
2A	Standard timing #3	01	00000001	1
2B		01	00000001	1
2C	Standard timing #4	01	00000001	1

2D		01	00000001	1
2E	Standard timing #5	01	00000001	1
2F		01	00000001	1
30	Standard timing #6	01	00000001	1
31		01	00000001	1
32	Standard timing #7	01	00000001	1
33		01	00000001	1
34	Standard timing #8	01	00000001	1
35		01	00000001	1
36	Pixel Clock/10000 LSB	14	00010100	20
37	Pixel Clock/10000 USB	37	00110111	55
38	Horz active <b>Lower 8bits</b>	80	10000000	128
39	Horz blanking <b>Lower 8bits</b>	B8	10111000	184
3A	HorzAct:HorzBlnk <b>Upper 4:4 bits</b>	70	01110000	112
3B	Vertical Active <b>Lower 8bits</b>	38	00111000	56
3C	Vertical Blanking <b>Lower 8bits</b>	24	00100100	36
3D	Vert Act : Vertical Blanking <b>(upper 4:4 bit)</b>	40	01000000	64
3E	HorzSync. Offset	10	00010000	16
3F	HorzSync.Width	10	00010000	16
40	VertSync.Offset : VertSync.Width	3E	00111110	62
41	Horz&Vert Sync Offset/Width <b>Upper 2bits</b>	00	00000000	0
42	Horizontal Image Size <b>Lower 8bits</b>	25	00100101	37
43	Vertical Image Size <b>Lower 8bits</b>	A5	10100101	165
44	Horizontal & Vertical Image Size <b>(upper 4:4 bits)</b>	10	00010000	16
45	Horizontal Border <i>(zero for internal LCD)</i>	00	00000000	0
46	Vertical Border <i>(zero for internal LCD)</i>	00	00000000	0
47	Signal <i>(non-intr, norm, no stero, sep sync, neg pol)</i>	18	00011000	24
48	Detailed timing/monitor	10	00010000	16
49	descriptor #2	2C	00101100	44
4A		80	10000000	128
4B		B8	10111000	184
4C		70	01110000	112
4D		38	00111000	56
4E		24	00100100	36
4F		40	01000000	64
50		10	00010000	16
51		10	00010000	16
52		3E	00111110	62
53		00	00000000	0
54		25	00100101	37
55		A5	10100101	165
56		10	00010000	16
57		00	00000000	0
58		00	00000000	0
59		18	00011000	24
5A	Detailed timing/monitor	00	00000000	0
5B	descriptor #3	00	00000000	0
5C		00	00000000	0
5D		FE	11111110	254

5E		00	00000000	0
5F	Manufacture	41	01000001	65
60	Manufacture	55	01010101	85
61	Manufacture	4F	01001111	79
62		0A	00001010	10
63		20	00100000	32
64		20	00100000	32
65		20	00100000	32
66		20	00100000	32
67		20	00100000	32
68		20	00100000	32
69		20	00100000	32
6A		20	00100000	32
6B		20	00100000	32
6C	Detailed timing/monitor	00	00000000	0
6D	descriptor #4	00	00000000	0
6E		00	00000000	0
6F		FE	11111110	254
70		00	00000000	0
71	Manufacture P/N	42	01000010	66
72	Manufacture P/N	31	00110001	49
73	Manufacture P/N	33	00110011	51
74	Manufacture P/N	33	00110011	51
75	Manufacture P/N	48	01001000	72
76	Manufacture P/N	41	01000001	65
77	Manufacture P/N	4B	01001011	75
78	Manufacture P/N	30	00110000	48
79	Manufacture P/N	31	00110001	49
7A	Manufacture P/N	2E	00101110	46
7B	Manufacture P/N	31	00110001	49
7C		20	00100000	32
7D		0A	00001010	10
7E	Extension Flag	00	00000000	0
7F	Checksum	A5	10100101	165