Product Specification

(V) **Preliminary Specifications**
(   ) **Final Specifications**

Module	14.1" WXGA Color TFT-LCD with LED Backlight design
Model Name	*B141EW05 V3*
Note ( )	*LED Backlight design*

Customer	Date	Approved by	Date
		Beyond Yang	09/25/2008
Checked & Approved by	Date	Prepared by	
		Jeff Hou	09/25/2008
Note: This Specification is subject to change without notice.		**NBBU Marketing Division / AU Optronics corporation**	

Contents

Record of Revision

Version and Date	Page	Old description	New Description	Remark
0.1 2008/5/16	All	First Edition for Customer		
0.2 2008/5/26	12	LED Light bar Driving	Update LED Light bar Driving = 25.2 (Row Output)	
0.3 2008/6/9	29,30	Update drawing	Update drawing	
0.4 2008/8/14	32	Update Label	Update Label	
0.5 2008/9/25	6		Update response time and color coodinates	
	20,28		Update drawing	
	22		Update clock frequency =70.5	
	33		Update EDID	

1. Handling Precautions

1) Since front polarizer is easily damaged, pay attention not to scratch it.

2) Be sure to turn off power supply when inserting or disconnecting from input connector.

3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.

4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.

5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.

6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.

7) Do not open nor modify the Module Assembly.

8) Do not press the reflector sheet at the back of the module to any directions.

9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.

11) After installation of the TFT Module into an enclosure (Notebook PC Bezel, for example), do not twist nor bend the TFT Module even momentary. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.

12) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.

13) Disconnecting power supply before handling LCD modules, it can prevent electric shock, DO NOT TOUCH the electrode parts, cables, connectors and LED circuit part of TFT module that a LED light bar build in as a light source of back light unit. High voltage is supplied to these parts when power turn on.

2. General Description

B141EW05 V3 is a Color Active Matrix Liquid Crystal Display composed of a TFT LCD panel, and LED backlight system. The screen format is intended to support the WXGA (1280(H) x 800(V)) screen and 262k colors (RGB 6-bits data driver) . All input signals are LVDS interface compatible.

B141EW05 V3 is designed for a display unit of notebook style personal computer and industrial machine.

2.1 General Specification

The following items are characteristics summary on the table at 25 ℃ condition:

Items	Unit	Specifications			
Screen Diagonal	[mm]	357.7 (14.1W")			
Active Area	[mm]	303.36 X 189.6			
Pixels H x V		1280x3(RGB) x 800			
Pixel Pitch	[mm]	0.237			
Pixel Format		B.G.R. Vertical Stripe			
Display Mode		Normally White			
White Luminance (I_{LED}=20mA) Note: I_{LED} is LED current	[cd/m^2]	220 typ. (5 points average) 187 min. (5 points average) (Note1)			
Luminance Uniformity		1.25 max. (5 points)			
Contrast Ratio		400 typ			
Response Time	[ms]	8 typ / 12 Max			
Nominal Input Voltage VDD	[Volt]	+3.3 typ.			
Power Consumption	[Watt]	4.4 max. (Include Logic and Blu power)			
Weight	[Grams]	385 max.			
Physical Size **without inverter, bracket.**	[mm]		Min.	Typ.	Max.
		Length	319	319.5	320
		Width	205	205.5	206
		Thickness	4.8	-	5.5
Electrical Interface		1 channel LVDS			
Surface Treatment		Anti-Glare,			

| Support Color		262K colors (RGB 6-bit)

Temperature Range
  Operating
  Storage (Non-Operating)
	[^{o}C]
	[^{o}C]
		0 to +50
		-20 to +65

RoHS Compliance		RoHS Compliance

2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25℃ (Room Temperature) :

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit	Note
White Luminance **I$_{LED}$=20mA**		**5 points average**	187	220	-	**cd/m^2**	1, 4, 5.
Viewing Angle	θ R θ L	**Horizontal (Right)** **CR = 10 (Left)**	40 40	45 45	- -	**degree**	4, 9
	ϕ H ϕ L	**Vertical (Upper)** **CR = 10 (Lower)**	10 30	15 35	- -		
Luminance Uniformity	δ 5P	**5 Points**	-	-	1.25		1, 3, 4
Luminance Uniformity	δ 13P	**13 Points**	-	-	1.50		2, 3, 4
Contrast Ratio	**CR**		300	400	-		4, 6
Cross talk	**%**				4		4, 7
Response Time	T$_r$	**Rising**	-	6	10	**msec**	4, 8
	T$_f$	**Falling**	-	2	5		
	T$_{RT}$	**Rising + Falling**	-	8	12		
Color / Chromaticity Coodinates	**Red x**	**CIE 1931**	0.556	0.586	0.616		4
	Red y		0.316	0.346	0.376		
	Green x		0.311	0.341	0.371		
	Green y		0.546	0.576	0.606		
	Blue x		0.127	0.157	0.187		
	Blue y		0.090	0.120	0.150		
	White x		0.283	0.313	0.343		
	White y		0.299	0.329	0.359		
NTSC	**%**		-	45	-		

Note 1: 5 points position (Ref: Active area)

W

W /4   W /4   W /4   W /4

H /4

1   2

H /4

H   3

H /4

4   5

H /4

Note 2: 13 points position (Ref: Active area)

W

W /4   W /4   W /4   W /4

10   10

10

1   2   3

H /4

4   5

H /4

H   6   7   8

H /4

9   10

H /4

11   12   13

10

**Note 3**: The luminance uniformity of 5 or13 points is defined by dividing the maximum luminance values by the minimum test point luminance

$$\delta_{W5} = \frac{\text{Maximum Brightness of five points}}{\text{Minimum Brightness of five points}}$$

$$\delta_{W13} = \frac{\text{Maximum Brightness of thirteen points}}{\text{Minimum Brightness of thirteen points}}$$

Note 4: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room, , and it should be measured in the center of screen.

Center of the screen

Note 5： Definition of Average Luminance of White (Y_L):

Measure the luminance of gray level 63 at 5 points，Y_L = [L (1)+ L (2)+ L (3)+ L (4)+ L (5)] / 5

L (x) is corresponding to the luminance of the point X at Figure in Note (1).

Note 6： Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$

Note 7： Definition of Cross Talk (CT)

$CT = |\ Y_B - Y_A\ | / Y_A \times 100\ (\%)$

Where

Y_A = Luminance of measured location without gray level 0 pattern (cd/m2)

Y_B = Luminance of measured location with gray level 0 pattern (cd/m2)

Note 8: Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are changed from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval between the 10% and 90% of amplitudes. Refer to figure as below.

Note 9. Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10, at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° (θ) horizontal left and right and 90° (Φ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.

3. Functional Block Diagram

The following diagram shows the functional block of the 14.1 inches wide Color TFT/LCD 30 Pin
One ch / connector Module:

4. Absolute Maximum Ratings

An absolute maximum rating of the module is as following:

4.1 Absolute Ratings of TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	Vin	-0.3	+4.0	[Volt]	Note 1,2

4.2 Absolute Ratings of Backlight Unit

Item	Symbol	Min	Typ	Unit	Conditions
LED Light bar Driving	V_{LED}		25.2 (Row Output)	[Volt]	Note 1,2,3
LED Light bar Driving	I_{LED}	-	20 (Row Output)	[mA] rms	Note 1,3

4.3 Absolute Ratings of Environment

Item	Symbol	Min	Max	Unit	Conditions
Operating Temperature	TOP	0	+50	[^{o}C]	Note 4
Operation Humidity	HOP	8	95	[%RH]	Note 4
Storage Temperature	TST	-20	+65	[^{o}C]	Note 4
Storage Humidity	HST	5	95	[%RH]	Note 4

Note 1: At Ta (25℃)

Note 2: I_{LED} =20mA

Note 3: LED specification refer to section 5.2

Note 4: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).

Operating Range   Storage Range

5. Electrical characteristics

5.1 TFT LCD Module

5.1.1 Power Specification

Input power specifications are as follows;

The power specification are measured under 25℃ and frame frenquency under 60Hz

Symble	Parameter	Min	Typ	Max	Units	Note
VDD	Logic/LCD Drive Voltage	3.0	3.3	3.6	[Volt]	
PDD	VDD Power	-	-	1.1	[Watt]	Note 1/2
IDD	IDD Current	-	350	450	[mA]	Note 1/2
IRush	Inrush Current	-	-	2000	[mA]	Note 3
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	100	[mV] p-p	

Note 1 : Maximum Measurement Condition：Black Pattern

Note 2：Typical Measurement Condition: Mosaic Pattern

Note 3：Measure Condition

Vin rising time

5.1.2 Signal Electrical Characteristics

Input signals shall be low or High-impedance state when VDD is off.

It is recommended to refer the specifications of THC63LVDF84A (Thine Electronics Inc.) in detail.

Signal electrical characteristics are as follows;

Parameter	Condition	Min	Max	Unit
Vth	Differential Input High Threshold (Vcm=+1.2V)	-	100	[mV]
Vtl	Differential Input Low Threshold (Vcm=+1.2V)	-100	-	[mV]
Vcm	Differential Input Common Mode Voltage	1.125	1.375	[V]

Note: LVDS Signal Waveform

5.2 Backlight Unit

LED Parameter guideline for LED driving selection (Ref. Remark 1)

Parameter	Symbol	Min	Typ	Max	Units	Condition
LED Forward Voltage	V_F	2.95	3.15	3.35	[Volt]	(Ta=25℃) Note 1
LED Forward Current	I_F		20	30	[mA]	(Ta=25℃) Note 1
LED Life-Time	N/A	10,000	-	-	Hour	(Ta=25℃) I_F=20 mA Note 2

Note 1: Calculator value for LED chip specification

Note 2: The LED life-time define as the estimated time to 50% degradation of initial luminous.

![AUO logo]

6. Signal Characteristic

6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.

6.2 The input data format

RxCLKIN

RxIN0   G0   R5   R4   R3   R2   R1   R0

RxIN1   B1   B0   G5   G4   G3   G2   G1

RxIN2   DE   VS   HS   B5   B4   B3   B2

Signal Name	Description	
R5 R4 R3 R2 R1 R0	Red Data 5 (MSB) Red Data 4 Red Data 3 Red Data 2 Red Data 1 Red Data 0 (LSB) Red-pixel Data	Red-pixel Data Each red pixel's brightness data consists of these 6 bits pixel data.
G5 G4 G3 G2 G1 G0	Green Data 5 (MSB) Green Data 4 Green Data 3 Green Data 2 Green Data 1 Green Data 0 (LSB) Green-pixel Data	Green-pixel Data Each green pixel's brightness data consists of these 6 bits pixel data.
B5 B4 B3 B2 B1 B0	Blue Data 5 (MSB) Blue Data 4 Blue Data 3 Blue Data 2 Blue Data 1 Blue Data 0 (LSB) Blue-pixel Data	Blue-pixel Data Each blue pixel's brightness data consists of these 6 bits pixel data.
RxCLKIN	Data Clock	The signal is used to strobe the pixel data and DE signals. All pixel data shall be valid at the falling edge when the DE signal is high.
DE	Display Timing	This signal is strobed at the falling edge of RxCLKIN. When the signal is high, the pixel data shall be valid to be displayed.
VS	Vertical Sync	The signal is synchronized to RxCLKIN .
HS	Horizontal Sync	The signal is synchronized to RxCLKIN .

Note: Output signals from any system shall be low or High-impedance state when VDD is off.

6.3 Signal Description/Pin Assignment

LVDS is a differential signal technology for LCD interface and high speed data transfer device.

PIN#	Symbol	Function
1	GND	Ground
2	VDD	+3.3V Power Supply
3	VDD	+3.3V Power Supply
4	VEDID	+3.3V EDID Power
5	NC	No Connection (Reserve for AUO test)
6	CLKEDID	EDID Clock Input
7	DATAEDID	EDID Data Input
8	RxIN0-	-LVDS differential data input (R0-R5, G0)
9	RxIN0+	+LVDS differential data input (R0-R5, G0)
10	GND	Ground
11	RxIN1-	-LVDS differential data input(G1-G5, B0-B1)
12	RxIN1+	+LVDS differential data input(G1-G5, B0-B1)
13	GND	Ground
14	RxIN2-	-LVDS differential data input(B2-B5, HS, VS, DE)
15	RxIN2+	+LVDS differential data input(B2-B5, HS, VS, DE)

PIN#	Symbol	Function
16	GND	Ground
17	RxCLKIN-	-LVDS differential clock input
18	RxCLKIN+	+LVDS differential clock input
19	GND	Ground
20	NC	No Connection
21	NC	No Connection)
22	GND	Ground
23	NC	No Connection
24	NC	No Connection
25	GND	Ground
26	NC	No Connection
27	NC	No Connection
28	GND	Ground
29	NC	No Connection
30	NC	No Connection

Note1: Start from right side

Note2: Input signals shall be low or High-impedance state when VDD is off.

internal circuit of LVDS inputs are as following.
The module uses a 100ohm resistor between positive and negative data lines of each receiver input

Signal Input

LVDS Receiver

Pin No.

8   RxIN0-

9   RxIN0+

11 RxIN1-

12 RxIN1+

14 RxIN2-

15 RxIN2+

17 RxCLKIN-

18 RxCLKIN+

R

R

R

R

6.4 Interface Timing

6.4.1 Timing Characteristics

Basically, interface timings should match the 1280x800 /60Hz   manufacturing guide line timing.

Parameter		Symbol	Min.	Typ.	Max.	Unit
Frame Rate		-	-	60	-	**Hz**
Clock frequency		1/ T_{Clock}	-	71.3	-	**MHz**
Vertical Section	**Period**	T_V	808	823	1023	T_{Line}
	Active	T_{VD}	800	800	800	
	Blanking	T_{VB}	8	23	223	
Horizontal Section	**Period**	T_H	1310	1438	2047	T_{Clock}
	Active	T_{HD}	1280	1280	1280	
	Blanking	T_{HB}	30	158	767	

Note : DE mode only

6.4.2 Timing diagram

Input Timing Definition (DE Mode)

7. Connector Description

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

7.1 TFT LCD Module

Connector Name / Designation	For Signal Connector
Manufacturer	JAE or compatible
Type / Part Number	JAE FI-XB30SL-HF10 or compatible
Mating Housing/Part Number	JAE FI-X30H or compatible

8. LED Driving Specification

8.1 Connector Description

Connector Name / Designation	For Signal Connector
Manufacturer	HRS or compatible
Type / Part Number	`HRS FH33-12S-0.5SH(05)` or compatible
Mating Housing/Part Number	compatible

8.2 Pin Assignment

PIN#	Signal Name Description
1	LCD channel 1 cathode
2	LCD channel 2 cathode
3	LCD channel 3 cathode
4	LCD channel 4 cathode
5	LCD channel 5 cathode
6	LCD channel 6 cathode (May be NC if channel<6)
7	LCD channel 7 cathode (May be NC if channel<7)
8	LCD channel 8 cathode (May be NC if channel<8)
9	NC
10	LED power bus (LED Anode)
11	LED power bus (LED Anode)
12	LED power bus (LED Anode)

9. Vibration and Shock Test

9.1 Vibration Test

Test Spec:

- Test method:　Non-Operation
- Acceleration:　1.5 G , Half sine pulse
- Frequency:　10 - 500Hz Sine wave
- Sweep:　30 Minutes each Axis (X, Y, Z)

9.2 Shock Test Spec:

Test Spec:

- Test method:　Non-Operation
- Acceleration:　240 G , Half sine pulse
- Active time:　2 ms
- Pulse:　X,Y,Z .one time for each side

10. Reliability

Items	Required Condition	Note
Temperature Humidity Bias	Ta= 40℃, 90%RH, 300h	
High Temperature Operation	Ta= 50℃, Dry, 300h	
Low Temperature Operation	Ta= 0℃, 300h	
High Temperature Storage	Ta= 60℃, 300h	
Low Temperature Storage	Ta= -20℃, 300h	
Thermal Shock Test	Ta=-20℃ to 60℃, Duration at 30 min, 100 cycles	
ESD	Contact : ±8 KV Air : ±15 KV	Note 1

Note1: According to EN 61000-4-2 , ESD class B: Some performance degradation allowed. No data lost

.   Self-recoverable. No hardware failures.

Remark: MTBF (Excluding the LED): 30,000 hours with a confidence level 90%

11. Mechanical Characteristics

11.1 LCM Outline Dimension

319.50±0.50(OUTLINE)
306.96±0.20(BEZEL OPENING)
303.36(ACTIVE AREA)

160.85±0.30
153.38±0.30

5.50Max.
3.10±0.20(4X)
18.15±0.20

18.15±0.20
3.10±0.20(4X)

CN1

96.60±0.30
84.95±0.30

108.50±1.00

30.00±1.00

61.50±0.30
108.50±0.30
168.60±0.30

61.50±0.30
108.50±0.30
168.60±0.30

205.50±0.50(OUTLINE)
193.20±0.20(BEZEL OPENING)
189.60(ACTIVE AREA)

14.1"WXGA(1280x800 PIXELS)
ACTIVE AREA 303.36x189.6
PIXEL PITCH 0.237x0.237

NOTES:
1.UNSPECIFIED TOLERANCE TO BE +/-0.50mm
2.CN1:CONNECTOR TO BE (JAE)FI-XB30SL-HF10
3.UNIT:mm

6.50±0.50

11.00±0.50

35.00±2.00
125.00±2.00

(3.68)

7146637.0.0.4 MKO

SEE DETAIL A

PULL TAB
5.00
0.30±0.05

DETAIL A
SCALE 3.200

DETAIL B
SCALE 3.200

SHIPPING LABEL

BLU LABEL

SEE DETAIL B

11.2 Screw Hole Depth and Center Position

Screw hole minimum depth, from side surface = 2.5 mm (See drawing)

Screw hole center location, from front surface = 3.1 ± 0.2mm (See drawing)

Screw Torque: Maximum 2.5 kgf-cm

12. Shipping and Package

12.1 Shipping Label Format

‖‖‖‖‖‖‖‖‖‖‖‖‖‖‖‖‖‖‖‖‖ * XXXXXXXXXXXX-XXXXXX	**Manufactured 0938** **Model No: B141EW05** **V.3** **AU Optronics** **1AXXG** **MADE IN CHINA (S1)** **H/W: 1A F/W:1** C ℞ JS xxxxxxx (Pb) RoHS (15)

12.2 Carton package

The outside dimension of carton is 455 (L)mm x 380 (W)mm x 355 (H)mm

11.3 Shipping package of palletizing sequence

13. Appendix: EDID description

| Address	FUNCTION	Value	Value	Value	Note
HEX		HEX	BIN	DEC	
00	Header	00	00000000	0	
01		FF	11111111	255	
02		FF	11111111	255	
03		FF	11111111	255	
04		FF	11111111	255	
05		FF	11111111	255	
06		FF	11111111	255	
07		00	00000000	0	
08	EISA Manuf. Code LSB	06	00000110	6	
09	Compressed ASCII	AF	10101111	175	
0A	Product Code	44	01000100	68	
0B	hex, LSB first	53	01010011	83	
0C	32-bit ser #	00	00000000	0	
0D		00	00000000	0	
0E		00	00000000	0	
0F		00	00000000	0	
10	Week of manufacture	01	00000001	1	
11	Year of manufacture	12	00010010	18	
12	EDID Structure Ver.	01	00000001	1	
13	EDID revision #	03	00000011	3	
14	**Video input def.** *(digital I/P, non-TMDS, CRGB)*	80	10000000	128	
15	**Max H image size** *(rounded to cm)*	1E	00011110	30	
16	**Max V image size** *(rounded to cm)*	13	00010011	19	
17	**Display Gamma** *(=(gamma*100)-100)*	78	01111000	120	
18	**Feature support** *(no DPMS, Active OFF, RGB, tmg Blk#1)*	0A	00001010	10	
19	Red/green low bits **(Lower 2:2:2:2 bits)**	26	00100110	38	
1A	Blue/white low bits **(Lower 2:2:2:2 bits)**	75	01110101	117	
1B	Red x **(Upper 8 bits)**	96	10010110	150	
1C	Red y/ highER 8 bits	58	01011000	88	
1D	Green x	57	01010111	87	
1E	Green y	93	10010011	147	
1F	Blue x	28	00101000	40	
20	Blue y	1E	00011110	30	
21	White x	50	01010000	80	
22	White y	54	01010100	84	
23	Established timing 1	00	00000000	0	
24	Established timing 2	00	00000000	0	
25	Established timing 3	00	00000000	0	
26	Standard timing #1	01	00000001	1	
27		01	00000001	1	
28	Standard timing #2	01	00000001	1	
29		01	00000001	1	
2A	Standard timing #3	01	00000001	1	
2B		01	00000001	1	
2C	Standard timing #4	01	00000001	1	
2D		01	00000001	1	
2E	Standard timing #5	01	00000001	1	
2F		01	00000001	1	
30	Standard timing #6	01	00000001	1	
31		01	00000001	1	
32	Standard timing #7	01	00000001	1	
33		01	00000001	1	
34	Standard timing #8	01	00000001	1	

35		01	00000001	1	
36	Pixel Clock/10000 LSB	C6	11000110	198	
37	Pixel Clock/10000 USB	1B	00011011	27	
38	Horz active **Lower 8bits**	00	00000000	0	
39	Horz blanking **Lower 8bits**	9E	10011110	158	
3A	HorzAct:HorzBlnk **Upper 4:4 bits**	50	01010000	80	
3B	Vertical Active **Lower 8bits**	20	00100000	32	
3C	Vertical Blanking **Lower 8bits**	17	00010111	23	
3D	Vert Act : Vertical Blanking **(upper 4:4 bit)**	30	00110000	48	
3E	HorzSync. Offset	30	00110000	48	
3F	HorzSync.Width	20	00100000	32	
40	VertSync.Offset : VertSync.Width	36	00110110	54	
41	Horz&Vert Sync Offset/Width **Upper 2bits**	00	00000000	0	
42	Horizontal Image Size **Lower 8bits**	2F	00101111	47	
43	Vertical Image Size **Lower 8bits**	BD	10111101	189	
44	Horizontal & Vertical Image Size **(upper 4:4 bits)**	10	00010000	16	
45	Horizontal Border *(zero for internal LCD)*	00	00000000	0	
46	Vertical Border *(zero for internal LCD)*	00	00000000	0	
47	Signal *(non-intr, norm, no stero, sep sync, neg pol)*	18	00011000	24	
48	Detailed timing/monitor	00	00000000	0	
49	descriptor #2	00	00000000	0	
4A		00	00000000	0	
4B		0F	00001111	15	
4C		00	00000000	0	
4D		00	00000000	0	
4E		00	00000000	0	
4F		00	00000000	0	
50		00	00000000	0	
51		00	00000000	0	
52		00	00000000	0	
53		00	00000000	0	
54		00	00000000	0	
55		00	00000000	0	
56		00	00000000	0	
57		00	00000000	0	
58		00	00000000	0	
59		20	00100000	32	
5A	Detailed timing/monitor	00	00000000	0	
5B	descriptor #3	00	00000000	0	
5C		00	00000000	0	
5D		FE	11111110	254	
5E		00	00000000	0	
5F	Manufacture	41	01000001	65	A
60	Manufacture	55	01010101	85	U
61	Manufacture	4F	01001111	79	O
62		0A	00001010	10	
63		20	00100000	32	
64		20	00100000	32	
65		20	00100000	32	
66		20	00100000	32	
67		20	00100000	32	
68		20	00100000	32	
69		20	00100000	32	
6A		20	00100000	32	
6B		20	00100000	32	
6C	Detailed timing/monitor	00	00000000	0	
6D	descriptor #4	00	00000000	0	
6E		00	00000000	0	
6F		FE	11111110	254	

70		00	00000000	0	
71	Manufacture P/N	42	01000010	66	B
72	Manufacture P/N	31	00110001	49	1
73	Manufacture P/N	34	00110100	52	4
74	Manufacture P/N	31	00110001	49	1
75	Manufacture P/N	45	01000101	69	E
76	Manufacture P/N	57	01010111	87	W
77	Manufacture P/N	30	00110000	48	0
78	Manufacture P/N	35	00110101	53	5
79	Manufacture P/N	20	00100000	32	
7A	Manufacture P/N	56	01010110	86	V
7B	Manufacture P/N	33	00110011	51	3
7C		20	00100000	32	
7D		0A	00001010	10	
7E	Extension Flag	00	00000000	0	
7F	Checksum	4D	01001101	77	
		SUM		5888	
		SUM to HEX		1700	