



CUSTOMER APPROVAL SHEET

| | |
|------------------------------|-----------------------|
| Company Name | |
| MODEL | C080EAN01.3 |
| CUSTOMER APPROVED | Title : Name : |

- ☐ APPROVAL FOR SPECIFICATIONS ONLY (Spec. Ver. 0.0)
- ☐ APPROVAL FOR SPECIFICATIONS AND ES SAMPLE (Spec. Ver. 0.0)
- ☐ APPROVAL FOR SPECIFICATIONS AND CS SAMPLE (Spec. Ver. 0.0)
- ☐ CUSTOMER REMARK :

1 Li-Hsin Rd. 2. Science-Based Industrial Park
Hsinchu 300, Taiwan, R.O.C.
Tel: +886-3-500-8899
Fax: +886-3-577-2730

For PROMATE Internal Use Only - Provided By prestonpeng On 2015/01/13

ALL RIGHTS STRICTLY RESERVED. ANY PORTION OF THIS PAPER SHALL NOT BE REPRODUCED, COPIED, OR TRANSFORMED TO ANY OTHER FORMS WITHOUT PERMISSION FROM AU OPTRONICS CORP.



| | |
|--------------|------------|
| Doc. Version | 0.0 |
| Total Page | 24 |
| Date | 2014/12/11 |

Product Specification

8.0" COLOR TFT-LCD MODULE

MODEL NAME: C080EAN01.3

Model Name: C080EAN01.3

| | |
|---------------------------|---------------------------|
| Planned Lifetime: | From 2015/Apr To 2018/Apr |
| Phase-out Control: | From 2017/Apr To 2018/Apr |
| EOL Schedule: | 2018/Apr |

< ◆ > Preliminary Specification

< > Final Specification

Note: The content of this specification is subject to change.

© 2014 AU Optonics
All Rights Reserved,
Do Not Copy.



Version 0.0

Page: 3/22

Record of Revision

| Version | Revise Date | Page | Content |
|---------|-------------|------|--------------|
| 0.0 | 2014/12/11 | | First draft. |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |



Contents

| | | |
|------------------|---|------------------|
| <u>A.</u> | <u>General Description</u> | <u>5</u> |
| <u>B.</u> | <u>Features</u> | <u>5</u> |
| <u>C.</u> | <u>Physical Specifications.....</u> | <u>6</u> |
| | 1. TFT LCD Panel..... | 6 |
| <u>D.</u> | <u>Outline Dimension.....</u> | <u>7</u> |
| | 1. TFT-LCD Module..... | 7 |
| <u>E.</u> | <u>Electrical Specifications</u> | <u>8</u> |
| | 1. TFT LCD Panel Pin Assignment | 8 |
| | 2. Differential Input Data Format..... | 10 |
| | a. JEIDA format (DE mode)..... | 10 |
| | 3. Input Timing Diagram | 11 |
| | 4. Absolute Maximum Ratings | 12 |
| | 5. DC Electrical Characteristics..... | 12 |
| | a. Power Specification | 12 |
| | b. Signal DC Electrical Characteristics..... | 13 |
| | C. Backlight Driving Conditions (Note 1)..... | 14 |
| | 6. AC Electrical Characteristics..... | 15 |
| | a. Input AC characteristics | 15 |
| | b. Differential signal AC characteristics..... | 15 |
| | 7. Power on/off sequence..... | 16 |
| | a. Power on sequence: | 16 |
| | b. Power off sequence:..... | 17 |
| <u>F.</u> | <u>Optical specifications (Note 1, 2).....</u> | <u>18</u> |
| <u>G.</u> | <u>Reliability Test Items(Note 1~3).....</u> | <u>20</u> |
| <u>H.</u> | <u>Packing and Marking</u> | <u>21</u> |
| | 1. Packing Form..... | 21 |
| | 2. Module/Panel Label Information..... | 22 |
| | 3. Carton Label Information | 22 |
| | 4. Warehouse storage condition:..... | 22 |



A. General Description

C080EAN01.3 is an a-Si type Thin Film Transistor Liquid crystal Display (TFT-LCD) with AHVA (Advanced Hyper-Viewing Angle) technology. This model is composed of a TFT-LCD, driver ICs, FPCA, and a backlight unit.

B. Features

- 8.0"-inch display
- 1280 RGB x 720 resolution in RGB stripe dot arrangement
- High brightness
- Interfaces: LVDS (8 bit, JEIDA, DE mode)
- AHVA – wide view technology
- RoHs compliance


C. Physical Specifications

1. TFT LCD Panel


| NO. | Item | Unit | Specification | Remark |
|-----|---------------------|---------------|----------------------|---------|
| 1 | Display Resolution | dot | 1280 RGB(H)x 720(V) | |
| 2 | Active Area | mm | 176.64 x 99.36 | |
| 3 | Screen Size | inch | 8.0(Diagonal) | |
| 4 | Dot Pitch | μm | 138 | |
| 5 | Color Configuration | — | R. G. B. Stripe | Note. 2 |
| 6 | Color Depth | — | 16.7 M colors | |
| 7 | Overall Dimension | mm | 186.5 x 117.12 x 7.2 | Note. 1 |
| 8 | Weight | g | 226 +/- 23 | |
| 9 | Display Mode | — | Normally Black | |
| 10 | Surface Treatment | — | AG | |

Note 1: FPCA is excluded

Note 2: Below figure shows dot stripe arrangement.




Note 3: Below figure shows absorbing axis



D. Outline Dimension

1. TFT-LCD Module





E. Electrical Specifications

1. TFT LCD Panel Pin Assignment


Recommended Connector: FH52-40S-0.5SH

| No. | Pin Name | I/O | Description | Remarks |
|-----|----------|-----|---|---------|
| 1 | NC | | Dummy | |
| 2 | SHLR | I | Horizontal scan direction control. “H” Left to Right; “L” Right to Left. | Note1 |
| 3 | UPDN | I | Vertical scan direction control. “H” Down to Up; “L” Up to Down. | Note1 |
| 4 | VDD | PI | Digital power supply voltage. | |
| 5 | GND | G | Digital Ground. | |
| 6 | GRB | I | Global reset pin. (Low active) | |
| 7 | NC | | Dummy | |
| 8 | GND | G | Digital Ground. | |
| 9 | CLKP | I | Positive LVDS differential clock input. | |
| 10 | CLKN | I | Negative LVDS differential clock input. | |
| 11 | GND | G | Digital Ground. | |
| 12 | PIND0 | I | Positive LVDS differential input. | |
| 13 | NIND0 | I | Negative LVDS differential input. | |
| 14 | GND | G | Digital Ground. | |
| 15 | PIND1 | I | Positive LVDS differential input. | |
| 16 | NIND1 | I | Negative LVDS differential input. | |
| 17 | GND | G | Digital Ground. | |
| 18 | PIND2 | I | Positive LVDS differential input. | |
| 19 | NIND2 | I | Negative LVDS differential input. | |
| 20 | GND | G | Digital Ground. | |
| 21 | PIND3 | I | Positive LVDS differential input. | |
| 22 | NIND3 | I | Negative LVDS differential input. | |
| 23 | GND | G | Digital Ground. | |
| 24 | GND | G | Digital Ground. | |
| 25 | VDD | PI | Digital power supply voltage. | |
| 26 | VDD | PI | Digital power supply voltage. | |
| 27 | GND | G | Digital Ground. | |
| 28 | NC | | Dummy | |
| 29 | VDDA | PI | Analog power supply voltage. | |
| 30 | VDDA | PI | Analog power supply voltage. | |
| 31 | VDDA | PI | Analog power supply voltage. | |
| 32 | VDDA | PI | Analog power supply voltage. | |
| 33 | VDDA | PI | Analog power supply voltage. | |

| | | | | |
|----|-----|---|----------------|--|
| 34 | NC | | Dummy | |
| 35 | GND | G | Analog Ground. | |
| 36 | GND | G | Analog Ground. | |
| 37 | GND | G | Analog Ground. | |
| 38 | GND | G | Analog Ground. | |
| 39 | GND | G | Analog Ground. | |
| 40 | GND | G | Analog Ground. | |

I: Digital signal input, O: Digital signal output, G: GND, PI: Power input

Note1



2. Differential Input Data Format

a. JEIDA format (DE mode)





Fig. 1. LVDS input data JEIDA format

3. Input Timing Diagram



| Parameter | | Symbol | Min. | Typ. | Max. | Unit. | Remark |
|---------------|-------------------------|---------------------|------|------|------|-------|--------|
| CLK Frequency | | F_{CLK} | 63 | 69 | 80 | MHz | |
| HSYNC | Period | T_H | 1388 | 1480 | 1569 | CLK | |
| | Horizontal display area | T_{HD} | 1280 | | | CLK | |
| | Blanking | $T_{HBP} + T_{HFP}$ | 108 | 200 | 289 | CLK | |
| VSYNC | Period | T_V | 757 | 773 | 850 | HS | |
| | Vertical display area | T_{VD} | 720 | | | HS | |
| | Blanking | $T_{VBP} + T_{VFP}$ | 37 | 53 | 130 | HS | |

4. Absolute Maximum Ratings

| Items | Symbol | Values | | Unit | Condition |
|-----------------------|--------|--------|------|------|-----------|
| | | Min. | Max. | | |
| Power Voltage | VDD | -0.5 | 5 | V | GND = 0 V |
| | VDDA | -0.5 | 5 | V | GND = 0 V |
| Operation Temperature | Topa | -30 | 85 | °C | Ambient |
| Storage Temperature | Tstg | -40 | 95 | °C | Ambient |

Note 1: Functional operation should be restricted under normal ambient temperature.

5. DC Electrical Characteristics

The following items are measured under stable condition and suggested application circuit.

a. Power Specification

| Parameter | Symbol | Min | Typ | Max | Unit | Notes |
|--------------|----------------------|-------|-------|--------|------|--------|
| Power Supply | VDD | 3 | 3.3 | 3.6 | V | Note 1 |
| | IVDD | (25) | (30) | (35) | mA | Note 1 |
| | IVDD inrush current | | (300) | (500) | mA | |
| | VDDA | 3 | 3.3 | 3.6 | V | Note 1 |
| | IVDDA | (180) | (350) | (550) | mA | Note 1 |
| | IVDDA inrush current | | (700) | (1000) | | |

Note 1: Test pattern is the following picture.



Fig. 3. Test pattern for power specification


b. Signal DC Electrical Characteristics

| Parameter | Symbol | Min | Typ | Max | Unit | Notes |
|--|------------|--------------|-----|----------------------|------|--------|
| Input signal voltage | V_i | -0.3 | - | VDD | V | Note 1 |
| Input high level voltage | V_{IH} | 0.7VDD | - | VDD | V | Note 1 |
| Input low level voltage | V_{IL} | GND | - | 0.3VDD | V | Note 1 |
| Differential input high threshold | R_{XVTH} | 0.1 | - | - | V | Note 2 |
| Differential input low threshold | R_{XVTL} | - | - | -0.1 | V | Note 2 |
| Input voltage range (singled-end) | R_{XVIN} | 0 | - | $VDD-1.2+ V_{ID} /2$ | V | Note 2 |
| Input differential voltage | $ V_{ID} $ | 0.2 | - | 0.6 | V | Note 2 |
| Differential Input Common Mode Voltage | R_{XVCM} | $ V_{ID} /2$ | - | VDD-1.2 | V | Note 2 |

Note 1: TTL interface signal DC characteristics

Note 2: LVDS interface signal DC characteristic

Single-end Signal



Differential Signal




Fig. 4. LVDS DC characteristics diagram

C. Backlight Driving Conditions (Note 1)

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Remark |
|--------------------|--------|--------|------|------|------|------------------------|
| LED Supply Current | I_L | | 80 | 85 | mA | Single serial (Note 2) |
| LED Supply Voltage | V_L | | 24 | 27.2 | V | (Note 3) |
| LED Life Time | L_L | 10,000 | | | hr | Note 4 |

Note 1: LED backlight is 16 LEDs (2strings, 8pcs for each string). Ambient temperature is 25 °C

Note 2: The LED supply power is for 2 string of LED.

Note 3: Be sure your system can provide enough voltage driving capability (larger than 28V is recommended) to provide 80mA for each LED or the brightness is possible to be below spec.

Note 4: The LED lifetime 10000hrs means , after normal use at 80mA, under +25°C, the brightness decreases to 50% of original level.




Fig. 5. Light bar structure

6. AC Electrical Characteristics

a. Input AC characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Remark |
|------------------------|-----------|------|------|------|------|--------------------|
| VDD power on slew time | T_{POR} | 1 | - | 15 | ms | From 0V to 90% VDD |
| GRB active pulse width | T_{GRB} | 1 | - | 20 | ms | VDD=3.3V |




Fig. 6. VDD and GRB timing diagram

b. Differential signal AC characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Remark |
|------------------------|-------------|------|------|------|------|--------|
| Clock frequency | R_{XFCLK} | 20 | - | 84 | MHz | |
| Input Data Skew Margin | T_{RSKM} | 400 | | | ps | |





Fig. 7 LVDS AC characteristics diagram

7. Power on/off sequence

The LCD adopts high voltage driver IC, so it could be permanently damaged under a wrong power on/off sequence. The suggested LCD power sequence is below:

- a. Power on sequence:
VDD&VDDA → GRB → LVDS → BKLEN:




Power on timing:

| Parameter | Value | | | Units |
|-----------|-------|------|------|-------|
| | Min. | Typ. | Max. | |
| T1 | 1 | - | 15 | ms |
| T2 | 1 | - | - | ms |
| T3 | 1 | - | 300 | ms |
| T4 | 300 | 350 | - | ms |



b. Power off sequence:
BKLEN → LVDS → GRB → VDD&VDDA



Power off timing:

| Parameter | Value | | | Units |
|-----------|-------|------|------|-------|
| | Min. | Typ. | Max. | |
| T1 | 90 | 100 | - | ms |
| T2 | 1 | 30 | 300 | ms |
| T3 | 1 | 30 | 40 | ms |
| T4 | 50 | - | - | ms |

F. Optical specifications (Note 1, 2)


| Item | Symbol | Condition | Min. | Typ. | Max. | Unit | Remark |
|--|--------|--------------------|---------|----------------------|---------|-------------------|-----------|
| Response Time Rise Fall | Tr | $\theta = 0^\circ$ | - | - | 20 | ms | Note 3 |
| | Tf | | - | - | 20 | | |
| Viewing Angle Top Bottom Left Right | | $CR \geq 10$ | - | 80 80 80 80 | - | deg. | Note 7, 9 |
| Contrast ratio | CR | $\theta = 0^\circ$ | 800 | 1000 | - | | Note 5, 6 |
| Brightness | Y_L | $\theta = 0^\circ$ | 400 | | - | cd/m ² | Note 8 |
| White Chromaticity | X | $\theta = 0^\circ$ | (0.267) | (0.307) | (0.347) | | Note 10 |
| | Y | $\theta = 0^\circ$ | (0.287) | (0.327) | (0.367) | | |
| Red Chromaticity | X | $\theta = 0^\circ$ | (0.589) | (0.639) | (0.689) | | |
| | Y | $\theta = 0^\circ$ | (0.279) | (0.329) | (0.379) | | |
| Green Chromaticity | X | $\theta = 0^\circ$ | (0.263) | (0.313) | (0.363) | | |
| | Y | $\theta = 0^\circ$ | (0.557) | (0.607) | (0.657) | | |
| Blue Chromaticity | X | $\theta = 0^\circ$ | (0.099) | (0.149) | (0.199) | | |
| | Y | $\theta = 0^\circ$ | (0.001) | (0.051) | (0.101) | | |
| Uniformity | | - | 80 | - | | % | Note 10 |

Note 1: Measurement should be performed in the dark room, optical ambient temperature = 25 °C, and backlight current $I_L = 80\text{mA}$.

Note 2: To be measured in the center area of TFT-LCD with a field angle of 1° by Topcon luminance meter SR3, after 10 minutes operation and warm up 30 minutes.

Note 3: Definition of response time:

The output signals of photo detector are measured when the input signals are changed from "black state" to "white state" (falling time) and from "white state" to "black state" (rising time), respectively.



Note 4: Based on liquid crystal characteristics, the response time will become slower and the color of panel will become darker than the above optical specification when ambient temperature is below 25 °C.

Note 5: Contrast ratio is calculated with the following formula.


$$\text{Contrast ratio} = \frac{\text{Photo detector output when LCD is at "White" state}}{\text{Photo detector output when LCD is at "Black" state}}$$

White : White : RGB data = "11111111" (V1 = 12.4 V & V18 = 0.6 V)

Black : RGB data = "00000000" (V9 = 6.9 V & V10 = 6.1 V)

The 100% transmission is defined as the transmission of LCD panel when all the input terminals of module are electrically opened

Note 6: Definition of viewing angle: refer to figure as below.




Note 7: Viewing angles are measured at the center of the panel when all the input terminals of LCD panel are electrically opened.

Note 8: Brightness is measured at the center of the display.

Note 9: The viewing angles are measured at the center area of the panel when all the input terminals of LCD panel are electrically opened.

Note 10: Luminance Uniformity of these 9 points is defined as below: (1 : 4 : 4 : 1)



$$\text{Uniformity} = \frac{\text{minimum luminance in 9 points (1-9)}}{\text{maximum luminance in 9 points (1-9)}}$$



G. Reliability Test Items(Note 1~3)

| No. | Test items | Conditions | | Remark |
|-----|------------------------------------|---|---------------------|------------------------------|
| 1 | High temperature storage | Ta= 95 °C | 240 Hrs | |
| 2 | Low temperature storage | Ta= -40 °C | 240 Hrs | |
| 3 | High temperature operation | Ta= 85 °C | 240 Hrs | |
| 4 | Low temperature operation | Ta= -30 °C | 240 Hrs | |
| 5 | High temperature and high humidity | Ta= 60 °C , 90 % RH | 240 Hrs | Operation |
| 6 | Heat shock | -30 °C ~ 85 °C / 100 cycles 1 Hrs/cycle | | Non-operation |
| 7 | Shock | 100 G, 6 ms, ±X, ±Y, ±Z 3 times for each direction | | |
| 8 | Electrostatic Discharge | Contact = ± 4 kV, class B Air = ± 8 kV, class B | | IEC61000-4-2 |
| 9 | Vibration | Frequency range | 8 ~ 33.3 Hz | JIS D1601,A10 Condition A |
| | | Stoke | 1.3 mm | |
| | | Sweep | 2.9 G, 33.3 ~ 400Hz | |
| | | Cycle | 15 min. | |
| | | 2 hours for each direction of X, Z 4 hours for Y direction | | |
| 10 | Vibration (with carton) | Random vibration: 0.015 G ² /Hz from 5 ~ 200 Hz -6 dB/Octave from 200 ~ 500 Hz | | IEC 68-34 |
| 11 | Drop (with carton) | Height: 60 cm 1 corner, 3 edges, 6 surfaces | | |

Note 1: Ta: Ambient temperature

Note 2: In the standard condition, there is no display function NG issue occurred. All the cosmetic specification is judged before the reliability stress.

Note 3: I_L = 80mA

H. Packing and Marking

1. Packing Form




Fig. 10. Packing diagram



2. Module/Panel Label Information

The module/panel (collectively called as the "Product") will be attached with a label of Shipping Number which represents the identification of the Product at a specific location. Refer to the Product outline drawing for detailed location and size of the label. The label is composed of a 22-digit serial number with the following definition:

ABCDEFGHIJKLMN OPQRST UV

- For internal system usage and production serial numbers.
- AUO Module or Panel factory code, represents the final production factory to complete the Product
- Product version code, ranging from 0~9 or A~Z (for Version after 9)
- Week Code, the production week when the product is finished at its production process

Example:

501M06ZL06123456781Z05:

Product Manufacturing Week Code: WK50

Product Version: Version 1

Product Manufacturing Factory: M06

3. Carton Label Information

The packing carton will be attached with a carton label where packing Q'ty, AUO Model Name, AUO Part Number, Customer Part Number (Optional) and a series of Carton Number in 13 or 14 digits are printed. The Carton Number is appearing in the following format:

ABC-DEFG-HIJK-LMN

- DEFG appear after first "-" represents the packing date of the carton
- Date from 01 to 31
- Month, ranging from 1~9, A~C. A for Oct, B for Nov and C for Dec.
- A.D. year, ranging from 1~9 and 0. The single digit code represents the last number of the year

Refer to the drawing of packing format for the location and size of the carton label.

4. Warehouse storage condition:

Room temperature: 25 +/- 5 degrees

Humidity: 30% ~ 70%